DocuSign Envelope ID: E72160C5-9F93-40D3-80D5-5174E877EC6B

501 510 512 525

1 - 24 X 12

1 - 24 X 24

ONE "U" POST PER SIGN

507 520 523

2 - 24 X 12

2 - 24 X 24

2 - 21 X 15

TWO "U" POSTS PER SIGN

502 511 513 526

1 - 24 X 12

1 - 24 X 24

ONE "U" POST PER SIGN

508 521 524

2 - 24 X 12

2 - 24 X 24

2 - 21 X 15

TWO "U" POSTS PER SIGN

503 506 515 519 522

1 - 21 X 15

1 - 24 X 24

ONE "U" POST PER SIGN

509



2 - 24 X 12

2 - 24 X 24

1 - 21 X 21
SEE U-TURN
DETAIL
1 - 21 X 15

TWO "U" POSTS PER SIGN

504 516



2 - 24 X 12

2 - 24 X 24

2 - 21 X 15

TWO "U" POSTS PER SIGN

514



2 - 24 X 12

2 - 24 X 24

1 - 21 X 21
SEE U-TURN
DETAIL
1 - 21 X 15

TWO "U" POSTS PER SIGN

505 517 518 527



2 - 24 X 12

2 - 24 X 24

2 - 21 X 15

TWO "U" POSTS PER SIGN

TIP NO.	SHEET NO.
U-3633	SIGN-3A

APPROVED: DocuSigned by: Betsy L. Watson 35E67BB34F8743F...

DATE: 10/2/2016

SEAL

NORTH CAROLINA PROFESSIONAL SEAL 29449 ENGINEER BETSY L. WATSON

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

Stantec

SIGN NUMBER: U-TURN DETAIL
TYPE: F
QUANTITY: 2

SIGN WIDTH: 21"
HEIGHT: 21"
TOTAL AREA: 3.1 Sq.Ft.

BORDER TYPE: RECESSED
RADII: 1.5"
WIDTH: 0.63"
RECESS: 0.38"

NO. Z BARS:
LENGTH:

BACKG COLOR: White
COPY COLOR: Black

SYMBOL	X	Y	WID	HT
U-TURN ARROW	3.6	3.5	12.7	13.9

MAT'L: 0.063" (1.6MM) ALUMINUM

DESIGN BY: RRH
CHECKED BY: BLW
PROJECT ID: U-3633
DIV: 12
DATE: Aug 30, 2016



Spacing Factor is 1 unless specified otherwise

USE NOTES

1. Legend and border shall be direct applied non-reflective sheeting.
2. Background shall be Grade C reflective sheeting.

LETTER POSITIONS

Letter spacings are to start of next letter

Series/Size
Text Length

TYPE 'F' SIGNS

$$$$$SYSTIME$$$$
$$$$$