

APPROVED: _____

DATE: _____



SIGN NUMBER: 101, 106
 TYPE: A
 QUANTITY: 2
 SIGN WIDTH: 14'-0"
 HEIGHT: 7'-0"
 TOTAL AREA: 98.0 Sq.Ft.
 BORDER TYPE: FLUSH
 RECESS: 0"
 WIDTH: 2"
 RADII: 11"
 NO. Z BARS: 2
 LENGTH: 160.0

BACKG COLOR: Green
 COPY COLOR: White

SYMBOL	X	Y	WID	HT

MAT'L: 0.125" (3.2 mm) ALUMINUM

DESIGN BY: M. Thigpen
 CHECKED BY: J. Lewis
 Nov 17, 2016
 PROJECT ID: U-5796
 DIV: 04

USE NOTES:
 1. Legend and border(except those that are colored black) shall be direct applied Grade B sheeting.
 2. Background shall be Grade C reflective sheeting.
 3. Shields; A, B, and C type arrows shall be on 0.032" (0.8mm) aluminum and demountable.

Panel Style: guide_exp_advance_intermediate.ssi
 M.U.T.C.D.: 2009 Edition
 Spacing Factor is 1 unless specified otherwise

LETTER POSITIONS

Letter spacings are to start of next letter

Series/Size	Text Length
EM 2000	134.9
EM 2000	71.4
E 2000	105.3

FILENAME: Guidesign_English
 NORTH CAROLINA D.O.T. SIGN DETAIL

SIGN NUMBER: 103, 104
 TYPE: A
 QUANTITY: 2
 SIGN WIDTH: 14'-0"
 HEIGHT: 8'-0"
 TOTAL AREA: 112.0 Sq.Ft.
 BORDER TYPE: FLUSH
 RECESS: 0"
 WIDTH: 2"
 RADII: 12"
 NO. Z BARS: 3
 LENGTH: 160.0

BACKG COLOR: Green
 COPY COLOR: White

SYMBOL	X	Y	WID	HT
AR_Type A	75	16.4	13.3	21

MAT'L: 0.125" (3.2 mm) ALUMINUM

DESIGN BY: M. Thigpen
 CHECKED BY: J. Lewis
 Nov 17, 2016
 PROJECT ID: U-5796
 DIV: 04

USE NOTES:
 1. Legend and border(except those that are colored black) shall be direct applied Grade B sheeting.
 2. Background shall be Grade C reflective sheeting.
 3. Shields; A, B, and C type arrows shall be on 0.032" (0.8mm) aluminum and demountable.

Panel Style: guide_exp_advance_intermediate.ssi
 M.U.T.C.D.: 2009 Edition
 Spacing Factor is 1 unless specified otherwise

LETTER POSITIONS

Letter spacings are to start of next letter

Series/Size	Text Length
EM 2000	134.9
EM 2000	71.4
E 2000	105.3

FILENAME: Guidesign_English
 NORTH CAROLINA D.O.T. SIGN DETAIL

SIGN NUMBER: 102, 105
 TYPE: A
 QUANTITY: 2
 SIGN WIDTH: 12'-6"
 HEIGHT: 5'-0"
 TOTAL AREA: 62.5 Sq.Ft.
 BORDER TYPE: FLUSH
 RECESS: 0"
 WIDTH: 2"
 RADII: 8"
 NO. Z BARS: 2
 LENGTH: 142.0

BACKG COLOR: Green
 COPY COLOR: White

SYMBOL	X	Y	WID	HT

MAT'L: 0.125" (3.2 mm) ALUMINUM

DESIGN BY: M. THIGPEN
 CHECKED BY: J. LEWIS
 Oct 31, 2016
 PROJECT ID: U-5796
 DIV: 04

USE NOTES: 1,2
 1. Legend and border(except those that are colored black) shall be direct applied Grade B sheeting.
 2. Background shall be Grade C reflective sheeting.
 3. Shields; A, B, and C type arrows shall be on 0.032" (0.8mm) aluminum and demountable.

Panel Style: guide_exp_supplemental.ssi
 M.U.T.C.D.: 2009 Edition
 Spacing Factor is 1 unless specified otherwise

LETTER POSITIONS

Letter locations are panel edge to lower left corner

Series/Size	Text Length
EM 2000	134.7
EM 2000	95.7
E 2000	67

FILENAME: Guidesign_English
 NORTH CAROLINA D.O.T. SIGN DETAIL

SIGN NUMBER: 107
 TYPE: B
 QUANTITY: 1
 SIGN WIDTH: 9'-6"
 HEIGHT: 2'-6"
 TOTAL AREA: 23.8 Sq.Ft.
 BORDER TYPE: FLUSH
 RECESS: 0"
 WIDTH: 1.75"
 RADII: 4"
 NO. Z BARS: 2
 LENGTH: 106.0

BACKG COLOR: Green
 COPY COLOR: White

SYMBOL	X	Y	WID	HT

MAT'L: 0.125" (3.2 mm) ALUMINUM

DESIGN BY: M. Thigpen
 CHECKED BY: J. Lewis
 Nov 15, 2016
 PROJECT ID: R-5719
 DIV: 04

USE NOTES: 1,2
 1. Legend and border(except those that are colored black) shall be direct applied Grade C sheeting.
 2. Background shall be Grade C reflective sheeting.

Panel Style: guide_exp_distance.ssi
 M.U.T.C.D.: 2009 Edition
 Spacing Factor is 1 unless specified otherwise

LETTER POSITIONS

Letter locations are panel edge to lower left corner

Series/Size	Text Length
EM 2000	76.6
EM 2000	95.7
E 2000	6.5

FILENAME: Guidesign_English_8-2-13
 NORTH CAROLINA D.O.T. SIGN DETAIL

C:\Users\mthigpen\OneDrive\Documents\Projects\2017\02_U-5796\NCDD01\Traffic\Signing\CA00\Signing Layout Plans\U-5796_sgn_sht04.dgn
 11/17/2016 10:52:27 AM Wetherill, T02_U-5796\NCDD01\Traffic\Signing\CA00\Signing Layout Plans\U-5796_sgn_sht04.dgn
 User: mthigpen