

APPROVED: \_\_\_\_\_

DATE: \_\_\_\_\_

SEAL



SIGN NUMBER: 305	BACKG COLOR: Green	DESIGN BY: M. THIGPEN	CHECKED BY: J. LEWIS	Jan 21, 2016
TYPE: D	COPY COLOR: White	PROJECT ID: U-5796		DIV: 04

SYMBOL	X	Y	WID	HT
AR_Type D	12.5	16.5	6	9
AR_Type D	57.1	4.5	6	9

QUANTITY: 1  
SIGN WIDTH: 6'-0"  
HEIGHT: 2'-6"  
TOTAL AREA: 15.0 Sq.Ft.

BORDER TYPE: FLUSH  
RECESS: 0"  
WIDTH: 0.75"  
RADII: 2.25"

NO. Z BARS: 1  
LENGTH: 0.125" (3.2 mm) ALUMINUM

MAT'L:

USE NOTES: 1,2,3

- Legend and border(except those that are colored black) shall be direct applied Grade C sheeting.
- Background shall be Grade C reflective sheeting.
- Shields; A, B, and C type arrows shall be on 0.032" (0.8mm) aluminum and demountable.

Panel Style: guide\_con\_destination.ssi  
M.U.T.C.D.: 2009 Edition

Spacing Factor is 1 unless specified otherwise

LETTER POSITIONS

Letter spacings are to start of next letter

Series/Size	Text Length
D 2000	35
D 2000	45.2

FILENAME: Guidesign\_English NORTH CAROLINA D.O.T. SIGN DETAIL

SIGN NUMBER: 307	BACKG COLOR: Green	DESIGN BY: M. Thigpen	CHECKED BY: J. Lewis	Nov 15, 2016
TYPE: D	COPY COLOR: White	PROJECT ID: R-5719		DIV: 04

SYMBOL	X	Y	WID	HT
AR_Type A	14.7	7.4	15	23.6

QUANTITY: 1  
SIGN WIDTH: 8'-0"  
HEIGHT: 2'-6"  
TOTAL AREA: 20.0 Sq.Ft.

BORDER TYPE: FLUSH  
RECESS: 0"  
WIDTH: 1.75"  
RADII: 4"

NO. Z BARS: 1  
LENGTH: 0.125" (3.2 mm) ALUMINUM

MAT'L:

USE NOTES: 1,2

- Legend and border(except those that are colored black) shall be direct applied Grade C sheeting.
- Background shall be Grade C reflective sheeting.

Panel Style: guide\_exp\_distance.ssi  
M.U.T.C.D.: 2009 Edition

Spacing Factor is 1 unless specified otherwise

LETTER POSITIONS

Letter locations are panel edge to lower left corner

Series/Size	Text Length
EM 2000	61.1
EM 2000	6.5

FILENAME: Guidesign\_English\_8-2-13 NORTH CAROLINA D.O.T. SIGN DETAIL

SIGN NUMBER: 306	BACKG COLOR: Green	DESIGN BY: M. THIGPEN	CHECKED BY: J. LEWIS	Jan 21, 2016
TYPE: D	COPY COLOR: White	PROJECT ID: U-5796		DIV: 04

SYMBOL	X	Y	WID	HT
AR_Type D	7.4	16.5	6	9
AR_Type D	52	4.5	6	9

QUANTITY: 1  
SIGN WIDTH: 6'-0"  
HEIGHT: 2'-6"  
TOTAL AREA: 15.0 Sq.Ft.

BORDER TYPE: FLUSH  
RECESS: 0"  
WIDTH: 0.75"  
RADII: 2.25"

NO. Z BARS: 1  
LENGTH: 0.125" (3.2 mm) ALUMINUM

MAT'L:

USE NOTES: 1,2,3

- Legend and border(except those that are colored black) shall be direct applied Grade C sheeting.
- Background shall be Grade C reflective sheeting.
- Shields; A, B, and C type arrows shall be on 0.032" (0.8mm) aluminum and demountable.

Panel Style: guide\_con\_destination.ssi  
M.U.T.C.D.: 2009 Edition

Spacing Factor is 1 unless specified otherwise

LETTER POSITIONS

Letter spacings are to start of next letter

Series/Size	Text Length
D 2000	45.2
D 2000	35

FILENAME: Guidesign\_English NORTH CAROLINA D.O.T. SIGN DETAIL

SIGN NUMBER: 201, 202	BACKG COLOR: Green	DESIGN BY: M. Thigpen	CHECKED BY: J. Lewis	Jan 21, 2016
TYPE: B	COPY COLOR: White	PROJECT ID: U-5796		DIV: 04

SYMBOL	X	Y	WID	HT
AR_Type A	14.7	7.4	15	23.6

QUANTITY: 2  
SIGN WIDTH: 4'-0"  
HEIGHT: 4'-6"  
TOTAL AREA: 18.0 Sq.Ft.

BORDER TYPE: FLUSH  
RECESS: 0"  
WIDTH: 1.5"  
RADII: 8"

NO. Z BARS: 2  
LENGTH: 40.0  
0.125" (3.2 mm) ALUMINUM

MAT'L:

USE NOTES: 1,2,3

- Legend and border(except those that are colored black) shall be direct applied Grade C sheeting.
- Background shall be Grade C reflective sheeting.
- Shields; A, B, and C type arrows shall be on 0.032" (0.8mm) aluminum and demountable.

Panel Style: guide\_exp\_gore.ssi  
M.U.T.C.D.: 2009 Edition

Spacing Factor is 1 unless specified otherwise

LETTER POSITIONS

Letter spacings are to start of next letter

Series/Size	Text Length
EM 2000	30.8

FILENAME: Guidesign\_English NORTH CAROLINA D.O.T. SIGN DETAIL

C:\Users\mthigpen\Documents\Projects\2016\02\_U-5796\NCDOT\Traffic\Signing\CA00\Signing Layout Plans\U-5796\_sign\_sht04.dgn