

04-MAY-2017 15:14 S:\Contracts\ContractDetails\Standard Drawings\Details in Lieu of Standards\Drawings\862d01 862d01 862d01.dgn
 JHowerton A:\CS0-29295

| | | |
|--|--|--------------------------------|
| STATE OF NORTH CAROLINA DEPT. OF TRANSPORTATION DIVISION OF HIGHWAYS RALEIGH, N.C. | ROADWAY DETAIL DRAWING FOR GUARDRAIL PLACEMENT | SHEET 2 OF 11 862D01 |
| | | |
| <p>NOTE SPECIAL LAYER OF PAVEMENT</p> <p>USE 3'-1 1/2" POST SPACING ON THE 50' OF GUARDRAIL PARALLEL TO LANES AND 6'-3" POST SPACING ON 15:1 TRANSITION SECTIONS. GRADE MEDIAN IN THE VICINITY OF THE SIGN SUPPORT AS ILLUSTRATED IN THE ROADWAY STANDARD DRAWINGS (STANDARD 862D01 SHEET 1 OF 12).</p> | | |
| <p>SECT. YY</p> | <p>SECT. ZZ</p> | |
| DETAIL OF GUARDRAIL AT MEDIAN SIGN SUPPORT | | |

| | | |
|--|--|--------------------------------|
| STATE OF NORTH CAROLINA DEPT. OF TRANSPORTATION DIVISION OF HIGHWAYS RALEIGH, N.C. | ROADWAY DETAIL DRAWING FOR GUARDRAIL PLACEMENT | SHEET 1 OF 11 862D01 |
| | | |
| <p>NOTE: WHEN OFFSET DISTANCE FROM FACE OF OBSTRUCTION TO FACE OF GUARDRAIL IS BETWEEN 3'-6" AND 5'-6" BEGIN 3'-1 1/2" POST SPACING AT A POINT 25' BEFORE REACHING THE OBSTRUCTION AND CARRY THROUGHOUT ITS LENGTH. IF THE OFFSET IS LESS THAN 3'-6" USE CONCRETE BARRIER.</p> | | |
| <p>SECT. XX</p> | <p>SECT. YY</p> | <p>SECT. ZZ</p> |
| DETAIL OF RIGHT SIDE GUARDRAIL AT UNDERPASS | | |

DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

**CONTRACT STANDARDS
AND DEVELOPMENT UNIT**
 Office 919-707-6950 FAX 919-250-4119

SEE TITLE BLOCK

| | |
|--------------------------|----------------|
| ORIGINAL BY: J. HOWERTON | DATE: 06-22-12 |
| MODIFIED BY: | DATE: |
| CHECKED BY: | DATE: |
| FILE SPEC.: | |



11/2/2017