





## NOTES

1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY. MAXIMUM JUNCTION BOX SPACING 1000' FOR FIBER OPTIC CABLE AND 150' FOR FEEDER CONDUCTORS OR AS DIRECTED BY THE ENGINEER.
2. SEE ROADWAY PLANS FOR GUARDRAIL DETAILS.

<p>Prepared in the Offices of:</p> <div style="text-align: center;">  <p>ENVIRONMENTAL MOBILITY AND SOCIAL DEVELOPMENT CENTER OF THE UNIVERSITY OF NORTH CAROLINA AT GREENSBORO</p> </div> <p>750 N. Greenfield Place, Garner, NC 27529</p> <div style="text-align: center;">  <p>SCALE</p> <p>0 </p> <p>A/B</p> </div>	<h2 style="margin: 0;">CABLE ROUTING PLAN</h2>	<p>SEAL</p> 
<div style="display: flex; justify-content: space-between; border-bottom: 1px solid black; padding-bottom: 5px;"> <span>DIVISION 07</span> <span>GUILFORD CO.</span> <span>GREENSBORO</span> </div> <div style="display: flex; justify-content: space-between; border-bottom: 1px solid black; padding-bottom: 5px;"> <span>PLAN DATE: NOVEMBER 2017</span> <span>REVIEWED BY: P. P. MARAK, PE</span> </div> <div style="display: flex; justify-content: space-between; border-bottom: 1px solid black; padding-bottom: 5px;"> <span>PREPARED BY: G. A. GREEN</span> <span>REVIEWED BY: M. A. ASLAMI, PE</span> </div>		
<p>REVISIONS</p>	<p>INIT.</p>	<p>DATE</p>