



**NOTES**

1. EXISTING CONDUIT, FIBER, JUNCTION BOX, AND SPLICE ENCLOSURE INSTALLED BY PROJECT U-2524D.
2. MAINTAIN A MINIMUM OF SIX (6) FEET FROM EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY. MAXIMUM JUNCTION BOX SPACING 1000' FOR FIBER OPTIC CABLE AND 150' FOR FEEDER CONDUCTORS OR AS DIRECTED BY THE ENGINEER.
3. SEE ROADWAY PLANS FOR GUARDRAIL DETAILS.

Prepared in the Offices of:		SEAL	
		NORTH CAROLINA PROFESSIONAL SEAL 031636	
750 N. Greenfield Pkwy., Garner, NC 27529		PAUL P. MARAK ENGINEER	
SCALE: 0' 1" = 100'		DATE: 11/14/2017	
CABLE ROUTING PLAN		DIVISION 07 GREENSBORO	
PLAN DATE: NOVEMBER 2017		REVIEWED BY: P.P. MARAK, PE	
PREPARED BY: G.A. GREEN		REVIEWED BY: M.A. ASLANI, PE	
REVISIONS		INIT. DATE	
SIGNATURE		DATE	
CADD Filename:			