

DEAD LOAD DEFLECTION TABLE FOR GIRDERS																					
0.6" ∅ LOW RELAXATION	GIRDER A1, B1, C1																				
	BRG.	0.05	0.1	0.15	0.2	0.25	0.3	0.35	0.4	0.45	0.5	0.55	0.6	0.65	0.7	0.75	0.8	0.85	0.90	0.95	BRG.
CAMBER (GIRDER IN PLACE) ↑	0	0.051	0.101	0.148	0.190	0.229	0.261	0.287	0.305	0.317	0.321	0.317	0.305	0.287	0.261	0.229	0.190	0.148	0.101	0.051	0
* DEFLECTION DUE TO SUPERIMPOSED D.L. ↓	0	0.026	0.053	0.080	0.105	0.125	0.140	0.151	0.159	0.167	0.176	0.167	0.159	0.151	0.140	0.125	0.105	0.080	0.053	0.026	0
FINAL CAMBER ↑	0	5/16"	9/16"	13/16"	1"	1 1/4"	1 7/16"	1 5/8"	1 3/16"	1 3/16"	1 3/16"	1 3/16"	1 3/16"	1 5/8"	1 7/16"	1 1/4"	1"	13/16"	9/16"	5/16"	0

* INCLUDES FUTURE WEARING SURFACE.
ALL VALUES ARE SHOWN IN FEET (DECIMAL FORM), EXCEPT "FINAL CAMBER", WHICH IS GIVEN IN INCHES (FRACTION FORM).

DEAD LOAD DEFLECTION TABLE FOR GIRDERS																					
0.6" ∅ LOW RELAXATION	GIRDER A2, B2, C2																				
	BRG.	0.05	0.1	0.15	0.2	0.25	0.3	0.35	0.4	0.45	0.5	0.55	0.6	0.65	0.7	0.75	0.8	0.85	0.90	0.95	BRG.
CAMBER (GIRDER IN PLACE) ↑	0	0.051	0.101	0.148	0.190	0.229	0.261	0.287	0.305	0.317	0.321	0.317	0.305	0.287	0.261	0.229	0.190	0.148	0.101	0.051	0
* DEFLECTION DUE TO SUPERIMPOSED D.L. ↓	0	0.027	0.054	0.081	0.106	0.126	0.141	0.152	0.160	0.168	0.178	0.168	0.160	0.152	0.141	0.126	0.106	0.081	0.054	0.027	0
FINAL CAMBER ↑	0	5/16"	9/16"	13/16"	1"	1 1/4"	1 7/16"	1 5/8"	1 3/4"	1 3/16"	1 3/16"	1 3/16"	1 3/4"	1 5/8"	1 7/16"	1 1/4"	1"	13/16"	9/16"	5/16"	0

* INCLUDES FUTURE WEARING SURFACE.
ALL VALUES ARE SHOWN IN FEET (DECIMAL FORM), EXCEPT "FINAL CAMBER", WHICH IS GIVEN IN INCHES (FRACTION FORM).

DEAD LOAD DEFLECTION TABLE FOR GIRDERS																					
0.6" ∅ LOW RELAXATION	GIRDER A3, B3, C3																				
	BRG.	0.05	0.1	0.15	0.2	0.25	0.3	0.35	0.4	0.45	0.5	0.55	0.6	0.65	0.7	0.75	0.8	0.85	0.90	0.95	BRG.
CAMBER (GIRDER IN PLACE) ↑	0	0.051	0.101	0.148	0.190	0.229	0.261	0.287	0.305	0.317	0.321	0.317	0.305	0.287	0.261	0.229	0.190	0.148	0.101	0.051	0
* DEFLECTION DUE TO SUPERIMPOSED D.L. ↓	0	0.026	0.053	0.080	0.104	0.124	0.139	0.149	0.158	0.165	0.174	0.165	0.158	0.149	0.139	0.124	0.104	0.080	0.053	0.026	0
FINAL CAMBER ↑	0	5/16"	9/16"	13/16"	1 1/16"	1 1/4"	1 7/16"	1 5/8"	1 3/4"	1 3/16"	1 3/16"	1 3/16"	1 3/4"	1 5/8"	1 7/16"	1 1/4"	1 1/16"	13/16"	9/16"	5/16"	0


* INCLUDES FUTURE WEARING SURFACE.
ALL VALUES ARE SHOWN IN FEET (DECIMAL FORM), EXCEPT "FINAL CAMBER", WHICH IS GIVEN IN INCHES (FRACTION FORM).

PROJECT NO. R-3825B
JOHNSTON COUNTY
STATION: 64+20.00 -L-

SHEET 1 OF 3

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

SUPERSTRUCTURE
DEAD LOAD
DEFLECTIONS



7/17/2018 9:13:46 AM EDT

V&M
Vaughn & Melton
Consulting Engineers

Asheville,
North Carolina
828-253-2796

- Boone, NC 828-395-9933
- Tri-Cities, TN 423-467-8400
- Knoxville, TN 865-546-5800
- Spartanburg, SC 864-574-4775
- Charleston, SC 843-974-5650
- Middlesboro, KY 606-248-6600
- Raleigh, NC 919-977-9455
- Charlotte, NC 704-357-0488
- Atlanta, GA 770-627-3550

Copyright © 2006 Vaughn & Melton, Inc. All Rights Reserved.

DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-24
1			3			TOTAL SHEETS
2			4			59

DRAWN BY: WDC DATE: 7/2017
CHECKED BY: ACO DATE: 12/2017
DESIGN ENGINEER OF RECORD: ACO DATE: 12/2017