

SUMMARY OF WORK BY INTERSECTION

Reference Information					Signal Items																										
NCDOT / CITY SIGNAL INV. NO.	Intersection Name	Cable Layout Sheet Number	Signal Design Sheet Number	In / near historically significant area (see box note at bottom of page)	16-inch Countdown Pedestrian Signal Head	12-inch 3-Section Signal Head	12-inch 4-Section Signal Head	12-inch 5-Section Signal Head	Signal Cable	Adjust Span Attachment	Messenger Cable (3/8")	Underground Conduit (1, 2")	Underground Conduit (2, 2")	Directional Drill	Inductive Loop Sawcut	Loop Lead-in Cable	Sign	Wood Pole	Metal Strain Pole	Standard Down Guy Assembly	Sidewalk Guy Assembly	Type I Post with Foundation	Junction Box	Remove existing pedestrian signal	Louvers	Backplates	Remove Line 4"	Remove Line 24"	Thermoplastic Pavement Marking Line 24", 120 MILS	Thermoplastic Pavement Marking Lines (8", 120 MILS)	Thermoplastic White yield lines, 90 MILS
193	B8027	Graham Street at Queen Ann Street	6.190	195.0		8			850	2	740		20			1140				3											
194	B8451	N. Beaumont Avenue at Vaughn Road	6.162	196.0																											
195	B8453	Graham Street at Beaumont Avenue	6.191	197.0		8			620	2	320					410				3	1										
196	B8454	E. Front Street at S. Spring Street	6.117	198.0																											
197	B8455	E. Davis Street at S. Spring Street	6.117	199.0	Y																										
198	B8456	S. Lexington Avenue at E. Davis Street	6.118	200.0	Y																										
199	B8457	Maple Avenue at S. Lexington Avenue	6.118	201.0	Y																										
200	B8458	S. Worth Street at W. Front Street	6.127	202.0					20																						
201	B9024	Boone Station Drive at Glidewell Drive/Tiki Lane	6.058	203.0		2	1		580																						
202	B9025	Boone Station Drive at Waltham Boulevard	6.059	204.0																											
203	G0100	Marshall Street at E. Elm Street	6.180	205.0																											
204	G0101	E. Pine Street at S. Marshall Street	6.180	206.0	Y															3											
205	G0102	E. Pine Street at S. Melville Street	6.180	207.0																											
206	G0103	N. Marshall Street at Albright Avenue	6.181	208.0					420		60							1		1											
Total					4	285	97	8	53020	63	5637	4756	200	550	6360	66985	13	6	2	117	27	2	69	2	4	2	90	54	66	170	50



10-III-2018_17:38
 ***sht:ins:com:project:GISRLA**transportation*Traffic*Cur*100056469 U-6015 B-G Sig. Sys*Task 05_11_Signal*Vol. III Front Sheets*Sig. 2.26.dgn
 ALEX3361 AT LUS340649

- Work shown on this sheet is for the upgrade of the traffic signals, including installation of new controllers and cabinets, new or modified foundations, electrical service and miscellaneous signal related items. Additional information can be found in the signal plans in this Volume. Work to be done for fiber-optic cable routing and interconnection is shown on the cable layout plans and on the sheets entitled "Summary of Work by Cable Layout Plans" in Volume I of III.
- The items listed above are for informational purposes only and represent work that is necessary to complete the contract and are not necessarily pay items. See Summary of Quantities and the Project Special Provisions for defined Pay Items for this contract.

Areas within this project have been determined to contain properties with documented historical significance. If it is necessary to deviate from the plans in an area identified to contain properties with historic significance, alert the engineer to contact Environmental Analysis Unit - Historic Architecture Group of North Carolina Department of Transportation for an effects determination before proceeding.

ATKINS 1616 EAST MILLBROOK ROAD, SUITE 160
 RALEIGH, NORTH CAROLINA 27609
 (919) 876-6888 NCBES #F-0326





DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

	Prepared for the Offices of: Department of Transportation, State of North Carolina		750 Greenfield Parkway, Garner, NC 27529	
	SCALE: NTS			
Burlington-Graham Signal System Summary of Work by Intersection (Sheet 3 of 3)		Division 7 Alamance County Burlington & Graham		
PLAN DATE: May 2018		REVIEWED BY: MB Toth		
PREPARED BY: PL Alexander		REVIEWED BY:		Designed by: <i>Melissa B. Toth</i> Date: _____ CADD File name: Sig 2.26.dgn
REVISIONS:		INIT. DATE		

EDI MODEL 2018ECLip-NC CONFLICT MONITOR PROGRAMMING DETAIL

(remove jumper and set switches as shown)

REMOVE DIODE JUMPER 2-6.



■ = DENOTES POSITION OF SWITCH

REMOVE JUMPER AS SHOWN

NOTES:

1. Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
2. Ensure jumpers SEL2-SEL5 and SEL9 are present on the monitor board.
3. Ensure that Red Enable is active at all times during normal operation.
4. Integrate monitor with Ethernet network in cabinet.

NOTES

1. To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
2. Program controller to start up in phase 2 Green and 6 Green.
3. The cabinet and controller are part of the Burlington-Graham Signal System.

EQUIPMENT INFORMATION

CONTROLLER.....2070LX
 CABINET.....336
 SOFTWARE.....ECONDLITE ASC/3-2070
 CABINET MOUNT.....POLE MOUNTED
 OUTPUT FILE POSITIONS...12
 LOAD SWITCHES USED.....S2,S8,S11
 PHASES USED.....2,6,8
 OVERLAPS.....NONE


SIGNAL HEAD HOOK-UP CHART

LOAD SWITCH NO.	S1	S2	S3	S4	S5	S6	S7	S8	S9	S10	S11	S12
CMU CHANNEL NO.	1	2	13	3	4	14	5	6	15	7	8	16
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED
SIGNAL HEAD NO.	NU	21,22	NU	NU	NU	NU	NU	61,62	NU	NU	81,82	NU
RED		128						134			107	
YELLOW		129						135			108	
GREEN		130						136			109	
RED ARROW												
YELLOW ARROW												
GREEN ARROW												

NU = Not Used

INPUT FILE POSITION LAYOUT

(front view)



EX. : 1A, 2A, ETC. = LOOP NO.'S


FS = FLASH SENSE
 ST = STOP TIME

INPUT FILE CONNECTION & PROGRAMMING CHART

LOOP NO.	LOOP TERMINAL	INPUT FILE POS.	PIN NO.	DETECTOR NO.	NEMA PHASE	CALL	EXTEND TIME	DELAY TIME	ADDED INITIAL	DETECTOR TYPE
* S1	TB21-13,14	I7U	57	7	SYS	No				N
8A	TB22-1,2	I8U	42	8	8	YES		3		S
8B	TB24-1,2	I8L	46	18	8	YES		15		S

* System detector only. Remove any assigned vehicle phase.

INPUT FILE POSITION LEGEND: J2L



THIS ELECTRICAL DETAIL IS FOR
 THE SIGNAL DESIGN: 07-0001
 DESIGNED: January 2018
 SEALED: 6/7/2018
 REVISED: N/A

Electrical Detail

ELECTRICAL AND PROGRAMMING DETAILS FOR:

Prepared for the Offices of:

750 N. Greenfield Pkwy, Garner, NC 27529

NC 87-100 (W. Webb Avenue) at SR 1352 (W. Davis Street)	
Division 7	Alamance County Burlington
PLAN DATE: January 2018	REVIEWED BY: AM Encarnacion
PREPARED BY: NA Ptak	REVIEWED BY: PL Alexander
REVISIONS	INIT. DATE

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED


SEAL

SEAL 023489
 PAMELA L. ALEXANDER
 ENGINEER

6/9/2018
 DATE

SIG. INVENTORY NO. 07-0001

PHASING DIAGRAM



PHASING DIAGRAM DETECTION LEGEND


- ◄● DETECTED MOVEMENT
- ◄ UNDETECTED MOVEMENT (OVERLAP)
- ◄... UNSIGNALIZED MOVEMENT
- ◄... PEDESTRIAN MOVEMENT

TABLE OF OPERATION

SIGNAL FACE	PHASE		
	Ø2+6	Ø8	FLASH
21,22,23	G	R	Y
61,62	G	R	Y
81,82	R	G	R

SIGNAL FACE I.D.

All Heads L.E.D.



21,22,23
61,62
81,82

ASC/3 DETECTOR INSTALLATION CHART


LOOP	SIZE (FT)	DISTANCE FROM STOPBAR (FT)	TURNS	NEW LOOP	PROGRAMMING							
					PHASE	CALLING	EXTEND TIME	DELAY TIME	USE ADDED INITIAL	TYPE	SYSTEM LOOP	NEW CARD
8A	6x40	+10	2-4-2	-	8	Yes	-	5	-	S	-	X
S1	6X6	+95	3	X	8	No	-	-	-	S	X	X

Remove Existing Pedestrian Signals and associated equipment

2 Phase Semi-Actuated (Burlington-Graham Signal System)

NOTES

- Refer to "Roadway Standard Drawings NCDOT" dated January 2018 and "Standard Specifications for Roads and Structures" dated January 2018.
- Do not program signal for late night flashing operation unless otherwise directed by the Engineer.
- Set all detector units to presence mode.
- In the event of loop replacement, refer to the current ITS and Signals Design Manual and submit a Plan of Record to the Signal Design Section.
- Locate new cabinet so as not to obstruct sight distance of vehicles turning right on red.
- Pavement markings are existing.
- Maximum times shown in timing chart are for free-run operation only. Coordinated signal system timing values supersede these values.



ASC/3 TIMING CHART

FEATURE	PHASE		
	2	6	8
Min Green *	10	10	7
Walk *	0	0	0
Ped Clear	0	0	0
Veh. Extension *	0.0	0.0	2.0
Max 1 *	40	40	20
Yellow	3.7	4.1	3.0
Red Clear	1.2	1.3	2.1
Actuations B4 Add *	-	-	-
Seconds / Actuation *	-	-	-
Max Initial *	-	-	-
Time Before Reduction *	-	-	-
Time To Reduce *	-	-	-
Minimum Gap	-	-	-
Locking Detector	-	-	-
Recall Position	MAX RECALL	MAX RECALL	-
Dual Entry	-	-	-
Simultaneous Gap	X	X	X

* These values may be field adjusted. Do not adjust Min Green and Extension times for phases 2 and 6 lower than what is shown. Min Green for all other phases should not be lower than 4 seconds.

LEGEND

PROPOSED	EXISTING
○ → Traffic Signal Head	● → N/A
◐ → Modified Signal Head	◐ → N/A
⊥ Sign	⊥ Sign
⊥ Pedestrian Signal Head With Push Button & Sign	⊥ Pedestrian Signal Head
○ Signal Pole with Guy	● Signal Pole with Guy
⊥ Signal Pole with Sidewalk Guy	⊥ Signal Pole with Sidewalk Guy
⊠ Inductive Loop Detector	⊠ Inductive Loop Detector
⊠ Controller & Cabinet	⊠ Controller & Cabinet
□ Junction Box	□ Junction Box
--- 2-in Underground Conduit	--- 2-in Underground Conduit
N/A Right of Way	--- Right of Way
→ Directional Arrow	→ Directional Arrow
⊠ Terminal Splice Box	⊠ Terminal Splice Box
N/A Curb Ramp	⊠ Curb Ramp
⊠ Right-turn "ONLY" Sign (R3-5R)	⊠ Right-turn "ONLY" Sign (R3-5R)

Signal Upgrade

Prepared for the Offices of:

 750 N. Greenfield Pkwy, Garner, NC 27529
 SCALE: 1"=20'

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

NC 87-100 (W. Webb Avenue) at Trolinger Street

Division 7 Alamance County Burlington
 PLAN DATE: October 2017 REVIEWED BY: AM Encarnacion
 PREPARED BY: NA Ptak REVIEWED BY: MB Toth

REVISIONS	INIT.	DATE


Designed by: Melissa B. Toth 6/7/2018
 SIGNATURE: _____ DATE: _____
 SIG. INVENTORY NO. 07-0005

ATKINS 1616 EAST MILLBROOK ROAD, SUITE 160
 RALEIGH, NORTH CAROLINA 27609
 (919) 876-6888 NCBES #F-0326

07-JUN-2018 11:10
 O:\Projects\2018\07-0005\07-0005.dgn
 ALEX3361 AT LUS340649

EDI MODEL 2018ECLip-NC CONFLICT MONITOR PROGRAMMING DETAIL

(remove jumpers and set switches as shown)



NOTES

- To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
- Program phases 4 and 8 for Dual Entry.
- Program controller to start up in phase 2 Green and 6 Green.
- The cabinet and controller are part of the Burlington-Graham Signal System.

SIGNAL HEAD HOOK-UP CHART

LOAD SWITCH NO.	S1	S2	S3	S4	S5	S6	S7	S8	S9	S10	S11	S12	AUX S1	AUX S2	AUX S3	AUX S4	AUX S5	AUX S6
CMU CHANNEL NO.	1	2	13	3	4	14	5	6	15	7	8	16	9	10	17	11	12	18
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED	OLA	OLB	SPARE	OLC	OLD	SPARE
SIGNAL HEAD NO.	NU	21,22	NU	NU	41,42	NU	NU	61,62	NU	NU	81,82	NU	NU	NU	NU	NU	NU	NU
RED		128			101			134			107							
YELLOW		129			102			135			108							
GREEN		130			103			136			109							
RED ARROW																		
YELLOW ARROW																		
GREEN ARROW																		

NU = Not Used

EQUIPMENT INFORMATION


CONTROLLER.....2070LX
 CABINET.....332 W/AUX
 SOFTWARE.....ECONOLITE ASC/3-2070
 CABINET MOUNT.....BASE
 OUTPUT FILE POSITIONS...18 WITH AUX.OUTPUT FILE
 LOAD SWITCHES USED.....S2,S5,S8,S11
 PHASES USED.....2,4,6,8
 OVERLAP "A".....NOT USED
 OVERLAP "B".....NOT USED
 OVERLAP "C".....NOT USED
 OVERLAP "D".....NOT USED

NOTES:

- Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
- Ensure jumpers SEL2-SEL5 and SEL9 are present on the monitor board.
- Ensure that Red Enable is active at all times during normal operation.
- Integrate monitor with Ethernet network in cabinet.


INPUT FILE POSITION LAYOUT

(front view)



INPUT FILE CONNECTION & PROGRAMMING CHART

LOOP NO.	LOOP TERMINAL	INPUT FILE POS.	PIN NO.	DETECTOR NO.	NEMA PHASE	CALL	EXTEND TIME	DELAY TIME	ADDED INITIAL	DETECTOR TYPE
2A	TB2-5,6	I2U	39	2	2	YES				S
4A	TB4-9,10	I6U	41	4	4	YES				S
6A	TB3-5,6	J2U	40	6	6	YES				S
8A	TB5-9,10	J6U	42	8	8	YES				S



THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 07-0006
 DESIGNED: Sept-2017
 SEALED: 06-13-2018
 REVISED: N/A

13-UNA-2018-17-12
 R:\66015\17\off\ek\signal\design\wiring\07-0006e.dgn
 7/10/2018 10:41:17 AM AT CAR-RLANTON-W7



Electrical Detail

ELECTRICAL AND PROGRAMMING DETAILS FOR:

Prepared for the Offices of:

750 N. Greenfield Pkwy, Garner, NC 27529

SR 1323 (W. Front Street) at Trollering Street

Division 7 Alamance County Burlington

PLAN DATE: September 2017 REVIEWED BY: LM Moon

PREPARED BY: AJ Davis REVIEWED BY:

REVISIONS INIT. DATE

DocuSigned by: Lisa M. Moon 6/13/2018

SIG. INVENTORY NO. 07-0006


DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

SEAL



DocuSigned by: Lisa M. Moon 6/13/2018

SIG. INVENTORY NO. 07-0006


DEFAULT PHASING DIAGRAM



SIGNAL FACE	PHASE		
	02+6	04+8	FLASH
21	G	R	Y
22	G	R	Y
41, 42, 43	R	G	R
61	G	R	Y
62	G	R	Y
81, 82	R	G	R




ALTERNATE 1 PHASING DIAGRAM



SIGNAL FACE	PHASE		
	01+6	02+6	04+8
21	R	G	R
22	R	G	R
41, 42, 43	R	R	G
61	G	R	Y
62	G	R	Y
81, 82	R	R	G

ALTERNATE 2 PHASING DIAGRAM




SIGNAL FACE	PHASE		
	02+5	02+6	04+8
21	G	R	Y
22	G	R	Y
41, 42, 43	R	R	G
61	R	G	R
62	R	G	R
81, 82	R	R	G

2 Phase Fully Actuated (Burlington-Graham Signal System)

NOTES

1. Refer to "Roadway Standard Drawings NCDOT" dated January 2018 and "Standard Specifications for Roads and Structures" dated January 2018.
2. Do not program signal for late night flashing operation unless otherwise directed by the Engineer.
3. Omit phase 1 during phase 2 on.
4. Omit phase 5 during phase 6 on.
5. Program controller to clear from phase 2+6 to phase 1 and/or 5 by progressing through phase 4+8 (see Electrical Details).
6. Reposition existing signal head numbered 22.
7. Set all detector units to presence mode.
8. In the event of loop replacement, refer to the current ITS and Signals Design Manual and submit a Plan of Record to the Signal Design Section.
9. Locate new cabinet so as not to obstruct sight distance of vehicles turning right on red.
10. The City Traffic Engineer will determine the hours of use for each phasing plan.
11. Maximum times shown in timing chart are for free-run operation only. Coordinated signal system timing values supersede these values.




FEATURE	PHASE							
	1	2	4	5	6	8		
Min Green *	7	12	7	7	12	7		
Walk *	0	0	0	0	0	0		
Ped Clear	0	0	0	0	0	0		
Veh. Extension *	0.0	0.0	0.0	0.0	0.0	0.0		
Max 1 *	15	60	30	15	60	30		
Yellow	3.0	4.4	3.8	3.0	4.6	3.8		
Red Clear	1.8	1.3	1.0	2.3	1.0	1.6		
Actuations B4 Add *	-	0	-	-	0	-		
Seconds /Actuation *	-	2.5	-	-	2.5	-		
Max Initial *	-	34	-	-	34	-		
Time Before Reduction *	-	20	-	-	20	-		
Time To Reduce *	-	20	-	-	20	-		
Minimum Gap	-	3.0	-	-	3.0	-		
Locking Detector	-	X	-	-	X	-		
Recall Position	-	VEH. RECALL	-	-	VEH. RECALL	-		
Dual Entry	-	-	X	-	-	X		
Simultaneous Gap	X	X	X	X	X	X		

* These values may be field adjusted. Do not adjust Min Green and Extension times for phases 2 and 6 lower than what is shown. Min Green for all other phases should not be lower than 4 seconds.

ASC/3 DETECTOR INSTALLATION CHART											
DETECTOR				PROGRAMMING							
LOOP	SIZE (FT)	DISTANCE FROM STOPBAR (FT)	TURNS	NEW LOOP	PHASE	CALLING	EXTEND TIME	DELAY TIME	USE ADDED INITIAL	SYSTEM LOOP	NEW CARD
1A	6x15	50	3	X	1*	Yes	-	15	-	S	- X
2A	6x6	300	4	X	2	Yes	-	-	X	N	- X
4A	6x60	0	2-4-2	-	4	Yes	-	5	-	S	- X
5A	6x15	50	3	X	5**	Yes	-	15	-	S	- X
6A	6x6	300	4	X	6	Yes	-	-	X	N	- X
8A	6x50	+10	2-4-2	-	8	Yes	-	-	-	S	- X
8B	6x40	+5	2-4-2	-	8	Yes	-	-	-	S	- X
S1	6x6	+230	EXIST.	-	-	No	-	-	-	N	X X

* Enable Loop 1A During Alternate 1 Phasing Operation Only.
 ** Enable Loop 5A During Alternate 2 Phasing Operation Only.



Signal Upgrade



12 BROAD STREET
 ASHEVILLE, NORTH CAROLINA 28801
 (828) 254-2201
 FAX (828) 254-4562
 NC LIC. NO. C-1154

Division 7 Alamance County Burlington

NC 54 (Chapel Hill Road) at Tucker Street

PLAN DATE: April 2018 REVIEWED BY: JB Voso

PREPARED BY: SE Greene REVIEWED BY:

REVISIONS

INIT. DATE

SEAL

SEAL 022599

James Voso


7/2/2018

SIG. INVENTORY NO. 07-0008

10:38:25 AM I:\Projects\Burlington-Graham Signal System\06 Working Folders with NCDOT File Structure If Working on NCDOT Project\DWG or Dgn\07-0008\070008_sig.dwg_20110808.dgn

EDI MODEL 2018ECLip-NC CONFLICT MONITOR
PROGRAMMING DETAIL

(remove jumpers and set switches as shown)



NOTES:

1. Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
2. Ensure jumpers SEL2-SEL5 and SEL9 are present on the monitor board.
3. Ensure that Red Enable is active at all times during normal operation.
4. Integrate monitor with Ethernet network in cabinet.

NOTES

1. To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
2. Program phases 4 and 8 for Dual Entry.
3. Program controller to start up in phase 2 Green and 6 Green.
4. The cabinet and controller are part of the Burlington-Graham Signal System.

EQUIPMENT INFORMATION

CONTROLLER.....2070LX
 CABINET.....336
 SOFTWARE.....ECONOLITE ASC/3-2070
 CABINET MOUNT.....POLE
 OUTPUT FILE POSITIONS...12
 LOAD SWITCHES USED.....S1,S2,S5,S7,S8,S11
 PHASES USED.....1,2,4,5,6,8
 OVERLAPS.....NONE

SIGNAL HEAD HOOK-UP CHART

LOAD SWITCH NO.	S1	S2	S3	S4	S5	S6	S7	S8	S9	S10	S11	S12
CMU CHANNEL NO.	1	2	13	3	4	14	5	6	15	7	8	16
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED
SIGNAL HEAD NO.	61	21,22	NU	NU	41,42,43	NU	21	61,62	NU	NU	81,82	NU
RED	*	128			101		*	134			107	
YELLOW		129			102			135			108	
GREEN		130			103			136			109	
RED ARROW												
YELLOW ARROW	126						132					
GREEN ARROW	127						133					

NU = Not Used

* Denotes install load resistor. See load resistor installation detail this sheet.

INPUT FILE POSITION LAYOUT

(front view)

FILE U	1	2	3	4	5	6	7	8	9	10	11	12	13	14
∅ 1	∅ 2	S	∅ 4	∅ 5	∅ 6	S	∅ 8	S	S	S	S	S	S	FS
1A	2A	STOP	4A	5A	6A	STOP	8A	STOP	STOP	STOP	STOP	STOP	STOP	DC ISOLATOR
NOT USED	NOT USED	←-→	NOT USED	NOT USED	SYS. DET. S1	←-→	∅ 8	←-→	←-→	←-→	←-→	←-→	←-→	ST
							8B	←-→	←-→	←-→	←-→	←-→	←-→	DC ISOLATOR

EX.: 1A, 2A, ETC. = LOOP NO.'S

FS = FLASH SENSE
 ST = STOP TIME

INPUT FILE CONNECTION & PROGRAMMING CHART

LOOP NO.	LOOP TERMINAL	INPUT FILE POS.	PIN NO.	DETECTOR NO.	NEMA PHASE	CALL	EXTEND TIME	DELAY TIME	ADDED INITIAL	DETECTOR TYPE
1A	TB21-1,2	11U	56	1★	-	YES		15		S
2A	TB21-3,4	12U	39	2	2	YES			X	N
4A	TB21-7,8	14U	41	4	4	YES		5		S
5A	TB21-9,10	15U	55	5★	-	YES		15		S
6A	TB21-11,12	16U	40	6	6	YES			X	N
* S1	TB23-11,12	16L	44	16	SYS	NO				N
8A	TB22-1,2	18U	42	8	8	YES				S
8B	TB24-1,2	18L	46	18	8	YES				S


★ There is no assigned vehicle phase for detectors 1 and 5 during default phasing operation. For the detectors to work as shown on the signal design plan, see the Vehicle Detector Setup Programming Detail for Alternate Phasing on sheet 3.

* System detector only. Remove the vehicle phase assigned to this detector in the default programming.


LOAD RESISTOR INSTALLATION DETAIL

(install resistors as shown)

VALUE (ohms)	WATTAGE
1.5K - 1.9K	25W (min)
2.0K - 3.0K	10W (min)



INPUT FILE POSITION LEGEND: J2L




THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 07-0008
 DESIGNED: April 2018
 SEALED: 7/2/2018
 REVISED: NA

Electrical Detail - Sheet 1 of 5



12 BROAD STREET
 ASHEVILLE, NORTH CAROLINA 28801
 (828) 254-2201
 FAX (828) 254-4562
 NC LIC. NO. C-1154



Prepared for the Offices of:		NC 54 (Chapel Hill Road) at Tucker Street	
PLAN DATE: April 2018	REVIEWED BY: JB Voso	INIT.	DATE
PREPARED BY: SE Greene	REVIEWED BY:		
REVISIONS			

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

DocuSigned By: James Voso	7/2/2018
SIG. INVENTORY NO. 07-0008	

*****SYTIME*****
 *****D*****
 *****USER*****

**ECONOLITE ASC/3-2070 BACKUP
PREVENT ENABLE PROGRAMMING**
(program controller as shown)

1. From Main Menu select 1. CONFIGURATION
2. From CONFIGURATION Submenu select 1. CONTROLLER SEQ
3. From CONTROLLER SEQUENCE Submenu select 3. BACKUP PREVENT PHASES

Follow programming as shown below. On the 'ENABLE BACKUP PREVENT' screen move cursor to the appropriate field and press 'YES/NO' on the controller keypad to toggle field value between 'X', 'B', 'C' and 'OFF'.

ENABLE	BACKUP	PREVENT														
TMG/BKUP	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6
1
2	B	.	C
3
4
5
6	.	.	C	B
7
8
9
10
11
12
13
14
15
16

END PROGRAMMING

NOTE

1. 'B' with a 'C' programmed for the 'TIMING' (row) phase places a demand on that 'BACKUP' (column) phase. The controller will then service the called phase and proceed normally.


THIS ELECTRICAL DETAIL IS FOR
THE SIGNAL DESIGN: 07-0008
DESIGNED: April 2018
SEALED: 7/2/2018
REVISED: NA

Electrical Detail - Sheet 2 of 5


DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED



12 BROAD STREET
ASHEVILLE, NORTH CAROLINA 28801
(828) 254-2201
FAX (828) 254-4562
NC LIC. NO. C-1154



ELECTRICAL AND PROGRAMMING DETAILS FOR:		NC 54 (Chapel Hill Road) at Tucker Street	
Prepared For the Offices of:	Division 7	Alamance County	Burlington
PLAN DATE: April 2018	REVIEWED BY: JB Voso		
PREPARED BY: SE Greene	REVIEWED BY:		
REVISIONS	INIT.	DATE	



SIG. INVENTORY NO. 07-0008

*****SYSTEM*****
*****USER*****

ALTERNATE PHASING ACTIVATION DETAIL

TO RUN ALT. PHASING DURING FREE RUN - PROGRAM CHANGES (SHOWN BELOW) IN A TIME BASED ACTION PLAN. SCHEDULE A DAY PLAN THAT INCLUDES THE ACTION PLAN PROGRAMMED TO SELECT VEH DET PLAN 2 FOR ALTERNATE 1 PHASING OPERATION AND VEH DET PLAN 3 FOR ALTERNATE 2 PHASING OPERATION.

TO RUN ALT. PHASING DURING COORDINATION - SELECT THE TIME BASED ACTION PLAN THAT IS PROGRAMMED TO SELECT VEH DET PLAN 2 FOR ALTERNATE 1 PHASING OPERATION AND VEH DET PLAN 3 FOR ALTERNATE 2 PHASING OPERATION.

PHASING	VEH DET PLAN
ACTIONS REQUIRED TO RUN <u>DEFAULT PHASING</u>	1
ACTIONS REQUIRED TO RUN <u>ALTERNATE 1 PHASING</u>	2
ACTIONS REQUIRED TO RUN <u>ALTERNATE 2 PHASING</u>	3

IMPORTANT: IF ALT. PHASING IS USED DURING FREE RUN AND COORDINATION, DO NOT OPERATE TIME OF DAY EVENTS CONCURRENTLY WITH COORDINATION PLAN EVENTS IN THE EVENT SCHEDULER. (EX. FREE RUN EVENT SHOULD END BEFORE COORDINATION PLAN EVENT STARTS AND VICE-VERSA).

ALTERNATE PHASING CHANGE SUMMARY

THE FOLLOWING IS A SUMMARY OF WHAT TAKES PLACE WHEN VEH DET PLAN 2 OR VEH DET PLAN 3 ACTIVATE TO CALL THE "ALTERNATE PHASING":

VEH DET PLAN 2: Enables phase 1 call on loop 1A.

VEH DET PLAN 3: Enables phase 5 call on loop 5A.

ECONOLITE ASC/3-2070 ACTION PLAN PROGRAMMING DETAIL

- From Main Menu select **5. TIME BASE**
- From TIME BASE Submenu select **2. ACTION PLAN**

```

ACTION PLAN...[ 1]
PATTERN.....AUTO   SYS OVERRIDE.... NO
TIMING PLAN..... 0   SEQUENCE..... 0
VEH DETECTOR PLAN.. 2   DET LOG.....NONE
FLASH..... --   RED REST..... NO
VEH DET DIAG PLN... 0   PED DET DIAG PLN..0
DIMMING ENABLE.. NO   PRIORITY RETURN. NO
PED PR RETURN.. NO   QUEUE DELAY..... NO
PMT COND DELAY NO
  PHASE 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6
PED RCL . . . . .
WALK 2 . . . . .
VEX 2 . . . . .
VEH RCL . . . . .
MAX RCL . . . . .
MAX 2 . . . . .
  PHASE 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6
MAX 3 . . . . .
CS INH . . . . .
OMIT . . . . .
SPC FCT . . . . . (1-8)
AUX FCT . . . (1-3)
      1 2 3 4 5 6 7 8 9 0 1 2 3 4 5
LP 1-15 . . . . .
LP 16-30 . . . . .
LP 31-45 . . . . .
LP 46-60 . . . . .
LP 61-75 . . . . .
LP 76-90 . . . . .
LP 91-100 . . . . .
  
```

ECONOLITE ASC/3-2070 ACTION PLAN PROGRAMMING DETAIL

- From Main Menu select **5. TIME BASE**
- From TIME BASE Submenu select **2. ACTION PLAN**

```

ACTION PLAN...[ 2]
PATTERN.....AUTO   SYS OVERRIDE.... NO
TIMING PLAN..... 0   SEQUENCE..... 0
VEH DETECTOR PLAN.. 3   DET LOG.....NONE
FLASH..... --   RED REST..... NO
VEH DET DIAG PLN... 0   PED DET DIAG PLN..0
DIMMING ENABLE.. NO   PRIORITY RETURN. NO
PED PR RETURN.. NO   QUEUE DELAY..... NO
PMT COND DELAY NO
  PHASE 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6
PED RCL . . . . .
WALK 2 . . . . .
VEX 2 . . . . .
VEH RCL . . . . .
MAX RCL . . . . .
MAX 2 . . . . .
  PHASE 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6
MAX 3 . . . . .
CS INH . . . . .
OMIT . . . . .
SPC FCT . . . . . (1-8)
AUX FCT . . . (1-3)
      1 2 3 4 5 6 7 8 9 0 1 2 3 4 5
LP 1-15 . . . . .
LP 16-30 . . . . .
LP 31-45 . . . . .
LP 46-60 . . . . .
LP 61-75 . . . . .
LP 76-90 . . . . .
LP 91-100 . . . . .
  
```

Mattern & Craig
ENGINEERS • SURVEYORS

12 BROAD STREET
ASHEVILLE, NORTH CAROLINA 28801
(828) 254-2201
FAX (828) 254-4562
NC LIC. NO. C-1154

THIS ELECTRICAL DETAIL IS FOR
THE SIGNAL DESIGN: 07-0008
DESIGNED: April 2018
SEALED: 7/2/2018
REVISED: NA

Electrical Detail - Sheet 5 of 5

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

SEAL
NORTH CAROLINA PROFESSIONAL ENGINEERS
SEAL 022599
JAMES B. VOSO

Division 7 Alamance County Burlington

PLAN DATE: April 2018 REVIEWED BY: JB Voso

PREPARED BY: SE Greene REVIEWED BY:

REVISIONS

REVISIONS	INIT.	DATE

James Voso 7/2/2018


SIG. INVENTORY NO. 07-0008

*****SYTIME*****
*****D*****
*****USER*****

EDI MODEL 2018ECLIP-NC CONFLICT MONITOR PROGRAMMING DETAIL

(remove jumpers and set switches as shown)


REMOVE DIODE JUMPERS 1-5, 1-6, 1-9, 1-11, 1-15, 2-5, 2-6, 2-9, 2-11, 2-13, 2-15, 3-7, 3-8, 3-10, 3-12, 3-16, 4-7, 4-8, 4-10, 4-12, 4-14, 4-16, 5-9, 5-11, 5-13, 6-9, 6-11, 6-13, 6-15, 7-10, 7-12, 7-14, 8-10, 8-12, 8-14, 8-16, 9-11, 9-13, 9-15, 10-12, 10-14, 10-16, 11-13, 11-15, 12-14, 12-16, 13-15, and 14-16.



REMOVE JUMPERS AS SHOWN

NOTES:

- 1. Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
2. Ensure jumpers SEL2-SEL5 and SEL9 are present on the monitor board.
3. Ensure that Red Enable is active at all times during normal operation.
4. Integrate monitor with Ethernet network in cabinet.



NOTES

- 1. To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file.
2. Program phases 4 and 8 for Dual Entry.
3. Program controller to start up in phase 2 Walk and 6 Walk.
4. The cabinet and controller are part of the Burlington-Graham Signal System.

EQUIPMENT INFORMATION

CONTROLLER.....2070LX
CABINET.....332 W/AUX
SOFTWARE.....ECONOLITE ASC/3-2070
CABINET MOUNT.....BASE
OUTPUT FILE POSITIONS...18 WITH AUX. OUTPUT FILE
LOAD SWITCHES USED.....S1,S2,S3,S4,S5,S6,S7,S8,S9, S10,S11,S12,AUX S1,AUX S2, AUX S4,AUX S5
PHASES USED.....1,2,2PED,3,4,4PED,5,6,6PED, 7,8,8PED

OVERLAP "A".....*
OVERLAP "B".....*
OVERLAP "C".....*
OVERLAP "D".....*
* See overlap programming detail on sheet 2


SIGNAL HEAD HOOK-UP CHART

Table with columns for LOAD SWITCH NO., S1-S12, AUX S1-S6, and rows for RED, YELLOW, GREEN, RED ARROW, YELLOW ARROW, FLASHING YELLOW ARROW, GREEN ARROW, and pedestrian symbols.

NU = Not Used
* Denotes install load resistor. See load resistor installation detail this sheet.
★ See pictorial of head wiring in detail this sheet.

INPUT FILE POSITION LAYOUT

(front view)



EX.: 1A, 2A, ETC. = LOOP NO.'S FS = FLASH SENSE ST = STOP TIME

Wired Input - Do not populate slot with detector cord


INPUT FILE CONNECTION & PROGRAMMING CHART

Table with columns: LOOP NO., LOOP TERMINAL, INPUT FILE POS., PIN NO., DETECTOR NO., NEMA PHASE, CALL, EXTEND TIME, DELAY TIME, ADDED INITIAL, DETECTOR TYPE.

NOTE: INSTALL DC ISOLATORS IN INPUT FILE SLOTS 112 AND 113.


- * System detector only. Remove any assigned vehicle phase.
1 Add jumper from I1-W to J4-W, on rear of input file.
2 Add jumper from I5-W to J8-W, on rear of input file.
3 Add jumper from J1-W to I4-W, on rear of input file.
4 Add jumper from J5-W to I8-W, on rear of input file.

INPUT FILE POSITION LEGEND:



FYA SIGNAL WIRING DETAIL


(wire signal heads as shown)



LOAD RESISTOR INSTALLATION DETAIL

(install resistors as shown)

Table with columns: VALUE (ohms), WATTAGE. Values: 1.5K - 1.9K, 25W (min); 2.0K - 3.0K, 10W (min).



Electrical Detail - Sheet 1 of 2

DRMP logo and address: 8000 Regency Parkway, Suite 175, Cary, NC 27518. NC License No. C-2213 (919) 650-1038.

Project information: NC 54 (Chapel Hill Road) at SR 1363 (S. Mebane Street). Division 7, Alamance County, Burlington. Plan Date: September 2017. Prepared by: AJ Davis.

Professional Engineer seal for Lisa M. Moon, License No. 022516, State of North Carolina.

THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 07-0009 DESIGNED: SEPT-2017 SEALED: 06-13-2018 REVISED:

COUNTDOWN PEDESTRIAN SIGNAL OPERATION

Countdown Ped Signals are required to display timing only during Ped Clearance Interval. Consult Ped Signal Module user's manual for instructions on selecting this feature.

ECONOLITE ASC/3-2070 OVERLAP PROGRAMMING DETAIL

(program controller as shown)

- From Main Menu select 2. CONTROLLER
- From CONTROLLER Submenu select 2. VEHICLE OVERLAPS

OVERLAP A

Select TMG VEH OVLP [A] and 'PPLT FYA'

```

TMG VEH OVLP...[A] TYPE: ....PPLT FYA
PROTECTED LEFT TURN.... PHASE 1
OPPOSING THROUGH..... PHASE 2

FLASHING ARROW OUTPUT.....CH9 ISOLATE
DELAY START OF: FYA..0.0 CLEARANCE..0.0
ACTION PLAN SF BIT DISABLE..... 0
    
```

Toggle Once

OVERLAP B

Select TMG VEH OVLP [B] and 'PPLT FYA'

```

TMG VEH OVLP...[B] TYPE: ....PPLT FYA
PROTECTED LEFT TURN.... PHASE 3
OPPOSING THROUGH..... PHASE 4

FLASHING ARROW OUTPUT.....CH10 ISOLATE
DELAY START OF: FYA..0.0 CLEARANCE..0.0
ACTION PLAN SF BIT DISABLE..... 0
    
```

Toggle Once

OVERLAP C

Select TMG VEH OVLP [C] and 'PPLT FYA'

```

TMG VEH OVLP...[C] TYPE: ....PPLT FYA
PROTECTED LEFT TURN.... PHASE 5
OPPOSING THROUGH..... PHASE 6

FLASHING ARROW OUTPUT.....CH11 ISOLATE
DELAY START OF: FYA..0.0 CLEARANCE..0.0
ACTION PLAN SF BIT DISABLE..... 0
    
```

Toggle Once

OVERLAP D

Select TMG VEH OVLP [D] and 'PPLT FYA'

```

TMG VEH OVLP...[D] TYPE: ....PPLT FYA
PROTECTED LEFT TURN.... PHASE 7
OPPOSING THROUGH..... PHASE 8

FLASHING ARROW OUTPUT.....CH12 ISOLATE
DELAY START OF: FYA..0.0 CLEARANCE..0.0
ACTION PLAN SF BIT DISABLE..... 0
    
```

END PROGRAMMING

FLASHER CIRCUIT MODIFICATION DETAIL

In order to ensure that signals flash concurrently on the Same approach, make the following flasher circuit changes:

- On rear of PDA - remove wire from Term. T2-4 and terminate on T2-2.
- On rear of PDA - remove wire from Term. T2-5 and terminate on T2-3.
- Remove flasher unit 2.

The changes listed above ties all phases and overlaps to flasher unit 1.

THIS ELECTRICAL DETAIL IS FOR
THE SIGNAL DESIGN: 07-0009
DESIGNED: SEPT-2017
SEALED: 06-13-2018
REVISED:

Electrical Detail - Sheet 2 of 2


Plans Prepared By:



DRMP, Inc.
8000 Regency Parkway, Suite 175
Cary, NC 27518
NC License No. C-2213 (919) 650-1038

ELECTRICAL AND PROGRAMMING
DETAILS FOR:

Prepared for the Offices of:



750 N. Greenfield Pkwy, Garner, NC 27529

NC 54 (Chapel Hill Road)
at
SR 1363 (S. Mebane Street)

Division 7 Alamance County Burlington


PLAN DATE: September 2017 REVIEWED BY: LM Moon

PREPARED BY: AJ Davis REVIEWED BY:

REVISIONS	INIT.	DATE

DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED

SEAL




DocuSigned by:
Lisa M. Moon 6/13/2018

SIG. INVENTORY NO. 07-0009

EDI MODEL 2018ECLip-NC CONFLICT MONITOR PROGRAMMING DETAIL

(keep jumpers and set switches as shown)



NOTES:

1. Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
2. Ensure jumpers SEL2-SEL5 and SEL9 are present on the monitor board.
3. Ensure that Red Enable is active at all times during normal operation.
4. Integrate monitor with Ethernet network in cabinet.

NOTES

1. To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
2. Program controller to start up in phase 2 Green.
3. The cabinet and controller are part of the Burlington-Graham Signal System.

EQUIPMENT INFORMATION

CONTROLLER.....2070LX
 CABINET.....332 W/AUX
 SOFTWARE.....ECONOLITE ASC/3-2070
 CABINET MOUNT.....BASE
 OUTPUT FILE POSITIONS...18 WITH AUX. OUTPUT FILE
 LOAD SWITCHES USED.....S2,S5
 PHASES USED.....2,4
 OVERLAP "A".....NOT USED
 OVERLAP "B".....NOT USED
 OVERLAP "C".....NOT USED
 OVERLAP "D".....NOT USED


SIGNAL HEAD HOOK-UP CHART

LOAD SWITCH NO.	S1	S2	S3	S4	S5	S6	S7	S8	S9	S10	S11	S12	AUX S1	AUX S2	AUX S3	AUX S4	AUX S5	AUX S6
CMU CHANNEL NO.	1	2	13	3	4	14	5	6	15	7	8	16	9	10	17	11	12	18
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED	OLA	OLB	SPARE	OLC	OLD	SPARE
SIGNAL HEAD NO.	NU	21,22 23,24,25	NU	NU	41,42 43,44	NU	NU	NU	NU	NU	NU	NU	NU	NU	NU	NU	NU	NU
RED		128			101													
YELLOW		129			102													
GREEN		130			103													
RED ARROW																		
YELLOW ARROW																		
GREEN ARROW																		

NU = Not Used

INPUT FILE POSITION LAYOUT

(front view)




EX.: 1A, 2A, ETC. = LOOP NO.'S

FS = FLASH SENSE
ST = STOP TIME

INPUT FILE CONNECTION & PROGRAMMING CHART


LOOP NO.	LOOP TERMINAL	INPUT FILE POS.	PIN NO.	DETECTOR NO.	NEMA PHASE	CALL	EXTEND TIME	DELAY TIME	ADDED INITIAL	DETECTOR TYPE
* S1	TB6-9,10	I9U	60	11	SYS	NO				N
* S2	TB6-11,12	I9L	62	13	SYS	NO				N

* System detector only. Remove any assigned vehicle phase.



THIS ELECTRICAL DETAIL IS FOR
 THE SIGNAL DESIGN: 07-0011
 DESIGNED: NOVEMBER 2017
 SEALED: 06-13-2018
 REVISED: N/A

13-Jul-2018 17:13
R:\66015\17\off\ek\esign\design\wiring\07-0011e.dgn
Lawton AT CAR-RLAWTON-W7



Electrical Detail

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

ELECTRICAL AND PROGRAMMING DETAILS FOR: US 70 - NC 62 (S. Church Street) at W. Fifth Street

Prepared for the Offices of:

Division 7 Alamance County Burlington

PLAN DATE: November 2017 REVIEWED BY: AJ Davis


PREPARED BY: RD Lawton REVIEWED BY: LM Moon

REVISIONS	INIT.	DATE

DocuSigned by: Lisa M. Moon 6/13/2018
 sig. INVENTORY NO. 07-0011

EDI MODEL 2018ECLip-NC CONFLICT MONITOR PROGRAMMING DETAIL

(remove jumpers and set switches as shown)



NOTES:

- Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
- Ensure jumpers SEL2-SEL5 and SEL9 are present on the monitor board.
- Ensure that Red Enable is active at all times during normal operation.
- Integrate monitor with Ethernet network in cabinet.

NOTES

- To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
- Program phases 4 and 8 for Dual Entry.
- Program controller to start up in phase 2 Green and 6 Green.
- The cabinet and controller are part of the Burlington-Graham Signal System.

SIGNAL HEAD HOOK-UP CHART

LOAD SWITCH NO.	S1	S2	S3	S4	S5	S6	S7	S8	S9	S10	S11	S12
CMU CHANNEL NO.	1	2	13	3	4	14	5	6	15	7	8	16
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED
SIGNAL HEAD NO.	NU	21,22	NU	NU	41,42	NU	NU	61,62	NU	NU	81,82	NU
RED		128			101			134			107	
YELLOW		129			102			135			108	
GREEN		130			103			136			109	
RED ARROW												
YELLOW ARROW												
GREEN ARROW												


NU = Not Used

EQUIPMENT INFORMATION

CONTROLLER.....2070LX
 CABINET.....336
 SOFTWARE.....ECONDLITE ASC/3-2070
 CABINET MOUNT.....POLE
 OUTPUT FILE POSITIONS...12
 LOAD SWITCHES USED.....S2,S5,S8,S11
 PHASES USED.....2,4,6,8
 OVERLAPS.....NONE

INPUT FILE POSITION LAYOUT


(front view)



INPUT FILE CONNECTION & PROGRAMMING CHART

LOOP NO.	LOOP TERMINAL	INPUT FILE POS.	PIN NO.	DETECTOR NO.	NEMA PHASE	CALL	EXTEND TIME	DELAY TIME	ADDED INITIAL	DETECTOR TYPE
4A	TB21-7,8	I4U	41	4	4	YES		5		S
* S1	TB21-11,12	I6U	40	6	SYS	NO				N
* S2	TB23-11,12	I6L	44	16	SYS	NO				N
8A	TB22-1,2	I8U	42	8	8	YES		5		S

* System detector only. Remove any assigned vehicle phase.



THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 07-0012
 DESIGNED: August-2017
 SEALED: 06-13-2018
 REVISED: N/A

13-UNA-2018-17-13
 R:\66015\17\off\ek\sign\design\w\ir\img\07-0012e.dgn
 C:\ewton AT CAR-RLANDON-W7



Electrical Detail

Electrical and Programming Details For:

Prepared for the Offices of:

750 N. Greenfield Pkwy, Garner, NC 27529

NC 87 (E. Webb Avenue) at Williamson Street

Division 7 Alamance County Burlington

PLAN DATE: August 2017 REVIEWED BY: LM Moon

PREPARED BY: AJ Davis REVIEWED BY:

REVISIONS	INIT.	DATE

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED


SEAL

DocuSigned by: Lisa M. Moon 6/13/2018

SIG. INVENTORY NO. 07-0012

EDI MODEL 2018ECLip-NC CONFLICT MONITOR PROGRAMMING DETAIL

(remove jumpers and set switches as shown)



NOTES:

- Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
- Ensure jumpers SEL2-SEL5 and SEL9 are present on the monitor board.
- Ensure that Red Enable is active at all times during normal operation.
- Integrate monitor with Ethernet network in cabinet.

NOTES

- To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
- Program phases 4 and 8 for Dual Entry.
- Program controller to start up in phase 2 Green and 6 Green.
- The cabinet and controller are part of the Burlington-Graham Signal System.

SIGNAL HEAD HOOK-UP CHART

LOAD SWITCH NO.	S1	S2	S3	S4	S5	S6	S7	S8	S9	S10	S11	S12
CMU CHANNEL NO.	1	2	13	3	4	14	5	6	15	7	8	16
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED
SIGNAL HEAD NO.	NU	21,22	NU	NU	41,42	NU	NU	61,62	NU	NU	81,82	NU
RED		128			101			134			107	
YELLOW		129			102			135			108	
GREEN		130			103			136			109	
RED ARROW												
YELLOW ARROW												
GREEN ARROW												


NU = Not Used

EQUIPMENT INFORMATION

CONTROLLER.....2070LX
 CABINET.....336
 SOFTWARE.....ECONDLITE ASC/3-2070
 CABINET MOUNT.....POLE
 OUTPUT FILE POSITIONS...12
 LOAD SWITCHES USED.....S2,S5,S8,S11
 PHASES USED.....2,4,6,8
 OVERLAPS.....NONE

INPUT FILE POSITION LAYOUT

(front view)



EX.: 1A, 2A, ETC. = LOOP NO.'S


FS = FLASH SENSE
 ST = STOP TIME

INPUT FILE CONNECTION & PROGRAMMING CHART

LOOP NO.	LOOP TERMINAL	INPUT FILE POS.	PIN NO.	DETECTOR NO.	NEMA PHASE	CALL	EXTEND TIME	DELAY TIME	ADDED INITIAL	DETECTOR TYPE
4A	TB21-7,8	I4U	41	4	4	YES		5		S
* S1	TB21-9,10	I5U	55	5	SYS	NO				N
* S2	TB23-9,10	I5L	48	26	SYS	NO				N
* S3	TB21-11,12	I6U	40	6	SYS	NO				N
* S4	TB23-11,12	I6L	44	16	SYS	NO				N
8A	TB22-1,2	I8U	42	8	8	YES		5		S

* System detector only. Remove any assigned vehicle phase.

INPUT FILE POSITION LEGEND: J2L




THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 07-0013
 DESIGNED: NOVEMBER 2017
 SEALED: 06-13-2018
 REVISED: N/A

Electrical Detail

ELECTRICAL AND PROGRAMMING DETAILS FOR:

Prepared for the Offices of:



NC 87-100 (E. Webb Ave.)
 at
 Flanner Street

Division 7 Alamance County Burlington

PLAN DATE: November 2017 REVIEWED BY: AJ Davis
 PREPARED BY: DJ White REVIEWED BY: LM Moon

REVISIONS	INIT.	DATE


DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED



DocuSigned by: Lisa M. Moon 6/13/2018
 DATE: 6/13/2018
 SIG. INVENTORY NO. 07-0013

EDI MODEL 2018ECLip-NC CONFLICT MONITOR PROGRAMMING DETAIL

(remove jumper and set switches as shown)



NOTES:

1. Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
2. Ensure jumpers SEL2-SEL5 and SEL9 are present on the monitor board.
3. Ensure that Red Enable is active at all times during normal operation.
4. Integrate monitor with Ethernet network in cabinet.

NOTES

1. To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
2. Program controller to start up in phase 2 Green and 6 Green.
3. The cabinet and controller are part of the Burlington-Graham Signal System.

SIGNAL HEAD HOOK-UP CHART

LOAD SWITCH NO.	S1	S2	S3	S4	S5	S6	S7	S8	S9	S10	S11	S12
CMU CHANNEL NO.	1	2	13	3	4	14	5	6	15	7	8	16
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED
SIGNAL HEAD NO.	NU	21,22	NU	NU	41,42	NU	NU	61,62	NU	NU	NU	NU
RED		128			101			134				
YELLOW		129			102			135				
GREEN		130			103			136				
RED ARROW												
YELLOW ARROW												
GREEN ARROW												


NU = Not Used

EQUIPMENT INFORMATION

CONTROLLER.....2070LX
 CABINET.....336
 SOFTWARE.....ECONDLITE ASC/3-2070
 CABINET MOUNT.....POLE
 OUTPUT FILE POSITIONS...12
 LOAD SWITCHES USED.....S2,S5,S8
 PHASES USED.....2,4,6
 OVERLAPS.....NONE

INPUT FILE POSITION LAYOUT

(front view)




EX.: 1A, 2A, ETC. = LOOP NO.'S

FS = FLASH SENSE
 ST = STOP TIME

INPUT FILE CONNECTION & PROGRAMMING CHART

LOOP NO.	LOOP TERMINAL	INPUT FILE POS.	PIN NO.	DETECTOR NO.	NEMA PHASE	CALL	EXTEND TIME	DELAY TIME	ADDED INITIAL	DETECTOR TYPE
4A	TB21-7,8	14U	41	4	4	YES		5		S

INPUT FILE POSITION LEGEND: J2L



THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 07-0014
 DESIGNED: SEPT-2017
 SEALED: 06-13-2018
 REVISED: N/A

13-UNA-2018-17-14
 R:\66015\17\off\ek\sign\des\gn\w\ir\ing\07-0014e.dgn
 C:\lowton AT CAR-RLANTON-W7

Electrical Detail

ELECTRICAL AND PROGRAMMING DETAILS FOR:




Plans Prepared By:
DRMP
 DRMP, Inc.
 8000 Regency Parkway, Suite 175
 Cary, NC 27518
 NC License No. C-2213 (919) 650-1038

NC 87-100 (E. Webb Avenue)
 at
 Everett Street

Division 7	Alamance County	Burlington
PLAN DATE: August 2017	REVIEWED BY: LM Moon	
PREPARED BY: AJ Davis	REVIEWED BY:	
REVISIONS	INIT.	DATE


DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED



DocuSigned by:
 Lisa M. Moon
 6/13/2018
 DATE
 SIG. INVENTORY NO. 07-0014

EDI MODEL 2018ECLip-NC CONFLICT MONITOR PROGRAMMING DETAIL

(remove jumpers and set switches as shown)



NOTES:

- Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
- Ensure jumpers SEL2-SEL5 and SEL9 are present on the monitor board.
- Ensure that Red Enable is active at all times during normal operation.
- Integrate monitor with Ethernet network in cabinet.

NOTES

- To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
- Program phases 4 and 8 for Dual Entry.
- Program controller to start up in phase 2 Green and 6 Green.
- The cabinet and controller are part of the Burlington-Graham Signal System.

EQUIPMENT INFORMATION

CONTROLLER.....2070LX
 CABINET.....332 W/AUX
 SOFTWARE.....ECONOLITE ASC/3-2070
 CABINET MOUNT.....BASE
 OUTPUT FILE POSITIONS...18 WITH AUX. OUTPUT FILE
 LOAD SWITCHES USED.....S2,S5,S8,S11
 PHASES USED.....2,4,6,8
 OVERLAP "A".....NOT USED
 OVERLAP "B".....NOT USED
 OVERLAP "C".....NOT USED
 OVERLAP "D".....NOT USED


SIGNAL HEAD HOOK-UP CHART

LOAD SWITCH NO.	S1	S2	S3	S4	S5	S6	S7	S8	S9	S10	S11	S12	AUX S1	AUX S2	AUX S3	AUX S4	AUX S5	AUX S6
CMU CHANNEL NO.	1	2	13	3	4	14	5	6	15	7	8	16	9	10	17	11	12	18
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED	OLA	OLB	SPARE	OLC	OLD	SPARE
SIGNAL HEAD NO.	NU	21,22	NU	NU	41,42	NU	NU	61,62	NU	NU	81,82	NU	NU	NU	NU	NU	NU	NU
RED		128			101			134			107							
YELLOW		129			102			135			108							
GREEN		130			103			136			109							
RED ARROW																		
YELLOW ARROW																		
GREEN ARROW																		

NU = Not Used

INPUT FILE POSITION LAYOUT

(front view)




INPUT FILE CONNECTION & PROGRAMMING CHART

LOOP NO.	LOOP TERMINAL	INPUT FILE POS.	PIN NO.	DETECTOR NO.	NEMA PHASE	CALL	EXTEND TIME	DELAY TIME	ADDED INITIAL	DETECTOR TYPE
2A	TB2-5,6	I2U	39	2	2	YES				S
4A	TB4-9,10	I6U	41	4	4	YES		3		S
4B	TB4-11,12	I6L	45	14	4	YES		10		S
* S1	TB6-9,10	I9U	60	11	SYS	NO				N
* S2	TB6-11,12	I9L	62	13	SYS	NO				N
6A	TB3-5,6	J2U	40	6	6	YES				S
8A	TB5-9,10	J6U	42	8	8	YES		3		S
8B	TB5-11,12	J6L	46	18	8	YES		10		S

* System detector only. Remove any assigned vehicle phase.

INPUT FILE POSITION LEGEND: J2L



THIS ELECTRICAL DETAIL IS FOR
 THE SIGNAL DESIGN: 07-0015
 DESIGNED: NOVEMBER 2017
 SEALED: 06-13-2018
 REVISED: N/A

13-Jul-2018 17:14 R:\66015\17\off\ek\sig\nc\edi\mon\ir\ing\07-0015e.dgn C:\Users\AT_CAB-R\AMT\W7

Electrical Detail

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

Prepared for the Offices of:
 DRMP, Inc. 8000 Regency Parkway, Suite 175 Cary, NC 27519 NC License No. C-2213 (919) 650-1038

NC 100 (Maple Ave)/Maple Ave at NC 100 (S. Anthony St)/Anthony St
 Division 7 Alamance County Burlington


PLAN DATE: November 2017 REVIEWED BY: AJ Davis
 PREPARED BY: DJ White REVIEWED BY: LM Moon

REVISIONS INIT. DATE

DocuSigned by: Lisa M. Moon 6/13/2018
 SEAL NORTH CAROLINA PROFESSIONAL ENGINEER LISA M. MOON 022516
 SIG. INVENTORY NO. 07-0015

EDI MODEL 2018ECLip-NC CONFLICT MONITOR PROGRAMMING DETAIL

(remove jumpers and set switches as shown)



NOTES:

1. Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
2. Ensure jumpers SEL2-SEL5 and SEL9 are present on the monitor board.
3. Ensure that Red Enable is active at all times during normal operation.
4. Integrate monitor with Ethernet network in cabinet.

NOTES

1. To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
2. Program phases 4 and 8 for Dual Entry.
3. Program controller to start up in phase 2 Green and 6 Green.
4. The cabinet and controller are part of the Burlington-Graham Signal System.

EQUIPMENT INFORMATION

CONTROLLER.....2070LX
 CABINET.....332 w/AUX
 SOFTWARE.....ECONOLITE ASC/3-2070
 CABINET MOUNT.....BASE
 OUTPUT FILE POSITIONS...18 w/AUX OUTPUT FILE
 LOAD SWITCHES USED.....S2,S5,S6,S8,S11
 PHASES USED.....2,4,4PED,6,8
 OVERLAP "A".....NOT USED
 OVERLAP "B".....NOT USED
 OVERLAP "C".....NOT USED
 OVERLAP "D".....NOT USED


SIGNAL HEAD HOOK-UP CHART

LOAD SWITCH NO.	S1	S2	S3	S4	S5	S6	S7	S8	S9	S10	S11	S12	AUX S1	AUX S2	AUX S3	AUX S4	AUX S5	AUX S6
CMU CHANNEL NO.	1	2	13	3	4	14	5	6	15	7	8	16	9	10	17	11	12	18
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED	OLA	OLB	SPARE	OLC	OLD	SPARE
SIGNAL HEAD NO.	NU	21,22	NU	NU	41,42	P41, P42	NU	61,62	NU	NU	81,82	NU	NU	NU	NU	NU	NU	NU
RED		128			101			134			107							
YELLOW		129			102			135			108							
GREEN		130			103			136			109							
RED ARROW																		
YELLOW ARROW																		
GREEN ARROW																		
Hand icon																		104
Person icon																		106

NU = Not Used

INPUT FILE POSITION LAYOUT

(front view)



EX. : 1A, 2A, ETC. = LOOP NO.'S


FS = FLASH SENSE
 ST = STOP TIME

INPUT FILE CONNECTION & PROGRAMMING CHART

LOOP NO.	LOOP TERMINAL	INPUT FILE POS.	PIN NO.	DETECTOR NO.	NEMA PHASE	CALL	EXTEND TIME	DELAY TIME	ADDED INITIAL	DETECTOR TYPE
4A	TB4-9,10	I6U	41	4	4	YES		3		S
4B	TB4-11,12	I6L	45	14	4	YES		10		S
8A	TB5-9,10	J6U	42	8	8	YES		3		S
8B	TB5-11,12	J6L	46	18	8	YES		10		S
PED PUSH BUTTONS										
P41,P42	TB8-5,6	I12L	69	PED 4	4 PED					

NOTE:
 INSTALL DC ISOLATOR IN INPUT FILE SLOT 112.

INPUT FILE POSITION LEGEND: J2L



COUNTDOWN PEDESTRIAN SIGNAL OPERATION


Countdown Ped Signals are required to display timing only during Ped Clearance Interval. Consult Ped Signal Module user's manual for instructions on selecting this feature.

THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 07-0016
 DESIGNED: NOVEMBER 2017
 SEALED: 06-13-2018
 REVISED: N/A

Electrical Detail

ELECTRICAL AND PROGRAMMING DETAILS FOR:

Prepared for the Offices of:



NC 87-100 (E. Webb Avenue) at NC 100 (Anthony Street)	
Division 7 Alamance County	Burlington
PLAN DATE: November 2017	REVIEWED BY: AJ Davis
PREPARED BY: RD Lawton	REVIEWED BY: LM Moon
REVISIONS	INIT. DATE


DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED



DocuSigned by: Lisa M. Moon 6/13/2018
 DATE: 6/13/2018
 SIG. INVENTORY NO. 07-0016

EDI MODEL 2018EClip-NC CONFLICT MONITOR PROGRAMMING DETAIL

(remove jumpers and set switches as shown)



NOTES

- To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
- Program controller to start up in phase 2 Green and 6 Green.
- The cabinet and controller are part of the Burlington-Graham Signal System.

SIGNAL HEAD HOOK-UP CHART

LOAD SWITCH NO.	S1	S2	S3	S4	S5	S6	S7	S8	S9	S10	S11	S12	AUX S1	AUX S2	AUX S3	AUX S4	AUX S5	AUX S6
CNU CHANNEL NO.	1	2	13	3	4	14	5	6	15	7	8	16	9	10	17	11	12	18
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED	OLA	OLB	SPARE	SPARE	SPARE	SPARE
SIGNAL HEAD NO.	NU	21,22	NU	31,32	41,42, 43	NU	NU	61,62	NU	NU	NU	NU	23,24	63,64	NU	NU	NU	NU
RED		128		116	101			134					A121	A124				
YELLOW		129		117	102			135					A122	A125				
GREEN		130		118	103			136					A123	A126				
RED ARROW																		
YELLOW ARROW																		
GREEN ARROW																		


NU = Not Used

EQUIPMENT INFORMATION

CONTROLLER.....2070LX
 CABINET.....332 W/AUX
 SOFTWARE.....ECONOLITE ASC/3-2070
 CABINET MOUNT.....BASE
 OUTPUT FILE POSITIONS...18 WITH AUX. OUTPUT FILE
 LOAD SWITCHES USED.....S2,S4,S5,S8,AUXS1,AUXS2
 PHASES USED.....2,3,4,6
 OVERLAP "A".....2+4 TOL
 OVERLAP "B".....3+6 TOL
 OVERLAP "C".....NOT USED
 OVERLAP "D".....NOT USED

INPUT FILE POSITION LAYOUT


(front view)



INPUT FILE CONNECTION & PROGRAMMING CHART

LOOP NO.	LOOP TERMINAL	INPUT FILE POS.	PIN NO.	DETECTOR NO.	NEMA PHASE	CALL	EXTEND TIME	DELAY TIME	ADDED INITIAL	DETECTOR TYPE
3A	TB4-5,6	15U	58	3	3	YES				S
4A	TB4-9,10	16U	41	4	4	YES		10		S

INPUT FILE POSITION LEGEND: J2L



THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 07-0017
 DESIGNED: DECEMBER 2017
 SEALED: 06-13-2018
 REVISED: N/A

Electrical Detail - Sheet 1 of 2

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

Prepared for the Offices of:

DRMP, Inc.
 8000 Regency Parkway, Suite 175
 Cary, NC 27518
 NC License No. C-2215 (019) 650-1038

NC 87 (E. Webb Avenue) at Whitsett Street/Sidney Avenue

Division 7 Alamance County Burlington

PLAN DATE: December 2017 REVIEWED BY: AJ Davis

PREPARED BY: J Le REVIEWED BY: LM Moon

REVISIONS	INIT.	DATE

SEAL

DocuSigned by: Lisa M. Moon 6/13/2018

SIG. INVENTORY NO. 07-0017

ECONOLITE ASC/3-2070 OVERLAP PROGRAMMING DETAIL

(program controller as shown)

1. From Main Menu select 2. CONTROLLER
2. From CONTROLLER Submenu select 2. VEHICLE OVERLAPS

OVERLAP A

Select TMG VEH OVLP [A] and 'OTHER/ECONOLITE'

```

TMG VEH OVLP...[A] TYPE: OTHER/ECONLITE

  PHASES 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6
INCLUDED . X . X . . . . .
PROTECT . . . . .
PED PRTC . . . . .
NOT OVLP . . . . .
FLSH GRN . . . . .
LAG X PH . X . . . . .
LAG 2 PH . . . . .

LAG GRN 2.0 YEL 3.8 RED 2.1 ADV GRN 0.0
    
```

Toggle Once

OVERLAP B

Select TMG VEH OVLP [B] and 'OTHER/ECONOLITE'

```

TMG VEH OVLP...[B] TYPE: OTHER/ECONLITE

  PHASES 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6
INCLUDED . . X . . X . . . . .
PROTECT . . . . .
PED PRTC . . . . .
NOT OVLP . . . . .
FLSH GRN . . . . .
LAG X PH . . X . . X . . . . .
LAG 2 PH . . . . .

LAG GRN 5.0 YEL 3.8 RED 1.4 ADV GRN 0.0
    
```

END PROGRAMMING

THIS ELECTRICAL DETAIL IS FOR
 THE SIGNAL DESIGN: 07-0017
 DESIGNED: DECEMBER 2017
 SEALED: 06-13-2018
 REVISED: N/A

Electrical Detail - Sheet 2 of 2

DOCUMENT NOT CONSIDERED
 FINAL UNLESS ALL
 SIGNATURES COMPLETED

<p style="font-size: x-small;">ELECTRICAL AND PROGRAMMING DETAILS FOR:</p> <p style="font-size: x-small;">Prepared for the Offices of:</p>	<p>NC 87 (E. Webb Avenue) at Whitsett Street/Sidney Avenue</p> <p style="font-size: x-small;">Division 7 Alamance County Burlington</p> <p style="font-size: x-small;">PLAN DATE: December 2017 REVIEWED BY: AJ Davis</p> <p style="font-size: x-small;">PREPARED BY: J Le REVIEWED BY: LM Moon</p> <table border="1" style="width: 100%; border-collapse: collapse; font-size: x-small;"> <thead> <tr> <th>REVISIONS</th> <th>INIT.</th> <th>DATE</th> </tr> </thead> <tbody> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> </tbody> </table>	REVISIONS	INIT.	DATE										<p style="font-size: x-small;">SEAL</p> <p style="font-size: x-small;">DocuSigned by: Lisa M. Moon 6/13/2018</p> <p style="font-size: x-small;">SIC#5808300421 DATE</p> <p style="font-size: x-small;">SIG. INVENTORY NO. 07-0017</p>
REVISIONS	INIT.	DATE												

Plans Prepared By:


DRMP

DRMP, Inc.
 8000 Regency Parkway, Suite 175
 Cary, NC 27519
 NC License No. C-2215 (919) 650-1038

750 N. Greenfield Pkwy, Garner, NC 27529

**EDI MODEL 2018ECLip-NC CONFLICT MONITOR
PROGRAMMING DETAIL**

(remove jumpers and set switches as shown)



NOTES

- To prevent "Flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
- Program controller to start up in phase 2 Green.
- The cabinet and controller are part of the Burlington-Graham Signal System.

EQUIPMENT INFORMATION

CONTROLLER.....2070LX
 CABINET.....336
 SOFTWARE.....ECONOLITE ASC/3-2070
 CABINET MOUNT.....BASE
 OUTPUT FILE POSITIONS...12
 LOAD SWITCHES USED.....S2,S5
 PHASES USED.....2,4
 OVERLAPS.....NONE


SIGNAL HEAD HOOK-UP CHART

LOAD SWITCH NO.	S1	S2	S3	S4	S5	S6	S7	S8	S9	S10	S11	S12
CMU CHANNEL NO.	1	2	13	3	4	14	5	6	15	7	8	16
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED
SIGNAL HEAD NO.	NU	21,22	NU	NU	41,42, 43,44	NU	NU	NU	NU	NU	NU	NU
RED		128			101							
YELLOW		129			102							
GREEN		130			103							
RED ARROW												
YELLOW ARROW												
GREEN ARROW												

NU = Not Used

INPUT FILE POSITION LAYOUT

(front view)



THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 07-0018
 PREPARED: October 2017
 SEALED: 5/16/2018
 REVISED: N/A

Prepared in the Office of:

NC FIRM LICENSE No: P-0339
 504 Meadowlands Drive
 Hillsborough, NC 27278
 (919) 732-3883
 (919) 732-6676 (FAX)

Electrical Detail

Prepared For:

750 N. Greenfield Pkwy, Garner, NC 27529

US 70/NC 62 (Church Street)
 At
 Front Street

Division 7 Alamance County Burlington

PLAN DATE: October 2017 REVIEWED BY: E. W. Sirgany

PREPARED BY: J. Smith RKA PROJ. NO:


REVISIONS INIT. DATE

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

DocuSigned by:
 Edward W. Sirgany 5/16/2018
 DATE
 SIG. INVENTORY NO. 07-0018

EDI MODEL 2018ECLip-NC CONFLICT MONITOR PROGRAMMING DETAIL

(remove jumpers and set switches as shown)



NOTES:

1. Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
2. Ensure jumpers SEL2-SEL5 and SEL9 are present on the monitor board.
3. Ensure that Red Enable is active at all times during normal operation.
4. Integrate monitor with Ethernet network in cabinet.

NOTES

1. To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
2. Program phases 4 and 8 for Dual Entry.
3. Program controller to start up in phase 2 Green and 6 Green.
4. The cabinet and controller are part of the Burlington-Graham Signal System.

SIGNAL HEAD HOOK-UP CHART

LOAD SWITCH NO.	S1	S2	S3	S4	S5	S6	S7	S8	S9	S10	S11	S12
CMU CHANNEL NO.	1	2	13	3	4	14	5	6	15	7	8	16
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED
SIGNAL HEAD NO.	NU	21,22	NU	NU	41,42	NU	NU	61,62	NU	NU	81,82,83	NU
RED		128			101			134			107	
YELLOW		129			102			135			108	
GREEN		130			103			136			109	
RED ARROW												
YELLOW ARROW												
GREEN ARROW												


NU = Not Used

EQUIPMENT INFORMATION

CONTROLLER.....2070LX
 CABINET.....336
 SOFTWARE.....ECONOLITE ASC/3-2070
 CABINET MOUNT.....POLE
 OUTPUT FILE POSITIONS...12
 LOAD SWITCHES USED.....S2,S5,S8,S11
 PHASES USED.....2,4,6,8
 OVERLAPS.....NONE

INPUT FILE POSITION LAYOUT

(front view)



EX.: 1A, 2A, ETC. = LOOP NO.'S

FS = FLASH SENSE
 ST = STOP TIME

INPUT FILE CONNECTION & PROGRAMMING CHART

LOOP NO.	LOOP TERMINAL	INPUT FILE POS.	PIN NO.	DETECTOR NO.	NEMA PHASE	CALL	EXTEND TIME	DELAY TIME	ADDED INITIAL	DETECTOR TYPE
2A	TB21-3,4	I2U	39	2	2	YES				S
4A	TB21-7,8	I4U	41	4	4	YES		5		S
6A	TB21-11,12	I6U	40	6	6	YES				S
8A	TB22-1,2	I8U	42	8	8	YES		5		S
8B	TB24-1,2	I8L	46	18	8	YES		15		S

THIS ELECTRICAL DETAIL IS FOR
 THE SIGNAL DESIGN: 07-0020
 DESIGNED: DECEMBER 2017
 SEALED: 06-13-2018
 REVISED: N/A

Electrical Detail

DOCUMENT NOT CONSIDERED FINAL
 UNLESS ALL SIGNATURES COMPLETED

Prepared for the Offices of:

Plans Prepared By:

 DRMP, Inc.
 8000 Regency Parkway, Suite 175
 Cary, NC 27519
 NC License No. C-2213 (919) 650-1038

NC 62 (Rauhut Street)
 at
 SR 1700 (Apple Street) /
 Apple Street
 Division 7 Alamance County Burlington
 PLAN DATE: December 2017 REVIEWED BY: AJ Davis
 PREPARED BY: DJ White REVIEWED BY: LM Moon

SEAL

 DocuSigned by:
 Lisa M. Moon 6/13/2018
 DATE: _____
 SIG. INVENTORY NO. 07-0020

13-UNA-2018-17-15
 R:\66015\17\off\esignals\design\wiring\07-0020e.dgn
 7/1/2018 10:41:17 AM AT CAR-RLAWTON-W7

PHASING DIAGRAM




TABLE OF OPERATION


SIGNAL FACE	PHASE		
	02	04+8	FLASH
21, 22, 23	G	R	Y
41, 42	R	G	R
81, 82	R	G	R

PHASING DIAGRAM DETECTION LEGEND

- ← DETECTED MOVEMENT
- ◐ ← UNDETECTED MOVEMENT (OVERLAP)
- ← UNSIGNALIZED MOVEMENT
- ← → PEDESTRIAN MOVEMENT

SIGNAL FACE I.D.

All Heads L.E.D.




21, 22, 23
41, 42
81, 82

**2 Phase
Pretimed
(Burlington-Graham Signal System)**

NOTES

- Refer to "Roadway Standard Drawings NCDOT" dated January 2018 and "Standard Specifications for Roads and Structures" dated January 2018.
- Do not program signal for late night flashing operation unless otherwise directed by the Engineer.
- Reposition existing heads 21 and 22.
- Locate new cabinet so as not to obstruct sight distance of vehicles turning right on red.
- The cabinet should be designed to include an Auxiliary Output file for future use.
- Pavement markings are existing, except as shown. Remove existing markings as necessary for new stopbar.
- Maximum times shown in timing chart are for free-run operation only. Coordinated signal system timing values supersede these values.




ASC/3 TIMING CHART

FEATURE	PHASE		
	2	4	8
Min Green *	10	7	7
Walk *	0	0	0
Ped Clear	0	0	0
Veh. Extension *	0.0	0.0	0.0
Max 1 *	51	17	17
Yellow	4.1	3.8	3.9
Red Clear	1.3	1.6	1.2
Actuations B4 Add *	-	-	-
Seconds /Actuation *	-	-	-
Max Initial *	-	-	-
Time Before Reduction *	-	-	-
Time To Reduce *	-	-	-
Minimum Gap	-	-	-
Locking Detector	-	-	-
Recall Position	MAX	RECALL	MAX
Dual Entry	-	-	-
Simultaneous Gap	X	X	X

* These values may be field adjusted. Do not adjust Min Green and Extension times for phase 2 lower than what is shown. Min Green for all other phases should not be lower than 4 seconds.

Stopbar Placement Inset



LEGEND

PROPOSED	EXISTING
○ → Traffic Signal Head	● → Traffic Signal Head
◐ → Modified Signal Head	N/A
— Sign	— Sign
⊥ Pedestrian Signal Head With Push Button & Sign	⊥ Pedestrian Signal Head With Push Button & Sign
⊥ Signal Pole with Guy	⊥ Signal Pole with Guy
⊥ Signal Pole with Sidewalk Guy	⊥ Signal Pole with Sidewalk Guy
⊥ Inductive Loop Detector	⊥ Inductive Loop Detector
⊥ Controller & Cabinet	⊥ Controller & Cabinet
⊥ Junction Box	⊥ Junction Box
⊥ 2-in Underground Conduit	⊥ 2-in Underground Conduit
⊥ Terminal Splice Box	⊥ Terminal Splice Box
N/A Right of Way	— Right of Way
→ Directional Arrow	→ Directional Arrow
N/A Fire Hydrant	⊕ Fire Hydrant
N/A Truncated Dome	⊞ Truncated Dome
⊕ "ONE WAY" Sign (R6-1)	⊕ "ONE WAY" Sign (R6-1)
⊕ No Right Turn Sign (R3-1)	⊕ No Right Turn Sign (R3-1)
⊕ No Left Turn Sign (R3-2)	⊕ No Left Turn Sign (R3-2)
⊕ Left Arrow "ONLY" Sign (R3-5L)	⊕ Left Arrow "ONLY" Sign (R3-5L)

Signal Upgrade

Prepared for the Offices of:

US 70-NC 62 (N. Church Street) at NC 62 (W. Holt Street) / W. Holt Street
 Division 7 Alamance County Burlington
 PLAN DATE: November 2017 REVIEWED BY: AJ Davis
 PREPARED BY: J Le REVIEWED BY: LM Moon
 SCALE: 1"=20'
 REVISIONS: INIT. DATE
 SEALS:


 DocuSigned by: Lisa M. Moon 6/13/2018
 SIGNATURE: DATE
 SIG. INVENTORY NO. 07-0021

Plans Prepared By:

 DRMP, Inc.
 8000 Regency Parkway, Suite 175
 Cary, NC 27519
 NC License No. C-2213 (919) 650-1038

EDI MODEL 2018ECLip-NC CONFLICT MONITOR PROGRAMMING DETAIL

(remove jumper and set switches as shown)



NOTES:

- Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
- Ensure jumpers SEL2-SEL5 and SEL9 are present on the monitor board.
- Ensure that Red Enable is active at all times during normal operation.
- Integrate monitor with Ethernet network in cabinet.

NOTES

- To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
- Program controller to start up in phase 2 Green.
- The cabinet and controller are part of the Burlington-Graham Signal System.

EQUIPMENT INFORMATION

CONTROLLER.....2070LX
 CABINET.....332 W/AUX
 SOFTWARE.....ECONOLITE ASC/3-2070
 CABINET MOUNT.....BASE
 OUTPUT FILE POSITIONS...18 WITH AUX.OUTPUT FILE
 LOAD SWITCHES USED.....S2,S5,S11
 PHASES USED.....2,4,8
 OVERLAP "A".....NOT USED
 OVERLAP "B".....NOT USED
 OVERLAP "C".....NOT USED
 OVERLAP "D".....NOT USED


SIGNAL HEAD HOOK-UP CHART

LOAD SWITCH NO.	S1	S2	S3	S4	S5	S6	S7	S8	S9	S10	S11	S12	AUX S1	AUX S2	AUX S3	AUX S4	AUX S5	AUX S6
CMU CHANNEL NO.	1	2	13	3	4	14	5	6	15	7	8	16	9	10	17	11	12	18
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED	OLA	OLB	SPARE	OLC	OLD	SPARE
SIGNAL HEAD NO.	NU	21,22, 23	NU	NU	41,42	NU	NU	NU	NU	NU	81,82	NU	NU	NU	NU	NU	NU	NU
RED		128			101						107							
YELLOW		129			102						108							
GREEN		130			103						109							
RED ARROW																		
YELLOW ARROW																		
GREEN ARROW																		

NU = Not Used

INPUT FILE POSITION LAYOUT

(front view)



EX.: 1A, 2A, ETC. = LOOP NO.'S

FS = FLASH SENSE
 ST = STOP TIME

THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 07-0021
 DESIGNED: NOVEMBER 2017
 SEALED: 06-13-2018
 REVISED: N/A

Electrical Detail

ELECTRICAL AND PROGRAMMING DETAILS FOR:

US 70-NC 62 (N. Church Street)


at
 NC 62 (W. Holt Street) /
 W. Holt Street
 Division 7 Alamance County Burlington

PLAN DATE: November 2017 REVIEWED BY: AJ Davis

PREPARED BY: DJ White REVIEWED BY: LM Moon

REVISIONS	INIT.	DATE

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED




DocuSigned by:
 Lisa M. Moon
 6/13/2018
 DATE
 SIG. INVENTORY NO. 07-0021



750 N. Greenfield Pkwy, Garner, NC 27529


PHASING DIAGRAM



PHASING DIAGRAM DETECTION LEGEND

- ←● DETECTED MOVEMENT
- ← UNDETECTED MOVEMENT (OVERLAP)
- ←--- UNSIGNALIZED MOVEMENT
- ←--- PEDESTRIAN MOVEMENT

RAIL PREEMPT PHASES (High Priority)



SIGNAL FACE	PHASE					
	0 + N	0 S	0 R	0 G	0 Y	0 P
21, 22	G	R	R	G	Y	Y
61, 62	G	R	R	G	Y	Y
81, 82	R	G	G	R	R	R
SIGN A	OFF	OFF	ON	ON	*	*
SIGN B	OFF	OFF	ON	ON	*	*

* SEE NOTE 7

ASC/3 DETECTOR INSTALLATION CHART												
DETECTOR				PROGRAMMING								
LOOP	SIZE (FT)	DISTANCE FROM STOPBAR (FT)	TURNS	NEW LOOP	PHASE	CALLING	EXTEND TIME	DELAY TIME	USE ADDED INITIAL	TYPE	SYSTEM LOOP	NEW CARD
8A	6X40	+5	2-4-2	-	8	Yes	-	3	-	S	-	X
8B	6X40	+5	2-4-2	-	8	Yes	-	15	-	S	-	X

2 Phase w/ RR Preemption Semi-Actuated (Burlington-Graham Signal System)

NOTES

1. Refer to "Roadway Standard Drawings NCDOT" dated January 2018 and "Standard Specifications for Roads and Structures" dated January 2018.
2. This location contains railroad preemption phasing. Do not program signal for late night flashing operation.
3. Set all detector units to presence mode.
4. Locate new cabinet so as not to obstruct sight distance of vehicles turning right on red.
5. The cabinet should be designed to include an Auxiliary Output File for future use.
6. Pavement markings are existing.
7. Ensure flashing operation does not alter operation of blankout signs.
8. Maximum times shown in timing chart are for free-run operation only. Coordinated signal system supersede these values.

ASC/3 RR PREEMPT

FUNCTION	PRE 1
Exit Phase(s)	2, 6
Preempt Override	ON
Delay Time	0
Ped Clear Through Yellow	N
Terminate Phases	N
Track Clear Reserve	Y
Entrance Walk	-
Entrance Ped Clear	-
Entrance Min Green	1
Entrance Yellow Change	25.5*
Entrance Red Clear	25.5*
Track Clear Min Green	18
Track Clear Yellow Change	3.1
Track Clear Red Clear	2.6
Min Dwell Time	10
Exit Yellow Change	25.5*
Exit Red Clear	25.5*

* Allows normal phase times to be used.


SIMULTANEOUS PREEMPT

FEATURE	PHASE		
	2	6	8
Min Green *	10	10	7
Walk *	0	0	0
Ped Clear	0	0	0
Veh. Extension *	0.0	0.0	2.0
Max 1 *	40	40	25
Yellow	3.9	3.9	3.1
Red Clear	1.3	1.2	2.6
Actuations B4 Add *	-	-	-
Seconds / Actuation *	-	-	-
Max Initial *	-	-	-
Time Before Reduction *	-	-	-
Time To Reduce *	-	-	-
Minimum Gap	-	-	-
Locking Detector	-	-	-
Recall Position	MAX RECALL	MAX RECALL	-
Dual Entry	-	-	-
Simultaneous Gap	X	X	X


* These values may be field adjusted. Do not adjust Min Green and Extension times for phases 2 and 6 lower than what is shown. Min Green for all other phases should not be lower than 4 seconds.

SIGNAL FACE I.D.

All Heads L.E.D.



21, 22
61, 62
81, 82



PROPOSED		EXISTING	
○	Traffic Signal Head	●	N/A
○	Modified Signal Head		
○	Sign		
○	Pedestrian Signal Head	■	
○	Signal Pole with Guy	○	
○	Signal Pole with Sidewalk Guy	○	
□	Inductive Loop Detector	□	
□	Controller & Cabinet	□	
□	Junction Box	□	
---	2-in Underground Conduit	---	
N/A	Right of Way		
→	Directional Arrow	→	
N/A	Railroad Cantilever	≡	
N/A	Railroad Gate and Flasher	≡	
N/A	Railroad Tracks	≡	
N/A	Curb Ramp	▲	
Ⓐ	"NO LEFT TURN - TRAIN" LED Blankout Sign	Ⓐ	
Ⓑ	"NO RIGHT TURN - TRAIN" LED Blankout Sign	Ⓑ	
Ⓒ	"DO NOT STOP ON TRACKS" Sign (R8-8)	Ⓒ	
Ⓓ	Left Arrow "ONLY" Sign (R3-5L)	Ⓓ	

Signal Upgrade

Prepared for the Offices of:

 750 N. Greenfield Pkwy, Garner, NC 27529
 SCALE: 0 30
 1"=30'

NC 87-100 (E. Webb Avenue) at Gilmer Street

Division 7 Alamance County Burlington
 PLAN DATE: January 2018 REVIEWED BY: PL Alexander
 PREPARED BY: AM Encarnacion REVIEWED BY:
 REVISIONS INIT. DATE

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED


SEAL
 NORTH CAROLINA PROFESSIONAL ENGINEER
 PAMELA L. ALEXANDER
 023489
 6/7/2018
 SIGNATURE DATE
 SIG. INVENTORY NO. 07-0022

07-JUN-2018 11:11:01 D:\Projects\2018\06\07\Task\00056469 U-6015 B-G S19 SysTask 05_11_Signal\Des\gpm07-0022.dgn ALEX3361 AT LUS310649

EDI MODEL 2018ECLip-NC CONFLICT MONITOR PROGRAMMING DETAIL

(remove jumper and set switches as shown)


REMOVE DIODE JUMPER 2-6.



REMOVE JUMPER AS SHOWN

NOTES:

1. Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
2. Ensure jumpers SEL2-SEL5 and SEL9 are present on the monitor board.
3. Ensure that Red Enable is active at all times during normal operation.
4. Integrate monitor with Ethernet network in cabinet.



NOTES

1. To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
2. Program controller to start up in phase 2 Green and 6 Green.
3. The cabinet and controller are part of the Burlington-Graham Signal System.

EQUIPMENT INFORMATION

CONTROLLER.....2070LX
 CABINET.....332 W/AUX
 SOFTWARE.....ECONDLITE ASC/3-2070
 CABINET MOUNT.....BASE
 OUTPUT FILE POSITIONS...18 WITH AUX. OUTPUT FILE
 LOAD SWITCHES USED.....S2,S8,S11
 PHASES USED.....2,6,8
 OVERLAP "A".....NOT USED
 OVERLAP "B".....NOT USED
 OVERLAP "C".....NOT USED
 OVERLAP "D".....NOT USED

SIGNAL HEAD HOOK-UP CHART

LOAD SWITCH NO.	S1	S2	S3	S4	S5	S6	S7	S8	S9	S10	S11	S12	AUX S1	AUX S2	AUX S3	AUX S4	AUX S5	AUX S6
CMU CHANNEL NO.	1	2	13	3	4	14	5	6	15	7	8	16	9	10	17	11	12	18
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED	OLA	OLB	SPARE	OLC	OLD	SPARE
SIGNAL HEAD NO.	NU	21,22	NU	NU	NU	NU	NU	61,62	NU	NU	81,82	NU	NU	NU	NU	NU	NU	NU
RED		128						134			107							
YELLOW		129						135			108							
GREEN		130						136			109							
RED ARROW																		
YELLOW ARROW																		
FLASHING YELLOW ARROW																		
GREEN ARROW																		

NU = Not Used

INPUT FILE POSITION LAYOUT

(front view)

FILE	1	2	3	4	5	6	7	8	9	10	11	12	13	14
U	←-T-0-0	←-T-0-0	←-T-0-0	←-T-0-0	←-T-0-0	←-T-0-0	←-T-0-0	←-T-0-0	←-T-0-0	←-T-0-0	←-T-0-0	←-T-0-0	←-T-0-0	FS DC ISOLATOR
L	←-T-0-0	←-T-0-0	←-T-0-0	←-T-0-0	←-T-0-0	←-T-0-0	←-T-0-0	←-T-0-0	←-T-0-0	←-T-0-0	←-T-0-0	←-T-0-0	←-T-0-0	ST DC ISOLATOR
U	←-T-0-0	←-T-0-0	←-T-0-0	←-T-0-0	←-T-0-0	∅ B	←-T-0-0	←-T-0-0	←-T-0-0	←-T-0-0	←-T-0-0	←-T-0-0	←-T-0-0	PRE1 AC ISOLATOR
L	←-T-0-0	←-T-0-0	←-T-0-0	←-T-0-0	←-T-0-0	∅ B	←-T-0-0	←-T-0-0	←-T-0-0	←-T-0-0	←-T-0-0	←-T-0-0	←-T-0-0	NOT USED


EX. : 1A, 2A, ETC. = LOOP NO.'S

FS = FLASH SENSE
 ST = STOP TIME
 PRE = PREEMPT

INPUT FILE CONNECTION & PROGRAMMING CHART

LOOP NO.	LOOP TERMINAL	INPUT FILE POS.	PIN NO.	DETECTOR NO.	NEMA PHASE	CALL	EXTEND TIME	DELAY TIME	ADDED INITIAL	DETECTOR TYPE
8A	TB5-9,10	J6U	42	8	8	YES		3		S
8B	TB5-11,12	J6L	46	18	8	YES		15		S

INPUT FILE POSITION LEGEND: J2L



THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 07-0022
 DESIGNED: January 2018
 SEALED: 6/7/2018
 REVISED: N/A

09-JUN-2018 13:38 ***DOTKINS.COM***C:\projects\181\A\Transportation\Traffic\Currr#100056469 U-6015 B-G Sig Sys*Task 05_11_15\Signal\406as\gn\WIF\Prog07-0022E.dgn ALEX3361 AT LUS510649

Electrical Detail - Sheet 1 of 2

ELECTRICAL AND PROGRAMMING DETAILS FOR:

Prepared for the Offices of:

750 N. Greenfield Pkwy, Garner, NC 27529

NC 87-100 (E. Webb Avenue)
 at
 Gilmer Street

Division 7 Alamance County Burlington

PLAN DATE: January 2018 REVIEWED BY: PL Alexander

PREPARED BY: AM Encarnacion REVIEWED BY: MB Toth

REVISIONS	INIT.	DATE

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

Seal of Melissa B. Toth, Engineer, License No. 025892

6/11/2018

SIG. INVENTORY NO. 07-0022

ECONOLITE ASC/3-2070 RAILROAD PREEMPT PROGRAMMING DETAIL

(program controller as shown)

- From Main Menu select 4. PREEMPTOR/TSP
- From PREEMPTOR/TSP/SCP Submenu select 1. PREEMPT PLAN 1-10


Place cursor in [] next to Preempt Plan and press 1. Then press the right cursor arrow and toggle the controller to YES. Next cursor down. This will select Railroad Preempt #1.

PREEMPT PLAN [1]	ENABLE....YES
VEH/PED 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6	
OVERLAP A B C D E F G H I J K L M N O P	
TRKCLR V X	
TRKCLR O	
ENA TRL	
DWEL VEH . X X	
DWEL PED	
DWEL OLP	
CYC VEH	
CYC PED	
CYC OLP	
EXIT PH . X X	
EXIT CAL	
SP FUNC	

ENABLE... YES	IPMT	OVRIDE.XI	INTERLOCK. NO
DET LOCK... X	IDELAY..	OINHIBIT... 0	
OVERIDE FL. .	IDURATION	OICLR=GRN... NO	
TERM OLP. NO	IPC>YEL	NOITERM PH NO	
PED DARK.. NO	ITC RESRV	YESIDWELL FL OFF	
LINK PMT....O	IX FLCOLR	REDIEXIT OPT. OFF	
X TMG PLN...O	IRE-SERV..	OIFLT TYPE.HARD	
FREE DUR PMT	IR1 NOIR2	NOIR3 NOIR4 NO	
--TIMING----	WALKIPED	CLIMN GRI YELI RED	
ENTRANCE TM. 255	1 2551	1125.5125.5	
-----MIN	GRIEXT GRIMX	GRI YELI RED	
TRACK CLEAR 181	01 01	3.11 2.6	
-----MIN	DLIPMTEXTIMX	TMI YELI RED	
DWL/CYC-EXIT 101	0.01	0125.5125.5	
PMT ACTIVE OUT..ON	PMT ACT	DWELL...NO	
OTHER - PRI	PMT.OFF	NON-PRI	PMT.....OFF
INH EXT TIME... 0.0	PED PR	RETURN...OFF	
PRIORITY RETURN.OFF	QUEUE	DELAY.... OFF	
COND DELAY.....OFF			
PHASES 1 2 3 4 5 6 7 8			
PR RTN% 0 0 0 0 0 0 0 0			
PHASES 9 10 11 12 13 14 15 16			
PR RTN% 0 0 0 0 0 0 0 0			

RAILROAD PREEMPTION WIRING DETAIL


(wire as shown below)



NOTES

- Relay K1 is shown in the energized (Preempt not active) normal operation state.
- Relay K1 is a DPDT with 120VAC coil with octal base.
- Relay SSR1 is a SPST (normally open) Solid State Relay with AC input and AC (25 amp) output.
- AC Isolator Card shall activate preemption upon removal of AC+ from the input (as shown above). To accomplish this set invert dip switch on AC Isolator Card.
- IMPORTANT!! Terminal TB22-4 (on input panel) shall be connected to AC- (jumper may have to be added).

FRONT VIEW




THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 07-0022
 DESIGNED: January 2018
 SEALED: 6/7/2018
 REVISED: N/A

ATKINS 1616 EAST MILLBROOK ROAD, SUITE 160
 RALEIGH, NORTH CAROLINA 27609
 (919) 876-6888 NCBEES #F-0326

Electrical Detail - Sheet 2 of 2

	ELECTRICAL AND PROGRAMMING DETAILS FOR: Prepared for the Offices of: NC 87-100 (E. Webb Avenue) at Gilmer Street	SEAL NORTH CAROLINA PROFESSIONAL ENGINEER SEAL 025892 MELISSA B. TOTH
	Division 7 Alamance County Burlington PLAN DATE: January 2018 REVIEWED BY: PL Alexander PREPARED BY: AM Encarnacion REVIEWED BY: MB Toth	
REVISIONS INIT. DATE	DEVELOPED BY: Melissa B. Toth 6/11/2018 CHECKED BY: DATE SIG. INVENTORY NO. 07-0022	

PHASING DIAGRAM



PHASING DIAGRAM DETECTION LEGEND


- ◄●► DETECTED MOVEMENT
- ◄◄◄ UNDETECTED MOVEMENT (OVERLAP)
- ◄◄◄ UNSIGNALIZED MOVEMENT
- ◄◄◄ PEDESTRIAN MOVEMENT

TABLE OF OPERATION

SIGNAL FACE	PHASE		
	02+6	04+8	FLASH
21,22	G	R	Y
41,42	R	G	R
61,62	G	R	Y
81,82	R	G	R

SIGNAL FACE I.D.

All Heads L.E.D.



- 21,22
- 41,42
- 61,62
- 81,82


ASC/3 DETECTOR INSTALLATION CHART

LOOP	SIZE (FT)	DISTANCE FROM STOPBAR (FT)	TURNS	NEW LOOP	PROGRAMMING							
					PHASE	CALLING	EXTEND TIME	DELAY TIME	USE ADDED INITIAL	TYPE	SYSTEM LOOP	NEW CARD
4A	6X60	+5	2-4-2	-	4	Yes	-	5	-	S	-	X
8A	6X60	+5	2-4-2	-	8	Yes	-	5	-	S	-	X

2 Phase Semi-Actuated (Burlington-Graham Signal System)

NOTES

- Refer to "Roadway Standard Drawings NCDOT" dated January 2018 and "Standard Specifications for Roads and Structures" dated January 2018.
- Do not program signal for late night flashing operation unless otherwise directed by the Engineer.
- In the event of loop replacement, refer to the current ITS and Signals Design Manual and submit a Plan of Record to the Signal Design Section.
- Locate new cabinet so as not to obstruct sight distance of vehicles turning right on red.
- Pavement markings are existing.
- Set all detector units to presence mode.
- Maximum times shown in timing chart are for free-run operation only. Coordinated signal system timing values supersede these values.



ASC/3 TIMING CHART

FEATURE	PHASE			
	2	4	6	8
Min Green *	10	7	10	7
Walk *	0	0	0	0
Ped Clear	0	0	0	0
Veh. Extension *	0.0	1.0	0.0	1.0
Max 1 *	45	20	45	20
Yellow	3.7	3.7	4.1	3.7
Red Clear	1.4	1.7	1.4	1.7
Actuations B4 Add *	-	-	-	-
Seconds / Actuation *	-	-	-	-
Max Initial *	-	-	-	-
Time Before Reduction *	-	-	-	-
Time To Reduce *	-	-	-	-
Minimum Gap	-	-	-	-
Locking Detector	-	-	-	-
Recall Position	MAX. RECALL	-	MAX. RECALL	-
Dual Entry	-	X	-	X
Simultaneous Gap	X	X	X	X

* These values may be field adjusted. Do not adjust Min Green and Extension times for phases 2 and 6 lower than what is shown. Min Green for all other phases should not be lower than 4 seconds.


LEGEND

- | | | | |
|--|-------------------------------|--|----------|
| | Traffic Signal Head | | EXISTING |
| | Modified Signal Head | | N/A |
| | Pedestrian Signal Head | | N/A |
| | Signal Pole with Guy | | N/A |
| | Signal Pole with Sidewalk Guy | | N/A |
| | Inductive Loop Detector | | N/A |
| | Controller & Cabinet | | N/A |
| | Junction Box | | N/A |
| | 2-in Underground Conduit | | N/A |
| | Right of Way | | N/A |
| | Directional Arrow | | N/A |
| | Curb Ramp | | N/A |

Signal Upgrade

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED


	<p>NC 87-100 (E. Webb Avenue) at Broad Street</p>		
	Division 7 PLAN DATE: October 2017 PREPARED BY: VJ Paul	Alamance County REVIEWED BY: AM Encarnacion REVIEWED BY: MB Toth	



07-JUN-2018 11:11:01 D:\Projects\2018\11\1101\01\Task\00056469_U-6015_B-G_Sig_Sys\Task_05_11_Signal\Des\gpm07-0023.dgn ALEX3361 AT LUS310649

EDI MODEL 2018EClip-NC CONFLICT MONITOR PROGRAMMING DETAIL

(remove jumpers and set switches as shown)



NOTES:

- Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
- Ensure jumpers SEL2-SEL5 and SEL9 are present on the monitor board.
- Ensure that Red Enable is active at all times during normal operation.
- Integrate monitor with Ethernet network in cabinet.

NOTES

- To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
- Program phases 4 and 8 for Dual Entry.
- Program controller to start up in phase 2 Green and 6 Green.
- The cabinet and controller are part of the Burlington-Graham Signal System.

EQUIPMENT INFORMATION

CONTROLLER.....2070LX
 CABINET.....336
 SOFTWARE.....ECONOLITE ASC/3-2070
 CABINET MOUNT.....POLE
 OUTPUT FILE POSITIONS...12
 LOAD SWITCHES USED.....S2,S5,S8,S11
 PHASES USED.....2,4,6,8
 OVERLAPS.....NONE


SIGNAL HEAD HOOK-UP CHART

LOAD SWITCH NO.	S1	S2	S3	S4	S5	S6	S7	S8	S9	S10	S11	S12
CMU CHANNEL NO.	1	2	13	3	4	14	5	6	15	7	8	16
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED
SIGNAL HEAD NO.	NU	21,22	NU	NU	41,42	NU	NU	61,62	NU	NU	81,82	NU
RED		128			101			134			107	
YELLOW		129			102			135			108	
GREEN		130			103			136			109	
RED ARROW												
YELLOW ARROW												
GREEN ARROW												

NU = Not Used

INPUT FILE POSITION LAYOUT


(front view)



INPUT FILE CONNECTION & PROGRAMMING CHART

LOOP NO.	LOOP TERMINAL	INPUT FILE POS.	PIN NO.	DETECTOR NO.	NEMA PHASE	CALL	EXTEND TIME	DELAY TIME	ADDED INITIAL	DETECTOR TYPE
4A	TB21-7,8	14U	41	4	4	YES		5		S
8A	TB22-1,2	18U	42	8	8	YES		5		S

INPUT FILE POSITION LEGEND: J2L



THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 07-0023
 DESIGNED: OCTOBER 2017
 SEALED: 6/7/2018
 REVISED: N/A

Electrical Detail

ELECTRICAL AND PROGRAMMING DETAILS FOR:

Prepared for the Offices of:

750 N. Greenfield Pkwy, Garner, NC 27529

NC 87-100 (E. Webb Avenue) at Broad Street	
Division 7	Alamance County Burlington
PLAN DATE: October 2017	REVIEWED BY: AM Encarnacion
PREPARED BY: VJ Paul	REVIEWED BY: MB Toth
REVISIONS	INIT. DATE

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

SEAL
 NORTH CAROLINA PROFESSIONAL ENGINEER
 MELISSA B. TOTH
 025892


6/11/2018

SIG. INVENTORY NO. 07-0023

1616 EAST MILLBROOK ROAD, SUITE 160
 RALEIGH, NORTH CAROLINA 27609
 (919) 876-6888 NCBEE #F-0326

EDI MODEL 2018ECLip-NC CONFLICT MONITOR PROGRAMMING DETAIL

(remove jumper and set switches as shown)



NOTES:

1. Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
2. Ensure jumpers SEL2-SEL5 and SEL9 are present on the monitor board.
3. Ensure that Red Enable is active at all times during normal operation.
4. Integrate monitor with Ethernet network in cabinet.

NOTES

1. To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
2. Program controller to start up in phase 2 Green.
3. Program phase 6 for Red Flash.
4. The cabinet and controller are part of the Burlington-Graham Signal System.

PROJECT REFERENCE NO. U-6015	SHEET NO. Sig. 22.1
---------------------------------	------------------------

SIGNAL HEAD HOOK-UP CHART

LOAD SWITCH NO.	S1	S2	S3	S4	S5	S6	S7	S8	S9	S10	S11	S12	AUX S1	AUX S2	AUX S3	AUX S4	AUX S5	AUX S6
CMU CHANNEL NO.	1	2	13	3	4	14	5	6	15	7	8	16	9	10	17	11	12	18
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED	OLA	OLB	SPARE	OLC	OLD	SPARE
SIGNAL HEAD NO.	NU	21,22	NU	NU	41,42,43	NU	NU	NU	NU	NU	81,82	NU	NU	NU	NU	NU	NU	NU
RED		128			101							107						
YELLOW		129			102							108						
GREEN		130			103							109						
RED ARROW																		
YELLOW ARROW																		
FLASHING YELLOW ARROW																		
GREEN ARROW																		


NU = Not Used

EQUIPMENT INFORMATION

CONTROLLER.....2070LX
 CABINET.....332 W/AUX
 SOFTWARE.....ECONOLITE ASC/3-2070
 CABINET MOUNT.....BASE
 OUTPUT FILE POSITIONS...18 WITH AUX. OUTPUT FILE
 LOAD SWITCHES USED.....S2,S5,S11
 PHASES USED.....2,4,8
 OVERLAPS.....NONE

INPUT FILE POSITION LAYOUT

(front view)



EX.: 1A, 2A, ETC. = LOOP NO.'S

FS = FLASH SENSE
 ST = STOP TIME

THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 07-0027
 DESIGNED: September 2017
 SEALED: 6/7/2018
 REVISED: N/A

Electrical Detail

ELECTRICAL AND PROGRAMMING DETAILS FOR: Prepared for the Offices of: 	US 70-NC 62 (S. Church Street) at NC 87-100 (W. Webb Avenue) Division 7 Alamance County Burlington PLAN DATE: September 2017 REVIEWED BY: AM Encarnacion PREPARED BY: NA Ptak REVIEWED BY: MB Toth						
1616 EAST MILLBROOK ROAD, SUITE 160 RALEIGH, NORTH CAROLINA 27609 (919) 876-6888 NCBEES #F-0326	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>REVISIONS</th> <th>INIT.</th> <th>DATE</th> </tr> <tr> <td> </td> <td> </td> <td> </td> </tr> </table>	REVISIONS	INIT.	DATE			
REVISIONS	INIT.	DATE					

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

SEAL

SEAL 025892
MELISSA B. TOTH
ENGINEER

6/11/2018

SIG. INVENTORY NO. 07-0027

PHASING DIAGRAM





TABLE OF OPERATION

SIGNAL FACE	PHASE		
	02	04+8	FLASH
21,22	G	R	Y
41,42	R	G	R
81,82	R	G	R

SIGNAL FACE I.D.

All Heads L.E.D.




**2 Phase
Pre-Timed
Burlington-Graham Signal System**

NOTES

1. Refer to "Roadway Standard Drawings NCDOT" dated January 2018 and "Standard Specifications for Roads and Structures" dated January 2018.
2. Do not program signal for late night flashing operation unless otherwise directed by the Engineer.
3. Locate new cabinet so as not to obstruct sight distance of vehicles turning right on red.
4. Pavement markings are existing.
5. Maximum times shown in timing chart are for free-run operation only. Coordinated signal system timing values supersede these values.

PHASING DIAGRAM DETECTION LEGEND

- ←● DETECTED MOVEMENT
- ← UNDETECTED MOVEMENT (OVERLAP)
- ← UN SIGNALIZED MOVEMENT
- ← PEDESTRIAN MOVEMENT



LEGEND

- | PROPOSED | EXISTING |
|------------------------------------|------------------------------------|
| ○ → Traffic Signal Head | ● → N/A |
| ● → Modified Signal Head | — N/A |
| — Sign | — N/A |
| □ Pedestrian Signal Head | — N/A |
| ○ → Signal Pole with Guy | ● → Signal Pole with Sidewalk Guy |
| ○ → Signal Pole with Sidewalk Guy | — Metal Pole with Mastarm |
| — Metal Pole with Mastarm | — Inductive Loop Detector |
| — Inductive Loop Detector | — Controller & Cabinet |
| — Controller & Cabinet | — Junction Box |
| — Junction Box | — 2-in Underground Conduit |
| — 2-in Underground Conduit | — Right of Way |
| — Right of Way | — Directional Arrow |
| — Directional Arrow | — N/A |
| — N/A | — Curb Ramp |
| — Curb Ramp | Ⓐ → Left Arrow "ONLY" Sign (R3-5L) |
| Ⓐ → Left Arrow "ONLY" Sign (R3-5L) | Ⓑ → "No Right Turn" Sign (R3-1) |
| Ⓑ → "No Right Turn" Sign (R3-1) | Ⓒ → "No Left Turn" Sign (R3-2) |
| Ⓒ → "No Left Turn" Sign (R3-2) | Ⓓ → "ONE WAY" Sign (R6-1) |
| Ⓓ → "ONE WAY" Sign (R6-1) | Ⓔ → Street Name Sign |

ASC/3 TIMING CHART

FEATURE	PHASE		
	2	4	8
Min Green *	10	7	7
Walk *	0	0	0
Ped Clear	0	0	0
Veh. Extension *	0.0	0.0	0.0
Max 1 *	35	35	35
Yellow	3.7	3.0	3.0
Red Clear	1.4	2.3	2.1
Actuations B4 Add *	-	-	-
Seconds / Actuation *	-	-	-
Max Initial *	-	-	-
Time Before Reduction *	-	-	-
Time To Reduce *	-	-	-
Minimum Gap	-	-	-
Locking Detector	-	-	-
Recall Position	MAX RECALL	MAX RECALL	MAX RECALL
Dual Entry	-	-	-
Simultaneous Gap	X	X	X

* These values may be field adjusted. Do not adjust Min Green and Extension times for phase 2 lower than what is shown. Min Green for all other phases should not be lower than 4 seconds.

Signal Upgrade


DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

	US 70-NC 62 (S. Church Street) at Morehead Street		
	Division 7 Alamance County Burlington		
	PLAN DATE: October 2017	REVIEWED BY: MB Toth	
	PREPARED BY: AM Encarnacion	REVIEWED BY:	
SCALE: 0 20 1"=20'		REVISIONS: _____ INIT. DATE _____	

07-JUN-2018 11:11:01
 D:\Projects\2018\06\07\Task\00056469_U-6015_B-G_Sig_Sys\Task_05_11_Sig\Des\gsm07-0029.dgn
 ALEX3361 AT LUS3361

EDI MODEL 2018ECLip-NC CONFLICT MONITOR PROGRAMMING DETAIL

(remove jumper and set switches as shown)



NOTES:

1. Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
2. Ensure jumpers SEL2-SEL5 and SEL9 are present on the monitor board.
3. Ensure that Red Enable is active at all times during normal operation.
4. Integrate monitor with Ethernet network in cabinet.

NOTES

1. To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
2. Program controller to start up in phase 2 Green.
3. The cabinet and controller are part of the Burlington-Graham Signal System.

PROJECT REFERENCE NO.	SHEET NO.
U-6015	Sig. 24.1

SIGNAL HEAD HOOK-UP CHART

LOAD SWITCH NO.	S1	S2	S3	S4	S5	S6	S7	S8	S9	S10	S11	S12
CMU CHANNEL NO.	1	2	13	3	4	14	5	6	15	7	8	16
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED
SIGNAL HEAD NO.	NU	21,22	NU	NU	41,42	NU	NU	NU	NU	NU	81,82	NU
RED		128			101						107	
YELLOW		129			102						108	
GREEN		130			103						109	
RED ARROW												
YELLOW ARROW												
GREEN ARROW												


NU = Not Used

EQUIPMENT INFORMATION

CONTROLLER.....2070LX
 CABINET.....336
 SOFTWARE.....ECONOLITE ASC/3-2070
 CABINET MOUNT.....BASE
 OUTPUT FILE POSITIONS...12
 LOAD SWITCHES USED.....S2,S5,S11
 PHASES USED.....2,4,8
 OVERLAPS.....NONE

INPUT FILE POSITION LAYOUT

(front view)




EX. : 1A, 2A, ETC. = LOOP NO.'S

FS = FLASH SENSE
 ST = STOP TIME

THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 07-0029
 DESIGNED: October 2017
 SEALED: 6/7/2018
 REVISED: N/A

Electrical Detail

ELECTRICAL AND PROGRAMMING DETAILS FOR:



US 70-NC 62 (S. Church Street) at Morehead Street


Division 7 Alamance County Burlington

PLAN DATE: October 2017 REVIEWED BY: MB Toth

PREPARED BY: AM Encarnacion REVIEWED BY:

REVISIONS INIT. DATE

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED





Developed by: Melissa B. Toth DATE: 6/11/2018

SIG. INVENTORY NO. 07-0029

ATKINS 1616 EAST MILLBROOK ROAD, SUITE 160
 RALEIGH, NORTH CAROLINA 27609
 (919) 876-6888 NCBEEES #F-0326

750 N. Greenfield Pkwy, Garner, NC 27529


PHASING DIAGRAM



SIGNAL FACE	PHASE		
	Ø2	Ø4	FLASH
21,22	G	R	Y
41,42,43,44	R	G	R

SIGNAL FACE I.D.

All Heads L.E.D.




**2 Phase
Pre-Timed
(Burlington-Graham Signal System)**

NOTES

1. Refer to "Roadway Standard Drawings NCDOT" dated January 2018 and "Standard Specifications for Roads and Structures" dated January 2018.
2. Do not program signal for late night flashing operation unless otherwise directed by the Engineer.
3. Locate new cabinet so as not to obstruct sign distance of vehicles turning right on red.
4. Pavement markings are existing.
5. Maximum times shown in timing chart are for free-run operation only. Coordinated signal system timing values supersede these values.

FEATURE	PHASE	
	2	4
Min Green *	10	7
Walk *	-	-
Ped Clear	-	-
Veh. Extension *	0.0	0.0
Max I *	38	30
Yellow	3.7	3.0
Red Clear	1.5	2.3
Actuations B4 Add *	-	-
Seconds /Actuation *	-	-
Max Initial *	-	-
Time Before Reduction *	-	-
Time To Reduce *	-	-
Minimum Gap	-	-
Locking Detector	-	-
Recall Position	MAX RECALL	MAX RECALL
Dual Entry	-	-
Simultaneous Gap	X	X

* These values may be field adjusted. Do not adjust Min Green and Extension times for phase 2 lower than what is shown. Min Green for all other phases should not be lower than 4 seconds.




LEGEND

PROPOSED	EXISTING
	N/A
N/A	

Signal Upgrade


**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

Prepared in the Office of:
SUMMIT
DESIGN AND ENGINEERING SERVICES
NC FIRM LICENSE No: P-0339
504 Meadowlands Drive
Hillsborough, NC 27278
(919) 732-3883
(919) 732-6676 (FAX)



**US 70/NC 62 (Church Street)
At
Maple Avenue**

Division 7 Alamance County Burlington
PLAN DATE: October 2017 REVIEWED BY: E. W. Sirgany
PREPARED BY: M. Parker REVIEWED BY:




REVISIONS	INIT.	DATE

DocuSigned by:
Edward W Sirgany 5/16/2018
DATE
SIG. INVENTORY NO. 07-0030


EDI MODEL 2018ECLip-NC CONFLICT MONITOR
PROGRAMMING DETAIL

(remove jumpers and set switches as shown)



NOTES:

1. Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
2. Ensure jumpers SEL2-SEL5 and SEL9 are present on the monitor board.
3. Ensure that Red Enable is active at all times during normal operation.
4. Integrate monitor with Ethernet network in cabinet.



NOTES

1. To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
2. Program controller to start up in phase 2 Green.
3. The cabinet and controller are part of the Burlington-Graham Signal System.

EQUIPMENT INFORMATION

CONTROLLER.....2070LX
 CABINET.....336
 SOFTWARE.....ECONOLITE ASC/3-2070
 CABINET MOUNT.....BASE
 OUTPUT FILE POSITIONS...12
 LOAD SWITCHES USED.....S2,S5
 PHASES USED.....2,4
 OVERLAPS.....NONE


SIGNAL HEAD HOOK-UP CHART

LOAD SWITCH NO.	S1	S2	S3	S4	S5	S6	S7	S8	S9	S10	S11	S12
CMU CHANNEL NO.	1	2	13	3	4	14	5	6	15	7	8	16
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED
SIGNAL HEAD NO.	NU	21,22	NU	NU	41,42, 43,44	NU	NU	NU	NU	NU	NU	NU
RED		128			101							
YELLOW		129			102							
GREEN		130			103							
RED ARROW												
YELLOW ARROW												
GREEN ARROW												

NU = Not Used

INPUT FILE POSITION LAYOUT

(front view)



THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 07-0030
 PREPARED: October 2017
 SEALED: 5/16/2018
 REVISED: N/A

Electrical Detail

Prepared in the Office of:



NC FIRM LICENSE No: P-0339
 504 Meadowlands Drive
 Hillsborough, NC 27278
 (919) 732-3883
 (919) 732-6676 (FAX)



US 70/NC 62 (Church Street)
 At
 Maple Avenue

Division 7 Alamance County Burlington
 PLAN DATE: October 2017 REVIEWED BY: E. W. Sirgany
 PREPARED BY: J. Smith RKA PROJ. NO:

REVISIONS	INIT.	DATE


DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

SEAL

DocuSigned by:
 Edward W Sirgany 5/16/2018
 DATE

SIG. INVENTORY NO. 07-0030

PHASING DIAGRAM




PHASING DIAGRAM DETECTION LEGEND

- ← ● → DETECTED MOVEMENT
- ← ○ → UNDETECTED MOVEMENT (OVERLAP)
- ← - - - → UNSIGNALIZED MOVEMENT
- ← - - - P → PEDESTRIAN MOVEMENT

SIGNAL FACE	PHASE							
	01+5	02+6	03+7	04+8	01+6	02+5	03+8	04+7
11	---	---	---	---	---	---	---	---
21,22,23	R	R	G	G	R	R	R	Y
31,32	R	R	R	R	---	---	---	---
41, 42	R	R	R	R	R	G	G	R
51	---	---	---	---	---	---	---	---
61,62,63	R	G	R	G	R	R	R	Y
71	R	R	R	R	---	---	---	---
81,82	R	R	R	R	G	R	G	R
P21, P22	DW	DW	W	W	DW	DW	DW	DRK
P41, P42	DW	DW	DW	DW	DW	W	W	DRK
P61, P62	DW	W	DW	W	DW	DW	DW	DRK
P81, P82	DW	DW	DW	DW	W	DW	W	DRK

SIGNAL FACE I.D.

All Heads L.E.D.




ASC/3 DETECTOR INSTALLATION CHART												
DETECTOR				PROGRAMMING								
LOOP	SIZE (FT)	DISTANCE FROM STOPBAR (FT)	TURNS	NEW LOOP	PHASE	CALLING	EXTEND TIME	DELAY TIME	USE ADDED INITIAL	TYPE	SYSTEM LOOP	
1A	6X40	0	2-4-2	-	1	Yes	-	-	-	S	-	X
1B	6X40	0	2-4-2	-	1	Yes	-	10	-	S	-	X
1C	6X6	0	3	-	1	Yes	-	25	-	S	-	X
2A	6X6	300	6	-	2	Yes	-	-	X	N	-	X
2B	6X6	300	6	-	2	Yes	-	-	X	N	-	X
2C	6X6	300	6	-	2	Yes	-	-	X	N	-	X
3A	6X40	0	2-4-2	-	3	Yes	-	-	-	S	-	X
3B	6X40	0	2-4-2	-	3	Yes	-	-	-	S	-	X
4A	6X40	+5	2-4-2	-	4	Yes	-	-	-	S	-	X
4B	6X40	+5	2-4-2	-	4	Yes	-	10	-	S	-	X
4C	6X6	0	5	-	4	Yes	-	25	-	S	-	X
5A	6X40	+5	2-4-2	-	5	Yes	-	-	-	S	-	X
6A	6X6	300	6	-	6	Yes	-	-	X	N	-	X
6B	6X6	300	6	-	6	Yes	-	-	X	N	-	X
6C	6X6	300	6	-	6	Yes	-	-	X	N	-	X
7A	6X40	0	2-4-2	-	7	Yes	-	-	-	S	-	X
8A	6X40	0	2-4-2	-	8	Yes	-	-	-	S	-	X
S1	6X6	+200	4	X	-	No	-	-	-	N	X	X
S2	6X6	+200	4	X	-	No	-	-	-	N	X	X
S3	6X6	+200	4	X	-	No	-	-	-	N	X	X
S4	6X6	+200	5	X	-	No	-	-	-	N	X	X
S5	6X6	+200	5	X	-	No	-	-	-	N	X	X
S6	6X6	+200	5	X	-	No	-	-	-	N	X	X

8 Phase Fully Actuated (Burlington-Graham Signal System)

NOTES

1. Refer to "Roadway Standard Drawings NCDOT" dated January 2018 and "Standard Specifications for Roads and Structures" dated January 2018.
2. Do not program signal for late night flashing operation unless otherwise directed by the Engineer.
3. Phase 1 and/or phase 5 may be lagged.
4. Phase 3 and/or phase 7 may be lagged.
5. Set all detector units to presence mode.
6. Locate new cabinet so as not to obstruct sight distance of vehicles turning right on red.
7. Omit "WALK" and flashing "DON'T WALK" with no pedestrian calls.
8. Program pedestrian heads to countdown the flashing "Don't Walk" time only.
9. Pavement markings are existing.
10. Maximum times shown in timing chart are for free-run operation only. Coordinated signal system timing values supersede these values.



ASC/3 TIMING CHART

FEATURE	PHASE							
	1	2	3	4	5	6	7	8
Min Green *	7	12	7	7	7	12	7	7
Walk *	0	7	0	7	0	7	0	7
Ped Clear	0	25	0	28	0	26	0	34
Veh. Extension *	2.0	6.0	2.0	1.0	1.0	6.0	1.0	2.0
Max 1 *	40	90	20	25	40	90	20	25
Yellow	3.0	4.5	3.0	3.8	3.0	4.6	3.0	3.9
Red Clear	3.1	1.9	4.1	2.7	3.1	1.8	3.7	2.8
Actuations B4 Add *	-	0	-	-	-	0	-	-
Seconds / Actuation *	-	2.5	-	-	-	2.5	-	-
Max Initial *	-	34	-	-	-	34	-	-
Time Before Reduction *	-	30	-	-	-	30	-	-
Time To Reduce *	-	30	-	-	-	30	-	-
Minimum Gap	-	3.0	-	-	-	3.0	-	-
Locking Detector	-	X	-	-	-	X	-	-
Recall Position	-	VEH. RECALL	-	-	-	VEH. RECALL	-	-
Dual Entry	-	-	-	-	-	-	-	-
Simultaneous Gap	X	-	X	X	X	X	X	X

* These values may be field adjusted. Do not adjust Min Green and Extension times for phases 2 and 6 lower than what is shown. Min Green for all other phases should not be lower than 4 seconds.

LEGEND

- | PROPOSED | EXISTING |
|--|--|
| ○ → Traffic Signal Head Sign | ● → Traffic Signal Head Sign |
| □ → Pedestrian Signal Head With Push Button & Sign | ■ → Pedestrian Signal Head With Push Button & Sign |
| □ → Metal Strain Pole | □ → Metal Strain Pole |
| ⊗ → Inductive Loop Detector | ⊗ → Inductive Loop Detector |
| ⊠ → Controller & Cabinet Junction Box | ⊠ → Controller & Cabinet Junction Box |
| - - - → 2-in Underground Conduit | - - - → 2-in Underground Conduit |
| N/A → Right of Way | N/A → Right of Way |
| → → Directional Arrow | → → Directional Arrow |
| - - - → Directional Drill | N/A → Directional Drill |
| ⊕ → Type I Pushbutton Post | ⊕ → Type I Pushbutton Post |
| ○ → Type II Signal Pedestal | ● → Type II Signal Pedestal |
| Ⓐ → Street Name Sign (D3-1) | Ⓐ → Street Name Sign (D3-1) |
| ⌒ → Curb Ramp | ⌒ → Curb Ramp |

Mattern & Craig
ENGINEERS • SURVEYORS

12 BROAD STREET
ASHEVILLE, NORTH CAROLINA 28801
(828) 254-2201
FAX (828) 254-4562
NC LIC. NO. C-1154

Signal Upgrade

Prepared for the Offices of:

 750 N. Greenfield Pkwy, Garner, NC 27529
 SCALE: 0 40
 1" = 40'

US 70 (N. Church Street)
at
SR 1716 (Graham-Hopedale Road)
Division 7 Alamance County Burlington
 PLAN DATE: December 2017 REVIEWED BY: JB Voso
 PREPARED BY: SE Greene REVIEWED BY:
 REVISIONS: INIT. DATE

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED


SEAL
 NORTH CAROLINA PROFESSIONAL ENGINEER
 JAMES B. VOSO
 022599
 6/13/2018
 DATE
 SIG. INVENTORY NO. 07-0032

*****SYTIME*****
 *****BUSINESS*****

EDI MODEL 2018ECLIP-NC CONFLICT MONITOR PROGRAMMING DETAIL

(remove jumpers and set switches as shown)

REMOVE DIODE JUMPERS 1-5, 1-6, 1-15, 2-5, 2-6, 2-13, 2-15, 3-7, 3-8, 3-16, 4-7, 4-8, 4-14, 4-16, 5-13, 6-13, 6-15, 7-14, 8-14, 8-16, 13-15, and 14-16.



REMOVE JUMPERS AS SHOWN

NOTES:

- Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
- Ensure jumpers SEL2-SEL5 and SEL9 are present on the monitor board.
- Ensure that Red Enable is active at all times during normal operation.
- Integrate monitor with Ethernet network in cabinet.

NOTES

- To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
- Program controller to start up in phase 2 Walk and 6 Walk.
- The cabinet and controller are part of the Burlington-Graham Signal System.

EQUIPMENT INFORMATION

CONTROLLER.....2070LX
 CABINET.....332 W/AUX
 SOFTWARE.....ECONOLITE ASC/3-2070
 CABINET MOUNT.....BASE
 OUTPUT FILE POSITIONS...18 WITH AUX. OUTPUT FILE
 LOAD SWITCHES USED.....S1.S2.S3.S4.S5.S6.S7.S8.S9.
 S10.S11.S12
 PHASES USED.....1.2.2PED.3.4.4PED.5.6.6PED.7.8.8PED
 OVERLAP "A".....NOT USED
 OVERLAP "B".....NOT USED
 OVERLAP "C".....NOT USED
 OVERLAP "D".....NOT USED

SIGNAL HEAD HOOK-UP CHART

LOAD SWITCH NO.	S1	S2	S3	S4	S5	S6	S7	S8	S9	S10	S11	S12	AUX S1	AUX S2	AUX S3	AUX S4	AUX S5	AUX S6
CMU CHANNEL NO.	1	2	13	3	4	14	5	6	15	7	8	16	9	10	17	11	12	18
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED	OLA	OLB	SPARE	OLC	OLD	SPARE
SIGNAL HEAD NO.	11	21,22, 23	P21, P22	31,32	41,42	P41, P42	51	61,62, 63	P61, P62	71	81,82	P81, P82	NU	NU	NU	NU	NU	NU
RED		128			101			134			107							
YELLOW		129			102			135			108							
GREEN		130			103			136			109							
RED ARROW	125			116			131			122								
YELLOW ARROW	126			117			132			123								
GREEN ARROW	127			118			133			124								
Hand			113			104			119		110							
Walking			115			106			121		112							

NU = Not Used

COUNTDOWN PEDESTRIAN SIGNAL OPERATION

Countdown Ped Signals are required to display timing only during Ped Clearance Interval. Consult Ped Signal Module user's manual for instructions on selecting this feature.

INPUT FILE POSITION LAYOUT

(front view)

FILE "I"	1	2	3	4	5	6	7	8	9	10	11	12	13	14
U	∅ 1	∅ 1	∅ 2	∅ 2	∅ 3	∅ 4	∅ 4	S	SYS. DET. S1	S	S	∅ 2PED	∅ 6PED	FS
L	NOT USED	∅ 1	∅ 2	NOT USED	∅ 3	∅ 4	NOT USED	S	SYS. DET. S2	S	S	∅ 4PED	∅ 8PED	ST
U	∅ 5	∅ 6	∅ 6	S	∅ 7	∅ 8	SYS. DET. S5	S	SYS. DET. S3	S	S	S	S	S
L	NOT USED	∅ 6	NOT USED	S	NOT USED	NOT USED	SYS. DET. S6	S	SYS. DET. S4	S	S	S	S	S

EX.: 1A, 2A, ETC. = LOOP NO.'S

FS = FLASH SENSE
 ST = STOP TIME


INPUT FILE CONNECTION & PROGRAMMING CHART

LOOP NO.	LOOP TERMINAL	INPUT FILE POS.	PIN NO.	DETECTOR NO.	NEMA PHASE	CALL	EXTEND TIME	DELAY TIME	ADDED INITIAL	DETECTOR TYPE
1A	TB2-1,2	I1U	56	1	1	YES				S
1B	TB2-5,6	I2U	39	2	1	YES		10		S
1C	TB2-7,8	I2L	43	12	1	YES		25		S
2A	TB2-9,10	I3U	63	32	2	YES			X	N
2B	TB2-11,12	I3L	76	42	2	YES			X	N
2C	TB4-1,2	I4U	47	22	2	YES			X	N
3A	TB4-5,6	I5U	58	3	3	YES				S
3B	TB4-5,6	I5L	58	3	3	YES				S
4A	TB4-9,10	I6U	41	4	4	YES				S
4B	TB4-11,12	I6L	45	14	4	YES		10		S
4C	TB6-1,2	I7U	65	34	4	YES		25		S
* S1	TB6-9,10	I9U	60	11	SYS	NO				N
* S2	TB6-11,12	I9L	62	13	SYS	NO				N
5A	TB3-1,2	J1U	55	5	5	YES				S
6A	TB3-5,6	J2U	40	6	6	YES			X	N
6B	TB3-7,8	J2L	44	16	6	YES			X	N
6C	TB3-9,10	J3U	64	36	6	YES			X	N
7A	TB5-5,6	J5U	57	7	7	YES				S
8A	TB5-9,10	J6U	42	8	8	YES				S
* S5	TB7-1,2	J7U	66	38	SYS	NO				N
* S6	TB7-3,4	J7L	79	48	SYS	NO				N
* S3	TB7-9,10	J9U	59	15	SYS	NO				N
* S4	TB7-11,12	J9L	61	17	SYS	NO				N
PED PUSH BUTTONS										
P21,P22	TB8-4,6	I12U	67	PED 2	2 PED					
P41,P42	TB8-5,6	I12L	69	PED 4	4 PED					
P61,P62	TB8-7,9	I13U	68	PED 6	6 PED					
P81,P82	TB8-8,9	I13L	70	PED 8	8 PED					

NOTE:
 INSTALL DC ISOLATORS IN INPUT FILE SLOTS 112 AND 113.

* System detector only. Remove any assigned vehicle phase.

INPUT FILE POSITION LEGEND: J2L



THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 07-0032
 DESIGNED: December 2017
 SEALED: 6/13/2018
 REVISED: NA



12 BROAD STREET
 ASHEVILLE, NORTH CAROLINA 28801
 (828) 254-2201
 FAX (828) 254-4562
 NC LIC. NO. C-1154


Electrical Detail

ELECTRICAL AND PROGRAMMING DETAILS FOR: Prepared for the Offices of: 750 N. Greenfield Pkwy, Corner, NC 27529	US 70 (N. Church Street) at SR 1716 (Graham-Hopedale Road)		DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED SEAL JAMES B. VOSO ENGINEER
	Division 7 Alamance County Burlington PLAN DATE: December 2017 REVIEWED BY: JB Voso PREPARED BY: SE Greene REVIEWED BY:	REVISIONS INIT. DATE	

*****SYTIME*****
 *****D*****
 *****USER*****

EDI MODEL 2018ECLip-NC CONFLICT MONITOR
PROGRAMMING DETAIL

(remove jumpers and set switches as shown)



NOTES:

1. Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
2. Ensure jumpers SEL2-SEL5 and SEL9 are present on the monitor board.
3. Ensure that Red Enable is active at all times during normal operation.
4. Integrate monitor with Ethernet network in cabinet.

NOTES

1. To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
2. Program phases 4 and 8 for Dual Entry.
3. Program controller to start up in phase 2 Green and 6 Green.
4. The cabinet and controller are part of the Burlington-Graham Signal System.

EQUIPMENT INFORMATION

CONTROLLER.....2070LX
 CABINET.....332 /W/ AUX
 SOFTWARE.....ECONOLITE ASC/3-2070
 CABINET MOUNT.....BASE
 OUTPUT FILE POSITIONS...18 WITH AUX. OUTPUT FILE
 LOAD SWITCHES USED.....S2,S5,S8,S11
 PHASES USED.....2,4,6,8
 OVERLAP "A".....NOT USED
 OVERLAP "B".....NOT USED
 OVERLAP "C".....NOT USED
 OVERLAP "D".....NOT USED


SIGNAL HEAD HOOK-UP CHART

LOAD SWITCH NO.	S1	S2	S3	S4	S5	S6	S7	S8	S9	S10	S11	S12	AUX S1	AUX S2	AUX S3	AUX S4	AUX S5	AUX S6
CMU CHANNEL NO.	1	2	13	3	4	14	5	6	15	7	8	16	9	10	17	11	12	18
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED	OLA	OLB	SPARE	OLC	OLD	SPARE
SIGNAL HEAD NO.	NU	21,22 23	NU	NU	41,42	NU	NU	61,62 63	NU	NU	81,82	NU	NU	NU	NU	NU	NU	NU
RED		128			101			134			107							
YELLOW		129			102			135			108							
GREEN		130			103			136			109							
RED ARROW																		
YELLOW ARROW																		
GREEN ARROW																		

NU = Not Used

INPUT FILE POSITION LAYOUT

(front view)




EX.: 1A, 2A, ETC. = LOOP NO.'S

FS = FLASH SENSE
 ST = STOP TIME

INPUT FILE CONNECTION & PROGRAMMING CHART

LOOP NO.	LOOP TERMINAL	INPUT FILE POS.	PIN NO.	DETECTOR NO.	NEMA PHASE	CALL	EXTEND TIME	DELAY TIME	ADDED INITIAL	DETECTOR TYPE
2A	TB2-5,6	I2U	39	2	2	YES			X	N
2B	TB2-7,8	I2L	43	12	2	YES			X	N
2C	TB2-9,10	I3U	63	32	2	YES			X	N
4A	TB4-9,10	I6U	41	4	4	YES		5		S
6A	TB3-5,6	J2U	40	6	6	YES			X	N
6B	TB3-7,8	J2L	44	16	6	YES			X	N
6C	TB3-9,10	J3U	64	36	6	YES			X	N
8A	TB5-9,10	J6U	42	8	8	YES		5		S

INPUT FILE POSITION LEGEND: J2L




THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 07-0033
 DESIGNED: December 2017
 SEALED: 6/13/2018
 REVISED: NA

Electrical Detail



12 BROAD STREET
 ASHEVILLE, NORTH CAROLINA 28801
 (828) 254-2201
 FAX (828) 254-4562
 NC LIC. NO. C-1154



US 70 (Church Street)
 at
 Cobb Avenue


Division 7 Alamance County Burlington

PLAN DATE: December 2017 REVIEWED BY: JB Voso

PREPARED BY: SE Greene REVIEWED BY:

REVISIONS	INIT.	DATE

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED



PHASING DIAGRAM




TABLE OF OPERATION

SIGNAL FACE	PHASE		
	Ø 2	Ø 4 + 8	FLASH
21, 22, 23	G	R	Y
41, 42	R	G	R
81, 82	R	G	R


**2 Phase
Pretimed
(Burlington-Graham Signal System)**

PHASING DIAGRAM DETECTION LEGEND

- ←●→ DETECTED MOVEMENT
- ←○→ UNDETECTED MOVEMENT (OVERLAP)
- ←○→ UNSIGNALIZED MOVEMENT
- ←○→ PEDESTRIAN MOVEMENT

SIGNAL FACE I.D.


All Heads L.E.D.



21, 22, 23
41, 42
81, 82

NOTES

1. Refer to "Roadway Standard Drawings NCDOT" dated January 2018 and "Standard Specifications for Roads and Structures" dated January 2018.
2. Do not program signal for late night flashing operation unless otherwise directed by the Engineer.
3. Reposition existing signal head 21.
4. Locate new cabinet so as not to obstruct sight distance of vehicles turning right on red.
5. Pavement markings are existing.
6. Maximum times shown in timing chart are for free-run operation only. Coordinated signal system timing values supersede these values.



FEATURE	PHASE		
	2	4	8
Min Green *	10	7	7
Walk *	0	0	0
Ped Clear	0	0	0
Veh. Extension *	0.0	0.0	0.0
Max 1 *	42	26	26
Yellow	3.9	4.0	4.0
Red Clear	1.2	1.4	1.1
Actuations B4 Add *	-	-	-
Seconds / Actuation *	-	-	-
Max Initial *	-	-	-
Time Before Reduction *	-	-	-
Time To Reduce *	-	-	-
Minimum Gap	-	-	-
Locking Detector	-	-	-
Recall Position	MAX	RECALL	MAX
Dual Entry	-	-	-
Simultaneous Gap	X	X	X

* These values may be field adjusted. Do not adjust Min Green and Extension times for phase 2 lower than what is shown. Min Green for all other phases should not be lower than 4 seconds.

PROPOSED	EXISTING
	N/A
N/A	

Signal Upgrade

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

Plans Prepared By:

DRMP, Inc.
8000 Regency Parkway, Suite 175
Cary, NC 27519
NC License No. C-2213 (919) 650-1038

750 N. Greenfield Pkwy, Garner, NC 27529

US 70-NC 62 (N. Church Street) at W. Trade Street	
Division 7	Alamance County
PLAN DATE: Sept 2017	REVIEWED BY: AJ Davis
PREPARED BY: RD Lawton	REVIEWED BY: LM Moon
REVISIONS	INIT. DATE

SEAL

DocuSigned by:
Lisa M. Moon 6/13/2018


SIGNATURE DATE

SIG. INVENTORY NO. 07-0034

13-JUN-2018 17:00 R:\66015\17\Traffic\Signal\Signal\07-0034.dgn C:\Lawton AT CAR-RLAWTON-WT

EDI MODEL 2018ECLip-NC CONFLICT MONITOR PROGRAMMING DETAIL

(remove jumper and set switches as shown)



NOTES:

1. Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
2. Ensure jumpers SEL2-SEL5 and SEL9 are present on the monitor board.
3. Ensure that Red Enable is active at all times during normal operation.
4. Integrate monitor with Ethernet network in cabinet.

NOTES

1. To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
2. Program controller to start up in phase 2 Green.
3. The cabinet and controller are part of the Burlington-Graham Signal System.

SIGNAL HEAD HOOK-UP CHART

LOAD SWITCH NO.	S1	S2	S3	S4	S5	S6	S7	S8	S9	S10	S11	S12
CMU CHANNEL NO.	1	2	13	3	4	14	5	6	15	7	8	16
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED
SIGNAL HEAD NO.	NU	21,22, 23	NU	NU	41,42	NU	NU	NU	NU	NU	81,82	NU
RED		128			101						107	
YELLOW		129			102						108	
GREEN		130			103						109	
RED ARROW												
YELLOW ARROW												
GREEN ARROW												


NU = Not Used

EQUIPMENT INFORMATION

CONTROLLER.....2070LX
 CABINET.....336
 SOFTWARE.....ECONDLITE ASC/3-2070
 CABINET MOUNT.....POLE
 OUTPUT FILE POSITIONS...12
 LOAD SWITCHES USED.....S2,S5,S11
 PHASES USED.....2,4,8
 OVERLAPS.....NONE

INPUT FILE POSITION LAYOUT

(front view)



THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 07-0034
 DESIGNED: SEPT-2017
 SEALED: 06-13-2018
 REVISED: N/A


Electrical Detail

ELECTRICAL AND PROGRAMMING DETAILS FOR:


US 70-NC 62 (N. Church Street) at W. Trade Street

Division 7 Alamance County Burlington
 PLAN DATE: September 2017 REVIEWED BY: LM Moon
 PREPARED BY: AJ Davis REVIEWED BY:

REVISIONS	INIT.	DATE



DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED



DocuSigned by: Lisa M. Moon 6/13/2018
 DATE: 6/13/2018
 SIG. INVENTORY NO. 07-0034

ECONOLITE ASC/3-2070 VEHICLE DETECTOR SETUP PROGRAMMING DETAIL FOR ALTERNATE PHASING LOOP 1A

(program controller as shown)

IMPORTANT!

Program detectors per the input file connection and programming chart shown on sheet 1 before proceeding.

1. From Main Menu select 8. UTILITIES
2. From UTILITIES Submenu select 1. COPY/CLEAR
3. Copy from DETECTOR PLAN "1" to DETECTOR PLAN "2".

```

COPY / CLEAR UTILITY
FROM          TO
PHASE TIMING... > PHASE TIMING...
TIMING PLAN... > TIMING PLAN...
PH DET OPT PLAN. > PH DET OPT PLAN.
DETECTOR PLAN... 1 > DETECTOR PLAN... 2
TOGGLE TO SELECT A "FROM" AND A "TO"
THEN PRESS ENTER
    
```

4. From Main Menu select 6. DETECTORS
5. From DETECTOR Submenu select 2. VEHICLE DETECTOR SETUP
6. Place cursor in VEH DET PLAN [] position and enter "2".

- Place cursor in VEH DETECTOR [] position and enter "1".
- Set delay time to "0".

```

VEH DETECTOR [ 1]  VEH DET PLAN [ 2]
TYPE: S-STANDARD
TS2 DETECTOR..... ECPI LOG..... NO
DET PH - 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6
1 1 .....
EXTEND TIME... 0.0 DELAY TIME... 0.0
USE ADDED INITIAL . CROSS SWITCH PH.. 0
LOCK IN..... NONE NTCIP VOL . OR OCC .
PMT QUEUE DELAY. NO
    
```

← NOTICE VEH DET PLAN 2

← ENSURE DELAY IS SET TO '0'

- Place cursor in VEH DETECTOR [] position and enter "26".
- Set assigned phase to "0".

```

VEH DETECTOR [26]  VEH DET PLAN [ 2]
TYPE: S-STANDARD
TS2 DETECTOR..... ECPI LOG..... NO
DET PH - 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6
26 0 .....
EXTEND TIME... 0.0 DELAY TIME... 0.0
USE ADDED INITIAL . CROSS SWITCH PH.. 0
LOCK IN..... NONE NTCIP VOL . OR OCC .
PMT QUEUE DELAY. NO
    
```

← NOTICE VEH DET PLAN 2

→ ENSURE PHASE IS SET TO "0"

END PROGRAMMING

ECONOLITE ASC/3-2070 OVERLAP PROGRAMMING DETAIL

(program controller as shown)

1. From Main Menu select 2. CONTROLLER
2. From CONTROLLER Submenu select 2. VEHICLE OVERLAPS

OVERLAP A

Select TMG VEH OVLP [A] and 'PPLT FYA'

```

TMG VEH OVLP...[A] TYPE: .....PPLT FYA
PROTECTED LEFT TURN.... PHASE 1
OPPOSING THROUGH..... PHASE 2

FLASHING ARROW OUTPUT.....CH9 ISOLATE
DELAY START OF: FYA..0.0 CLEARANCE..0.0
ACTION PLAN SF BIT DISABLE..... 1
    
```

← NOTICE ACTION PLAN SF BIT "1"

Toggle Once

OVERLAP B

Select TMG VEH OVLP [B] and 'NORMAL'

```

TMG VEH OVLP...[B] TYPE: .....NORMAL
PHASES 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6
INCLUDED X . . . . . X . . . . .

LAG GRN 0.0 YEL 0.0 RED 0.0
    
```

Toggle Once

OVERLAP C

Select TMG VEH OVLP [C] and 'OTHER/ECONOLITE'

```

TMG VEH OVLP...[C] TYPE: OTHER/ECONOLITE
PHASES 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6
INCLUDED . . . . . X . . . . .
PROTECT . . . . .
PED PRTC . . . . .
NOT OVLP . . . . .
FLSH GRN . . . . . 1 . . . . .
LAG X PH . . . . .
LAG 2 PH . . . . .

LAG GRN 0.0 YEL 0.0 RED 0.0 ADV GRN 0.0
    
```

END PROGRAMMING

THIS ELECTRICAL DETAIL IS FOR
THE SIGNAL DESIGN: 07-0035
DESIGNED: March 2018
SEALED: 6/7/2018
REVISED: N/A

Electrical Detail - Sheet 2 of 3

**DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED**

<p style="font-size: small;">ELECTRICAL AND PROGRAMMING DETAILS FOR:</p> <p style="font-size: x-small;">Prepared for the Offices of:</p> <p style="font-size: x-small;">750 N. Greenfield Pkwy, Garner, NC 27529</p>	<p>US 70/US 70-NC 62 (S. Church Street) at NC 62 (Alamance Road)</p> <p style="font-size: x-small;">Division 7 Alamance County Burlington</p> <p>PLAN DATE: March 2018 REVIEWED BY: PL Alexander</p> <p>PREPARED BY: NA Ptak REVIEWED BY: AM Encarnacion</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="font-size: x-small;">REVISIONS</th> <th style="font-size: x-small;">INIT.</th> <th style="font-size: x-small;">DATE</th> </tr> </thead> <tbody> <tr> <td> </td> <td> </td> <td> </td> </tr> </tbody> </table>	REVISIONS	INIT.	DATE				<p style="font-size: x-small;">SEAL</p> <p style="font-size: x-small;">PAMELA L. ALEXANDER ENGINEER</p> <p style="font-size: x-small;">6/9/2018</p> <p style="font-size: x-small;">DATE</p> <p style="font-size: x-small;">SIG. INVENTORY NO. 07-0035</p>
REVISIONS	INIT.	DATE						

09-JUN-2018 13:14
D:\Transpor\at\off\c\cur\100056469 U-6015 B-G S1g Sys\Task 05_11_Signal\Des\gn\mtr\ing\07-0035E.dgn
ALEX3361 AT LUS210649

ALTERNATE PHASING ACTIVATION DETAIL

TO RUN ALT. PHASING DURING FREE RUN - PROGRAM CHANGES (SHOWN BELOW) IN A TIME BASED ACTION PLAN. SCHEDULE A DAY PLAN THAT INCLUDES THE ACTION PLAN PROGRAMMED TO SELECT VEH DET PLAN 2 AND ENABLE SF BIT 1.

TO RUN ALT. PHASING DURING COORDINATION - SELECT THE TIME BASED ACTION PLAN THAT IS PROGRAMMED TO SELECT VEH DET PLAN 2 AND ENABLE SF BIT 1.

PHASING	VEH DET PLAN	SF BITS ENABLED
ACTIONS REQUIRED TO RUN <u>DEFAULT PHASING</u>	1	NONE
ACTIONS REQUIRED TO RUN <u>ALTERNATE PHASING</u>	2	1

IMPORTANT: IF ALT. PHASING IS USED DURING FREE RUN AND COORDINATION, DO NOT OPERATE TIME OF DAY EVENTS CONCURRENTLY WITH COORDINATION PLAN EVENTS IN THE EVENT SCHEDULER. (EX. FREE RUN EVENT SHOULD END BEFORE COORDINATION PLAN EVENT STARTS AND VICE-VERSA).

ALTERNATE PHASING CHANGE SUMMARY

THE FOLLOWING IS A SUMMARY OF WHAT TAKES PLACE WHEN SF BIT 1 AND VEH DET PLAN 2 ACTIVATE TO CALL THE "ALTERNATE PHASING":

SF BIT 1: Modifies overlap parent phases for head 11 to run protected turns only.

VEH DET PLAN 2: Disables phase 6 call on loop 1A and reduces delay time for phase 1 call on loop 1A to 0 seconds.

ECONOLITE ASC/3-2070 ACTION PLAN PROGRAMMING DETAIL

- From Main Menu select 5. TIME BASE
- From TIME BASE Submenu select 2. ACTION PLAN



```

ACTION PLAN...[ 1]
PATTERN.....AUTO  SYS OVERRIDE.... NO
TIMING PLAN..... 0  SEQUENCE..... 0
VEH DETECTOR PLAN.. 2  DET LOG.....NONE
FLASH..... --  RED REST..... NO
VEH DET DIAG PLN... 0  PED DET DIAG PLN..0
DIMMING ENABLE.. 0  PRIORITY RETURN. NO
PED PR RETURN.. NO  QUEUE DELAY..... NO
PMT COND DELAY  NO
  PHASE  1  2  3  4  5  6  7  8  9  0  1  2  3  4  5  6
PED RCL  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .
WALK 2   .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .
VEX 2    .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .
VEH RCL  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .
MAX RCL  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .
MAX 2    .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .
  PHASE  1  2  3  4  5  6  7  8  9  0  1  2  3  4  5  6
MAX 3    .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .
CS INH   .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .
OMIT     .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .
SPC FCT  X  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .
AUX FCT  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .
          1  2  3  4  5  6  7  8  9  0  1  2  3  4  5
LP 1-15  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .
LP 16-30 .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .
LP 31-45 .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .
LP 46-60 .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .
LP 61-75 .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .
LP 76-90 .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .
LP 91-100 .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .
    
```

THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 07-0035
 DESIGNED: March 2018
 SEALED: 6/7/2018
 REVISED: N/A

Electrical Detail - Sheet 3 of 3


DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

ELECTRICAL AND PROGRAMMING DETAILS FOR: Prepared for the Offices of: 	US 70/US 70-NC 62 (S. Church Street) at NC 62 (Alamance Road) Division 7 Alamance County Burlington PLAN DATE: March 2018 REVIEWED BY: AM Encarnacion PREPARED BY: NA Ptak REVIEWED BY: PL Alexander	SEAL  SEAL 023489 PAMELA L. ALEXANDER ENGINEER
	REVISIONS INIT. DATE	Date signed by: Pamela Alexander 6/9/2018 DATE
		SIG. INVENTORY NO. 07-0035

EDI MODEL 2018EClip-NC CONFLICT MONITOR PROGRAMMING DETAIL

(remove jumpers and set switches as shown)


REMOVE DIODE JUMPERS 1-5, 1-6, 1-9, 1-11, 2-5, 2-6, 2-9, 2-11, 4-8, 5-9, 5-11, 6-9, 6-11 and 9-11.



REMOVE JUMPERS AS SHOWN

NOTES:

- Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
- Ensure jumpers SEL2-SEL5 and SEL9 are present on the monitor board.
- Ensure that Red Enable is active at all times during normal operation.
- Integrate monitor with Ethernet network in cabinet.



NOTES

- To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
- Program phases 4 and 8 for Dual Entry.
- Program controller to start up in phase 2 Green and 6 Green.
- The cabinet and controller are part of the Burlington-Graham Signal System.

EQUIPMENT INFORMATION

CONTROLLER.....2070LX
 CABINET.....332 W/AUX
 SOFTWARE.....ECONOLITE ASC/3-2070
 CABINET MOUNT.....BASE
 OUTPUT FILE POSITIONS...18 WITH AUX. OUTPUT FILE
 LOAD SWITCHES USED.....S1,S2,S5,S7,S8,S11,AUX S1,
 AUX S4
 PHASES USED.....1,2,4,5,6,8
 OVERLAP "A".....*
 OVERLAP "B".....NOT USED
 OVERLAP "C".....*
 OVERLAP "D".....NOT USED
 * See overlap programming detail on sheet 2

SIGNAL HEAD HOOK-UP CHART

LOAD SWITCH NO.	S1	S2	S3	S4	S5	S6	S7	S8	S9	S10	S11	S12	AUX S1	AUX S2	AUX S3	AUX S4	AUX S5	AUX S6	
CNU CHANNEL NO.	1	2	13	3	4	14	5	6	15	7	8	16	9	10	17	11	12	18	
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED	OLA	OLB	SPARE	OLC	OLD	SPARE	
SIGNAL HEAD NO.	11	21,22,23	NU	NU	41,42	NU	51	61,62,63	NU	NU	81,82	NU	11	NU	NU	51	NU	NU	
RED	128			101			134			107									
YELLOW	*	129		102		*	135			108									
GREEN		130		103			136			109									
RED ARROW													A121					A114	
YELLOW ARROW														A122					A115
FLASHING YELLOW ARROW														A123					A116
GREEN ARROW	127						133												


NU = Not Used

* Denotes install load resistor. See load resistor installation detail this sheet.

★ See pictorial of head wiring in detail this sheet.

INPUT FILE POSITION LAYOUT

(front view)




EX.: 1A, 2A, ETC. = LOOP NO.'S
 FS = FLASH SENSE
 ST = STOP TIME
 ⊗ Wired Input - Do not populate slot with detector card

INPUT FILE CONNECTION & PROGRAMMING CHART

LOOP NO.	LOOP TERMINAL	INPUT FILE POS.	PIN NO.	DETECTOR NO.	NEMA PHASE	CALL	EXTEND TIME	DELAY TIME	ADDED INITIAL	DETECTOR TYPE
1A ¹	TB2-1,2	J1U	56	1	1	YES		15		S
		J4U	48	26	6	YES				S
2A,2B,2C	TB2-5,6	J2U	39	2	2	YES	1.6			S
2D,2E,2F	TB2-7,8	J2L	43	12	2	YES				S
4A	TB4-9,10	J6U	41	4	4	YES		3		S
4B	TB4-11,12	J6L	45	14	4	YES		10		S
5A ²	TB3-1,2	J1U	55	5	5	YES		15		S
		J14U	47	22	2	YES				S
6A,6B,6C	TB3-5,6	J2U	40	6	6	YES	1.6			S
6D,6E,6F	TB3-7,8	J2L	44	16	6	YES				S
8A	TB5-9,10	J6U	42	8	8	YES		3		S
8B	TB5-11,12	J6L	46	18	8	YES		10		S


¹Add jumper from I1-W to J4-W, on rear of input file.
²Add jumper from J1-W to I4-W, on rear of input file.

INPUT FILE POSITION LEGEND: J2L



FYA SIGNAL WIRING DETAIL


(wire signal heads as shown)



LOAD RESISTOR INSTALLATION DETAIL

(install resistors as shown)

VALUE (ohms)	WATTAGE
1.5K - 1.9K	25W (min)
2.0K - 3.0K	10W (min)



1:46:14 PM 11/13/18 - Burlington-Graham Signal System06 Working Folders with NCDOT File Structure if Working on NCDOT Project:Wing or DgnW07-0036-070036-sm.eie-20131223.dgn Local User



12 BROAD STREET
 ASHEVILLE, NORTH CAROLINA 28801
 (828) 254-2201
 FAX (828) 254-4562
 NC LIC. NO. C-1154

Electrical Detail - Sheet 1 of 2

ELECTRICAL AND PROGRAMMING DETAILS FOR:
 Prepared for the Offices of:

 750 N. Greenfield Pkwy, Corner, NC 27529

US 70 (N. Church Street)
 at
 Beaumont Avenue

Division 7 Alamance County Burlington

PLAN DATE: December 2017 REVIEWED BY: JB Voso
 PREPARED BY: SE Greene REVIEWED BY:

REVISIONS	INIT.	DATE

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

SEAL

 James Voso
 6/13/2018
 DATE
 SIG. INVENTORY NO. 07-0036

ECONOLITE ASC/3-2070 OVERLAP PROGRAMMING DETAIL

(program controller as shown)

1. From Main Menu select 2. CONTROLLER
2. From CONTROLLER Submenu select 2. VEHICLE OVERLAPS

OVERLAP A

Select TMG VEH OVLP [A] and 'PPLT FYA'

TMG VEH OVLP...[A] TYPE:PPLT FYA

PROTECTED LEFT TURN.... PHASE 1

OPPOSING THROUGH..... PHASE 2

FLASHING ARROW OUTPUT.....CH9 ISOLATE

DELAY START OF: FYA..0.0 CLEARANCE..0.0

ACTION PLAN SF BIT DISABLE..... 0

↓ Toggle Twice

OVERLAP C

Select TMG VEH OVLP [C] and 'PPLT FYA'

TMG VEH OVLP...[C] TYPE:PPLT FYA

PROTECTED LEFT TURN.... PHASE 5

OPPOSING THROUGH..... PHASE 6

FLASHING ARROW OUTPUT.....CH11 ISOLATE


DELAY START OF: FYA..0.0 CLEARANCE..0.0

ACTION PLAN SF BIT DISABLE..... 0

END PROGRAMMING

THIS ELECTRICAL DETAIL IS FOR
 THE SIGNAL DESIGN: 07-0036
 DESIGNED: December 2017
 SEALED: 6/13/2018
 REVISED: NA

1:47:00 PM I:\3789 - Burlington Graham Signal System\06 Working Folders\Replace Sub-folders with NCDOT File Structure if Working on NCDOT Project\HWg or Dgn\07-0036\070036.sm.ele_20131223.dgn Local User



Mattern & Craig
 ENGINEERS & SURVEYORS


12 BROAD STREET
 ASHEVILLE, NORTH CAROLINA 28801
 (828) 254-2201
 FAX (828) 254-4562
 NC LIC. NO. C-1154

Electrical Detail - Sheet 2 of 2



<p><small>ELECTRICAL AND PROGRAMMING DETAILS FOR:</small></p> <p style="text-align: center;">US 70 (N. Church Street) at Beaumont Avenue</p> <p><small>Division 7 Alamance County Burlington</small></p> <p><small>PREPARED BY: SE Greene REVIEWED BY: JB Voso</small></p> <p><small>REVISIONS</small></p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 80%;">REVISIONS</th> <th style="width: 10%;">INIT.</th> <th style="width: 10%;">DATE</th> </tr> </thead> <tbody> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> </tbody> </table> <p><small>750 N. Greenfield Pkwy, Corner, NC 27529</small></p>	REVISIONS	INIT.	DATE										<p style="text-align: center;">SEAL</p> <p style="text-align: center;">NORTH CAROLINA PROFESSIONAL ENGINEER SEAL 022599 JAMES B. VOSO</p> <p style="text-align: center;">James Voso 6/13/2018 DATE</p> <p style="text-align: center;">SIG. INVENTORY NO. 07-0036</p>
REVISIONS	INIT.	DATE											

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED


DEFAULT PHASING DIAGRAM



ALTERNATE PHASING DIAGRAM



SIGNAL FACE I.D.



FEATURE	PHASE			
	2	4	5	6
Min Green *	10	7	7	10
Walk *	-	-	-	-
Ped Clear	-	-	-	-
Veh. Extension *	3.0	1.0	1.0	3.0
Max 1 *	30	20	20	30
Yellow	3.9	3.0	3.0	3.9
Red Clear	2.3	1.9	2.6	2.3
Actuations B4 Add *	-	-	-	-
Seconds / Actuation *	-	-	-	-
Max Initial *	-	-	-	-
Time Before Reduction *	-	-	-	-
Time To Reduce *	-	-	-	-
Minimum Gap	-	-	-	-
Locking Detector	X	-	-	X
Recall Position	VEH. RECALL	-	-	VEH. RECALL
Dual Entry	-	-	-	-
Simultaneous Gap	X	X	X	X

* These values may be field adjusted. Do not adjust Min Green and Extension times for phases 2 and 6 lower than what is shown. Min Green for all other phases should not be lower than 4 seconds.

SIGNAL FACE	PHASE			
	02+5	02+6	04	F L
21, 22	G	G	R	Y
41	R	R	G	R
42	R	R	G	R
51	-	-	-	-
61	R	G	R	Y
62	R	G	R	Y


SIGNAL FACE	PHASE			
	02+5	02+6	04	F L
21, 22	G	G	R	Y
41	R	R	G	R
42	R	R	G	R
51	-	-	-	-
61	R	G	R	Y
62	R	G	R	Y

3 Phase Fully Actuated (Burlington-Graham Signal System)

NOTES


- Refer to "Roadway Standard Drawings NCDOT" dated January 2018 and "Standard Specifications for Roads and Structures" dated January 2018.
- Do not program signal for late night flashing operation unless otherwise directed by the Engineer.
- Phase 5 may be lagged.
- Reposition existing signal head numbered 41.
- Set all detector units to presence mode.
- In the event of loop replacement, refer to the current ITS and Signals Design Manual and submit a Plan of Record to the Signal Design Section.
- Locate new cabinet so as not to obstruct sight distance of vehicles turning right on red.
- Existing lane control signs may be removed at the direction of the Engineer.
- Pavement markings are existing unless otherwise shown.
- The City Traffic Engineer will determine the hours of use for each phasing plan.
- Maximum times shown in timing chart are for free-run operation only. Coordinated signal system timing values supersede these values.
- Proposed cabinet shall accommodate existing school flashers.

LEGEND




LOOP	SIZE (FT)	DISTANCE FROM STOPBAR (FT)	TURNS	NEW LOOP	PHASE	PROGRAMMING						
						CALLING	EXTEND TIME	DELAY TIME	USE ADDED INITIAL	TYPE	SYSTEM LOOP	NEW CARD
2A	6x20	70	EXIST	-	2	Yes	-	-	-	S	-	X
4A	6x60	+5	2-4-2	-	4	Yes	-	3	-	S	-	X
5A	6x60	+5	2-4-2	-	5	Yes	-	15*	-	S	-	X
5B	6x60	+5	2-4-2	-	5	Yes	-	15	-	S	-	X
6A	6x20	70	EXIST	-	6	Yes	-	-	-	S	-	X
S1	6x6	+150	4	X	-	No	-	-	-	N	X	X
S2	6x6	+150	4	X	-	No	-	-	-	N	X	X

* Disable Delay During Alternate Phasing Operation.
Disable Phase Call for Loop during Alternate Phasing Operation.



This plan supersedes the plan signed and sealed on 6/13/2018.

Signal Upgrade



SR 1716 (Graham-Hopedale Road) at Vaughn Road

Division 7 Alamance County Burlington

PLAN DATE: June 2021 REVIEWED BY:

PREPARED BY: J.A. Lohr REVIEWED BY:

REVISIONS: INIT. DATE

DATE: 6/11/2021

SIG. INVENTORY NO. 07-0037

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

SEAL






ROBERT J. ZIEMBA

ENGINEER

07-0037

EDI MODEL 2018EClip-NC CONFLICT MONITOR PROGRAMMING DETAIL

(remove jumpers and set switches as shown)



■ = DENOTES POSITION OF SWITCH

NOTES:

- Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
- Ensure jumpers SEL2-SEL5 and SEL9 are present on the monitor board.
- Ensure that Red Enable is active at all times during normal operation.
- Integrate monitor with Ethernet network in cabinet.

NOTES

- To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
- Program controller to start up in phase 2 Green and 6 Green.
- The cabinet and controller are part of the Burlington-Graham Signal System.

EQUIPMENT INFORMATION

CONTROLLER.....2070LX
 CABINET.....332 W/AUX
 SOFTWARE.....ECONOLITE ASC/3-2070
 CABINET MOUNT.....BASE
 OUTPUT FILE POSITIONS...18 WITH AUX. OUTPUT FILE
 LOAD SWITCHES USED.....S2,S5,S7,S8,AUX S4
 PHASES USED.....2,4,5,6
 OVERLAP "A".....NOT USED
 OVERLAP "B".....NOT USED
 OVERLAP "C".....*
 OVERLAP "D".....NOT USED

* See overlap programming detail on sheet 2

SIGNAL HEAD HOOK-UP CHART

LOAD SWITCH NO.	S1	S2	S3	S4	S5	S6	S7	S8	S9	S10	S11	S12	AUX S1	AUX S2	AUX S3	AUX S4	AUX S5	AUX S6	
CMU CHANNEL NO.	1	2	13	3	4	14	5	6	15	7	8	16	9	10	17	11	12	18	
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED	OLA	OLB	SPARE	OLC	OLD	SPARE	
SIGNAL HEAD NO.	NU	21,22	NU	NU	41,42	62	NU	51*	42	61,62	NU	NU	NU	NU	NU	51*	NU	NU	
RED		128			101			*		134									
YELLOW		129			102					135									
GREEN		130			103					136									
RED ARROW																		A114	
YELLOW ARROW						102			132										A115
FLASHING YELLOW ARROW																			A116
GREEN ARROW						103		133	133										


NU = Not Used

* Denotes install load resistor. See load resistor installation detail this sheet.

* See pictorial of head wiring in detail this sheet.

INPUT FILE POSITION LAYOUT

(front view)



EX.: 1A, 2A, ETC. = LOOP NO.'S

FS = FLASH SENSE
ST = STOP TIME

⊗ Wired Input - Do not populate slot with detector card

INPUT FILE CONNECTION & PROGRAMMING CHART


LOOP NO.	LOOP TERMINAL	INPUT FILE POS.	PIN NO.	DETECTOR NO.	NEMA PHASE	CALL	EXTEND TIME	DELAY TIME	ADDED INITIAL	DETECTOR TYPE
2A	TB2-5,6	I2U	39	2	2	YES				S
4A	TB4-9,10	I6U	41	4	4	YES		3		S
5B	TB4-11,12	I6L	45	14	5	YES		15		S
5A ¹	TB3-1,2	J1U	55	5	5	YES		15		S
		I4U	47	22	2	YES				S
6A	TB3-5,6	J2U	40	6	6	YES				S
* S1	TB6-9,10	I9U	60	11	SYS	NO				N
* S2	TB6-11,12	I9L	62	13	SYS	NO				N

¹Add jumper from J1-W to I4-W, on rear of input file.

* For the detectors to work as shown on the signal design plan, see the Vehicle Detector Setup Programming Detail for Alternate Phasing on sheet 3.


* System detector only. Remove any assigned vehicle phase.

INPUT FILE POSITION LEGEND: J2L



FYA SIGNAL WIRING DETAIL


(wire signal head as shown)



LOAD RESISTOR INSTALLATION DETAIL

(install resistors as shown)

VALUE (ohms)	WATTAGE
1.5K - 1.9K	25W (min)
2.0K - 3.0K	10W (min)



THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 07-0037
 DESIGNED: June 2021
 SEALED: 6/11/2021
 REVISED:

THIS ELECTRICAL DETAIL SUPERSEDES THE DETAIL SEALED ON 06/13/2018

Electrical Detail - Sheet 1 of 4

Electrical and Programming Details for: SR 1716 (Graham-Hopedale Road) at Vaughn Road

Prepared for the Offices of: Division 7 Alameda County Burlington

PLAN DATE: June 2021 REVIEWED BY: T. Joyce
 PREPARED BY: C. Strickland REVIEWED BY:

REVISIONS: _____ INIT. DATE

DocuSigned by: 6/21/2021

750 N. Greenfield Pkwy, Garner, NC 27529

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

SEAL

SEAL 031001

DATE: _____

SIG. INVENTORY NO. 07-0037

18-June-2021 1:45:04 S:\Projects\18-0037\Sigs\Sig 31.1\EDI Model 2018EClip-NC Conflict Monitor\Projects\18-0037_Sig.31.1_EDI Model 2018EClip-NC Conflict Monitor.dgn

ECONOLITE ASC/3-2070 OVERLAP PROGRAMMING DETAIL
(program controller as shown)

1. From Main Menu select 2. CONTROLLER
2. From CONTROLLER Submenu select 2. VEHICLE OVERLAPS
 Toggle Twice

OVERLAP C

Select TMG VEH OVLP [C] and 'PPLT FYA'

```

TMG VEH OVLP...[C] TYPE: ....[PPLT FYA]
PROTECTED LEFT TURN.... PHASE 5
OPPOSING THROUGH..... PHASE 6

FLASHING ARROW OUTPUT....CH11 ISOLATE
DELAY START OF: FYA..0.0 CLEARANCE..0.0
ACTION PLAN SF BIT DISABLE..... 5
    
```



← NOTICE ACTION
PLAN SF BIT "5"

END PROGRAMMING

THIS ELECTRICAL DETAIL IS FOR
THE SIGNAL DESIGN: 07-0037
DESIGNED: June 2021
SEALED: 6/11/2021
REVISED:

THIS ELECTRICAL DETAIL
SUPERSEDES THE DETAIL
SEALED ON 06/13/2018

Electrical Detail - Sheet 2 of 4

<p>ELECTRICAL AND PROGRAMMING DETAILS FOR:</p> <p align="center"><i>Prepared for the Offices of:</i></p>  <p align="center">750 N. Greenfield Pkwy, Garner, NC 27529</p>	<p>SR 1716 (Graham-Hopedale Road) at Vaughn Road</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td colspan="2">Division 7</td> <td colspan="2">Alamance County</td> <td colspan="2">Burlington</td> </tr> <tr> <td>PLAN DATE:</td> <td>June 2021</td> <td>REVIEWED BY:</td> <td colspan="3">T. Joyce</td> </tr> <tr> <td>PREPARED BY:</td> <td>C. Strickland</td> <td>REVIEWED BY:</td> <td colspan="3"></td> </tr> <tr> <td>REVISIONS</td> <td>INIT.</td> <td>DATE</td> <td colspan="3"></td> </tr> <tr> <td> </td> <td> </td> <td> </td> <td colspan="3"> </td> </tr> <tr> <td> </td> <td> </td> <td> </td> <td colspan="3"> </td> </tr> </table>	Division 7		Alamance County		Burlington		PLAN DATE:	June 2021	REVIEWED BY:	T. Joyce			PREPARED BY:	C. Strickland	REVIEWED BY:				REVISIONS	INIT.	DATE																<p align="center">DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED</p> <p align="center">SEAL</p>  <p>DocuSigned by: <i>T. Todd Joyce</i> 6/23/2021 DATE</p> <p>SIG. INVENTORY NO. 07-0037</p>
Division 7		Alamance County		Burlington																																		
PLAN DATE:	June 2021	REVIEWED BY:	T. Joyce																																			
PREPARED BY:	C. Strickland	REVIEWED BY:																																				
REVISIONS	INIT.	DATE																																				

18-JUN-2021 14:07
 *070037.dwg ele xxx.dgn
 c88trickland