

**This electronic collection of documents is provided
for the convenience of the user
and is Not a Certified Document –**

**The documents contained herein were originally issued
and sealed by the individuals whose names and license
numbers appear on each page, on the dates appearing
with their signature on that page.**

**This file or an individual page
shall not be considered a certified document.**

REFERENCE: B-5302

PROJECT: 46016

CONTENTS

<u>SHEET NO.</u>	<u>DESCRIPTION</u>
1	TITLE SHEET
2	LEGEND (SOIL & ROCK)
3	SITE PLAN
4	PROFILE
5-8	CROSS SECTION(S)
9-17	BORE LOG(S)
18	SOIL TEST RESULTS
19	SITE PHOTOGRAPH(S)

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 DIVISION OF HIGHWAYS
 GEOTECHNICAL ENGINEERING UNIT

STRUCTURE
SUBSURFACE INVESTIGATION

COUNTY BEAUFORT
 PROJECT DESCRIPTION BRIDGE NO. 3 ON US 17
BUSINESS OVER NORFOLK SOUTHERN RAILROAD

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	B-5302	1	19

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT (919) 707-6850. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

NOTES:

- THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.
- BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

PERSONNEL

J.R. SWARTLEY

T.J. WHITE

K.S. HARDEE

D.L. MOSS

M.S. HAYES


INVESTIGATED BY J.R. SWARTLEY

DRAWN BY J.R. SWARTLEY

CHECKED BY S.S. LANEY

SUBMITTED BY S.S. LANEY

DATE AUGUST 2017



DocuSigned by:

Jarett Swartley

9/11/2017


919459487 SIGNATURE

DATE

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT
SUBSURFACE INVESTIGATION
SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS


SOIL DESCRIPTION										GRADATION										ROCK DESCRIPTION										TERMS AND DEFINITIONS																																																																																																																																																						
<p>SOIL IS CONSIDERED UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER AND YIELD LESS THAN 100 BLOWS PER FOOT ACCORDING TO THE STANDARD PENETRATION TEST (AASHTO T 206, ASTM D1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY INCLUDE THE FOLLOWING: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. FOR EXAMPLE, VERY STIFF, GRAY, SILTY CLAY, MOIST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC, A-7-6</p>										<p>WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. UNIFORMLY GRADED - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES.</p>										<p>HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED, AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS IN NON-COASTAL PLAIN MATERIAL. THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:</p>										<p>ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER. AQUIFER - A WATER BEARING FORMATION OR STRATA. ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND. ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC. ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE. CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE. COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE. CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK. DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL. DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH. FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE. FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES. FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLOADED FROM PARENT MATERIAL. FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM. FORMATION (FM) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD. JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED. LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT. LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS. MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS. MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM. RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK. ROCK QUALITY DESIGNATION (ROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. SAPROLITE (SAP.) - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK. SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS. SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE. STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N OR BPF) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE. STRATA ROCK QUALITY DESIGNATION (SROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.</p>																																																																																																																																																						
SOIL LEGEND AND AASHTO CLASSIFICATION										ANGULARITY OF GRAINS										WEATHERED ROCK (WR)										NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT N VALUES > 100 BLOWS PER FOOT IF TESTED.																																																																																																																																																						
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>GENERAL CLASS.</th> <th colspan="5">GRANULAR MATERIALS (<= 35% PASSING #200)</th> <th colspan="5">SILT-CLAY MATERIALS (> 35% PASSING #200)</th> <th colspan="5">ORGANIC MATERIALS</th> </tr> <tr> <th>GROUP CLASS.</th> <th>A-1</th> <th>A-3</th> <th>A-2</th> <th>A-2-4</th> <th>A-2-5</th> <th>A-2-6</th> <th>A-2-7</th> <th>A-4</th> <th>A-5</th> <th>A-6</th> <th>A-7</th> <th>A-1, A-2</th> <th>A-3</th> <th>A-4, A-5</th> <th>A-6, A-7</th> </tr> <tr> <th>SYMBOL</th> <td colspan="5">[Pattern]</td> <td colspan="5">[Pattern]</td> <td colspan="5">[Pattern]</td> </tr> <tr> <th>% PASSING #10 #40 #200</th> <td>50 MX 30 MX 15 MX</td> <td>50 MX 25 MX</td> <td>51 MN 35 MX 35 MX</td> <td>40 MX 41 MN 10 MX 11 MN</td> <td>40 MX 41 MN 11 MN 11 MN</td> <td>40 MX 41 MN 11 MN 11 MN</td> <td>40 MX 41 MN 11 MN 11 MN</td> <td>36 MN 36 MN</td> <td>36 MN 36 MN</td> <td>36 MN 36 MN</td> <td>36 MN 36 MN</td> <td>GRANULAR SOILS</td> <td>SILT-CLAY SOILS</td> <td>MUCK, PEAT</td> <td></td> </tr> <tr> <th>MATERIAL PASSING #40 LL PI</th> <td colspan="5">-</td> <td>40 MX 41 MN NP</td> <td>40 MX 41 MN NP</td> <td>40 MX 41 MN NP</td> <td>40 MX 41 MN NP</td> <td>40 MX 41 MN NP</td> <td>40 MX 41 MN NP</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <th>GROUP INDEX</th> <td colspan="5">0</td> <td>0</td> <td>4 MX</td> <td>8 MX</td> <td>12 MX</td> <td>16 MX</td> <td>NO MX</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <th>USUAL TYPES OF MAJOR MATERIALS</th> <td colspan="2">STONE FRAGS. GRAVEL, AND SAND</td> <td>FINE SAND</td> <td colspan="2">SILTY OR CLAYEY GRAVEL AND SAND</td> <td colspan="2">SILTY SOILS</td> <td colspan="2">CLAYEY SOILS</td> <td colspan="5">SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER</td> <td>HIGHLY ORGANIC SOILS</td> </tr> <tr> <th>GEN. RATING AS SUBGRADE</th> <td colspan="5">EXCELLENT TO GOOD</td> <td colspan="5">FAIR TO POOR</td> <td>FAIR TO POOR</td> <td>POOR</td> <td>UNSATURABLE</td> </tr> <tr> <td colspan="15">PI OF A-7-5 SUBGROUP IS ≤ LL - 30 ; PI OF A-7-6 SUBGROUP IS > LL - 30</td> </tr> </table>										GENERAL CLASS.	GRANULAR MATERIALS (<= 35% PASSING #200)					SILT-CLAY MATERIALS (> 35% PASSING #200)					ORGANIC MATERIALS					GROUP CLASS.	A-1	A-3	A-2	A-2-4	A-2-5	A-2-6	A-2-7	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7	SYMBOL	[Pattern]					[Pattern]					[Pattern]					% PASSING #10 #40 #200	50 MX 30 MX 15 MX	50 MX 25 MX	51 MN 35 MX 35 MX	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 11 MN 11 MN	40 MX 41 MN 11 MN 11 MN	40 MX 41 MN 11 MN 11 MN	36 MN 36 MN	36 MN 36 MN	36 MN 36 MN	36 MN 36 MN	GRANULAR SOILS	SILT-CLAY SOILS	MUCK, PEAT		MATERIAL PASSING #40 LL PI	-					40 MX 41 MN NP	40 MX 41 MN NP	40 MX 41 MN NP	40 MX 41 MN NP	40 MX 41 MN NP	40 MX 41 MN NP					GROUP INDEX	0					0	4 MX	8 MX	12 MX	16 MX	NO MX					USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS. GRAVEL, AND SAND		FINE SAND	SILTY OR CLAYEY GRAVEL AND SAND		SILTY SOILS		CLAYEY SOILS		SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER					HIGHLY ORGANIC SOILS	GEN. RATING AS SUBGRADE	EXCELLENT TO GOOD					FAIR TO POOR					FAIR TO POOR	POOR	UNSATURABLE	PI OF A-7-5 SUBGROUP IS ≤ LL - 30 ; PI OF A-7-6 SUBGROUP IS > LL - 30															<p>THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS IS DESIGNATED BY THE TERMS: ANGULAR, SUBANGULAR, SUBROUNDED, OR ROUNDED.</p>										<p>CRYSTALLINE ROCK (CR) NON-CRYSTALLINE ROCK (NCR) COASTAL PLAIN SEDIMENTARY ROCK (CP)</p>										<p>CRUSTALINE ROCK (CR) NON-CRYSTALLINE ROCK (NCR) COASTAL PLAIN SEDIMENTARY ROCK (CP)</p>									
GENERAL CLASS.	GRANULAR MATERIALS (<= 35% PASSING #200)					SILT-CLAY MATERIALS (> 35% PASSING #200)					ORGANIC MATERIALS																																																																																																																																																																									
GROUP CLASS.	A-1	A-3	A-2	A-2-4	A-2-5	A-2-6	A-2-7	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7																																																																																																																																																																					
SYMBOL	[Pattern]					[Pattern]					[Pattern]																																																																																																																																																																									
% PASSING #10 #40 #200	50 MX 30 MX 15 MX	50 MX 25 MX	51 MN 35 MX 35 MX	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 11 MN 11 MN	40 MX 41 MN 11 MN 11 MN	40 MX 41 MN 11 MN 11 MN	36 MN 36 MN	36 MN 36 MN	36 MN 36 MN	36 MN 36 MN	GRANULAR SOILS	SILT-CLAY SOILS	MUCK, PEAT																																																																																																																																																																						
MATERIAL PASSING #40 LL PI	-					40 MX 41 MN NP	40 MX 41 MN NP	40 MX 41 MN NP	40 MX 41 MN NP	40 MX 41 MN NP	40 MX 41 MN NP																																																																																																																																																																									
GROUP INDEX	0					0	4 MX	8 MX	12 MX	16 MX	NO MX																																																																																																																																																																									
USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS. GRAVEL, AND SAND		FINE SAND	SILTY OR CLAYEY GRAVEL AND SAND		SILTY SOILS		CLAYEY SOILS		SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER					HIGHLY ORGANIC SOILS																																																																																																																																																																					
GEN. RATING AS SUBGRADE	EXCELLENT TO GOOD					FAIR TO POOR					FAIR TO POOR	POOR	UNSATURABLE																																																																																																																																																																							
PI OF A-7-5 SUBGROUP IS ≤ LL - 30 ; PI OF A-7-6 SUBGROUP IS > LL - 30																																																																																																																																																																																				
MINERALOGICAL COMPOSITION										COMPRESSION										WEATHERING										FRESH																																																																																																																																																						
<p>MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHEN THEY ARE CONSIDERED OF SIGNIFICANCE.</p>										<p>SLIGHTLY COMPRESSIBLE LL < 31 MODERATELY COMPRESSIBLE LL = 31 - 50 HIGHLY COMPRESSIBLE LL > 50</p>										<p>ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING. ROCK RINGS UNDER HAMMER IF CRYSTALLINE.</p>										<p>ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN. CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF OF A CRYSTALLINE NATURE.</p>																																																																																																																																																						
PERCENTAGE OF MATERIAL										GROUND WATER										MODERATE (MOD.)										SEVERE (SEV.)																																																																																																																																																						
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>ORGANIC MATERIAL</th> <th>GRANULAR SOILS</th> <th>SILT - CLAY SOILS</th> <th>OTHER MATERIAL</th> </tr> <tr> <td>TRACE OF ORGANIC MATTER</td> <td>2 - 3%</td> <td>3 - 5%</td> <td>TRACE 1 - 10%</td> </tr> <tr> <td>LITTLE ORGANIC MATTER</td> <td>3 - 5%</td> <td>5 - 12%</td> <td>LITTLE 10 - 20%</td> </tr> <tr> <td>MODERATELY ORGANIC</td> <td>5 - 10%</td> <td>12 - 20%</td> <td>SOME 20 - 35%</td> </tr> <tr> <td>HIGHLY ORGANIC</td> <td>> 10%</td> <td>> 20%</td> <td>HIGHLY 35% AND ABOVE</td> </tr> </table>										ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL	TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE 1 - 10%	LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE 10 - 20%	MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME 20 - 35%	HIGHLY ORGANIC	> 10%	> 20%	HIGHLY 35% AND ABOVE	<p>WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING STATIC WATER LEVEL AFTER 24 HOURS PERCHED WATER, SATURATED ZONE, OR WATER BEARING STRATA SPRING OR SEEP</p>										<p>ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK. ROCK GIVES "CLUNK" SOUND WHEN STRUCK. IF TESTED, WOULD YIELD SPT REFUSAL</p>										<p>ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC CLEAR AND EVIDENT BUT REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN. IF TESTED, WOULD YIELD SPT N VALUES > 100 BPF</p>																																																																																																																																		
ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL																																																																																																																																																																																	
TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE 1 - 10%																																																																																																																																																																																	
LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE 10 - 20%																																																																																																																																																																																	
MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME 20 - 35%																																																																																																																																																																																	
HIGHLY ORGANIC	> 10%	> 20%	HIGHLY 35% AND ABOVE																																																																																																																																																																																	
CONSISTENCY OR DENSENESS										MISCELLANEOUS SYMBOLS										SEVERE (SEV.)										VERY SEVERE (IV SEV.)																																																																																																																																																						
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>PRIMARY SOIL TYPE</th> <th>COMPACTNESS OR CONSISTENCY</th> <th>RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)</th> <th>RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT²)</th> </tr> <tr> <td>GENERALLY GRANULAR MATERIAL (NON-COHESSIVE)</td> <td>VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE</td> <td>< 4 4 TO 10 10 TO 30 30 TO 50 > 50</td> <td>N/A</td> </tr> <tr> <td>GENERALLY SILT-CLAY MATERIAL (COHESIVE)</td> <td>VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD</td> <td>< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30</td> <td>< 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4</td> </tr> </table>										PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT ²)	GENERALLY GRANULAR MATERIAL (NON-COHESSIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	< 4 4 TO 10 10 TO 30 30 TO 50 > 50	N/A	GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30	< 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4	<p>ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION SOIL SYMBOL ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT INFERRED SOIL BOUNDARY INFERRED ROCK LINE ALLUVIAL SOIL BOUNDARY</p>										<p>DIP & DIP DIRECTION OF ROCK STRUCTURES SPT DMT TEST BORING AUGER BORING CORE BORING MONITORING WELL PIEZOMETER INSTALLATION</p>										<p>SLOPE INDICATOR INSTALLATION CONE PENETROMETER TEST SOUNDING ROD TEST BORING WITH CORE SPT N-VALUE</p>																																																																																																																																										
PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT ²)																																																																																																																																																																																	
GENERALLY GRANULAR MATERIAL (NON-COHESSIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	< 4 4 TO 10 10 TO 30 30 TO 50 > 50	N/A																																																																																																																																																																																	
GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30	< 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4																																																																																																																																																																																	
TEXTURE OR GRAIN SIZE										RECOMMENDATION SYMBOLS										MODERATELY HARD										MEDIUM HARD																																																																																																																																																						
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>U.S. STD. SIEVE SIZE OPENING (MM)</th> <th>4</th> <th>10</th> <th>40</th> <th>60</th> <th>200</th> <th>270</th> </tr> <tr> <td></td> <td>4.75</td> <td>2.00</td> <td>0.42</td> <td>0.25</td> <td>0.075</td> <td>0.053</td> </tr> <tr> <th>BOULDER (BLDR.)</th> <th>COBBLE (COB.)</th> <th>GRAVEL (GR.)</th> <th>COARSE SAND (CSE. SD.)</th> <th>FINE SAND (F SD.)</th> <th>SILT (SL.)</th> <th>CLAY (CL.)</th> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </table>										U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270		4.75	2.00	0.42	0.25	0.075	0.053	BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE. SD.)	FINE SAND (F SD.)	SILT (SL.)	CLAY (CL.)								<p>UNDERCUT SHALLOW UNDERCUT UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE USED IN THE TOP 3 FEET OF EMBANKMENT OR BACKFILL</p>										<p>CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.</p>										<p>CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.</p>																																																																																																																										
U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270																																																																																																																																																																														
	4.75	2.00	0.42	0.25	0.075	0.053																																																																																																																																																																														
BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE. SD.)	FINE SAND (F SD.)	SILT (SL.)	CLAY (CL.)																																																																																																																																																																														
SOIL MOISTURE - CORRELATION OF TERMS										ABBREVIATIONS										SOFT										VERY SOFT																																																																																																																																																						
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>SOIL MOISTURE SCALE (ATTERBERG LIMITS)</th> <th>FIELD MOISTURE DESCRIPTION</th> <th>GUIDE FOR FIELD MOISTURE DESCRIPTION</th> </tr> <tr> <td>LL - LIQUID LIMIT PL - PLASTIC LIMIT</td> <td>- SATURATED - (SAT.) - WET - (W)</td> <td>USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td>OM - OPTIMUM MOISTURE SL - SHRINKAGE LIMIT</td> <td>- MOIST - (M) - DRY - (D)</td> <td>SOLID; AT OR NEAR OPTIMUM MOISTURE REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td> </tr> </table>										SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION	LL - LIQUID LIMIT PL - PLASTIC LIMIT	- SATURATED - (SAT.) - WET - (W)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE	OM - OPTIMUM MOISTURE SL - SHRINKAGE LIMIT	- MOIST - (M) - DRY - (D)	SOLID; AT OR NEAR OPTIMUM MOISTURE REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE	<p>AR - AUGER REFUSAL BT - BORING TERMINATED CL - CLAY CPT - COARSE PENETRATION TEST CSE - COARSE DMT - DILATOMETER TEST DPT - DYNAMIC PENETRATION TEST e - VOID RATIO F - FINE FOSS. - FOSSILIFEROUS FRAC. - FRACTURED, FRACTURES FRAGS. - FRAGMENTS HI. - HIGHLY MED. - MEDIUM MICA - MICACEOUS MOD. - MODERATELY NP - NON PLASTIC ORG. - ORGANIC PMT - PRESSUREMETER TEST SAP. - SAPROLITIC SD. - SAND, SANDY SL. - SILT, SILTY SLI. - SLIGHTLY TCR - TRICONE REFUSAL w - MOISTURE CONTENT V - VERY VST - VANE SHEAR TEST WEA. - WEATHERED W - UNIT WEIGHT W_g - DRY UNIT WEIGHT SAMPLE ABBREVIATIONS S - BULK SS - SPLIT SPOON ST - SHELBY TUBE RS - ROCK RT - RECOMPACTED TRIAXIAL CBR - CALIFORNIA BEARING RATIO</p>										<p>CAN BE GROVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.</p>										<p>CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.</p>																																																																																																																																													
SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION																																																																																																																																																																																		
LL - LIQUID LIMIT PL - PLASTIC LIMIT	- SATURATED - (SAT.) - WET - (W)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																																		
OM - OPTIMUM MOISTURE SL - SHRINKAGE LIMIT	- MOIST - (M) - DRY - (D)	SOLID; AT OR NEAR OPTIMUM MOISTURE REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																																		
PLASTICITY										EQUIPMENT USED ON SUBJECT PROJECT										FRACTURE SPACING										BEDDING																																																																																																																																																						
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>NON PLASTIC</th> <th colspan="2">PLASTICITY INDEX (PI)</th> <th>DRY STRENGTH</th> </tr> <tr> <td></td> <td>0-5</td> <td>6-15</td> <td>VERY LOW</td> </tr> <tr> <td>SLIGHTLY PLASTIC</td> <td>6-15</td> <td>16-25</td> <td>SLIGHT</td> </tr> <tr> <td>MODERATELY PLASTIC</td> <td>16-25</td> <td>26 OR MORE</td> <td>MEDIUM</td> </tr> <tr> <td>HIGHLY PLASTIC</td> <td>26 OR MORE</td> <td></td> <td>HIGH</td> </tr> </table>										NON PLASTIC	PLASTICITY INDEX (PI)		DRY STRENGTH		0-5	6-15	VERY LOW	SLIGHTLY PLASTIC	6-15	16-25	SLIGHT	MODERATELY PLASTIC	16-25	26 OR MORE	MEDIUM	HIGHLY PLASTIC	26 OR MORE		HIGH	<p>DRILL UNITS: CME-45C CME-55 CME-550 VANE SHEAR TEST PORTABLE HOIST CME-550X</p>										<p>ADVANCING TOOLS: CLAY BITS 6" CONTINUOUS FLIGHT AUGER 8" HOLLOW AUGERS HARD FACED FINGER BITS TUNG-CARBIDE INSERTS CASING w/ ADVANCER TRICONE 2 15/16" STEEL TEETH TRICONE TUNG-CARB. CORE BIT BWJ RODS</p>										<p>TERMS SPACING VERY WIDE MORE THAN 10 FEET WIDE 3 TO 10 FEET MODERATELY CLOSE 1 TO 3 FEET CLOSE 0.16 TO 1 FOOT VERY CLOSE LESS THAN 0.16 FEET</p>										<p>TERMS THICKNESS VERY THICKLY BEDDED 4 FEET THICKLY BEDDED 1.5 - 4 FEET THINLY BEDDED 0.16 - 1.5 FEET VERY THINLY BEDDED 0.03 - 0.16 FEET THICKLY LAMINATED 0.008 - 0.03 FEET THINLY LAMINATED < 0.008 FEET</p>																																																																																																																								
NON PLASTIC	PLASTICITY INDEX (PI)		DRY STRENGTH																																																																																																																																																																																	
	0-5	6-15	VERY LOW																																																																																																																																																																																	
SLIGHTLY PLASTIC	6-15	16-25	SLIGHT																																																																																																																																																																																	
MODERATELY PLASTIC	16-25	26 OR MORE	MEDIUM																																																																																																																																																																																	
HIGHLY PLASTIC	26 OR MORE		HIGH																																																																																																																																																																																	
COLOR										INDURATION										FRAGILE										MODERATELY INDURATED																																																																																																																																																						
<p>DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-GRAY). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.</p>										<p>FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.</p>										<p>RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</p>										<p>GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</p>																																																																																																																																																						
BENCH MARK: BL-4, 27+53, 3ILT, -L-, N: 653454 E: 2573091										ELEVATION: 28.83 FEET										NOTES:										EXTREMELY INDURATED																																																																																																																																																						
INDURATION										FRAGILE										MODERATELY INDURATED										INDURATED																																																																																																																																																						
<p>FRAGILE MODERATELY INDURATED INDURATED EXTREMELY INDURATED</p>										<p>RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE. GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER. GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER. SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</p>																																																																																																																																																																										



SKEW = 39° 31' 45"




PROFILE ALONG -L-



VE = 2:1
40' : 1" (40 SCALE)


NOTE: EXISTING GROUND SURFACE PROFILE OF -L- CENTERLINE TAKEN FROM ELECTRONIC TIN FILE: 'B5302_LS_TIN_16047.TIN' DATED 6/8/17. INFERRED STRATIGRAPHY IS DRAWN THROUGH THE BORINGS WITH BOTH PROJECTED ONTO THE PROFILE.

- (A) LOOSE, BLACK, MUCK, WET
- (B) MED. STIFF TO STIFF, GREEN AND GRAY, SANDY SILT, WET
- (C) LOOSE, CALCAREOUS, GREEN AND GRAY, CLAYEY SAND, SATURATED
- (D) LOOSE TO MED. DENSE, CALCAREOUS, GRAY, SILTY SAND AND CLAYEY SAND WITH FRIABLE TO MODERATELY INDURATED SEAMS (0.1'), SATURATED
- (E) GRAY, MODERATELY TO VERY SEVERELY WEATHERED, LIMESTONE, (CASTLE HAYNE FORMATION)



NOTE: CROSS SECTION GROUND LINES CONSTRUCTED ALONG BENT LINE WITH SKEW OF 39° 31' 45". INFERRED STRATIGRAPHY IS DRAWN THROUGH THE BORINGS WITH BOTH PROJECTED ONTO IT.


SCHEMATIC OF GROUNDWATER MONITORING SYSTEM FOR THE CASTLE HAYNE FORMATION




NOTE: CROSS SECTION GROUND LINES CONSTRUCTED ALONG BENT LINE WITH SKEW OF 39° 31' 45". INFERRED STRATIGRAPHY IS DRAWN THROUGH THE BORINGS WITH BOTH PROJECTED ONTO IT.

SYSTEMS
 CONSULTING
 INC.
 1000
 W. BIRCH
 AVE.
 SUITE 200
 CHARLOTTE, NC 28202
 (704) 366-8800
 WWW.SYSTEMS-CONSULTING.COM

- (A) LOOSE, BLACK, MUCK, WET
- (B) MED. STIFF, GREEN, SANDY SILT, WET
- (C) GRAY, MODERATELY TO SEVERLY WEATHERED, LIMESTONE, (CASTLE HAYNE FORMATION)
- (D) MED. DENSE TO DENSE, CALCAREOUS, GRAY, SILTY SAND WITH FRIABLE TO MODERATELY INDURATED SEAMS (0.1'), SATURATED



CASTLE HAYNE FORMATION



- (A) LOOSE, BLACK, MUCK, WET (ALLUVIAL)
- (B) GRAY, MODERATELY TO SEVERLY WEATHERED, LIMESTONE, (CASTLE HAYNE FORMATION)
- (C) MED. DENSE TO DENSE, CALCAREOUS, GRAY, SILTY SAND WITH SHELL FRAGMENTS, SATURATED

30 + 12
-L-

NOTE: CROSS SECTION GROUND LINES CONSTRUCTED ALONG BENT LINE WITH SKEW OF 39° 31' 45". INFERRED STRATIGRAPHY IS DRAWN THROUGH THE BORINGS WITH BOTH PROJECTED ONTO IT.

GEOTECHNICAL BORING REPORT

BORE LOG

WBS 46016.1.1		TIP B-5302		COUNTY BEAUFORT		GEOLOGIST Swartley, J. R.									
SITE DESCRIPTION BRIDGE NO. 3 ON US 17 BUSINESS (-L-) OVER NORFOLK SOUTHERN RAILROAD							GROUND WTR (ft)								
BORING NO. EB1-A		STATION 27+44		OFFSET 21 ft LT		ALIGNMENT -L-									
COLLAR ELEV. 29.1 ft		TOTAL DEPTH 159.3 ft		NORTHING 653,441		EASTING 2,573,093									
DRILL RIG/HAMMER EFF./DATE SME9563 CME-550X 88% 08/16/2017				DRILL METHOD Mud Rotary		HAMMER TYPE Automatic									
DRILLER White, T.J.		START DATE 05/25/17		COMP. DATE 05/26/17		SURFACE WATER DEPTH N/A									
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	MOI	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)
			0.5ft	0.5ft	0.5ft	0	25	50	75	100					
-130						Match Line								Boring Terminated at Elevation -130.2 ft IN COASTAL PLAIN (SILTY SAND)	

NCDOT BORE DOUBLE B5302_GEO_BRDG0003.GPJ NC_DOT_GDT 8/10/17

GEOTECHNICAL BORING REPORT

BORE LOG

WBS 46016.1.1		TIP B-5302		COUNTY BEAUFORT		GEOLOGIST Hayes, M.S.	
SITE DESCRIPTION BRIDGE NO. 3 ON US 17 BUSINESS (-L-) OVER NORFOLK SOUTHERN RAILROAD							GROUND WTR (ft)
BORING NO. EB1-B		STATION 27+89		OFFSET 21 ft RT		ALIGNMENT -L-	
COLLAR ELEV. 29.4 ft		TOTAL DEPTH 139.1 ft		NORTHING 653,450		EASTING 2,573,154	
DRILL RIG/HAMMER EFF./DATE SME9563 CME-550X 88% 08/16/2017			DRILL METHOD Mud Rotary		HAMMER TYPE Automatic		
DRILLER White, T.J.		START DATE 05/30/17		COMP. DATE 05/30/17		SURFACE WATER DEPTH N/A	

ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)	
			0.5ft	0.5ft	0.5ft	0	25	50	75	100					
30															
	28.7	0.7	19	12	10										29.4
															28.7
	25.5	3.9	3	4	7										
	21.8	7.6	3	5	8										
	16.8	12.6	3	4	5										
	11.8	17.6	3	5	8										
	6.8	22.6	1	2	2										
	1.8	27.6	1	1	1										
	-3.2	32.6	1	2	2										
	-8.2	37.6	4	6	7										
	-13.2	42.6	3	3	4										
	-18.2	47.6	2	1	1										
	-23.2	52.6	1	2	3										
	-28.2	57.6	2	3	6										
	-33.2	62.6	4	3	6										
	-38.2	67.6	8	4	7										
	-43.2	72.6	2	4	3										
	-48.2	77.6	2	1	1										

ELEV (ft)	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)
0.0		GROUND SURFACE	0.0
0.7		ROADWAY EMBANKMENT (PAVEMENT)	0.7
8.4		ALLUVIAL TAN AND BROWN, SILTY SAND AND SAND	8.4
21.0			21.0
36.0		COASTAL PLAIN GREEN AND GRAY, CLAYEY SAND (YORKTOWN FORMATION)	36.0
46.0			46.0
61.0		GREEN AND GRAY, CALCAREOUS, CLAYEY SAND WITH FRIABLE TO MODERATELY INDURATED SEAMS (<0.1')	61.0

WBS 46016.1.1		TIP B-5302		COUNTY BEAUFORT		GEOLOGIST Hayes, M.S.	
SITE DESCRIPTION BRIDGE NO. 3 ON US 17 BUSINESS (-L-) OVER NORFOLK SOUTHERN RAILROAD							GROUND WTR (ft)
BORING NO. EB1-B		STATION 27+89		OFFSET 21 ft RT		ALIGNMENT -L-	
COLLAR ELEV. 29.4 ft		TOTAL DEPTH 139.1 ft		NORTHING 653,450		EASTING 2,573,154	
DRILL RIG/HAMMER EFF./DATE SME9563 CME-550X 88% 08/16/2017			DRILL METHOD Mud Rotary		HAMMER TYPE Automatic		
DRILLER White, T.J.		START DATE 05/30/17		COMP. DATE 05/30/17		SURFACE WATER DEPTH N/A	

ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)	
			0.5ft	0.5ft	0.5ft	0	25	50	75	100					
-50															
	-53.2	82.6	2	2	3										
	-58.2	87.6	1	1	1										
	-63.2	92.6	1	1	1										
	-68.2	97.6	2	2	2										
	-73.2	102.6	3	5	5										
	-78.2	107.6	2	3	3										
	-83.2	112.6	10	4	4										
	-88.2	117.6	37	63/0.3											
	-93.2	122.6	22	23	13										
	-98.2	127.6	17	21	14										
	-103.2	132.6	6	7	8										
	-108.2	137.6	8	8	10										

ELEV (ft)	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)
-50		Match Line	-50
-56.6		GREEN AND GRAY, CALCAREOUS, CLAYEY SAND WITH FRIABLE TO MODERATELY INDURATED SEAMS (<0.1') (continued)	-56.6
-85.6		COASTAL PLAIN GRAY, MODERATELY TO SEVERLY WEATHERED, LIMESTONE (CASTLE HAYNE FORMATION)	-85.6
-90.6		GRAY, CALCAREOUS, SILTY SAND WITH FRIABLE TO MODERATELY INDURATED SEAMS (<0.1)	-90.6
-101.6		GRAY, CALCAREOUS, SILTY SAND WITH SHELL FRAGMENTS	-101.6
-109.7		Boring Terminated at Elevation -109.7 ft IN COASTAL PLAIN (SILTY SAND)	-109.7

NCDOT BORE DOUBLE B5302_GEO_BRDG003.GPJ_NC_DOT.GDT 8/10/17

GEOTECHNICAL BORING REPORT

BORE LOG

WBS 46016.1.1		TIP B-5302		COUNTY BEAUFORT		GEOLOGIST Swartley, J. R.									
SITE DESCRIPTION BRIDGE NO. 3 ON US 17 BUSINESS (-L-) OVER NORFOLK SOUTHERN RAILROAD						GROUND WTR (ft)									
BORING NO. B1-A		STATION 27+94		OFFSET 21 ft LT		ALIGNMENT -L-									
COLLAR ELEV. 19.4 ft		TOTAL DEPTH 129.2 ft		NORTHING 653,480		EASTING 2,573,125									
DRILL RIG/HAMMER EFF./DATE SME9563 CME-550X XX% XX/XX/2017				DRILL METHOD Mud Rotary		HAMMER TYPE Automatic									
DRILLER White, T.J.		START DATE 06/08/17		COMP. DATE 06/09/17		SURFACE WATER DEPTH N/A									
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)	
			0.5ft	0.5ft	0.5ft	0	25	50	75	100					
20	19.4	0.0	1	2	1										19.4
ROADWAY EMBANKMENT TAN, SILTY SAND															
15	15.4	4.0	2	1	2										
10	10.4	9.0	2	2	2										
5	6.7	12.7	2	2	2										
0	1.7	17.7	1	0	1										2.9
ALLUVIAL BROWN AND GRAY, SILTY SAND AND SAND															
-5	-3.3	22.7	2	2	2										
-10	-8.3	27.7	2	4	4										
-15	-13.3	32.7	4	4	7										
-20	-18.3	37.7	2	3	2										
-25	-23.3	42.7	2	3	4										
-30	-28.3	47.7	4	3	5										
-35	-33.3	52.7	9	8	9										
-40	-38.3	57.7	8	5	12										
-45	-43.3	62.7	3	2	5										
-50	-48.3	67.7	2	1	2										
-55	-53.3	72.7	4	3	4										
-60	-58.3	77.7	1	2	3										

WBS 46016.1.1		TIP B-5302		COUNTY BEAUFORT		GEOLOGIST Swartley, J. R.									
SITE DESCRIPTION BRIDGE NO. 3 ON US 17 BUSINESS (-L-) OVER NORFOLK SOUTHERN RAILROAD						GROUND WTR (ft)									
BORING NO. B1-A		STATION 27+94		OFFSET 21 ft LT		ALIGNMENT -L-									
COLLAR ELEV. 19.4 ft		TOTAL DEPTH 129.2 ft		NORTHING 653,480		EASTING 2,573,125									
DRILL RIG/HAMMER EFF./DATE SME9563 CME-550X XX% XX/XX/2017				DRILL METHOD Mud Rotary		HAMMER TYPE Automatic									
DRILLER White, T.J.		START DATE 06/08/17		COMP. DATE 06/09/17		SURFACE WATER DEPTH N/A									
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)	
			0.5ft	0.5ft	0.5ft	0	25	50	75	100					
-60															
Match Line															
-65	-63.3	82.7	1	2	3										
-70	-68.3	87.7	2	1	3										
-75	-73.3	92.7	3	7	7										
-80	-78.3	97.7	5	5	5										
-85	-83.3	102.7	7	4	5										
-90	-88.3	107.7	80	20/0.1											100/0.6
-95	-93.3	112.7	15	16	14										
-100	-98.3	117.7	18	15	15										
-105	-103.3	122.7	10	9	12										
-109.8	-108.3	127.7	12	8	9										
GRAY AND GREEN, CALCAREOUS, CLAYEY SAND (continued)															
GRAY AND GREEN, CALCAREOUS, SANDY SILT															
GRAY AND GREEN, CALCAREOUS, CLAYEY SAND															
COASTAL PLAIN GREEN, SILTY SAND (YORKTOWN FORMATION) GREEN, SANDY SILT															
GRAY, MODERATELY WEATHERED, LIMESTONE (CASTLE HAYNE FORMATION) GRAY, CALCAREOUS, SILTY SAND WITH SHELL FRAGMENTS AND FRIABLE SEAMS (0.1)															
GRAY, CALCAREOUS, SILTY SAND WITH SHELL FRAGMENTS															
Boring Terminated at Elevation -109.8 ft IN COASTAL PLAIN (SILTY SAND)															

NCDOT BORE DOUBLE B5302_GEO_BRDG003.GPJ_NC_DOT.GDT 8/10/17

GEOTECHNICAL BORING REPORT

BORE LOG

WBS 46016.1.1		TIP B-5302		COUNTY BEAUFORT		GEOLOGIST Swartley, J. R.											
SITE DESCRIPTION BRIDGE NO. 3 ON US 17 BUSINESS (-L-) OVER NORFOLK SOUTHERN RAILROAD							GROUND WTR (ft)										
BORING NO. B1-B		STATION 28+49		OFFSET 21 ft RT		ALIGNMENT -L-											
COLLAR ELEV. 18.7 ft		TOTAL DEPTH 128.3 ft		NORTHING 653,497		EASTING 2,573,192											
DRILL RIG/HAMMER EFF./DATE SME9563 CME-550X 88% 08/16/2017			DRILL METHOD Mud Rotary		HAMMER TYPE Automatic												
DRILLER White, T.J.		START DATE 06/06/17		COMP. DATE 06/07/17		SURFACE WATER DEPTH N/A											
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)			
			0.5ft	0.5ft	0.5ft	0	25	50	75	100							
20	18.7	0.0	1	2	1										18.7	GROUND SURFACE	
																	ROADWAY EMBANKMENT
15	15.6	3.1	2	1	2												TAN, SILTY SAND
10	10.6	8.1	1	1	2												
5	6.9	11.8	2	2	2												
0	1.9	16.8	1	1	0												
-5	-3.1	21.8	2	2	3												
-10	-8.1	26.8	5	7	7												
-15	-13.1	31.8	4	6	6												
-20	-18.1	36.8	1	2	2												
-25	-23.1	41.8	2	3	4												
-30	-28.1	46.8	2	4	4												
-35	-33.1	51.8	3	5	8												
-40	-38.1	56.8	9	7	9												
-45	-43.1	61.8	3	3	4												
-50	-48.1	66.8	2	2	1												
-55	-53.1	71.8	2	2	2												
-60	-58.1	76.8	1	2	3												

WBS 46016.1.1		TIP B-5302		COUNTY BEAUFORT		GEOLOGIST Swartley, J. R.											
SITE DESCRIPTION BRIDGE NO. 3 ON US 17 BUSINESS (-L-) OVER NORFOLK SOUTHERN RAILROAD							GROUND WTR (ft)										
BORING NO. B1-B		STATION 28+49		OFFSET 21 ft RT		ALIGNMENT -L-											
COLLAR ELEV. 18.7 ft		TOTAL DEPTH 128.3 ft		NORTHING 653,497		EASTING 2,573,192											
DRILL RIG/HAMMER EFF./DATE SME9563 CME-550X 88% 08/16/2017			DRILL METHOD Mud Rotary		HAMMER TYPE Automatic												
DRILLER White, T.J.		START DATE 06/06/17		COMP. DATE 06/07/17		SURFACE WATER DEPTH N/A											
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)			
			0.5ft	0.5ft	0.5ft	0	25	50	75	100							
-60																	
-65	-63.1	81.8	1	2	5												
-70	-68.1	86.8	2	1	3												
-75	-73.1	91.8	3	3	5												
-80	-78.1	96.8	7	4	7												
-85	-83.1	101.8	3	2	4												
-90	-88.1	106.8	41	59/0.2													
-95	-93.1	111.8	26	17	16												
-100	-98.1	116.8	17	17	17												
-105	-103.1	121.8	10	8	10												
	-108.1	126.8	8	7	8												

NCDOT BORE DOUBLE B5302_GEO_BRDG003.GPJ NC_DOT_GDT_8/10/17

GEOTECHNICAL BORING REPORT

BORE LOG

WBS 46016.1.1		TIP B-5302		COUNTY BEAUFORT		GEOLOGIST Swartley, J. R.	
SITE DESCRIPTION BRIDGE NO. 3 ON US 17 BUSINESS (-L-) OVER NORFOLK SOUTHERN RAILROAD							GROUND WTR (ft)
BORING NO. B2-A		STATION 29+26		OFFSET 21 ft LT		ALIGNMENT -L-	
COLLAR ELEV. 20.5 ft		TOTAL DEPTH 130.2 ft		NORTHING 653,583		EASTING 2,573,207	
DRILL RIG/HAMMER EFF./DATE SME9563 CME-550X 88% 08/16/2017				DRILL METHOD Mud Rotary		HAMMER TYPE Automatic	
DRILLER White, T.J.		START DATE 06/07/17		COMP. DATE 06/08/17		SURFACE WATER DEPTH N/A	

ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)		
			0.5ft	0.5ft	0.5ft	0	25	50	75	100						
25																
20	20.5	0.0	1	1	2									20.5	GROUND SURFACE ROADWAY EMBANKMENT TAN, SILTY SAND	0.0
15	15.5	5.0	2	1	2											
10	11.8	8.7	1	2	2											
5	6.8	13.7	2	2	2											
0	1.8	18.7	2	1	3											
-5	-3.2	23.7	1	2	5											
-10	-8.2	28.7	9	8	11											
-15	-13.2	33.7	6	10	12											
-20	-18.2	38.7	1	3	2											
-25	-23.2	43.7	1	1	2											
-30	-28.2	48.7	3	3	3											
-35	-33.2	53.7	6	6	5											
-40	-38.2	58.7	7	7	12											
-45	-43.2	63.7	4	4	3											
-50	-48.2	68.7	2	2	2											
-55	-53.2	73.7	4	2	5											

ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)		
			0.5ft	0.5ft	0.5ft	0	25	50	75	100						
-55																
-60	-58.2	78.7	2	2	2											
-65	-63.2	83.7	3	2	3											
-70	-68.2	88.7	2	2	4											
-75	-73.2	93.7	3	3	10											
-80	-78.2	98.7	17	8	12											
-85	-83.2	103.7	9	8	10											
-90	-88.2	108.7	10	90/0.2												
-95	-93.2	113.7	25	20	23											
-100	-98.2	118.7	13	19	18											
-105	-103.2	123.7	12	16	12											
-109.7	-108.2	128.7	9	10	10											

WBS 46016.1.1		TIP B-5302		COUNTY BEAUFORT		GEOLOGIST Swartley, J. R.	
SITE DESCRIPTION BRIDGE NO. 3 ON US 17 BUSINESS (-L-) OVER NORFOLK SOUTHERN RAILROAD							GROUND WTR (ft)
BORING NO. B2-A		STATION 29+26		OFFSET 21 ft LT		ALIGNMENT -L-	
COLLAR ELEV. 20.5 ft		TOTAL DEPTH 130.2 ft		NORTHING 653,583		EASTING 2,573,207	
DRILL RIG/HAMMER EFF./DATE SME9563 CME-550X 88% 08/16/2017				DRILL METHOD Mud Rotary		HAMMER TYPE Automatic	
DRILLER White, T.J.		START DATE 06/07/17		COMP. DATE 06/08/17		SURFACE WATER DEPTH N/A	

ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)		
			0.5ft	0.5ft	0.5ft	0	25	50	75	100						
-55																
-60	-58.2	78.7	2	2	2											
-65	-63.2	83.7	3	2	3											
-70	-68.2	88.7	2	2	4											
-75	-73.2	93.7	3	3	10											
-80	-78.2	98.7	17	8	12											
-85	-83.2	103.7	9	8	10											
-90	-88.2	108.7	10	90/0.2												
-95	-93.2	113.7	25	20	23											
-100	-98.2	118.7	13	19	18											
-105	-103.2	123.7	12	16	12											
-109.7	-108.2	128.7	9	10	10											

ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)		
			0.5ft	0.5ft	0.5ft	0	25	50	75	100						
-55																
-60	-58.2	78.7	2	2	2											
-65	-63.2	83.7	3	2	3											
-70	-68.2	88.7	2	2	4											
-75	-73.2	93.7	3	3	10											
-80	-78.2	98.7	17	8	12											
-85	-83.2	103.7	9	8	10											
-90	-88.2	108.7	10	90/0.2												
-95	-93.2	113.7	25	20	23											
-100	-98.2	118.7	13	19	18											
-105	-103.2	123.7	12	16	12											
-109.7	-108.2	128.7	9	10	10											

NCDOT BORE DOUBLE B5302_GEO_BRDG003.GPJ_NC_DOT.GDT 8/10/17

GEOTECHNICAL BORING REPORT BORE LOG

WBS 46016.1.1		TIP B-5302		COUNTY BEAUFORT		GEOLOGIST Swartley, J. R.									
SITE DESCRIPTION BRIDGE NO. 3 ON US 17 BUSINESS (-L-) OVER NORFOLK SOUTHERN RAILROAD						GROUND WTR (ft)									
BORING NO. B2-B		STATION 29+80		OFFSET 21 ft RT		ALIGNMENT -L-									
COLLAR ELEV. 23.2 ft		TOTAL DEPTH 132.9 ft		NORTHING 653,599		EASTING 2,573,274									
DRILL RIG/HAMMER EFF./DATE SME9563 CME-550X 88% 08/16/2017				DRILL METHOD Mud Rotary		HAMMER TYPE Automatic									
DRILLER White, T.J.		START DATE 05/31/17		COMP. DATE 06/01/17		SURFACE WATER DEPTH N/A									
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)	
			0.5ft	0.5ft	0.5ft	0	25	50	75	100					
25	23.2	0.0													23.2
			WOH			1	2								
20	19.2	4.0													
			2	2	2										
15	15.5	7.7													
			4	3	3										
10	11.8	11.4													
			2	2	2										
5	6.8	16.4													
			2	3	2										
0	1.8	21.4													
			2	1	2										
-5	-3.2	26.4													
			2	2	4										
-10	-8.2	31.4													
			4	7	6										
-15	-13.2	36.4													
			6	8	7										
-20	-18.2	41.4													
			2	2	2										
-25	-23.2	46.4													
			1	2	3										
-30	-28.2	51.4													
			4	3	4										
-35	-33.2	56.4													
			5	9	7										
-40	-38.2	61.4													
			5	7	5										
-45	-43.2	66.4													
			2	3	2										
-50	-48.2	71.4													
			1	2	1										
-55	-53.2	76.4													
			3	2	1										

NCDOT BORE DOUBLE B5302_GEO_BRDG003.GPJ_NC_DOT.GDT 8/10/17

WBS 46016.1.1		TIP B-5302		COUNTY BEAUFORT		GEOLOGIST Swartley, J. R.										
SITE DESCRIPTION BRIDGE NO. 3 ON US 17 BUSINESS (-L-) OVER NORFOLK SOUTHERN RAILROAD						GROUND WTR (ft)										
BORING NO. B2-B		STATION 29+80		OFFSET 21 ft RT		ALIGNMENT -L-										
COLLAR ELEV. 23.2 ft		TOTAL DEPTH 132.9 ft		NORTHING 653,599		EASTING 2,573,274										
DRILL RIG/HAMMER EFF./DATE SME9563 CME-550X 88% 08/16/2017				DRILL METHOD Mud Rotary		HAMMER TYPE Automatic										
DRILLER White, T.J.		START DATE 05/31/17		COMP. DATE 06/01/17		SURFACE WATER DEPTH N/A										
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)		
			0.5ft	0.5ft	0.5ft	0	25	50	75	100						
-55																
						Match Line										
-60	-58.2	81.4				3	1	2								
-65	-63.2	86.4				2	1	2								
-70	-68.2	91.4				1	2	3								
-75	-73.2	96.4				2	3	3								
-80	-78.2	101.4				4	4	5								
-85	-83.2	106.4				5	4	6								
-90	-88.2	111.4				12	88/0.3				100/0.8					
-95	-93.2	116.4				25	21	15								
-100	-98.2	121.4				31	21	16								
-105	-103.2	126.4				9	8	11								
-110	-108.2	131.4				9	10	9								

Match Line

GRAY AND GREEN, CALCAREOUS, CLAYEY SAND AND SILTY SAND (continued)

-66.8 90.0

-71.8 95.0

GREEN, SANDY SILT

-76.8 100.0

GREEN AND GRAY, SILTY SAND

-87.3 110.5

COASTAL PLAIN
GRAY, MODERATELY TO SEVERLY WEATHERED, LIMESTONE (CASTLE HAYNE FORMATION)

-90.5 113.7

GRAY, CALCAREOUS, SILTY SAND WITH SOME FRIABLE TO MODERATELY INDURATED SEAMS (<0.1)

-109.7 132.9

Boring Terminated at Elevation -109.7 ft IN COASTAL PLAIN (SILTY SAND)

GEOTECHNICAL BORING REPORT

BORE LOG

WBS 46016.1.1		TIP B-5302		COUNTY BEAUFORT		GEOLOGIST Swartley, J. R.										
SITE DESCRIPTION BRIDGE NO. 3 ON US 17 BUSINESS (-L-) OVER NORFOLK SOUTHERN RAILROAD							GROUND WTR (ft)									
BORING NO. EB2-A		STATION 29+92		OFFSET 21 ft LT		ALIGNMENT -L-										
COLLAR ELEV. 29.3 ft		TOTAL DEPTH 139.3 ft		NORTHING 653,634		EASTING 2,573,249										
DRILL RIG/HAMMER EFF./DATE SME9563 CME-550X 88% 08/16/2017			DRILL METHOD Mud Rotary		HAMMER TYPE Automatic											
DRILLER White, T.J.		START DATE 05/24/17		COMP. DATE 05/25/17		SURFACE WATER DEPTH N/A										
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)		
			0.5ft	0.5ft	0.5ft	0	25	50	75	100						
30																
	28.5	0.8	23	19	8											29.3
																28.5
	25.3	4.0	2	2	1											
	21.5	7.8	1	1	2											
	16.5	12.8	2	3	3											18.3
	11.5	17.8	1	2	2											
	6.5	22.8	1	1	2											
	1.5	27.8	1	1	2											
	-3.5	32.8	1	3	5											
	-8.5	37.8	3	4	5											
	-13.5	42.8	6	8	9											
	-18.5	47.8	1	2	3											
	-23.5	52.8	1	2	3											
	-28.5	57.8	2	3	3											
	-33.5	62.8	6	9	6											
	-38.5	67.8	10	7	5											
	-43.5	72.8	3	3	5											
	-48.5	77.8	2	2	3											

WBS 46016.1.1		TIP B-5302		COUNTY BEAUFORT		GEOLOGIST Swartley, J. R.										
SITE DESCRIPTION BRIDGE NO. 3 ON US 17 BUSINESS (-L-) OVER NORFOLK SOUTHERN RAILROAD							GROUND WTR (ft)									
BORING NO. EB2-A		STATION 29+92		OFFSET 21 ft LT		ALIGNMENT -L-										
COLLAR ELEV. 29.3 ft		TOTAL DEPTH 139.3 ft		NORTHING 653,634		EASTING 2,573,249										
DRILL RIG/HAMMER EFF./DATE SME9563 CME-550X 88% 08/16/2017			DRILL METHOD Mud Rotary		HAMMER TYPE Automatic											
DRILLER White, T.J.		START DATE 05/24/17		COMP. DATE 05/25/17		SURFACE WATER DEPTH N/A										
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)		
			0.5ft	0.5ft	0.5ft	0	25	50	75	100						
-50																
	-53.5	82.8	1	2	2											
	-58.5	87.8	1	2	2											
	-63.5	92.8	1	1	4											
	-68.5	97.8	2	2	4											
	-73.5	102.8	3	4	5											
	-78.5	107.8	4	3	6											
	-83.5	112.8	3	7	4											
	-88.5	117.8	100/0.3													
	-93.5	122.8	19	20	15											
	-98.5	127.8	35	18	16											
	-103.5	132.8	7	9	11											
	-108.5	137.8	14	18	13											

NCDOT BORE DOUBLE B5302_GEO_BRDG003.GPJ_NC_DOT.GDT 8/10/17

GEOTECHNICAL BORING REPORT

BORE LOG

WBS 46016.1.1		TIP B-5302		COUNTY BEAUFORT		GEOLOGIST Swartley, J. R.	
SITE DESCRIPTION BRIDGE NO. 3 ON US 17 BUSINESS (-L-) OVER NORFOLK SOUTHERN RAILROAD							GROUND WTR (ft)
BORING NO. EB2-B		STATION 30+37		OFFSET 21 ft RT		ALIGNMENT -L-	
COLLAR ELEV. 29.2 ft		TOTAL DEPTH 139.2 ft		NORTHING 653,643		EASTING 2,573,309	
DRILL RIG/HAMMER EFF./DATE SME9563 CME-550X 88% 08/16/2017				DRILL METHOD Mud Rotary		HAMMER TYPE Automatic	
DRILLER White, T.J.		START DATE 06/01/17		COMP. DATE 06/02/17		SURFACE WATER DEPTH N/A	

ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG MOI	LOG SOIL AND ROCK DESCRIPTION	DEPTH (ft)	
			0.5ft	0.5ft	0.5ft	0	25	50	75	100					
30															
	28.5	0.7		26	20	9									
	25.2	4.0		6	8	7									
	21.5	7.7		7	7	5									
	16.5	12.7		2	3	2									
	11.5	17.7		3	3	4									
	6.5	22.7		1	2	2									
	1.5	27.7		1	1	1									
	-3.5	32.7		3	5	5									
	-8.5	37.7		4	4	5									
	-13.5	42.7		6	7	8									
	-18.5	47.7		1	2	3									
	-23.5	52.7		1	2	2									
	-28.5	57.7		3	3	4									
	-33.5	62.7		6	9	7									
	-38.5	67.7		16	11	7									
	-43.5	72.7		3	3	3									
	-48.5	77.7		2	1	1									

ELEV. (ft)	SOIL AND ROCK DESCRIPTION	DEPTH (ft)
29.2	GROUND SURFACE	0.0
28.5	ROADWAY EMBANKMENT (PAVEMENT)	0.7
	TAN, SILTY SAND	
8.2	ALLUVIAL BROWN, SILTY SAND	21.0
-4.8	BLACK MUCK	34.0
-6.8	BROWN, GRAY AND WHITE, SAND AND COARSE SAND	36.0
-11.8	COASTAL PLAIN GREEN, SILTY SAND (YORKTOWN FORMATION)	46.0
-16.8	GREEN, SANDY SILT	51.0
-26.8	GRAY, CALCAREOUS, CLAYEY SAND	56.0
-31.8	GRAY, CALCAREOUS, CLAYEY SAND WITH SOME FRIABLE TO MODERATELY INDURATED SEAMS (<0.1)	61.0
-41.8	GRAY AND GREEN, CALCAREOUS, CLAYEY SAND	71.0

WBS 46016.1.1		TIP B-5302		COUNTY BEAUFORT		GEOLOGIST Swartley, J. R.	
SITE DESCRIPTION BRIDGE NO. 3 ON US 17 BUSINESS (-L-) OVER NORFOLK SOUTHERN RAILROAD							GROUND WTR (ft)
BORING NO. EB2-B		STATION 30+37		OFFSET 21 ft RT		ALIGNMENT -L-	
COLLAR ELEV. 29.2 ft		TOTAL DEPTH 139.2 ft		NORTHING 653,643		EASTING 2,573,309	
DRILL RIG/HAMMER EFF./DATE SME9563 CME-550X 88% 08/16/2017				DRILL METHOD Mud Rotary		HAMMER TYPE Automatic	
DRILLER White, T.J.		START DATE 06/01/17		COMP. DATE 06/02/17		SURFACE WATER DEPTH N/A	

ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG MOI	LOG SOIL AND ROCK DESCRIPTION	DEPTH (ft)	
			0.5ft	0.5ft	0.5ft	0	25	50	75	100					
-50															
	-53.5	82.7	2	2	2										
	-58.5	87.7	2	0	1										
	-63.5	92.7	1	1	2										
	-68.5	97.7	1	2	1										
	-73.5	102.7	3	2	3										
	-78.5	107.7	3	2	3										
	-83.5	112.7	6	7	2										
	-88.5	117.7	80	20/0.1											
	-93.5	122.7	12	15	16										
	-98.5	127.7	25	20	17										
	-103.5	132.7	7	8	7										
	-108.5	137.7	10	11	10										

ELEV. (ft)	SOIL AND ROCK DESCRIPTION	DEPTH (ft)
-71.8	GRAY AND GREEN, CALCAREOUS, CLAYEY SAND (continued)	101.0
-71.8	GRAY AND GREEN, SANDY SILT	101.0
-81.8	GRAY AND GREEN, CALCAREOUS, CLAYEY SAND WITH SOME FRIABLE TO MODERATELY INDURATED SEAMS (<0.1')	111.0
-88.3	COASTAL PLAIN GRAY, MODERATELY TO SEVERLY WEATHERED, LIMESTONE (CASTLE HAYNE FORMATION) GRAY, CALCAREOUS, CLAYEY SAND WITH SHELL FRAGMENTS AND SOME MODERATELY INDURATED SEAMS (<0.1)	117.5
-90.3	GRAY, CALCAREOUS, SILTY SAND WITH SHELL FRAGMENTS	119.5
-96.8	GRAY, CALCAREOUS, SILTY SAND WITH SHELL FRAGMENTS	126.0
-110.0	Boring Terminated at Elevation -110.0 ft IN COASTAL PLAIN (SILTY SAND)	139.2

NCDOT BORE DOUBLE B5302_GEO_BRDG003.GPJ_NC_DOT.GDT 8/10/17

SUMMARY OF LABORATORY TEST DATA
Soil Classification and Gradation



Quality Assurance

S&ME, Inc. Raleigh, 3201 Spring Forest Road, Raleigh, North Carolina 27616

S&ME Project #:	6235-17-018	Date Report	6/15/2017
State Project No.:	46016.1.1	County:	Beaufort
Federal ID No.:		Date Tested	6/5 - 6/10/17
Project Name:	Br. No. 3 on US 17 Business over Norfolk Southern Railroad		
Client Name:	NCDOT Geotechnical Engineering Unit	Client Address:	Raleigh, NC
TIP No.:	B-5302		

Sample No.	Station #:	Offset	Alignment	Sample Depth (ft)	AASHTO Classification	Total % Passing Sieve #					Total Mortar Fraction (%)				LL	PL	PI	Organic Content %	Moist. %	
						10	40	60	200	270	Coarse Sand	Fine Sand	Silt	Clay						
						SS-1	29+92	21' LT	L	12.8-14.3	A-3 (0)	99	53	22						8.2
SS-2	29+92	21' LT	L	32.8-33.3	A-2-4 (0)	99	66	50	31.8	29.9	50	20	27	3	33	0	N.P.	36.7	189.3	
SS-3	29+92	21' LT	L	37.8-39.3	A-1-b (0)	88	25	7	1.3	1.1	92	7	1	0	16	0	N.P.	ND	ND	
SS-4	29+92	21' LT	L	47.8-49.3	A-2-4 (0)	100	91	76	32.9	19.8	24	56	12	8	24	22	2	ND	ND	
SS-5	29+92	21' LT	L	52.8-54.3	A-2-4 (0)	100	77	56	30.6	27.2	44	29	14	13	28	19	9	ND	23.4	
SS-6	29+92	21' LT	L	57.8-59.3	A-2-4 (0)	99	85	75	33.3	32.1	24	44	17	15	19	16	3	ND	ND	
SS-7	29+92	21' LT	L	97.8-99.3	A-2-4 (0)	99	96	90	29.8	27.3	9	63	12	16	23	22	1	ND	ND	
SS-8	29+92	21' LT	L	122.8-124.3	A-2-4 (0)	87	62	47	21.1	18.7	46	33	12	9	15	0	N.P.	ND	ND	
SS-9	29+80	21' RT	L	91.4-92.9	A-2-4 (0)	96	92	85	29.5	27.2	11	61	11	17	24	23	1	ND	ND	
SS-10	29+80	21' RT	L	96.4-97.9	A-4 (0)	95	89	85	39.0	35.2	11	52	16	21	27	22	5	ND	ND	
SS-11	30+37	21' RT	L	107.7-109.2	A-4 (0)	98	90	83	37.4	35.1	15	49	14	22	27	21	6	ND	29.2	

References / Comments / Deviations: ND=Not Determined.

- AASHTO T88: Particle Size Analysis of Soils as Modified by the NCDOT
- AASHTO T89: Determining the Liquid Limit of Soils
- AASHTO T90: Determining the Plastic Limit & Plasticity Index of Soils
- AASHTO T265: Laboratory Determination of Moisture Content of Soils
- AASHTO M145: The Classification of Soils and Soil Aggregate Mixtures for Highway Construction Purposes

Mal Krajan, ET
Technician Name:


Signature

104-01-0703
Certification #

Jarett Swartley
Technical Responsibility:

Project Manager
Position

This report shall not be reproduced, except in full, without the written approval of S&ME, Inc.

SITE PHOTOGRAPH

Bridge No. 3 on -L- (US 17 Business) over Norfolk Southern RR



Looking South towards End Bent 1