

REFERENCE: U-2714

PROJECT: 38979

SEE SHEET 3 FOR PLAN SHEET LAYOUT  
AT TIME OF INVESTIGATION

**STATE OF NORTH CAROLINA**  
DEPARTMENT OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
GEOTECHNICAL ENGINEERING UNIT

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	U-2714	1	31

**CONTENTS**

<u>LINE</u>	<u>STATION</u>	<u>PLAN</u>	<u>PROFILE</u>
-L-	10+00 - 91+64	4-11	12-15
-Y4-	10+00 - 21+32	6,11	16
-Y5-	10+00 - 17+54	6	16

**CROSS SECTIONS**

<u>LINE</u>	<u>STATION</u>	<u>SHEETS</u>
-L-	12+00 - 89+00	17-29
-Y4-	17+50	30
-Y5-	16+50	31

# ROADWAY SUBSURFACE INVESTIGATION

COUNTY WAYNE  
PROJECT DESCRIPTION US 117A (N. WILLIAM ST) FROM NORTH  
OF US 70 TO SR 1571 (TOMMY'S RD)

## INVENTORY

**CAUTION NOTICE**

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT (919) 707-6850. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

- NOTES:
1. THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.
  2. BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

PERSONNEL

B. KEANEY

C. JONES

B. HOWEY

C. TAYLOR

M. MORGAN

**HDR ENGINEERING, INC.**

INVESTIGATED BY HDR-ICA


DRAWN BY CBJ

CHECKED BY ECH

SUBMITTED BY **HDR ENGINEERING, INC.**

DATE 9/2016

**DOCUMENT NOT CONSIDERED FINAL  
UNLESS ALL SIGNATURES COMPLETED**



<p style="text-align: center;">SIGNATURE _____</p>	<p style="text-align: center;">DATE _____</p>
--	---

**NORTH CAROLINA DEPARTMENT OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
GEOTECHNICAL ENGINEERING UNIT  
SUBSURFACE INVESTIGATION  
SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS**

SOIL DESCRIPTION										GRADATION										ROCK DESCRIPTION										TERMS AND DEFINITIONS																																																																																																																																																		
SOIL IS CONSIDERED UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER AND YIELD LESS THAN 100 BLOWS PER FOOT ACCORDING TO THE STANDARD PENETRATION TEST (AASHTO T 206, ASTM D1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY INCLUDE THE FOLLOWING: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. FOR EXAMPLE, <i>VERY STIFF, GRAY, SILTY CLAY, MOIST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC, A-7-6</i>										WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. UNIFORMLY GRADED - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES.										HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED, AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS IN NON-COASTAL PLAIN MATERIAL. THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:										ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER. AQUIFER - A WATER BEARING FORMATION OR STRATA. ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND. ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC. ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE. CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE. COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE. CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK. DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL. DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH. FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE. FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES. FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLOADED FROM PARENT MATERIAL. FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM. FORMATION (FM) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD. JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED. LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT. LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS. MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS. MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM. RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK. ROCK QUALITY DESIGNATION (ROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. SAPROLITE (SAP.) - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK. SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS. SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE. STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (IN OR BPF) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE. STRATA ROCK QUALITY DESIGNATION (SROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.																																																																																																																																																		
SOIL LEGEND AND AASHTO CLASSIFICATION										ANGULARITY OF GRAINS										WEATHERED ROCK (WR)										CALCAREOUS (CALC.)																																																																																																																																																		
<table border="1"> <tr> <th>GENERAL CLASS.</th> <th colspan="5">GRANULAR MATERIALS (&lt;= 35% PASSING #200)</th> <th colspan="5">SILT-CLAY MATERIALS (&gt; 35% PASSING #200)</th> <th colspan="5">ORGANIC MATERIALS</th> </tr> <tr> <th>GROUP CLASS.</th> <th>A-1</th> <th>A-3</th> <th>A-2</th> <th>A-2-4</th> <th>A-2-5</th> <th>A-2-6</th> <th>A-2-7</th> <th>A-4</th> <th>A-5</th> <th>A-6</th> <th>A-7</th> <th>A-1, A-2</th> <th>A-3</th> <th>A-4, A-5</th> <th>A-6, A-7</th> <th></th> </tr> <tr> <th>SYMBOL</th> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <th>% PASSING #10 #40 #200</th> <td>50 MX 30 MX 15 MX</td> <td>50 MX 25 MX</td> <td>51 MN 35 MX 35 MX</td> <td>40 MX 35 MX</td> <td>41 MN 35 MX</td> <td>41 MN 35 MX</td> <td>41 MN 35 MX</td> <td>40 MN 36 MN</td> <td>41 MN 36 MN</td> <td>40 MN 36 MN</td> <td>41 MN 36 MN</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <th>MATERIAL PASSING #40 LL PI</th> <td colspan="2">-</td> <td>NP</td> <td>40 MX 10 MX</td> <td>41 MN 10 MX</td> <td>41 MN 11 MN</td> <td>41 MN 11 MN</td> <td>40 MN 10 MX</td> <td>41 MN 10 MX</td> <td>40 MN 11 MN</td> <td>41 MN 11 MN</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <th>GROUP INDEX</th> <td>0</td> <td>0</td> <td>0</td> <td>4 MX</td> <td>8 MX</td> <td>12 MX</td> <td>16 MX</td> <td>NO MX</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <th>USUAL TYPES OF MAJOR MATERIALS</th> <td colspan="2">STONE FRAGS. GRAVEL, AND SAND</td> <td>FINE SAND</td> <td colspan="3">SILTY OR CLAYEY GRAVEL AND SAND</td> <td>SILTY SOILS</td> <td colspan="2">CLAYEY SOILS</td> <td colspan="2">SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER</td> <td colspan="2">HIGHLY ORGANIC SOILS</td> <td colspan="2"></td> <td></td> </tr> <tr> <th>GEN. RATING AS SUBGRADE</th> <td colspan="5">EXCELLENT TO GOOD</td> <td colspan="5">FAIR TO POOR</td> <td>FAIR TO POOR</td> <td>POOR</td> <td>UNSATURABLE</td> <td colspan="5"></td> </tr> </table>										GENERAL CLASS.	GRANULAR MATERIALS (<= 35% PASSING #200)					SILT-CLAY MATERIALS (> 35% PASSING #200)					ORGANIC MATERIALS					GROUP CLASS.	A-1	A-3	A-2	A-2-4	A-2-5	A-2-6	A-2-7	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7		SYMBOL																	% PASSING #10 #40 #200	50 MX 30 MX 15 MX	50 MX 25 MX	51 MN 35 MX 35 MX	40 MX 35 MX	41 MN 35 MX	41 MN 35 MX	41 MN 35 MX	40 MN 36 MN	41 MN 36 MN	40 MN 36 MN	41 MN 36 MN						MATERIAL PASSING #40 LL PI	-		NP	40 MX 10 MX	41 MN 10 MX	41 MN 11 MN	41 MN 11 MN	40 MN 10 MX	41 MN 10 MX	40 MN 11 MN	41 MN 11 MN						GROUP INDEX	0	0	0	4 MX	8 MX	12 MX	16 MX	NO MX									USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS. GRAVEL, AND SAND		FINE SAND	SILTY OR CLAYEY GRAVEL AND SAND			SILTY SOILS	CLAYEY SOILS		SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER		HIGHLY ORGANIC SOILS					GEN. RATING AS SUBGRADE	EXCELLENT TO GOOD					FAIR TO POOR					FAIR TO POOR	POOR	UNSATURABLE						THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS IS DESIGNATED BY THE TERMS: ANGULAR, SUBANGULAR, SUBROUNDED, OR ROUNDED.										NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT N VALUES > 100 BLOWS PER FOOT IF TESTED.										FINE TO COARSE GRAIN IGNEOUS AND METAMORPHIC ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES GRANITE, GNEISS, GABBRO, SCHIST, ETC.									
GENERAL CLASS.	GRANULAR MATERIALS (<= 35% PASSING #200)					SILT-CLAY MATERIALS (> 35% PASSING #200)					ORGANIC MATERIALS																																																																																																																																																																					
GROUP CLASS.	A-1	A-3	A-2	A-2-4	A-2-5	A-2-6	A-2-7	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7																																																																																																																																																																	
SYMBOL																																																																																																																																																																																
% PASSING #10 #40 #200	50 MX 30 MX 15 MX	50 MX 25 MX	51 MN 35 MX 35 MX	40 MX 35 MX	41 MN 35 MX	41 MN 35 MX	41 MN 35 MX	40 MN 36 MN	41 MN 36 MN	40 MN 36 MN	41 MN 36 MN																																																																																																																																																																					
MATERIAL PASSING #40 LL PI	-		NP	40 MX 10 MX	41 MN 10 MX	41 MN 11 MN	41 MN 11 MN	40 MN 10 MX	41 MN 10 MX	40 MN 11 MN	41 MN 11 MN																																																																																																																																																																					
GROUP INDEX	0	0	0	4 MX	8 MX	12 MX	16 MX	NO MX																																																																																																																																																																								
USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS. GRAVEL, AND SAND		FINE SAND	SILTY OR CLAYEY GRAVEL AND SAND			SILTY SOILS	CLAYEY SOILS		SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER		HIGHLY ORGANIC SOILS																																																																																																																																																																				
GEN. RATING AS SUBGRADE	EXCELLENT TO GOOD					FAIR TO POOR					FAIR TO POOR	POOR	UNSATURABLE																																																																																																																																																																			
CONSISTENCY OR DENSENESS										MINERALOGICAL COMPOSITION										NON-CRYSTALLINE ROCK (NCR)										COASTAL PLAIN SEDIMENTARY ROCK (CP)																																																																																																																																																		
<table border="1"> <tr> <th>PRIMARY SOIL TYPE</th> <th>COMPACTNESS OR CONSISTENCY</th> <th>RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)</th> <th>RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT<sup>2</sup>)</th> </tr> <tr> <td>GENERALLY GRANULAR MATERIAL (NON-COHESSIVE)</td> <td>VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE</td> <td>&lt; 4 4 TO 10 10 TO 30 30 TO 50 &gt; 50</td> <td>N/A</td> </tr> <tr> <td>GENERALLY SILT-CLAY MATERIAL (COHESIVE)</td> <td>VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD</td> <td>&lt; 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 &gt; 30</td> <td>&lt; 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 &gt; 4</td> </tr> </table>										PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT <sup>2</sup> )	GENERALLY GRANULAR MATERIAL (NON-COHESSIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	< 4 4 TO 10 10 TO 30 30 TO 50 > 50	N/A	GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30	< 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4	MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHEN THEY ARE CONSIDERED OF SIGNIFICANCE.										FINE TO COARSE GRAIN METAMORPHIC AND NON-COASTAL PLAIN SEDIMENTARY ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES PHYLLITE, SLATE, SANDSTONE, ETC.										COASTAL PLAIN SEDIMENTS CEMENTED INTO ROCK, BUT MAY NOT YIELD SPT REFUSAL. ROCK TYPE INCLUDES LIMESTONE, SANDSTONE, CEMENTED SHELL BEDS, ETC.																																																																																																																																						
PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT <sup>2</sup> )																																																																																																																																																																													
GENERALLY GRANULAR MATERIAL (NON-COHESSIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	< 4 4 TO 10 10 TO 30 30 TO 50 > 50	N/A																																																																																																																																																																													
GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30	< 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4																																																																																																																																																																													
TEXTURE OR GRAIN SIZE										COMPRESSION										WEATHERING										GROUND WATER																																																																																																																																																		
<table border="1"> <tr> <th>U.S. STD. SIEVE SIZE OPENING (MM)</th> <th>4</th> <th>10</th> <th>40</th> <th>60</th> <th>200</th> <th>270</th> </tr> <tr> <td></td> <td>4.76</td> <td>2.00</td> <td>0.42</td> <td>0.25</td> <td>0.075</td> <td>0.053</td> </tr> <tr> <th>BOULDER (BLDR.)</th> <th>COBBLE (COB.)</th> <th>GRAVEL (GR.)</th> <th>COARSE SAND (CSE. SD.)</th> <th>FINE SAND (F SD.)</th> <th>SILT (SL.)</th> <th>CLAY (CL.)</th> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <th>GRAIN SIZE</th> <th>MM</th> <th>305</th> <th>75</th> <th>2.0</th> <th>0.25</th> <th>0.05</th> <th>0.005</th> </tr> <tr> <td></td> <td>IN.</td> <td>12</td> <td>3</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>										U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270		4.76	2.00	0.42	0.25	0.075	0.053	BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE. SD.)	FINE SAND (F SD.)	SILT (SL.)	CLAY (CL.)								GRAIN SIZE	MM	305	75	2.0	0.25	0.05	0.005		IN.	12	3					SLIGHTLY COMPRESSIBLE LL < 31 MODERATELY COMPRESSIBLE LL = 31 - 50 HIGHLY COMPRESSIBLE LL > 50										FRESH ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING. ROCK RINGS UNDER HAMMER IF CRYSTALLINE. VERY SLIGHT (V SL.) ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN. CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF OF A CRYSTALLINE NATURE. SLIGHT (SL.) ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO 1 INCH. OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR CRYSTALS ARE DULL AND DISCOLORED. CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS. MODERATE (MOD.) SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY. ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED WITH FRESH ROCK. MODERATELY SEVERE (MOD. SEV.) ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK. ROCK GIVES "CLUNK" SOUND WHEN STRUCK. IF TESTED, WOULD YIELD SPT REFUSAL SEVERE (SEV.) ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC CLEAR AND EVIDENT BUT REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN. IF TESTED, WOULD YIELD SPT N VALUES > 100 BPF VERY SEVERE (V SEV.) ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC ELEMENTS ARE DISCERNIBLE BUT MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK REMAINING. SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE THAT ONLY MINOR VESTIGES OF ORIGINAL ROCK FABRIC REMAIN. IF TESTED, WOULD YIELD SPT N VALUES < 100 BPF COMPLETE ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.										WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING STATIC WATER LEVEL AFTER 24 HOURS PERCHED WATER, SATURATED ZONE, OR WATER BEARING STRATA SPRING OR SEEP																																																																																																						
U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270																																																																																																																																																																										
	4.76	2.00	0.42	0.25	0.075	0.053																																																																																																																																																																										
BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE. SD.)	FINE SAND (F SD.)	SILT (SL.)	CLAY (CL.)																																																																																																																																																																										
GRAIN SIZE	MM	305	75	2.0	0.25	0.05	0.005																																																																																																																																																																									
	IN.	12	3																																																																																																																																																																													
SOIL MOISTURE - CORRELATION OF TERMS										PERCENTAGE OF MATERIAL										MISCELLANEOUS SYMBOLS										RECOMMENDATION SYMBOLS																																																																																																																																																		
<table border="1"> <tr> <th>SOIL MOISTURE SCALE (ATTERBERG LIMITS)</th> <th>FIELD MOISTURE DESCRIPTION</th> <th>GUIDE FOR FIELD MOISTURE DESCRIPTION</th> </tr> <tr> <td>LL - LIQUID LIMIT</td> <td>- SATURATED - (SAT.)</td> <td>USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE</td> </tr> <tr> <td>PL - PLASTIC LIMIT</td> <td>- WET - (W)</td> <td>SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td>OM - OPTIMUM MOISTURE SHRINKAGE LIMIT</td> <td>- MOIST - (M)</td> <td>SOLID; AT OR NEAR OPTIMUM MOISTURE</td> </tr> <tr> <td>SL - SHRINKAGE LIMIT</td> <td>- DRY - (D)</td> <td>REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td> </tr> </table>										SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION	LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE	PL - PLASTIC LIMIT	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE	OM - OPTIMUM MOISTURE SHRINKAGE LIMIT	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE	SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE	<table border="1"> <tr> <th>ORGANIC MATERIAL</th> <th>GRANULAR SOILS</th> <th>SILT - CLAY SOILS</th> <th>OTHER MATERIAL</th> </tr> <tr> <td>TRACE OF ORGANIC MATTER</td> <td>2 - 3%</td> <td>3 - 5%</td> <td>TRACE 1 - 10%</td> </tr> <tr> <td>LITTLE ORGANIC MATTER</td> <td>3 - 5%</td> <td>5 - 12%</td> <td>LITTLE 10 - 20%</td> </tr> <tr> <td>MODERATELY ORGANIC</td> <td>5 - 10%</td> <td>12 - 20%</td> <td>SOME 20 - 35%</td> </tr> <tr> <td>HIGHLY ORGANIC</td> <td>&gt; 10%</td> <td>&gt; 20%</td> <td>HIGHLY 35% AND ABOVE</td> </tr> </table>										ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL	TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE 1 - 10%	LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE 10 - 20%	MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME 20 - 35%	HIGHLY ORGANIC	> 10%	> 20%	HIGHLY 35% AND ABOVE	ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION SOIL SYMBOL ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT INFERRED SOIL BOUNDARY INFERRED ROCK LINE ALLUVIAL SOIL BOUNDARY										DIP & DIP DIRECTION OF ROCK STRUCTURES TEST BORING AUGER BORING CORE BORING MONITORING WELL PIEZOMETER INSTALLATION SLOPE INDICATOR INSTALLATION CONE PENETROMETER TEST SOUNDING ROD TEST BORING WITH CORE SPT N-VALUE										UNDERCUT EXCAVATION SHALLOW UNDERCUT UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE USED IN THE TOP 3 FEET OF EMBANKMENT OR BACKFILL																																																																																																					
SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION																																																																																																																																																																														
LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE																																																																																																																																																																														
PL - PLASTIC LIMIT	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																														
OM - OPTIMUM MOISTURE SHRINKAGE LIMIT	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE																																																																																																																																																																														
SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																														
ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL																																																																																																																																																																													
TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE 1 - 10%																																																																																																																																																																													
LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE 10 - 20%																																																																																																																																																																													
MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME 20 - 35%																																																																																																																																																																													
HIGHLY ORGANIC	> 10%	> 20%	HIGHLY 35% AND ABOVE																																																																																																																																																																													
PLASTICITY										ABBREVIATIONS										EQUIPMENT USED ON SUBJECT PROJECT										FRACTURE SPACING																																																																																																																																																		
<table border="1"> <tr> <th>NON PLASTIC</th> <th colspan="2">PLASTICITY INDEX (PI)</th> <th>DRY STRENGTH</th> </tr> <tr> <td>SLIGHTLY PLASTIC</td> <td>0-5</td> <td></td> <td>VERY LOW</td> </tr> <tr> <td>MODERATELY PLASTIC</td> <td>6-15</td> <td></td> <td>SLIGHT</td> </tr> <tr> <td>HIGHLY PLASTIC</td> <td>16-25</td> <td></td> <td>MEDIUM</td> </tr> <tr> <td></td> <td>26 OR MORE</td> <td></td> <td>HIGH</td> </tr> </table>										NON PLASTIC	PLASTICITY INDEX (PI)		DRY STRENGTH	SLIGHTLY PLASTIC	0-5		VERY LOW	MODERATELY PLASTIC	6-15		SLIGHT	HIGHLY PLASTIC	16-25		MEDIUM		26 OR MORE		HIGH	AR - AUGER REFUSAL BT - BORING TERMINATED CL - CLAY CPT - COARSE PENETRATION TEST CSE - COARSE DMT - DILATOMETER TEST DPT - DYNAMIC PENETRATION TEST e - VOID RATIO F - FINE FOSS. - FOSSILIFEROUS FRAC. - FRACTURED, FRACTURES FRAGS. - FRAGMENTS HI. - HIGHLY MED. - MEDIUM MICA - MICACEOUS MOD. - MODERATELY NP - NON PLASTIC ORG. - ORGANIC PMT - PRESSUREMETER TEST SAP. - SAPROLITIC SD. - SAND, SANDY SL. - SILT, SILTY SLI. - SLIGHTLY TCR - TRICONE REFUSAL w - MOISTURE CONTENT V - VERY VST - VANE SHEAR TEST WEA. - WEATHERED W - UNIT WEIGHT Wg - DRY UNIT WEIGHT SAMPLE ABBREVIATIONS S - BULK SS - SPLIT SPOON ST - SHELBY TUBE RS - ROCK RT - RECOMPACTED TRIAXIAL CBR - CALIFORNIA BEARING RATIO										DRILL UNITS: <input checked="" type="checkbox"/> CME-45C <input type="checkbox"/> CME-55 <input type="checkbox"/> CME-550 <input type="checkbox"/> VANE SHEAR TEST <input type="checkbox"/> PORTABLE HOIST ADVANCING TOOLS: <input type="checkbox"/> CLAY BITS <input checked="" type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER <input type="checkbox"/> 8" HOLLOW AUGERS <input type="checkbox"/> HARD FACED FINGER BITS <input type="checkbox"/> TUNG-CARBIDE INSERTS <input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER <input type="checkbox"/> TRICONE * STEEL TEETH <input type="checkbox"/> TRICONE * TUNG-CARB. <input type="checkbox"/> CORE BIT HAMMER TYPE: <input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL CORE SIZE: <input type="checkbox"/> -B <input type="checkbox"/> -H <input type="checkbox"/> -N HAND TOOLS: <input type="checkbox"/> POST HOLE DIGGER <input checked="" type="checkbox"/> HAND AUGER <input type="checkbox"/> SOUNDING ROD <input type="checkbox"/> VANE SHEAR TEST										VERY WIDE MORE THAN 10 FEET WIDE 3 TO 10 FEET MODERATELY CLOSE 1 TO 3 FEET CLOSE 0.16 TO 1 FOOT VERY CLOSE LESS THAN 0.16 FEET																																																																																																																														
NON PLASTIC	PLASTICITY INDEX (PI)		DRY STRENGTH																																																																																																																																																																													
SLIGHTLY PLASTIC	0-5		VERY LOW																																																																																																																																																																													
MODERATELY PLASTIC	6-15		SLIGHT																																																																																																																																																																													
HIGHLY PLASTIC	16-25		MEDIUM																																																																																																																																																																													
	26 OR MORE		HIGH																																																																																																																																																																													
COLOR										INDURATION										BEDDING										BENCH MARK:																																																																																																																																																		
DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-BROWN). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.										FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC. FRIABLE RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE. MODERATELY INDURATED GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER. INDURATED GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER. EXTREMELY INDURATED SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.										VERY THICKLY BEDDED 4 FEET THICKLY BEDDED 1.5 - 4 FEET THINLY BEDDED 0.16 - 1.5 FEET VERY THINLY BEDDED 0.03 - 0.16 FEET THICKLY LAMINATED 0.008 - 0.03 FEET THINLY LAMINATED < 0.008 FEET										ELEVATION: FEET																																																																																																																																																		
NOTES:										FRACTURE SPACING										BEDDING										BENCH MARK:																																																																																																																																																		
BORING AND GROUND SURFACE ELEVATIONS OBTAINED FROM NCDOT - PROVIDED DTM FILE LABELED 'U2714.IS_T1n.T1n' DATED 1/27/16										FRAC. SPACING										BEDDING										BENCH MARK:																																																																																																																																																		
FIAD - FILLED IMMEDIATELY AFTER DRILLING										FRAC. SPACING										BEDDING										BENCH MARK:																																																																																																																																																		

09/28/99

PLOT DRIVER: NCDOT...  
USER: CHARNDEN  
DATE: 4/28/2016  
FILE: North\_Carolina\_Dept\_of\_Transportation\NCDOT...  
PENTABLE: NCDOT...  
TIME: 2:04:50 PM

**CONTRACT:**

**TIP PROJECT: U-2714**

See Sheet 1-A For Index of Sheets


# STATE OF NORTH CAROLINA DIVISION OF HIGHWAYS

## WAYNE COUNTY


**LOCATION: US 117A (N. WILLIAMS ST) FROM NORTH OF US 70  
TO SR 1571 (TOMMY'S RD)**

**TYPE OF WORK: GRADING, PAVING, DRAINAGE, CULVERT  
AND SIGNALS**

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	U-2714	3	31
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	




25% PLANS



CLEARING ON THIS PROJECT SHALL BE PERFORMED TO THE LIMITS ESTABLISHED BY METHOD \_\_\_\_  
A PORTION OF THIS PROJECT IS WITHIN THE MUNICIPAL BOUNDARIES OF THE CITY OF GOLDSBORO


★ PROPOSED TRAFFIC SIGNAL

Prepared by the Office of:



HDR Engineering, Inc. of the Carolinas  
555 Fayetteville St, Suite 900 Raleigh, N.C. 27601  
N.C.B.E.L.S. License Number: F-0116

**INCOMPLETE PLANS**  
DO NOT USE FOR R/W ACQUISITION  
DOCUMENT NOT CONSIDERED FINAL  
UNLESS ALL SIGNATURES COMPLETED



**DESIGN DATA**

ADT 2018 =	17,390
ADT 2038 =	27,310
DHV =	9 %
D =	60 %
T =	4 % *
V =	40 MPH
(* TTST = 1% + DUAL 3%)	
FUNC CLASS =	MINOR ARTERIAL (URBAN)
STATEWIDE TIER	

**PROJECT LENGTH**

LENGTH ROADWAY TIP PROJECT U-2714 =	1.546 MILES
TOTAL LENGTH TIP PROJECT U-2714 =	1.546 MILES

Prepared for the Office of:

**DIVISION OF HIGHWAYS**  
1000 Birch Ridge Dr., Raleigh NC, 27610

2012 STANDARD SPECIFICATIONS


<b>RIGHT OF WAY DATE:</b> FEBRUARY 17, 2017	<b>CALVIN W. MOODY, III, P.E.</b> PROJECT ENGINEER
<b>LETTING DATE:</b> FEBRUARY 20, 2018	<b>CASEY E. HARRIS, P.E.</b> PROJECT DESIGN ENGINEER

**HYDRAULICS ENGINEER**

SIGNATURE: \_\_\_\_\_ P.E.

**ROADWAY DESIGN ENGINEER**

SIGNATURE: \_\_\_\_\_ P.E.





September 30, 2016

**STATE PROJECT: 38979.1.2**  
**TIP NUMBER: U-2714**  
**COUNTY: Wayne**  
**DESCRIPTION: US 117A (N. Williams St) from North of US 70 to SR 1571 (Tommy's Rd)**

**SUBJECT: Geotechnical Roadway Inventory Report**

**PROJECT DESCRIPTION**

The U-2714 project is an existing alignment designed to help increase the flow of traffic around the city of Goldsboro in eastern North Carolina. The U-2714 project consists of improving the current US 117 Business / US 117 roadway by widening the current roadway from just north of US 70 to just south of NC 44 (Goldsboro Bypass). It also includes improvements along tie in alignments. The project length is approximately 1.5 miles along US 117 Business / US 117.

The field investigation was conducted in June 2016, using a CME-45C track rig with automatic hammer. Standard Penetration Tests (SPT) were performed at selected locations. Representative soil samples were collected and kept for in-office identification purposes. All available test locations are plotted on the plan view and also appear projected into the profiles and selected cross sections.

The following alignments, totaling approximately 1.7 miles, were investigated

Line	Station		Length (ft)
-L-	10+00	to 91+64	8,164
-Y4-	10+00	to 21+32.34	1,132
-Y5-	10+00	to 17+54.20	754
		Total =	10,050 (~1.9 miles)

**PHYSIOGRAPHY AND GEOLOGY**

**Physiography and Geography**

The project is located in the Coastal Plain Physiographic Province. Geologically, it is located in an area mapped as Tertiary Age deposits of the Yorktown Formation described as fossiliferous clay with varying amounts of fine grained sand. The topography is flat and the drainage from the area is very poor. The soils along the project were deposited during periods of fluctuating shoreline.

**Soil Properties**

Soils encountered on the project site include alluvium, existing roadway embankment fill, and Undivided Coastal Plain sediments.

Existing roadway embankment fill soils are present in the upper few feet along part of the existing mainline alignment -L- and consist of fine to coarse sand (A-3), clayey sand (A-2-6) and sandy clay (A-6).

Alluvial soils were encountered in the hand auger boring advanced near the inlet of the existing box culvert at Station 75+50. These soils consist of clayey fine to coarse sand (A-2-6).

The Undivided Coastal Plain deposits are present at all boring locations except the shallow hand auger boring at -L- Station 75+50 and consist of fine to coarse sand and clayey sand (A-3, A-2-4, A-2-6/7), clay (A-6, A-7-6) and silt (A-4, A-5). The consistency of the sands is generally loose to medium dense while the consistency of the clays and silts is generally medium stiff to stiff. The field moisture content of the soils sampled was described as moist to wet.

**Groundwater**

Only 0 hour measurements were taken due to the boring locations being in or next to the roadway. For safety reasons, borings were backfilled immediately after drilling. Borings were either dry at the time of drilling or the 0 hour groundwater was encountered from approximately 5.4 to 8.4 feet below the existing ground surface at the boring locations. Based on the proposed grades, no special ditches for groundwater are anticipated.

**Pavement**

Eight of the borings were advanced through existing roadway pavement and pavement cores were obtained. For borings advanced through existing roadway pavement and at 4 other locations, the subgrade was tested with a Kessler Dynamic Cone Penetrometer. The cone penetrometer results were correlated to the California Bearing Ratio for subgrade quality based on the NCDOT correlation method. See the Pavement Design Investigation for the pavement core photos and CBR correlations. The pavement thicknesses are provided in the table below.

Boring	Thickness (in)
L_1200L	7
L_1853L	7
L_2352L	6
L_2800	6
L_3445L	4.5
L_6300R	5.5
L_8100R	5.5
L_8900L	6.5

**Areas of Special Geotechnical Interest**


The following areas encountered moderately plastic cohesive soil at subgrade:

Alignment	Begin Station	End Station
-L-	14+25	21+50

Sincerely,

Elizabeth C. Howey, PE, PG  
Senior Geotechnical Project Manager  
HDR ENGINEERING, INC.






10

15

20



REVISIONS

-L- STA. 10+00.00  
BEGIN PROJECT U-2714  
BEGIN CONSTRUCTION

-YI- STA. 11+50.00  
END CONSTRUCTION




-YI- POT Sta. 12+98.38

2018 ADT	NEIL ST	
2038 ADT	8	9
(ADT IN 100's)		
US 117	143	253
	5	4
	2	5
	159	283
US 117		
	14	33
	25	54
	48	79
	158.77	158.77
		EX. RW
		60.00' RT
		160.00' RT
		EX. RW
		US 1370 BYP

-L-	
PI Sta 14+86.81	PI Sta 18+45.73
$\Delta = 2^{\circ} 55' 01.3''$ (RT)	$\Delta = 5^{\circ} 42' 04.5''$ (LT)
$D = 1^{\circ} 12' 04.2''$	$D = 1^{\circ} 12' 04.2''$
$L = 242.85'$	$L = 474.64'$
$T = 121.45'$	$T = 237.52'$
$R = 4,770.00'$	$R = 4,770.00'$
SE = NC	SE = NC

★ PROPOSED SIGNAL  
SEE SHEET 12 FOR -L- PROFILE  
SEE SHEET 16 FOR -YI- PROFILE  
DRIVEWAY RADII 10' UNLESS OTHERWISE NOTED

MATCHLINE -L- STA. 22+00, SEE SHEET 5



2018 ADT	2038 ADT	SR 1305	
(ADT IN 100's)	(ADT IN 100's)	HOOKS RIVER RD	
		33	43
		169	265
		30	31
		4	13
		144	246
US 117			US 117

2018 ADT	2038 ADT	145	154
(ADT IN 100's)	(ADT IN 100's)	246	254
US 117			US 117
		9	19
		13	20
		27	33
		SR 1555	
		11th ST	


-L-  
 PI Sta 27+63.84  
 $\Delta = 31' 31" 17.9' (LT)$   
 $D = 5' 43' 46.5"$   
 $L = 550.16'$   
 $T = 282.23'$   
 $R = 1,000.00'$   
 $SE = 0.04$   
 $RO = 148'$

★ PROPOSED SIGNAL  
 SEE SHEET 12 FOR -L- PROFILE  
 SEE SHEET 16 FOR -Y2- PROFILE  
 SEE SHEET 16 FOR -Y3- PROFILE  
 DRIVEWAY RADII 10' UNLESS OTHERWISE NOTED

PLOT DRIVER: \$PLTDVRS\$    PENTABLE: \$PENTBL\$  
 USER: \$USER\$    TIME: \$TIME\$  
 DATE: \$DATE\$  
 FILE: \$PWVARVAULTPATHDESC\$

REVISIONS



PROPOSED SIGNAL ★  
 PAVEMENT REMOVAL   
 SEE SHEET 13 FOR -L- PROFILE  
 SEE SHEET 18 FOR -Y4- PROFILE  
 SEE SHEET 17 FOR -Y4RT- PROFILE  
 SEE SHEET 17 FOR -Y4LT- PROFILE  
 SEE SHEET 18 FOR -Y5- PROFILE  
 SEE SHEET 19 FOR -Y6- PROFILE  
 DRIVEWAY RADII 10' UNLESS OTHERWISE NOTED


**-Y4-**  
 PI Sta 17+04.64  
 $\Delta = 51^{\circ} 19' 16.9''$  (RT)  
 $D = 15^{\circ} 54' 55.8''$   
 $L = 322.46'$   
 $T = 172.95'$   
 $R = 360.00'$   
 $SE = 0.06$

**-Y4RT-**  
 PI Sta 17+06.56  
 $\Delta = 51^{\circ} 19' 16.9''$  (RT)  
 $D = 15^{\circ} 54' 55.8''$   
 $L = 322.46'$   
 $T = 172.95'$   
 $R = 360.00'$   
 $SE = 0.06$   
 $RO = 70'$

**-Y4LT-**  
 PI Sta 17+02.72  
 $\Delta = 51^{\circ} 19' 16.9''$  (RT)  
 $D = 15^{\circ} 54' 55.8''$   
 $L = 322.46'$   
 $T = 172.95'$   
 $R = 360.00'$   
 $SE = 0.06$   
 $RO = 120'$

MATCHLINE -L- STA. 35+00, SEE SHEET 5

MATCHLINE -L- STA. 49+00, SEE SHEET 7



**-L-**  
 PI Sta 49+56.47  
 $\Delta = 11^{\circ} 02' 53.8''$  (RT)  
 $D = 1^{\circ} 46' 45.7''$   
 $L = 620.91'$   
 $T = 311.42'$   
 $R = 3,220.00'$   
 $SE = RC$   
 $RO = 92.5'$

**-Y5-**  
 PI Sta 11+21.89  
 $\Delta = 53^{\circ} 36' 11.2''$  (RT)  
 $D = 32^{\circ} 44' 25.6''$   
 $L = 163.72'$   
 $T = 88.40'$   
 $R = 175.00'$

PI Sta 13+68.75  
 $\Delta = 9^{\circ} 01' 08.6''$  (LT)  
 $D = 2^{\circ} 38' 03.4''$   
 $L = 342.37'$   
 $T = 171.54'$   
 $R = 2,175.00'$   
 $SE = RC$   
 $RO = 50'$

PI Sta 16+52.17  
 $\Delta = 62^{\circ} 18' 22.2''$  (RT)  
 $D = 45^{\circ} 50' 11.8''$   
 $L = 135.93'$   
 $T = 75.56'$   
 $R = 125.00'$


**-Y6-**  
 PI Sta 10+78.94  
 $\Delta = 19^{\circ} 32' 16.4''$  (LT)  
 $D = 17^{\circ} 54' 17.8''$   
 $L = 109.12'$   
 $T = 55.09'$   
 $R = 320.00'$

PI Sta 16+13.43  
 $\Delta = 5^{\circ} 59' 09.7''$  (RT)  
 $D = 2^{\circ} 03' 13.0''$   
 $L = 291.49'$   
 $T = 145.88'$   
 $R = 2,790.00'$   
 $SE = EX.$


2018 ADT		US 117A	
2038 ADT		PATETOWN RD	
(ADT IN 100's)			
	58	26	136
	71	34	197
US 117	154	6	254
	254	12	254
	38	4	58
	58	7	58
	68	90	90
	90		
NC 111 PATETOWN RD			

PLOT DRIVER: \$PLTDVRS\$  
 USER: \$USER\$  
 FILE: \$PWRVAULTPATHDESC\$  
 PENTABLE: \$PENTBL\$  
 TIME: \$TIME\$  
 DATE: \$DATE\$




PROJECT REFERENCE NO. U-2714	SHEET NO. 7
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
<b>INCOMPLETE PLANS</b> DO NOT USE FOR R/W ACQUISITION	
<b>DOCUMENT NOT CONSIDERED FINAL</b> UNLESS ALL SIGNATURES COMPLETED	
 HDR Engineering, Inc. of the Carolinas 555 Fayetteville St. Suite 900 Raleigh, N.C. 27601 N.C.B.E.L.S. License Number: F-0116	

2018 ADT	2038 ADT	SR 1306	
(ADT IN 100's)		FEDELON TRL	
		33	47
		28	5
US 117	225	40	7
			116
			192
			US 117



MATCHLINE -L- STA. 49 + 00, SEE SHEET 6

MATCHLINE -L- STA. 62 + 00, SEE SHEET 8



REVISIONS

-L-
PI Sta 49+56.47
Δ = 1' 02' 53.8" (RT)
D = 1' 46' 45.7"
L = 620.91'
T = 311.42'
R = 3,220.00'
SE = RC

-L-	-L-
PI Sta 60+22.15	PI Sta 62+89.67
Δ = 3' 12' 48.3" (RT)	Δ = 3' 12' 48.3" (LT)
D = 1' 12' 04.2"	D = 1' 12' 04.2"
L = 267.52'	L = 267.52'
T = 133.80'	T = 133.80'
R = 4,770.00'	R = 4,770.00'
SE = NC	SE = NC


SEE SHEET 13 FOR -L- PROFILE  
SEE SHEET 19 FOR -Y7- PROFILE  
DRIVEWAY RADII 10' UNLESS OTHERWISE NOTED

PLOT DRIVER: \$PLTDVRS\$  
 USER: \$USER\$  
 FILE: \$PWVARVAULTPATHDESC\$  
 PENTABLE: \$PENTBL\$  
 TIME: \$TIME\$  
 DATE: \$DATE\$



-L-

PI Sta 72+89.74  
 $\Delta = 14^{\circ} 37' 34.0''$  (RT)  
 $D = 4^{\circ} 10' 55.8''$   
 $L = 349.72'$   
 $T = 175.82'$   
 $R = 1,370.00'$   
 $SE = 0.03$   
 $RO = 111'$



-L-

PI Sta 60+22.15	PI Sta 62+89.67
$\Delta = 3^{\circ} 12' 48.3''$ (RT)	$\Delta = 3^{\circ} 12' 48.3''$ (LT)
$D = 1^{\circ} 12' 04.2''$	$D = 1^{\circ} 12' 04.2''$
$L = 267.52'$	$L = 267.52'$
$T = 133.80'$	$T = 133.80'$
$R = 4,770.00'$	$R = 4,770.00'$
$SE = NC$	$SE = NC$


2018 ADT	
2038 ADT	
(ADT IN 100's)	
105	107
172	167
US 117	US 117
12	14
19	14
25	32
SR 1668	
INDUSTRY CT	


-Y8-

PI Sta 11+62.11	PI Sta 12+79.59
$\Delta = 12^{\circ} 14' 19.5''$ (RT)	$\Delta = 12^{\circ} 14' 19.5''$ (LT)
$D = 10^{\circ} 25' 02.7''$	$D = 10^{\circ} 25' 02.7''$
$L = 117.48'$	$L = 117.48'$
$T = 58.97'$	$T = 58.97'$
$R = 550.00'$	$R = 550.00'$
$SE = 0.02$	$SE = 0.02$
$RO = 40'$	$RO = 40'$

SEE SHEET 14 FOR -L- PROFILE  
 SEE SHEET 20 FOR -Y8- PROFILE  
 SEE SHEET 20 FOR -DRI- PROFILE  
 DRIVEWAY RADII 10' UNLESS OTHERWISE NOTED

PLOT DRIVER: \$PLTDVRS\$  
 USER: \$USER\$  
 FILE: \$PWVARVAULTPATIDESC\$  
 DATE: \$DATE\$  
 TIME: \$TIME\$  
 PENTABLE: \$PENTBL\$  
 REVISIONS:

PROJECT REFERENCE NO.	SHEET NO.
U-2714	9
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
<b>INCOMPLETE PLANS</b> DO NOT USE FOR R/W ACQUISITION	
<b>DOCUMENT NOT CONSIDERED FINAL</b> UNLESS ALL SIGNATURES COMPLETED	
 HDR Engineering, Inc. of the Carolinas 555 Fayetteville St. Suite 900 Raleigh, N.C. 27601 N.C.B.E.L.S. License Number: F-01116	






-L-	
PI Sta 78+50.70	PI Sta 90+49.87
Δ = 2° 41' 01.5" (RT)	Δ = 3° 39' 47.4" (LT)
D = 1' 12' 04.2"	D = 1' 29' 38.5"
L = 223.43'	L = 2119.32'
T = 111.73'	T = 1087.48'
R = 4770.00'	R = 3,835.00'
SE = NC	SE = 0.03
	RO = 126'

SEE SHEET 14 FOR -L- PROFILE  
 SEE SHEET 20 FOR -Y9- PROFILE  
 DRIVEWAY RADII 10' UNLESS OTHERWISE NOTED

PLOT DRIVER: \$PLTDVRS\$ PENTABLE: \$PENTBL\$  
 USER: \$USER\$ DATE: \$DATE\$ TIME: \$TIME\$  
 FILE: \$PWVARVAULTPATHDESC\$

REVISIONS

PROJECT REFERENCE NO.	SHEET NO.
U-2714	10
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
<b>INCOMPLETE PLANS</b> DO NOT USE FOR R/W ACQUISITION	
<b>DOCUMENT NOT CONSIDERED FINAL</b> UNLESS ALL SIGNATURES COMPLETED	
 HDR Engineering, Inc. of the Carolinas 555 Fayetteville St. Suite 900 Raleigh, N.C. 27601 N.C.B.E.L.S. License Number: F-0116	




-L-
PI Sta 90+49.87
$\Delta = 31^{\circ} 39' 47.4''$ (LT)
$D = 129.38.5'$
$L = 2,119.32'$
$T = 1,087.48'$
$R = 3,835.00'$
$SE = 0.03$
$RO = 126'$

-YII-
PI Sta 13+14.09
$\Delta = 33^{\circ} 12' 31.5''$ (LT)
$D = 7.26' 27.6''$
$L = 446.29'$
$T = 229.61'$
$R = 770.00'$



PLOT DRIVER: \$PLTDVRS\$      PENTABLE: \$PENTBL\$  
 USER: \$USER\$                  DATE: \$DATE\$                  TIME: \$TIME\$  
 FILE: \$PWVARVAULTPATHDESC\$

REVISIONS

SEE SHEET 15 FOR -L- PROFILE  
DRIVEWAY RADII 10' UNLESS OTHERWISE NOTED

PROJECT REFERENCE NO.	SHEET NO.
U-2714	11
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
<b>INCOMPLETE PLANS</b> DO NOT USE FOR A/W ACQUISITION	
<b>DOCUMENT NOT CONSIDERED FINAL</b> UNLESS ALL SIGNATURES COMPLETED	
 HDR Engineering, Inc. of the Carolinas 555 Fayetteville St. Suite 900 Raleigh, N.C. 27601 N.C.B.E.L.S. License Number: F-0116	


-Y4RT-	-Y4-	-Y4LT-
PI Sta 17+06.56 $\Delta = 51' 19" 16.9'$ (RT) $D = 15' 54" 55.8'$ $L = 322.46'$ $T = 172.95'$ $R = 360.00'$ $SE = 0.06$	PI Sta 17+04.64 $\Delta = 51' 19" 16.9'$ (RT) $D = 15' 54" 55.8'$ $L = 322.46'$ $T = 172.95'$ $R = 360.00'$ $SE = 0.06$	PI Sta 17+02.72 $\Delta = 51' 19" 16.9'$ (RT) $D = 15' 54" 55.8'$ $L = 322.46'$ $T = 172.95'$ $R = 360.00'$ $SE = 0.06$



REVISIONS


PLOT DRIVER: \$PLTDVRS\$      PENTABLE: \$PENTBL\$  
USER: \$USER\$                      DATE: \$DATE\$              TIME: \$TIME\$  
FILE: \$PWVAVULTPATHDESC\$

SEE SHEET 18 FOR -Y4- PROFILE  
SEE SHEET 17 FOR -Y4RT- PROFILE  
SEE SHEET 17 FOR -Y4LT- PROFILE  
DRIVEWAY RADII 10' UNLESS OTHERWISE NOTED



DOCUMENT NOT CONSIDERED FINAL  
UNLESS ALL SIGNATURES COMPLETED

SEE SHEET 4 FOR -L- PLAN




SEE SHEET 5 FOR -L- PLAN


PLOT DRIVER: \$PLTDVRS\$  
USER: \$USER\$  
FILE: \$PWVARVAULTPATHDESC\$  
PENTABLE: \$PENTBL\$  
TIME: \$TIME\$  
DATE: \$DATE\$

REVISIONS

**DOCUMENT NOT CONSIDERED FINAL  
UNLESS ALL SIGNATURES COMPLETED**



SEE SHEET 6 FOR -L- PLAN



SEE SHEET 7 FOR -L- PLAN

REVISIONS


PLOT DRIVER: \$PLTDVRS\$  
 USER: \$USER\$  
 FILE: \$PWVARVAULTPATHDESC\$  
 PENTABLE: \$PENTBL\$  
 TIME: \$TIME\$  
 DATE: \$DATE\$

**INCOMPLETE PLANS**  
 DO NOT USE FOR R/W ACQUISITION


**DOCUMENT NOT CONSIDERED FINAL**  
 UNLESS ALL SIGNATURES COMPLETED

SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-1	33' LT	67+80	4.70-6.20	A-4(2)	27	6	2.9	22.7	21.1	53.2	99.9	98.6	81.3	17.7	-

BM#7  
 -L- STA. 72+85.31 (340' RT.)  
 EL. = 123.21'  
 BM 12" SPIKE IN POWERPOLE



SEE SHEET 8 FOR -L- PLAN



SEE SHEET 9 FOR -L- PLAN

PLOT DRIVER: \$PLTDVRS\$ PENTABLE: \$PENTBL\$  
 USER: \$USER\$ DATE: \$DATE\$ TIME: \$TIME\$  
 FILE: \$PWVARVAULTPATHDESC\$

REVISIONS



**INCOMPLETE PLANS**  
 DO NOT USE FOR R/W ACQUISITION

**DOCUMENT NOT CONSIDERED FINAL**  
 UNLESS ALL SIGNATURES COMPLETED


SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL	PI	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-1	15' LT	89+00	4.60-6.10	A-6(2)	14	11	0.3	24.8	24.8	22.4	99.7	82.2	51.8	14.0	-

END TIP PROJECT U-2714  
 END GRADE  
 END CONSTRUCTION  
 -L- STA. 91+64.74  
 EL. = 128.84'

PI = 89+50.00  
 EL = 129.48'  
 K = 320  
 VC = 200'

Ⓐ ASPHALT PAVEMENT  
 Ⓒ ROADWAY EMBANKMENT  
 TAN, GRAY, BROWN-ORANGE & ORANGE FINE TO COARSE SANDY CLAY (A-6) WITH SOME SILT, MOIST, SOFT

BM#8  
 -L- STA. 91+64.74  
 N 0°28'15.2" E (1030.39')  
 EL. = 128.88'  
 BM CHISELED X IN CONC. W/ ORANGE PAINT





88	89	90	91	92	93	94	95	96	97	98	99	100
----	----	----	----	----	----	----	----	----	----	----	----	-----

REVISIONS

PLOT DRIVER: \$PLTDRV\$ PENTABLE: \$PENTBL\$  
 USER: \$USER\$ DATE: \$DATE\$ TIME: \$TIME\$  
 FILE: \$PWVARVAULTPATHDESC\$

**DOCUMENT NOT CONSIDERED FINAL**  
 UNLESS ALL SIGNATURES COMPLETED



REVISIONS


PLOT DRIVER: \$PLOTDRVS\$  
 USER: \$USER\$  
 FILE: \$PWVARVAULTPATHDESC\$  
 PENTABLE: \$PENTBL\$  
 TIME: \$TIME\$  
 DATE: \$DATE\$

8/23/99




PROJ. REFERENCE NO.	SHEET NO.
U-2714	17

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150



PLOT DRIVER: \$PLTRV\$  
 USER: \$USER\$  
 FILE: \$PWVAVULTPATHDESC\$  
 DATE: \$DATE\$  
 TIME: \$TIME\$  
 PENTABLE: \$PENTBL\$

12 + 00.00




150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

### SOIL TEST RESULTS

SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-1	11 LT	18+53	4.40-5.90	A-7-6(5)	48	20	45.8	9.4	7.3	37.4	99.9	64.4	44.8	20	-

- (A) ASPHALT PAVEMENT
- ROADWAY EMBANKMENT
- (B) BROWN, FINE TO COARSE SAND (A-2-7) WITH CLAY AND BLACK SUBBASE
- (H) UNDIVIDED COASTAL PLAIN GRAY AND TAN, FINE TO COARSE SANDY CLAY (A-7-6)(5), STIFF, MOIST
- (I) GRAY, CLAYEY FINE TO COARSE SAND (A-2-7), LOOSE, WET

SS-1  
L1853L



18 + 50.00



150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-1	26LT	23+52	4.50-6.00	A-2-6(2)	36	18	63.0	8.4	6.6	19.1	97.1	48.6	26.4	14	-

(A) ASPHALT PAVEMENT

SS-1

L2352L  
26' LT

0.025

0.009

121.65

4:1

120.37

UNDIVIDED COASTAL PLAIN  
BROWN, GRAY & ORANGE, MOIST, LOOSE TO MEDIUM DENSE,  
CLAYEY FINE TO COARSE SAND (A-2-6)(2)

BT  
DRY (06/16)  
FIAD


23 + 50.00

1/4"

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

8/23/99

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150



(A) ASPHALT PAVEMENT

L2800R

4:1

0.040

0.040

125.11

3:1

122.17

121.64

(5)

(20)

BT  
FIAD

UNDIVIDED COASTAL PLAIN  
BROWN, BLACK, TAN, AND GRAY, SILTY FINE  
TO COARSE SAND (A-2-4) AND SILTY CLAYEY  
SAND (A-2-6), LOOSE TO MEDIUM; DENSE,  
MOIST

28 + 00.00


PLOT DRIVER: \$PLTRV\$  
 USER: \$USER\$  
 FILE: \$PWVAVULTPATHDESC\$  
 DATE: \$DATE\$  
 TIME: \$TIME\$  
 PENTABLE: \$PENTBL\$

8/23/99



PROJ. REFERENCE NO.	SHEET NO.
U-2714	21

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150



(A) ASPHALT PAVEMENT

L 3445L

123.20

0.025

0.025

123.20

4:1

4:1

(13)

(11)


(A)

BT

FIAD

UNDIVIDED COASTAL PLAIN 122.24  
 DARK GRAY, TAN, BROWN, AND GRAY, FINE  
 TO COARSE SAND (A-3); SILTY SAND  
 (A-2-4) AND CLAYEY SAND (A-2-6), MEDIUM  
 DENSE, MOIST


34 + 50.00




PLOT DRIVER: \$PLTRV\$  
 USER: \$USER\$  
 FILE: \$PWVAVULTPATHDESC\$  
 DATE: \$DATE\$  
 TIME: \$TIME\$  
 PENTABLE: \$PENTBL\$

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150



40 + 50.00






8/23/99



PROJ. REFERENCE NO.	SHEET NO.
U-2714	23

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150



(A) ASPHALT PAVEMENT - PARKING LOT

UNDIVIDED COASTAL PLAIN  
 (T) RED-ORANGE, BROWN AND GRAY, CLAYEY FINE TO COARSE SAND (A-2-7), MEDIUM DENSE, MOIST

136.87  
 (A)  
 BT  
 DRY (06/16)  
 FIAD

(T) RED-ORANGE AND GRAY, SANDY CLAY (A-6), STIFF, MOIST

0.025

0.025

133.61

134.23

4:1

4:1

51 + 50.00



150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150


PLOT DRIVER: \$PLTRV\$  
 USER: \$USER\$  
 FILE: \$PWVAVULTPATHDESC\$  
 DATE: \$DATE\$  
 TIME: \$TIME\$  
 PENTABLE: \$PENTBL\$

8/23/99



PROJ. REFERENCE NO.	SHEET NO.
U-2714	24

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150



(A) ASPHALT PAVEMENT - PARKING LOT

UNDIVIDED COASTAL PLAIN

(1) TAN AND BROWN ORANGE CLAYEY FINE TO COARSE SAND (A-2-7), LOOSE, MOIST

L5823R

0.025

0.025

127.09

3.97:1

127.79

GRAY, BROWN AND RED-ORANGE, SANDY CLAY (A-6), MEDIUM STIFF, MOIST

(6)

(7)

BT DRY (06/16) FIAD


58 + 00.00




150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

PLOT DRIVER: \$PLTRV\$  
 USER: \$USER\$  
 FILE: \$PWVAVULTPATHDESC\$  
 DATE: \$DATE\$  
 TIME: \$TIME\$  
 PENTABLE: \$PENTBL\$

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150




63 + 00.00



150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			MOISTURE	ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-1	33 LT	67+80	4.70-6.20	A-4(2)	21	6	2.9	22.7	21.1	53.2	99.9	98.6	81.3	17.7	-



68 + 00.00

BT  
FIAD

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

8/23/99




PROJ. REFERENCE NO.	SHEET NO.
U-2714	27

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

160 150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150


ROADWAY EMBANKMENT  
TAN, FINE SAND (A-3), LOOSE, DRY

UNDIVIDED COASTAL PLAIN  
BROWN-ORANGE AND TAN, SANDY CLAY (A+6)  
MEDIUM STIFF, MOIST



BROWN-ORANGE, GRAY AND TAN, CLAYEY FINE TO COARSE SAND (A-2-7), MEDIUM DENSE, MOIST

73 + 50.00



PLOT DRIVER: \$PLTRV\$  
 USER: \$USER\$  
 FILE: \$PWVAVULTPATHDESC\$  
 DATE: \$DATE\$  
 TIME: \$TIME\$  
 PENTABLE: \$PENTBL\$


150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

8/23/99




PROJ. REFERENCE NO.	SHEET NO.
U-2714	28

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150



- (A) ASPHALT PAVEMENT
- ROADWAY EMBANKMENT
- (E) TAN, ORANGE AND GRAY, CLAYEY FINE TO COARSE SAND (A-2-6), LOOSE, MOIST
- UNDIVIDED COASTAL PLAIN
- TAN, ORANGE AND GRAY, CLAYEY FINE TO COARSE SAND (A-2-6), LOOSE, MOIST

81+00.00




PLOT DRIVER: \$PLTDVRS\$  
 USER: \$USER\$  
 FILE: \$PWVAVULTPATHDESC\$  
 DATE: \$DATE\$  
 TIME: \$TIME\$  
 PENTABLE: \$PENTBL\$

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150


SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-1	15LT	89+00	4.60-6.10	A-6(2)	14	11	0.3	24.8	24.8	22.4	99.7	82.2	51.8	14.0	-



150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150



150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150



17 + 50.00


-Y4-

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150





150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150



16 + 50.00

-Y5-