

**This electronic collection of documents is provided  
for the convenience of the user  
and is Not a Certified Document –**

**The documents contained herein were originally issued  
and sealed by the individuals whose names and license  
numbers appear on each page, on the dates appearing  
with their signature on that page.**

**This file or an individual page  
shall not be considered a certified document.**

STATE OF NORTH CAROLINA  
DIVISION OF HIGHWAYS


**FORSYTH COUNTY**

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	I-5795	1	
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
53034.1.2	-	P.E.	
53034.3.1	NHPP-0040(032)	CONST.	


**TYPE OF WORK: BRIDGE PRESERVATION: DECK REPAIR, POLYESTER POLYMER CONCRETE OVERLAY, POURABLE SILICONE JOINT SEALANT AND FOAM JOINT REPLACEMENT, PAINTING EXISTING WEATHERING STEEL STRUCTURE, PAINTING OF BEARINGS FOR THESE BRIDGES IS INCLUDED IN THE STRUCTURE STEEL PAINTING, CLEAN AND EPOXY COAT EXISTING PRESTRESSED CONCRETE GIRDER ENDS, REMOVE DEBRIS FROM TOP OF EXISTING END BENT & BENT CAPS AND APPLY EPOXY COATING AND SUBSTRUCTURE REPAIR**

**LOCATION:** BRIDGE No. 330439 ON NC 66 OVER I-40  
BRIDGE No. 330441 ON US 158 (S. STRATFORD RD.) OVER I-40  
BRIDGE No. 330451 ON I-40 EBL OVER SR 3153 (HANES MALL BLVD.)  
BRIDGE No. 330452 ON I-40 WBL OVER SR 3153 (HANES MALL BLVD.)  
BRIDGE No. 330454 ON NC 150 OVER I-40  
BRIDGE No. 330458 ON SR 2643 (UNION CROSS RD.) OVER I-40  
BRIDGE No. 330479 ON I-40 WBL OVER BUCHANAN STREET

BRIDGE No. 330480 ON I-40 EBL OVER BUCHANAN STREET  
BRIDGE No. 330481 ON I-40 WBL OVER I-40 RAMP  
BRIDGE No. 330482 ON I-40 EBL OVER I-40 RAMP  
BRIDGE No. 330486 ON I-40 WBL OVER SALEM CREEK  
BRIDGE No. 330487 ON I-40 EBL OVER SALEM CREEK  
BRIDGE No. 330488 ON I-40 WBL OVER NC 150 RAMPS  
BRIDGE No. 330489 ON I-40 EBL OVER NC 150 RAMPS




VICINITY MAP - FORSYTH CO.



VICINITY MAP - FORSYTH CO.

PROJECT: I-5795

CONTRACT NO: C203978



**DESIGN DATA**

FORSYTH COUNTY		FORSYTH COUNTY	
BRIDGE No. 330439	ADT 2017 = 18,000	BRIDGE No. 330480	ADT 2018 = 48,000
BRIDGE No. 330441	ADT 2017 = 43,000	BRIDGE No. 330481	ADT 2018 = 48,000
BRIDGE No. 330451	ADT 2018 = 40,750	BRIDGE No. 330482	ADT 2018 = 48,000
BRIDGE No. 330452	ADT 2018 = 40,750	BRIDGE No. 330486	ADT 2018 = 53,500
BRIDGE No. 330454	ADT 2017 = 34,000	BRIDGE No. 330487	ADT 2018 = 53,500
BRIDGE No. 330458	ADT 2018 = 18,000	BRIDGE No. 330488	ADT 2018 = 48,000
BRIDGE No. 330479	ADT 2018 = 48,000	BRIDGE No. 330489	ADT 2018 = 48,000

**PROJECT LENGTH**

FORSYTH COUNTY		FORSYTH COUNTY	
BRIDGE No. 330439	= 0.042 MILE	BRIDGE No. 330480	= 0.022 MILE
BRIDGE No. 330441	= 0.050 MILE	BRIDGE No. 330481	= 0.023 MILE
BRIDGE No. 330451	= 0.035 MILE	BRIDGE No. 330482	= 0.022 MILE
BRIDGE No. 330452	= 0.035 MILE	BRIDGE No. 330486	= 0.036 MILE
BRIDGE No. 330454	= 0.038 MILE	BRIDGE No. 330487	= 0.036 MILE
BRIDGE No. 330458	= 0.040 MILE	BRIDGE No. 330488	= 0.033 MILE
BRIDGE No. 330479	= 0.026 MILE	BRIDGE No. 330489	= 0.031 MILE

Prepared in the Office of:  
**DIVISION OF HIGHWAYS**  
STRUCTURES MANAGEMENT UNIT  
1000 BIRCH RIDGE DR.  
RALEIGH, N.C. 27610

---

2018 STANDARD SPECIFICATIONS

LETTING DATE :  
SEPTEMBER 15, 2020


A. KEITH PASCHAL, P.E.  
PROJECT ENGINEER

K. P. SEDAI, P.E.  
PROJECT DESIGN ENGINEER

STATE OF NORTH CAROLINA  
DIVISION OF HIGHWAYS


**FORSYTH COUNTY**

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	I-5795	2	
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
53034.1.2	-	P.E.	
53034.3.1	NHPP-0040(032)	CONST.	



**LOCATION:** BRIDGE No. 330161 ON I-40 EBL OVER MUDDY CREEK  
 BRIDGE No. 330162 ON I-40 WBL OVER MUDDY CREEK  
 BRIDGE No. 330444 ON US 421 SBL RAMP OVER I-40 & I-40 BUS  
 BRIDGE No. 330448 ON I-40 EBL OVER WESTGATE DRIVE  
 BRIDGE No. 330449 ON I-40 WBL OVER WESTGATE DRIVE  
 BRIDGE No. 330508 ON I-40 WBL OVER I-40 BUS EBL  
 BRIDGE No. 330509 ON I-40 WBL RAMP OVER I-40 BUS AND US 421 EBL


**TYPE OF WORK:** BRIDGE PRESERVATION: DECK REPAIR, SILANE DECK TREATMENT, SILANE BARRIER RAIL TREATMENT, JOINT REPLACEMENT, BRIDGE JACKING, PAINTING EXISTING WEATHERING STEEL STRUCTURE, CLEANING AND PAINTING EXISTING BEARINGS WITH HRCSA, CLEAN AND EPOXY COAT EXISTING PRESTRESSED CONCRETE GIRDER ENDS, REMOVE DEBRIS FROM TOP OF EXISTING END BENT & BENT CAPS AND APPLY EPOXY COATING AND SUBSTRUCTURE REPAIR



VICINITY MAP - FORSYTH CO.

PROJECT: I-5795

CONTRACT: C203978



**DESIGN DATA**

FORSYTH COUNTY		
BRIDGE No. 330161	ADT 2015	= 31,500
BRIDGE No. 330162	ADT 2015	= 31,500
BRIDGE No. 330444	ADT 2013	= 6,500
BRIDGE No. 330448	ADT 2015	= 39,500
BRIDGE No. 330449	ADT 2015	= 39,500
BRIDGE No. 330508	ADT 2015	= 39,500
BRIDGE No. 330509	ADT 2013	= 19,250

**PROJECT LENGTH**

FORSYTH COUNTY	
BRIDGE No. 330161	= 0.037 MILE
BRIDGE No. 330162	= 0.037 MILE
BRIDGE No. 330444	= 0.112 MILE
BRIDGE No. 330448	= 0.027 MILE
BRIDGE No. 330449	= 0.029 MILE
BRIDGE No. 330508	= 0.075 MILE
BRIDGE No. 330509	= 0.156 MILE

Prepared in the Office of:  
**DIVISION OF HIGHWAYS**  
 STRUCTURES MANAGEMENT UNIT  
 1000 BIRCH RIDGE DR.  
 RALEIGH, N.C. 27610

2018 STANDARD SPECIFICATIONS

LETTING DATE :  
 SEPTEMBER 15, 2020

A. KEITH PASCHAL, P.E.  
 PROJECT ENGINEER

K. P. SEDAI, P.E.  
 PROJECT DESIGN ENGINEER

STATE OF NORTH CAROLINA  
DIVISION OF HIGHWAYS

**FORSYTH COUNTY**

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	I-5795	1A	
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
53034.1.2	-	P.E.	
53034.3.1	NHPP-0040(032)	CONST.	



**PROJECT: I-5795**

**CONTRACT NO: C203978**

**LOCATION:** BRIDGE No. 330439 ON NC 66 OVER I-40  
 BRIDGE No. 330441 ON US 158 (S. STRATFORD RD.) OVER I-40  
 BRIDGE No. 330451 ON I-40 EBL OVER SR 3153 (HANES MALL BLVD.)  
 BRIDGE No. 330452 ON I-40 WBL OVER SR 3153 (HANES MALL BLVD.)  
 BRIDGE No. 330454 ON NC 150 OVER I-40  
 BRIDGE No. 330458 ON SR 2643 (UNION CROSS RD.) OVER I-40  
 BRIDGE No. 330479 ON I-40 WBL OVER BUCHANAN STREET  
 BRIDGE No. 330480 ON I-40 EBL OVER BUCHANAN STREET  
 BRIDGE No. 330481 ON I-40 WBL OVER I-40 RAMP  
 BRIDGE No. 330482 ON I-40 EBL OVER I-40 RAMP  
 BRIDGE No. 330486 ON I-40 WBL OVER SALEM CREEK  
 BRIDGE No. 330487 ON I-40 EBL OVER SALEM CREEK  
 BRIDGE No. 330488 ON I-40 WBL OVER NC 150 RAMPS  
 BRIDGE No. 330489 ON I-40 EBL OVER NC 150 RAMPS

**INDEX OF STRUCTURES SHEETS**

<u>SHEET No.</u>	<u>DESCRIPTION</u>	<u>SHEET No.</u>	<u>DESCRIPTION</u>	<u>SHEET No.</u>	<u>DESCRIPTION</u>	<u>SHEET No.</u>	<u>DESCRIPTION</u>
1	TITLE SHEET	STRUCTURE No. 330439		STRUCTURE No. 330452		STRUCTURE No. 330479	
2	TITLE SHEET	S1-01	GENERAL DRAWING	S4-01	GENERAL DRAWING	S7-01	GENERAL DRAWING
1A	INDEX OF SHEETS	S1-02	TYPICAL SECTION	S4-02	TYPICAL SECTION	S7-02	TYPICAL SECTION
2A	INDEX OF SHEETS	S1-03	DECK SURFACE REPAIR	S4-03	DECK SURFACE REPAIR	S7-03	DECK SURFACE REPAIR
3A	INDEX OF SHEETS	S1-04	END BENT JOINT DETAILS	S4-04	JOINT DETAILS	S7-04	JOINT DETAILS
S-1	LOCATION SKETCHES	S1-05	BENT JOINT DETAILS	STRUCTURE No. 330454		S7-05	END BENTS
S-2	LOCATION SKETCHES	STRUCTURE No. 330441		S5-01	GENERAL DRAWING	S7-06	BENT 1
S-3	LOCATION SKETCHES	S2-01	GENERAL DRAWING	S5-02	TYPICAL SECTION	S7-07	BENT 2
S-4	TOTAL BILL OF MATERIALS	S2-02	TYPICAL SECTION	S5-03	DECK SURFACE REPAIR	STRUCTURE No. 330480	
S-5	TOTAL BILL OF MATERIALS	S2-03	DECK SURFACE REPAIR	S5-04	JOINT DETAILS	S8-01	GENERAL DRAWING
S-6	GENERAL NOTES	S2-04	END BENT JOINT DETAILS	STRUCTURE No. 330458		S8-02	TYPICAL SECTION
		S2-05	BENT JOINT DETAILS	S6-01	GENERAL DRAWING	S8-03	DECK SURFACE REPAIR
		S2-06	BENT 1	S6-02	TYPICAL SECTION	S8-04	JOINT DETAILS
		STRUCTURE No. 330451		S6-03	DECK SURFACE REPAIR	S8-05	END BENTS
		S3-01	GENERAL DRAWING	S6-04	END BENT JOINT DETAILS	S8-06	BENT 1
		S3-02	TYPICAL SECTION	S6-05	BENT JOINT DETAILS	S8-07	BENT 2
		S3-03	DECK SURFACE REPAIR				
		S3-04	END BENT JOINT DETAILS				
		S3-05	BENT JOINT DETAILS				



**TYPE OF WORK:**  
 BRIDGE PRESERVATION: DECK REPAIR, POLYESTER POLYMER CONCRETE OVERLAY, POURABLE SILICONE JOINT SEALANT AND FOAM JOINT REPLACEMENT, PAINTING EXISTING WEATHERING STEEL STRUCTURE, PAINTING OF BEARINGS FOR THESE BRIDGES IS INCLUDED IN THE STRUCTURE STEEL PAINTING, CLEAN AND EPOXY COAT EXISTING PRESTRESSED CONCRETE GIRDER ENDS, REMOVE DEBRIS FROM TOP OF EXISTING END BENT & BENT CAPS AND APPLY EPOXY COATING AND SUBSTRUCTURE REPAIR

Prepared in the Office of:  
**DIVISION OF HIGHWAYS**  
 STRUCTURES MANAGEMENT UNIT  
 1000 BIRCH RIDGE DR.  
 RALEIGH, N.C. 27610

**PROJECT: I-5795**

**CONTRACT NO: C203978**

STATE OF NORTH CAROLINA  
DIVISION OF HIGHWAYS

**FORSYTH COUNTY**



STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	I-5795	2A	
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
53034.1.2	-	P.E.	
53034.3.1	NHPP-0040(032)	CONST.	

**LOCATION:**

- |  |   |
|--|---|
| <b>BRIDGE No. 330439 ON NC 66 OVER I-40</b>                          | <b>BRIDGE No. 330480 ON I-40 EBL OVER BUCHANAN STREET</b> |
| <b>BRIDGE No. 330441 ON US 158 (S. STRATFORD RD.) OVER I-40</b>      | <b>BRIDGE No. 330481 ON I-40 WBL OVER I-40 RAMP</b>       |
| <b>BRIDGE No. 330451 ON I-40 EBL OVER SR 3153 (HANES MALL BLVD.)</b> | <b>BRIDGE No. 330482 ON I-40 EBL OVER I-40 RAMP</b>       |
| <b>BRIDGE No. 330452 ON I-40 WBL OVER SR 3153 (HANES MALL BLVD.)</b> | <b>BRIDGE No. 330486 ON I-40 WBL OVER SALEM CREEK</b>     |
| <b>BRIDGE No. 330454 ON NC 150 OVER I-40</b>                         | <b>BRIDGE No. 330487 ON I-40 EBL OVER SALEM CREEK</b>     |
| <b>BRIDGE No. 330458 ON SR 2643 (UNION CROSS RD.) OVER I-40</b>      | <b>BRIDGE No. 330488 ON I-40 WBL OVER NC 150 RAMPS</b>    |
| <b>BRIDGE No. 330479 ON I-40 WBL OVER BUCHANAN STREET</b>            | <b>BRIDGE No. 330489 ON I-40 EBL OVER NC 150 RAMPS</b>    |

**INDEX OF STRUCTURES SHEETS**

<u>SHEET No.</u>	<u>DESCRIPTION</u>	<u>SHEET No.</u>	<u>DESCRIPTION</u>	<u>SHEET No.</u>	<u>DESCRIPTION</u>
<b>STRUCTURE No. 330481</b>		<b>STRUCTURE No. 330486</b>		<b>STRUCTURE No. 330488</b>	
S9-01	GENERAL DRAWING	S11-01	GENERAL DRAWING	S13-01	GENERAL DRAWING
S9-02	TYPICAL SECTION	S11-02	TYPICAL SECTION	S13-02	TYPICAL SECTION
S9-03	DECK SURFACE REPAIR	S11-03	DECK SURFACE REPAIR	S13-03	DECK SURFACE REPAIR
S9-04	END BENT JOINT DETAILS	S11-04	JOINT DETAILS	S13-04	END BENT JOINT DETAILS
S9-05	BENT JOINT DETAILS	<b>STRUCTURE No. 330487</b>		S13-05	BENT JOINT DETAILS
<b>STRUCTURE No. 330482</b>		S12-01	GENERAL DRAWING	S13-06	END BENTS
S10-01	GENERAL DRAWING	S12-02	TYPICAL SECTION	<b>STRUCTURE No. 330489</b>	
S10-02	TYPICAL SECTION	S12-03	DECK SURFACE REPAIR	S14-01	GENERAL DRAWING
S10-03	DECK SURFACE REPAIR	S12-04	JOINT DETAILS	S14-02	TYPICAL SECTION
S10-04	END BENT JOINT DETAILS			S14-03	DECK SURFACE REPAIR
S10-05	BENT JOINT DETAILS			S14-04	END BENT JOINT DETAILS
				S14-05	BENT JOINT DETAILS
				S14-06	END BENTS



**TYPE OF WORK:**

**BRIDGE PRESERVATION: DECK REPAIR, POLYESTER POLYMER CONCRETE OVERLAY, POURABLE SILICONE JOINT SEALANT AND FOAM JOINT REPLACEMENT, PAINTING EXISTING WEATHERING STEEL STRUCTURE, PAINTING OF BEARINGS FOR THESE BRIDGES IS INCLUDED IN THE STRUCTURE STEEL PAINTING, CLEAN AND EPOXY COAT EXISTING PRESTRESSED CONCRETE GIRDER ENDS, REMOVE DEBRIS FROM TOP OF EXISTING END BENT & BENT CAPS AND APPLY EPOXY COATING AND SUBSTRUCTURE REPAIR**

Prepared in the Office of:  
**DIVISION OF HIGHWAYS**  
STRUCTURES MANAGEMENT UNIT  
1000 BIRCH RIDGE DR.  
RALEIGH, N.C. 27610

STATE OF NORTH CAROLINA  
DIVISION OF HIGHWAYS

**FORSYTH COUNTY**

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	I-5795	3A	
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
53034.1.2	-	P.E.	
53034.3.1	NHPP-0040(032)	CONST.	

**LOCATION: FORSYTH COUNTY:**



BRIDGE No. 330161 ON I-40 EBL OVER MUDDY CREEK  
BRIDGE No. 330162 ON I-40 WBL OVER MUDDY CREEK  
BRIDGE No. 330444 ON US 421 SBL RAMP OVER I-40 & I-40 BUS  
BRIDGE No. 330448 ON I-40 EBL OVER WESTGATE DRIVE  
BRIDGE No. 330449 ON I-40 WBL OVER WESTGATE DRIVE  
BRIDGE No. 330508 ON I-40 WBL OVER I-40 BUS EBL  
BRIDGE No. 330509 ON I-40 WBL RAMP OVER I-40 BUS AND US 421 EBL

**INDEX OF STRUCTURES SHEETS**

<u>SHEET No.</u>	<u>DESCRIPTION</u>	<u>SHEET No.</u>	<u>DESCRIPTION</u>	<u>SHEET No.</u>	<u>DESCRIPTION</u>	<u>SHEET No.</u>	<u>DESCRIPTION</u>
<b>STRUCTURE No. 330161</b>		<b>STRUCTURE No. 330444</b>		<b>STRUCTURE No. 330449</b>		<b>STRUCTURE No. 330509</b>	
S15-01	GENERAL DRAWING	S17-01	GENERAL DRAWING	S19-01	GENERAL DRAWING	S21-01	GENERAL DRAWING
S15-02	TYPICAL SECTION	S17-02	GENERAL DRAWING	S19-02	TYPICAL SECTION	S21-02	GENERAL DRAWING
S15-03	DECK SURFACE REPAIR	S17-03	TYPICAL SECTION	S19-03	DECK SURFACE REPAIR	S21-03	TYPICAL SECTION
S15-04	DECK UNDERSIDE REPAIR	S17-04	DECK SURFACE REPAIR	S19-04	JOINT DETAILS	S21-04	DECK SURFACE REPAIR SPANS A & B
S15-05	JOINT DETAILS	S17-05	DECK SURFACE REPAIR	S19-05	END BENTS	S21-05	DECK SURFACE REPAIR SPAN C
S15-06	END BENTS	S17-06	JOINT DETAILS	S19-06	BENT	S21-06	DECK SURFACE REPAIR SPAN D
S15-07	BENT	S17-07	JOINT DETAILS	<b>STRUCTURE No. 330508</b>		S21-07	DECK SURFACE REPAIR SPANS E & F
<b>STRUCTURE No. 330162</b>		S17-08	JOINT DETAILS	S20-01	GENERAL DRAWING	S21-08	JOINT DETAILS
S16-01	GENERAL DRAWING	S17-09	JOINT DETAILS	S20-02	TYPICAL SECTION	S21-09	JOINT DETAILS
S16-02	TYPICAL SECTION	S17-10	BENT	S20-03	DECK SURFACE REPAIR	S21-10	JOINT DETAILS
S16-03	DECK SURFACE REPAIR	<b>STRUCTURE No. 330448</b>		S20-04	JOINT DETAILS	S21-11	JOINT DETAILS
S16-04	DECK UNDERSIDE REPAIR	S18-01	GENERAL DRAWING				
S16-05	JOINT DETAILS	S18-02	TYPICAL SECTION				
		S18-03	DECK SURFACE REPAIR				
		S18-04	DECK UNDERSIDE REPAIR				
		S18-05	JOINT DETAILS				
		S18-06	END BENTS				
		S18-07	BENT				
		<b>STANDARD SHEETS</b>					
		SD-1	TYPICAL CAP AND COLUMN REPAIR DETAILS				
		SD-2	DIAPHRAGM REPAIR DETAILS				
		SD-3	JACKING DETAILS				
		SN	STANDARD NOTES				

PROJECT: I-5795

CONTRACT NO: C203978



**TYPE OF WORK:**

BRIDGE PRESERVATION: DECK REPAIR, SILANE DECK TREATMENT, SILANE BARRIER RAIL TREATMENT, JOINT REPLACEMENT, BRIDGE JACKING, PAINTING EXISTING WEATHERING STEEL STRUCTURE, CLEANING AND PAINTING EXISTING BEARINGS WITH HRCSA, CLEAN AND EPOXY COAT EXISTING PRESTRESSED CONCRETE GIRDER ENDS, REMOVE DEBRIS FROM TOP OF EXISTING END BENT & BENT CAPS AND APPLY EPOXY COATING AND SUBSTRUCTURE REPAIR


Prepared in the Office of:  
**DIVISION OF HIGHWAYS**  
STRUCTURES MANAGEMENT UNIT  
1000 BIRCH RIDGE DR.  
RALEIGH, N.C. 27610

**NOTES**

INFORMATION INDICATED ON THE LOCATION SKETCH SHALL BE CONSIDERED GENERAL INFORMATION ONLY. THE CONTRACTOR SHALL CONFIRM, THROUGH OTHER SOURCES, SPECIFIC INFORMATION REGARDING BRIDGES, ROADWAYS, UTILITIES, THE SURROUNDING AREA, AND ANY OTHER ASPECTS THAT MAY BE NECESSARY TO PERFORM AND COMPLETE THE PROJECT.



**BRIDGE 330439 LOCATION SKETCH**



**BRIDGE 330441 LOCATION SKETCH**



**BRIDGE 330458 LOCATION SKETCH**




**BRIDGES 330451 & 330452 LOCATION SKETCH**



**BRIDGE 330454 LOCATION SKETCH**

<b>BRIDGE COORDINATES</b>		
BRIDGE NO.	LATITUDE	LONGITUDE
330439	36°-05'-07.58"	80°-03'-49.30"
330441	36°-03'-58.41"	80°-18'-28.68"
330451	36°-03'-51.93"	80°-18'-01.77"
330452	36°-03'-52.67"	80°-18'-01.12"
330454	36°-03'-55.32"	80°-15'-29.56"
330458	36°-04'-30.03"	80°-06'-34.38"

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330439, 330441, 330451  
330452, 330454, 330458  
 SHEET 1 OF 6



STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH  
  
 LOCATION SKETCHES

DRAWN BY : R.L.PUTEK DATE : 06/2020  
 CHECKED BY : K.P.SEDAI DATE : 06/2020


DOCUMENT NOT CONSIDERED  
 FINAL UNLESS ALL  
 SIGNATURES COMPLETED

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-1
1			3			TOTAL SHEETS
2			4			6


**NOTES**

INFORMATION INDICATED ON THE LOCATION SKETCH SHALL BE CONSIDERED GENERAL INFORMATION ONLY. THE CONTRACTOR SHALL CONFIRM, THROUGH OTHER SOURCES, SPECIFIC INFORMATION REGARDING BRIDGES, ROADWAYS, UTILITIES, THE SURROUNDING AREA, AND ANY OTHER ASPECTS THAT MAY BE NECESSARY TO PERFORM AND COMPLETE THE PROJECT.

<b>BRIDGE COORDINATES</b>		
BRIDGE No.	LATITUDE	LONGITUDE
330479	36°-03'-55.09"	80°-15'-06.77"
330480	36°-03'-54.25"	80°-15'-06.73"
330481	36°-03'-53.47"	80°-14'-53.69"
330482	36°-03'-52.66"	80°-14'-53.19"
330486	36°-03'-44.69"	80°-16'-12.36"
330487	36°-03'-43.90"	80°-16'-11.92"
330488	36°-03'-52.95"	80°-15'-46.68"
330489	36°-03'-52.25"	80°-15'-45.89"




**BRIDGES 330479 & 330480 LOCATION SKETCH**



**BRIDGES 330481 & 330482 LOCATION SKETCH**




**BRIDGES 330486 & 330487 LOCATION SKETCH**



**BRIDGES 330488 & 330489 LOCATION SKETCH**

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330479, 330480, 330481  
330482, 330486, 330487  
330488, 330489

SHEET 2 OF 6



STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH  
  
 LOCATION SKETCHES

DRAWN BY : R.L.PUTEK DATE : 06/2020  
 CHECKED BY : K.P.SEDAII DATE : 06/2020

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-2
1			3			TOTAL SHEETS
2			4			6

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED




**NOTES**


INFORMATION INDICATED ON THE LOCATION SKETCH SHALL BE CONSIDERED GENERAL INFORMATION ONLY. THE CONTRACTOR SHALL CONFIRM, THROUGH OTHER SOURCES, SPECIFIC INFORMATION REGARDING BRIDGES, ROADWAYS, UTILITIES, THE SURROUNDING AREA, AND ANY OTHER ASPECTS THAT MAY BE NECESSARY TO PERFORM AND COMPLETE THE PROJECT.



**BRIDGES 330161 & 330162 LOCATION SKETCH**



**BRIDGES 330448 & 330449 LOCATION SKETCH**




**BRIDGES 330444, 330508 & 330509 LOCATION SKETCH**

<b>BRIDGE COORDINATES</b>		
BRIDGE No.	LATITUDE	LONGITUDE
330161	36°-02'-49.61"	80°-21'-58.66"
330162	36°-02'-50.70"	80°-21'-59.31"
330444	36°-04'-11.90"	80°-19'-42.59"
330448	36°-04'-04.44"	80°-18'-45.43"
330449	36°-04'-05.17"	80°-18'-44.68"
330508	36°-04'-17.77"	80°-19'-32.66"
330509	36°-04'-20.90"	80°-19'-29.13"

PROJECT NO. I-5795  
 FORSYTH COUNTY

BRIDGE NO. 330161, 330162, 330444  
330448, 330449, 330508, 330509

SHEET 3 OF 6



STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

LOCATION SKETCHES

DRAWN BY : R.L.PUTEK DATE : 06/2020  
 CHECKED BY : K.P.SEDA DATE : 06/2020

DOCUMENT NOT CONSIDERED  
 FINAL UNLESS ALL  
 SIGNATURES COMPLETED


REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-3
1			3			TOTAL SHEETS
2			4			6

TOTAL BILL OF MATERIAL

BRIDGE NO.	GROOVING BRIDGE FLOORS	EPOXY COATED REINFORCING STEEL	POLLUTION CONTROL	CLASS II SURFACE PREPARATION	SURFACE PREPARATION FOR CONCRETE BARRIER RAIL	CONCRETE REPAIRS	SHOTCRETE REPAIRS	EPOXY RESIN INJECTION	FOAM JOINT SEALS FOR PRESERVATION	CLEANING & PAINTING EXISTING WEATHERING STEEL FOR BRIDGE NO...	MOLDED RUBBER SEGMENTAL EXPANSION JOINT	PAINTING CONTAINMENT FOR BRIDGE NO...	VOLUMETRIC MIXER	POURABLE SILICONE JOINT SEALANT	POLYESTER POLYMER CONCRETE MATERIALS
	SO. FT.	LBS.	LUMP SUM	SO. YDS.	SO. FT.	CU. FT.	CU. FT.	LIN. FT.	LIN. FT.	LUMP SUM	LUMP SUM	LUMP SUM	LUMP SUM	LIN. FT.	CU. YDS.
330439	15,693	-	-	51.3	-	-	0.6	-	227.7	-	-	-	-	154.0	63.7
330441	20,573	-	LUMP SUM	46.3	-	-	12.2	-	256.5	LUMP SUM	-	LUMP SUM	-	174.8	84.3
330451	10,854	-	LUMP SUM	33.6	-	-	-	-	123.0	LUMP SUM	-	LUMP SUM	-	126.0	44.9
330452	10,983	-	LUMP SUM	27.2	-	-	-	-	-	LUMP SUM	-	LUMP SUM	-	252.0	45.4
330454	25,008	-	LUMP SUM	60.4	-	-	-	-	-	LUMP SUM	-	LUMP SUM	-	510.0	102.6
330458	10,591	-	-	34.2	-	-	-	-	153.6	-	-	-	-	102.4	43.1
330479	8,731	-	-	27.2	-	25.7	3.2	6.0	-	-	-	-	-	232.8	34.5
330480	7,248	-	-	25.6	-	-	3.0	6.0	-	-	-	-	-	232.8	30.3
330481	6,944	-	-	31.1	-	-	-	4.0	116.6	-	-	-	-	120.0	29.0
330482	7,629	-	-	34.2	-	-	-	-	129.2	-	-	-	-	134.7	31.6
330486	12,617	-	-	28.6	-	-	-	-	-	-	-	-	-	264.0	52.1
330487	10,961	-	-	25.0	-	-	-	-	-	-	-	-	-	232.0	45.6
330488	11,769	-	LUMP SUM	38.6	-	-	5.1	5.0	146.8	LUMP SUM	-	LUMP SUM	-	149.2	48.4
330489	9,701	-	LUMP SUM	33.5	-	-	0.2	2.7	128.6	LUMP SUM	-	LUMP SUM	-	131.0	39.4
330161	-	-	-	-	1368.0	2.2	11.6	4.0	157.4	-	-	-	-	-	-
330162	-	-	-	-	1368.0	-	2.5	-	157.4	-	-	-	-	-	-
330444	-	1726	LUMP SUM	-	4124.0	-	1.5	-	-	LUMP SUM	LUMP SUM	LUMP SUM	LUMP SUM	-	-
330448	-	-	-	-	969.7	-	3.6	5.0	284.4	-	-	-	-	-	-
330449	-	-	-	-	1042.4	-	0.6	13.5	284.4	-	-	-	-	-	-
330508	-	-	LUMP SUM	12.4	2769.0	-	-	-	112.0	LUMP SUM	-	LUMP SUM	-	-	-
330509	-	1410	LUMP SUM	-	5784.0	-	-	-	-	LUMP SUM	LUMP SUM	LUMP SUM	LUMP SUM	-	-
TOTAL	169,302	3,136	LUMP SUM	509.2	17,425.1	27.9	44.1	46.2	2,277.6	LUMP SUM	LUMP SUM	LUMP SUM	LUMP SUM	2,815.7	694.9

PROJECT NO. I-5795  
FORSYTH COUNTY

BRIDGE NO. 439, 441, 451, 452, 454, 458, 479, 480, 481, 482, 486, 487, 488, 489, 161, 162, 444, 448, 449, 508 & 509  
 SHEET 4 OF 6



STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH  
**TOTAL  
 BILL OF MATERIALS**

DRAWN BY : A. SORSENGINH DATE : 1/2020  
 CHECKED BY : H. A. LOCKLEAR DATE : 4/2020


DOCUMENT NOT CONSIDERED  
 FINAL UNLESS ALL  
 SIGNATURES COMPLETED

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-4
1			3			TOTAL SHEETS
2			4			6

**TOTAL BILL OF MATERIAL**

BRIDGE NO.	CONCRETE DECK REPAIR FOR POLYESTER POLYMER CONCRETE OVERLAY	ELASTOMERIC CONCRETE FOR PRESERVATION	BRIDGE JOINT DEMOLITION	CONCRETE DECK REPAIR FOR SILANE DECK TREATMENT	EPOXY COATING	EPOXY COATING CONCRETE GIRDER ENDS	JOINT REPAIR	PLACING & FINISHING POLYESTER POLYMER CONCRETE OVERLAY	SCARIFYING BRIDGE DECK	SHOTBLASTING BRIDGE DECK	SILANE DECK TREATMENT	SILANE BARRIER RAIL TREATMENT	CLEANING & PAINTING EXISTING BEARINGS WITH HRCSA BRIDGE NO....	TYPE I BRIDGE JACKING
	SO. YDS.	CU. FT.	SO. FT.	SO. FT.	SO. FT.	SO. FT.	SO. FT.	SO. YDS.	SO. YDS.	SO. YDS.	SO. YDS.	SO. FT.	EA.	EA.
330439	51.3	-	-	-	1100.0	1700.0	-	1,828	1,828	1,828	-	-	-	-
330441	46.3	-	-	-	1271.0	-	-	2,425	2,425	2,425	-	-	-	-
330451	33.6	-	-	-	708.0	-	-	1,292	1,292	1,292	-	-	-	-
330452	27.2	-	-	-	708.0	-	-	1,307	1,307	1,307	-	-	-	-
330454	60.4	-	-	-	1277.0	-	-	2,956	2,956	2,956	-	-	-	-
330458	34.2	-	-	-	713.0	1075.6	-	1,240	1,240	1,240	-	-	-	-
330479	27.2	-	-	-	582.8	909.0	-	988	988	988	-	-	-	-
330480	25.6	-	-	-	582.8	909.0	-	875	875	875	-	-	-	-
330481	31.1	-	-	-	626.8	790.2	-	831	831	831	-	-	-	-
330482	34.2	-	-	-	694.8	790.2	-	912	912	912	-	-	-	-
330486	28.6	-	-	-	656.7	1252.9	-	1,494	1,494	1,494	-	-	-	-
330487	25.0	-	-	-	571.3	1096.3	-	1,309	1,309	1,309	-	-	-	-
330488	38.6	-	-	-	841.0	-	-	1,393	1,393	1,393	-	-	-	-
330489	33.5	-	-	-	739.0	-	-	1,137	1,137	1,137	-	-	-	-
330161	-	39.4	157.4	5.7	927.4	484.2	-	-	-	1,833	1,833	1,368.0	-	1
330162	-	39.4	157.4	5.0	927.4	484.2	-	-	-	1,833	1,833	1,368.0	-	-
330444	-	-	-	-	233.0	-	568.0	-	-	3,266	3,266	4,124.0	12	-
330448	-	71.2	284.4	-	922.2	1156.4	-	-	-	1,207	1,207	969.7	-	-
330449	-	71.2	284.4	6.3	922.2	1156.4	-	-	-	1,303	1,303	1,042.4	-	-
330508	-	28.0	-	112.0	389.0	-	-	-	-	2,624	2,624	2,769.0	12	-
330509	-	-	-	-	293.6	-	473.4	-	-	3,746	3,746	5,784.0	10	-
TOTAL	496.8	249.2	883.6	129.0	15,687.0	11,804.4	1,041.4	19,987	19,987	35,799	15,812	17,425.1	34	1

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 439, 441, 451, 452, 454,  
458, 479, 480, 481, 482, 486, 487, 488,  
489, 161, 162, 444, 448, 449, 508 & 509  
 SHEET 5 OF 6



STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH  
  
**TOTAL  
 BILL OF MATERIALS**

DRAWN BY : A. SORSENGINH DATE : 1/2020  
 CHECKED BY : H. A. LOCKLEAR DATE : 4/2020

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-5
1			3			TOTAL SHEETS
2			4			6

DOCUMENT NOT CONSIDERED  
 FINAL UNLESS ALL  
 SIGNATURES COMPLETED

## NOTES

REPAIR LOCATIONS AND ESTIMATES OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS.

EXISTING DIMENSIONS AND BRIDGE CONDITION ARE FROM THE BEST INFORMATION AVAILABLE. THE CONTRACTOR SHALL FIELD VERIFY THE INFORMATION SHOWN ON THE PLANS AND NOTIFY THE ENGINEER IF ACTUAL DIMENSIONS AND CONDITIONS DIFFER.

THE CONTRACTOR SHALL HAVE NO CLAIM WHATSOEVER AGAINST THE DEPARTMENT FOR ANY DELAYS OR ADDITIONAL COST INCURRED BASED ON DIFFERENCES BETWEEN WHAT IS SHOWN ON THE PLANS AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

IT IS THE CONTRACTOR'S RESPONSIBILITY TO FOLLOW ALL STATE AND FEDERAL SAFETY REQUIREMENTS.

EXISTING JOINTS AND DECK DRAINS SHALL BE SEALED PRIOR TO BEGINNING SURFACE PREPARATIONS OF THE BRIDGE DECK. THE CONTRACTOR SHALL TAKE CARE THAT ANY CONSTRUCTION DEBRIS THAT COLLECTS IN THE DRAINS IS CONTAINED. DRAINS IN SHOULDERS OF ADJACENT TRAVEL LANE(S) SHALL BE KEPT FREE AND CLEAR OF DEBRIS.

LONGITUDINAL CONSTRUCTION JOINTS OF OVERLAYS SHALL BE LOCATED ALONG THE CENTERLINE OR EDGE OF TRAVEL LANES.

WORK ON THE BRIDGES SHALL BE PERFORMED SO AS NOT TO ALLOW DEBRIS TO FALL BELOW. THE CONTRACTOR SHALL SUBMIT PLANS FOR CONSTRUCTION IN ACCORDANCE WITH ARTICLE 402-2 OF THE STANDARD SPECIFICATIONS AND THE PROJECT SPECIAL PROVISIONS.

THE CONTRACTOR SHALL PERFORM ALL WORK WITH CARE SO THAT THE EXISTING STRUCTURE WHICH IS TO REMAIN IN PLACE WILL NOT BE DAMAGED. IF THE CONTRACTOR DAMAGES ANY PART OF THE EXISTING STRUCTURE WHICH IS TO REMAIN IN PLACE, THE DAMAGED AREA SHALL BE REPAIRED OR REPLACED IN A MANNER SATISFACTORY TO THE ENGINEER AT NO ADDITIONAL COST TO THE DEPARTMENT.

CONTRACTOR SHALL DETERMINE EXTENT OF WORKING AREA, STAGING PROCESS, AND INSTALL COVER & ASSEMBLY AS NECESSARY TO MEET THE REQUIREMENTS OF TRAFFIC MANAGEMENT PLANS.

PRIOR TO BEGINNING WORK, THE CONTRACTOR SHALL SUBMIT FOR REVIEW AND APPROVAL A COMPLETE SEQUENCE OF TASKS FOR EACH OPERATION AFFECTING THE BRIDGE SURFACE AND/OR TRAFFIC.

FOR CONTROL OF TRAFFIC AND LIMITS ON PHASING OF CONSTRUCTION, SEE TRANSPORTATION MANAGEMENT PLANS.

EXISTING MODULAR JOINT AND DECK REINFORCING STEEL SHOWN IS BASED ON BEST INFORMATION AVAILABLE.

FOR BRIDGE JACKING, SEE SPECIAL PROVISIONS.

ALL PROPOSED EXPANSION JOINT DIMENSIONS, OPENINGS AND BLOCKOUTS ARE SHOWN AT 60 DEGREES FAHRENHEIT. CONTRACTOR SHALL FOLLOW MANUFACTURER'S INSTALLATION GUIDELINES AND MAKE ANY NECESSARY ADJUSTMENTS.

ADHESIVE ANCHOR BOLTS AND HARDWARE FOR THE PROPOSED EXPANSION JOINT SHALL BE GALVANIZED PER ASTM A153 AND INSTALLED PER THE MANUFACTURER'S RECOMMENDATIONS.

FOR EPOXY COATED REINFORCING STEEL, SEE 2018 NORTH CAROLINA STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES, SECTION 425.

THE CONTRACTOR SHALL PROVIDE INDEPENDENT ASSURANCE SAMPLES OF REINFORCING STEEL AS FOLLOWS: FOR PROJECTS REQUIRING UP TO 400 TONS OF REINFORCING STEEL, ONE 30 INCH SAMPLE OF EACH SIZE BAR USED, AND FOR PROJECTS REQUIRING OVER 400 TONS OF REINFORCING STEEL, TWO 30 INCH SAMPLES OF EACH SIZE BAR USED. THE BARS FROM WHICH THE SAMPLES ARE TAKEN MUST THEN BE SPLICED WITH REPLACEMENT BARS OF THE SIZE AND LENGTH OF THE SAMPLE, PLUS A MINIMUM LAP SPLICE OF THIRTY BAR DIAMETERS. PAYMENT FOR THE SAMPLES OF REINFORCING STEEL SHALL BE CONSIDERED INCIDENTAL TO VARIOUS PAY ITEMS.

AT THE TIME OF PREPARATION OF THESE PLANS, IT WAS NOT ANTICIPATED THAT ITEMS SHOWN BELOW WOULD BE REQUIRED. HOWEVER, IT MAY BE DETERMINED IN THE FIELD THAT THESE ITEMS, OR OTHER WORK WILL BE NECESSARY TO PROPERLY COMPLETE THE INTENDED BRIDGE PRESERVATION/REHABILITATION WORK. THE CONTRACTOR SHALL BE PREPARED TO PERFORM SUCH WORK IN A TIMELY MANNER, AS DETERMINED IN THE FIELD. SUCH WORK SHALL BE CONSIDERED EXTRA WORK AND SHALL BE ADDRESSED AS PER ARTICLE 104-7 OF THE STANDARD SPECIFICATIONS. PROJECT SPECIAL PROVISIONS THAT OUTLINE REQUIREMENTS FOR THESE POTENTIAL ADDITIONAL WORK ITEMS HAVE BEEN PROVIDED IN PROJECT DOCUMENTS, BUT NO QUANTITIES HAVE BEEN LISTED. ACTUAL PAY ITEMS, QUANTITIES, AND COSTS WILL BE ESTABLISHED, AS REQUIRED, IF EXTRA WORK IS ENCOUNTERED.

UNANTICIPATED ITEMS:

ITEM NO.	DESCRIPTION	UNIT
1	CLASS III SURFACE PREPARATION	LIN. FT.

FOR SCARIFYING BRIDGE DECK, SHOTBLASTING BRIDGE DECK AND CLASS II SURFACE PREPARATION, SEE OVERLAY SURFACE PREPARATION FOR POLYESTER POLYMER CONCRETE SPECIAL PROVISION.

FOR CONCRETE DECK REPAIR FOR PPC OVERLAY, PPC MATERIALS, AND PLACING AND FINISHING PPC OVERLAY, SEE POLYESTER POLYMER CONCRETE BRIDGE DECK OVERLAY SPECIAL PROVISION.

THE ELEVATION(S) AND CLEARANCE(S) SHOWN ON THE PLANS AT THE POINT(S) OF MINIMUM VERTICAL CLEARANCE ARE FROM THE BEST INFORMATION AVAILABLE. PRIOR TO BEGINNING BRIDGE CONSTRUCTION, VERIFY THE ELEVATION(S) ON THE EXISTING PAVEMENT AND CHECK THE CLEARANCE. REPORT ANY VARIATIONS TO THE ENGINEER. ANY PLAN REVISIONS NECESSARY TO ACHIEVE THE REQUIRED MINIMUM VERTICAL CLEARANCE WILL BE PROVIDED BY THE DEPARTMENT.

THE CONTRACTOR SHALL FIELD VERIFY THE EXISTING JOINT OPENING PRIOR TO ORDERING JOINT SEAL MATERIAL. IF ACTUAL JOINT OPENING VARIES FROM THE OPENING INDICATED IN DETAIL BY MORE THAN 1/4", NOTIFY ENGINEER. REVISION TO THE JOINT SEAL SIZE MIGHT BE NECESSARY.

CONTRACTOR SHALL HAVE A REPRESENTATIVE FROM THE JOINT MANUFACTURER PRESENT DURING INSTALLATION OF PROPOSED MOLDED RUBBER SEGMENTAL EXPANSION JOINT.

FOR POURABLE SILICONE JOINT SEALANT, SEE SPECIAL PROVISIONS.

FOR JOINT REPAIR, SEE SPECIAL PROVISIONS.

FOR SUBMITTAL OF WORKING DRAWINGS, SEE SPECIAL PROVISIONS.

FOR FALSEWORK AND FORMWORK, SEE SPECIAL PROVISIONS.

FOR GROUT FOR STRUCTURES, SEE SPECIAL PROVISIONS.

FOR CRANE SAFETY, SEE SPECIAL PROVISIONS.

FOR VOLUMETRIC MIXER, SEE SPECIAL PROVISIONS.

FOR SHOTCRETE REPAIRS, SEE SPECIAL PROVISIONS.

FOR CONCRETE REPAIRS, SEE SPECIAL PROVISIONS.

SHOTCRETE REPAIRS MAY BE REPLACED WITH CONCRETE REPAIRS WITH THE APPROVAL OF THE ENGINEER.

FOR PAINTING EXISTING WEATHERING STEEL STRUCTURE, SEE SPECIAL PROVISIONS.

FOR PAINTING CONTAINMENT AND POLLUTION CONTROL, SEE PAINTING EXISTING WEATHERING STEEL STRUCTURE SPECIAL PROVISION.

FOR PAINTING CONTAINMENT, POLLUTION CONTROL, AND CLEANING & PAINTING EXISTING BEARINGS WITH HPCSA, SEE CLEANING & PAINTING EXISTING BEARINGS WITH HPCSA SPECIAL PROVISION.

FOR EPOXY COATING AND DEBRIS REMOVAL, SEE SPECIAL PROVISIONS.

FOR EPOXY RESIN INJECTIONS (ERI), SEE SPECIAL PROVISIONS.

FOR SILANE DECK TREATMENT, SEE SPECIAL PROVISIONS.

FOR FOAM JOINT SEALS FOR PRESERVATION, SEE SPECIAL PROVISIONS.

FOR CONCRETE DECK REPAIR FOR SILANE DECK TREATMENT, SEE SPECIAL PROVISIONS.

FOR BRIDGE JOINT DEMOLITION, SEE SPECIAL PROVISIONS.

FOR CONCRETE FOR DECK REPAIR, SEE SPECIAL PROVISIONS.


FOR ELASTOMERIC CONCRETE FOR PRESERVATION, SEE SPECIAL PROVISIONS.

FOR EPOXY COATING CONCRETE GIRDER ENDS, SEE SPECIAL PROVISIONS.

FOR SILANE BARRIER RAIL TREATMENT, SEE SPECIAL PROVISIONS.

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330439, 330441, 330451  
 330452, 330454, 330458, 330479  
 330480, 330481, 330482, 330486  
 330487, 330488, 330489, 330161  
 330162, 330444, 330448, 330449  
 330508, 330509

SHEET 6 OF 6



STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

### GENERAL NOTES

DRAWN BY : A. SORSENGINH DATE : 04/2020  
 CHECKED BY : E. BAYISSA DATE : 04/2020


DOCUMENT NOT CONSIDERED  
 FINAL UNLESS ALL  
 SIGNATURES COMPLETED

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-6
1			3			TOTAL SHEETS
2			4			6

**NOTES**

GENERAL DRAWING INFORMATION IS TAKEN FROM THE ORIGINAL PLANS AND THE ROUTINE INSPECTION REPORT DATED 7/18/2018.


BRIDGE ORIENTATION CONFORMS TO THE EXISTING BRIDGE PLANS.



**SECTION ALONG Q BRIDGE**

**SCOPE OF WORK**

- PARTIALLY REMOVE TOP OF BRIDGE DECK CONCRETE BY SCARIFICATION AND SHOTBLASTING METHODS.
- OVERLAY PREPARED TOP OF BRIDGE DECK WITH POLYESTER POLYMER CONCRETE (PPC).
- REMOVE EXISTING JOINT MATERIAL AND INSTALL FOAM JOINTS.
- REMOVE EXISTING JOINT MATERIAL AND INSTALL POURABLE SILICONE JOINTS.
- GROOVE PPC BRIDGE DECK.
- CLEAN AND EPOXY COAT EXISTING PRESTRESSED CONCRETE GIRDER ENDS.
- REMOVE DEBRIS FROM TOP OF EXISTING END BENT AND BENT CAPS AND APPLY EPOXY COATING.
- REMOVE UNSOUND CONCRETE AND PROPERLY PREPARE EXISTING END BENT AND BENT AREAS FOR SHOTCRETE AND CONCRETE REPAIRS.





**PLAN**

I HEREBY CERTIFY THAT THIS STRUCTURE WAS REHABILITATED ACCORDING TO THESE PLANS OR AS NOTED HEREIN.

RESIDENT ENGINEER \_\_\_\_\_ DATE \_\_\_\_\_


PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330439




STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH  
**GENERAL DRAWING**  
 FOR BRIDGE ON NC 66  
 OVER I-40

DRAWN BY : C. RUIZ DATE : 08/2019  
 CHECKED BY : ASRA YASMEEN DATE : 08/2019


REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S1-01
1			3			TOTAL SHEETS 5
2			4			




TYPICAL SECTION  
(EXISTING)



TYPICAL SECTION - APPROACH SLAB  
(EXISTING)




TYPICAL SECTION  
(PROPOSED)




TYPICAL SECTION - APPROACH SLAB  
(PROPOSED)

NOTES:  
SEE TRANSPORTATION MANAGEMENT PLANS FOR LANE WIDTHS, SEQUENCING AND OTHER TRAFFIC CONTROL MEASURES FOR STAGING OF OVERLAY SURFACE PREPARATION AND POLYESTER POLYMER CONCRETE PLACEMENT.




DETAIL FOR POLYESTER  
POLYMER CONCRETE OVERLAY



STAGED PPC OVERLAY JOINT  
(AS NEEDED)

PROJECT NO. I-5795  
FORSYTH COUNTY  
BRIDGE NO. 330439




STATE OF NORTH CAROLINA  
DEPARTMENT OF TRANSPORTATION  
RALEIGH  
SUPERSTRUCTURE  
TYPICAL SECTION &  
PPC OVERLAY DETAIL

DRAWN BY : C. RUIZ DATE : 08/2019  
CHECKED BY : A. YASMEEN DATE : 02/2020

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S1-02
1			3			TOTAL SHEETS
2			4			5

DOCUMENT NOT CONSIDERED  
FINAL UNLESS ALL  
SIGNATURES COMPLETED



**AS-BUILT REPAIR QUANTITY TABLE**

TOP OF DECK REPAIRS	APPROACH SLAB 1		SPAN A		SPAN B		SPAN C		SPAN D		APPROACH SLAB 2	
	ESTIMATE	ACTUAL	ESTIMATE	ACTUAL	ESTIMATE	ACTUAL	ESTIMATE	ACTUAL	ESTIMATE	ACTUAL	ESTIMATE	ACTUAL
SCARIFYING BRIDGE DECK	91.0 SQ. YDS.		298.0 SQ. YDS.		523.0 SQ. YDS.		523.0 SQ. YDS.		302.0 SQ. YDS.		91.0 SQ. YDS.	
SHOTBLASTING BRIDGE DECK	91.0 SQ. YDS.		298.0 SQ. YDS.		523.0 SQ. YDS.		523.0 SQ. YDS.		302.0 SQ. YDS.		91.0 SQ. YDS.	
CLASS II SURFACE PREPARATION	0.0 SQ. YDS.		0.0 SQ. YDS.		0.6 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.	
CONCRETE DECK REPAIR FOR PPC OVERLAY	0.0 SQ. YDS.		0.0 SQ. YDS.		0.6 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.	
POLYESTER POLYMER CONCRETE MATERIALS	3.2 CU. YDS.		10.4 CU. YDS.		18.2 CU. YDS.		18.2 CU. YDS.		10.5 CU. YDS.		3.2 CU. YDS.	
PLACING & FINISHING PPC OVERLAY	91.0 SQ. YDS.		298.0 SQ. YDS.		523.0 SQ. YDS.		523.0 SQ. YDS.		302.0 SQ. YDS.		91.0 SQ. YDS.	
GROOVING BRIDGE FLOOR	651.0 SQ. FT.		2645.0 SQ. FT.		4534.0 SQ. FT.		4534.0 SQ. FT.		2678.0 SQ. FT.		651.0 SQ. FT.	
EPOXY COATING CONCRETE GIRDER ENDS			414.2 SQ. FT.		435.8 SQ. FT.		435.8 SQ. FT.		414.2 SQ. FT.			
EPOXY RESIN INJECTION			0.0 LIN. FT.		0.0 LIN. FT.		0.0 LIN. FT.		0.0 LIN. FT.			
SHOTCRETE REPAIRS	ESTIMATE		ACTUAL		ESTIMATE		ACTUAL		ESTIMATE		ACTUAL	
	AREA SQ. FT.	VOLUME CU. FT.	AREA SQ. FT.	VOLUME CU. FT.	AREA SQ. FT.	VOLUME CU. FT.	AREA SQ. FT.	VOLUME CU. FT.	AREA SQ. FT.	VOLUME CU. FT.	AREA SQ. FT.	VOLUME CU. FT.
CONCRETE BARRIER RAIL	0.0	0.0			0.0	0.0			0.0	0.0	1.7	0.6
EPOXY COATING	ESTIMATE		ACTUAL		ESTIMATE		ACTUAL		ESTIMATE		ACTUAL	
	AREA SQ. FT.		AREA SQ. FT.		AREA SQ. FT.		AREA SQ. FT.		AREA SQ. FT.		AREA SQ. FT.	
TOP OF CAP AT END BENTS 1 & 2 AND BENTS 1 THRU 3			1100.0		0.0							

**NOTES:**

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE BASED ON THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER WILL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATIONS AND DESCRIPTION OF THE REPAIRS AND ENTER THE ACTUAL QUANTITIES INTO THE AS-BUILT REPAIR QUANTITY TABLE.

FOR SECTION A-A AND SECTION B-B, SEE "JOINT DETAILS" SHEET.


FOR SCARIFYING BRIDGE DECK, SHOTBLASTING BRIDGE DECK AND CLASS II SURFACE PREPARATION, SEE OVERLAY SURFACE PREPARATION FOR POLYESTER POLYMER CONCRETE SPECIAL PROVISION.

FOR CONCRETE DECK REPAIR FOR PPC OVERLAY, PPC MATERIALS, AND PLACING AND FINISHING PPC OVERLAY, SEE POLYESTER POLYMER CONCRETE BRIDGE DECK OVERLAY SPECIAL PROVISION.

DECK SURFACE REPAIR QUANTITIES REPRESENT ESTIMATED VALUES OF CLASS II SURFACE PREPARATION AND CONCRETE DECK REPAIR FOR PPC OVERLAY AFTER REMOVAL OF UNSOUND CONCRETE (MIN. 2" CLEAR TO SAWCUT.) SEE OVERLAY SURFACE PREPARATION FOR POLYESTER POLYMER CONCRETE SPECIAL PROVISION.

CLEAN AND REMOVE DEBRIS FROM THE TOP OF THE CAP AND APPLY EPOXY PROTECTIVE COATING. EPOXY COATING SHALL BE APPLIED TO THE TOP SURFACE OF THE CAP. THE CONTRACTOR SHALL NOT COAT THE AREA OF THE CAP BENEATH THE MASONRY PLATES. FOR EPOXY COATING, SEE SPECIAL PROVISIONS.

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330439




STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

**DECK SURFACE REPAIR  
 SPANS A THRU D**


DRAWN BY : C. RUIZ DATE : 08/2019  
 CHECKED BY : A. YASMEEN DATE : 02/2020

DOCUMENT NOT CONSIDERED  
 FINAL UNLESS ALL  
 SIGNATURES COMPLETED


REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			S1-03
2			4			TOTAL SHEETS 5



EXISTING JOINT



MINIMUM EXISTING JOINT DEMOLITION & SCARIFICATION




PROPOSED JOINT WITH SAWED DIMENSIONS

Δ SAW CUT SHALL BE 3/4" BELOW THE BOTTOM OF THE JOINT SEAL. SEE MANUFACTURER RECOMMENDATIONS


JOINT INSTALLATION SEQUENCE AT END BENTS  
SECTION A-A

**NOTES:**  
 THE CONTRACTOR SHALL FIELD VERIFY THE EXISTING JOINT OPENING PRIOR TO ORDERING JOINT SEAL MATERIAL. IF ACTUAL JOINT OPENING VARIES FROM THE OPENING INDICATED IN DETAIL BY MORE THAN 1/4", NOTIFY ENGINEER. REVISION TO THE JOINT SEAL SIZE MIGHT BE NECESSARY.  
 FINAL JOINT SEALS SHALL NOT BE INSTALLED UNTIL THE OVERLAY IS COMPLETE.  
 THE CONTRACTOR SHALL TAKE CARE DURING JOINT REHAB OPERATIONS NOT TO DROP ANY MATERIAL BELOW THE BRIDGE WITHOUT PROTECTIVE DEVICES BELOW TO CATCH THE MATERIAL. ANY MATERIAL THAT FALLS BELOW THE BRIDGE SHALL BE CONTAINED, REMOVED AND DISPOSED OF BY THE CONTRACTOR AT NO EXTRA COST TO THE DEPARTMENT. IF THE ENGINEER DETERMINES THAT THE PROTECTIVE DEVICES ARE NOT ADEQUATE OR NOT BEING EMPLOYED, THE WORK SHALL BE SUSPENDED UNTIL ADEQUATE PROTECTION IS PROVIDED.  
 THE CONTRACTOR WILL NOT BE PERMITTED TO FORM THE JOINTS IN LIEU OF SAWING THE JOINT.  
 DURING THE JOINT INSTALLATION PROCEDURE, THE JOINT AND SURROUNDING AREA SHALL BE KEPT CLEAN AND FREE OF DEBRIS.  
 FOR POURABLE SILICONE JOINT SEALANT, SEE SPECIAL PROVISIONS.  
 THE MANUFACTURER IS TO PROVIDE THE NOMINAL UNCOMPRESSED SEAL WIDTH OF THE BACKER ROD FOR THE EXISTING JOINT SIZE AND ACCOMMODATE THE MINIMUM EXPANSION SHOWN ON THE PLANS.  
 A MANUFACTURER'S CERTIFIED TRAINED REPRESENTATIVE SHALL BE PRESENT DURING THE INSTALLATION OF THE FIRST JOINT OF THE PROJECT, OR UNTIL THE ENGINEER IS SATISFIED WITH THE INSTALLATION PROCESS.  
 THE INSTALLATION OF THE JOINT SEAL SHALL BE WATERTIGHT.  
 FINAL SURFACE OF THE JOINT DEMOLITION AREA PRIOR TO PLACEMENT OF CONCRETE REPAIR MATERIAL SHOULD BE REASONABLY FLAT AND LEVEL. ENGINEER SHALL DETERMINE THE ACCEPTABILITY OF THE SURFACE PRIOR TO PLACEMENT OF REPAIR CONCRETE.


JOINT REPAIR QUANTITY TABLE		
	CLASS II SURFACE PREPARATION	CONCRETE DECK REPAIR FOR PPC OVERLAY
END BENT 1	8.4 SY	8.4 SY
END BENT 2	8.4 SY	8.4 SY
TOTAL	16.8 SY	16.8 SY



PLAN (@ END BENT)




SECTION C-C



DETAIL "A"

JOINT REPAIR QUANTITY TABLE			
	ESTIMATE	ACTUAL	
POURABLE SILICONE JOINT SEALANT			
END BENT 1	77 LF		
END BENT 2	77 LF		
TOTAL	154 LF		

PROJECT NO. I-5795  
 FORSYTH  
 BRIDGE NO. 330439



STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

JOINT DETAILS

DRAWN BY : C. RUIZ DATE : 08/2019  
 CHECKED BY : ASRA YASMEEN DATE : 08/2019

NO.	REVISIONS			NO.	REVISIONS			SHEET NO.
	BY:	DATE:			BY:	DATE:		
1				3			S1-04	
2				4			TOTAL SHEETS 5	

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED



**NOTES**

FOAM JOINTS SHALL BE INSTALLED AS PER MANUFACTURER'S RECOMMENDATIONS.

FOR FOAM JOINT SEALS FOR PRESERVATION, SEE SPECIAL PROVISIONS.

THE INSTALLED FOAM JOINTS SHALL BE WATER TIGHT.


THE FOAM JOINTS SHALL MEET THE MANUFACTURER'S RECOMMENDATION FOR THE SIZE OF OPENING ON THE PLANS, AND ACCOMMODATE THE MINIMUM EXPANSION SHOWN ON THE PLANS.

THE CONTRACTOR WILL NOT BE PERMITTED TO FORM THE JOINTS IN LIEU OF SAWING THE JOINT.

THE MANUFACTURER IS TO PROVIDE THE NOMINAL UNCOMPRESSED SEAL WIDTH OF THE FOAM JOINT SEAL BASED ON JOINT OPENINGS AT THE BENTS.

CONTRACTOR SHALL FIELD VERIFY THE EXISTING JOINT OPENING PRIOR TO ORDERING JOINT SEAL MATERIAL. IF ACTUAL JOINT OPENING VARIES FROM OPENING INDICATED IN DETAIL BY MORE THAN 1/4", NOTIFY ENGINEER REVISION TO THE JOINT SEAL SIZE MIGHT BE NECESSARY.

FINAL SURFACE OF THE JOINT DEMOLITION AREA PRIOR TO PLACEMENT OF CONCRETE REPAIR MATERIAL SHALL BE REASONABLY FLAT AND LEVEL. ENGINEER SHALL DETERMINE THE ACCEPTABILITY OF THE SURFACE PRIOR TO PLACEMENT OF REPAIR CONCRETE.



MINIMUM EXISTING JOINT DEMOLITION

PROPOSED PRE-SAWED JOINT


PROPOSED FOAM JOINT SEAL

▲ SAW CUT SHALL BE 3/4" BELOW THE BOTTOM OF THE JOINT SEAL, SEE MANUFACTURER RECOMMENDATIONS

**JOINT INSTALLATION SEQUENCE AT BENTS**  
SECTION B-B


	CLASS II SURFACE PREPARATION		CONCRETE DECK REPAIR FOR PPC OVERLAY	
	ESTIMATED	ACTUAL	ESTIMATED	ACTUAL
BENT 1	11.3 SY		11.3 SY	
BENT 2	11.3 SY		11.3 SY	
BENT 3	11.3 SY		11.3 SY	
* TOTAL	33.9 SY		33.9 SY	

\* BASED ON THE BLOCKOUT SHOWN.



**JOINT SEAL DETAILS AT BENTS**

FOAM JOINT SEALS FOR PRESERVATION	ESTIMATED	ACTUAL
BENT 1	75.9 LF	
BENT 2	75.9 LF	
BENT 3	75.9 LF	
TOTAL	227.7 LF	



PROJECT NO. I-5795  
FORSYTH COUNTY  
BRIDGE NO. 330439

STATE OF NORTH CAROLINA  
DEPARTMENT OF TRANSPORTATION  
RALEIGH

**JOINT DETAILS  
BENTS 1, 2 & 3**

DRAWN BY : A. SORSENGINH DATE : 5/2020  
CHECKED BY : ASRA YASMEEN DATE : 5/2020

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	SHEET NO.
1			3			S1-05
2			4			TOTAL SHEETS 5

**NOTES**

GENERAL DRAWING INFORMATION IS TAKEN FROM THE ORIGINAL PLANS AND THE ROUTINE INSPECTION REPORT DATED 8/16/2018.

BRIDGE ORIENTATION CONFORMS TO EXISTING BRIDGE PLANS.

**SCOPE OF WORK**

PARTIALLY REMOVE TOP OF BRIDGE DECK CONCRETE BY SCARIFICATION AND SHOTBLASTING METHODS.

OVERLAY PREPARED TOP OF BRIDGE DECK WITH POLYESTER POLYMER CONCRETE (PPC).

REMOVE EXISTING JOINT MATERIAL AND INSTALL FOAM JOINTS.


REMOVE EXISTING JOINT MATERIAL AND INSTALL POURABLE SILICONE JOINTS.

GROOVE PPC BRIDGE DECK.



REMOVE DEBRIS FROM TOP OF EXISTING END BENT AND BENT CAPS AND APPLY EPOXY COATING.

REMOVE UNSOUND CONCRETE AND PROPERLY PREPARE EXISTING END BENT AND BENT AREAS FOR SHOTCRETE AND CONCRETE REPAIR.

SURFACE PREPARATION AND PAINTING OF GIRDER ENDS AND BEARINGS.





**SECTION ALONG C BRIDGE**



**PLAN**

I HEREBY CERTIFY THAT THIS STRUCTURE WAS REHABILITATED ACCORDING TO THESE PLANS OR AS NOTED HEREIN.

RESIDENT ENGINEER \_\_\_\_\_ DATE \_\_\_\_\_



PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330441


STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH  
**GENERAL DRAWING**  
 BRIDGE ON US-158  
 OVER I-40

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S2-01
1			3			TOTAL SHEETS
2			4			6


DRAWN BY : J. A. TILLMAN DATE : 10/2019  
 CHECKED BY : H. A. LOCKLEAR DATE : 4/2020

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED


**NOTE:**  
 SEE TRANSPORTATION MANAGEMENT PLANS FOR LANE WIDTHS, SEQUENCING, AND OTHER TRAFFIC CONTROL MEASURES FOR STAGING OF OVERLAY SURFACE PREPARATION AND POLYESTER POLYMER CONCRETE PLACEMENT.




**TYPICAL SECTION - APPROACH SLAB**  
(EXISTING)




**TYPICAL SECTION**  
(EXISTING)




**TYPICAL SECTION - APPROACH SLAB**  
(PROPOSED)



**TYPICAL SECTION**  
(PROPOSED)




**STAGED PPC OVERLAY JOINT**  
(AS NEEDED)



**DETAIL OF POLYESTER POLYMER CONCRETE OVERLAY**

FINISHED SURFACE ELEVATION SHALL MATCH EXISTING CONCRETE SURFACE ELEVATION. ACTUAL THICKNESS OF PPC OVERLAY MAY VARY.

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330441



STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

**TYPICAL SECTION & PPC OVERLAY DETAILS**

DRAWN BY: J. A. TILLMAN DATE: 2/2020  
 CHECKED BY: H. A. LOCKLEAR DATE: 4/2020

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S2-02
1			3			TOTAL SHEETS
2			4			6

## AS-BUILT REPAIR QUANTITY TABLE

TOP OF DECK REPAIRS	APPROACH SLAB 1		SPAN A		SPAN B		SPAN C		SPAN D		APPROACH SLAB 2	
	ESTIMATE	ACTUAL	ESTIMATE	ACTUAL	ESTIMATE	ACTUAL	ESTIMATE	ACTUAL	ESTIMATE	ACTUAL	ESTIMATE	ACTUAL
SCARIFYING BRIDGE DECK	102.0 SQ. YDS.		366.0 SQ. YDS.		738.0 SQ. YDS.		738.0 SQ. YDS.		379.0 SQ. YDS.		102.0 SQ. YDS.	
SHOTBLASTING BRIDGE DECK	102.0 SQ. YDS.		366.0 SQ. YDS.		738.0 SQ. YDS.		738.0 SQ. YDS.		379.0 SQ. YDS.		102.0 SQ. YDS.	
CLASS II SURFACE PREPARATION	0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.	
CONCRETE DECK REPAIR FOR PPC OVERLAY	0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.	
POLYESTER POLYMER CONCRETE MATERIALS	3.6 CU. YDS.		12.7 CU. YDS.		25.6 CU. YDS.		25.6 CU. YDS.		13.2 CU. YDS.		3.6 CU. YDS.	
PLACING & FINISHING PPC OVERLAY	102.0 SQ. YDS.		366.0 SQ. YDS.		738.0 SQ. YDS.		738.0 SQ. YDS.		379.0 SQ. YDS.		102.0 SQ. YDS.	
GROOVING BRIDGE FLOOR	847.0 SQ. FT.		3098.0 SQ. FT.		6286.0 SQ. FT.		6286.0 SQ. FT.		3208.0 SQ. FT.		848.0 SQ. FT.	
SHORTCRETE REPAIRS	ESTIMATE		ACTUAL		ESTIMATE		ACTUAL		ESTIMATE		ACTUAL	
	AREA SQ. FT.	VOLUME CU. FT.	AREA SQ. FT.	VOLUME CU. FT.	AREA SQ. FT.	VOLUME CU. FT.	AREA SQ. FT.	VOLUME CU. FT.	AREA SQ. FT.	VOLUME CU. FT.	AREA SQ. FT.	VOLUME CU. FT.
SIDEWALK (SPAN B)	0.0	0.0			32.5	10.9			0.0	0.0		

### NOTES:


REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE BASED ON THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER WILL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATIONS AND DESCRIPTION OF THE REPAIRS AND ENTER THE ACTUAL QUANTITIES INTO THE AS-BUILT REPAIR QUANTITY TABLE.

FOR SCARIFYING BRIDGE DECK, SHOTBLASTING BRIDGE DECK AND CLASS II SURFACE PREPARATION, SEE OVERLAY SURFACE PREPARATION FOR POLYESTER POLYMER CONCRETE SPECIAL PROVISION.

FOR CONCRETE DECK REPAIR FOR PPC OVERLAY, PPC MATERIALS, AND PLACING AND FINISHING PPC OVERLAY, SEE POLYESTER POLYMER CONCRETE BRIDGE DECK OVERLAY SPECIAL PROVISION.

FOR SECTION A-A AND SECTION B-B, SEE "JOINT DETAILS" SHEET.


TOP OF DECK REPAIR QUANTITIES REPRESENT ESTIMATED VALUES OF CLASS II SURFACE PREPARATION CONCRETE DECK REPAIR FOR PPC OVERLAY AFTER REMOVAL OF UNSOUND CONCRETE (MIN. 2" CLEAR TO SAWCUT). SEE OVERLAY SURFACE PREPARATION FOR POLYESTER POLYMER CONCRETE SPECIAL PROVISION.



PLAN

- SHOTCRETE REPAIRS FOR SIDEWALKS
- BRIDGE JOINTS

PROJECT NO. I-5795  
 FORSYTH COUNTY  
 STATION: 330441




STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

### PLAN OF SPANS AND APPROACH SLAB


DRAWN BY: J. A. TILLMAN DATE: 2/2020  
 CHECKED BY: H. A. LOCKLEAR DATE: 4/2020

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			S2-03
2			4			TOTAL SHEETS 6


DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED




EXISTING JOINT



MINIMUM EXISTING JOINT DEMOLITION & SCARIFICATION



PROPOSED JOINT PRE-SAWED & PPC OVERLAY



PROPOSED JOINT WITH SAWED DIMENSIONS

▲ SAW CUT SHALL BE 3/4" BELOW THE BOTTOM OF THE JOINT SEAL, SEE MANUFACTURER RECOMMENDATIONS

NOTE

THE CONTRACTOR SHALL FIELD VERIFY THE EXISTING JOINT OPENING PRIOR TO ORDERING JOINT SEAL MATERIAL. IF ACTUAL JOINT OPENING VARIES FROM THE OPENING INDICATED IN DETAIL BY MORE THAN 1/4", NOTIFY ENGINEER. REVISION TO THE JOINT SEAL SIZE MIGHT BE NECESSARY.

FINAL JOINT SEALS SHALL NOT BE INSTALLED UNTIL THE OVERLAY IS COMPLETE.

THE CONTRACTOR SHALL TAKE CARE DURING JOINT REHAB OPERATIONS NOT TO DROP ANY MATERIAL BELOW THE BRIDGE WITHOUT PROTECTIVE DEVICES BELOW TO CATCH THE MATERIAL. ANY MATERIAL THAT FALLS BELOW THE BRIDGE SHALL BE CONTAINED, REMOVED AND DISPOSED OF BY THE CONTRACTOR AT NO COST TO THE DEPARTMENT. IF THE ENGINEER DETERMINES THAT THE PROTECTIVE DEVICES ARE NOT ADEQUATE OR NOT BEING EMPLOYED, THE WORK SHALL BE SUSPENDED UNTIL ADEQUATE PROTECTION IS PROVIDED.

THE CONTRACTOR WILL NOT BE PERMITTED TO FORM THE JOINTS IN LIEU OF SAWING THE JOINT.

DURING THE JOINT INSTALLATION PROCEDURE, THE JOINT AND SURROUNDING AREA SHALL BE KEPT CLEAN AND FREE OF DEBRIS.

FOR POURABLE SILICONE JOINT SEALANT, SEE SPECIAL PROVISIONS.

THE MANUFACTURER IS TO PROVIDE THE NOMIAL UNCOMPRESSED SEAL WIDTH OF THE BACKER ROD FOR THE EXISTING JOINT SIZE AND ACCOMMODATE THE MINIMUM EXPANSION SHOWN ON THE PLANS.


A MANUFACTURER'S CERTIFIED TRAINED REPRESENTATIVE SHALL BE PRESENT DURING THE INSTALLATION OF THE FIRST JOINT OF THE PROJECT, OR UNTIL THE ENGINEER IS SATISFIED WITH THE INSTALLATION PROCESS.

THE INSTALLATION OF THE JOINT SEAL SHALL BE WATERTIGHT.


FINAL SURFACE OF THE JOINT DEMOLITION AREA PRIOR TO PLACEMENT OF CONCRETE REPAIR MATERIAL SHOULD BE REASONABLY FLAT AND LEVEL. ENGINEER SHALL DETERMINE THE ACCEPTABILITY OF THE SURFACE PRIOR TO PLACEMENT OF REPAIR CONCRETE.

JOINT INSTALLATION SEQUENCE AT END BENTS


SECTION A-A




PLAN




PLAN



SECTION C-C



DETAIL A



SECTION B-B


JOINT REPAIR QUANTITY TABLE

	CLASS II SURFACE PREPARATION	CONCRETE DECK REPAIR FOR PPC OVERLAY
END BENT 1	8.9 SY	8.9 SY
END BENT 2	8.9 SY	8.9 SY
TOTAL	17.8 SY	17.8 SY

JOINT REPAIR QUANTITY TABLE

POURABLE SILICONE JOINT SEALANT	ESTIMATE	ACTUAL
END BENT 1	87.4 LF	
END BENT 2	87.4 LF	
TOTAL	174.8 LF	

PROJECT NO. I-5795  
 FORSYTH COUNTY  
 BRIDGE NO. 330441




STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

JOINT REPAIR DETAILS


DRAWN BY: J. A. TILLMAN DATE: 3/2020  
 CHECKED BY: H. A. LOCKLEAR DATE: 4/2020

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED


REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			S2-04
2			4			TOTAL SHEETS 6



MINIMUM EXISTING JOINT DEMOLITION FOR EXPANSION JOINT SEAL



PROPOSED PRE-SAWED JOINT



PROPOSED FOAM JOINT SEAL

JOINT INSTALLATION SEQUENCE AT BENTS

SECTION B-B

▲ SAW CUT SHALL BE 3/4" BELOW THE BOTTOM OF THE JOINT SEAL, SEE MANUFACTURER RECOMMENDATIONS

NOTES

FOAM JOINTS SHALL BE INSTALLED AS PER MANUFACTURER'S RECOMMENDATIONS.

FOR FOAM JOINT SEALS FOR PRESERVATION, SEE SPECIAL PROVISIONS.

THE INSTALLED FOAM JOINTS SHALL BE WATER TIGHT.

THE FOAM JOINTS SHALL MEET THE MANUFACTURER'S RECOMMENDATION FOR THE SIZE OF OPENING ON THE PLANS, AND ACCOMMODATE THE MINIMUM EXPANSION SHOWN ON THE PLANS.

THE CONTRACTOR WILL NOT BE PERMITTED TO FORM THE JOINTS IN LIEU OF SAWING THE JOINT.


THE MANUFACTURER IS TO PROVIDE THE NOMINAL UNCOMPRESSED SEAL WIDTH OF THE FOAM JOINT SEAL BASED ON JOINT OPENINGS AT THE BENTS.

CONTRACTOR SHALL FIELD VERIFY THE EXISTING JOINT OPENING PRIOR TO ORDERING JOINT SEAL MATERIAL. IF ACTUAL JOINT OPENING VARIES FROM OPENING INDICATED IN DETAIL BY MORE THAN 1/4", NOTIFY ENGINEER REVISION TO THE JOINT SEAL SIZE MIGHT BE NECESSARY.

FINAL SURFACE OF THE JOINT DEMOLITION AREA PRIOR TO PLACEMENT OF CONCRETE REPAIR MATERIAL SHOULD BE REASONABLY FLAT AND LEVEL. ENGINEER SHALL DETERMINE THE ACCEPTABILITY OF THE SURFACE PRIOR TO PLACEMENT OF REPAIR CONCRETE.

	CLASS II SURFACE PREPARATION		CONCRETE DECK REPAIR FOR PPC OVERLAY	
	ESTIMATED	ACTUAL	ESTIMATED	ACTUAL
BENT 1	9.5 SY		9.5 SY	
BENT 2	9.5 SY		9.5 SY	
BENT 3	9.5 SY		9.5 SY	
TOTAL	28.5 SY		28.5 SY	


\* BASED ON THE MINIMUM BLOCKOUT SHOWN.




PLAN (@ BENT)

JOINT SEAL DETAILS AT BENTS

(LEFT SIDE)




SECTION C-C



PLAN (@ BENT)

JOINT SEAL DETAILS AT BENTS

(RIGHT SIDE)




SECTION D-D

JOINT REPAIR QUANTITY TABLE		
FOAM JOINT SEALS FOR PRESERVATION	ESTIMATED	ACTUAL
BENT 1	85.5 LF	
BENT 2	85.5 LF	
BENT 3	85.5 LF	
TOTAL	256.5 LF	

\* BASED ON THE MINIMUM BLOCKOUT SHOWN.

PROJECT NO. I-5795  
 FORSYTH COUNTY  
 BRIDGE NO. 330441



STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

JOINT DETAILS  
 BENTS 1, 2 & 3

DRAWN BY : A. SORSENGINH DATE : 5/2020  
 CHECKED BY : H. A. LOCKLEAR DATE : 5/2020

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S2-05
1			3			TOTAL SHEETS
2			4			6

AS-BUILT REPAIR QUANTITY TABLE



BENT 1 SPAN A FACE	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SO. FT.	VOLUME CU. FT.	AREA SO. FT.	VOLUME CU. FT.
CAP	0.0	0.0		
COLUMN	2.6	1.3		
CONCRETE REPAIRS	AREA SO. FT.	VOLUME CU. FT.	AREA SO. FT.	VOLUME CU. FT.
CAP	0.0	0.0		
COLUMN	0.0	0.0		
EPOXY RESIN INJECTION		LIN. FT.	LIN. FT.	
CAP		0.0		
COLUMN		0.0		
EPOXY COATING	AREA SO. FT.		AREA SO. FT.	
TOP OF CAP AT END BENTS 1 & 2 AND BENTS 1 THRU 3	1271.0		0.0	

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MINIMUM OF 1" BEHIND REBAR AND MINIMUM 2" CLEARANCE TO SAWCUT. SEE "TYPICAL CAP AND COLUMN REPAIR DETAILS" SHEET.

NOTES


REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN BASED ON THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ENTER THE ACTUAL QUANTITIES INTO THE AS-BUILT REPAIR QUANTITY TABLE.

FOR "SHOTCRETE REPAIRS", SEE SPECIAL PROVISIONS.



 SHOTCRETE REPAIR AREA

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO.: 330441



STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH  
**SUBSTRUCTURE REPAIR  
 BENT 1  
 SPAN A FACE**

DRAWN BY : J. A. TILLMAN DATE : 2/2020  
 CHECKED BY: H. A. LOCKLEAR DATE : 4/2020

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	SHEET NO.
1			3			S2-06
2			4			TOTAL SHEETS 6

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED


**NOTES**

GENERAL DRAWING INFORMATION IS TAKEN FROM THE ORIGINAL PLANS AND THE ROUTINE INSPECTION REPORT DATED 7/09/2019.


BRIDGE ORIENTATION CONFORMS TO EXISTING BRIDGE PLANS / ROUTINE INSPECTION.

**SCOPE OF WORK**

- PARTIALLY REMOVE TOP OF BRIDGE DECK CONCRETE BY SCARIFICATION AND SHOTBLASTING METHODS.
- OVERLAY PREPARED TOP OF BRIDGE DECK WITH POLYESTER POLYMER CONCRETE (PPC).
- REMOVE EXISTING JOINT MATERIAL AND INSTALL FOAM JOINTS.
- REMOVE EXISTING JOINT MATERIAL AND INSTALL POURABLE SILICONE JOINTS.
- GROOVE PPC BRIDGE DECK.
- CLEAN AND PAINT EXISTING WEATHERING STEEL BEAM ENDS.
- REMOVE DEBRIS FROM TOP OF EXISTING END BENT AND BENT CAPS, AND APPLY EPOXY COATING.
- REMOVE UNSOUND CONCRETE AND PROPERLY PREPARE EXISTING END BENT AND BENT AREAS FOR SHOTCRETE AND CONCRETE REPAIRS.
- PROPERLY PREPARE SPALLED AREAS IN EXISTING END BENT AND BENTS, AND PERFORM SHOTCRETE AND CONCRETE REPAIRS.
- CLEAN AND PAINT EXISTING STEEL BEARINGS.





SECTION ALONG ORIGINAL GRADE LINE



PLAN

I HEREBY CERTIFY THAT THIS STRUCTURE WAS REHABILITATED ACCORDING TO THESE PLANS OR AS NOTED HEREIN.

RESIDENT ENGINEER \_\_\_\_\_ DATE \_\_\_\_\_



PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330451

STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH


GENERAL DRAWING  
 BRIDGE ON I-40 EBL  
 OVER SR 3153  
 (HANES MALL BLVD)

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S3-01
1			3			TOTAL SHEETS
2			4			5


DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

DRAWN BY : H.A. LOCKLEAR DATE : 8-14-19  
 CHECKED BY : K. PUROHIT DATE : 3-2020







TYPICAL SECTION - APPROACH SLAB  
(EXISTING)



TYPICAL SECTION  
(EXISTING)




TYPICAL SECTION - APPROACH SLAB  
(PROPOSED)



TYPICAL SECTION  
(PROPOSED)


NOTES

SEE TRAFFIC MANAGEMENT PLANS FOR LANE WIDTHS, SEQUENCING, AND OTHER TRAFFIC CONTROL MEASURES FOR STAGING OF OVERLAY SURFACE PREPARATION AND DECK SEAL PLACEMENT.




DETAIL FOR POLYESTER POLYMER CONCRETE OVERLAY

FINISHED SURFACE ELEVATION SHALL MATCH EXISTING CONCRETE SURFACE ELEVATION. ACTUAL THICKNESS OF PPC OVERLAY MAY VARY.



STAGED PPC OVERLAY JOINT  
(AS NEEDED)

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330451




STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH  
 SUPERSTRUCTURE  
 TYPICAL SECTION  
 AND  
 OVERLAY DETAILS

DRAWN BY : H.A. LOCKLEAR DATE : 9-2019  
 CHECKED BY : K. PUROHIT DATE : 3-2020

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S3-02
1			3			TOTAL SHEETS
2			4			5

# AS-BUILT REPAIR QUANTITY TABLE

TOP OF DECK REPAIRS		
	ESTIMATE	ACTUAL
<b>SCARIFYING BRIDGE DECK</b>		
APPROACH SLAB 1	75 SQ. YDS.	
SPAN A	278 SQ. YDS.	
SPAN B	640 SQ. YDS.	
SPAN C	224 SQ. YDS.	
APPROACH SLAB 2	75 SQ. YDS.	
<b>CLASS II SURFACE PREPARATION</b>		
APPROACH SLAB 1	0.0 SQ. YDS.	
SPAN A	0.0 SQ. YDS.	
SPAN B	1.8 SQ. YDS.	
SPAN C	0.0 SQ. YDS.	
APPROACH SLAB 2	0.0 SQ. YDS.	
<b>CONCRETE DECK REPAIR FOR PPC OVERLAY</b>		
APPROACH SLAB 1	0.0 SQ. YDS.	
SPAN A	0.0 SQ. YDS.	
SPAN B	1.8 SQ. YDS.	
SPAN C	0.0 SQ. YDS.	
APPROACH SLAB 2	0.0 SQ. YDS.	
<b>SHOTBLASTING BRIDGE DECK</b>		
APPROACH SLAB 1	75 SQ. YDS.	
SPAN A	278 SQ. YDS.	
SPAN B	640 SQ. YDS.	
SPAN C	224 SQ. YDS.	
APPROACH SLAB 2	75 SQ. YDS.	
<b>PPC MATERIALS</b>		
APPROACH SLAB 1	2.6 CU. YDS.	
SPAN A	9.7 CU. YDS.	
SPAN B	22.2 CU. YDS.	
SPAN C	7.8 CU. YDS.	
APPROACH SLAB 2	2.6 CU. YDS.	
<b>PLACING AND FINISHING PPC OVERLAY</b>		
APPROACH SLAB 1	75 SQ. YDS.	
SPAN A	278 SQ. YDS.	
SPAN B	640 SQ. YDS.	
SPAN C	224 SQ. YDS.	
APPROACH SLAB 2	75 SQ. YDS.	
<b>GROOVING BRIDGE FLOORS</b>		
APPROACH SLAB 1	612 SQ. FT.	
SPAN A	2337 SQ. FT.	
SPAN B	5421 SQ. FT.	
SPAN C	1872 SQ. FT.	
APPROACH SLAB 2	612 SQ. FT.	
<b>EPOXY COATING</b>		
TOP OF CAP AT END BENTS 1 & 2 AND BENTS 1 & 2	AREA SQ. FT.	AREA SQ. FT.
	708.0	0.0



PLAN

### NOTES

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE BASED ON THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER WILL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATIONS AND DESCRIPTION OF THE REPAIRS AND ENTER THE ACTUAL QUANTITIES INTO THE AS-BUILT REPAIR QUANTITY TABLE.

FOR SECTION A-A AND SECTION B-B, SEE "JOINT DETAILS" SHEET.

FOR SCARIFYING BRIDGE DECK, SHOTBLASTING BRIDGE DECK AND CLASS II SURFACE PREPARATION, SEE OVERLAY SURFACE PREPARATION FOR POLYESTER POLYMER CONCRETE SPECIAL PROVISION.


FOR CONCRETE DECK REPAIR FOR PPC OVERLAY, PPC MATERIALS, AND PLACING AND FINISHING PPC OVERLAY, SEE POLYESTER POLYMER CONCRETE BRIDGE DECK OVERLAY SPECIAL PROVISION.

TOP OF DECK REPAIR QUANTITIES REPRESENT ESTIMATED VALUES OF CLASS II SURFACE PREPARATION AND CONCRETE DECK REPAIR FOR PPC OVERLAY AFTER REMOVAL OF UNSOUND CONCRETE (MIN. 2" CLEAR TO SAWCUT.) SEE OVERLAY SURFACE PREPARATION FOR POLYESTER POLYMER CONCRETE SPECIAL PROVISION.

CLEAN AND REMOVE DEBRIS FROM THE TOP OF THE CAP AND APPLY EPOXY PROTECTIVE COATING. EPOXY COATING SHALL BE APPLIED TO THE TOP SURFACE OF THE CAP. THE CONTRACTOR SHALL NOT COAT THE AREA OF THE CAP BENEATH THE MASONRY PLATES. FOR EPOXY COATING, SEE SPECIAL PROVISIONS.

APPROX. CLASS II SURFACE PREPARATION

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330451




STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

## PLAN OF SPANS AND APPROACH SLAB


DRAWN BY : H.A. LOCKLEAR DATE : 9-11-2019  
 CHECKED BY : K. PUROHIT DATE : 3-2020

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED


REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			S3-03
2			4			TOTAL SHEETS 5




EXISTING JOINT



MINIMUM EXISTING JOINT REMOVAL & SCARIFICATION



PROPOSED JOINT PRE-SAWED & PPC OVERLAY




PROPOSED JOINT WITH SAWED DIMENSIONS

JOINT INSTALLATION SEQUENCE AT END BENTS

SECTION A-A


▲ SAW CUT SHALL BE 3/4" BELOW THE BOTTOM OF THE JOINT SEAL. SEE MANUFACTURER RECOMMENDATIONS

**NOTES:**  
 THE CONTRACTOR SHALL FIELD VERIFY THE EXISTING JOINT OPENING PRIOR TO ORDERING JOINT SEAL MATERIAL. IF ACTUAL JOINT OPENING VARIES FROM THE OPENING INDICATED IN DETAIL BY MORE THAN 1/4", NOTIFY ENGINEER. REVISION TO THE JOINT SEAL SIZE MIGHT BE NECESSARY.  
 FINAL JOINT SEALS SHALL NOT BE INSTALLED UNTIL THE OVERLAY IS COMPLETE.  
 THE CONTRACTOR SHALL TAKE CARE DURING JOINT REHAB OPERATIONS NOT TO DROP ANY MATERIAL BELOW THE BRIDGE WITHOUT PROTECTIVE DEVICES BELOW TO CATCH THE MATERIAL. ANY MATERIAL THAT FALLS BELOW THE BRIDGE SHALL BE CONTAINED, REMOVED AND DISPOSED OF BY THE CONTRACTOR AT NO EXTRA COST TO THE DEPARTMENT. IF THE ENGINEER DETERMINES THAT THE PROTECTIVE DEVICES ARE NOT ADEQUATE OR NOT BEING EMPLOYED, THE WORK SHALL BE SUSPENDED UNTIL ADEQUATE PROTECTION IS PROVIDED.  
 THE CONTRACTOR WILL NOT BE PERMITTED TO FORM THE JOINTS IN LIEU OF SAWING THE JOINT.  
 DURING THE JOINT INSTALLATION PROCEDURE, THE JOINT AND SURROUNDING AREA SHALL BE KEPT CLEAN AND FREE OF DEBRIS.  
 FOR POURABLE SILICONE JOINT SEALANT, SEE SPECIAL PROVISIONS.  
 THE MANUFACTURER IS TO PROVIDE THE NOMINAL UNCOMPRESSED SEAL WIDTH OF THE BACKER ROD FOR THE EXISTING JOINT SIZE AND ACCOMMODATE THE MINIMUM EXPANSION SHOWN ON THE PLANS.  
 A MANUFACTURER'S CERTIFIED TRAINED REPRESENTATIVE SHALL BE PRESENT DURING THE INSTALLATION OF THE FIRST JOINT OF THE PROJECT, OR UNTIL THE ENGINEER IS SATISFIED WITH THE INSTALLATION PROCESS.  
 THE INSTALLATION OF THE JOINT SEAL SHALL BE WATERTIGHT.  
 FINAL SURFACE OF THE JOINT DEMOLITION AREA PRIOR TO PLACEMENT OF CONCRETE REPAIR MATERIAL SHOULD BE REASONABLY FLAT AND LEVEL. ENGINEER SHALL DETERMINE THE ACCEPTABILITY OF THE SURFACE PRIOR TO PLACEMENT OF REPAIR CONCRETE.




PLAN

\* NON-SAG SILICONE JOINT SEALANT TO BE PLACED AND ALLOWED TO SET, PRIOR TO PLACEMENT OF SELF-LEVELING SILICONE JOINT SEALANT.



SECTION E-E

JOINT DETAIL AT BARRIER RAIL




DETAIL A

JOINT REPAIR QUANTITY TABLE		
	CLASS II SURFACE PREPARATION	CONCRETE DECK REPAIR FOR PPC OVERLAY
END BENT 1	6.8 SY	6.8 SY
END BENT 2	6.8 SY	6.8 SY
TOTAL	13.6 SY	13.6 SY

JOINT REPAIR QUANTITY TABLE		
	ESTIMATE	ACTUAL
POURABLE SILICONE JOINT SEALANT		
END BENT 1	63 LF	
END BENT 2	63 LF	
TOTAL	126 LF	

PROJECT NO. I-5795  
 FORSYTH COUNTY  
 BRIDGE NO. 330451



STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

JOINT REPAIR DETAILS

DRAWN BY : H.A. LOCKLEAR DATE : 9-12-2019  
 CHECKED BY : K. PUROHIT DATE : 3-2020

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			S3-04
2			4			TOTAL SHEETS 5

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

**NOTES**

FOAM JOINTS SHALL BE INSTALLED AS PER MANUFACTURER'S RECOMMENDATIONS.

FOR FOAM JOINT SEALS FOR PRESERVATION, SEE SPECIAL PROVISIONS.

THE INSTALLED FOAM JOINTS SHALL BE WATER TIGHT.


THE FOAM JOINTS SHALL MEET THE MANUFACTURER'S RECOMMENDATION FOR THE SIZE OF OPENING ON THE PLANS, AND ACCOMMODATE THE MINIMUM EXPANSION SHOWN ON THE PLANS.

THE CONTRACTOR WILL NOT BE PERMITTED TO FORM THE JOINTS IN LIEU OF SAWING THE JOINT.


THE MANUFACTURER IS TO PROVIDE THE NOMINAL UNCOMPRESSED SEAL WIDTH OF THE FOAM JOINT SEAL BASED ON JOINT OPENINGS AT THE BENTS.

CONTRACTOR SHALL FIELD VERIFY THE EXISTING JOINT OPENING PRIOR TO ORDERING JOINT SEAL MATERIAL. IF ACTUAL JOINT OPENING VARIES FROM OPENING INDICATED IN DETAIL BY MORE THAN 1/4", NOTIFY ENGINEER REVISION TO THE JOINT SEAL SIZE MIGHT BE NECESSARY.


FINAL SURFACE OF THE JOINT DEMOLITION AREA PRIOR TO PLACEMENT OF CONCRETE REPAIR MATERIAL SHOULD BE REASONABLY FLAT AND LEVEL. ENGINEER SHALL DETERMINE THE ACCEPTABILITY OF THE SURFACE PRIOR TO PLACEMENT OF REPAIR CONCRETE.



**MINIMUM EXISTING JOINT DEMOLITION**




**PROPOSED PRE-SAWED JOINT**




**PROPOSED FOAM JOINT SEAL**

▲ SAW CUT SHALL BE 3/4" BELOW THE BOTTOM OF THE JOINT SEAL, SEE MANUFACTURER RECOMMENDATIONS

**JOINT INSTALLATION SEQUENCE AT BENTS**  
SECTION B-B



**PLAN**  
(@ BENT)



**SECTION C-C**


**JOINT SEAL DETAILS AT BENTS**

	CLASS II SURFACE PREPARATION	CONCRETE DECK REPAIR FOR PPC OVERLAY
BENT 1	9.1 SY	9.1 SY
BENT 2	9.1 SY	9.1 SY
TOTAL	18.2 SY	18.2 SY

\* BASED ON THE MINIMUM BLOCKOUT SHOWN.

FOAM JOINT SEALS FOR PRESERVATION	ESTIMATED	ACTUAL
BENT 1	61.5 LF	
BENT 2	61.5 LF	
TOTAL	123.0 LF	

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330451




STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

**JOINT DETAILS  
 BENTS 1 & 2**

DRAWN BY : A. SORSENGINH DATE : 5/2020  
 CHECKED BY : K. PUROHIT DATE : 5/2020


DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S3-05
1			3			TOTAL SHEETS
2			4			5



**NOTES**  
 GENERAL DRAWING INFORMATION IS TAKEN FROM THE ORIGINAL PLANS AND THE ROUTINE INSPECTION REPORT DATED 7/09/2019.  
 BRIDGE ORIENTATION CONFORMS TO EXISTING BRIDGE PLANS / ROUTINE INSPECTION.



**SCOPE OF WORK**  
 PARTIALLY REMOVE TOP OF BRIDGE DECK CONCRETE BY SCARIFICATION AND SHOTBLASTING METHODS.  
 OVERLAY PREPARED TOP OF BRIDGE DECK WITH POLYESTER POLYMER CONCRETE (PPC).  
 REMOVE EXISTING JOINT MATERIAL AND INSTALL POURABLE SILICONE JOINTS.  
 GROOVE PPC BRIDGE DECK.  
 CLEAN AND PAINT EXISTING WEATHERING STEEL BEAM ENDS.  
 REMOVE DEBRIS FROM TOP OF EXISTING END BENT AND BENT CAPS, AND APPLY EPOXY COATING.  
 REMOVE UNSOUND CONCRETE AND PROPERLY PREPARE EXISTING END BENT AND BENT AREAS FOR SHOTCRETE AND CONCRETE REPAIRS.  
 PROPERLY PREPARE SPALLED AREAS IN EXISTING END BENT AND BENTS, AND PERFORM SHOTCRETE AND CONCRETE REPAIRS.  
 CLEAN AND PAINT EXISTING STEEL BEARINGS.



PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330452

I HEREBY CERTIFY THAT THIS STRUCTURE WAS REHABILITATED ACCORDING TO THESE PLANS OR AS NOTED HEREIN.

RESIDENT ENGINEER \_\_\_\_\_ DATE \_\_\_\_\_







STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

GENERAL DRAWING  
 BRIDGE ON I-40 WBL  
 OVER SR 3153  
 (HANES MALL BLVD)

DRAWN BY : H.A. LOCKLEAR      DATE : 8-14-19  
 CHECKED BY : K. PUROHIT      DATE : 3-2020


REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S4-01
1			3			TOTAL SHEETS
2			4			4

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED




**NOTES**

SEE TRAFFIC MANAGEMENT PLANS FOR LANE WIDTHS, SEQUENCING, AND OTHER TRAFFIC CONTROL MEASURES FOR STAGING OF OVERLAY SURFACE PREPARATION AND DECK SEAL PLACEMENT.




**DETAIL FOR POLYESTER POLYMER CONCRETE OVERLAY**

FINISHED SURFACE ELEVATION SHALL MATCH EXISTING CONCRETE SURFACE ELEVATION. ACTUAL THICKNESS OF PPC OVERLAY MAY VARY.



**STAGED PPC OVERLAY JOINT (AS NEEDED)**

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330452



STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH  
 SUPERSTRUCTURE  
 TYPICAL SECTION  
 AND  
 OVERLAY DETAILS


DRAWN BY : H.A. LOCKLEAR DATE : 9-2019  
 CHECKED BY : K. PUROHIT DATE : 3-2020

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S4-02
1			3			TOTAL SHEETS
2			4			4

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

# AS-BUILT REPAIR QUANTITY TABLE

TOP OF DECK REPAIRS		
	ESTIMATE	ACTUAL
<b>SCARIFYING BRIDGE DECK</b>		
APPROACH SLAB 1	75 SQ. YDS.	
SPAN A	281 SQ. YDS.	
SPAN B	646 SQ. YDS.	
SPAN C	230 SQ. YDS.	
APPROACH SLAB 2	75 SQ. YDS.	
<b>CLASS II SURFACE PREPARATION</b>		
APPROACH SLAB 1	0.0 SQ. YDS.	
SPAN A	0.0 SQ. YDS.	
SPAN B	0.0 SQ. YDS.	
SPAN C	0.0 SQ. YDS.	
APPROACH SLAB 2	0.0 SQ. YDS.	
<b>CONCRETE DECK REPAIR FOR PPC OVERLAY</b>		
APPROACH SLAB 1	0.0 SQ. YDS.	
SPAN A	0.0 SQ. YDS.	
SPAN B	0.0 SQ. YDS.	
SPAN C	0.0 SQ. YDS.	
APPROACH SLAB 2	0.0 SQ. YDS.	
<b>SHOTBLASTING BRIDGE DECK</b>		
APPROACH SLAB 1	75 SQ. YDS.	
SPAN A	281 SQ. YDS.	
SPAN B	646 SQ. YDS.	
SPAN C	230 SQ. YDS.	
APPROACH SLAB 2	75 SQ. YDS.	
<b>PPC MATERIALS</b>		
APPROACH SLAB 1	2.6 CU. YDS.	
SPAN A	9.8 CU. YDS.	
SPAN B	22.4 CU. YDS.	
SPAN C	8.0 CU. YDS.	
APPROACH SLAB 2	2.6 CU. YDS.	
<b>PLACING AND FINISHING PPC OVERLAY</b>		
APPROACH SLAB 1	75 SQ. YDS.	
SPAN A	281 SQ. YDS.	
SPAN B	646 SQ. YDS.	
SPAN C	230 SQ. YDS.	
APPROACH SLAB 2	75 SQ. YDS.	
<b>GROOVING BRIDGE FLOORS</b>		
APPROACH SLAB 1	612 SQ. FT.	
SPAN A	2361 SQ. FT.	
SPAN B	5470 SQ. FT.	
SPAN C	1928 SQ. FT.	
APPROACH SLAB 2	612 SQ. FT.	
<b>EPOXY COATING</b>		
TOP OF CAP AT END BENTS 1 & 2 AND BENTS 1 & 2	708.0	0.0



PLAN

## NOTES

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE BASED ON THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER WILL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATIONS AND DESCRIPTION OF THE REPAIRS AND ENTER THE ACTUAL QUANTITIES INTO THE AS-BUILT REPAIR QUANTITY TABLE.

FOR SECTION A-A AND SECTION B-B, SEE "JOINT DETAILS" SHEET.


FOR SCARIFYING BRIDGE DECK, SHOTBLASTING BRIDGE DECK AND CLASS II SURFACE PREPARATION, SEE OVERLAY SURFACE PREPARATION FOR POLYESTER POLYMER CONCRETE SPECIAL PROVISION.

FOR CONCRETE DECK REPAIR FOR PPC OVERLAY, PPC MATERIALS, AND PLACING AND FINISHING PPC OVERLAY, SEE POLYESTER POLYMER CONCRETE BRIDGE DECK OVERLAY SPECIAL PROVISION.

TOP OF DECK REPAIR QUANTITIES REPRESENT ESTIMATED VALUES OF CLASS II SURFACE PREPARATION AND CONCRETE DECK REPAIR FOR PPC OVERLAY AFTER REMOVAL OF UNSOUND CONCRETE (MIN. 2" CLEAR TO SAWCUT.) SEE OVERLAY SURFACE PREPARATION FOR POLYESTER POLYMER CONCRETE SPECIAL PROVISION.

CLEAN AND REMOVE DEBRIS FROM THE TOP OF THE CAP AND APPLY EPOXY PROTECTIVE COATING. EPOXY COATING SHALL BE APPLIED TO THE TOP SURFACE OF THE CAP. THE CONTRACTOR SHALL NOT COAT THE AREA OF THE CAP BENEATH THE MASONRY PLATES. FOR EPOXY COATING, SEE SPECIAL PROVISIONS.

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330452



STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH


## PLAN OF SPANS AND APPROACH SLAB

DRAWN BY : H.A. LOCKLEAR DATE : 9-11-2019  
 CHECKED BY : K. PUROHIT DATE : 3-2020


04-AUG-2020 16:40  
 N:\Division09\I5795\Structures\Final Plans Combined\404.007.I-5795.SMU.S.03.330452.dgn  
 ksedai

DOCUMENT NOT CONSIDERED  
 FINAL UNLESS ALL  
 SIGNATURES COMPLETED


REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			S4-03
2			4			TOTAL SHEETS 4



EXISTING JOINT




EXISTING JOINT REMOVAL AND MINIMUM SCARIFICATION




PROPOSED JOINT WITH SAWED DIMENSIONS

JOINT INSTALLATION SEQUENCE AT END BENTS


SECTION A-A



EXISTING JOINT



EXISTING JOINT REMOVAL AND MINIMUM SCARIFICATION



PROPOSED JOINT WITH SAWED DIMENSIONS

NOTES:

THE CONTRACTOR SHALL FIELD VERIFY THE EXISTING JOINT OPENING PRIOR TO ORDERING JOINT SEAL MATERIAL. IF ACTUAL JOINT OPENING VARIES FROM THE OPENING INDICATED IN DETAIL BY MORE THAN 1/4", NOTIFY ENGINEER. REVISION TO THE JOINT SEAL SIZE MIGHT BE NECESSARY.

FINAL JOINT SEALS SHALL NOT BE INSTALLED UNTIL THE OVERLAY IS COMPLETE.

THE CONTRACTOR SHALL TAKE CARE DURING JOINT REHAB OPERATIONS NOT TO DROP ANY MATERIAL BELOW THE BRIDGE WITHOUT PROTECTIVE DEVICES BELOW TO CATCH THE MATERIAL. ANY MATERIAL THAT FALLS BELOW THE BRIDGE SHALL BE CONTAINED, REMOVED AND DISPOSED OF BY THE CONTRACTOR AT NO EXTRA COST TO THE DEPARTMENT. IF THE ENGINEER DETERMINES THAT THE PROTECTIVE DEVICES ARE NOT ADEQUATE OR NOT BEING EMPLOYED, THE WORK SHALL BE SUSPENDED UNTIL ADEQUATE PROTECTION IS PROVIDED.

THE CONTRACTOR WILL NOT BE PERMITTED TO FORM THE JOINTS IN LIEU OF SAWING THE JOINT.

DURING THE JOINT INSTALLATION PROCEDURE, THE JOINT AND SURROUNDING AREA SHALL BE KEPT CLEAN AND FREE OF DEBRIS.

FOR POURABLE SILICONE JOINT SEALANT, SEE SPECIAL PROVISIONS.

THE MANUFACTURER IS TO PROVIDE THE NOMINAL UNCOMPRESSED SEAL WIDTH OF THE BACKER ROD FOR THE EXISTING JOINT SIZE AND ACCOMMODATE THE MINIMUM EXPANSION SHOWN ON THE PLANS.

A MANUFACTURER'S CERTIFIED TRAINED REPRESENTATIVE SHALL BE PRESENT DURING THE INSTALLATION OF THE FIRST JOINT OF THE PROJECT, OR UNTIL THE ENGINEER IS SATISFIED WITH THE INSTALLATION PROCESS.

THE INSTALLATION OF THE JOINT SEAL SHALL BE WATERTIGHT.


FINAL SURFACE OF THE JOINT DEMOLITION AREA PRIOR TO PLACEMENT OF CONCRETE REPAIR MATERIAL SHOULD BE REASONABLY FLAT AND LEVEL. ENGINEER SHALL DETERMINE THE ACCEPTABILITY OF THE SURFACE PRIOR TO PLACEMENT OF REPAIR CONCRETE.

CLASS II SURFACE PREPARATION	
END BENT 1	6.8 SQ. YDS.
BENT 1	6.8 SQ. YDS.
BENT 2	6.8 SQ. YDS.
END BENT 2	6.8 SQ. YDS.
TOTAL	27.2 SQ. YDS.


CONCRETE DECK REPAIR FOR PPC OVERLAY	
END BENT 1	6.8 SQ. YDS.
BENT 1	6.8 SQ. YDS.
BENT 2	6.8 SQ. YDS.
END BENT 2	6.8 SQ. YDS.
TOTAL	27.2 SQ. YDS.

JOINT INSTALLATION SEQUENCE AT BENTS

SECTION B-B




JOINT DETAIL AT BARRIER RAIL




SECTION C-C

\*NON-SAG SILICONE JOINT SEALANT TO BE PLACED AND ALLOWED TO SET, PRIOR TO PLACEMENT OF SELF-LEVELING SILICONE JOINT SEALANT.



DETAIL "A"

JOINT REPAIR QUANTITY TABLE		
POURABLE SILICONE JOINT SEALANT	ESTIMATE	ACTUAL
END BENT 1	63 LF	
BENT 1	63 LF	
BENT 2	63 LF	
END BENT 2	63 LF	
TOTAL	252 LF	




PROJECT NO. I-5795  
 FORSYTH COUNTY  
 BRIDGE NO. 330452

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH						SHEET NO. S4-04 TOTAL SHEETS 4
JOINT REPAIR DETAILS						
REVISIONS						
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			
2			4			


DRAWN BY : H.A. LOCKLEAR DATE : 9-12-2019  
 CHECKED BY : K. PUROHIT DATE : 3-2020

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED





SECTION ALONG ORIGINAL GRADE LINE



PLAN

NOTES

GENERAL DRAWING INFORMATION IS TAKEN FROM THE ORIGINAL PLANS AND THE ROUTINE INSPECTION REPORT DATED 9/9/2019.

BRIDGE ORIENTATION CONFORMS TO THE EXISTING BRIDGE PLANS.

SCOPE OF WORK

PARTIALLY REMOVE TOP OF BRIDGE DECK CONCRETE BY SCARIFICATION AND SHOTBLASTING METHODS.

OVERLAY PREPARED TOP OF BRIDGE DECK WITH POLYESTER POLYMER CONCRETE (PPC).

REMOVE EXISTING JOINT MATERIAL AND INSTALL POURABLE SILICONE JOINTS.

GROOVE PPC BRIDGE DECK.

CLEAN AND PAINT EXISTING WEATHERING STEEL BEAM ENDS.

REMOVE DEBRIS FROM TOP OF EXISTING END BENT AND BENT CAPS, AND APPLY EPOXY COATING.

REMOVE UNSOUND CONCRETE AND PROPERLY PREPARE EXISTING END BENTS AND BENT AREAS FOR SHOTCRETE AND CONCRETE REPAIRS.

PROPERLY PREPARE SPALLED AREAS IN EXISTING END BENTS AND BENTS, AND PERFORM SHOTCRETE AND CONCRETE REPAIRS.



CLEAN AND PAINT EXISTING STEEL BEARINGS.

I HEREBY CERTIFY THAT THIS STRUCTURE WAS REHABILITATED ACCORDING TO THESE PLANS OR AS NOTED HEREIN.

RESIDENT ENGINEER

DATE

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330454




STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

GENERAL DRAWING  
 FOR  
 BRIDGE ON NC-150  
 OVER I-40





DRAWN BY : C. RUIZ DATE : 08/2019  
 CHECKED BY : E. BAYISSA DATE : 04/2020

DOCUMENT NOT CONSIDERED  
 FINAL UNLESS ALL  
 SIGNATURES COMPLETED

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S5-01
1			3			TOTAL SHEETS
2			4			4




NOTES:  
 SEE TRANSPORTATION MANAGEMENT PLANS FOR LANE WIDTHS, SEQUENCING AND OTHER TRAFFIC CONTROL MEASURES FOR STAGING OF OVERLAY SURFACE PREPARATION AND POLYESTER POLYMER CONCRETE PLACEMENT.




DETAIL FOR POLYESTER POLYMER CONCRETE OVERLAY

FINISHED SURFACE ELEVATION SHALL MATCH EXISTING CONCRETE SURFACE ELEVATION. ACTUAL THICKNESS OF PPC OVERLAY MAY VARY.



STAGED PPC OVERLAY JOINT




PROJECT NO. I-5795  
 FORSYTH COUNTY  
 BRIDGE NO. 330454

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
TYPICAL SECTION & PPC OVERLAY DETAIL					
SHEET NO. S5-02					
TOTAL SHEETS 4					
REVISIONS					
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		

DRAWN BY : C. RUIZ DATE : 08/2019  
 CHECKED BY : E. BAYISSA DATE : 04/2020

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED



PLAN OF SPANS

**NOTES:**

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE BASED ON THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER WILL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATIONS AND DESCRIPTION OF THE REPAIRS AND ENTER THE ACTUAL QUANTITIES INTO THE AS-BUILT REPAIR QUANTITY TABLE.


FOR SECTION A-A AND SECTION B-B, SEE "JOINT REPAIR DETAILS" SHEET.

FOR SCARIFYING BRIDGE DECK, SHOTBLASTING BRIDGE DECK AND CLASS II SURFACE PREPARATION, SEE OVERLAY SURFACE PREPARATION FOR POLYESTER POLYMER CONCRETE SPECIAL PROVISION.

FOR CONCRETE DECK REPAIR FOR PPC OVERLAY, PPC MATERIALS, AND PLACING AND FINISHING PPC OVERLAY, SEE POLYESTER POLYMER CONCRETE BRIDGE DECK OVERLAY SPECIAL PROVISION.


TOP OF DECK REPAIR QUANTITIES REPRESENT ESTIMATED VALUES OF CLASS II SURFACE PREPARATION AND CONCRETE DECK REPAIR FOR PPC OVERLAY AFTER REMOVAL OF UNSOUND CONCRETE (MIN. 2" CLEAR TO SAWCUT.) SEE OVERLAY SURFACE PREPARATION FOR POLYESTER POLYMER CONCRETE SPECIAL PROVISION.

CLEAN AND REMOVE DEBRIS FROM THE TOP OF THE CAP AND APPLY EPOXY PROTECTIVE COATING. EPOXY COATING SHALL BE APPLIED TO THE TOP SURFACE OF THE CAP. THE CONTRACTOR SHALL NOT COAT THE AREA OF THE CAP BENEATH THE MASONRY PLATES. FOR EPOXY COATING, SEE SPECIAL PROVISIONS.



AS-BUILT REPAIR QUANTITY TABLE										
TOP OF DECK REPAIRS	APPROACH SLAB 1		SPAN A		SPAN B		SPAN C		APPROACH SLAB 2	
	ESTIMATE	ACTUAL	ESTIMATE	ACTUAL	ESTIMATE	ACTUAL	ESTIMATE	ACTUAL	ESTIMATE	ACTUAL
SCARIFYING BRIDGE DECK	167.0 SQ. YDS.		1025.0 SQ. YDS.		1128.0 SQ. YDS.		476.0 SQ. YDS.		160.0 SQ. YDS.	
SHOTBLASTING BRIDGE DECK	167.0 SQ. YDS.		1025.0 SQ. YDS.		1128.0 SQ. YDS.		476.0 SQ. YDS.		160.0 SQ. YDS.	
CLASS II SURFACE PREPARATION	0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.	
CONCRETE DECK REPAIR FOR PPC OVERLAY	0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.	
POLYESTER POLYMER CONCRETE MATERIALS	5.8 CU. YDS.		35.4 CU. YDS.		39.2 CU. YDS.		16.6 CU. YDS.		5.6 CU. YDS.	
PLACING & FINISHING PPC OVERLAY	167.0 SQ. YDS.		1025.0 SQ. YDS.		1128.0 SQ. YDS.		476.0 SQ. YDS.		160.0 SQ. YDS.	
GROOVING BRIDGE FLOORS	1381.0 SQ. FT.		8709.0 SQ. FT.		9584.0 SQ. FT.		4010.0 SQ. FT.		1324.0 SQ. FT.	
EPOXY COATING	AREA SQ. FT.	AREA SQ. FT.								
TOP OF CAP AT END BENTS 1 & 2 AND BENTS 1 & 2	1277.0	0.0								

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330454






STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH  
 DECK SURFACE REPAIR  
 SPANS A THRU C




DRAWN BY : C. RUIZ DATE : 08/2019  
 CHECKED BY : E. BAYISSA DATE : 04/2020

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			S5-03
2			4			TOTAL SHEETS 4



DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED




**JOINT INSTALLATION SEQUENCE AT END BENTS**



**JOINT INSTALLATION SEQUENCE AT BENTS**



\* NON-SAG SILICONE JOINT SEALANT TO BE PLACED AND ALLOWED TO SET, PRIOR TO PLACEMENT OF SELF-LEVELING SILICONE JOINT SEALANT.



**JOINT DETAIL AT BARRIER RAIL**

**NOTES:**

THE CONTRACTOR SHALL FIELD VERIFY THE EXISTING JOINT OPENING PRIOR TO ORDERING JOINT SEAL MATERIAL. IF ACTUAL JOINT OPENING VARIES FROM THE OPENING INDICATED IN DETAIL BY MORE THAN 1/4", NOTIFY ENGINEER. REVISION TO THE JOINT SEAL SIZE MIGHT BE NECESSARY.

FINAL JOINT SEALS SHALL NOT BE INSTALLED UNTIL THE OVERLAY IS COMPLETE.

THE CONTRACTOR SHALL TAKE CARE DURING JOINT REHAB OPERATIONS NOT TO DROP ANY MATERIAL BELOW THE BRIDGE WITHOUT PROTECTIVE DEVICES BELOW TO CATCH THE MATERIAL. ANY MATERIAL THAT FALLS BELOW THE BRIDGE SHALL BE CONTAINED, REMOVED AND DISPOSED OF BY THE CONTRACTOR AT NO EXTRA COST TO THE DEPARTMENT. IF THE ENGINEER DETERMINES THAT THE PROTECTIVE DEVICES ARE NOT ADEQUATE OR NOT BEING EMPLOYED, THE WORK SHALL BE SUSPENDED UNTIL ADEQUATE PROTECTION IS PROVIDED.

THE CONTRACTOR WILL NOT BE PERMITTED TO FORM THE JOINTS IN LIEU OF SAWING THE JOINT.

DURING THE JOINT INSTALLATION PROCEDURE, THE JOINT AND SURROUNDING AREA SHALL BE KEPT CLEAN AND FREE OF DEBRIS.

FOR POURABLE SILICONE JOINT SEALANT, SEE SPECIAL PROVISIONS.

THE MANUFACTURER IS TO PROVIDE THE NOMINAL UNCOMPRESSED SEAL WIDTH OF THE BACKER ROD FOR THE EXISTING JOINT SIZE AND ACCOMMODATE THE MINIMUM EXPANSION SHOWN ON THE PLANS.

A MANUFACTURER'S CERTIFIED TRAINED REPRESENTATIVE SHALL BE PRESENT DURING THE INSTALLATION OF THE FIRST JOINT OF THE PROJECT, OR UNTIL THE ENGINEER IS SATISFIED WITH THE INSTALLATION PROCESS.


THE INSTALLATION OF THE JOINT SEAL SHALL BE WATERTIGHT.

FINAL SURFACE OF THE JOINT DEMOLITION AREA PRIOR TO PLACEMENT OF CONCRETE REPAIR MATERIAL SHOULD BE REASONABLY FLAT AND LEVEL. ENGINEER SHALL DETERMINE THE ACCEPTABILITY OF THE SURFACE PRIOR TO PLACEMENT OF REPAIR CONCRETE.

JOINT REPAIR QUANTITY TABLE		
	ESTIMATE	ACTUAL
POURABLE SILICONE JOINT SEALANT		
END BENT 1	127.5 LF	
BENT 1	127.5 LF	
BENT 2	127.5 LF	
END BENT 2	127.5 LF	
TOTAL	510.0 LF	

JOINT REPAIR QUANTITY TABLE		
	CLASS II SURFACE PREPARATION	CONCRETE DECK REPAIR FOR PPC OVERLAY
END BENT 1	15.1 SY	15.1 SY
BENT 1	15.1 SY	15.1 SY
BENT 2	15.1 SY	15.1 SY
END BENT 2	15.1 SY	15.1 SY
TOTAL	60.4 SY	60.4 SY

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330454




STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

**JOINT REPAIR DETAILS**



DRAWN BY : C. RUIZ DATE : 08/2019  
 CHECKED BY : E. BAYISSA DATE : 04/2020

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S5-04
1			3			TOTAL SHEETS
2			4			4



**NOTES:**  
 GENERAL DRAWING INFORMATION IS TAKEN FROM THE ORIGINAL PLANS AND THE ROUTINE INSPECTION REPORT DATED 07/02/2018.  
 BRIDGE ORIENTATION CONFORMS TO THE EXISTING BRIDGE PLANS / ROUTINE INSPECTION.

SECTION ALONG C BRIDGE



PLAN



PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330458

SCOPE OF WORK

- PARTIALLY REMOVE TOP OF BRIDGE DECK CONCRETE BY SCARIFICATION AND SHOTBLASTING METHODS.
- OVERLAY PREPARED TOP OF BRIDGE DECK WITH POLYESTER POLYMER CONCRETE (PPC).
- REMOVE EXISTING JOINT MATERIAL AND INSTALL POURABLE SILICONE JOINTS.
- REMOVE EXISTING JOINT MATERIAL AND INSTALL FOAM JOINTS..
- GROOVE PPC BRIDGE DECK.
- CLEAN AND EPOXY COAT EXISTING PRESTRESSED CONCRETE GIRDER ENDS.
- REMOVE DEBRIS FROM TOP OF EXISTING END BENT AND BENT CAPS, AND APPLY EPOXY COATING.
- REMOVE UNSOUND CONCRETE AND PROPERLY PERPARE EXISTING END BENT AND BENT AREAS FOR SHOTCRETE AND CONCRETE REPAIRS.

I HEREBY CERTIFY THAT THIS STRUCTURE WAS REHABILITATED ACCORDING TO THESE PLANS OR AS NOTED HEREIN.  
 \_\_\_\_\_  
 RESIDENT ENGINEER DATE


DRAWN BY : C. RUIZ DATE : 08/2019  
 CHECKED BY : E. BAYISSA DATE : 04/2020




STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH  
**GENERAL DRAWINGS**  
 FOR BRIDGE  
 ON UNION CROSS RD.  
 (SR 2643)  
 OVER I-40

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S6-01
1			3			TOTAL SHEETS
2			4			5


DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED




TYPICAL SECTION  
(EXISTING)



TYPICAL SECTION - APPROACH SLAB  
(EXISTING)




TYPICAL SECTION  
(PROPOSED)




TYPICAL SECTION - APPROACH SLAB  
(PROPOSED)

NOTES:

SEE TRANSPORTATION MANAGEMENT PLANS FOR LANE WIDTHS, SEQUENCING AND OTHER TRAFFIC CONTROL MEASURES FOR STAGING OF OVERLAY SURFACE PREPARATION AND POLYESTER POLYMER CONCRETE PLACEMENT.




STAGED PPC OVERLAY JOINT  
(AS NEEDED)



DETAIL FOR PPC OVERLAY

\* FINISHED SURFACE ELEVATION SHALL MATCH EXISTING CONCRETE DECK SURFACE ELEVATION. ACTUAL THICKNESS OF PPC OVERLAY MAY VARY.

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330458




STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH  
 TYPICAL SECTION  
 AND  
 OVERLAY DETAILS

DRAWN BY : C. RUIZ DATE : 07/2019  
 CHECKED BY : E. BAYISSA DATE : 04/2020

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			S6-02
2			4			TOTAL SHEETS 5

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED



PLAN OF SPANS

AS-BUILT REPAIR QUANTITY TABLE

TOP OF DECK REPAIRS	APPROACH SLAB 1		SPAN A		SPAN B		SPAN C		SPAN D		APPROACH SLAB 2	
	ESTIMATE	ACTUAL	ESTIMATE	ACTUAL	ESTIMATE	ACTUAL	ESTIMATE	ACTUAL	ESTIMATE	ACTUAL	ESTIMATE	ACTUAL
SCARIFYING BRIDGE DECK	64 SQ. YDS.		215.0 SQ. YDS.		351.0 SQ. YDS.		351.0 SQ. YDS.		195.0 SQ. YDS.		64 SQ. YDS.	
SHOTBLASTING BRIDGE DECK	64 SQ. YDS.		215.0 SQ. YDS.		351.0 SQ. YDS.		351.0 SQ. YDS.		195.0 SQ. YDS.		64 SQ. YDS.	
CLASS II SURFACE PREPARATION	0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.	
CONCRETE DECK REPAIR FOR PPC OVERLAY	0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.	
POLYESTER POLYMER CONCRETE MATERIALS	2.2 CU. YDS.		7.5 CU. YDS.		12.2 CU. YDS.		12.2 CU. YDS.		6.8 CU. YDS.		2.2 CU. YDS.	
PLACING & FINISHING PPC OVERLAY	64 SQ. YDS.		215.0 SQ. YDS.		351.0 SQ. YDS.		351.0 SQ. YDS.		195.0 SQ. YDS.		64 SQ. YDS.	
GROOVING BRIDGE FLOORS	498.0 SQ. FT.		1791.0 SQ. FT.		2940.0 SQ. FT.		2940.0 SQ. FT.		1924.0 SQ. FT.		498.0 SQ. FT.	
EPOXY COATING CONCRETE GIRDER ENDS			247.3 SQ. FT.		290.5 SQ. FT.		290.5 SQ. FT.		247.3 SQ. FT.			
EPOXY COATING	AREA SQ. FT.	AREA SQ. FT.										
TOP OF CAP AT END BENTS 1 & 2 AND BENTS 1 THRU 3	713.0	0.0										

**NOTES:**

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE BASED ON THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER WILL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATIONS AND DESCRIPTION OF THE REPAIRS AND ENTER THE ACTUAL QUANTITIES INTO THE "AS-BUILT REPAIR QUANTITY TABLE."


FOR SECTION A-A AND SECTION B-B, SEE "JOINT DETAILS" SHEET.

FOR SCARIFYING BRIDGE DECK, SHOTBLASTING BRIDGE DECK AND CLASS II SURFACE PREPARATION, SEE OVERLAY SURFACE PREPARATION FOR POLYESTER POLYMER CONCRETE SPECIAL PROVISION.

FOR CONCRETE DECK REPAIR FOR PPC OVERLAY, PPC MATERIALS, AND PLACING AND FINISHING PPC OVERLAY, SEE POLYESTER POLYMER CONCRETE BRIDGE DECK OVERLAY SPECIAL PROVISION.


TOP OF DECK REPAIR QUANTITIES REPRESENT ESTIMATED VALUES OF CLASS II SURFACE PREPARATION AND CONCRETE DECK REPAIR FOR PPC OVERLAY AFTER REMOVAL OF UNSOUND CONCRETE (MIN. 2" CLEAR TO SAWCUT.) SEE OVERLAY SURFACE PREPARATION FOR POLYESTER POLYMER CONCRETE SPECIAL PROVISION.

CLEAN AND REMOVE DEBRIS FROM THE TOP OF THE CAP AND APPLY EPOXY PROTECTIVE COATING. EPOXY COATING SHALL BE APPLIED TO THE TOP SURFACE OF THE CAP. THE CONTRACTOR SHALL NOT COAT THE AREA OF THE CAP BENEATH THE MASONRY PLATES. FOR EPOXY COATING, SEE SPECIAL PROVISIONS.



BRIDGE JOINT @ BENTS

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330458



STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

DECK SURFACE REPAIR  
 SPANS A THRU D

DRAWN BY : C. RUIZ      DATE : 08/2019  
 CHECKED BY : E. BAYISSA      DATE : 04/2020

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			S6-03
2			4			TOTAL SHEETS 5

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

**NOTE:**

THE CONTRACTOR SHALL FIELD VERIFY THE EXISTING JOINT OPENING PRIOR TO ORDERING JOINT SEAL MATERIAL. IF ACTUAL JOINT OPENING VARIES FROM THE OPENING INDICATED IN DETAIL BY MORE THAN 1/4", NOTIFY ENGINEER. REVISION TO THE JOINT SEAL SIZE MIGHT BE NECESSARY.

FINAL JOINT SEALS SHALL NOT BE INSTALLED UNTIL THE OVERLAY IS COMPLETE.

THE CONTRACTOR SHALL TAKE CARE DURING JOINT REHAB OPERATIONS NOT TO DROP ANY MATERIAL BELOW THE BRIDGE WITHOUT PROTECTIVE DEVICES BELOW TO CATCH THE MATERIAL. ANY MATERIAL THAT FALLS BELOW THE BRIDGE SHALL BE CONTAINED, REMOVED AND DISPOSED OF BY THE CONTRACTOR AT NO EXTRA COST TO THE DEPARTMENT. IF THE ENGINEER DETERMINES THAT THE PROTECTIVE DEVICES ARE NOT ADEQUATE OR NOT BEING EMPLOYED, THE WORK SHALL BE SUSPENDED UNTIL ADEQUATE PROTECTION IS PROVIDED.

THE CONTRACTOR WILL NOT BE PERMITTED TO FORM THE JOINTS IN LIEU OF SAWING THE JOINT.

DURING THE JOINT INSTALLATION PROCEDURE, THE JOINT AND SURROUNDING AREA SHALL BE KEPT CLEAN AND FREE OF DEBRIS.


FOR POURABLE SILICONE JOINT SEALANT, SEE SPECIAL PROVISIONS.

THE MANUFACTURER IS TO PROVIDE THE NOMINAL UNCOMPRESSED SEAL WIDTH OF THE BACKER ROD FOR THE EXISTING JOINT SIZE AND ACCOMMODATE THE MINIMUM EXPANSION SHOWN ON THE PLANS.


A MANUFACTURER'S CERTIFIED TRAINED REPRESENTATIVE SHALL BE PRESENT DURING THE INSTALLATION OF THE FIRST JOINT OF THE PROJECT, OR UNTIL THE ENGINEER IS SATISFIED WITH THE INSTALLATION PROCESS.

THE INSTALLATION OF THE JOINT SEAL SHALL BE WATERTIGHT.


FINAL SURFACE OF THE JOINT DEMOLITION AREA PRIOR TO PLACEMENT OF CONCRETE REPAIR MATERIAL SHOULD BE REASONABLY FLAT AND LEVEL. ENGINEER SHALL DETERMINE THE ACCEPTABILITY OF THE SURFACE PRIOR TO PLACEMENT OF REPAIR CONCRETE.



EXISTING JOINT



EXISTING JOINT REMOVAL AND MINIMUM SCARIFICATIONS




PROPOSED JOINT WITH SAWED DIMENSIONS

Δ SAW CUT SHALL BE 3/4" BELOW THE BOTTOM OF THE JOINT SEAL. SEE MANUFACTURER RECOMMENDATIONS


JOINT INSTALLATION SEQUENCE AT END BENTS  
SECTION A-A

	CLASS II SURFACE PREPARATION	CONCRETE DECK REPAIR FOR PPC OVERLAY
END BENT 1	5.7 SY	5.7 SY
END BENT 2	5.7 SY	5.7 SY
TOTAL	11.4 SY	11.4 SY


	ESTIMATE	ACTUAL
POURABLE SILICONE JOINT SEALANT		
END BENT 1	51.2 LF	
END BENT 2	51.2 LF	
TOTAL	102.4 LF	



PLAN




SECTION C-C



DETAIL "A"

\*NON-SAG SILICONE JOINT SEALANT TO BE PLACED AND ALLOWED TO SET, PRIOR TO PLACEMENT OF SELF-LEVELING SILICONE JOINT SEALANT.

PROJECT NO. I-5795  
FORSYTH  
BRIDGE NO. 330458



STATE OF NORTH CAROLINA  
DEPARTMENT OF TRANSPORTATION  
RALEIGH

JOINT DETAILS

DRAWN BY : C. RUIZ DATE : 08/2019  
CHECKED BY : E. BAYISSA DATE : 04/2020

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S6-04
1			3			TOTAL SHEETS
2			4			5

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED



**NOTES**

FOAM JOINTS SHALL BE INSTALLED AS PER MANUFACTURER'S RECOMMENDATIONS.

FOR FOAM JOINT SEALS FOR PRESERVATION, SEE SPECIAL PROVISIONS.

THE INSTALLED FOAM JOINTS SHALL BE WATER TIGHT.


THE FOAM JOINTS SHALL MEET THE MANUFACTURER'S RECOMMENDATION FOR THE SIZE OF OPENING ON THE PLANS, AND ACCOMMODATE THE MINIMUM EXPANSION SHOWN ON THE PLANS.

THE CONTRACTOR WILL NOT BE PERMITTED TO FORM THE JOINTS IN LIEU OF SAWING THE JOINT.


THE MANUFACTURER IS TO PROVIDE THE NOMINAL UNCOMPRESSED SEAL WIDTH OF THE FOAM JOINT SEAL BASED ON JOINT OPENINGS AT THE BENTS.

CONTRACTOR SHALL FIELD VERIFY THE EXISTING JOINT OPENING PRIOR TO ORDERING JOINT SEAL MATERIAL. IF ACTUAL JOINT OPENING VARIES FROM OPENING INDICATED IN DETAIL BY MORE THAN 1/4", NOTIFY ENGINEER REVISION TO THE JOINT SEAL SIZE MIGHT BE NECESSARY.


FINAL SURFACE OF THE JOINT DEMOLITION AREA PRIOR TO PLACEMENT OF CONCRETE REPAIR MATERIAL SHOULD BE REASONABLY FLAT AND LEVEL. ENGINEER SHALL DETERMINE THE ACCEPTABILITY OF THE SURFACE PRIOR TO PLACEMENT OF REPAIR CONCRETE.



MINIMUM EXISTING JOINT DEMOLITION



PROPOSED PRE-SAWED JOINT




PROPOSED FOAM JOINT SEAL


▲ SAW CUT SHALL BE 3/4" BELOW THE BOTTOM OF THE JOINT SEAL, SEE MANUFACTURER RECOMMENDATIONS

**JOINT INSTALLATION SEQUENCE AT BENTS**

SECTION B-B



PLAN (@ BENT)



SECTION C-C


**JOINT SEAL DETAILS AT BENTS**

	CLASS II SURFACE PREPARATION		CONCRETE DECK REPAIR FOR PPC OVERLAY	
	ESTIMATED	ACTUAL	ESTIMATED	ACTUAL
BENT 1	7.6 SY		7.6 SY	
BENT 2	7.6 SY		7.6 SY	
BENT 3	7.6 SY		7.6 SY	
TOTAL	22.8 SY		22.8 SY	

\* BASED ON THE MINIMUM BLOCKOUT SHOWN.

FOAM JOINT SEALS FOR PRESERVATION	ESTIMATED	ACTUAL
BENT 1	51.2 LF	
BENT 2	51.2 LF	
BENT 3	51.2 LF	
TOTAL	153.6 LF	

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330458




STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

**JOINT DETAILS  
 BENTS 1, 2 & 3**

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S6-05
1			3			TOTAL SHEETS
2			4			5

DRAWN BY : A. SORSENGINH DATE : 5/2020  
 CHECKED BY : E. BAYISSA DATE : 5/2020

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED



NOTES




GENERAL DRAWING INFORMATION IS TAKEN FROM THE ORIGINAL PLANS AND THE ROUTINE INSPECTION REPORT DATED 8/16/2018.  
 BRIDGE ORIENTATION CONFORMS TO THE EXISTING BRIDGE PLANS / ROUTINE INSPECTION.

SCOPE OF WORK

- PARTIALLY REMOVE TOP OF BRIDGE DECK CONCRETE BY SCARIFICATION AND SHOTBLASTING METHODS.
- OVERLAY PREPARED TOP OF BRIDGE DECK WITH POLYESTER POLYMER CONCRETE (PPC).
- REMOVE EXISTING JOINT MATERIAL AND INSTALL POURABLE SILICONE JOINTS.
- GROOVE PPC BRIDGE DECK.
- INJECT CONCRETE CRACKS WITH EPOXY RESIN.
- REMOVE UNSOUND CONCRETE AND PROPERLY PREPARE EXISTING END BENT AND BENT AREAS AND PERFORM SHOTCRETE AND/OR CONCRETE REPAIRS.
- REPAIR EXISTING CRACKED CONCRETE SLOPE PROTECTION WITH CLASS B CONCRETE MATERIAL.
- REMOVE DEBRIS FROM TOP OF EXISTING END BENT AND BENT CAPS AND APPLY EPOXY COATING.
- CLEAN AND EPOXY COAT EXISTING PRESTRESSED CONCRETE GIRDER ENDS.

I HEREBY CERTIFY THAT THIS STRUCTURE WAS REHABILITATED ACCORDING TO THESE PLANS OR AS NOTED HEREIN.

RESIDENT ENGINEER \_\_\_\_\_ DATE \_\_\_\_\_




PROJECT NO. I-5795  
 FORSYTH COUNTY  
 BRIDGE NO. 330479

STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH  
 GENERAL DRAWING  
 FOR  
 BRIDGE ON I-40 WBL OVER  
 BUCHANAN STREET


DRAWN BY : A. SORSENGINH      DATE : 1/2020  
 CHECKED BY : K. PUROHIT      DATE : 4/2020

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	TOTAL SHEETS
1			3			7
2			4			


DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED




**TYPICAL SECTION - APPROACH SLAB**  
(EXISTING)



**TYPICAL SECTION**  
(EXISTING)




**TYPICAL SECTION**  
(PROPOSED)




**TYPICAL SECTION - APPROACH SLAB**  
(PROPOSED)

**NOTE:**

SEE TRANSPORTATION MANAGEMENT PLANS FOR LANE WIDTHS, SEQUENCING AND OTHER TRAFFIC CONTROL MEASURES FOR STAGING OF OVERLAY SURFACE PREPARATION AND POLYESTER POLYMER CONCRETE PLACEMENT.




**DETAIL OF POLYESTER POLYMER CONCRETE OVERLAY**  
FINISHED SURFACE ELEVATION SHALL MATCH EXISTING CONCRETE SURFACE ELEVATION. ACTUAL THICKNESS OF PPC OVERLAY MAY VARY.



**STAGED PPC OVERLAY JOINT**  
(AS NEEDED)

PROJECT NO. I-5795  
FORSYTH COUNTY  
BRIDGE NO. 330479



STATE OF NORTH CAROLINA  
DEPARTMENT OF TRANSPORTATION  
RALEIGH

**TYPICAL SECTION & PPC OVERLAY DETAILS**

DRAWN BY : A. SORSENGINH DATE : 1/2020  
CHECKED BY : K. PUROHIT DATE : 4/2020

DOCUMENT NOT CONSIDERED  
FINAL UNLESS ALL  
SIGNATURES COMPLETED

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S7-02
1			3			TOTAL SHEETS
2			4			7

**NOTES:**

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE BASED ON THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER WILL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATIONS AND DESCRIPTION OF THE REPAIRS AND ENTER THE ACTUAL QUANTITIES INTO THE AS-BUILT REPAIR QUANTITY TABLE.




FOR CONCRETE DECK REPAIR FOR PPC OVERLAY, PPC MATERIALS, AND PLACING AND FINISHING PPC OVERLAY, SEE POLYESTER POLYMER CONCRETE BRIDGE DECK OVERLAY SPECIAL PROVISION.


FOR SECTIONS A-A & B-B, SEE "JOINT DETAILS" SHEET.

TOP OF DECK REPAIR QUANTITIES REPRESENT ESTIMATED VALUES OF CLASS II SURFACE PREPARATION AND CONCRETE DECK REPAIR FOR PPC OVERLAY AFTER REMOVAL OF UNSOUND CONCRETE (MIN. 2" CLEAR TO SAWCUT.) SEE OVERLAY SURFACE PREPARATION FOR POLYESTER POLYMER CONCRETE SPECIAL PROVISION.

FOR SCARIFYING BRIDGE DECK, SHOTBLASTING BRIDGE DECK AND CLASS II SURFACE PREPARATION, SEE OVERLAY SURFACE PREPARATION FOR POLYESTER POLYMER CONCRETE SPECIAL PROVISION.

FOR EPOXY COATING CONCRETE GIRDER ENDS, SEE SPECIAL PROVISIONS.

-  APPROX. CLASS II SURFACE PREPARATION
-  CURB AND BARRIER RAIL
-  EPOXY RESIN INJECTION (ERI)




**PLAN**

**AS-BUILT REPAIR QUANTITY TABLE**

TOP OF DECK REPAIRS	APPROACH SLAB 1		SPAN A		SPAN B		SPAN C		APPROACH SLAB 2	
	ESTIMATE	ACTUAL	ESTIMATE	ACTUAL	ESTIMATE	ACTUAL	ESTIMATE	ACTUAL	ESTIMATE	ACTUAL
SCARIFYING BRIDGE DECK	74.0 SQ. YDS.		252.0 SQ. YDS.		331.0 SQ. YDS.		257.0 SQ. YDS.		74.0 SQ. YDS.	
SHOTBLASTING BRIDGE DECK	74.0 SQ. YDS.		252.0 SQ. YDS.		331.0 SQ. YDS.		257.0 SQ. YDS.		74.0 SQ. YDS.	
CLASS II SURFACE PREPARATION	0.6 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.		1.4 SQ. YDS.	
CONCRETE DECK REPAIR FOR PPC OVERLAY	0.6 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.		1.4 SQ. YDS.	
POLYESTER POLYMER CONCRETE MATERIALS	2.6 CU. YDS.		9.0 CU. YDS.		11.5 CU. YDS.		8.8 CU. YDS.		2.6 CU. YDS.	
PLACING & FINISHING PPC OVERLAY	74.0 SQ. YDS.		252.0 SQ. YDS.		331.0 SQ. YDS.		257.0 SQ. YDS.		74.0 SQ. YDS.	
GROOVING BRIDGE FLOORS	629.0 SQ. FT.		2141.0 SQ. FT.		2848.0 SQ. FT.		2484.0 SQ. FT.		629.0 SQ. FT.	
EPOXY COATING CONCRETE GIRDER ENDS			285.0 SQ. FT.		339.0 SQ. FT.		285.0 SQ. FT.			
EPOXY RESIN INJECTION			0.0 LIN. FT.		0.0 LIN. FT.		0.0 LIN. FT.			

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330479




STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH  
 DECK SURFACE REPAIR  
 SPANS A THRU C


DRAWN BY : A. SORSENGINH DATE : 1/2020  
 CHECKED BY : K. PUROHIT DATE : 4/2020

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S7-03
1			3			TOTAL SHEETS
2			4			7


DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED




EXISTING JOINT



MINIMUM EXISTING JOINT DEMOLITION & SCARIFICATION




PROPOSED JOINT PRE-SAWED & PPC OVERLAY




PROPOSED JOINT WITH SAWED DIMENSIONS

JOINT INSTALLATION SEQUENCE AT END BENTS


SECTION A-A




EXISTING COMPRESSION JOINT SEAL



MINIMUM EXISTING JOINT DEMOLITION AND SCARIFICATION



PROPOSED JOINT PRE-SAWED AND PPC OVERLAY




PROPOSED JOINT WITH SAWED DIMENSIONS


▲ SAW CUT SHALL BE 3/4" BELOW THE BOTTOM OF THE JOINT SEAL. SEE MANUFACTURER RECOMMENDATIONS

JOINT INSTALLATION SEQUENCE AT BENTS

SECTION B-B




PLAN (@ END BENT)




PLAN (@ BENT)

\* NON-SAG SILICONE JOINT SEALANT TO BE PLACED AND ALLOWED TO SET, PRIOR TO PLACEMENT OF SELF-LEVELING SILICONE JOINT SEALANT.




SECTION C-C



DETAIL A

	CLASS II SURFACE PREPARATION	CONCRETE DECK REPAIR FOR PPC OVERLAY
END BENT 1	6.3 SY	6.3 SY
BENT 1	6.3 SY	6.3 SY
BENT 2	6.3 SY	6.3 SY
END BENT 2	6.3 SY	6.3 SY
* TOTAL	25.2 SY	25.2 SY

\* BASED ON THE MINIMUM BLOCKOUT SHOWN.



NOTE

THE CONTRACTOR SHALL FIELD VERIFY THE EXISTING JOINT OPENING PRIOR TO ORDERING JOINT SEAL MATERIAL, IF ACTUAL JOINT OPENING VARIES FROM THE OPENING INDICATED IN DETAIL BY MORE THAN 1/4", NOTIFY ENGINEER, REVISION TO THE JOINT SEAL SIZE MIGHT BE NECESSARY.

FINAL JOINT SEALS SHALL NOT BE INSTALLED UNTIL THE OVERLAY IS COMPLETE.

THE CONTRACTOR SHALL TAKE CARE DURING JOINT REHAB OPERATIONS NOT TO DROP ANY MATERIAL BELOW THE BRIDGE WITHOUT PROTECTIVE DEVICES BELOW TO CATCH THE MATERIAL. ANY MATERIAL THAT FALLS BELOW THE BRIDGE SHALL BE CONTAINED, REMOVED AND DISPOSED OF BY THE CONTRACTOR AT NO EXTRA COST TO THE DEPARTMENT. IF THE ENGINEER DETERMINES THAT THE PROTECTIVE DEVICES ARE NOT ADEQUATE OR NOT BEING EMPLOYED, THE WORK SHALL BE SUSPENDED UNTIL ADEQUATE PROTECTION IS PROVIDED.

THE CONTRACTOR WILL NOT BE PERMITTED TO FORM THE JOINTS IN LIEU OF SAWING THE JOINT.

DURING THE JOINT INSTALLATION PROCEDURE, THE JOINT AND SURROUNDING AREA SHALL BE KEPT CLEAN AND FREE OF DEBRIS.

FOR POURABLE SILICONE JOINT SEALANT, SEE SPECIAL PROVISIONS.

THE MANUFACTURER IS TO PROVIDE THE NOMINAL UNCOMPRESSED SEAL WIDTH OF THE BACKER ROD FOR THE EXISTING JOINT SIZE AND ACCOMMODATE THE MINIMUM EXPANSION SHOWN ON THE PLANS.

A MANUFACTURER'S CERTIFIED TRAINED REPRESENTATIVE SHALL BE PRESENT DURING THE INSTALLATION OF THE FIRST JOINT OF THE PROJECT, OR UNTIL THE ENGINEER IS SATISFIED WITH THE INSTALLATION PROCESS.

THE INSTALLATION OF THE JOINT SEAL SHALL BE WATERTIGHT.

FINAL SURFACE OF THE JOINT DEMOLITION AREA PRIOR TO PLACEMENT OF CONCRETE REPAIR MATERIAL SHOULD BE REASONABLY FLAT AND LEVEL. ENGINEER SHALL DETERMINE THE ACCEPTABILITY OF THE SURFACE PRIOR TO PLACEMENT OF REPAIR CONCRETE.

	ESTIMATE	ACTUAL
POURABLE SILICONE JOINT SEALANT		
END BENT 1	58.2 LF	
BENT 1	58.2 LF	
BENT 2	58.2 LF	
END BENT 2	58.2 LF	
TOTAL	232.8 LF	


PROJECT NO. I-5795  
 FORSYTH COUNTY  
 BRIDGE NO. 330479

STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH


JOINT DETAILS

DRAWN BY: A. SORSENGINH DATE: 1/2020  
 CHECKED BY: K. PUROHIT DATE: 4/2020


REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			S7-04
2			4			TOTAL SHEETS 7



PLAN




ELEVATION




TYPICAL SECTION

END BENT 1



PLAN



ELEVATION

END BENT 2

- CONCRETE REPAIR AREA CLASS A
- CONCRETE REPAIR AREA CLASS B
- SHOTCRETE REPAIR AREA
- EPOXY RESIN INJECTION (ERI)

AS-BUILT REPAIR QUANTITY TABLE

END BENT 1	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SQ. FT.	VOLUME CU. FT.	AREA SQ. FT.	VOLUME CU. FT.
CAP	0.0	0.0		
BACKWALL	0.7	0.4		
CONCRETE REPAIRS	AREA SQ. FT.	VOLUME CU. FT.	AREA SQ. FT.	VOLUME CU. FT.
SLOPE PROTECTION REPAIR (CLASS B CONCRETE)	76.6	25.5		
EPOXY RESIN INJECTION		LIN. FT.		LIN. FT.
BACKWALL		6.0		
CAP		0.0		
EPOXY COATING	AREA SQ. FT.		AREA SQ. FT.	
TOP OF CAP	115.6			

AS-BUILT REPAIR QUANTITY TABLE

END BENT 2	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SQ. FT.	VOLUME CU. FT.	AREA SQ. FT.	VOLUME CU. FT.
CAP	0.0	0.0		
BACKWALL	0.0	0.0		
CONCRETE REPAIRS	AREA SQ. FT.	VOLUME CU. FT.	AREA SQ. FT.	VOLUME CU. FT.
CAP	0.0	0.0		
EPOXY RESIN INJECTION		LIN. FT.		LIN. FT.
BACKWALL		0.0		
CAP		0.0		
EPOXY COATING	AREA SQ. FT.		AREA SQ. FT.	
TOP OF CAP	115.6			

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MINIMUM OF 1" BEHIND REBAR AND MINIMUM OF 2" CLEARANCE TO SAWCUT. FOR REPAIR DETAILS, SEE "TYPICAL CAP AND COLUMN REPAIR DETAILS" SHEET.

NOTES:

SHOTCRETE REPAIRS MAY BE REPLACED WITH CONCRETE REPAIRS WITH THE APPROVAL OF THE ENGINEER.

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE BASED ON THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER WILL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATIONS AND DESCRIPTION OF THE REPAIRS AND ENTER THE ACTUAL QUANTITIES INTO THE AS-BUILT REPAIR QUANTITY TABLE.

FOR CAP REPAIRS, SEE "TYPICAL CAP AND COLUMN REPAIR DETAILS" SHEET.


FOR SHOTCRETE REPAIR, SEE SPECIAL PROVISIONS.

FOR CONCRETE REPAIR, SEE SPECIAL PROVISIONS.

CLEAN AND REMOVE DEBRIS FROM THE TOP OF THE CAP AND APPLY EPOXY PROTECTIVE COATING. EPOXY COATING SHALL BE APPLIED TO THE TOP SURFACE OF THE CAP. THE CONTRACTOR SHALL NOT COAT THE AREA OF THE CAP BENEATH THE MASONRY PLATES. FOR EPOXY COATING, SEE SPECIAL PROVISIONS.

FOR CRACK REPAIR ON SLOPE PROTECTION, SAW CUT 1 FOOT EACH SIDE OF CRACK LINE, REMOVE CONCRETE, PREPARE SOIL SUBGRADE WITH PROPER COMPACTION THEN FILL WITH CLASS B CONCRETE TO COMPLETE THE REPAIR.

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE: 330479




STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

END BENTS 1 & 2



DRAWN BY : A. SORSENGINH DATE : 1/2020  
 CHECKED BY : K. PUROHIT DATE : 4/2020

NO.	REVISIONS			SHEET NO.
	BY:	DATE:	DATE:	
1				S7-05
2				TOTAL SHEETS 7



PLAN - TOP OF CAP

PLAN - BOTTOM OF CAP



SPAN A VIEW - ELEVATION

SPAN B VIEW - ELEVATION

**NOTES:**

SHOTCRETE REPAIRS MAY BE REPLACED WITH CONCRETE REPAIRS WITH THE APPROVAL OF THE ENGINEER.

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE BASED ON THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER WILL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATIONS AND DESCRIPTION OF THE REPAIRS AND ENTER THE ACTUAL QUANTITIES INTO THE AS-BUILT REPAIR QUANTITY TABLE.

FOR CAP REPAIRS, SEE "TYPICAL CAP AND COLUMN REPAIR DETAILS" SHEET.

FOR SHOTCRETE REPAIRS, SEE SPECIAL PROVISIONS.

FOR CONCRETE REPAIRS, SEE SPECIAL PROVISIONS.


CLEAN AND REMOVE DEBRIS FROM THE TOP OF THE CAP AND APPLY EPOXY PROTECTIVE COATING. EPOXY COATING SHALL BE APPLIED TO THE TOP SURFACE OF THE CAP. THE CONTRACTOR SHALL NOT COAT THE AREA OF THE CAP BENEATH THE MASONRY PLATES. FOR EPOXY COATING, SEE SPECIAL PROVISIONS.

- SHOTCRETE AREA
- CONCRETE AREA
- ERI - EPOXY RESIN INJECTION

AS-BUILT REPAIR QUANTITY TABLE				
BENT 1 REPAIRS	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP	0.0	0.0		
COLUMN	0.0	0.0		
CONCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP	0.4	0.2		
EPOXY RESIN INJECTION		LN. FT.		LN. FT.
CAP		0.0		
COLUMN		0.0		
EPOXY COATING	AREA SF		AREA SF	
TOP OF CAP	175.8			

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MINIMUM OF 1" BEHIND REBAR AND MINIMUM OF 2" CLEARANCE TO SAWCUT. FOR REPAIR DETAILS, SEE "TYPICAL CAP AND COLUMN REPAIR DETAILS" SHEET.

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330479



STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

BENT 1

DRAWN BY : A. SORSENGINH DATE : 1/2020  
 CHECKED BY : K. PUROHIT DATE : 4/2020

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			S7-06
2			4			TOTAL SHEETS 7

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

SPAN C  
SPAN B




PLAN - TOP OF CAP


SPAN B  
SPAN C



PLAN - BOTTOM OF CAP



SPAN B VIEW - ELEVATION



SPAN C VIEW - ELEVATION

AS-BUILT REPAIR QUANTITY TABLE				
BENT 2 REPAIRS	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP	0.0	0.0		
COLUMN	5.5	2.8		
CONCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP	0.0	0.0		
EPOXY RESIN INJECTION		LN. FT.		LN. FT.
CAP		0.0		
COLUMN		0.0		
EPOXY COATING	AREA SF		AREA SF	
TOP OF CAP	175.8			

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MINIMUM OF 1" BEHIND REBAR AND MINIMUM OF 2" CLEARANCE TO SAWCUT. FOR REPAIR DETAILS, SEE "TYPICAL CAP AND COLUMN REPAIR DETAILS" SHEET.

NOTES:

SHOTCRETE REPAIRS MAY BE REPLACED WITH CONCRETE REPAIRS WITH THE APPROVAL OF THE ENGINEER.

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE BASED ON THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER WILL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATIONS AND DESCRIPTION OF THE REPAIRS AND ENTER THE ACTUAL QUANTITIES INTO THE AS-BUILT REPAIR QUANTITY TABLE.

FOR CAP REPAIRS, SEE "TYPICAL CAP AND COLUMN REPAIR DETAILS" SHEET.

FOR SHOTCRETE REPAIRS, SEE SPECIAL PROVISIONS.

FOR CONCRETE REPAIRS, SEE SPECIAL PROVISIONS.


CLEAN AND REMOVE DEBRIS FROM THE TOP OF THE CAP AND APPLY EPOXY PROTECTIVE COATING. EPOXY COATING SHALL BE APPLIED TO THE TOP SURFACE OF THE CAP. THE CONTRACTOR SHALL NOT COAT THE AREA OF THE CAP BENEATH THE MASONRY PLATES. FOR EPOXY COATING, SEE SPECIAL PROVISIONS.

SHOTCRETE AREA

CONCRETE AREA

ERI - EPOXY RESIN INJECTION

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330479



STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH


BENT 2

DRAWN BY : A. SORSENGINH DATE : 1/2020  
 CHECKED BY : K. PUROHIT DATE : 4/2020


DOCUMENT NOT CONSIDERED  
 FINAL UNLESS ALL  
 SIGNATURES COMPLETED

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S7-07
1			3			TOTAL SHEETS
2			4			7





SECTION ALONG ORIGINAL GRADE LINE



PLAN

NOTES

GENERAL DRAWING INFORMATION IS TAKEN FROM THE ORIGINAL PLANS AND THE ROUTINE INSPECTION REPORT DATED 8/16/2018. BRIDGE ORIENTATION CONFORMS TO THE EXISTING BRIDGE PLANS / ROUTINE INSPECTION.



SCOPE OF WORK

- PARTIALLY REMOVE TOP OF BRIDGE DECK CONCRETE BY SCARIFICATION AND SHOTBLASTING METHODS.
- OVERLAY PREPARED TOP OF BRIDGE DECK WITH POLYESTER POLYMER CONCRETE (PPC).
- REMOVE EXISTING JOINT MATERIAL AND INSTALL POURABLE SILICONE JOINTS.
- GROOVE PPC BRIDGE DECK.
- INJECT CONCRETE CRACKS WITH EPOXY RESIN.
- REMOVE UNSOUND CONCRETE AND PROPERLY PREPARE EXISTING END BENT AND BENT AREAS AND PERFORM SHOTCRETE AND/OR CONCRETE REPAIRS.
- REMOVE DEBRIS FROM TOP OF EXISTING END BENT AND BENT CAPS AND APPLY EPOXY COATING.
- CLEAN AND EPOXY COAT EXISTING PRESTRESSED CONCRETE GIRDER ENDS.

I HEREBY CERTIFY THAT THIS STRUCTURE WAS REHABILITATED ACCORDING TO THESE PLANS OR AS NOTED HEREIN.

RESIDENT ENGINEER \_\_\_\_\_ DATE \_\_\_\_\_

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330480



STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH  
**GENERAL DRAWING**  
 FOR  
 BRIDGE ON I-40 EBL OVER  
 BUCHANAN STREET


DRAWN BY : A. SORSENGINH DATE : 2/2020  
 CHECKED BY : K. PUROHIT DATE : 4/2020

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S8-01
1			3			TOTAL SHEETS
2			4			7


DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

**NOTE:**


SEE TRANSPORTATION MANAGEMENT PLANS FOR LANE WIDTHS, SEQUENCING AND OTHER TRAFFIC CONTROL MEASURES FOR STAGING OF OVERLAY SURFACE PREPARATION AND POLYESTER POLYMER CONCRETE PLACEMENT.




**TYPICAL SECTION - APPROACH SLAB**  
(EXISTING)




**TYPICAL SECTION**  
(EXISTING)




**TYPICAL SECTION**  
(PROPOSED)



**TYPICAL SECTION - APPROACH SLAB**  
(PROPOSED)




**DETAIL OF POLYESTER POLYMER CONCRETE OVERLAY**  
FINISHED SURFACE ELEVATION SHALL MATCH EXISTING CONCRETE SURFACE ELEVATION. ACTUAL THICKNESS OF PPC OVERLAY MAY VARY.



**STAGED PPC OVERLAY JOINT**  
(AS NEEDED)

PROJECT NO. I-5795  
FORSYTH COUNTY  
BRIDGE NO. 330480



STATE OF NORTH CAROLINA  
DEPARTMENT OF TRANSPORTATION  
RALEIGH  
**TYPICAL SECTION & PPC OVERLAY DETAILS**

DRAWN BY : A. SORSENGINH DATE : 2/2020  
CHECKED BY : K. PUROHIT DATE : 4/2020

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S8-02
1			3			TOTAL SHEETS
2			4			7

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

**NOTES:**

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE BASED ON THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER WILL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATIONS AND DESCRIPTION OF THE REPAIRS AND ENTER THE ACTUAL QUANTITIES INTO THE AS-BUILT REPAIR QUANTITY TABLE.




FOR CONCRETE DECK REPAIR FOR PPC OVERLAY, PPC MATERIALS, AND PLACING AND FINISHING PPC OVERLAY, SEE POLYESTER POLYMER CONCRETE BRIDGE DECK OVERLAY SPECIAL PROVISION.


FOR SECTIONS A-A & B-B, SEE "JOINT DETAILS" SHEET.

TOP OF DECK REPAIR QUANTITIES REPRESENT ESTIMATED VALUES OF CLASS II SURFACE PREPARATION AND CONCRETE DECK REPAIR FOR PPC OVERLAY AFTER REMOVAL OF UNSOUND CONCRETE (MIN. 2" CLEAR TO SAWCUT.) SEE OVERLAY SURFACE PREPARATION FOR POLYESTER POLYMER CONCRETE SPECIAL PROVISION.

FOR SCARIFYING BRIDGE DECK, SHOTBLASTING BRIDGE DECK AND CLASS II SURFACE PREPARATION, SEE OVERLAY SURFACE PREPARATION FOR POLYESTER POLYMER CONCRETE SPECIAL PROVISION.

FOR EPOXY COATING CONCRETE GIRDER ENDS, SEE SPECIAL PROVISIONS.

-  APPROX. CLASS II SURFACE PREPARATION
-  CURB AND BARRIER RAIL
-  EPOXY RESIN INJECTION (ERI)




**PLAN**

**AS-BUILT REPAIR QUANTITY TABLE**

TOP OF DECK REPAIRS	APPROACH SLAB 1		SPAN A		SPAN B		SPAN C		APPROACH SLAB 2	
	ESTIMATE	ACTUAL	ESTIMATE	ACTUAL	ESTIMATE	ACTUAL	ESTIMATE	ACTUAL	ESTIMATE	ACTUAL
SCARIFYING BRIDGE DECK	74.0 SQ. YDS.		193.0 SQ. YDS.		338.0 SQ. YDS.		196.0 SQ. YDS.		74.0 SQ. YDS.	
SHOTBLASTING BRIDGE DECK	74.0 SQ. YDS.		193.0 SQ. YDS.		338.0 SQ. YDS.		196.0 SQ. YDS.		74.0 SQ. YDS.	
CLASS II SURFACE PREPARATION	0.4 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.	
CONCRETE DECK REPAIR FOR PPC OVERLAY	0.4 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.	
POLYESTER POLYMER CONCRETE MATERIALS	2.6 CU. YDS.		6.7 CU. YDS.		11.7 CU. YDS.		6.7 CU. YDS.		2.6 CU. YDS.	
PLACING & FINISHING PPC OVERLAY	74.0 SQ. YDS.		193.0 SQ. YDS.		338.0 SQ. YDS.		196.0 SQ. YDS.		74.0 SQ. YDS.	
GROOVING BRIDGE FLOORS	629.0 SQ. FT.		1558.0 SQ. FT.		2848.0 SQ. FT.		1584.0 SQ. FT.		629.0 SQ. FT.	
EPOXY COATING CONCRETE GIRDER ENDS			285.0 SQ. FT.		339.0 SQ. FT.		285.0 SQ. FT.			
EPOXY RESIN INJECTION			0.0 LIN. FT.		0.0 LIN. FT.		0.0 LIN. FT.			

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330480




STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH  
 DECK SURFACE REPAIR  
 SPANS A THRU C


DRAWN BY : A. SORSENGINH DATE : 2/2020  
 CHECKED BY : K. PUROHIT DATE : 4/2020

DOCUMENT NOT CONSIDERED  
 FINAL UNLESS ALL  
 SIGNATURES COMPLETED


REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			S8-03
2			4			TOTAL SHEETS 7




EXISTING JOINT



MINIMUM EXISTING JOINT DEMOLITION & SCARIFICATION




PROPOSED JOINT PRE-SAWED & PPC OVERLAY




PROPOSED JOINT WITH SAWED DIMENSIONS

JOINT INSTALLATION SEQUENCE AT END BENTS


SECTION A-A




EXISTING COMPRESSION JOINT SEAL



MINIMUM EXISTING JOINT DEMOLITION AND SCARIFICATION



PROPOSED JOINT PRE-SAWED AND PPC OVERLAY




PROPOSED JOINT WITH SAWED DIMENSIONS


▲ SAW CUT SHALL BE 3/4" BELOW THE BOTTOM OF THE JOINT SEAL. SEE MANUFACTURER RECOMMENDATIONS

JOINT INSTALLATION SEQUENCE AT BENTS

SECTION B-B




PLAN (@ END BENT)




PLAN (@ BENT)

\*NON-SAG SILICONE JOINT SEALANT TO BE PLACED AND ALLOWED TO SET, PRIOR TO PLACEMENT OF SELF-LEVELING SILICONE JOINT SEALANT.



SECTION C-C



DETAIL A

	CLASS II SURFACE PREPARATION	CONCRETE DECK REPAIR FOR PPC OVERLAY
END BENT 1	6.3 SY	6.3 SY
BENT 1	6.3 SY	6.3 SY
BENT 2	6.3 SY	6.3 SY
END BENT 2	6.3 SY	6.3 SY
* TOTAL	25.2 SY	25.2 SY

\* BASED ON THE MINIMUM BLOCKOUT SHOWN.

NOTE

THE CONTRACTOR SHALL FIELD VERIFY THE EXISTING JOINT OPENING PRIOR TO ORDERING JOINT SEAL MATERIAL. IF ACTUAL JOINT OPENING VARIES FROM THE OPENING INDICATED IN DETAIL BY MORE THAN 1/4", NOTIFY ENGINEER. REVISION TO THE JOINT SEAL SIZE MIGHT BE NECESSARY.

FINAL JOINT SEALS SHALL NOT BE INSTALLED UNTIL THE OVERLAY IS COMPLETE.

THE CONTRACTOR SHALL TAKE CARE DURING JOINT REHAB OPERATIONS NOT TO DROP ANY MATERIAL BELOW THE BRIDGE WITHOUT PROTECTIVE DEVICES BELOW TO CATCH THE MATERIAL. ANY MATERIAL THAT FALLS BELOW THE BRIDGE SHALL BE CONTAINED, REMOVED AND DISPOSED OF BY THE CONTRACTOR AT NO EXTRA COST TO THE DEPARTMENT. IF THE ENGINEER DETERMINES THAT THE PROTECTIVE DEVICES ARE NOT ADEQUATE OR NOT BEING EMPLOYED, THE WORK SHALL BE SUSPENDED UNTIL ADEQUATE PROTECTION IS PROVIDED.

THE CONTRACTOR WILL NOT BE PERMITTED TO FORM THE JOINTS IN LIEU OF SAWING THE JOINT.

DURING THE JOINT INSTALLATION PROCEDURE, THE JOINT AND SURROUNDING AREA SHALL BE KEPT CLEAN AND FREE OF DEBRIS.

FOR POURABLE SILICONE JOINT SEALANT, SEE SPECIAL PROVISIONS.

THE MANUFACTURER IS TO PROVIDE THE NOMINAL UNCOMPRESSED SEAL WIDTH OF THE BACKER ROD FOR THE EXISTING JOINT SIZE AND ACCOMMODATE THE MINIMUM EXPANSION SHOWN ON THE PLANS.


A MANUFACTURER'S CERTIFIED TRAINED REPRESENTATIVE SHALL BE PRESENT DURING THE INSTALLATION OF THE FIRST JOINT OF THE PROJECT, OR UNTIL THE ENGINEER IS SATISFIED WITH THE INSTALLATION PROCESS.

THE INSTALLATION OF THE JOINT SEAL SHALL BE WATERTIGHT.

FINAL SURFACE OF THE JOINT DEMOLITION AREA PRIOR TO PLACEMENT OF CONCRETE REPAIR MATERIAL SHOULD BE REASONABLY FLAT AND LEVEL. ENGINEER SHALL DETERMINE THE ACCEPTABILITY OF THE SURFACE PRIOR TO PLACEMENT OF REPAIR CONCRETE.

	ESTIMATE	ACTUAL
POURABLE SILICONE JOINT SEALANT		
END BENT 1	58.2 LF	
BENT 1	58.2 LF	
BENT 2	58.2 LF	
END BENT 2	58.2 LF	
TOTAL	232.8 LF	

PROJECT NO. I-5795  
 FORSYTH COUNTY  
 BRIDGE NO. 330480



STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

JOINT DETAILS

DRAWN BY: A. SORSENGINH DATE: 1/2020  
 CHECKED BY: K. PUROHIT DATE: 4/2020

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S8-04
1			3			TOTAL SHEETS
2			4			7

AS-BUILT REPAIR QUANTITY TABLE

END BENT 1	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SQ. FT.	VOLUME CU. FT.	AREA SQ. FT.	VOLUME CU. FT.
CAP	0.0	0.0		
BACKWALL	0.0	0.0		
CONCRETE REPAIRS	AREA SQ. FT.	VOLUME CU. FT.	AREA SQ. FT.	VOLUME CU. FT.
CAP	0.0	0.0		
EPOXY RESIN INJECTION	LIN. FT.		LIN. FT.	
BACKWALL	6.0			
CAP	0.0			
EPOXY COATING	AREA SQ. FT.		AREA SQ. FT.	
TOP OF CAP	115.6			

AS-BUILT REPAIR QUANTITY TABLE

END BENT 2	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SQ. FT.	VOLUME CU. FT.	AREA SQ. FT.	VOLUME CU. FT.
CAP	0.0	0.0		
BACKWALL	0.0	0.0		
CONCRETE REPAIRS	AREA SQ. FT.	VOLUME CU. FT.	AREA SQ. FT.	VOLUME CU. FT.
CAP	0.0	0.0		
EPOXY RESIN INJECTION	LIN. FT.		LIN. FT.	
BACKWALL	0.0			
CAP	0.0			
EPOXY COATING	AREA SQ. FT.		AREA SQ. FT.	
TOP OF CAP	115.6			

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MINIMUM OF 1" BEHIND REBAR AND MINIMUM OF 2" CLEARANCE TO SAWCUT. FOR REPAIR DETAILS, SEE "TYPICAL CAP AND COLUMN REPAIR DETAILS" SHEET.

NOTES:

SHOTCRETE REPAIRS MAY BE REPLACED WITH CONCRETE REPAIRS WITH THE APPROVAL OF THE ENGINEER.

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE BASED ON THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER WILL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATIONS AND DESCRIPTION OF THE REPAIRS AND ENTER THE ACTUAL QUANTITIES INTO THE AS-BUILT REPAIR QUANTITY TABLE.


FOR CAP REPAIRS, SEE "TYPICAL CAP AND COLUMN REPAIR DETAILS" SHEET.

FOR SHOTCRETE REPAIR, SEE SPECIAL PROVISIONS.

FOR CONCRETE REPAIR, SEE SPECIAL PROVISIONS.

CLEAN AND REMOVE DEBRIS FROM THE TOP OF THE CAP AND APPLY EPOXY PROTECTIVE COATING. EPOXY COATING SHALL BE APPLIED TO THE TOP SURFACE OF THE CAP. THE CONTRACTOR SHALL NOT COAT THE AREA OF THE CAP BENEATH THE MASONRY PLATES. FOR EPOXY COATING, SEE SPECIAL PROVISIONS.

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE: 330480




STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH


END BENTS 1 & 2

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S8-05
1			3			TOTAL SHEETS
2			4			7


DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED



PLAN




ELEVATION




TYPICAL SECTION

END BENT 1



PLAN



ELEVATION

END BENT 2


- CONCRETE REPAIR AREA
- SHOTCRETE REPAIR AREA
- EPOXY RESIN INJECTION (ERI)

DRAWN BY : A. SORSENGINH DATE : 1/2020  
 CHECKED BY : K. PUROHIT DATE : 4/2020




PLAN - TOP OF CAP

PLAN - BOTTOM OF CAP



SPAN A VIEW - ELEVATION



SPAN B VIEW - ELEVATION

**NOTES:**

SHOTCRETE REPAIRS MAY BE REPLACED WITH CONCRETE REPAIRS WITH THE APPROVAL OF THE ENGINEER.

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE BASED ON THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER WILL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATIONS AND DESCRIPTION OF THE REPAIRS AND ENTER THE ACTUAL QUANTITIES INTO THE AS-BUILT REPAIR QUANTITY TABLE.

FOR CAP REPAIRS, SEE "TYPICAL CAP AND COLUMN REPAIR DETAILS" SHEET.

FOR SHOTCRETE REPAIRS, SEE SPECIAL PROVISIONS.

FOR CONCRETE REPAIRS, SEE SPECIAL PROVISIONS.

CLEAN AND REMOVE DEBRIS FROM THE TOP OF THE CAP AND APPLY EPOXY PROTECTIVE COATING. EPOXY COATING SHALL BE APPLIED TO THE TOP SURFACE OF THE CAP. THE CONTRACTOR SHALL NOT COAT THE AREA OF THE CAP BENEATH THE MASONRY PLATES. FOR EPOXY COATING, SEE SPECIAL PROVISIONS.

SHOTCRETE AREA


CONCRETE AREA

ERI - EPOXY RESIN INJECTION

AS-BUILT REPAIR QUANTITY TABLE				
BENT 1 REPAIRS	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP	0.0	0.0		
COLUMN	1.6	0.8		
CONCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP	0.0	0.0		
EPOXY RESIN INJECTION		LN. FT.		LN. FT.
CAP		0.0		
COLUMN		0.0		
EPOXY COATING	AREA SF		AREA SF	
TOP OF CAP	175.8			

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MINIMUM OF 1" BEHIND REBAR AND MINIMUM OF 2" CLEARANCE TO SAWCUT. FOR REPAIR DETAILS, SEE "TYPICAL CAP AND COLUMN REPAIR DETAILS" SHEET.

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330480



STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

**BENT 1**

DRAWN BY : A. SORSENGINH DATE : 1/2020  
 CHECKED BY : K. PUROHIT DATE : 4/2020



DOCUMENT NOT CONSIDERED  
 FINAL UNLESS ALL  
 SIGNATURES COMPLETED

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	SHEET NO.
1			3			S8-06
2			4			TOTAL SHEETS 7



PLAN - TOP OF CAP

PLAN - BOTTOM OF CAP



SPAN B VIEW - ELEVATION

SPAN C VIEW - ELEVATION

AS-BUILT REPAIR QUANTITY TABLE				
BENT 2 REPAIRS	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP	4.4	2.2		
COLUMN	0.0	0.0		
CONCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP	0.0	0.0		
EPOXY RESIN INJECTION		LN. FT.		LN. FT.
CAP		0.0		
COLUMN		0.0		
EPOXY COATING	AREA SF		AREA SF	
TOP OF CAP	175.8			

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MINIMUM OF 1" BEHIND REBAR AND MINIMUM OF 2" CLEARANCE TO SAWCUT. FOR REPAIR DETAILS, SEE "TYPICAL CAP AND COLUMN REPAIR DETAILS" SHEET.

NOTES:

SHOTCRETE REPAIRS MAY BE REPLACED WITH CONCRETE REPAIRS WITH THE APPROVAL OF THE ENGINEER.

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE BASED ON THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER WILL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATIONS AND DESCRIPTION OF THE REPAIRS AND ENTER THE ACTUAL QUANTITIES INTO THE AS-BUILT REPAIR QUANTITY TABLE.

FOR CAP REPAIRS, SEE "TYPICAL CAP AND COLUMN REPAIR DETAILS" SHEET.


FOR SHOTCRETE REPAIRS, SEE SPECIAL PROVISIONS.

FOR CONCRETE REPAIRS, SEE SPECIAL PROVISIONS.

CLEAN AND REMOVE DEBRIS FROM THE TOP OF THE CAP AND APPLY EPOXY PROTECTIVE COATING. EPOXY COATING SHALL BE APPLIED TO THE TOP SURFACE OF THE CAP. THE CONTRACTOR SHALL NOT COAT THE AREA OF THE CAP BENEATH THE MASONRY PLATES. FOR EPOXY COATING, SEE SPECIAL PROVISIONS.

- SHOTCRETE AREA
- CONCRETE AREA
- ERI - EPOXY RESIN INJECTION

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330480




STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

BENT 2

DRAWN BY : A. SORSENGINH DATE : 1/2020  
 CHECKED BY : K. PUROHIT DATE : 4/2020

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			S8-07
2			4			TOTAL SHEETS 7

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED



SECTION ALONG ORIGINAL GRADE LINE

NOTES


GENERAL DRAWING INFORMATION IS TAKEN FROM THE ORIGINAL PLANS AND THE ROUTINE INSPECTION REPORT DATED 8/22/2018.  
BRIDGE ORIENTATION CONFORMS TO THE EXISTING BRIDGE PLANS / ROUTINE INSPECTION.

SCOPE OF WORK

- PARTIALLY REMOVE TOP OF BRIDGE DECK CONCRETE BY SCARIFICATION AND SHOTBLASTING METHODS.
- OVERLAY PREPARED TOP OF BRIDGE DECK WITH POLYESTER POLYMER CONCRETE (PPC).
- REMOVE EXISTING JOINT MATERIAL AND INSTALL POURABLE SILICONE JOINTS.
- REMOVE EXISTING JOINT MATERIAL AND INSTALL FOAM JOINTS.
- GROOVE PPC BRIDGE DECK.
- INJECT CONCRETE CRACKS WITH EPOXY RESIN.
- REMOVE DEBRIS FROM TOP OF EXISTING END BENTS AND BENT CAPS, AND APPLY EPOXY COATING.
- REMOVE UNSOUND CONCRETE AND PROPERLY PREPARE EXISTING END BENT AND BENT AREAS FOR SHOTCRETE AND CONCRETE REPAIRS.
- PROPERLY PREPARE SPALLED AREAS IN EXISTING END BENTS AND BENTS, AND PERFORM SHOTCRETE AND CONCRETE REPAIRS.
- CLEAN AND EPOXY COAT EXISTING PRESTRESSED CONCRETE GIRDER ENDS.



I HEREBY CERTIFY THAT THIS STRUCTURE WAS REHABILITATED ACCORDING TO THESE PLANS OR AS NOTED HEREIN.

RESIDENT ENGINEER \_\_\_\_\_ DATE \_\_\_\_\_



PLAN

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330481



STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH  
**GENERAL DRAWING**  
 FOR BRIDGE ON I-40 WBL  
 OVER I-40 RAMP


DRAWN BY : FBAYISSA DATE : 07/2019  
 CHECKED BY : A.SORSENGINH DATE : 01/2020

DOCUMENT NOT CONSIDERED  
 FINAL UNLESS ALL  
 SIGNATURES COMPLETED

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S9-01
1			3			TOTAL SHEETS
2			4			5




**NOTE:**  
SEE TRANSPORTATION MANAGEMENT PLANS FOR LANE WIDTHS, SEQUENCING AND OTHER TRAFFIC CONTROL MEASURES FOR STAGING OF OVERLAY SURFACE PREPARATION AND POLYESTER POLYMER CONCRETE PLACEMENT.




**TYPICAL SECTION - APPROACH SLAB**

(EXISTING)  
\*RADIAL DIMENSION




**TYPICAL SECTION**

(EXISTING)  
\*RADIAL DIMENSION




**DETAIL OF POLYESTER POLYMER CONCRETE OVERLAY**

FINISHED SURFACE ELEVATION SHALL MATCH EXISTING CONCRETE SURFACE ELEVATION. ACTUAL THICKNESS OF PPC OVERLAY MAY VARY.




**STAGED PPC OVERLAY JOINT**



**TYPICAL SECTION - APPROACH SLAB**


(PROPOSED)  
\*RADIAL DIMENSION



**TYPICAL SECTION**

(PROPOSED)  
\*RADIAL DIMENSION

PROJECT NO. I-5795  
FORSYTH COUNTY  
BRIDGE NO. 330481



STATE OF NORTH CAROLINA  
DEPARTMENT OF TRANSPORTATION  
RALEIGH

**TYPICAL SECTION & PPC OVERLAY DETAILS**

DRAWN BY : E. BAYISSA DATE : 07/2019  
CHECKED BY : A. SORSENGIH DATE : 01/2020


DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S9-02
1			3			TOTAL SHEETS
2			4			5


# AS-BUILT REPAIR QUANTITY TABLE

## TOP OF DECK REPAIRS


	ESTIMATE	ACTUAL
<b>SCARIFYING BRIDGE DECK</b>		
APPROACH SLAB 1	69.0 SQ. YDS.	
SPAN A	238.0 SQ. YDS.	
SPAN B	228.0 SQ. YDS.	
SPAN C	229.0 SQ. YDS.	
APPROACH SLAB 2	67.0 SQ. YDS.	
<b>CLASS II SURFACE PREPARATION</b>		
APPROACH SLAB 1	0.0 SQ. YDS.	
SPAN A	0.3 SQ. YDS.	
SPAN B	0.0 SQ. YDS.	
SPAN C	0.4 SQ. YDS.	
APPROACH SLAB 2	0.0 SQ. YDS.	
<b>CONCRETE DECK REPAIR FOR PPC OVERLAY</b>		
APPROACH SLAB 1	0.0 SQ. YDS.	
SPAN A	0.3 SQ. YDS.	
SPAN B	0.0 SQ. YDS.	
SPAN C	0.4 SQ. YDS.	
APPROACH SLAB 2	0.0 SQ. YDS.	
<b>SHOTBLASTING BRIDGE DECK</b>		
APPROACH SLAB 1	69.0 SQ. YDS.	
SPAN A	238.0 SQ. YDS.	
SPAN B	228.0 SQ. YDS.	
SPAN C	229.0 SQ. YDS.	
APPROACH SLAB 2	67.0 SQ. YDS.	
<b>PPC MATERIALS</b>		
APPROACH SLAB 1	2.4 CU. YDS.	
SPAN A	8.3 CU. YDS.	
SPAN B	8.0 CU. YDS.	
SPAN C	8.0 CU. YDS.	
APPROACH SLAB 2	2.3 CU. YDS.	
<b>PLACING AND FINISHING PPC OVERLAY</b>		
APPROACH SLAB 1	69.0 SQ. YDS.	
SPAN A	238.0 SQ. YDS.	
SPAN B	228.0 SQ. YDS.	
SPAN C	229.0 SQ. YDS.	
APPROACH SLAB 2	67.0 SQ. YDS.	
<b>GROOVING BRIDGE FLOORS</b>		
APPROACH SLAB 1	547.0 SQ. FT.	
SPAN A	2007.0 SQ. FT.	
SPAN B	1924.0 SQ. FT.	
SPAN C	1926.0 SQ. FT.	
APPROACH SLAB 2	540.0 SQ. FT.	
<b>EPOXY RESIN INJECTION</b>		
SPAN A	0.0 LIN. FT.	
SPAN B	2.0 LIN. FT.	
SPAN C	2.0 LIN. FT.	
<b>EPOXY COATING CONCRETE GIRDER ENDS</b>		
SPAN A	263.4 SQ. FT.	
SPAN B	263.4 SQ. FT.	
SPAN C	263.4 SQ. FT.	
<b>EPOXY COATING</b>		
	ESTIMATE	ACTUAL
END BENT 1	116.3 SQ. FT.	
BENT 1	177.9 SQ. FT.	
BENT 2	209.0 SQ. FT.	
END BENT 2	123.6 SQ. FT.	




PLAN OF SPANS



DETAIL "A"



DETAIL "B"



DETAIL "C"

- APPROX. CLASS II SURFACE PREPARATION
- EPOXY RESIN INJECTION (ERI)
- BRIDGE JOINT @ BENTS

**NOTES:**

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE BASED ON THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER WILL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATIONS AND DESCRIPTION OF THE REPAIRS AND ENTER THE ACTUAL QUANTITIES INTO THE AS-BUILT REPAIR QUANTITY TABLE.

FOR SECTION A-A AND SECTION B-B, SEE "JOINT DETAILS" SHEET.

FOR SCARIFYING BRIDGE DECK, SHOTBLASTING BRIDGE DECK AND CLASS II SURFACE PREPARATION, SEE OVERLAY SURFACE PREPARATION FOR POLYESTER POLYMER CONCRETE SPECIAL PROVISION.

FOR CONCRETE DECK REPAIR FOR PPC OVERLAY, PPC MATERIALS, AND PLACING AND FINISHING PPC OVERLAY, SEE POLYESTER POLYMER CONCRETE BRIDGE DECK OVERLAY SPECIAL PROVISION.


TOP OF DECK REPAIR QUANTITIES REPRESENT ESTIMATED VALUES OF CLASS II SURFACE PREPARATION AND CONCRETE DECK REPAIR FOR PPC OVERLAY AFTER REMOVAL OF UNSOUND CONCRETE (MIN. 2" CLEAR TO SAWCUT.) SEE OVERLAY SURFACE PREPARATION FOR POLYESTER POLYMER CONCRETE SPECIAL PROVISION.

FOR EPOXY COATING CONCRETE GIRDER ENDS, SEE SPECIAL PROVISIONS.

CLEAN AND REMOVE DEBRIS FROM THE TOP OF THE CAP AND APPLY EPOXY PROTECTIVE COATING. EPOXY COATING SHALL BE APPLIED TO THE TOP SURFACE OF THE CAP. THE CONTRACTOR SHALL NOT COAT THE AREA OF THE CAP BENEATH THE MASONRY PLATES.

FOR EPOXY COATING, SEE SPECIAL PROVISIONS.

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330481




STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

**DECK SURFACE REPAIR AND APPROACH SLAB**


DRAWN BY : E. BAYISSA DATE : 07/2019  
 CHECKED BY : A. SORSENGIHN DATE : 01/2020

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S9-03
1			3			TOTAL SHEETS
2			4			5


DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED




EXISTING JOINT



MINIMUM EXISTING JOINT DEMOLITION & SCARIFICATION



PROPOSED JOINT PRE-SAWED & PPC OVERLAY



PROPOSED JOINT WITH SAWED DIMENSIONS

▲ SAW CUT SHALL BE 3/4" BELOW THE BOTTOM OF THE JOINT SEAL. SEE MANUFACTURER RECOMMENDATIONS

NOTE

THE CONTRACTOR SHALL FIELD VERIFY THE EXISTING JOINT OPENING PRIOR TO ORDERING JOINT SEAL MATERIAL. IF ACTUAL JOINT OPENING VARIES FROM THE OPENING INDICATED IN DETAIL BY MORE THAN 1/4", NOTIFY ENGINEER. REVISION TO THE JOINT SEAL SIZE MIGHT BE NECESSARY.

FINAL JOINT SEALS SHALL NOT BE INSTALLED UNTIL THE OVERLAY IS COMPLETE.

THE CONTRACTOR SHALL TAKE CARE DURING JOINT REHAB OPERATIONS NOT TO DROP ANY MATERIAL BELOW THE BRIDGE WITHOUT PROTECTIVE DEVICES BELOW TO CATCH THE MATERIAL. ANY MATERIAL THAT FALLS BELOW THE BRIDGE SHALL BE CONTAINED, REMOVED AND DISPOSED OF BY THE CONTRACTOR AT NO EXTRA COST TO THE DEPARTMENT. IF THE ENGINEER DETERMINES THAT THE PROTECTIVE DEVICES ARE NOT ADEQUATE OR NOT BEING EMPLOYED, THE WORK SHALL BE SUSPENDED UNTIL ADEQUATE PROTECTION IS PROVIDED.

THE CONTRACTOR WILL NOT BE PERMITTED TO FORM THE JOINTS IN LIEU OF SAWING THE JOINT.

DURING THE JOINT INSTALLATION PROCEDURE, THE JOINT AND SURROUNDING AREA SHALL BE KEPT CLEAN AND FREE OF DEBRIS.

FOR POURABLE SILICONE JOINT SEALANT, SEE SPECIAL PROVISIONS.

THE MANUFACTURER IS TO PROVIDE THE NOMINAL UNCOMPRESSED SEAL WIDTH OF THE BACKER ROD FOR THE EXISTING JOINT SIZE AND ACCOMMODATE THE MINIMUM EXPANSION SHOWN ON THE PLANS.


A MANUFACTURER'S CERTIFIED TRAINED REPRESENTATIVE SHALL BE PRESENT DURING THE INSTALLATION OF THE FIRST JOINT OF THE PROJECT, OR UNTIL THE ENGINEER IS SATISFIED WITH THE INSTALLATION PROCESS.

THE INSTALLATION OF THE JOINT SEAL SHALL BE WATERTIGHT.


FINAL SURFACE OF THE JOINT DEMOLITION AREA PRIOR TO PLACEMENT OF CONCRETE REPAIR MATERIAL SHOULD BE REASONABLY FLAT AND LEVEL. ENGINEER SHALL DETERMINE THE ACCEPTABILITY OF THE SURFACE PRIOR TO PLACEMENT OF REPAIR CONCRETE.

JOINT INSTALLATION SEQUENCE AT END BENTS


SECTION A-A



PLAN



SECTION C-C




DETAIL A

JOINT REPAIR QUANTITY TABLE		
	ESTIMATE	ACTUAL
POURABLE SILICONE JOINT SEALANT		
END BENT 1	58.5 LF	
END BENT 1	61.5 LF	
TOTAL	120.0 LF	

JOINT REPAIR QUANTITY TABLE		
	CLASS II SURFACE PREPARATION	CONCRETE DECK REPAIR FOR PPC OVERLAY
END BENT 1	6.4 SY	6.4 SY
END BENT 2	6.7 SY	6.7 SY
* TOTAL	13.1 SY	13.1 SY

\* BASED ON THE MINIMUM BLOCKOUT SHOWN.

PROJECT NO. I-5795  
 FORSYTH COUNTY  
 BRIDGE NO. 330481



STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

JOINT DETAILS

DRAWN BY : E. BAYISSA DATE : .09/2019  
 CHECKED BY : A. SORSENGINH DATE : .01/2020

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			S9-04
2			4			TOTAL SHEETS 5

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

**NOTES**

FOR FOAM JOINT SEALS FOR PRESERVATION, SEE SPECIAL PROVISIONS.

THE INSTALLED FOAM JOINTS SHALL BE WATER TIGHT.

THE FOAM JOINTS SHALL MEET THE MANUFACTURER'S RECOMMENDATION FOR THE SIZE OF OPENING ON THE PLANS, AND ACCOMMODATE THE MINIMUM EXPANSION SHOWN ON THE PLANS.

THE CONTRACTOR WILL NOT BE PERMITTED TO FORM THE JOINTS IN LIEU OF SAWING THE JOINT.

DURING THE JOINT INSTALLATION PROCEDURE, THE JOINT AND SURROUNDING AREA SHALL BE KEPT CLEAN AND FREE OF DEBRIS.

THE MANUFACTURER IS TO PROVIDE THE NOMINAL UNCOMPRESSED SEAL WIDTH OF THE FOAM JOINT SEAL BASED ON JOINT OPENINGS AT THE BENTS.

A MANUFACTURER'S CERTIFIED TRAINED REPRESENTATIVE SHALL BE PRESENT DURING THE INSTALLATION OF THE FIRST JOINT OF THE PROJECT, OR UNTIL THE ENGINEER IS SATISFIED WITH THE INSTALLATION PROCESS.


FINAL JOINT SEALS SHALL NOT BE INSTALLED UNTIL THE OVERLAY IS COMPLETE.

THE CONTRACTOR SHALL TAKE CARE DURING JOINT REHAB OPERATIONS NOT TO DROP ANY MATERIAL BELOW THE BRIDGE WITHOUT PROTECTIVE DEVICES BELOW TO CATCH THE MATERIAL. ANY MATERIAL THAT FALLS BELOW THE BRIDGE SHALL BE CONTAINED, REMOVED AND DISPOSED OF BY THE CONTRACTOR AT NO EXTRA COST TO THE DEPARTMENT. IF THE ENGINEER DETERMINES THAT THE PROTECTIVE DEVICES ARE NOT ADEQUATE OR NOT BEING EMPLOYED, THE WORK SHALL BE SUSPENDED UNTIL ADEQUATE PROTECTION IS PROVIDED.


THE MANUFACTURER IS TO PROVIDE THE NOMINAL UNCOMPRESSED SEAL WIDTH OF THE BACKER ROD FOR THE EXISTING JOINT SIZE AND ACCOMMODATE THE MINIMUM EXPANSION SHOWN ON THE PLANS.

CONTRACTOR SHALL FIELD VERIFY THE EXISTING JOINT OPENING PRIOR TO ORDERING JOINT SEAL MATERIAL. IF ACTUAL JOINT OPENING VARIES FROM OPENING INDICATED IN DETAIL BY MORE THAN 1/4", NOTIFY ENGINEER REVISION TO THE JOINT SEAL SIZE MIGHT BE NECESSARY.


FINAL SURFACE OF THE JOINT DEMOLITION AREA PRIOR TO PLACEMENT OF CONCRETE REPAIR MATERIAL SHOULD BE REASONABLY FLAT AND LEVEL. ENGINEER SHALL DETERMINE THE ACCEPTABILITY OF THE SURFACE PRIOR TO PLACEMENT OF REPAIR CONCRETE.



MINIMUM EXISTING JOINT DEMOLITION



PROPOSED PRE-SAWED JOINT




PROPOSED FOAM JOINT SEAL


**JOINT INSTALLATION SEQUENCE AT BENTS**

SECTION B-B

▲ SAW CUT SHALL BE 3/4" BELOW THE BOTTOM OF THE JOINT SEAL, SEE MANUFACTURER RECOMMENDATIONS



PLAN @ BENT



SECTION C-C


**JOINT SEAL DETAILS AT BENTS**

	CLASS II SURFACE PREPARATION	CONCRETE DECK REPAIR FOR PPC OVERLAY
BENT 1	8.6 SY	8.6 SY
BENT 2	8.7 SY	8.7 SY
* TOTAL	17.3 SY	17.3 SY

\* BASED ON THE MINIMUM BLOCKOUT SHOWN.

FOAM JOINT SEALS FOR PRESERVATION	ESTIMATED	ACTUAL
BENT 1	57.9 LF	
BENT 2	58.7 LF	
TOTAL	116.6 LF	

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330481




STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

**JOINT DETAILS  
 BENTS 1 & 2**

DRAWN BY : A. SORSENGINH DATE : 5/2020  
 CHECKED BY : E. BAYISSA DATE : 5/2020

NO.	REVISIONS			SHEET NO.
	BY:	DATE:	NO.	
1			3	S9-05 TOTAL SHEETS 5
2			4	

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED



**NOTES**

GENERAL DRAWING INFORMATION IS TAKEN FROM THE ORIGINAL PLANS AND THE ROUTINE INSPECTION REPORT DATED 8/22/2018.  
 BRIDGE ORIENTATION CONFORMS TO THE EXISTING BRIDGE PLANS / ROUTINE INSPECTION.


**SCOPE OF WORK**

- PARTIALLY REMOVE TOP OF BRIDGE DECK CONCRETE BY SCARIFICATION AND SHOTBLASTING METHODS.
- OVERLAY PREPARED TOP OF BRIDGE DECK WITH POLYESTER POLYMER CONCRETE (PPC).
- REMOVE EXISTING JOINT MATERIAL AND INSTALL POURABLE SILICONE JOINTS.
- REMOVE EXISTING JOINT MATERIAL AND INSTALL FOAM JOINTS.
- GROOVE PPC BRIDGE DECK.
- INJECT CONCRETE CRACKS WITH EPOXY RESIN.
- REMOVE DEBRIS FROM TOP OF EXISTING END BENTS AND BENT CAPS, AND APPLY EPOXY COATING.
- REMOVE UNSOUND CONCRETE AND PROPERLY PREPARE EXISTING END BENT AND BENT AREAS FOR SHOTCRETE AND CONCRETE REPAIRS.
- PROPERLY PREPARE SPALLED AREAS IN EXISTING END BENTS AND BENTS, AND PERFORM SHOTCRETE AND CONCRETE REPAIRS.
- CLEAN AND EPOXY COAT EXISTING PRESTRESSED CONCRETE GIRDER ENDS.

I HEREBY CERTIFY THAT THIS STRUCTURE WAS REHABILITATED ACCORDING TO THESE PLANS OR AS NOTED HEREIN.



RESIDENT ENGINEER \_\_\_\_\_

DATE \_\_\_\_\_



TO SOUTH MAIN ST. →

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330482



STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH


GENERAL DRAWING  
 FOR BRIDGE ON I-40 EBL  
 OVER I-40 RAMP

DRAWN BY : E.BAYISSA DATE : 07/2019  
 CHECKED BY : A.SORSENGINH DATE : 01/2020

DOCUMENT NOT CONSIDERED  
 FINAL UNLESS ALL  
 SIGNATURES COMPLETED


REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S10-01
1			3			TOTAL SHEETS
2			4			5

**NOTE:**  
 SEE TRANSPORTATION MANAGEMENT PLANS FOR LANE WIDTHS, SEQUENCING, AND OTHER TRAFFIC CONTROL MEASURES FOR STAGING OF OVERLAY SURFACE PREPARATION AND POLYESTER POLYMER CONCRETE PLACEMENT.




**TYPICAL SECTION - APPROACH SLAB**

(EXISTING)  
 RADIAL DIMENSION \*




**TYPICAL SECTION**

(EXISTING)  
 RADIAL DIMENSION \*




**TYPICAL SECTION - APPROACH SLAB**

(PROPOSED)  
 RADIAL DIMENSION \*




**TYPICAL SECTION**

(PROPOSED)  
 RADIAL DIMENSION \*




**DETAIL OF POLYESTER POLYMER CONCRETE OVERLAY**

FINISHED SURFACE ELEVATION SHALL MATCH EXISTING CONCRETE SURFACE ELEVATION. ACTUAL THICKNESS OF PPC OVERLAY MAY VARY.



**STAGED PPC OVERLAY JOINT**

PROJECT NO. I-5795  
 FORSYTH COUNTY  
 BRIDGE NO. 330482



STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH  
**TYPICAL SECTION & PPC OVERLAY DETAILS**


DRAWN BY : E. BAYISSA DATE : 07/2019  
 CHECKED BY : A. SORSENGINH DATE : 01/2020

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	TOTAL SHEETS
1			3			5
2			4			

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

# AS-BUILT REPAIR QUANTITY TABLE

TOP OF DECK REPAIRS		
	ESTIMATE	ACTUAL
<b>SCARIFYING BRIDGE DECK</b>		
APPROACH SLAB 1	67.0 SQ. YDS.	
SPAN A	251.0 SQ. YDS.	
SPAN B	260.0 SQ. YDS.	
SPAN C	233.0 SQ. YDS.	
APPROACH SLAB 2	101.0 SQ. YDS.	
<b>CLASS II SURFACE PREPARATION</b>		
APPROACH SLAB 1	0.0 SQ. YDS.	
SPAN A	0.0 SQ. YDS.	
SPAN B	0.0 SQ. YDS.	
SPAN C	0.0 SQ. YDS.	
APPROACH SLAB 2	0.3 SQ. YDS.	
<b>CONCRETE DECK REPAIR FOR PPC OVERLAY</b>		
APPROACH SLAB 1	0.0 SQ. YDS.	
SPAN A	0.0 SQ. YDS.	
SPAN B	0.0 SQ. YDS.	
SPAN C	0.0 SQ. YDS.	
APPROACH SLAB 2	0.3 SQ. YDS.	
<b>SHOTBLASTING BRIDGE DECK</b>		
APPROACH SLAB 1	67.0 SQ. YDS.	
SPAN A	251.0 SQ. YDS.	
SPAN B	260.0 SQ. YDS.	
SPAN C	233.0 SQ. YDS.	
APPROACH SLAB 2	101.0 SQ. YDS.	
<b>PPC MATERIALS</b>		
APPROACH SLAB 1	2.3 CU. YDS.	
SPAN A	8.7 CU. YDS.	
SPAN B	9.0 CU. YDS.	
SPAN C	8.1 CU. YDS.	
APPROACH SLAB 2	3.5 CU. YDS.	
<b>PLACING AND FINISHING PPC OVERLAY</b>		
APPROACH SLAB 1	67.0 SQ. YDS.	
SPAN A	251.0 SQ. YDS.	
SPAN B	260.0 SQ. YDS.	
SPAN C	233.0 SQ. YDS.	
APPROACH SLAB 2	101.0 SQ. YDS.	
<b>GROOVING BRIDGE FLOORS</b>		
APPROACH SLAB 1	535.0 SQ. FT.	
SPAN A	2117.0 SQ. FT.	
SPAN B	2191.0 SQ. FT.	
SPAN C	1967.0 SQ. FT.	
APPROACH SLAB 2	819.0 SQ. FT.	
<b>EPOXY COATING CONCRETE GIRDER ENDS</b>		
SPAN A	263.4 SQ. FT.	
SPAN B	263.4 SQ. FT.	
SPAN C	263.4 SQ. FT.	
<b>EPOXY COATING</b>		
	ESTIMATE	ACTUAL
END BENT 1	137.0 SQ. FT.	
BENT 1	197.1 SQ. FT.	
BENT 2	199.5 SQ. FT.	
END BENT 2	161.2 SQ. FT.	



PLAN OF SPANS

- APPROX. CLASS II SURFACE PREPARATION
- BRIDGE JOINT @ BENTS

## NOTES:

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE BASED ON THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER WILL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATIONS AND DESCRIPTION OF THE REPAIRS AND ENTER THE ACTUAL QUANTITIES INTO THE AS-BUILT REPAIR QUANTITY TABLE.

FOR SECTION A-A AND SECTION B-B, SEE "JOINT DETAILS" SHEET.

FOR SCARIFYING BRIDGE DECK, SHOTBLASTING BRIDGE DECK AND CLASS II SURFACE PREPARATION, SEE OVERLAY SURFACE PREPARATION FOR POLYESTER POLYMER CONCRETE SPECIAL PROVISION.


FOR CONCRETE DECK REPAIR FOR PPC OVERLAY, PPC MATERIALS, AND PLACING AND FINISHING PPC OVERLAY, SEE POLYESTER POLYMER CONCRETE BRIDGE DECK OVERLAY SPECIAL PROVISION.

TOP OF DECK REPAIR QUANTITIES REPRESENT ESTIMATED VALUES OF CLASS II SURFACE PREPARATION AND CONCRETE DECK REPAIR FOR PPC OVERLAY AFTER REMOVAL OF UNSOUND CONCRETE (MIN. 2" CLEAR TO SAWCUT). SEE OVERLAY SURFACE PREPARATION FOR POLYESTER POLYMER CONCRETE SPECIAL PROVISION.

FOR EPOXY COATING CONCRETE GIRDER ENDS, SEE SPECIAL PROVISIONS.

CLEAN AND REMOVE DEBRIS FROM THE TOP OF THE CAP AND APPLY EPOXY PROTECTIVE COATING. EPOXY COATING SHALL BE APPLIED TO THE TOP SURFACE OF THE CAP. THE CONTRACTOR SHALL NOT COAT THE AREA OF THE CAP BENEATH THE MASONRY PLATES. FOR EPOXY COATING, SEE SPECIAL PROVISIONS.

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330482




STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

**DECK SURFACE REPAIR AND APPROACH SLAB**


DRAWN BY : E. BAYISSA DATE : 07/2019  
 CHECKED BY : A. SORSENGIHN DATE : 01/2020

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			SHEET NO. I-5795
2			4			TOTAL SHEETS 5


DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED




EXISTING JOINT



MINIMUM EXISTING JOINT DEMOLITION & SCARIFICATION



PROPOSED JOINT PRE-SAWED & PPC OVERLAY



PROPOSED JOINT WITH SAWED DIMENSIONS

**NOTE**

THE CONTRACTOR SHALL FIELD VERIFY THE EXISTING JOINT OPENING PRIOR TO ORDERING JOINT SEAL MATERIAL. IF ACTUAL JOINT OPENING VARIES FROM THE OPENING INDICATED IN DETAIL BY MORE THAN 1/4", NOTIFY ENGINEER. REVISION TO THE JOINT SEAL SIZE MIGHT BE NECESSARY.

FINAL JOINT SEALS SHALL NOT BE INSTALLED UNTIL THE OVERLAY IS COMPLETE.

THE CONTRACTOR SHALL TAKE CARE DURING JOINT REHAB OPERATIONS NOT TO DROP ANY MATERIAL BELOW THE BRIDGE WITHOUT PROTECTIVE DEVICES THAT FALLS BELOW THE BRIDGE SHALL BE CONTAINED, REMOVED AND DISPOSED OF BY THE CONTRACTOR AT NO EXTRA COST TO THE DEPARTMENT. IF THE ENGINEER DETERMINES THAT THE PROTECTIVE DEVICES ARE NOT ADEQUATE OR NOT BEING EMPLOYED, THE WORK SHALL BE SUSPENDED UNTIL ADEQUATE PROTECTION IS PROVIDED.

THE CONTRACTOR WILL NOT BE PERMITTED TO FORM THE JOINTS IN LIEU OF SAWING THE JOINT.

DURING THE JOINT INSTALLATION PROCEDURE, THE JOINT AND SURROUNDING AREA SHALL BE KEPT CLEAN AND FREE OF DEBRIS.

FOR POURABLE SILICONE JOINT SEALANT, SEE SPECIAL PROVISIONS.

THE MANUFACTURER IS TO PROVIDE THE NOMINAL UNCOMPRESSED SEAL WIDTH OF THE BACKER ROD FOR THE EXISTING JOINT SIZE AND ACCOMMODATE THE MINIMUM EXPANSION SHOWN ON THE PLANS.

A MANUFACTURER'S CERTIFIED TRAINED REPRESENTATIVE SHALL BE PRESENT DURING THE INSTALLATION OF THE FIRST JOINT OF THE PROJECT, OR UNTIL THE ENGINEER IS SATISFIED WITH THE INSTALLATION PROCESS.

THE INSTALLATION OF THE JOINT SEAL SHALL BE WATERTIGHT.

FINAL SURFACE OF THE JOINT DEMOLITION AREA PRIOR TO PLACEMENT OF CONCRETE REPAIR MATERIAL SHOULD BE REASONABLY FLAT AND LEVEL. ENGINEER SHALL DETERMINE THE ACCEPTABILITY OF THE SURFACE PRIOR TO PLACEMENT OF REPAIR CONCRETE.

**JOINT INSTALLATION SEQUENCE AT END BENTS**


SECTION A-A

JOINT REPAIR QUANTITY TABLE		
	ESTIMATE	ACTUAL
POURABLE SILICONE JOINT SEALANT		
END BENT 1	63.0 LF	
END BENT 2	71.7 LF	
TOTAL	134.7 LF	


JOINT REPAIR QUANTITY TABLE			
	CLASS II SURFACE PREPARATION	CONCRETE DECK REPAIR FOR PPC OVERLAY	
END BENT 1	6.9 SY	6.9 SY	
END BENT 2	7.8 SY	7.8 SY	
* TOTAL	14.7 SY	14.7 SY	

\* BASED ON THE MINIMUM BLOCKOUT SHOWN.


PROJECT NO. I-5795  
 FORSYTH COUNTY  
 BRIDGE NO. 330482



PLAN  
(@ END BENT)



SECTION C-C




DETAIL A

**JOINT SEAL DETAILS AT END BENTS**

DRAWN BY : E. BAYISSA DATE : 09/2019  
 CHECKED BY : A. SORSENGINH DATE : 01/2020

04-AUG-2020 16:42  
 N:\Division09\I5795\Structures\Final Plans Combined\410.009.I-5795.SMU.JT.04.330482.dgn  
 kssedl



STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

**JOINT DETAILS**

NO.	REVISIONS			NO.	REVISIONS			SHEET NO.
	BY:	DATE:			BY:	DATE:		
1				3				S10-04 TOTAL SHEETS 5
2				4				

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED



**NOTES**

FOR FOAM JOINT SEALS FOR PRESERVATION, SEE SPECIAL PROVISIONS.

THE INSTALLED FOAM JOINTS SHALL BE WATER TIGHT.

THE FOAM JOINTS SHALL MEET THE MANUFACTURER'S RECOMMENDATION FOR THE SIZE OF OPENING ON THE PLANS, AND ACCOMMODATE THE MINIMUM EXPANSION SHOWN ON THE PLANS.

THE CONTRACTOR WILL NOT BE PERMITTED TO FORM THE JOINTS IN LIEU OF SAWING THE JOINT.

DURING THE JOINT INSTALLATION PROCEDURE, THE JOINT AND SURROUNDING AREA SHALL BE KEPT CLEAN AND FREE OF DEBRIS.

THE MANUFACTURER IS TO PROVIDE THE NOMINAL UNCOMPRESSED SEAL WIDTH OF THE FOAM JOINT SEAL BASED ON JOINT OPENINGS AT THE BENTS.

A MANUFACTURER'S CERTIFIED TRAINED REPRESENTATIVE SHALL BE PRESENT DURING THE INSTALLATION OF THE FIRST JOINT OF THE PROJECT, OR UNTIL THE ENGINEER IS SATISFIED WITH THE INSTALLATION PROCESS.


FINAL JOINT SEALS SHALL NOT BE INSTALLED UNTIL THE OVERLAY IS COMPLETE.

THE CONTRACTOR SHALL TAKE CARE DURING JOINT REHAB OPERATIONS NOT TO DROP ANY MATERIAL BELOW THE BRIDGE WITHOUT PROTECTIVE DEVICES BELOW TO CATCH THE MATERIAL. ANY MATERIAL THAT FALLS BELOW THE BRIDGE SHALL BE CONTAINED, REMOVED AND DISPOSED OF BY THE CONTRACTOR AT NO EXTRA COST TO THE DEPARTMENT. IF THE ENGINEER DETERMINES THAT THE PROTECTIVE DEVICES ARE NOT ADEQUATE OR NOT BEING EMPLOYED, THE WORK SHALL BE SUSPENDED UNTIL ADEQUATE PROTECTION IS PROVIDED.


THE MANUFACTURER IS TO PROVIDE THE NOMINAL UNCOMPRESSED SEAL WIDTH OF THE BACKER ROD FOR THE EXISTING JOINT SIZE AND ACCOMMODATE THE MINIMUM EXPANSION SHOWN ON THE PLANS.

CONTRACTOR SHALL FIELD VERIFY THE EXISTING JOINT OPENING PRIOR TO ORDERING JOINT SEAL MATERIAL. IF ACTUAL JOINT OPENING VARIES FROM OPENING INDICATED IN DETAIL BY MORE THAN 1/4", NOTIFY ENGINEER REVISION TO THE JOINT SEAL SIZE MIGHT BE NECESSARY.


FINAL SURFACE OF THE JOINT DEMOLITION AREA PRIOR TO PLACEMENT OF CONCRETE REPAIR MATERIAL SHOULD BE REASONABLY FLAT AND LEVEL. ENGINEER SHALL DETERMINE THE ACCEPTABILITY OF THE SURFACE PRIOR TO PLACEMENT OF REPAIR CONCRETE.



MINIMUM EXISTING JOINT DEMOLITION



PROPOSED PRE-SAWED JOINT




PROPOSED FOAM JOINT SEAL


**JOINT INSTALLATION SEQUENCE AT BENTS**

SECTION B-B

▲ SAW CUT SHALL BE 3/4" BELOW THE BOTTOM OF THE JOINT SEAL, SEE MANUFACTURER RECOMMENDATIONS



**JOINT SEAL DETAILS AT BENTS**




	CLASS II SURFACE PREPARATION	CONCRETE DECK REPAIR FOR PPC OVERLAY
BENT 1	9.5 SY	9.5 SY
BENT 2	9.7 SY	9.7 SY
* TOTAL	19.2 SY	19.2 SY

\* BASED ON THE MINIMUM BLOCKOUT SHOWN.

FOAM JOINT SEALS FOR PRESERVATION	ESTIMATED	ACTUAL
BENT 1	64.2 LF	
BENT 2	65.0 LF	
TOTAL	129.2 LF	

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330482



STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

**JOINT DETAILS  
 BENTS 1 & 2**

DRAWN BY : A. SORSENGINH DATE : 5/2020  
 CHECKED BY : E. BAYISSA DATE : 5/2020

NO.	REVISIONS			NO.	REVISIONS			SHEET NO.
	BY:	DATE:			BY:	DATE:		
1				3			S10-05	
2				4			TOTAL SHEETS 5	

**NOTES:**


GENERAL DRAWING INFORMATION IS TAKEN FROM THE ORIGINAL PLANS AND THE ROUTINE INSPECTION REPORT DATED 09/05/2018.  
 BRIDGE ORIENTATION CONFORMS TO THE EXISTING BRIDGE PLANS / ROUTINE INSPECTION.

**SCOPE OF WORK**


- PARTIALLY REMOVE TOP OF BRIDGE DECK CONCRETE BY SCARIFICATION AND SHOTBLASTING METHODS.
- OVERLAY PREPARED TOP OF BRIDGE DECK WITH POLYESTER POLYMER CONCRETE (PPC).
- REMOVE EXISTING JOINT MATERIAL AND INSTALL POURABLE SILICONE JOINTS.
- GROOVE PPC BRIDGE DECK.
- REMOVE DEBRIS FROM TOP OF EXISTING END BENTS AND BENT CAPS, AND APPLY EPOXY COATING.
- CLEAN AND EPOXY COAT EXISTING PRESTRESSED CONCRETE GIRDER ENDS.

I HEREBY CERTIFY THAT THIS STRUCTURE WAS REHABILITATED ACCORDING TO THESE PLANS OR AS NOTED HEREIN.

RESIDENT ENGINEER \_\_\_\_\_ DATE \_\_\_\_\_





SECTION ALONG ORIGINAL GRADE LINE



PLAN

PROJECT NO. I-5795  
 FORSYTH COUNTY  
 BRIDGE NO. 330486




STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH  
**GENERAL DRAWING**  
 FOR  
 BRIDGE ON I-40(WBL)  
 OVER SALEM CREEK

DRAWN BY : C. RUIZ DATE : 06/2019  
 CHECKED BY : E. BAYISSA DATE : 01/2020


DOCUMENT NOT CONSIDERED  
 FINAL UNLESS ALL  
 SIGNATURES COMPLETED

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	SHEET NO.
1			3			S11-01
2			4			TOTAL SHEETS 4


**NOTES:**  
 SEE TRANSPORTATION MANAGEMENT PLANS FOR LANE WIDTHS, SEQUENCING AND OTHER TRAFFIC CONTROL MEASURES FOR STAGING OF OVERLAY SURFACE PREPARATION AND POLYESTER POLYMER CONCRETE PLACEMENT.




**TYPICAL SECTION**  
(EXISTING)




**TYPICAL SECTION - APPROACH SLAB**  
(EXISTING)



**TYPICAL SECTION**  
(PROPOSED)




**TYPICAL SECTION - APPROACH SLAB**  
(PROPOSED)




**DETAIL FOR POLYESTER POLYMER CONCRETE OVERLAY**

FINISHED SURFACE ELEVATION SHALL MATCH EXISTING CONCRETE SURFACE ELEVATION. ACTUAL THICKNESS OF PPC OVERLAY MAY VARY.



**STAGED PPC OVERLAY JOINT**  
(AS NEEDED)

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330486



STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH  
**SUPERSTRUCTURE  
 TYPICAL SECTION &  
 PPC OVERLAY DETAIL**

DRAWN BY : C. RUIZ DATE : 06/2019  
 CHECKED BY : E. BAYISSA DATE : 01/2020

DOCUMENT NOT CONSIDERED  
 FINAL UNLESS ALL  
 SIGNATURES COMPLETED

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	TOTAL SHEETS
1			3			4
2			4			


# AS-BUILT REPAIR QUANTITY TABLE

## TOP OF DECK REPAIRS

	ESTIMATE	ACTUAL
<b>SCARIFYING BRIDGE DECK</b>		
APPROACH SLAB 1	85 SQ. YDS.	
SPAN A	379 SQ. YDS.	
SPAN B	576 SQ. YDS.	
SPAN C	369 SQ. YDS.	
APPROACH SLAB 2	85 SQ. YDS.	
<b>CLASS II SURFACE PREPARATION</b>		
APPROACH SLAB 1	0.0 SQ. YDS.	
SPAN A	0.0 SQ. YDS.	
SPAN B	0.0 SQ. YDS.	
SPAN C	0.0 SQ. YDS.	
APPROACH SLAB 2	0.0 SQ. YDS.	
<b>CONCRETE DECK REPAIR FOR PPC OVERLAY</b>		
APPROACH SLAB 1	0.0 SQ. YDS.	
SPAN A	0.0 SQ. YDS.	
SPAN B	0.0 SQ. YDS.	
SPAN C	0.0 SQ. YDS.	
APPROACH SLAB 2	0.0 SQ. YDS.	
<b>SHOTBLASTING BRIDGE DECK</b>		
APPROACH SLAB 1	85 SQ. YDS.	
SPAN A	379 SQ. YDS.	
SPAN B	576 SQ. YDS.	
SPAN C	369 SQ. YDS.	
APPROACH SLAB 2	85 SQ. YDS.	
<b>PPC MATERIALS</b>		
APPROACH SLAB 1	3.0 CU. YDS.	
SPAN A	13.2 CU. YDS.	
SPAN B	20.0 CU. YDS.	
SPAN C	12.9 CU. YDS.	
APPROACH SLAB 2	3.0 CU. YDS.	
<b>PLACING AND FINISHING PPC OVERLAY</b>		
APPROACH SLAB 1	85 SQ. YDS.	
SPAN A	379 SQ. YDS.	
SPAN B	576 SQ. YDS.	
SPAN C	369 SQ. YDS.	
APPROACH SLAB 2	85 SQ. YDS.	
<b>GROOVING BRIDGE FLOORS</b>		
APPROACH SLAB 1	676 SQ. FT.	
SPAN A	3223 SQ. FT.	
SPAN B	4911 SQ. FT.	
SPAN C	3131 SQ. FT.	
APPROACH SLAB 2	676 SQ. FT.	
<b>EPOXY COATING CONCRETE GIRDER ENDS</b>		
SPAN A	387.4 SQ. FT.	
SPAN B	478.1 SQ. FT.	
SPAN C	387.4 SQ. FT.	

## EPOXY COATING

	ESTIMATE	ACTUAL
	AREA SQ. FT.	AREA SQ. FT.
END BENT 1	128.2	0
BENT 1	200.3	0
BENT 2	200.3	0
END BENT 2	127.9	0



PLAN OF SPANS

### NOTES:

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE BASED ON THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER WILL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATIONS AND DESCRIPTION OF THE REPAIRS AND ENTER THE ACTUAL QUANTITIES INTO THE AS-BUILT REPAIR QUANTITY TABLE.

FOR SECTION A-A AND SECTION B-B, SEE "JOINT DETAILS" SHEET.

FOR SCARIFYING BRIDGE DECK, SHOTBLASTING BRIDGE DECK AND CLASS II SURFACE PREPARATION, SEE OVERLAY SURFACE PREPARATION FOR POLYESTER POLYMER CONCRETE SPECIAL PROVISION.


FOR CONCRETE DECK REPAIR FOR PPC OVERLAY, PPC MATERIALS, AND PLACING AND FINISHING PPC OVERLAY, SEE POLYESTER POLYMER CONCRETE BRIDGE DECK OVERLAY SPECIAL PROVISION.

TOP OF DECK REPAIR QUANTITIES REPRESENT ESTIMATED VALUES OF CLASS II SURFACE PREPARATION AND CONCRETE DECK REPAIR FOR PPC OVERLAY AFTER REMOVAL OF UNSOUND CONCRETE (MIN. 2" CLEAR TO SAWCUT.) SEE OVERLAY SURFACE PREPARATION FOR POLYESTER POLYMER CONCRETE SPECIAL PROVISION.

FOR EPOXY COATING CONCRETE GIRDER ENDS, SEE SPECIAL PROVISIONS.

CLEAN AND REMOVE DEBRIS FROM THE TOP OF THE CAP AND APPLY EPOXY PROTECTIVE COATING. EPOXY COATING SHALL BE APPLIED TO THE TOP SURFACE OF THE CAP. THE CONTRACTOR SHALL NOT COAT THE AREA OF THE CAP BENEATH THE MASONRY PLATES. FOR EPOXY COATING, SEE SPECIAL PROVISIONS.

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330486




STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH  
**DECK SURFACE REPAIR**  
 SPANS A THRU C


DRAWN BY : C. RUIZ DATE : 06/2019  
 CHECKED BY : E. BAYISSA DATE : 01/2020

DOCUMENT NOT CONSIDERED  
 FINAL UNLESS ALL  
 SIGNATURES COMPLETED


REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	SHEET NO.
1			3			S11-03
2			4			TOTAL SHEETS 4



EXISTING JOINT




MINIMUM EXISTING JOINT DEMOLITION & SCARIFICATION




PROPOSED JOINT WITH SAWED DIMENSIONS

JOINT INSTALLATION SEQUENCE AT END BENTS


SECTION A-A



EXISTING JOINT



MINIMUM EXISTING JOINT DEMOLITION & SCARIFICATION



PROPOSED JOINT WITH SAWED DIMENSIONS

NOTES:

THE CONTRACTOR SHALL FIELD VERIFY THE EXISTING JOINT OPENING PRIOR TO ORDERING JOINT SEAL MATERIAL. IF ACTUAL JOINT OPENING VARIES FROM THE OPENING INDICATED IN DETAIL BY MORE THAN 1/4", NOTIFY ENGINEER. REVISION TO THE JOINT SEAL SIZE MIGHT BE NECESSARY.

FINAL JOINT SEALS SHALL NOT BE INSTALLED UNTIL THE OVERLAY IS COMPLETE.

THE CONTRACTOR SHALL TAKE CARE DURING JOINT REHAB OPERATIONS NOT TO DROP ANY MATERIAL BELOW THE BRIDGE WITHOUT PROTECTIVE DEVICES BELOW THE BRIDGE SHALL BE CONTAINED, REMOVED AND DISPOSED OF BY THE CONTRACTOR AT NO EXTRA COST TO THE DEPARTMENT. IF THE ENGINEER DETERMINES THAT THE PROTECTIVE DEVICES ARE NOT ADEQUATE OR NOT BEING EMPLOYED, THE WORK SHALL BE SUSPENDED UNTIL ADEQUATE PROTECTION IS PROVIDED.

THE CONTRACTOR WILL NOT BE PERMITTED TO FORM THE JOINTS IN LIEU OF SAWING THE JOINT.

DURING THE JOINT INSTALLATION PROCEDURE, THE JOINT AND SURROUNDING AREA SHALL BE KEPT CLEAN AND FREE OF DEBRIS.

FOR POURABLE SILICONE JOINT SEALANT, SEE SPECIAL PROVISIONS.

THE MANUFACTURER IS TO PROVIDE THE NOMINAL UNCOMPRESSED SEAL WIDTH OF THE BACKER ROD FOR THE EXISTING JOINT SIZE AND ACCOMMODATE THE MINIMUM EXPANSION SHOWN ON THE PLANS.

A MANUFACTURER'S CERTIFIED TRAINED REPRESENTATIVE SHALL BE PRESENT DURING THE INSTALLATION OF THE FIRST JOINT OF THE PROJECT, OR UNTIL THE ENGINEER IS SATISFIED WITH THE INSTALLATION PROCESS.

THE INSTALLATION OF THE JOINT SEAL SHALL BE WATERTIGHT.


FINAL SURFACE OF THE JOINT DEMOLITION AREA PRIOR TO PLACEMENT OF CONCRETE REPAIR MATERIAL SHOULD BE REASONABLY FLAT AND LEVEL. ENGINEER SHALL DETERMINE THE ACCEPTABILITY OF THE SURFACE PRIOR TO PLACEMENT OF REPAIR CONCRETE.

JOINT REPAIR QUANTITY TABLE		
	CLASS II SURFACE PREPARATION	CONCRETE DECK REPAIR FOR PPC OVERLAY
END BENT 1	7.2 SQ. Y.	7.2 SQ. Y.
BENT 1	7.2 SQ. Y.	7.2 SQ. Y.
BENT 2	7.1 SQ. Y.	7.1 SQ. Y.
END BENT 2	7.1 SQ. Y.	7.1 SQ. Y.
* TOTAL	28.6 SQ. Y.	28.6 SQ. Y.


\* BASED ON THE MINIMUM BLOCKOUT SHOWN.

JOINT INSTALLATION SEQUENCE AT BENTS

SECTION B-B




JOINT DETAIL AT BARRIER RAIL



SECTION C-C


\* NON-SAG SILICONE JOINT SEALANT TO BE PLACED AND ALLOWED TO SET, PRIOR TO PLACEMENT OF SELF-LEVELING SILICONE JOINT SEALANT.



DETAIL "A"

JOINT REPAIR QUANTITY TABLE		
	ESTIMATE	ACTUAL
POURABLE SILICONE JOINT SEALANT		
END BENT 1	66 LF	
BENT 1	66 LF	
BENT 2	66 LF	
END BENT 2	66 LF	
TOTAL	264 LF	

8/4/2020



PROJECT NO. I-5795  
 FORSYTH COUNTY  
 BRIDGE NO. 330486


STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

JOINT DETAILS

DRAWN BY : C. RUIZ DATE : 06/2019  
 CHECKED BY : E. BAYISSA DATE : 01/2020

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S11-04
1			3			TOTAL SHEETS
2			4			4

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED



SECTION ALONG ORIGINAL GRADE LINE

NOTES


GENERAL DRAWING INFORMATION IS TAKEN FROM THE ORIGINAL PLANS AND THE ROUTINE INSPECTION REPORT DATED 09/05/2018.  
 BRIDGE ORIENTATION CONFORMS TO THE EXISTING BRIDGE PLANS / ROUTINE INSPECTION.

SCOPE OF WORK

- PARTIALLY REMOVE TOP OF BRIDGE DECK CONCRETE BY SCARIFICATION AND SHOTBLASTING METHODS.
- OVERLAY PREPARED TOP OF BRIDGE DECK WITH POLYESTER POLYMER CONCRETE (PPC).
- REMOVE EXISTING JOINT MATERIAL AND INSTALL POURABLE SILICONE JOINTS.
- GROOVE PPC BRIDGE DECK.
- REMOVE DEBRIS FROM TOP OF EXISTING END BENTS AND BENT CAPS, AND APPLY EPOXY COATING.
- CLEAN AND EPOXY COAT EXISTING PRESTRESSED CONCRETE GIRDER ENDS.



I HEREBY CERTIFY THAT THIS STRUCTURE WAS REHABILITATED ACCORDING TO THESE PLANS OR AS NOTED HEREIN.

RESIDENT ENGINEER \_\_\_\_\_ DATE \_\_\_\_\_



PLAN

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330487




STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH  
**GENERAL DRAWING**  
 FOR  
 BRIDGE ON I-40(EBL)  
 OVER SALEM CREEK

DRAWN BY : C. RUIZ DATE : 06/2019  
 CHECKED BY : E. BAYISSA DATE : 01/2020


DOCUMENT NOT CONSIDERED  
 FINAL UNLESS ALL  
 SIGNATURES COMPLETED

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	SHEET NO.
1			3			S12-01
2			4			TOTAL SHEETS 4


**NOTES:**  
 SEE TRANSPORTATION MANAGEMENT PLANS FOR LANE WIDTHS, SEQUENCING AND OTHER TRAFFIC CONTROL MEASURES FOR STAGING OF OVERLAY SURFACE PREPARATION AND POLYESTER POLYMER CONCRETE PLACEMENT.




**TYPICAL SECTION**  
(EXISTING)




**TYPICAL SECTION - APPROACH SLAB**  
(EXISTING)



**TYPICAL SECTION**  
(PROPOSED)




**TYPICAL SECTION - APPROACH SLAB**  
(PROPOSED)




**DETAIL FOR POLYESTER POLYMER CONCRETE OVERLAY**

FINISHED SURFACE ELEVATION SHALL MATCH EXISTING CONCRETE SURFACE ELEVATION. ACTUAL THICKNESS OF PPC OVERLAY MAY VARY



**STAGED PPC OVERLAY JOINT**  
(AS NEEDED)

PROJECT NO. I5795  
 FORSYTH COUNTY  
 BRIDGE NO. 330487



STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH  
 SUPERSTRUCTURE  
 TYPICAL SECTION &  
 PPC OVERLAY DETAIL

DRAWN BY : C. RUIZ DATE : .06/2019  
 CHECKED BY : E. BAYISSA DATE : .01/2020

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	TOTAL SHEETS
1			3			4
2			4			

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED


# AS-BUILT REPAIR QUANTITY TABLE

## TOP OF DECK REPAIRS

	ESTIMATE	ACTUAL
<b>SCARIFYING BRIDGE DECK</b>		
APPROACH SLAB 1	75 SQ. YDS.	
SPAN A	332 SQ. YDS.	
SPAN B	504 SQ. YDS.	
SPAN C	323 SQ. YDS.	
APPROACH SLAB 2	75 SQ. YDS.	
<b>CLASS II SURFACE PREPARATION</b>		
APPROACH SLAB 1	0.0 SQ. YDS.	
SPAN A	0.0 SQ. YDS.	
SPAN B	0.0 SQ. YDS.	
SPAN C	0.0 SQ. YDS.	
APPROACH SLAB 2	0.0 SQ. YDS.	
<b>CONCRETE DECK REPAIR FOR PPC OVERLAY</b>		
APPROACH SLAB 1	0.0 SQ. YDS.	
SPAN A	0.0 SQ. YDS.	
SPAN B	0.0 SQ. YDS.	
SPAN C	0.0 SQ. YDS.	
APPROACH SLAB 2	0.0 SQ. YDS.	
<b>SHOTBLASTING BRIDGE DECK</b>		
APPROACH SLAB 1	75 SQ. YDS.	
SPAN A	332 SQ. YDS.	
SPAN B	504 SQ. YDS.	
SPAN C	323 SQ. YDS.	
APPROACH SLAB 2	75 SQ. YDS.	
<b>PPC MATERIALS</b>		
APPROACH SLAB 1	2.6 CU. YDS.	
SPAN A	11.6 CU. YDS.	
SPAN B	17.5 CU. YDS.	
SPAN C	11.3 CU. YDS.	
APPROACH SLAB 2	2.6 CU. YDS.	
<b>PLACING AND FINISHING PPC OVERLAY</b>		
APPROACH SLAB 1	75 SQ. YDS.	
SPAN A	332 SQ. YDS.	
SPAN B	504 SQ. YDS.	
SPAN C	323 SQ. YDS.	
APPROACH SLAB 2	75 SQ. YDS.	
<b>GROOVING BRIDGE FLOORS</b>		
APPROACH SLAB 1	587 SQ. FT.	
SPAN A	2800 SQ. FT.	
SPAN B	4266 SQ. FT.	
SPAN C	2721 SQ. FT.	
APPROACH SLAB 2	587 SQ. FT.	
<b>EPOXY COATING CONCRETE GIRDER ENDS</b>		
SPAN A	339.0 SQ. FT.	
SPAN B	418.3 SQ. FT.	
SPAN C	339.0 SQ. FT.	

## EPOXY COATING

	ESTIMATE	ACTUAL
	AREA SQ. FT.	AREA SQ. FT.
END BENT 1	114.2	0
BENT 1	173.4	0
BENT 2	173.4	0
END BENT 2	110.3	0



## PLAN OF SPANS

### NOTES:

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE BASED ON THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER WILL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATIONS AND DESCRIPTION OF THE REPAIRS AND ENTER THE ACTUAL QUANTITIES INTO THE AS-BUILT REPAIR QUANTITY TABLE.

FOR SECTION A-A AND SECTION B-B, SEE "JOINT DETAILS" SHEET.

FOR SCARIFYING BRIDGE DECK, SHOTBLASTING BRIDGE DECK AND CLASS II SURFACE PREPARATION, SEE OVERLAY SURFACE PREPARATION FOR POLYESTER POLYMER CONCRETE SPECIAL PROVISION.


FOR CONCRETE DECK REPAIR FOR PPC OVERLAY, PPC MATERIALS, AND PLACING AND FINISHING PPC OVERLAY, SEE POLYESTER POLYMER CONCRETE BRIDGE DECK OVERLAY SPECIAL PROVISION.

TOP OF DECK REPAIR QUANTITIES REPRESENT ESTIMATED VALUES OF CLASS II SURFACE PREPARATION AND CONCRETE DECK REPAIR FOR PPC OVERLAY AFTER REMOVAL OF UNSOUND CONCRETE (MIN. 2" CLEAR TO SAWCUT.) SEE OVERLAY SURFACE PREPARATION FOR POLYESTER POLYMER CONCRETE SPECIAL PROVISION.

FOR EPOXY COATING CONCRETE GIRDER ENDS, SEE SPECIAL PROVISIONS.

CLEAN AND REMOVE DEBRIS FROM THE TOP OF THE CAP AND APPLY EPOXY PROTECTIVE COATING. EPOXY COATING SHALL BE APPLIED TO THE TOP SURFACE OF THE CAP. THE CONTRACTOR SHALL NOT COAT THE AREA OF THE CAP BENEATH THE MASONRY PLATES. FOR EPOXY COATING, SEE SPECIAL PROVISIONS.

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330487




STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH  
**DECK SURFACE REPAIR**  
 SPANS A THRU C

DRAWN BY : C. RUIZ DATE : 06/2019  
 CHECKED BY : E. BAYISSA DATE : 01/2020


DOCUMENT NOT CONSIDERED  
 FINAL UNLESS ALL  
 SIGNATURES COMPLETED

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	TOTAL SHEETS
1			3			4
2			4			






EXISTING JOINT




MINIMUM EXISTING JOINT DEMOLITION & SCARIFICATION




PROPOSED JOINT WITH SAWED DIMENSIONS

JOINT INSTALLATION SEQUENCE AT END BENTS


SECTION A-A



EXISTING JOINT




MINIMUM EXISTING JOINT DEMOLITION & SCARIFICATION




PROPOSED JOINT WITH SAWED DIMENSIONS

JOINT INSTALLATION SEQUENCE AT BENTS

SECTION B-B




JOINT DETAIL AT BARRIER RAIL




SECTION C-C

\*NON-SAG SILICONE JOINT SEALANT TO BE PLACED AND ALLOWED TO SET, PRIOR TO PLACEMENT OF SELF-LEVELING SILICONE JOINT SEALANT.



DETAIL "A"



DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

**NOTES:**  
 THE CONTRACTOR SHALL FIELD VERIFY THE EXISTING JOINT OPENING PRIOR TO ORDERING JOINT SEAL MATERIAL. IF ACTUAL JOINT OPENING VARIES FROM THE OPENING INDICATED IN DETAIL BY MORE THAN 1/4", NOTIFY ENGINEER. REVISION TO THE JOINT SEAL SIZE MIGHT BE NECESSARY.  
 FINAL JOINT SEALS SHALL NOT BE INSTALLED UNTIL THE OVERLAY IS COMPLETE.  
 THE CONTRACTOR SHALL TAKE CARE DURING JOINT REHAB OPERATIONS NOT TO DROP ANY MATERIAL BELOW THE BRIDGE WITHOUT PROTECTIVE DEVICES BELOW THE BRIDGE SHALL BE CONTAINED, REMOVED AND DISPOSED OF BY THE CONTRACTOR AT NO EXTRA COST TO THE DEPARTMENT. IF THE ENGINEER DETERMINES THAT THE PROTECTIVE DEVICES ARE NOT ADEQUATE OR NOT BEING EMPLOYED, THE WORK SHALL BE SUSPENDED UNTIL ADEQUATE PROTECTION IS PROVIDED.  
 THE CONTRACTOR WILL NOT BE PERMITTED TO FORM THE JOINTS IN LIEU OF SAWING THE JOINT.  
 DURING THE JOINT INSTALLATION PROCEDURE, THE JOINT AND SURROUNDING AREA SHALL BE KEPT CLEAN AND FREE OF DEBRIS.  
 FOR POURABLE SILICONE JOINT SEALANT, SEE SPECIAL PROVISIONS.  
 THE MANUFACTURER IS TO PROVIDE THE NOMINAL UNCOMPRESSED SEAL WIDTH OF THE BACKER ROD FOR THE EXISTING JOINT SIZE AND ACCOMMODATE THE MINIMUM EXPANSION SHOWN ON THE PLANS.  
 A MANUFACTURER'S CERTIFIED TRAINED REPRESENTATIVE SHALL BE PRESENT DURING THE INSTALLATION OF THE FIRST JOINT OF THE PROJECT, OR UNTIL THE ENGINEER IS SATISFIED WITH THE INSTALLATION PROCESS.  
 THE INSTALLATION OF THE JOINT SEAL SHALL BE WATERTIGHT.  
 FINAL SURFACE OF THE JOINT DEMOLITION AREA PRIOR TO PLACEMENT OF CONCRETE REPAIR MATERIAL SHOULD BE REASONABLY FLAT AND LEVEL. ENGINEER SHALL DETERMINE THE ACCEPTABILITY OF THE SURFACE PRIOR TO PLACEMENT OF REPAIR CONCRETE.

JOINT REPAIR QUANTITY TABLE		
	CLASS II SURFACE PREPARATION	CONCRETE DECK REPAIR FOR PPC OVERLAY
END BENT 1	6.3 SY	6.3 SY
BENT 1	6.3 SY	6.3 SY
BENT 2	6.2 SY	6.2 SY
END BENT 2	6.2 SY	6.2 SY
* TOTAL	25.0 SY	25.0 SY

\*BASED ON THE MINIMUM BLOCKOUT SHOWN.

JOINT REPAIR QUANTITY TABLE		
	ESTIMATE	ACTUAL
POURABLE SILICONE JOINT SEALANT		
END BENT 1	58 LF	
BENT 1	58 LF	
BENT 2	58 LF	
END BENT 2	58 LF	
TOTAL	232 LF	


PROJECT NO. I-5795  
 FORSYTH COUNTY  
 BRIDGE NO. 330487

STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

JOINT DETAILS


REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	SHEET NO.
1			3			S12-04
2			4			TOTAL SHEETS 4

DRAWN BY : C. RUIZ DATE : 06/2019  
 CHECKED BY : E. BAYISSA DATE : 01/2020






**NOTES**

- GENERAL DRAWING INFORMATION IS TAKEN FROM THE ORIGINAL PLANS AND THE ROUTINE INSPECTION REPORT DATED 8/20/2018.
- BRIDGE ORIENTATION CONFORMS TO THE EXISTING BRIDGE PLANS/ROUTINE INSPECTION.
- SCOPE OF WORK**
- PARTIALLY REMOVE TOP OF BRIDGE DECK CONCRETE BY SCARIFICATION AND SHOTBLASTING METHODS.
  - OVERLAY PREPARED TOP OF BRIDGE DECK WITH POLYESTER POLYMER CONCRETE (PPC).
  - REMOVE EXISTING JOINT MATERIAL AND INSTALL POURABLE SILICONE JOINTS.
  - REMOVE EXISTING JOINT MATERIAL AND INSTALL FOAM JOINTS.
  - GROOVE PPC BRIDGE DECK.
  - CLEAN AND PAINT EXISTING WEATHERING STEEL BEAM ENDS.
  - INJECT CONCRETE CRACKS WITH EPOXY RESIN.
  - REMOVE UNSOUND CONCRETE AND PROPERLY PREPARE EXISTING END BENT AND BENT AREAS AND PERFORM SHOTCRETE AND/OR CONCRETE REPAIRS.
  - REMOVE DEBRIS FROM TOP OF EXISTING END BENT AND BENT CAPS AND APPLY EPOXY COATING.



I HEREBY CERTIFY THAT THIS STRUCTURE WAS REHABILITATED ACCORDING TO THESE PLANS OR AS NOTED HEREIN.

RESIDENT ENGINEER \_\_\_\_\_ DATE \_\_\_\_\_



PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330488

STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

**GENERAL DRAWING  
 FOR BRIDGE ON I-40 WBL  
 OVER NC 150 RAMPS**







DRAWN BY : A. SORSENGINH DATE : 6/2019  
 CHECKED BY : E. BAYISSA DATE : 1/2020

DOCUMENT NOT CONSIDERED  
 FINAL UNLESS ALL  
 SIGNATURES COMPLETED


REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	TOTAL SHEETS
1			3			6
2			4			

**NOTE:**

SEE TRANSPORTATION MANAGEMENT PLANS FOR LANE WIDTHS, SEQUENCING AND OTHER TRAFFIC CONTROL MEASURES FOR STAGING OF OVERLAY SURFACE PREPARATION AND POLYESTER POLYMER CONCRETE PLACEMENT.



PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330488



STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

**TYPICAL SECTION &  
 PPC OVERLAY DETAILS**

DRAWN BY : A. SORSENGINH DATE : 7/2019  
 CHECKED BY : E. BAYISSA DATE : 1/2020

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S13-02
1			3			TOTAL SHEETS
2			4			7

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED




NOTES:


REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE BASED ON THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER WILL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATIONS AND DESCRIPTION OF THE REPAIRS AND ENTER THE ACTUAL QUANTITIES INTO THE AS-BUILT REPAIR QUANTITY TABLE.

FOR CONCRETE DECK REPAIR FOR PPC OVERLAY, PPC MATERIALS, AND PLACING AND FINISHING PPC OVERLAY, SEE POLYESTER POLYMER CONCRETE BRIDGE DECK OVERLAY SPECIAL PROVISION.

FOR SECTION A-A AND SECTION B-B, SEE "JOINT DETAILS" SHEET.

FOR SCARIFYING BRIDGE DECK, SHOTBLASTING BRIDGE DECK AND CLASS II SURFACE PREPARATION SEE OVERLAY SURFACE PREPARATION FOR POLYESTER POLYMER CONCRETE SPECIAL PROVISION.

-  APPROX. CLASS II SURFACE PREPARATION
-  CURB AND BARRIER RAIL
-  EPOXY RESIN INJECTION (ERI)




PLAN  
\* RADIAL DIMENSION

AS-BUILT REPAIR QUANTITY TABLE

TOP OF DECK REPAIRS	APPROACH SLAB 1		SPAN A		SPAN B		SPAN C		APPROACH SLAB 2	
	ESTIMATE	ACTUAL	ESTIMATE	ACTUAL	ESTIMATE	ACTUAL	ESTIMATE	ACTUAL	ESTIMATE	ACTUAL
SCARIFYING BRIDGE DECK	85.0 SQ. YDS.		370.0 SQ. YDS.		560.0 SQ. YDS.		293.0 SQ. YDS.		85.0 SQ. YDS.	
SHOTBLASTING BRIDGE DECK	85.0 SQ. YDS.		370.0 SQ. YDS.		560.0 SQ. YDS.		293.0 SQ. YDS.		85.0 SQ. YDS.	
CLASS II SURFACE PREPARATION	0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.		0.6 SQ. YDS.	
CONCRETE DECK REPAIR FOR PPC OVERLAY	0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.		0.0 SQ. YDS.		0.6 SQ. YDS.	
POLYESTER POLYMER CONCRETE MATERIALS	3.0 CU. YDS.		12.8 CU. YDS.		19.4 CU. YDS.		10.2 CU. YDS.		3.0 CU. YDS.	
PLACING & FINISHING PPC OVERLAY	85.0 SQ. YDS.		370.0 SQ. YDS.		560.0 SQ. YDS.		293.0 SQ. YDS.		85.0 SQ. YDS.	
GROOVING BRIDGE FLOOR	669.0 SQ. FT.		3151.0 SQ. FT.		4792.0 SQ. FT.		2489.0 SQ. FT.		668.0 SQ. FT.	
EPOXY RESIN INJECTION			5.0 LIN. FT.		0.0 LIN. FT.		0.0 LIN. FT.			
SHOTCRETE REPAIRS			ESTIMATE	ACTUAL	ESTIMATE	ACTUAL	ESTIMATE	ACTUAL		
CONCRETE BARRIER RAIL			AREA SQ. FT.	VOLUME CU. FT.	AREA SQ. FT.	VOLUME CU. FT.	AREA SQ. FT.	VOLUME CU. FT.	AREA SQ. FT.	VOLUME CU. FT.
			0.0	0.0			1.7	0.6	0.0	0.0

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330488







STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH  
 DECK SURFACE REPAIR  
 SPANS A THRU C

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	TOTAL SHEETS
1			3			6
2			4			

DRAWN BY : A. SORSENGINH DATE : 7/2019  
 CHECKED BY : E. BAYISSA DATE : 1/2020

DOCUMENT NOT CONSIDERED  
 FINAL UNLESS ALL  
 SIGNATURES COMPLETED



**NOTE**

THE CONTRACTOR SHALL FIELD VERIFY THE EXISTING JOINT OPENING PRIOR TO ORDERING JOINT SEAL MATERIAL. IF ACTUAL JOINT OPENING VARIES FROM THE OPENING INDICATED IN DETAIL BY MORE THAN 1/4", NOTIFY ENGINEER. REVISION TO THE JOINT SEAL SIZE MIGHT BE NECESSARY.

FINAL JOINT SEALS SHALL NOT BE INSTALLED UNTIL THE OVERLAY IS COMPLETE.

THE CONTRACTOR SHALL TAKE CARE DURING JOINT REHAB OPERATIONS NOT TO DROP ANY MATERIAL BELOW THE BRIDGE WITHOUT PROTECTIVE DEVICES BELOW TO CATCH THE MATERIAL. ANY MATERIAL THAT FALLS BELOW THE BRIDGE SHALL BE CONTAINED, REMOVED AND DISPOSED OF BY THE CONTRACTOR AT NO EXTRA COST TO THE DEPARTMENT. IF THE ENGINEER DETERMINES THAT THE PROTECTIVE DEVICES ARE NOT ADEQUATE OR NOT BEING EMPLOYED, THE WORK SHALL BE SUSPENDED UNTIL ADEQUATE PROTECTION IS PROVIDED.

THE CONTRACTOR WILL NOT BE PERMITTED TO FORM THE JOINTS IN LIEU OF SAWING THE JOINT.

DURING THE JOINT INSTALLATION PROCEDURE, THE JOINT AND SURROUNDING AREA SHALL BE KEPT CLEAN AND FREE OF DEBRIS.

FOR POURABLE SILICONE JOINT SEALANT, SEE SPECIAL PROVISIONS.

THE MANUFACTURER IS TO PROVIDE THE NOMINAL UNCOMPRESSED SEAL WIDTH OF THE BACKER ROD FOR THE EXISTING JOINT SIZE AND ACCOMMODATE THE MINIMUM EXPANSION SHOWN ON THE PLANS.

A MANUFACTURER'S CERTIFIED TRAINED REPRESENTATIVE SHALL BE PRESENT DURING THE INSTALLATION OF THE FIRST JOINT OF THE PROJECT, OR UNTIL THE ENGINEER IS SATISFIED WITH THE INSTALLATION PROCESS.

THE INSTALLATION OF THE JOINT SEAL SHALL BE WATERTIGHT.

FINAL SURFACE OF THE JOINT DEMOLITION AREA PRIOR TO PLACEMENT OF CONCRETE REPAIR MATERIAL SHOULD BE REASONABLY FLAT AND LEVEL. ENGINEER SHALL DETERMINE THE ACCEPTABILITY OF THE SURFACE PRIOR TO PLACEMENT OF REPAIR CONCRETE.




**JOINT INSTALLATION SEQUENCE AT END BENTS**

**SECTION A-A**

	CLASS II SURFACE PREPARATION	CONCRETE DECK REPAIR FOR PPC OVERLAY
END BENT 1	8.1 SY	8.1 SY
END BENT 2	8.2 SY	8.2 SY
* TOTAL	16.3 SY	16.3 SY


\* BASED ON THE MINIMUM BLOCKOUT SHOWN.

	ESTIMATE	ACTUAL
POURABLE SILICONE JOINT SEALANT		
END BENT 1	74.4 LF	
END BENT 2	74.8 LF	
TOTAL	149.2 LF	



**JOINT DETAILS AT BARRIER RAIL**

PROJECT NO. I-5795  
FORSYTH COUNTY  
 BRIDGE NO. 330488



STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

**JOINT DETAILS**

DRAWN BY : A. SORSENGINH DATE : 7/2019  
 CHECKED BY : E. BAYISSA DATE : 1/2020

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	TOTAL SHEETS
1			3			6
2			4			

**NOTES**

FOAM JOINTS SHALL BE INSTALLED AS PER MANUFACTURER'S RECOMMENDATIONS.

FOR FOAM JOINT SEALS FOR PRESERVATION, SEE SPECIAL PROVISIONS.

THE INSTALLED FOAM JOINTS SHALL BE WATER TIGHT.


THE FOAM JOINTS SHALL MEET THE MANUFACTURER'S RECOMMENDATION FOR THE SIZE OF OPENING ON THE PLANS, AND ACCOMMODATE THE MINIMUM EXPANSION SHOWN ON THE PLANS.

THE CONTRACTOR WILL NOT BE PERMITTED TO FORM THE JOINTS IN LIEU OF SAWING THE JOINT.


THE MANUFACTURER IS TO PROVIDE THE NOMINAL UNCOMPRESSED SEAL WIDTH OF THE FOAM JOINT SEAL BASED ON JOINT OPENINGS AT THE BENTS.

CONTRACTOR SHALL FIELD VERIFY THE EXISTING JOINT OPENING PRIOR TO ORDERING JOINT SEAL MATERIAL. IF ACTUAL JOINT OPENING VARIES FROM OPENING INDICATED IN DETAIL BY MORE THAN 1/4", NOTIFY ENGINEER REVISION TO THE JOINT SEAL SIZE MIGHT BE NECESSARY.

FINAL SURFACE OF THE JOINT DEMOLITION AREA PRIOR TO PLACEMENT OF CONCRETE REPAIR MATERIAL SHOULD BE REASONABLY FLAT AND LEVEL. ENGINEER SHALL DETERMINE THE ACCEPTABILITY OF THE SURFACE PRIOR TO PLACEMENT OF REPAIR CONCRETE.



**JOINT INSTALLATION SEQUENCE AT BENTS**  
SECTION B-B




**JOINT SEAL DETAILS AT BENTS**

	CLASS II SURFACE PREPARATION	CONCRETE DECK REPAIR FOR PPC OVERLAY
BENT 1	10.8 SY	10.8 SY
BENT 2	10.9 SY	10.9 SY
* TOTAL	21.7 SY	21.7 SY

\* BASED ON THE MINIMUM BLOCKOUT SHOWN.

FOAM JOINT SEALS FOR PRESERVATION	ESTIMATED	ACTUAL
BENT 1	73.3 LF	
BENT 2	73.5 LF	
TOTAL	146.8 LF	

PROJECT NO. I-5795  
FORSYTH COUNTY  
BRIDGE NO. 330488



STATE OF NORTH CAROLINA  
DEPARTMENT OF TRANSPORTATION  
RALEIGH  
**JOINT DETAILS  
BENTS 1 & 2**

DRAWN BY : A. SORSENGINH DATE : 5/2020  
CHECKED BY : E. BAYISSA DATE : 5/2020

DOCUMENT NOT CONSIDERED  
FINAL UNLESS ALL  
SIGNATURES COMPLETED

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S13-05
1			3			TOTAL SHEETS
2			4			6