

SIGNING FOR RESURFACING PROJECTS 3 4 (3) (SEE NOTE 1) 1000' OR MORE-3 (4) (SEE NOTE BELOW) 5 1 MILE SPACING (SEE NOTE BELOW) Y2 MAINLINE (-L-) SIGNING PLACE 1000' PRIOR TO BEGINNING OF CONSTRUCTION LIMITS. ONLY USED ON -Y- LINES IF RESURFACING LIMITS EXTEND 1000' ALONG -Y- LINE. 2) SUBDIVISION ROADS 3) DEAD END ROADS #2 SIGN ONLY USED WHEN RESURFACING LIMITS ARE 2 OR MORE MILES IN LENGTH. NEXT W7-3aP #2 SIGN UNLY USED WHEN RECOMPOSED PLACE INITIALLY AT THE CONSTRUCTION LIMITS AND SPACED 1 MILE APART THEREAFTER. IF NO -Y- LINES EXIST, PLACE 2ND SET $\frac{1}{2}$ MILE FROM THE CONSTRUCTION LIMITS AND THEN SPACE 1 MILE THEREAFTER. ROAD WORK AHEAD THESE ARE FOR -Y- LINES THAT ARE "THROUGH" ROADWAYS. DEAD END AND W20–1 48″ X 48″ SUBDIVISION ROADS ARE NOT "THROUGH" ROADWAYS. INSTALL 500' +/- FROM EACH -Y- LINE APPROACH AS SHOWN ABOVE. FOR MULTIPLE -Y- LINES THAT ARE SEPARATED BY 0.25 MILES OR LESS, TREAT AS A SINGLE UNIT AND INSTALL WITHIN 500' OF EACH APPROACH. A MAXIMUM OF 2 SIGN SETS PER MILE. DO NOT SP 13106 48" X 48" INSTALL WHEN -Y- LINES ARE WITHIN 0.5 MILES FROM "END ROAD WORK" SIGN. NOTES: PLACE 500' FOLLOWING THE END OF CONSTRUCTION LIMITS.

THE INTERSECTION.

