

SEE SHEET 2A FOR PLAN SHEET LAYOUT  
AT TIME OF INVESTIGATION

STATE OF NORTH CAROLINA  
DEPARTMENT OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
GEOTECHNICAL ENGINEERING UNIT

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	I-5711	1	33

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT (919) 707-6850. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

- NOTES:
- THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.
  - BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

PERSONNEL

TRIGON

WEIS, J.M.

INVESTIGATED BY FALCON ENG.

DRAWN BY HILL, M. J.

CHECKED BY HUNSBERGER, W. S.

SUBMITTED BY FALCON ENG.

DATE JANUARY 2019

ROADWAY  
SUBSURFACE INVESTIGATION

COUNTY ALAMANCE

PROJECT DESCRIPTION INTERCHANGE IMPROVEMENTS

AT I-40/I-85 AND SR 1007 (MEBANE OAKS RD)

IN MEBANE

INVENTORY

CONTENTS

LINE	STATION	PLAN	PROFILE
-L-	18+03.85 - 50+00.00	4-6	9,10
-RPA.YI-	12+50.00 - 15+70.28	5	10
-RPB.YI-	10+75.00 - 21+28.91	5,7	11

CROSS SECTIONS

LINE	STATION	SHEETS
-L-	41+50.00 - 44+50.00	13-27

APPENDICES

APPENDIX	TITLE	SHEETS
A	LABORATORY RESULTS	28-30

REFERENCE: I-5711

PROJECT: 50401



DocuSigned by  
*W. Scott Hunsberger*

54499AC805CD49E...  
1/11/2019

SIGNATURE DATE

DOCUMENT NOT CONSIDERED FINAL  
UNLESS ALL SIGNATURES COMPLETED


**NORTH CAROLINA DEPARTMENT OF TRANSPORTATION**  
**DIVISION OF HIGHWAYS**  
**GEOTECHNICAL ENGINEERING UNIT**  
**SUBSURFACE INVESTIGATION**  
**SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS**

SOIL DESCRIPTION										GRADATION										ROCK DESCRIPTION										TERMS AND DEFINITIONS																																																																	
SOIL IS CONSIDERED UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER AND YIELD LESS THAN 100 BLOWS PER FOOT ACCORDING TO THE STANDARD PENETRATION TEST (AASHTO T 208, ASTM D1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY INCLUDE THE FOLLOWING: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. FOR EXAMPLE, VERY STIFF, GRAY, SILTY CLAY, MOIST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC, A-7-6										WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. UNIFORMLY GRADED - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES.										HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED, AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS IN NON-COASTAL PLAIN MATERIAL. THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:										ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER. AQUIFER - A WATER BEARING FORMATION OR STRATA. ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND. ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC. ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE. CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE. COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE. CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK. DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL. DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH. FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE. FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES. FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLOGGED FROM PARENT MATERIAL. FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM. FORMATION (FM) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD. JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED. LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT. LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS. MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS. MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM. RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK. ROCK QUALITY DESIGNATION (ROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. SAPROLITE (SAP.) - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK. SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS. SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE. STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N OR BPF) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE. STRATA ROCK QUALITY DESIGNATION (SROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.																																																																	
SOIL LEGEND AND AASHTO CLASSIFICATION										ANGULARITY OF GRAINS										WEATHERED ROCK (WR)																																																																											
<table border="1"> <tr> <th>GENERAL CLASS.</th> <th colspan="5">GRANULAR MATERIALS (≤ 35% PASSING #200)</th> <th colspan="5">SILT-CLAY MATERIALS (&gt; 35% PASSING #200)</th> <th colspan="5">ORGANIC MATERIALS</th> </tr> <tr> <th>GROUP CLASS.</th> <th>A-1</th> <th>A-3</th> <th>A-2</th> <th>A-2-4</th> <th>A-2-5</th> <th>A-2-6</th> <th>A-2-7</th> <th>A-4</th> <th>A-5</th> <th>A-6</th> <th>A-7</th> <th>A-1, A-2</th> <th>A-3</th> <th>A-4, A-5</th> <th>A-6, A-7</th> <th></th> </tr> <tr> <th>SYMBOL</th> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </table>										GENERAL CLASS.	GRANULAR MATERIALS (≤ 35% PASSING #200)					SILT-CLAY MATERIALS (> 35% PASSING #200)					ORGANIC MATERIALS					GROUP CLASS.	A-1	A-3	A-2	A-2-4	A-2-5	A-2-6	A-2-7	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7		SYMBOL																	<p align="center"><b>MINERALOGICAL COMPOSITION</b></p> <p>MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHEN THEY ARE CONSIDERED OF SIGNIFICANCE.</p>										<p align="center"><b>CRYSTALLINE ROCK (CR)</b></p> <p>FINE TO COARSE GRAIN IGNEOUS AND METAMORPHIC ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES GRANITE, GNEISS, GABBRO, SCHIST, ETC.</p>																									
GENERAL CLASS.	GRANULAR MATERIALS (≤ 35% PASSING #200)					SILT-CLAY MATERIALS (> 35% PASSING #200)					ORGANIC MATERIALS																																																																																				
GROUP CLASS.	A-1	A-3	A-2	A-2-4	A-2-5	A-2-6	A-2-7	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7																																																																																
SYMBOL																																																																																															
CONSISTENCY OR DENSENESS										COMPRESSION										NON-CRYSTALLINE ROCK (NCR)																																																																											
<table border="1"> <tr> <th>PRIMARY SOIL TYPE</th> <th>COMPACTNESS OR CONSISTENCY</th> <th>RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)</th> <th>RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT<sup>2</sup>)</th> </tr> <tr> <td>GENERALLY GRANULAR MATERIAL (NON-COHESIVE)</td> <td>VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE</td> <td>&lt; 4 4 TO 10 10 TO 30 30 TO 50 &gt; 50</td> <td>N/A</td> </tr> <tr> <td>GENERALLY SILT-CLAY MATERIAL (COHESIVE)</td> <td>VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD</td> <td>&lt; 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 &gt; 30</td> <td>&lt; 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 &gt; 4</td> </tr> </table>										PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT <sup>2</sup> )	GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	< 4 4 TO 10 10 TO 30 30 TO 50 > 50	N/A	GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30	< 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4	<p align="center"><b>PERCENTAGE OF MATERIAL</b></p> <table border="1"> <tr> <th>ORGANIC MATERIAL</th> <th>GRANULAR SOILS</th> <th>SILT - CLAY SOILS</th> <th>OTHER MATERIAL</th> </tr> <tr> <td>TRACE OF ORGANIC MATTER</td> <td>2 - 3%</td> <td>3 - 5%</td> <td>TRACE 1 - 10%</td> </tr> <tr> <td>LITTLE ORGANIC MATTER</td> <td>3 - 5%</td> <td>5 - 12%</td> <td>LITTLE 10 - 20%</td> </tr> <tr> <td>MODERATELY ORGANIC</td> <td>5 - 10%</td> <td>12 - 20%</td> <td>SOME 20 - 35%</td> </tr> <tr> <td>HIGHLY ORGANIC</td> <td>&gt; 10%</td> <td>&gt; 20%</td> <td>HIGHLY 35% AND ABOVE</td> </tr> </table>										ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL	TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE 1 - 10%	LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE 10 - 20%	MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME 20 - 35%	HIGHLY ORGANIC	> 10%	> 20%	HIGHLY 35% AND ABOVE	<p align="center"><b>GROUND WATER</b></p> <p>▽ WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING                  ▼ STATIC WATER LEVEL AFTER 24 HOURS                  ▽PW PERCHED WATER, SATURATED ZONE, OR WATER BEARING STRATA   SPRING OR SEEP</p>																																											
PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT <sup>2</sup> )																																																																																												
GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	< 4 4 TO 10 10 TO 30 30 TO 50 > 50	N/A																																																																																												
GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30	< 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4																																																																																												
ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL																																																																																												
TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE 1 - 10%																																																																																												
LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE 10 - 20%																																																																																												
MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME 20 - 35%																																																																																												
HIGHLY ORGANIC	> 10%	> 20%	HIGHLY 35% AND ABOVE																																																																																												
TEXTURE OR GRAIN SIZE										MISCELLANEOUS SYMBOLS										WEATHERING																																																																											
<table border="1"> <tr> <th>U.S. STD. SIEVE SIZE OPENING (MM)</th> <th>4</th> <th>10</th> <th>40</th> <th>60</th> <th>200</th> <th>270</th> </tr> <tr> <td></td> <td>4.75</td> <td>2.00</td> <td>0.42</td> <td>0.25</td> <td>0.075</td> <td>0.053</td> </tr> </table>										U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270		4.75	2.00	0.42	0.25	0.075	0.053	<p align="center"><b>RECOMMENDATION SYMBOLS</b></p> <p>  UNDERCUT   SHALLOW UNDERCUT   UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE   UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK                 </p>										<p align="center"><b>ROCK HARDNESS</b></p> <p>                     VERY HARD CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.                      HARD CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.                      MODERATELY HARD CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.                      MEDIUM HARD CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.                      SOFT CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.                      VERY SOFT CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.                 </p>																																																													
U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270																																																																																									
	4.75	2.00	0.42	0.25	0.075	0.053																																																																																									
SOIL MOISTURE - CORRELATION OF TERMS										ABBREVIATIONS										FRESH																																																																											
<table border="1"> <tr> <th>SOIL MOISTURE SCALE (ATTERBERG LIMITS)</th> <th>FIELD MOISTURE DESCRIPTION</th> <th>GUIDE FOR FIELD MOISTURE DESCRIPTION</th> </tr> <tr> <td rowspan="3">LL PLASTIC RANGE (PI) PL</td> <td>- SATURATED - (SAT.)</td> <td>USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE</td> </tr> <tr> <td>- WET - (W)</td> <td>SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td>- MOIST - (M)</td> <td>SOLID; AT OR NEAR OPTIMUM MOISTURE</td> </tr> <tr> <td>OM SL</td> <td>- DRY - (D)</td> <td>REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td> </tr> </table>										SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION	LL PLASTIC RANGE (PI) PL	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE	OM SL	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE	<p align="center"><b>ABBREVIATIONS</b></p> <p>                     AR - AUGER REFUSAL                      BT - BORING TERMINATED                      CL - CLAY                      CPT - CORE PENETRATION TEST                      CSE - COARSE                      DMT - DILATOMETER TEST                      DPT - DYNAMIC PENETRATION TEST                      e - VOID RATIO                      F - FINE                      FOSS. - FOSSILIFEROUS                      FRAC. - FRACTURED, FRACTURES                      FRAGS. - FRAGMENTS                      HI. - HIGHLY                      MED. - MEDIUM                      MICA. - MICACEOUS                      MOD. - MODERATELY                      NP - NON PLASTIC                      ORG. - ORGANIC                      PMT - PRESSUREMETER TEST                      SAP. - SAPROLITIC                      SD. - SAND, SANDY                      SL. - SILT, SILTY                      SLI. - SLIGHTLY                      TCR - TRICONE REFUSAL                      w - MOISTURE CONTENT                      V - VERY                      VST - VANE SHEAR TEST                      WEA. - WEATHERED                      W - UNIT WEIGHT                      W<sub>g</sub> - DRY UNIT WEIGHT                      SAMPLE ABBREVIATIONS                      S - BULK                      SS - SPLIT SPOON                      ST - SHELBY TUBE                      RS - ROCK                      RT - RECOMPACTED TRIAXIAL                      CBR - CALIFORNIA BEARING RATIO                 </p>										<p align="center"><b>WEATHERING</b></p> <p>                     FRESH ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING. ROCK RINGS UNDER HAMMER IF CRYSTALLINE.                      VERY SLIGHT (V SLI.) ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN. CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF OF A CRYSTALLINE NATURE.                      SLIGHT (SLI.) ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO 1 INCH. OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR CRYSTALS ARE DULL AND DISCOLORED. CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS.                      MODERATE (MOD.) SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY. ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED WITH FRESH ROCK.                      MODERATELY SEVERE (MOD. SEV.) ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK. ROCK GIVES "CLUNK" SOUND WHEN STRUCK. IF TESTED, WOULD YIELD SPT REFUSAL                      SEVERE (SEV.) ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC CLEAR AND EVIDENT BUT REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN. IF TESTED, WOULD YIELD SPT N VALUES &gt; 100 BPF                      VERY SEVERE (V SEV.) ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC ELEMENTS ARE DISCERNIBLE BUT MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK REMAINING. SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE THAT ONLY MINOR VESTIGES OF ORIGINAL ROCK FABRIC REMAIN. IF TESTED, WOULD YIELD SPT N VALUES &lt; 100 BPF                      COMPLETE ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.                 </p>																																																														
SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION																																																																																													
LL PLASTIC RANGE (PI) PL	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE																																																																																													
	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE																																																																																													
	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE																																																																																													
OM SL	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE																																																																																													
PLASTICITY										EQUIPMENT USED ON SUBJECT PROJECT										MODERATELY SEVERE (MOD. SEV.)																																																																											
<table border="1"> <tr> <th>NON PLASTIC</th> <th colspan="2">PLASTICITY INDEX (PI)</th> <th>DRY STRENGTH</th> </tr> <tr> <td>SIGHTLY PLASTIC</td> <td>0-5</td> <td></td> <td>VERY LOW</td> </tr> <tr> <td>MODERATELY PLASTIC</td> <td>6-15</td> <td></td> <td>SLIGHT</td> </tr> <tr> <td>HIGHLY PLASTIC</td> <td>16-25</td> <td></td> <td>MEDIUM</td> </tr> <tr> <td></td> <td>26 OR MORE</td> <td></td> <td>HIGH</td> </tr> </table>										NON PLASTIC	PLASTICITY INDEX (PI)		DRY STRENGTH	SIGHTLY PLASTIC	0-5		VERY LOW	MODERATELY PLASTIC	6-15		SLIGHT	HIGHLY PLASTIC	16-25		MEDIUM		26 OR MORE		HIGH	<p align="center"><b>EQUIPMENT USED ON SUBJECT PROJECT</b></p> <p>                     DRILL UNITS:  <input type="checkbox"/> CME-45C  <input checked="" type="checkbox"/> CME-55  <input type="checkbox"/> CME-550  <input type="checkbox"/> VANE SHEAR TEST  <input type="checkbox"/> PORTABLE HOIST  <input type="checkbox"/> _____  <input type="checkbox"/> _____                 </p> <p>                     ADVANCING TOOLS:  <input type="checkbox"/> CLAY BITS  <input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER  <input checked="" type="checkbox"/> 8" HOLLOW AUGERS  <input type="checkbox"/> HARD FACED FINGER BITS  <input type="checkbox"/> TUNG-CARBIDE INSERTS  <input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER  <input type="checkbox"/> TRICONE _____ * STEEL TEETH  <input type="checkbox"/> TRICONE _____ * TUNG-CARB.  <input type="checkbox"/> CORE BIT  <input type="checkbox"/> _____                 </p> <p>                     HAMMER TYPE:  <input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL                      CORE SIZE:  <input type="checkbox"/> -B _____ <input type="checkbox"/> -H _____  <input type="checkbox"/> -N _____                      HAND TOOLS:  <input type="checkbox"/> POST HOLE DIGGER  <input type="checkbox"/> HAND AUGER  <input type="checkbox"/> SOUNDING ROD  <input type="checkbox"/> VANE SHEAR TEST  <input type="checkbox"/> _____                 </p>										<p align="center"><b>FRACURE SPACING</b></p> <table border="1"> <tr> <th>TERM</th> <th>SPACING</th> </tr> <tr> <td>VERY WIDE</td> <td>MORE THAN 10 FEET</td> </tr> <tr> <td>WIDE</td> <td>3 TO 10 FEET</td> </tr> <tr> <td>MODERATELY CLOSE</td> <td>1 TO 3 FEET</td> </tr> <tr> <td>CLOSE</td> <td>0.16 TO 1 FOOT</td> </tr> <tr> <td>VERY CLOSE</td> <td>LESS THAN 0.16 FEET</td> </tr> </table>										TERM	SPACING	VERY WIDE	MORE THAN 10 FEET	WIDE	3 TO 10 FEET	MODERATELY CLOSE	1 TO 3 FEET	CLOSE	0.16 TO 1 FOOT	VERY CLOSE	LESS THAN 0.16 FEET	<p align="center"><b>BEDDING</b></p> <table border="1"> <tr> <th>TERM</th> <th>THICKNESS</th> </tr> <tr> <td>VERY THICKLY BEDDED</td> <td>4 FEET</td> </tr> <tr> <td>THICKLY BEDDED</td> <td>1.5 - 4 FEET</td> </tr> <tr> <td>THINLY BEDDED</td> <td>0.16 - 1.5 FEET</td> </tr> <tr> <td>VERY THINLY BEDDED</td> <td>0.03 - 0.16 FEET</td> </tr> <tr> <td>THICKLY LAMINATED</td> <td>0.008 - 0.03 FEET</td> </tr> <tr> <td>THINLY LAMINATED</td> <td>&lt; 0.008 FEET</td> </tr> </table>										TERM	THICKNESS	VERY THICKLY BEDDED	4 FEET	THICKLY BEDDED	1.5 - 4 FEET	THINLY BEDDED	0.16 - 1.5 FEET	VERY THINLY BEDDED	0.03 - 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET	THINLY LAMINATED	< 0.008 FEET										
NON PLASTIC	PLASTICITY INDEX (PI)		DRY STRENGTH																																																																																												
SIGHTLY PLASTIC	0-5		VERY LOW																																																																																												
MODERATELY PLASTIC	6-15		SLIGHT																																																																																												
HIGHLY PLASTIC	16-25		MEDIUM																																																																																												
	26 OR MORE		HIGH																																																																																												
TERM	SPACING																																																																																														
VERY WIDE	MORE THAN 10 FEET																																																																																														
WIDE	3 TO 10 FEET																																																																																														
MODERATELY CLOSE	1 TO 3 FEET																																																																																														
CLOSE	0.16 TO 1 FOOT																																																																																														
VERY CLOSE	LESS THAN 0.16 FEET																																																																																														
TERM	THICKNESS																																																																																														
VERY THICKLY BEDDED	4 FEET																																																																																														
THICKLY BEDDED	1.5 - 4 FEET																																																																																														
THINLY BEDDED	0.16 - 1.5 FEET																																																																																														
VERY THINLY BEDDED	0.03 - 0.16 FEET																																																																																														
THICKLY LAMINATED	0.008 - 0.03 FEET																																																																																														
THINLY LAMINATED	< 0.008 FEET																																																																																														
COLOR										INDURATION										VERY SEVERE (V SEV.)																																																																											
<p>DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-BROWN). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.</p>										<p align="center"><b>INDURATION</b></p> <p>FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.</p> <p>                     FRIABLE RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.                      MODERATELY INDURATED GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.                      INDURATED GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.                      EXTREMELY INDURATED SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.                 </p>										<p align="center"><b>FRACURE SPACING</b></p> <p>                     VERY WIDE MORE THAN 10 FEET                      WIDE 3 TO 10 FEET                      MODERATELY CLOSE 1 TO 3 FEET                      CLOSE 0.16 TO 1 FOOT                      VERY CLOSE LESS THAN 0.16 FEET                 </p>										<p align="center"><b>BEDDING</b></p> <p>                     VERY THICKLY BEDDED 4 FEET                      THICKLY BEDDED 1.5 - 4 FEET                      THINLY BEDDED 0.16 - 1.5 FEET                      VERY THINLY BEDDED 0.03 - 0.16 FEET                      THICKLY LAMINATED 0.008 - 0.03 FEET                      THINLY LAMINATED &lt; 0.008 FEET                 </p>																																																																	
																				BENCH MARK:																																																																											
																				<p>BENCH MARK:                  BORING ELEVATIONS TAKEN FROM I57II.LS.tin_I7I025.tin                  DATED 05/24/18 ELEVATION: FEET</p>																																																																											
																				NOTES:																																																																											
																				<p>FIAD - FILLED IMMEDIATELY AFTER DRILLING</p>																																																																											

I:\Projects\2017\G170566.00 Lochner I-5711 Interchange Improvements\15711\_NCDOT\_Electronic\_File\_Tree\Geotech\InvestigationDesign\15711\_GEO\_RDWY\CADD\_GEO\TECH\PlanProf\I-5711\_GEO\_TSH.dwg  
 09/28/24

**TIP PROJECT: I-5711**

**CONTRACT: 50401**



**25% PLANS**


STATE OF NORTH CAROLINA  
DIVISION OF HIGHWAYS

**ALAMANCE COUNTY**

**LOCATION: INTERCHANGE IMPROVEMENTS AT I-40/I-85  
AND SR 1007 (MEBANE OAKS RD) IN MEBANE**


**TYPE OF WORK: GRADING, DRAINAGE, PAVING, STRUCTURES, SIGNALS AND PAVEMENT MARKINGS**

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	I-5711	2A	33
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
50401.1.FS1	NHPP-040-4(161)220	PE	



PORTIONS OF THIS PROJECT ARE WITHIN THE MUNICIPAL BOUNDARY OF MEBANE.  
CLEARING ON THIS PROJECT SHALL BE PERFORMED TO THE LIMITS ESTABLISHED BY METHOD \_\_\_\_\_

**INCOMPLETE PLANS**  
DO NOT USE FOR R/W ACQUISITION  
DOCUMENT NOT CONSIDERED FINAL  
UNLESS ALL SIGNATURES COMPLETED



**DESIGN DATA**

ADT 2019 =	26,440
ADT 2039 =	30,020
K =	8 %
D =	55 %
T =	3 % *
V =	40 MPH
* TTST =	1 DUAL 2
FUNC CLASS =	MAJOR COLLECTOR
STATEWIDE TIER	STATEWIDE TIER

**PROJECT LENGTH**

TOTAL LENGTH ROADWAY PROJECT	-	0.605 mi
TOTAL LENGTH BRIDGE PROJECT	-	0.042 mi
TOTAL LENGTH PROJECT	-	0.563 mi

Prepared in the Office of:

**LOCHNER**  
H. W. LOCHNER, INC.  
2840 PLAZA PLACE, SUITE 202  
RALEIGH, NC 27612  
(919) 571-7111

2018 STANDARD SPECIFICATIONS

RIGHT OF WAY DATE: **SEPT. 21, 2018**

LETTING DATE: **SEPT. 17, 2019**

**BRIAN K. EASON, PE**  
PROJECT ENGINEER

**JEFFREY HEXT**  
PROJECT DESIGN ENGINEER

NC HIRBA LICENSE No. P-1148  
1151 SE Gary Parkway  
Suite 101  
Cary, NC 27518  
(919) 557-0929


ECOLOGICAL ENGINEERING  
NC License Number: E-0159

**HYDRAULICS ENGINEER**

SIGNATURE: \_\_\_\_\_ P.E.

**ROADWAY DESIGN ENGINEER**

SIGNATURE: \_\_\_\_\_ P.E.





## Roadway Subsurface Investigation Report - Inventory

### Interchange Improvements at I-85/I-40 and SR 1007 (Mebane Oaks Road) in Mebane

Alamance County, North Carolina

WBS: 50401.1.FS1, TIP: I-5711

Falcon Project No.: G17066.00

#### Prepared for:

Lochner  
2840 Plaza Place, Suite 202  
Raleigh, NC 27612

#### Submitted by:

Falcon Engineering, Inc.  
1210 Trinity Road, Suite 110  
Cary, North Carolina 27513  
(919) 871-0800  
www.falconengineers.com

January 11, 2019

**TIP:** I-5711  
**WBS:** 50401.1.FS1  
**COUNTY:** Alamance  
**DESCRIPTION:** Interchange Improvements at I-40/I-85 and SR 1007 (Mebane Oaks Road) in Mebane  
**SUBJECT:** Roadway Subsurface Investigation – Inventory

### PROJECT DESCRIPTION

This project consists of 0.563 miles of proposed roadway improvements along SR 1007 (Mebane Oaks Road) in Alamance County. A portion of SR 1007 will be widened and/or resurfaced near the interchange with I-40/I-85. The project also includes the widening and resurfacing of a portion of I-40/I-85 and Ramp B. Resurfacing and minor modifications to short sections of other various Y-lines, interchange ramps and driveways are also included at various locations. The bridge over I-40/I-85 on SR 1007 will be widened on both sides and will match the current 4 span, 5 bent arrangement of the existing bridge. The structure investigation will be included under separate cover.

The investigation was conducted between June 6<sup>th</sup> and July 5<sup>th</sup>, 2018 in general accordance with our Proposal for Geotechnical Investigation and Engineering Services dated September 13, 2017. The recommendations provided in this report are based solely on our site reconnaissance, soil and pavement test borings laboratory test data, engineering evaluation of these data, and generally accepted soil and foundation engineering practices and principles.

A total of nineteen (19) Standard Penetration Test (SPT) were drilled for the proposed roadway alignments. All mechanical borings were drilled using a CME 55 ATV mounted drill rig equipped with 2 1/4-inch inside diameter hollow-stem augers, and SPT testing was performed with automatic hammers. Representative soil samples, collected with a split-barrel sampler or hand auger, were selected for laboratory testing to verify visual field classifications. In addition, bulk samples were collected for standard Proctor compaction and California Bearing Ratio (CBR) testing. At seventeen (17) locations along the existing roadway, existing pavements were cored, measured and Dual Mass Dynamic Cone Penetrometer (DCP) testing completed on the subgrade to correlate in-situ CBR values to depths of up to three feet below subgrade. The dual mass DCP used is manufactured by Kessler Soils Engineering Products, Inc. CBR values were estimated using software provided by the manufacturer which utilizes correlations established by the Army Corps of Engineers Waterways Experiment Station. The pavement investigation will be included under separate cover.





Portions of the following alignments, totaling approximately 0.86 miles were investigated. Other minor Y-lines, ramps and driveways are included on the project but improvements are not anticipated to be significant enough to warrant investigation.

<u>Alignment</u>	<u>Station (ft)</u>
-L- (Mebane Oaks Road)	18+04—50+00
-RPA_Y1- (Ramp A)	12+50—15+43
-RPB_Y1- (Ramp A)	10+75—21+28

## AREAS OF SPECIAL GEOTECHNICAL INTEREST

- I. The following locations contain very soft to soft or very loose soils with an N-value less than 4 near the ground surface:

<u>Alignment</u>	<u>Station (ft)</u>
-L-	30+89, RT
-RPA_Y1-	12+88, RT

- II. The following locations contain highly plastic soils with plasticity indices (PI) greater than 25 within 3 feet of proposed subgrade elevations:

<u>Alignment</u>	<u>Station (ft)</u>
-L-	43+12, LT

## PHYSIOGRAPHY AND GEOLOGY

The project site is in the Piedmont Physiographic Province of North Carolina. According to the *Geologic Map of North Carolina* (1985), the site is underlain by two major geologic units in the Carolina Slate Belt. The site transitions from north to south across Intermediate Metavolcanic Rock (**CZiv**) to Felsic Metavolcanic Rock (**CZfv**).

The Intermediate Metavolcanic Rock (**CZiv**) consists of metamorphosed andesitic tuffs and flows, medium to dark grayish green; minor felsic and mafic metavolcanic rock. The Felsic Metavolcanic Rock (**CZfv**) consists of metamorphosed dacitic to rhyolitic flows and tuffs, light gray to greenish gray, interbedded with mafic and intermediate metavolcanic rock, meta-argillite, and metamudstone.

The corridor is highly developed with commercial properties north of I-40/I-85 and both commercial and residential properties to the south of the interchange. The site generally slopes down from north to south, elevating in the center to cross over I-40/I-85. Vegetation along the corridor consists largely of roadside grasses with intermittent landscaping, heavy and unmaintained brush, and in some locations mature forested lands or landscaped lawns. Surrounding land throughout the corridor is highly developed. Drainage along the roadways and developed properties is facilitated by a mixture of confined systems and roadside swales and ditches which direct drainage outside of the project limits. No standing water or natural drainage features were noted within the project limits.





## SOIL PROPERTIES

A variety of soils were encountered along the project, including existing roadway embankments and residual soils and weathered and crystalline rock.

Topsoil was encountered in grassy areas ranging in thickness from 0.1 to 0.3 feet, and typically on the order of 0.2 feet.

Roadway Embankment soils were encountered at the ground surface beneath and adjacent to existing roadways. These soils consist of up to 8 feet of dry to moist, very loose to medium dense, silty sand (A-2-4) and very soft to stiff, sandy and silty clay and clayey silt (A-5, A-6, A-7). Tested samples have a PI value range from 13 to 25.

Residual soils were encountered at the ground surface or beneath the roadway embankment fills. These soils consist of dry to wet, soft to hard, sandy and silty clay and clayey silt (A-5, A-6, A-7). Tested samples have a PI value range from 5 to 45.

Weathered Rock (WR) is a very hard material with properties intermediate of soil and rock. WR is classified as having an N-value of greater than 100 blows per foot. WR encountered on this project generally consists of tan and white Metavolcanic Rock. WR was encountered from elevation 623.6 ft to 662.4 ft.

Crystalline Rock, in the form of Metavolcanic Rock was encountered beneath weathered rock at various locations throughout the site. Crystalline rock is classified as material that yields auger refusal or SPT refusal (blow count of 60/0.0 or 60/0.1 feet). CR was encountered from elevation 609.5 ft to 629.2 ft.

## GROUNDWATER PROPERTIES

Groundwater levels were measured at the time of boring completion, and in many cases after a waiting period of at least 24 hours. Borings drilled within and in close proximity to existing roadways, and within residential or commercial areas were backfilled immediately after completion due to safety considerations.

Shallow groundwater was not encountered in the areas explored.

## ADDITIONAL LABORATORY TESTING

The following bulk samples were obtained:

Sample	Location	Depth (ft)	Test
BS-1	43+12, 63' LT, -L-	1.0 – 5.0	California Bearing Ratio, Standard Proctor
BS-2	17+21, 68'LT, -RPB_Y1-	1.0 – 5.0	California Bearing Ratio, Standard Proctor

Classification test results for bulk samples are included in the subsurface profiles and cross sections and Standard Proctor and California Bearing Ratio (CBR) data is attached in the Appendix.

## CLOSING

Falcon appreciates the opportunity to have provided our geotechnical engineering services for the above referenced project. If you have any questions concerning the contents of this report or need additional information, please do not hesitate to contact our office.

### FALCON ENGINEERING, INC.

Report Prepared By:

Report Reviewed By:



*W. Scott Hunsberger*

5A469AC80FCD49E...  
1/11/2019

W. Scott Hunsberger, PE  
Geotechnical Engineer

Jeremy R. Hamm, PE  
Geotechnical Engineering Manager













# LOCHNER


H. W. LOCHNER, INC.  
2840 PLAZA PLACE, SUITE 202  
RALEIGH, NC 27612  
(919) 571-7111



NC License Number F-0159  
NC FIRM LICENSE No. F-1148  
1151 SE Cary Parkway  
Suite 101  
Cary, NC 27518  
(919) 557-0929

PROJECT REFERENCE NO. <b>1-5711</b>	SHEET NO. <b>8</b>
R/W SHEET NO.	HYDRAULICS ENGINEER
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
<b>INCOMPLETE PLANS</b> DO NOT USE FOR A/W ACQUISITION	
<b>DOCUMENT NOT CONSIDERED FINAL</b> UNLESS ALL SIGNATURES COMPLETED	

## NO BORINGS ON THIS SHEET



MATCHLINE TO SHEET 5  
-RPA YI- STA. 10+00.00

MATCHLINE TO SHEET 5  
-YI- STA. 31+00.00

MATCHLINE TO SHEET 5  
-RPD YI- STA. 11+00.00

SEE SHEET 12 FOR -YI- PROFILE

REVISIONS  
 10-JAN-2018 09:54  
 I:\Projects\17\617066.00 Lochner 1-5711\Infrchange\_Improvements\15711.NCDDT\_Electromc.File\_Tree\Geotech\InvestigationDesign\15711.GEO\_RDWY\CADD\_GEO\TechPlan\Prof\1-5711\_GEO\_PSH\_08.dgn  
 8/17/99

I:\JAN-2018 09:55  
 I:\Projects\17\017066.00 Lochner 1-5711 Interchange Improvements\15711.NCDDT\_Electronic\_File\_Tree\Geotech\InvestigationDesign\15711.GEO\_RDWY\CADD\_GEO\TECH\Plan\Prof\1-5711\_GEO\_PFL\_09.dgn  
 5/28/9c

-L-  
MEBANE OAKS RD.

**LOCHNER**  
 H. W. LOCHNER, INC.  
 2840 PLAZA PLACE, SUITE 202  
 RALEIGH, NC 27612  
 (919) 571-7111

NC License Number F-0152  
 NC FIRM LICENSE No. 15-1148  
 1151 SE Cary Parkway  
 Suite 101  
 Cary, NC 27518  
 (919) 557-0929


**ECOLOGICAL ENGINEERING**

PROJECT REFERENCE NO. 1-5711	SHEET NO. 9
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
<b>INCOMPLETE PLANS</b> DO NOT USE FOR R/W ACQUISITION	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

BM#4  
 -L- STA 14+33.18  
 65.34 RIGHT  
 ELEV 673.90'

**SOIL TEST RESULTS**

SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-1	54 FT RT	20+08	1.0'-2.5'	A-7-6	46	13	7	8	30	55	96	91	81	21.8	-




-L-  
MEBANE OAKS RD.

- Ⓐ ROADWAY EMBANKMENT: RED, MOIST, V. LOOSE TO MED. DENSE; SILTY SAND WITH TRACE GRAVEL
- Ⓑ ROADWAY EMBANKMENT: RED, BROWN, AND TAN, MOIST, MED. STIFF TO HARD, SILTY CLAY WITH TRACE GRAVEL
- Ⓓ WEATHERED ROCK: TAN, METAVOLCANIC ROCK

**SOIL TEST RESULTS**


SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-2	84 FT LT	22+99	1.0'-2.5'	A-7-5	45	14	7	5	37	51	97	92	85	18.0	-
SS-3	75 FT LT	25+50	1.0'-2.5'	A-7-6	41	13	7	7	31	55	92	87	78	25.3	-
SS-4	59 FT LT	29+00	1.0'-2.5'	A-7-5	58	25	5	3	35	57	84	80	76	16.1	-
SS-5	43 FT RT	30+89	1.0'-2.5'	A-2-4	35	13	54	6	30	10	50	41	32	8.7	-
SS-6	50 FT LT	33+00	1.0'-2.5'	A-7-5	54	20	15	5	25	55	93	87	80	24.1	-
SS-7	60 FT RT	34+97	1.0'-2.5'	A-7-5	66	14	9	8	28	55	99	93	82	39.0	-




5/28/9c  
 I:\JAN-2018 0955  
 I:\P\15711\15711-017066.00 Lochner I-5711 Interchange Improvements\15711.NCDDT\_Electronic\_File\_Tree\Geotech\InvestigationDesign\15711\_GEO\_RDWY\CADD\_GEO\TECH\Plan\Prof\1-5711\_GEO\_PFL\_10.dgn  
 10/10/2018 10:00 AM

**LOCHNER**  
 H. W. LOCHNER, INC.  
 2840 PLAZA PLACE, SUITE 202  
 RALEIGH, NC 27612  
 (919) 571-7111  
 NC License Number F-0152  
 NC FIRM LICENSE No. 1348  
 1151 SE Cary Parkway  
 Suite 101  
 Cary, NC 27518  
 (919) 557-0929  
**ECOLOGICAL ENGINEERING**


PROJECT REFERENCE NO. 1-5711	SHEET NO. 10
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
<b>INCOMPLETE PLANS</b> DO NOT USE FOR R/W ACQUISITION	
<b>DOCUMENT NOT CONSIDERED FINAL</b> UNLESS ALL SIGNATURES COMPLETED	



SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-8	45 FT LT	36+99	1.0'-2.5'	A-7-6	46	17	7	3	40	50	97	93	87	18.9	-
SS-9	45 FT LT	36+99	3.5'-5.0'	A-7-5	67	23	2	4	42	52	100	99	95	30.1	-
SS-11	40 FT LT	41+00	1.0'-2.5'	A-7-5	58	23	2	1	37	60	100	99	97	26.5	-
SS-12	40 FT LT	41+00	3.5'-5.0'	A-7-5	58	21	1	2	30	67	100	99	97	31.9	-
SS-13	63 FT LT	43+12	1.0'-2.5'	A-7-5	94	45	1	2	29	68	100	100	97	35.5	-
S-1	63 FT LT	43+12	1.0'-5.0'	A-7-5	65	25	2	3	37	58	99	98	94	40.5	-
SS-14	30 FT LT	45+29	1.0'-2.5'	A-6	34	12	5	4	41	50	97	93	89	15.1	-
SS-15	35 FT LT	47+00	1.0'-2.5'	A-7-6	43	16	3	3	36	58	99	97	93	25.4	-
SS-16	30 FT LT	49+00	1.0'-2.5'	A-4	32	10	8	2	63	27	96	90	86	21.9	-



SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-19	64 FT RT	12+88	1.0'-2.5'	A-7-5	49	19	5	2	31	62	89	85	82	26.6	-
SS-20	64 FT RT	12+88	3.5'-5.0'	A-6	38	12	5	4	38	53	97	93	88	34.2	-



I:\Projects\2018\09\56\1-5711\Interchange\_Improvements\15711\_NCDOT\_Electronic\_File\_Tree\Geotech\InvestigationDesign\15711\_GEO\_RDWY\CADD\_GEO\TECH\Plan\1-5711\_GEO\_PFL\_11.dgn  
 5/28/2018  
 I:\Projects\2018\09\56\1-5711\Interchange\_Improvements\15711\_NCDOT\_Electronic\_File\_Tree\Geotech\InvestigationDesign\15711\_GEO\_RDWY\CADD\_GEO\TECH\Plan\1-5711\_GEO\_PFL\_11.dgn  
 5/28/2018

### -RPB\_Y1-


**LOCHNER**  
 H. W. LOCHNER, INC.  
 2840 PLAZA PLACE, SUITE 202  
 RALEIGH, NC 27612  
 (919) 571-7111

NC License Number F-0152  
 NC FIRM LICENSE No: F-1148  
 1151 SE Cary Parkway  
 Suite 101  
 Cary, NC 27518  
 (919) 557-0929

**ECOLOGICAL ENGINEERING**

PROJECT REFERENCE NO. 1-5711	SHEET NO. 11
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
<b>INCOMPLETE PLANS</b> DO NOT USE FOR R/W ACQUISITION	
<b>DOCUMENT NOT CONSIDERED FINAL</b> UNLESS ALL SIGNATURES COMPLETED	


SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-21	65 FT LT	13+02	1.0'-2.5'	A-4	29	7	5	3	32	40	69	65	61	8.3	-
SS-22	65 FT LT	13+02	3.5'-5.0'	A-7-5	57	18	3	9	33	55	100	98	88	30.6	-
SS-23	68 FT LT	14+96	1.0'-2.5'	A-4	30	7	5	2	58	35	80	76	73	16.5	-
S-2	68 FT LT	17+21	1.0'-5.0'	A-4	22	5	22	8	49	21	84	67	54	10.7	-
SS-24	72 FT LT	19+02	1.0'-2.5'	A-4	40	10	13	6	49	32	93	83	74	20.3	-



SEE SHEETS 5 & 7 FOR -RPB\_Y1- PLAN VIEW

### -RPD\_Y1-

NO BORINGS ON THIS SHEET




SEE SHEET 5 FOR -RPD\_Y1- PLAN VIEW

### -Y2-

SR 2210 FOREST OAKS LN.

NO BORINGS ON THIS SHEET




SEE SHEET 5 FOR -Y2- PLAN VIEW

### -Y3-

SR 2186 BRUNDAGE LN.

NO BORINGS ON THIS SHEET



SEE SHEET 5 FOR -Y3- PLAN VIEW



5/28/9c  
I:\Projects\2018\0956\1-5711 Interchange Improvements\15711.NCDDT\_Electronic\_File\_Tree\Geotech\InvestigationDesign\15711.GEO\_RDWY\CADD\_GEO\TECH\Plan\Prof\1-5711\_GEO\_PFL\_12.dgn  
10-JAN-2018 09:56  
1-5711 Interchange Improvements\15711.NCDDT\_Electronic\_File\_Tree\Geotech\InvestigationDesign\15711.GEO\_RDWY\CADD\_GEO\TECH\Plan\Prof\1-5711\_GEO\_PFL\_12.dgn

**LOCHNER**  
 H. W. LOCHNER, INC.  
 2840 PLAZA PLACE, SUITE 202  
 RALEIGH, NC 27612  
 (919) 571-7111

NC License Number F-0152  
 NC FIRM LICENSE No. F-1148  
 1151 SE Cary Parkway  
 Suite 101  
 Cary, NC 27518  
 (919) 557-0929

**ECOLOGICAL ENGINEERING**


PROJECT REFERENCE NO. I-5711	SHEET NO. 12
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
<b>INCOMPLETE PLANS</b> DO NOT USE FOR R/W ACQUISITION	
<b>DOCUMENT NOT CONSIDERED FINAL</b> UNLESS ALL SIGNATURES COMPLETED	



6/23/16  
I:\Projects\2017\US\7066.00\Lochner\1-5711 Interchange Improvements\15711\_NCDOT\_Electromc\_File\_Tree\Geotech\InvestigationDesign\15711\_GEO\_RDWY\CADD\_GEO\TECH\SSC\1-5711\_GEO.XSL.L.dgn

**INCOMPLETE PLANS**  
DO NOT USE FOR R/W ACQUISITION  
**DOCUMENT NOT CONSIDERED FINAL**  
UNLESS ALL SIGNATURES COMPLETED

SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-1	54 FT RT	20+08	10'-2.5'	A-7-6	46	13	7	8	30	55	96	91	81	21.8	-




-L-






SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-2	84 FT LT	22+99	1.0'-2.5'	A-7-5	45	14	7	5	37	51	97	92	85	18.0	-



I:\JAN-2019 09:16  
 I:\Projects\2017\US\7066.00 Lochner I-5711 Interchange Improvements\15711-NCDDT-Electronic-File-Tree\Geotech\InvestigationDesign\15711-GEO-RDWAY\CADD\_GEO\TECH\SSC\1-5711-GEO.XSL.L.dgn  
 6/23/16

-L-

SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-3	75 FT LT	25+50	10'-2.5'	A-7-6	41	13	7	7	31	55	92	87	78	25.3	-



25 + 50.00


-L-

I:\JAN-2019 09:17  
 I:\Projects\2017\US\7066.00 Lochner I-5711 Interchange Improvements\15711-NCDDT-Electromc-File-Tree\Geotech\InvestigationDesign\15711-GEO-RDWAY\CADD-GEO\TECH\SSC\1-5711-GEO.XSL.L.dgn  
 6/23/16  
 11-5711 Interchange Improvements\15711-NCDDT-Electromc-File-Tree\Geotech\InvestigationDesign\15711-GEO-RDWAY\CADD-GEO\TECH\SSC\1-5711-GEO.XSL.L.dgn



150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-4	59 FT LT	29+00	1.0'-2.5'	A-7-5	58	25	5	3	35	57	84	80	76	16.1	-



29 + 00.00




150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

6/23/16  
I:\JAN-2019 09:17  
I:\Projects\2017\US\7066.00 Lochner I-5711 Interchange Improvements\15711-NCDDT-Electromc-File-Tree\Geotech\InvestigationDesign\15711-GEO-RDWAY\CADD-GEO\TECH\SSC\1-5711-GEO.XSL.L.dgn  
cadd\line


150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-5	43 FT RT	30+89	1.0'-2.5'	A-2-4	35	13	54	6	30	10	50	41	32	8.7	-




-L-

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150



SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-7	60 FT RT	34+97	1.0'-2.5'	A-7-5	66	14	9	8	28	55	99	93	82	39.0	-




**RESIDUAL:**  
BROWN TAN AND RED.  
MOIST. MED. STIFF. TO STIFF.  
SILTY CLAY AND CLAYEY SILT

**RESIDUAL:**  
BROWN TAN AND RED.  
MOIST. MED. STIFF. TO STIFF.  
SILTY CLAY AND CLAYEY SILT

35 + 00.00

SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-6	50 FT LT	33+00	1.0'-2.5'	A-7-5	54	20	15	5	25	55	93	87	80	24.1	-



**ROADWAY EMBANKMENT:**  
RED. AND BROWN. MOIST.  
MED. STIFF. TO STIFF.  
SILTY CLAY

**ROADWAY EMBANKMENT:**  
RED. AND BROWN. MOIST.  
MED. STIFF. TO STIFF. SILTY CLAY


**RESIDUAL:**  
RED. MOIST. STIFF.  
SILTY CLAY

**RESIDUAL:**  
RED. MOIST. STIFF.  
SILTY CLAY

33 + 00.00


-L-

I:\JAN-2019 09:18 I:\Projects\2017\US7066.00 Lochner I-5711 Interchange Improvements\15711\_NCDOT\_Electromc\_File\_Tree\Geotech\InvestigationDesign\15711\_GEO\_RDWY\CADD\_GEO\TECH\SSC\1-5711\_GEO\_XSL.L.dgn



150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150


SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-8	45 FT LT	36+99	1.0'-2.5'	A-7-6	46	17	7	3	40	50	97	93	87	18.9	-
SS-9	45 FT LT	36+99	3.5'-5.0'	A-7-5	67	23	2	4	42	52	100	99	95	30.1	-




37 + 00.00

I:\JAN-2019 09:18  
 I:\Projects\2017\US\7066.00 Lochner I-5711 Interchange Improvements\15711-NCDDT-Electromc-File-Tree\Geotech\InvestigationDesign\15711-GEO-RDWAY\CADD-GEO\TECH\SSC\I-5711-GEO.XSL.L.dgn  
 6/23/16  
 cadmachine AI CAD01

6/23/16




PROJ. REFERENCE NO.	SHEET NO.
I-5711	20



**ROADWAY EMBANKMENT: RED AND TAN, MOIST, STIFF, SILTY CLAY**

**RESIDUAL: TAN AND WHITE, MOIST, V. STIFF, CLAYEY SILT**


41 + 50.00




I:\JAN-2019 09:18  
I:\Projects\2017\US7066.00 Lochner I-5711 Interchange Improvements\15711-NCDDT-Electronic-File-Tree\Geotech\InvestigationDesign\15711-GEO-RDWAY\CADD-GEO\TECH\XSEC\I-5711-GEO.XSL.L.dgn  
cadd\cadd



I:\JAN-2019 09:18  
 I:\Projects\2017\US7066.00 Lochner I-5711 Interchange Improvements\15711\_NCDOT\_Electronic\_File\_Tree\Geotech\InvestigationDesign\15711\_GEO\_RDMY\CADD\_GEO\TECH\SSC\1-5711\_GEO.XSL.L.dgn  
 6/23/16  
 cadmachine



SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-13	63 FT LT	43+12	1.0'-2.5'	A-7-5	94	45	1	2	29	68	100	100	97	35.5	-
S-1	63 FT LT	43+12	1.0'-5.0'	A-7-5	65	25	2	3	37	58	99	98	94	40.5	-






6/23/16  
I:\JAN-2019 09:19  
I:\Projects\2017\07\066.00 Lochner I-5711 Interchange Improvements\15711\_NCDOT\_Electromc\_File\_Tree\Geotech\InvestigationDesign\15711\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\I-5711\_GEO.XSL.L.dgn  
cadd\ch\ne




PROJ. REFERENCE NO.	SHEET NO.
I-5711	22



6/23/16

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-19	64 FT RT	12+88	1.0'-2.5'	A-7-5	49	19	5	2	31	62	89	85	82	26.6	-
SS-20	64 FT RT	12+88	3.5'-5.0'	A-6	38	12	5	4	38	53	97	93	88	34.2	-



13 + 00.00

-RPA\_YI-


150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

I:\Projects\2017\07066\00 Lochner I-5711 Interchange Improvements\15711\_NCDOT\_Electronic\_File\_Tree\Geotech\InvestigationDesign\15711\_GEO\_RDWY\CADD\_GEO\TECH\15711\_GEO\_XPL\_RPA\_YI.dgn



150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-21	65 FT LT	13+02	1.0'-2.5'	A-4	29	7	5	3	52	40	69	65	61	8.3	-
SS-22	65 FT LT	13+02	3.5'-5.0'	A-7-5	57	18	3	9	33	55	100	98	88	30.6	-



RESIDUAL  
TAN MOIST MED. STIFF TO V. STIFF  
SANDY SILT AND SILTY CLAY WITH  
TRACE ROCK FRAGMENTS


RESIDUAL  
TAN MOIST MED. STIFF TO V. STIFF  
SANDY SILT AND SILTY CLAY WITH  
TRACE ROCK FRAGMENTS

BT  
DRY (06/18)

13 + 00.00  
-RPB\_YI-


150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

I:\Projects\2017\SI\7066.00 Lochner I-5711 Interchange Improvements\15711\_NCDOT\_Electronic\_File\_Tree\Geotech\InvestigationDesign\15711\_GEO\_RDMY\CADD\_GEO\TECH\SSC\1-5711\_GEO\_XPL\_RPB\_YI.dgn  
 6/23/16  
 10-JAN-2019 11:39  
 cadmachine AI CAD01



150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150


SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-23	68 FT LT	14+96	1.0'-2.5'	A-4	30	7	5	2	58	35	80	76	73	16.5	-



15 + 00.00

-RPB\_YI-


I:\Projects\2017\07066\00 Lochner I-5711 Interchange Improvements\15711\_NCDOT\_Electromc\_File\_Tree\Geotech\InvestigationDesign\15711\_GEO\_RDWY\CADD\_GEO\TECH\SSC\1-5711\_GEO\_XPL\_RPB\_YI.dgn  
 6/23/16  
 10-JAN-2019 11:39  
 I:\Projects\2017\07066\00 Lochner I-5711 Interchange Improvements\15711\_NCDOT\_Electromc\_File\_Tree\Geotech\InvestigationDesign\15711\_GEO\_RDWY\CADD\_GEO\TECH\SSC\1-5711\_GEO\_XPL\_RPB\_YI.dgn  
 cadmachine AI CAD01



150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

I:\Projects\2017\07066\00 Lochner I-5711 Interchange Improvements\15711\_NCDOT\_Electronic\_File\_Tree\Geotech\InvestigationDesign\15711\_GEO\_RDMY\CADD\_GEO\TECH\XSEC\I-5711\_GEO\_XPL\_RPB\_YI.dgn  
 6/23/16  
 10-JAN-2019 11:39  
 I:\Projects\2017\07066\00 Lochner I-5711 Interchange Improvements\15711\_NCDOT\_Electronic\_File\_Tree\Geotech\InvestigationDesign\15711\_GEO\_RDMY\CADD\_GEO\TECH\XSEC\I-5711\_GEO\_XPL\_RPB\_YI.dgn  
 cadmachine AI CAD01

SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
S-2	68 FT LT	17+21	1.0'-5.0'	A-4	22	5	22	8	49	21	84	67	54	10.7	-



17 + 00.00

-RPB\_YI-

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

6/23/16




PROJ. REFERENCE NO.  
I-5711

SHEET NO.  
27

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-24	72 FT LT	19+02	1.0'-2.5'	A-4	40	10	13	6	49	32	93	83	74	20.3	-



19 + 00.00

-RPB\_YI-

I:\Projects\2017\07066\00 Lochner I-5711 Interchange Improvements\15711\_NCDOT\_Electromc\_File\_Tree\Geotech\InvestigationDesign\15711\_GEO\_RDWY\CADD\_GEO\TECH\SSC\1-5711\_GEO\_XPL\_RPB\_YI.dgn  
10-JAN-2019 11:40  
caddmachine

*NORTH CAROLINA DEPARTMENT OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
GEOTECHNICAL ENGINEERING UNIT*

---

***SUBSURFACE INVESTIGATION***

---

*APPENDIX A  
LABORATORY RESULTS*

*REFERENCE: I-5711*

*PROJECT: 50401*



FALCON ENGINEERING, INC.  
1210 TRINITY ROAD, SUITE 110  
CARY, NC 27513  
PHONE: 919.871.0800  
www.falconengineers.com

**FALCON ENGINEERING**

1210 TRINITY RD., SUITE 110, Cary, NC 27513

**CBR (CALIFORNIA BEARING RATIO) OF LABORATORY COMPACTED SOIL**

**AASHTO T-193**



PROJECT #: **G17066.00** DATE: **9/16/2018**  
PROJECT NAME: **I-5711 Interchange Improvement**  
BORING: **B-11** SAMPLE: **BS-1** DEPTH: **1-5'**

SOIL DESCRIPTION: <b>A-7-5 Clay</b>			
COMPACTION METHOD	AASHTO T-99A	SOAK	96 HRS.
MAXIMUM DRY DENSITY	82.5 PCF	STRAIN RATE	.05 IN / MIN.
OPTIMUM MOISTURE CONTENT	34.0%	LOAD CELL	6000
TEST DATA		SURCHARGE WEIGHT	
DRY DENSITY	80.4 PCF	SURCHARGE PER SQUARE FOOT	51 lbs/sq.ft.
MOISTURE CONTENT	35.0%	FINAL MOISTURE CONTENT	N/A
PERCENT COMPACTION	97.5%	SWELL	4.38%

Project No: **G17066.00**  
Project Name: **I-5711 Interchange Improvements**  
Sample No: **BS-1**  
Source of Material: **B-11**  
Visual/Manual Description: **A-7-5**  
USCS Classification: \_\_\_\_\_  
AASHTO Classification: \_\_\_\_\_  
Test Method: **AASHTO T-99**

TEST RESULTS  
Maximum Dry Unit Weight: **82.5 PCF**  
Optimum Water Content: **34.0 %**

ATTERBERG LIMITS  
LL **65** PL **40** PI **25**  
Curves of 100% Saturation for Specific Gravity Equal to:  
— 2.6  
- - - 2.5  
... 2.4



01A COMPACTION G17066.LAB.GPJ FALCON\_FORMAT.GDT 9/17/18





FALCON ENGINEERING, INC.  
1210 TRINITY ROAD, SUITE 110  
CARY, NC 27513

PHONE: 919.871.0800  
www.falconengineers.com

**FALCON ENGINEERING**

1210 TRINITY RD., SUITE 110, Cary, NC 27513

**CBR (CALIFORNIA BEARING RATIO) OF LABORATORY COMPACTED SOIL**

AASHTO T-193

PROJECT #:	G17066.00	DATE:	9/16/2018
PROJECT NAME:	I-5711 Interchange Improvement		
BORING:	RPB-3	SAMPLE:	BS-2
		DEPTH:	1-5'

SOIL DESCRIPTION: <b>A-4 Silt</b>			
COMPACTION METHOD	AASHTO T-99A	SOAK	96 HRS.
MAXIMUM DRY DENSITY	116.0 PCF	STRAIN RATE	.05 IN / MIN.
OPTIMUM MOISTURE CONTENT	15.2%	LOAD CELL	6000
TEST DATA		SURCHARGE WEIGHT	
DRY DENSITY	114.2 PCF	SURCHARGE PER SQUARE FOOT	51 lbs/sq.ft.
MOISTURE CONTENT	14.5%	FINAL MOISTURE CONTENT	N/A
PERCENT COMPACTION	98.4%	SWELL	2.08%

Project No: G17066.00  
 Project Name: I-5711 Interchange Improvements  
 Sample No: BS-2  
 Source of Material: RPB-3  
 Visual/Manual Description: A-4  
 USCS Classification: \_\_\_\_\_  
 AASHTO Classification: \_\_\_\_\_  
 Test Method: AASHTO T-99

TEST RESULTS  
 Maximum Dry Unit Weight: 116.0 PCF  
 Optimum Water Content: 15.3 %

ATTERBERG LIMITS  

LL	PL	PI
22	17	5

Curves of 100% Saturation  
for Specific Gravity Equal to:  
 — 2.8  
 - - - 2.7  
 ····· 2.6

