

PROJECT: 50401.1.FSI REFERENCE: I-5711

**STATE OF NORTH CAROLINA**  
**DEPARTMENT OF TRANSPORTATION**  
**DIVISION OF HIGHWAYS**  
**GEOTECHNICAL ENGINEERING UNIT**

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	I-5711	1	4

**CONTENTS**

<u>SHEET NO.</u>	<u>DESCRIPTION</u>
1	TITLE SHEET
2	LEGEND
3	MSE WALL PLAN AND SUBSURFACE PROFILE
4	BORE LOGS

**STRUCTURE**  
**SUBSURFACE INVESTIGATION**

COUNTY ALAMANCE  
PROJECT DESCRIPTION INTERCHANGE IMPROVEMENTS  
AT I-40/I-85 AND SR 1007 (MEBANE OAKS ROAD)  


---

SITE DESCRIPTION RETAINING WALL NO.1 (-WALL-)  
-L- STA. 34+82.39, 72.38' RT TO  
-L- STA. 36+04.76, 94.03' RT

**CAUTION NOTICE**

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT (919) 707-6850. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

- NOTES:
1. THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.
  2. BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

PERSONNEL  
**CAROLINA DRILLING**  
PAUL, A. S.

INVESTIGATED BY PAUL, A. S.  
DRAWN BY CROCKETT, S. C.  
CHECKED BY HAMM, J. R.  
SUBMITTED BY FALCON ENG.  
DATE JUNE 2019



DocuSigned by:  
Jeremy R Hamm 6/27/2019  
ED7938089E22487...  
SIGNATURE DATE

**DOCUMENT NOT CONSIDERED FINAL  
UNLESS ALL SIGNATURES COMPLETED**

**NORTH CAROLINA DEPARTMENT OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
GEOTECHNICAL ENGINEERING UNIT  
SUBSURFACE INVESTIGATION  
SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS**

SOIL DESCRIPTION										GRADATION										ROCK DESCRIPTION										TERMS AND DEFINITIONS																																																																																																																																																																											
<p>SOIL IS CONSIDERED UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER AND YIELD LESS THAN 100 BLOWS PER FOOT ACCORDING TO THE STANDARD PENETRATION TEST (AASHTO T 206, ASTM D1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY INCLUDE THE FOLLOWING: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. FOR EXAMPLE, <i>VERY STIFF, GRAY, SILTY CLAY, MOIST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC, A-7-6</i></p>																																								<p><b>WELL GRADED</b> - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE.  <b>UNIFORMLY GRADED</b> - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE.  <b>GAP-GRADED</b> - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES.</p>																																								<p>HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED, AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS IN NON-COASTAL PLAIN MATERIAL. THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:</p>																																								<p><b>ALLUVIUM (ALLUV.)</b> - SOILS THAT HAVE BEEN TRANSPORTED BY WATER.  <b>AQUIFER</b> - A WATER BEARING FORMATION OR STRATA.  <b>ARENACEOUS</b> - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND.  <b>ARGILLACEOUS</b> - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC.  <b>ARTESIAN</b> - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE.  <b>CALCAREOUS (CALC.)</b> - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE.  <b>COLLUVIUM</b> - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE.  <b>CORE RECOVERY (REC.)</b> - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.  <b>DIKE</b> - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK.  <b>DIP</b> - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL.  <b>DIP DIRECTION (DIP AZIMUTH)</b> - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH.  <b>FAULT</b> - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE.  <b>FISSILE</b> - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES.  <b>FLOAT</b> - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLOGGED FROM PARENT MATERIAL.  <b>FLOOD PLAIN (FP)</b> - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM.  <b>FORMATION (FM)</b> - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD.  <b>JOINT</b> - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED.  <b>LEDGE</b> - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT.  <b>LENS</b> - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS.  <b>MOTTLED (MOT.)</b> - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS, MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE.  <b>PERCHED WATER</b> - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM.  <b>RESIDUAL (RES.) SOIL</b> - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK.  <b>ROCK QUALITY DESIGNATION (ROD)</b> - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.  <b>SAPROLITE (SAP.)</b> - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK.  <b>SILL</b> - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS.  <b>SLICKENSIDE</b> - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE.  <b>STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT)</b> - NUMBER OF BLOWS (N OR BPF) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS.  <b>STRATA CORE RECOVERY (SREC.)</b> - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE.  <b>STRATA ROCK QUALITY DESIGNATION (SROD)</b> - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE.  <b>TOPSOIL (TS.)</b> - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.</p>																																																																																	
<b>SOIL LEGEND AND AASHTO CLASSIFICATION</b>																																								<b>ANGULARITY OF GRAINS</b>																																								<b>WEATHERED ROCK (WR)</b>																																								<b>NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT N VALUES &gt; 100 BLOWS PER FOOT IF TESTED.</b>																																																																																	
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>GENERAL CLASS.</th> <th colspan="5">GRANULAR MATERIALS (≤ 35% PASSING #200)</th> <th colspan="5">SILT-CLAY MATERIALS (&gt; 35% PASSING #200)</th> <th colspan="5">ORGANIC MATERIALS</th> </tr> <tr> <td>GROUP CLASS.</td> <td>A-1</td><td>A-3</td><td>A-2</td><td>A-2-4</td><td>A-2-5</td><td>A-2-6</td><td>A-2-7</td> <td>A-4</td><td>A-5</td><td>A-6</td><td>A-7</td> <td>A-1, A-2</td><td>A-3</td><td>A-4, A-5</td><td>A-6, A-7</td> </tr> <tr> <td>SYMBOL</td> <td colspan="5">[Pattern]</td> <td colspan="5">[Pattern]</td> <td colspan="5">[Pattern]</td> </tr> </table>										GENERAL CLASS.	GRANULAR MATERIALS (≤ 35% PASSING #200)					SILT-CLAY MATERIALS (> 35% PASSING #200)					ORGANIC MATERIALS					GROUP CLASS.	A-1	A-3	A-2	A-2-4	A-2-5	A-2-6	A-2-7	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7	SYMBOL	[Pattern]					[Pattern]					[Pattern]					<b>MINERALOGICAL COMPOSITION</b>																																								<b>CRYSTALLINE ROCK (CR)</b>																																								<b>FINE TO COARSE GRAIN IGNEOUS AND METAMORPHIC ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES GRANITE, GNEISS, GABBRO, SCHIST, ETC.</b>																																																															
GENERAL CLASS.	GRANULAR MATERIALS (≤ 35% PASSING #200)					SILT-CLAY MATERIALS (> 35% PASSING #200)					ORGANIC MATERIALS																																																																																																																																																																																														
GROUP CLASS.	A-1	A-3	A-2	A-2-4	A-2-5	A-2-6	A-2-7	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7																																																																																																																																																																																										
SYMBOL	[Pattern]					[Pattern]					[Pattern]																																																																																																																																																																																														
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2">% PASSING</th> <th colspan="2">#10</th> <th colspan="2">#40</th> <th colspan="2">#200</th> <th colspan="2">GRANULAR SOILS</th> <th colspan="2">SILT-CLAY SOILS</th> <th colspan="2">MUCK, PEAT</th> </tr> <tr> <td>50 MX</td><td>30 MX</td><td>30 MX</td><td>25 MX</td><td>10 MX</td><td>51 MN</td><td>35 MX</td><td>35 MX</td><td>35 MX</td><td>35 MX</td><td>36 MN</td><td>36 MN</td><td>36 MN</td><td>36 MN</td> </tr> <tr> <td>15 MX</td><td>10 MX</td><td>10 MX</td><td>10 MX</td><td>10 MX</td><td>10 MN</td><td>11 MN</td><td>11 MN</td><td>11 MN</td><td>11 MN</td><td>11 MN</td><td>11 MN</td><td>11 MN</td><td>11 MN</td> </tr> </table>										% PASSING		#10		#40		#200		GRANULAR SOILS		SILT-CLAY SOILS		MUCK, PEAT		50 MX	30 MX	30 MX	25 MX	10 MX	51 MN	35 MX	35 MX	35 MX	35 MX	36 MN	36 MN	36 MN	36 MN	15 MX	10 MX	10 MX	10 MX	10 MX	10 MN	11 MN	11 MN	11 MN	11 MN	11 MN	11 MN	11 MN	11 MN	<b>COMPRESSIBILITY</b>																																								<b>NON-CRYSTALLINE ROCK (NCR)</b>																																								<b>FINE TO COARSE GRAIN METAMORPHIC AND NON-COASTAL PLAIN SEDIMENTARY ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES PHYLLITE, SLATE, SANDSTONE, ETC.</b>																																																																					
% PASSING		#10		#40		#200		GRANULAR SOILS		SILT-CLAY SOILS		MUCK, PEAT																																																																																																																																																																																													
50 MX	30 MX	30 MX	25 MX	10 MX	51 MN	35 MX	35 MX	35 MX	35 MX	36 MN	36 MN	36 MN	36 MN																																																																																																																																																																																												
15 MX	10 MX	10 MX	10 MX	10 MX	10 MN	11 MN	11 MN	11 MN	11 MN	11 MN	11 MN	11 MN	11 MN																																																																																																																																																																																												
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2">MATERIAL PASSING #40</th> <th colspan="2">LL</th> <th colspan="2">PI</th> <th colspan="2">GROUP INDEX</th> <th colspan="2">USUAL TYPES OF MAJOR MATERIALS</th> <th colspan="2">GEN. RATING AS SUBGRADE</th> <th colspan="2">FAIR TO POOR</th> <th colspan="2">POOR</th> <th colspan="2">UNSATURABLE</th> </tr> <tr> <td>6 MX</td><td>NP</td><td>40 MX</td><td>41 MN</td><td>40 MX</td><td>41 MN</td><td>40 MX</td><td>41 MN</td><td>40 MX</td><td>41 MN</td><td>40 MX</td><td>41 MN</td><td>40 MX</td><td>41 MN</td><td>40 MX</td><td>41 MN</td><td>40 MX</td><td>41 MN</td> </tr> <tr> <td>10 MX</td><td>NP</td><td>10 MX</td><td>10 MN</td><td>11 MN</td><td>11 MN</td><td>11 MN</td><td>11 MN</td><td>11 MN</td><td>11 MN</td><td>11 MN</td><td>11 MN</td><td>11 MN</td><td>11 MN</td><td>11 MN</td><td>11 MN</td><td>11 MN</td><td>11 MN</td> </tr> </table>										MATERIAL PASSING #40		LL		PI		GROUP INDEX		USUAL TYPES OF MAJOR MATERIALS		GEN. RATING AS SUBGRADE		FAIR TO POOR		POOR		UNSATURABLE		6 MX	NP	40 MX	41 MN	40 MX	41 MN	40 MX	41 MN	40 MX	41 MN	40 MX	41 MN	40 MX	41 MN	40 MX	41 MN	40 MX	41 MN	10 MX	NP	10 MX	10 MN	11 MN	11 MN	11 MN	11 MN	11 MN	11 MN	11 MN	11 MN	11 MN	11 MN	11 MN	11 MN	11 MN	11 MN	<b>PERCENTAGE OF MATERIAL</b>																																								<b>COASTAL PLAIN SEDIMENTARY ROCK (CP)</b>																																								<b>COASTAL PLAIN SEDIMENTS CEMENTED INTO ROCK, BUT MAY NOT YIELD SPT REFUSAL. ROCK TYPE INCLUDES LIMESTONE, SANDSTONE, CEMENTED SHELL BEDS, ETC.</b>																																																									
MATERIAL PASSING #40		LL		PI		GROUP INDEX		USUAL TYPES OF MAJOR MATERIALS		GEN. RATING AS SUBGRADE		FAIR TO POOR		POOR		UNSATURABLE																																																																																																																																																																																									
6 MX	NP	40 MX	41 MN	40 MX	41 MN	40 MX	41 MN	40 MX	41 MN	40 MX	41 MN	40 MX	41 MN	40 MX	41 MN	40 MX	41 MN																																																																																																																																																																																								
10 MX	NP	10 MX	10 MN	11 MN	11 MN	11 MN	11 MN	11 MN	11 MN	11 MN	11 MN	11 MN	11 MN	11 MN	11 MN	11 MN	11 MN																																																																																																																																																																																								
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2">ORGANIC MATERIAL</th> <th colspan="2">GRANULAR SOILS</th> <th colspan="2">SILT-CLAY SOILS</th> <th colspan="2">OTHER MATERIAL</th> </tr> <tr> <td>TRACE OF ORGANIC MATTER</td><td>2 - 3%</td><td>3 - 5%</td><td>3 - 5%</td><td>TRACE</td><td>1 - 10%</td> </tr> <tr> <td>LITTLE ORGANIC MATTER</td><td>3 - 5%</td><td>5 - 12%</td><td>5 - 12%</td><td>LITTLE</td><td>10 - 20%</td> </tr> <tr> <td>MODERATELY ORGANIC</td><td>5 - 10%</td><td>12 - 20%</td><td>12 - 20%</td><td>SOME</td><td>20 - 35%</td> </tr> <tr> <td>HIGHLY ORGANIC</td><td>&gt; 10%</td><td>&gt; 20%</td><td>&gt; 20%</td><td>HIGHLY</td><td>35% AND ABOVE</td> </tr> </table>										ORGANIC MATERIAL		GRANULAR SOILS		SILT-CLAY SOILS		OTHER MATERIAL		TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	3 - 5%	TRACE	1 - 10%	LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	5 - 12%	LITTLE	10 - 20%	MODERATELY ORGANIC	5 - 10%	12 - 20%	12 - 20%	SOME	20 - 35%	HIGHLY ORGANIC	> 10%	> 20%	> 20%	HIGHLY	35% AND ABOVE	<b>GROUND WATER</b>																																								<b>WEATHERING</b>																																								<b>FRESH</b>																																								<b>ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING. ROCK RINGS UNDER HAMMER IF CRYSTALLINE.</b>																																							
ORGANIC MATERIAL		GRANULAR SOILS		SILT-CLAY SOILS		OTHER MATERIAL																																																																																																																																																																																																			
TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	3 - 5%	TRACE	1 - 10%																																																																																																																																																																																																				
LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	5 - 12%	LITTLE	10 - 20%																																																																																																																																																																																																				
MODERATELY ORGANIC	5 - 10%	12 - 20%	12 - 20%	SOME	20 - 35%																																																																																																																																																																																																				
HIGHLY ORGANIC	> 10%	> 20%	> 20%	HIGHLY	35% AND ABOVE																																																																																																																																																																																																				
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2">CONSISTENCY OR DENSENESS</th> <th colspan="2">RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)</th> <th colspan="2">RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT<sup>2</sup>)</th> </tr> <tr> <td>VERY LOOSE</td><td>&lt; 4</td><td>4 TO 10</td><td>N/A</td> </tr> <tr> <td>LOOSE</td><td>4 TO 10</td><td>10 TO 30</td><td>N/A</td> </tr> <tr> <td>MEDIUM DENSE</td><td>10 TO 30</td><td>30 TO 50</td><td>N/A</td> </tr> <tr> <td>DENSE</td><td>30 TO 50</td><td>&gt; 50</td><td>N/A</td> </tr> <tr> <td>VERY DENSE</td><td>&gt; 50</td><td>&gt; 50</td><td>N/A</td> </tr> </table>										CONSISTENCY OR DENSENESS		RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)		RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT <sup>2</sup> )		VERY LOOSE	< 4	4 TO 10	N/A	LOOSE	4 TO 10	10 TO 30	N/A	MEDIUM DENSE	10 TO 30	30 TO 50	N/A	DENSE	30 TO 50	> 50	N/A	VERY DENSE	> 50	> 50	N/A	<b>MISCELLANEOUS SYMBOLS</b>																																								<b>MODERATE (MOD.)</b>																																								<b>SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY. ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED WITH FRESH ROCK.</b>																																																																																					
CONSISTENCY OR DENSENESS		RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)		RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT <sup>2</sup> )																																																																																																																																																																																																					
VERY LOOSE	< 4	4 TO 10	N/A																																																																																																																																																																																																						
LOOSE	4 TO 10	10 TO 30	N/A																																																																																																																																																																																																						
MEDIUM DENSE	10 TO 30	30 TO 50	N/A																																																																																																																																																																																																						
DENSE	30 TO 50	> 50	N/A																																																																																																																																																																																																						
VERY DENSE	> 50	> 50	N/A																																																																																																																																																																																																						
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2">TEXTURE OR GRAIN SIZE</th> <th colspan="2">U.S. STD. SIEVE SIZE OPENING (MM)</th> <th colspan="2">4</th> <th colspan="2">10</th> <th colspan="2">40</th> <th colspan="2">60</th> <th colspan="2">200</th> <th colspan="2">270</th> </tr> <tr> <td>BOULDER (BLDR.)</td><td>COBBLE (COB.)</td><td>GRAVEL (GR.)</td><td>COARSE SAND (CSE. SD.)</td><td>FINE SAND (F SD.)</td><td>SILT (SL.)</td><td>CLAY (CL.)</td> </tr> <tr> <td>305</td><td>75</td><td>2.0</td><td>0.25</td><td>0.075</td><td>0.05</td><td>0.005</td> </tr> </table>										TEXTURE OR GRAIN SIZE		U.S. STD. SIEVE SIZE OPENING (MM)		4		10		40		60		200		270		BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE. SD.)	FINE SAND (F SD.)	SILT (SL.)	CLAY (CL.)	305	75	2.0	0.25	0.075	0.05	0.005	<b>RECOMMENDATION SYMBOLS</b>																																								<b>SEVERE (SEV.)</b>																																								<b>ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK. ROCK GIVES "CLUNK" SOUND WHEN STRUCK. IF TESTED, WOULD YIELD SPT REFUSAL.</b>																																																																																	
TEXTURE OR GRAIN SIZE		U.S. STD. SIEVE SIZE OPENING (MM)		4		10		40		60		200		270																																																																																																																																																																																											
BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE. SD.)	FINE SAND (F SD.)	SILT (SL.)	CLAY (CL.)																																																																																																																																																																																																			
305	75	2.0	0.25	0.075	0.05	0.005																																																																																																																																																																																																			
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2">SOIL MOISTURE - CORRELATION OF TERMS</th> <th colspan="2">FIELD MOISTURE DESCRIPTION</th> <th colspan="2">GUIDE FOR FIELD MOISTURE DESCRIPTION</th> </tr> <tr> <td>LL</td><td>LIQUID LIMIT</td><td>- SATURATED - (SAT.)</td><td>USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE</td> </tr> <tr> <td>PL</td><td>PLASTIC LIMIT</td><td>- WET - (W)</td><td>SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td>OM</td><td>OPTIMUM MOISTURE SHRINKAGE LIMIT</td><td>- MOIST - (M)</td><td>SOLID; AT OR NEAR OPTIMUM MOISTURE</td> </tr> <tr> <td>SL</td><td></td><td>- DRY - (D)</td><td>REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td> </tr> </table>										SOIL MOISTURE - CORRELATION OF TERMS		FIELD MOISTURE DESCRIPTION		GUIDE FOR FIELD MOISTURE DESCRIPTION		LL	LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE	PL	PLASTIC LIMIT	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE	OM	OPTIMUM MOISTURE SHRINKAGE LIMIT	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE	SL		- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE	<b>ABBREVIATIONS</b>																																								<b>SEVERE (SEV.)</b>																																								<b>ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC CLEAR AND EVIDENT BUT REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN. IF TESTED, WOULD YIELD SPT N VALUES &gt; 100 BPF.</b>																																																																																									
SOIL MOISTURE - CORRELATION OF TERMS		FIELD MOISTURE DESCRIPTION		GUIDE FOR FIELD MOISTURE DESCRIPTION																																																																																																																																																																																																					
LL	LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE																																																																																																																																																																																																						
PL	PLASTIC LIMIT	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																																																						
OM	OPTIMUM MOISTURE SHRINKAGE LIMIT	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE																																																																																																																																																																																																						
SL		- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																																																						
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2">PLASTICITY</th> <th colspan="2">PLASTICITY INDEX (PI)</th> <th colspan="2">DRY STRENGTH</th> </tr> <tr> <td>NON PLASTIC</td><td>0-5</td><td>VERY LOW</td> </tr> <tr> <td>SLIGHTLY PLASTIC</td><td>6-15</td><td>SLIGHT</td> </tr> <tr> <td>MODERATELY PLASTIC</td><td>16-25</td><td>MEDIUM</td> </tr> <tr> <td>HIGHLY PLASTIC</td><td>26 OR MORE</td><td>HIGH</td> </tr> </table>										PLASTICITY		PLASTICITY INDEX (PI)		DRY STRENGTH		NON PLASTIC	0-5	VERY LOW	SLIGHTLY PLASTIC	6-15	SLIGHT	MODERATELY PLASTIC	16-25	MEDIUM	HIGHLY PLASTIC	26 OR MORE	HIGH	<b>EQUIPMENT USED ON SUBJECT PROJECT</b>																																								<b>COMPLETE</b>																																								<b>ROCK REDUCED TO SOIL, ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.</b>																																																																																													
PLASTICITY		PLASTICITY INDEX (PI)		DRY STRENGTH																																																																																																																																																																																																					
NON PLASTIC	0-5	VERY LOW																																																																																																																																																																																																							
SLIGHTLY PLASTIC	6-15	SLIGHT																																																																																																																																																																																																							
MODERATELY PLASTIC	16-25	MEDIUM																																																																																																																																																																																																							
HIGHLY PLASTIC	26 OR MORE	HIGH																																																																																																																																																																																																							
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2">COLOR</th> <th colspan="2">DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-BROWN). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.</th> </tr> </table>										COLOR		DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-BROWN). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.		<b>FRACURE SPACING</b>																																								<b>BEDDING</b>																																								<b>BENCH MARK:</b>																																																																																																											
COLOR		DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-BROWN). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.																																																																																																																																																																																																							
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2">FRACURE SPACING</th> <th colspan="2">BEDDING</th> </tr> <tr> <td>VERY WIDE</td><td>MORE THAN 10 FEET</td> <td>VERY THICKLY BEDDED</td><td>4 FEET</td> </tr> <tr> <td>WIDE</td><td>3 TO 10 FEET</td> <td>THICKLY BEDDED</td><td>1.5 - 4 FEET</td> </tr> <tr> <td>MODERATELY CLOSE</td><td>1 TO 3 FEET</td> <td>THINLY BEDDED</td><td>0.16 - 1.5 FEET</td> </tr> <tr> <td>CLOSE</td><td>0.16 TO 1 FOOT</td> <td>VERY THINLY BEDDED</td><td>0.03 - 0.16 FEET</td> </tr> <tr> <td>VERY CLOSE</td><td>LESS THAN 0.16 FEET</td> <td>THICKLY LAMINATED</td><td>0.008 - 0.03 FEET</td> </tr> <tr> <td></td><td></td> <td>THINLY LAMINATED</td><td>&lt; 0.008 FEET</td> </tr> </table>										FRACURE SPACING		BEDDING		VERY WIDE	MORE THAN 10 FEET	VERY THICKLY BEDDED	4 FEET	WIDE	3 TO 10 FEET	THICKLY BEDDED	1.5 - 4 FEET	MODERATELY CLOSE	1 TO 3 FEET	THINLY BEDDED	0.16 - 1.5 FEET	CLOSE	0.16 TO 1 FOOT	VERY THINLY BEDDED	0.03 - 0.16 FEET	VERY CLOSE	LESS THAN 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET			THINLY LAMINATED	< 0.008 FEET	<b>INDURATION</b>																																								<b>FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.</b>																																								<b>FRIBLE</b>																																								<b>RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</b>																																											
FRACURE SPACING		BEDDING																																																																																																																																																																																																							
VERY WIDE	MORE THAN 10 FEET	VERY THICKLY BEDDED	4 FEET																																																																																																																																																																																																						
WIDE	3 TO 10 FEET	THICKLY BEDDED	1.5 - 4 FEET																																																																																																																																																																																																						
MODERATELY CLOSE	1 TO 3 FEET	THINLY BEDDED	0.16 - 1.5 FEET																																																																																																																																																																																																						
CLOSE	0.16 TO 1 FOOT	VERY THINLY BEDDED	0.03 - 0.16 FEET																																																																																																																																																																																																						
VERY CLOSE	LESS THAN 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET																																																																																																																																																																																																						
		THINLY LAMINATED	< 0.008 FEET																																																																																																																																																																																																						
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2">INDURATION</th> <th colspan="2">FRIBLE</th> </tr> <tr> <td>MODERATELY INDURATED</td><td>GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</td> </tr> <tr> <td>INDURATED</td><td>GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</td> </tr> <tr> <td>EXTREMELY INDURATED</td><td>SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</td> </tr> </table>										INDURATION		FRIBLE		MODERATELY INDURATED	GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.	INDURATED	GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.	EXTREMELY INDURATED	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.	<b>NOTES:</b>																																								<b>BORING ELEVATIONS TAKEN FROM I5711_LS_TIN_I71025_TIN DATED 10/25/17</b>																																								<b>ELEVATION: FEET</b>																																																																																																					
INDURATION		FRIBLE																																																																																																																																																																																																							
MODERATELY INDURATED	GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.																																																																																																																																																																																																								
INDURATED	GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.																																																																																																																																																																																																								
EXTREMELY INDURATED	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.																																																																																																																																																																																																								
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2">EQUIPMENT USED ON SUBJECT PROJECT</th> <th colspan="2">DRILL UNITS:</th> <th colspan="2">ADVANCING TOOLS:</th> <th colspan="2">HAMMER TYPE:</th> </tr> <tr> <td><input checked="" type="checkbox"/></td><td>CME-45</td> <td><input type="checkbox"/></td><td>CLAY BITS</td> <td><input type="checkbox"/></td><td>6" CONTINUOUS FLIGHT AUGER</td> <td><input checked="" type="checkbox"/></td><td>AUTOMATIC</td> </tr> <tr> <td><input type="checkbox"/></td><td>CME-55</td> <td><input type="checkbox"/></td><td>8" HOLLOW AUGERS</td> <td><input type="checkbox"/></td><td>HARD FACED FINGER BITS</td> <td><input type="checkbox"/></td><td>MANUAL</td> </tr> <tr> <td><input type="checkbox"/></td><td>CME-550</td> <td><input type="checkbox"/></td><td>TUNG-CARBIDE INSERTS</td> <td><input type="checkbox"/></td><td>CASING</td> <td><input type="checkbox"/></td><td>W/ ADVANCER</td> </tr> <tr> <td><input type="checkbox"/></td><td>VANE SHEAR TEST</td> <td><input type="checkbox"/></td><td>CASING</td> <td><input type="checkbox"/></td><td>TRICONE</td> <td><input type="checkbox"/></td><td>* STEEL TEETH</td> </tr> <tr> <td><input type="checkbox"/></td><td>PORTABLE HOIST</td> <td><input type="checkbox"/></td><td>TRICONE</td> <td><input type="checkbox"/></td><td>TRICONE</td> <td><input type="checkbox"/></td><td>* TUNG-CARB.</td> </tr> <tr> <td><input type="checkbox"/></td><td></td> <td><input type="checkbox"/></td><td>CORE BIT</td> <td><input type="checkbox"/></td><td></td> <td><input type="checkbox"/></td><td></td> </tr> </table>										EQUIPMENT USED ON SUBJECT PROJECT		DRILL UNITS:		ADVANCING TOOLS:		HAMMER TYPE:		<input checked="" type="checkbox"/>	CME-45	<input type="checkbox"/>	CLAY BITS	<input type="checkbox"/>	6" CONTINUOUS FLIGHT AUGER	<input checked="" type="checkbox"/>	AUTOMATIC	<input type="checkbox"/>	CME-55	<input type="checkbox"/>	8" HOLLOW AUGERS	<input type="checkbox"/>	HARD FACED FINGER BITS	<input type="checkbox"/>	MANUAL	<input type="checkbox"/>	CME-550	<input type="checkbox"/>	TUNG-CARBIDE INSERTS	<input type="checkbox"/>	CASING	<input type="checkbox"/>	W/ ADVANCER	<input type="checkbox"/>	VANE SHEAR TEST	<input type="checkbox"/>	CASING	<input type="checkbox"/>	TRICONE	<input type="checkbox"/>	* STEEL TEETH	<input type="checkbox"/>	PORTABLE HOIST	<input type="checkbox"/>	TRICONE	<input type="checkbox"/>	TRICONE	<input type="checkbox"/>	* TUNG-CARB.	<input type="checkbox"/>		<input type="checkbox"/>	CORE BIT	<input type="checkbox"/>		<input type="checkbox"/>		<b>INDURATION</b>																																								<b>MODERATELY INDURATED</b>																																								<b>GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</b>																																																							
EQUIPMENT USED ON SUBJECT PROJECT		DRILL UNITS:		ADVANCING TOOLS:		HAMMER TYPE:																																																																																																																																																																																																			
<input checked="" type="checkbox"/>	CME-45	<input type="checkbox"/>	CLAY BITS	<input type="checkbox"/>	6" CONTINUOUS FLIGHT AUGER	<input checked="" type="checkbox"/>	AUTOMATIC																																																																																																																																																																																																		
<input type="checkbox"/>	CME-55	<input type="checkbox"/>	8" HOLLOW AUGERS	<input type="checkbox"/>	HARD FACED FINGER BITS	<input type="checkbox"/>	MANUAL																																																																																																																																																																																																		
<input type="checkbox"/>	CME-550	<input type="checkbox"/>	TUNG-CARBIDE INSERTS	<input type="checkbox"/>	CASING	<input type="checkbox"/>	W/ ADVANCER																																																																																																																																																																																																		
<input type="checkbox"/>	VANE SHEAR TEST	<input type="checkbox"/>	CASING	<input type="checkbox"/>	TRICONE	<input type="checkbox"/>	* STEEL TEETH																																																																																																																																																																																																		
<input type="checkbox"/>	PORTABLE HOIST	<input type="checkbox"/>	TRICONE	<input type="checkbox"/>	TRICONE	<input type="checkbox"/>	* TUNG-CARB.																																																																																																																																																																																																		
<input type="checkbox"/>		<input type="checkbox"/>	CORE BIT	<input type="checkbox"/>		<input type="checkbox"/>																																																																																																																																																																																																			
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2">INDURATION</th> <th colspan="2">MODERATELY INDURATED</th> </tr> <tr> <td>INDURATED</td><td>GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</td> </tr> <tr> <td>EXTREMELY INDURATED</td><td>SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</td> </tr> </table>										INDURATION		MODERATELY INDURATED		INDURATED	GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.	EXTREMELY INDURATED	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.	<b>INDURATION</b>																																								<b>INDURATED</b>																																								<b>GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</b>																																																																																																							
INDURATION		MODERATELY INDURATED																																																																																																																																																																																																							
INDURATED	GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.																																																																																																																																																																																																								
EXTREMELY INDURATED	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.																																																																																																																																																																																																								
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2">INDURATION</th> <th colspan="2">EXTREMELY INDURATED</th> </tr> <tr> <td>EXTREMELY INDURATED</td><td>SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</td> </tr> </table>										INDURATION		EXTREMELY INDURATED		EXTREMELY INDURATED	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.	<b>INDURATION</b>																																								<b>EXTREMELY INDURATED</b>																																								<b>SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</b>																																																																																																									
INDURATION		EXTREMELY INDURATED																																																																																																																																																																																																							
EXTREMELY INDURATED	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.																																																																																																																																																																																																								



# GEOTECHNICAL BORING REPORT

## BORE LOG

WBS 50401.1.FS1		TIP I-5711		COUNTY ALAMANCE		GEOLOGIST A. Paul										
SITE DESCRIPTION Interchange Improvements at I-40/I-85 and SR 1007 (Mebane Oaks Rd.)							GROUND WTR (ft)									
BORING NO. B-1		STATION 10+42		OFFSET 1 ft LT		ALIGNMENT -WALL-										
COLLAR ELEV. 648.7 ft		TOTAL DEPTH 19.5 ft		NORTHING 844,152		EASTING 1,920,011										
DRILL RIG/HAMMER EFF./DATE BRI0674 CME-45C 91% 02/22/2017		DRILL METHOD H.S. Augers		HAMMER TYPE Automatic												
DRILLER J. Radford		START DATE 05/07/19		COMP. DATE 05/07/19		SURFACE WATER DEPTH N/A										
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	MOI	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)	
			0.5ft	0.5ft	0.5ft	0	25	50	75	100						
650															648.7	0.0
	647.8	0.9	1	2	2											
	646.2	2.5	1	2	3											
645																
	643.2	5.5	2	3	4											
	640.7	8.0	1	1	3											
640																
	635.7	13.0	1	3	3											
635																
	630.7	18.0	1	3	4											
630																
															629.2	19.5
Boring Terminated at Elevation 629.2 ft IN RESIDUAL: SILTY CLAY																

WBS 50401.1.FS1		TIP I-5711		COUNTY ALAMANCE		GEOLOGIST A. Paul										
SITE DESCRIPTION Interchange Improvements at I-40/I-85 and SR 1007 (Mebane Oaks Rd.)							GROUND WTR (ft)									
BORING NO. B-2		STATION 10+97		OFFSET 10 ft RT		ALIGNMENT -WALL-										
COLLAR ELEV. 648.8 ft		TOTAL DEPTH 24.5 ft		NORTHING 844,097		EASTING 1,920,025										
DRILL RIG/HAMMER EFF./DATE BRI0674 CME-45C 91% 02/22/2017		DRILL METHOD H.S. Augers		HAMMER TYPE Automatic												
DRILLER J. Radford		START DATE 05/07/19		COMP. DATE 05/07/19		SURFACE WATER DEPTH N/A										
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	MOI	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)	
			0.5ft	0.5ft	0.5ft	0	25	50	75	100						
650															648.8	0.0
	647.8	1.0	2	2	3											
	646.0	2.8	1	3	5											
645																
	642.8	6.0	4	6	8											
	640.8	8.0	2	2	4											
640																
	635.8	13.0	2	3	5											
635																
	630.8	18.0	1	1	4											
630																
	625.8	23.0	2	6	8											
625																
															624.3	24.5
Boring Terminated at Elevation 624.3 ft IN RESIDUAL: SILTY CLAY																

NCDOT BORE DOUBLE I5711\_GEO\_RWAL\_LOGS.GPJ NC\_DOT.GDT 6/21/19