

REFERENCE: R-5020B

PROJECT: 41499

SEE SHEET 3 FOR PLAN SHEET LAYOUT  
AT TIME OF INVESTIGATION

**STATE OF NORTH CAROLINA**  
DEPARTMENT OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
GEOTECHNICAL ENGINEERING UNIT

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	R-5020B	1	102

**ROADWAY**  
**SUBSURFACE INVESTIGATION**

COUNTY COLUMBUS  
PROJECT DESCRIPTION US 701 BYPASS (MADISON  
STREET - JK POWELL BLVD.) FROM SR 1437  
(VIRGIL AVENUE) TO US 7476

**INVENTORY**

**CONTENTS**

LINE	STATION	PLAN
-L-	174+79 TO 289+75	4-12
-RPA-	13+47 TO 19+50	11,13
-RPB-	11+30 TO 13+50	11
-RPC-	15+00 TO 23+00	11,14
-RPD-	12+20 TO 14+50	11
-Y3I-	12+25 TO 17+00	9

**CROSS SECTIONS**

LINE	STATION	SHEETS
-L-	175+00 TO 263+50	15-66
-L-	266+00 TO 271+50	67-71
-L-	273+50 TO 289+75	72-82
-RPA-	13+47 TO 19+50	83-87
-RPB-	11+30 TO 13+50	88-89
-RPC-	15+00 TO 23+00	90-95
-RPD-	12+20 TO 14+50	96-98
-Y3I-	12+25 TO 17+00	99-102

**CAUTION NOTICE**

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT 1919 707-6850. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

- NOTES:
1. THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.
  2. BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

PERSONNEL

N.O. MOORE

C.L. SMITH

D.G. PINTER


INVESTIGATED BY N.O. MOORE

DRAWN BY N.O.M./J.L.L.

CHECKED BY J.L. LOVE

SUBMITTED BY N. T. ROBERSON

DATE FEBRUARY 2018



DocuSigned by:

*Neil T. Roberson*

2/15/2018

4081D9A8C8C819C  
SIGNATURE

DATE

**DOCUMENT NOT CONSIDERED FINAL  
UNLESS ALL SIGNATURES COMPLETED**

**NORTH CAROLINA DEPARTMENT OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
GEOTECHNICAL ENGINEERING UNIT  
SUBSURFACE INVESTIGATION  
SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS**

SOIL DESCRIPTION										GRADATION										ROCK DESCRIPTION										TERMS AND DEFINITIONS																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																												
<p>SOIL IS CONSIDERED UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER AND YIELD LESS THAN 100 BLOWS PER FOOT ACCORDING TO THE STANDARD PENETRATION TEST (AASHTO T 206, ASTM D1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY INCLUDE THE FOLLOWING: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. FOR EXAMPLE, <i>VERY STIFF, GRAY, SILTY CLAY, MOIST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC, A-7-6</i></p>										<p><b>WELL GRADED</b> - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. <b>UNIFORMLY GRADED</b> - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. <b>GAP-GRADED</b> - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES.</p>										<p>HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED, AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS IN NON-COASTAL PLAIN MATERIAL. THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:</p>										<p><b>ALLUVIUM (ALLUV.)</b> - SOILS THAT HAVE BEEN TRANSPORTED BY WATER. <b>AQUIFER</b> - A WATER BEARING FORMATION OR STRATA. <b>ARENACEOUS</b> - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND. <b>ARGILLACEOUS</b> - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC. <b>ARTESIAN</b> - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE. <b>CALCAREOUS (CALC.)</b> - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE. <b>COLLUVIUM</b> - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE. <b>CORE RECOVERY (REC.)</b> - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. <b>DIKE</b> - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK. <b>DIP</b> - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL. <b>DIP DIRECTION (DIP AZIMUTH)</b> - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH. <b>FAULT</b> - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE. <b>FISSILE</b> - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES. <b>FLOAT</b> - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLOGGED FROM PARENT MATERIAL. <b>FLOOD PLAIN (FP)</b> - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM. <b>FORMATION (FM)</b> - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD. <b>JOINT</b> - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED. <b>LEDGE</b> - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT. <b>LENS</b> - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS. <b>MOTTLED (MOT.)</b> - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS. MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. <b>PERCHED WATER</b> - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM. <b>RESIDUAL (RES.) SOIL</b> - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK. <b>ROCK QUALITY DESIGNATION (ROD)</b> - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. <b>SAPROLITE (SAP.)</b> - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK. <b>SILL</b> - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS. <b>SLICKENSIDE</b> - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE. <b>STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT)</b> - NUMBER OF BLOWS (N OR BPF) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. <b>STRATA CORE RECOVERY (SREC.)</b> - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE. <b>STRATA ROCK QUALITY DESIGNATION (SROD)</b> - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. <b>TOPSOIL (TS.)</b> - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.</p>																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																												
<p><b>SOIL LEGEND AND AASHTO CLASSIFICATION</b></p> <table border="1"> <tr> <th>GENERAL CLASS.</th> <th colspan="5">GRANULAR MATERIALS (≤ 35% PASSING #200)</th> <th colspan="5">SILT-CLAY MATERIALS (&gt; 35% PASSING #200)</th> <th colspan="5">ORGANIC MATERIALS</th> </tr> <tr> <th>GROUP CLASS.</th> <th>A-1</th> <th>A-3</th> <th>A-2</th> <th>A-4</th> <th>A-5</th> <th>A-6</th> <th>A-7</th> <th>A-1, A-2</th> <th>A-3</th> <th>A-4, A-5</th> <th>A-6, A-7</th> <th colspan="5"></th> </tr> <tr> <th>SYMBOL</th> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <th>% PASSING #10 #40 #200</th> <td>50 MX 30 MX 15 MX</td> <td>50 MX 25 MX 10 MX</td> <td>51 MN 35 MX 35 MX 35 MX</td> <td>36 MN 36 MN 36 MN</td> <td>36 MN 36 MN 36 MN</td> <td>36 MN 36 MN 36 MN</td> <td>36 MN 36 MN 36 MN</td> <td>36 MN 36 MN 36 MN</td> <td>36 MN 36 MN 36 MN</td> <td>36 MN 36 MN 36 MN</td> <td>36 MN 36 MN 36 MN</td> <td>36 MN 36 MN 36 MN</td> <td>36 MN 36 MN 36 MN</td> <td>36 MN 36 MN 36 MN</td> <td>36 MN 36 MN 36 MN</td> <td>36 MN 36 MN 36 MN</td> <td>36 MN 36 MN 36 MN</td> <td>36 MN 36 MN 36 MN</td> </tr> <tr> <th>MATERIAL PASSING #40 LL PI</th> <td>— 6 MX</td> <td>— NP</td> <td>40 MX 41 MN 10 MX 11 MN</td> <td>40 MX 41 MN 10 MX 11 MN</td> <td>40 MX 41 MN 10 MX 11 MN</td> <td>40 MX 41 MN 10 MX 11 MN</td> <td>40 MX 41 MN 10 MX 11 MN</td> <td>40 MX 41 MN 10 MX 11 MN</td> <td>40 MX 41 MN 10 MX 11 MN</td> <td>40 MX 41 MN 10 MX 11 MN</td> <td>40 MX 41 MN 10 MX 11 MN</td> <td>40 MX 41 MN 10 MX 11 MN</td> <td>40 MX 41 MN 10 MX 11 MN</td> <td>40 MX 41 MN 10 MX 11 MN</td> <td>40 MX 41 MN 10 MX 11 MN</td> <td>40 MX 41 MN 10 MX 11 MN</td> <td>40 MX 41 MN 10 MX 11 MN</td> <td>40 MX 41 MN 10 MX 11 MN</td> </tr> <tr> <th>GROUP INDEX</th> <td>0</td> <td>0</td> <td>0</td> <td>4 MX</td> <td>8 MX</td> <td>12 MX</td> <td>16 MX</td> <td>NO MX</td> <td>NO MX</td> <td>NO MX</td> <td>NO MX</td> <td>NO MX</td> <td>NO MX</td> <td>NO MX</td> <td>NO MX</td> <td>NO MX</td> <td>NO MX</td> <td>NO MX</td> </tr> <tr> <th>USUAL TYPES OF MAJOR MATERIALS</th> <td>STONE FRAGS. GRAVEL, AND SAND</td> <td>FINE SAND</td> <td>SILTY OR CLAYEY GRAVEL AND SAND</td> <td>SILTY SOILS</td> <td>CLAYEY SOILS</td> <td colspan="5">SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER</td> <td colspan="5">HIGHLY ORGANIC SOILS</td> </tr> <tr> <th>GEN. RATING AS SUBGRADE</th> <td colspan="5">EXCELLENT TO GOOD</td> <td colspan="5">FAIR TO POOR</td> <td>FAIR TO POOR</td> <td>POOR</td> <td>UNSATURABLE</td> <td colspan="5"></td> </tr> <tr> <td colspan="10">PI OF A-7-5 SUBGROUP IS ≤ LL - 30 ; PI OF A-7-6 SUBGROUP IS &gt; LL - 30</td> <td colspan="10"></td> <td colspan="10"></td> </tr> <tr> <td colspan="10"> <p><b>CONSISTENCY OR DENSENESS</b></p> <table border="1"> <tr> <th>PRIMARY SOIL TYPE</th> <th>COMPACTNESS OR CONSISTENCY</th> <th>RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)</th> <th>RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT<sup>2</sup>)</th> </tr> <tr> <td>GENERALLY GRANULAR MATERIAL (NON-COHESIVE)</td> <td>VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE</td> <td>&lt; 4 4 TO 10 10 TO 30 30 TO 50 &gt; 50</td> <td>N/A</td> </tr> <tr> <td>GENERALLY SILT-CLAY MATERIAL (COHESIVE)</td> <td>VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD</td> <td>&lt; 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 &gt; 30</td> <td>&lt; 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 &gt; 4</td> </tr> </table> </td> <td colspan="10"> <p><b>MISCELLANEOUS SYMBOLS</b></p> <table border="1"> <tr> <td></td> <td>ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION</td> <td></td> <td>DIP &amp; DIP DIRECTION OF ROCK STRUCTURES</td> <td></td> <td>SOIL SYMBOL</td> <td></td> <td>ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT</td> <td></td> <td>INFERRED SOIL BOUNDARY</td> <td></td> <td>INFERRED ROCK LINE</td> <td></td> <td>ALLUVIAL SOIL BOUNDARY</td> <td></td> <td>TEST BORING</td> <td></td> <td>AUGER BORING</td> <td></td> <td>CORE BORING</td> <td></td> <td>MONITORING WELL</td> <td></td> <td>PIEZOMETER INSTALLATION</td> <td></td> <td>SPT N-VALUE</td> </tr> </table> </td> <td colspan="10"> <p><b>ROCK HARDNESS</b></p> <table border="1"> <tr> <th>VERY HARD</th> <td>CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.</td> </tr> <tr> <th>HARD</th> <td>CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.</td> </tr> <tr> <th>MODERATELY HARD</th> <td>CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.</td> </tr> <tr> <th>MEDIUM HARD</th> <td>CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.</td> </tr> <tr> <th>SOFT</th> <td>CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.</td> </tr> <tr> <th>VERY SOFT</th> <td>CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.</td> </tr> </table> </td> <td colspan="10"> <p><b>TEXTURE OR GRAIN SIZE</b></p> <table border="1"> <tr> <th>U.S. STD. SIEVE SIZE OPENING (MM)</th> <td>4</td> <td>10</td> <td>40</td> <td>60</td> <td>200</td> <td>270</td> </tr> <tr> <td></td> <td>4.76</td> <td>2.00</td> <td>0.42</td> <td>0.25</td> <td>0.075</td> <td>0.053</td> </tr> <tr> <th>BOULDER (BLD.)</th> <th>COBBLE (COB.)</th> <th>GRAVEL (GR.)</th> <th>COARSE SAND (CS. SD.)</th> <th>FINE SAND (F SD.)</th> <th>SILT (SL.)</th> <th>CLAY (CL.)</th> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <th>GRAIN SIZE</th> <td>MM 305</td> <td>75</td> <td>2.0</td> <td>0.25</td> <td>0.05</td> <td>0.005</td> </tr> <tr> <td></td> <td>IN. 12</td> <td>3</td> <td></td> <td></td> <td></td> <td></td> </tr> </table> </td> <td colspan="10"> <p><b>RECOMMENDATION SYMBOLS</b></p> <table border="1"> <tr> <td></td> <td>UNDERCUT</td> <td></td> <td>UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE</td> <td></td> <td>UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK</td> <td></td> <td>UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE USED IN THE TOP 3 FEET OF EMBANKMENT OR BACKFILL</td> </tr> </table> </td> <td colspan="10"> <p><b>ABBREVIATIONS</b></p> <table border="1"> <tr> <td>AR - AUGER REFUSAL</td> <td>CL - CLAY</td> <td>CPT - COARSE PENETRATION TEST</td> <td>CSE - COARSE</td> <td>DMT - DILATOMETER TEST</td> <td>DPT - DYNAMIC PENETRATION TEST</td> <td>e - VOID RATIO</td> <td>F - FINE</td> <td>FOSS. - FOSSILIFEROUS</td> <td>FRAC. - FRACTURED, FRACTURES</td> <td>FRAGS. - FRAGMENTS</td> <td>HI. - HIGHLY</td> <td>MED. - MEDIUM</td> <td>MICA. - MICACEOUS</td> <td>MOD. - MODERATELY</td> <td>NP - NON PLASTIC</td> <td>ORG. - ORGANIC</td> <td>PMT - PRESSUREMETER TEST</td> <td>SAP. - SAPROLITIC</td> <td>SD. - SAND, SANDY</td> <td>SL. - SILT, SILTY</td> <td>SLI. - SLIGHTLY</td> <td>TCR - TRICONE REFUSAL</td> <td>w - MOISTURE CONTENT</td> <td>V - VERY</td> <td>VST - VANE SHEAR TEST</td> <td>WEA. - WEATHERED</td> <td>UNIT WEIGHT</td> <td>DRY UNIT WEIGHT</td> </tr> <tr> <td colspan="10">SAMPLE ABBREVIATIONS</td> <td colspan="10"></td> </tr> <tr> <td>S - BULK</td> <td>SS - SPLIT SPOON</td> <td>ST - SHELBY TUBE</td> <td>RS - ROCK</td> <td>RT - RECOMPACTED TRIAXIAL</td> <td>CBR - CALIFORNIA BEARING RATIO</td> <td colspan="10"></td> </tr> </table> </td> <td colspan="10"> <p><b>SOIL MOISTURE - CORRELATION OF TERMS</b></p> <table border="1"> <tr> <th>SOIL MOISTURE SCALE (ATTERBERG LIMITS)</th> <th>FIELD MOISTURE DESCRIPTION</th> <th>GUIDE FOR FIELD MOISTURE DESCRIPTION</th> </tr> <tr> <td>LL - LIQUID LIMIT</td> <td>- SATURATED - (SAT.)</td> <td>USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE</td> </tr> <tr> <td>PL - PLASTIC LIMIT</td> <td>- WET - (W)</td> <td>SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td>OM - OPTIMUM MOISTURE SHRINKAGE LIMIT</td> <td>- MOIST - (M)</td> <td>SOLID; AT OR NEAR OPTIMUM MOISTURE</td> </tr> <tr> <td>SL - SHRINKAGE LIMIT</td> <td>- DRY - (D)</td> <td>REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td> </tr> </table> </td> <td colspan="10"> <p><b>EQUIPMENT USED ON SUBJECT PROJECT</b></p> <table border="1"> <tr> <td><input type="checkbox"/> CME-45C</td> <td><input type="checkbox"/> CLAY BITS</td> <td><input type="checkbox"/> AUTOMATIC</td> <td><input type="checkbox"/> MANUAL</td> </tr> <tr> <td><input type="checkbox"/> CME-55</td> <td><input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER</td> <td colspan="2">CORE SIZE:</td> </tr> <tr> <td><input type="checkbox"/> CME-550</td> <td><input type="checkbox"/> 8" HOLLOW AUGERS</td> <td><input type="checkbox"/> -B</td> <td><input type="checkbox"/> -H</td> </tr> <tr> <td><input type="checkbox"/> VANE SHEAR TEST</td> <td><input type="checkbox"/> HARD FACED FINGER BITS</td> <td><input type="checkbox"/> -N</td> <td></td> </tr> <tr> <td><input type="checkbox"/> PORTABLE HOIST</td> <td><input type="checkbox"/> TUNG-CARBIDE INSERTS</td> <td colspan="2">HAND TOOLS:</td> </tr> <tr> <td><input type="checkbox"/></td> <td><input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER</td> <td><input type="checkbox"/> POST HOLE DIGGER</td> <td></td> </tr> <tr> <td><input type="checkbox"/></td> <td><input type="checkbox"/> TRICONE <input type="checkbox"/> STEEL TEETH</td> <td><input checked="" type="checkbox"/> HAND AUGER</td> <td></td> </tr> <tr> <td><input type="checkbox"/></td> <td><input type="checkbox"/> TRICONE <input type="checkbox"/> TUNG-CARB.</td> <td><input type="checkbox"/> SOUNDING ROD</td> <td></td> </tr> <tr> <td><input type="checkbox"/></td> <td><input type="checkbox"/> CORE BIT</td> <td><input type="checkbox"/> VANE SHEAR TEST</td> <td></td> </tr> </table> </td> <td colspan="10"> <p><b>FRACATURE SPACING</b></p> <table border="1"> <tr> <th>TERM</th> <th>SPACING</th> </tr> <tr> <td>VERY WIDE</td> <td>MORE THAN 10 FEET</td> </tr> <tr> <td>WIDE</td> <td>3 TO 10 FEET</td> </tr> <tr> <td>MODERATELY CLOSE</td> <td>1 TO 3 FEET</td> </tr> <tr> <td>CLOSE</td> <td>0.16 TO 1 FOOT</td> </tr> <tr> <td>VERY CLOSE</td> <td>LESS THAN 0.16 FEET</td> </tr> </table> </td> <td colspan="10"> <p><b>BEDDING</b></p> <table border="1"> <tr> <th>TERM</th> <th>THICKNESS</th> </tr> <tr> <td>VERY THICKLY BEDDED</td> <td>4 FEET</td> </tr> <tr> <td>THICKLY BEDDED</td> <td>1.5 - 4 FEET</td> </tr> <tr> <td>THINLY BEDDED</td> <td>0.16 - 1.5 FEET</td> </tr> <tr> <td>VERY THINLY BEDDED</td> <td>0.03 - 0.16 FEET</td> </tr> <tr> <td>THICKLY LAMINATED</td> <td>0.008 - 0.03 FEET</td> </tr> <tr> <td>THINLY LAMINATED</td> <td>&lt; 0.008 FEET</td> </tr> </table> </td> <td colspan="10"> <p><b>INDURATION</b></p> <table border="1"> <tr> <th>FRIBLE</th> <td>RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</td> </tr> <tr> <th>MODERATELY INDURATED</th> <td>GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</td> </tr> <tr> <th>INDURATED</th> <td>GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</td> </tr> <tr> <th>EXTREMELY INDURATED</th> <td>SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</td> </tr> </table> </td> <td colspan="10"> <p><b>BENCH MARK:</b></p> <p align="right">ELEVATION: FEET</p> </td> <td colspan="10"> <p><b>NOTES:</b></p> <p>BORINGS LOCATED USING GPK FILED DATED 5/25/17 AND ELEVATIONS FROM TIN FILE DATED 5/30/17.</p> </td> </tr> <tr> <td colspan="10"> <p><b>PLASTICITY</b></p> <table border="1"> <tr> <th>NON PLASTIC</th> <th>SLIGHTLY PLASTIC</th> <th>MODERATELY PLASTIC</th> <th>HIGHLY PLASTIC</th> </tr> <tr> <td>0-5</td> <td>6-15</td> <td>16-25</td> <td>26 OR MORE</td> </tr> <tr> <th>VERY LOW</th> <th>SLIGHT</th> <th>MEDIUM</th> <th>HIGH</th> </tr> <tr> <td>0-5</td> <td>6-15</td> <td>16-25</td> <td>26 OR MORE</td> </tr> </table> </td> <td colspan="10"> <p><b>COLOR</b></p> <p>DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-BROWN). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.</p> </td> <td colspan="10"> <p><b>INDURATION</b></p> <p>FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.</p> </td> <td colspan="10"> <p>DATE: 8-15-14</p> </td> </tr> </table>										GENERAL CLASS.	GRANULAR MATERIALS (≤ 35% PASSING #200)					SILT-CLAY MATERIALS (> 35% PASSING #200)					ORGANIC MATERIALS					GROUP CLASS.	A-1	A-3	A-2	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7						SYMBOL																		% PASSING #10 #40 #200	50 MX 30 MX 15 MX	50 MX 25 MX 10 MX	51 MN 35 MX 35 MX 35 MX	36 MN 36 MN 36 MN	36 MN 36 MN 36 MN	36 MN 36 MN 36 MN	36 MN 36 MN 36 MN	36 MN 36 MN 36 MN	36 MN 36 MN 36 MN	36 MN 36 MN 36 MN	36 MN 36 MN 36 MN	36 MN 36 MN 36 MN	36 MN 36 MN 36 MN	36 MN 36 MN 36 MN	36 MN 36 MN 36 MN	36 MN 36 MN 36 MN	36 MN 36 MN 36 MN	36 MN 36 MN 36 MN	MATERIAL PASSING #40 LL PI	— 6 MX	— NP	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 10 MX 11 MN	GROUP INDEX	0	0	0	4 MX	8 MX	12 MX	16 MX	NO MX	NO MX	NO MX	NO MX	NO MX	NO MX	NO MX	NO MX	NO MX	NO MX	NO MX	USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS. GRAVEL, AND SAND	FINE SAND	SILTY OR CLAYEY GRAVEL AND SAND	SILTY SOILS	CLAYEY SOILS	SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER					HIGHLY ORGANIC SOILS					GEN. RATING AS SUBGRADE	EXCELLENT TO GOOD					FAIR TO POOR					FAIR TO POOR	POOR	UNSATURABLE						PI OF A-7-5 SUBGROUP IS ≤ LL - 30 ; PI OF A-7-6 SUBGROUP IS > LL - 30																														<p><b>CONSISTENCY OR DENSENESS</b></p> <table border="1"> <tr> <th>PRIMARY SOIL TYPE</th> <th>COMPACTNESS OR CONSISTENCY</th> <th>RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)</th> <th>RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT<sup>2</sup>)</th> </tr> <tr> <td>GENERALLY GRANULAR MATERIAL (NON-COHESIVE)</td> <td>VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE</td> <td>&lt; 4 4 TO 10 10 TO 30 30 TO 50 &gt; 50</td> <td>N/A</td> </tr> <tr> <td>GENERALLY SILT-CLAY MATERIAL (COHESIVE)</td> <td>VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD</td> <td>&lt; 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 &gt; 30</td> <td>&lt; 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 &gt; 4</td> </tr> </table>										PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT <sup>2</sup> )	GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	< 4 4 TO 10 10 TO 30 30 TO 50 > 50	N/A	GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30	< 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4	<p><b>MISCELLANEOUS SYMBOLS</b></p> <table border="1"> <tr> <td></td> <td>ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION</td> <td></td> <td>DIP &amp; DIP DIRECTION OF ROCK STRUCTURES</td> <td></td> <td>SOIL SYMBOL</td> <td></td> <td>ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT</td> <td></td> <td>INFERRED SOIL BOUNDARY</td> <td></td> <td>INFERRED ROCK LINE</td> <td></td> <td>ALLUVIAL SOIL BOUNDARY</td> <td></td> <td>TEST BORING</td> <td></td> <td>AUGER BORING</td> <td></td> <td>CORE BORING</td> <td></td> <td>MONITORING WELL</td> <td></td> <td>PIEZOMETER INSTALLATION</td> <td></td> <td>SPT N-VALUE</td> </tr> </table>											ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION		DIP & DIP DIRECTION OF ROCK STRUCTURES		SOIL SYMBOL		ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT		INFERRED SOIL BOUNDARY		INFERRED ROCK LINE		ALLUVIAL SOIL BOUNDARY		TEST BORING		AUGER BORING		CORE BORING		MONITORING WELL		PIEZOMETER INSTALLATION		SPT N-VALUE	<p><b>ROCK HARDNESS</b></p> <table border="1"> <tr> <th>VERY HARD</th> <td>CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.</td> </tr> <tr> <th>HARD</th> <td>CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.</td> </tr> <tr> <th>MODERATELY HARD</th> <td>CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.</td> </tr> <tr> <th>MEDIUM HARD</th> <td>CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.</td> </tr> <tr> <th>SOFT</th> <td>CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.</td> </tr> <tr> <th>VERY SOFT</th> <td>CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.</td> </tr> </table>										VERY HARD	CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.	HARD	CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.	MODERATELY HARD	CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.	MEDIUM HARD	CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.	SOFT	CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.	VERY SOFT	CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.	<p><b>TEXTURE OR GRAIN SIZE</b></p> <table border="1"> <tr> <th>U.S. STD. SIEVE SIZE OPENING (MM)</th> <td>4</td> <td>10</td> <td>40</td> <td>60</td> <td>200</td> <td>270</td> </tr> <tr> <td></td> <td>4.76</td> <td>2.00</td> <td>0.42</td> <td>0.25</td> <td>0.075</td> <td>0.053</td> </tr> <tr> <th>BOULDER (BLD.)</th> <th>COBBLE (COB.)</th> <th>GRAVEL (GR.)</th> <th>COARSE SAND (CS. SD.)</th> <th>FINE SAND (F SD.)</th> <th>SILT (SL.)</th> <th>CLAY (CL.)</th> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <th>GRAIN SIZE</th> <td>MM 305</td> <td>75</td> <td>2.0</td> <td>0.25</td> <td>0.05</td> <td>0.005</td> </tr> <tr> <td></td> <td>IN. 12</td> <td>3</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>										U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270		4.76	2.00	0.42	0.25	0.075	0.053	BOULDER (BLD.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CS. SD.)	FINE SAND (F SD.)	SILT (SL.)	CLAY (CL.)								GRAIN SIZE	MM 305	75	2.0	0.25	0.05	0.005		IN. 12	3					<p><b>RECOMMENDATION SYMBOLS</b></p> <table border="1"> <tr> <td></td> <td>UNDERCUT</td> <td></td> <td>UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE</td> <td></td> <td>UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK</td> <td></td> <td>UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE USED IN THE TOP 3 FEET OF EMBANKMENT OR BACKFILL</td> </tr> </table>											UNDERCUT		UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE		UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK		UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE USED IN THE TOP 3 FEET OF EMBANKMENT OR BACKFILL	<p><b>ABBREVIATIONS</b></p> <table border="1"> <tr> <td>AR - AUGER REFUSAL</td> <td>CL - CLAY</td> <td>CPT - COARSE PENETRATION TEST</td> <td>CSE - COARSE</td> <td>DMT - DILATOMETER TEST</td> <td>DPT - DYNAMIC PENETRATION TEST</td> <td>e - VOID RATIO</td> <td>F - FINE</td> <td>FOSS. - FOSSILIFEROUS</td> <td>FRAC. - FRACTURED, FRACTURES</td> <td>FRAGS. - FRAGMENTS</td> <td>HI. - HIGHLY</td> <td>MED. - MEDIUM</td> <td>MICA. - MICACEOUS</td> <td>MOD. - MODERATELY</td> <td>NP - NON PLASTIC</td> <td>ORG. - ORGANIC</td> <td>PMT - PRESSUREMETER TEST</td> <td>SAP. - SAPROLITIC</td> <td>SD. - SAND, SANDY</td> <td>SL. - SILT, SILTY</td> <td>SLI. - SLIGHTLY</td> <td>TCR - TRICONE REFUSAL</td> <td>w - MOISTURE CONTENT</td> <td>V - VERY</td> <td>VST - VANE SHEAR TEST</td> <td>WEA. - WEATHERED</td> <td>UNIT WEIGHT</td> <td>DRY UNIT WEIGHT</td> </tr> <tr> <td colspan="10">SAMPLE ABBREVIATIONS</td> <td colspan="10"></td> </tr> <tr> <td>S - BULK</td> <td>SS - SPLIT SPOON</td> <td>ST - SHELBY TUBE</td> <td>RS - ROCK</td> <td>RT - RECOMPACTED TRIAXIAL</td> <td>CBR - CALIFORNIA BEARING RATIO</td> <td colspan="10"></td> </tr> </table>										AR - AUGER REFUSAL	CL - CLAY	CPT - COARSE PENETRATION TEST	CSE - COARSE	DMT - DILATOMETER TEST	DPT - DYNAMIC PENETRATION TEST	e - VOID RATIO	F - FINE	FOSS. - FOSSILIFEROUS	FRAC. - FRACTURED, FRACTURES	FRAGS. - FRAGMENTS	HI. - HIGHLY	MED. - MEDIUM	MICA. - MICACEOUS	MOD. - MODERATELY	NP - NON PLASTIC	ORG. - ORGANIC	PMT - PRESSUREMETER TEST	SAP. - SAPROLITIC	SD. - SAND, SANDY	SL. - SILT, SILTY	SLI. - SLIGHTLY	TCR - TRICONE REFUSAL	w - MOISTURE CONTENT	V - VERY	VST - VANE SHEAR TEST	WEA. - WEATHERED	UNIT WEIGHT	DRY UNIT WEIGHT	SAMPLE ABBREVIATIONS																				S - BULK	SS - SPLIT SPOON	ST - SHELBY TUBE	RS - ROCK	RT - RECOMPACTED TRIAXIAL	CBR - CALIFORNIA BEARING RATIO											<p><b>SOIL MOISTURE - CORRELATION OF TERMS</b></p> <table border="1"> <tr> <th>SOIL MOISTURE SCALE (ATTERBERG LIMITS)</th> <th>FIELD MOISTURE DESCRIPTION</th> <th>GUIDE FOR FIELD MOISTURE DESCRIPTION</th> </tr> <tr> <td>LL - LIQUID LIMIT</td> <td>- SATURATED - (SAT.)</td> <td>USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE</td> </tr> <tr> <td>PL - PLASTIC LIMIT</td> <td>- WET - (W)</td> <td>SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td>OM - OPTIMUM MOISTURE SHRINKAGE LIMIT</td> <td>- MOIST - (M)</td> <td>SOLID; AT OR NEAR OPTIMUM MOISTURE</td> </tr> <tr> <td>SL - SHRINKAGE LIMIT</td> <td>- DRY - (D)</td> <td>REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td> </tr> </table>										SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION	LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE	PL - PLASTIC LIMIT	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE	OM - OPTIMUM MOISTURE SHRINKAGE LIMIT	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE	SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE	<p><b>EQUIPMENT USED ON SUBJECT PROJECT</b></p> <table border="1"> <tr> <td><input type="checkbox"/> CME-45C</td> <td><input type="checkbox"/> CLAY BITS</td> <td><input type="checkbox"/> AUTOMATIC</td> <td><input type="checkbox"/> MANUAL</td> </tr> <tr> <td><input type="checkbox"/> CME-55</td> <td><input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER</td> <td colspan="2">CORE SIZE:</td> </tr> <tr> <td><input type="checkbox"/> CME-550</td> <td><input type="checkbox"/> 8" HOLLOW AUGERS</td> <td><input type="checkbox"/> -B</td> <td><input type="checkbox"/> -H</td> </tr> <tr> <td><input type="checkbox"/> VANE SHEAR TEST</td> <td><input type="checkbox"/> HARD FACED FINGER BITS</td> <td><input type="checkbox"/> -N</td> <td></td> </tr> <tr> <td><input type="checkbox"/> PORTABLE HOIST</td> <td><input type="checkbox"/> TUNG-CARBIDE INSERTS</td> <td colspan="2">HAND TOOLS:</td> </tr> <tr> <td><input type="checkbox"/></td> <td><input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER</td> <td><input type="checkbox"/> POST HOLE DIGGER</td> <td></td> </tr> <tr> <td><input type="checkbox"/></td> <td><input type="checkbox"/> TRICONE <input type="checkbox"/> STEEL TEETH</td> <td><input checked="" type="checkbox"/> HAND AUGER</td> <td></td> </tr> <tr> <td><input type="checkbox"/></td> <td><input type="checkbox"/> TRICONE <input type="checkbox"/> TUNG-CARB.</td> <td><input type="checkbox"/> SOUNDING ROD</td> <td></td> </tr> <tr> <td><input type="checkbox"/></td> <td><input type="checkbox"/> CORE BIT</td> <td><input type="checkbox"/> VANE SHEAR TEST</td> <td></td> </tr> </table>										<input type="checkbox"/> CME-45C	<input type="checkbox"/> CLAY BITS	<input type="checkbox"/> AUTOMATIC	<input type="checkbox"/> MANUAL	<input type="checkbox"/> CME-55	<input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER	CORE SIZE:		<input type="checkbox"/> CME-550	<input type="checkbox"/> 8" HOLLOW AUGERS	<input type="checkbox"/> -B	<input type="checkbox"/> -H	<input type="checkbox"/> VANE SHEAR TEST	<input type="checkbox"/> HARD FACED FINGER BITS	<input type="checkbox"/> -N		<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> TUNG-CARBIDE INSERTS	HAND TOOLS:		<input type="checkbox"/>	<input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER	<input type="checkbox"/> POST HOLE DIGGER		<input type="checkbox"/>	<input type="checkbox"/> TRICONE <input type="checkbox"/> STEEL TEETH	<input checked="" type="checkbox"/> HAND AUGER		<input type="checkbox"/>	<input type="checkbox"/> TRICONE <input type="checkbox"/> TUNG-CARB.	<input type="checkbox"/> SOUNDING ROD		<input type="checkbox"/>	<input type="checkbox"/> CORE BIT	<input type="checkbox"/> VANE SHEAR TEST		<p><b>FRACATURE SPACING</b></p> <table border="1"> <tr> <th>TERM</th> <th>SPACING</th> </tr> <tr> <td>VERY WIDE</td> <td>MORE THAN 10 FEET</td> </tr> <tr> <td>WIDE</td> <td>3 TO 10 FEET</td> </tr> <tr> <td>MODERATELY CLOSE</td> <td>1 TO 3 FEET</td> </tr> <tr> <td>CLOSE</td> <td>0.16 TO 1 FOOT</td> </tr> <tr> <td>VERY CLOSE</td> <td>LESS THAN 0.16 FEET</td> </tr> </table>										TERM	SPACING	VERY WIDE	MORE THAN 10 FEET	WIDE	3 TO 10 FEET	MODERATELY CLOSE	1 TO 3 FEET	CLOSE	0.16 TO 1 FOOT	VERY CLOSE	LESS THAN 0.16 FEET	<p><b>BEDDING</b></p> <table border="1"> <tr> <th>TERM</th> <th>THICKNESS</th> </tr> <tr> <td>VERY THICKLY BEDDED</td> <td>4 FEET</td> </tr> <tr> <td>THICKLY BEDDED</td> <td>1.5 - 4 FEET</td> </tr> <tr> <td>THINLY BEDDED</td> <td>0.16 - 1.5 FEET</td> </tr> <tr> <td>VERY THINLY BEDDED</td> <td>0.03 - 0.16 FEET</td> </tr> <tr> <td>THICKLY LAMINATED</td> <td>0.008 - 0.03 FEET</td> </tr> <tr> <td>THINLY LAMINATED</td> <td>&lt; 0.008 FEET</td> </tr> </table>										TERM	THICKNESS	VERY THICKLY BEDDED	4 FEET	THICKLY BEDDED	1.5 - 4 FEET	THINLY BEDDED	0.16 - 1.5 FEET	VERY THINLY BEDDED	0.03 - 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET	THINLY LAMINATED	< 0.008 FEET	<p><b>INDURATION</b></p> <table border="1"> <tr> <th>FRIBLE</th> <td>RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</td> </tr> <tr> <th>MODERATELY INDURATED</th> <td>GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</td> </tr> <tr> <th>INDURATED</th> <td>GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</td> </tr> <tr> <th>EXTREMELY INDURATED</th> <td>SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</td> </tr> </table>										FRIBLE	RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.	MODERATELY INDURATED	GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.	INDURATED	GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.	EXTREMELY INDURATED	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.	<p><b>BENCH MARK:</b></p> <p align="right">ELEVATION: FEET</p>										<p><b>NOTES:</b></p> <p>BORINGS LOCATED USING GPK FILED DATED 5/25/17 AND ELEVATIONS FROM TIN FILE DATED 5/30/17.</p>										<p><b>PLASTICITY</b></p> <table border="1"> <tr> <th>NON PLASTIC</th> <th>SLIGHTLY PLASTIC</th> <th>MODERATELY PLASTIC</th> <th>HIGHLY PLASTIC</th> </tr> <tr> <td>0-5</td> <td>6-15</td> <td>16-25</td> <td>26 OR MORE</td> </tr> <tr> <th>VERY LOW</th> <th>SLIGHT</th> <th>MEDIUM</th> <th>HIGH</th> </tr> <tr> <td>0-5</td> <td>6-15</td> <td>16-25</td> <td>26 OR MORE</td> </tr> </table>										NON PLASTIC	SLIGHTLY PLASTIC	MODERATELY PLASTIC	HIGHLY PLASTIC	0-5	6-15	16-25	26 OR MORE	VERY LOW	SLIGHT	MEDIUM	HIGH	0-5	6-15	16-25	26 OR MORE	<p><b>COLOR</b></p> <p>DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-BROWN). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.</p>										<p><b>INDURATION</b></p> <p>FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.</p>										<p>DATE: 8-15-14</p>									
GENERAL CLASS.	GRANULAR MATERIALS (≤ 35% PASSING #200)					SILT-CLAY MATERIALS (> 35% PASSING #200)					ORGANIC MATERIALS																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
GROUP CLASS.	A-1	A-3	A-2	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
SYMBOL																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
% PASSING #10 #40 #200	50 MX 30 MX 15 MX	50 MX 25 MX 10 MX	51 MN 35 MX 35 MX 35 MX	36 MN 36 MN 36 MN	36 MN 36 MN 36 MN	36 MN 36 MN 36 MN	36 MN 36 MN 36 MN	36 MN 36 MN 36 MN	36 MN 36 MN 36 MN	36 MN 36 MN 36 MN	36 MN 36 MN 36 MN	36 MN 36 MN 36 MN	36 MN 36 MN 36 MN	36 MN 36 MN 36 MN	36 MN 36 MN 36 MN	36 MN 36 MN 36 MN	36 MN 36 MN 36 MN	36 MN 36 MN 36 MN																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																								
MATERIAL PASSING #40 LL PI	— 6 MX	— NP	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 10 MX 11 MN																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																								
GROUP INDEX	0	0	0	4 MX	8 MX	12 MX	16 MX	NO MX	NO MX	NO MX	NO MX	NO MX	NO MX	NO MX	NO MX	NO MX	NO MX	NO MX																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																								
USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS. GRAVEL, AND SAND	FINE SAND	SILTY OR CLAYEY GRAVEL AND SAND	SILTY SOILS	CLAYEY SOILS	SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER					HIGHLY ORGANIC SOILS																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
GEN. RATING AS SUBGRADE	EXCELLENT TO GOOD					FAIR TO POOR					FAIR TO POOR	POOR	UNSATURABLE																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																													
PI OF A-7-5 SUBGROUP IS ≤ LL - 30 ; PI OF A-7-6 SUBGROUP IS > LL - 30																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
<p><b>CONSISTENCY OR DENSENESS</b></p> <table border="1"> <tr> <th>PRIMARY SOIL TYPE</th> <th>COMPACTNESS OR CONSISTENCY</th> <th>RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)</th> <th>RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT<sup>2</sup>)</th> </tr> <tr> <td>GENERALLY GRANULAR MATERIAL (NON-COHESIVE)</td> <td>VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE</td> <td>&lt; 4 4 TO 10 10 TO 30 30 TO 50 &gt; 50</td> <td>N/A</td> </tr> <tr> <td>GENERALLY SILT-CLAY MATERIAL (COHESIVE)</td> <td>VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD</td> <td>&lt; 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 &gt; 30</td> <td>&lt; 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 &gt; 4</td> </tr> </table>										PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT <sup>2</sup> )	GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	< 4 4 TO 10 10 TO 30 30 TO 50 > 50	N/A	GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30	< 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4	<p><b>MISCELLANEOUS SYMBOLS</b></p> <table border="1"> <tr> <td></td> <td>ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION</td> <td></td> <td>DIP &amp; DIP DIRECTION OF ROCK STRUCTURES</td> <td></td> <td>SOIL SYMBOL</td> <td></td> <td>ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT</td> <td></td> <td>INFERRED SOIL BOUNDARY</td> <td></td> <td>INFERRED ROCK LINE</td> <td></td> <td>ALLUVIAL SOIL BOUNDARY</td> <td></td> <td>TEST BORING</td> <td></td> <td>AUGER BORING</td> <td></td> <td>CORE BORING</td> <td></td> <td>MONITORING WELL</td> <td></td> <td>PIEZOMETER INSTALLATION</td> <td></td> <td>SPT N-VALUE</td> </tr> </table>											ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION		DIP & DIP DIRECTION OF ROCK STRUCTURES		SOIL SYMBOL		ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT		INFERRED SOIL BOUNDARY		INFERRED ROCK LINE		ALLUVIAL SOIL BOUNDARY		TEST BORING		AUGER BORING		CORE BORING		MONITORING WELL		PIEZOMETER INSTALLATION		SPT N-VALUE	<p><b>ROCK HARDNESS</b></p> <table border="1"> <tr> <th>VERY HARD</th> <td>CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.</td> </tr> <tr> <th>HARD</th> <td>CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.</td> </tr> <tr> <th>MODERATELY HARD</th> <td>CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.</td> </tr> <tr> <th>MEDIUM HARD</th> <td>CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.</td> </tr> <tr> <th>SOFT</th> <td>CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.</td> </tr> <tr> <th>VERY SOFT</th> <td>CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.</td> </tr> </table>										VERY HARD	CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.	HARD	CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.	MODERATELY HARD	CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.	MEDIUM HARD	CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.	SOFT	CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.	VERY SOFT	CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.	<p><b>TEXTURE OR GRAIN SIZE</b></p> <table border="1"> <tr> <th>U.S. STD. SIEVE SIZE OPENING (MM)</th> <td>4</td> <td>10</td> <td>40</td> <td>60</td> <td>200</td> <td>270</td> </tr> <tr> <td></td> <td>4.76</td> <td>2.00</td> <td>0.42</td> <td>0.25</td> <td>0.075</td> <td>0.053</td> </tr> <tr> <th>BOULDER (BLD.)</th> <th>COBBLE (COB.)</th> <th>GRAVEL (GR.)</th> <th>COARSE SAND (CS. SD.)</th> <th>FINE SAND (F SD.)</th> <th>SILT (SL.)</th> <th>CLAY (CL.)</th> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <th>GRAIN SIZE</th> <td>MM 305</td> <td>75</td> <td>2.0</td> <td>0.25</td> <td>0.05</td> <td>0.005</td> </tr> <tr> <td></td> <td>IN. 12</td> <td>3</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>										U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270		4.76	2.00	0.42	0.25	0.075	0.053	BOULDER (BLD.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CS. SD.)	FINE SAND (F SD.)	SILT (SL.)	CLAY (CL.)								GRAIN SIZE	MM 305	75	2.0	0.25	0.05	0.005		IN. 12	3					<p><b>RECOMMENDATION SYMBOLS</b></p> <table border="1"> <tr> <td></td> <td>UNDERCUT</td> <td></td> <td>UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE</td> <td></td> <td>UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK</td> <td></td> <td>UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE USED IN THE TOP 3 FEET OF EMBANKMENT OR BACKFILL</td> </tr> </table>											UNDERCUT		UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE		UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK		UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE USED IN THE TOP 3 FEET OF EMBANKMENT OR BACKFILL	<p><b>ABBREVIATIONS</b></p> <table border="1"> <tr> <td>AR - AUGER REFUSAL</td> <td>CL - CLAY</td> <td>CPT - COARSE PENETRATION TEST</td> <td>CSE - COARSE</td> <td>DMT - DILATOMETER TEST</td> <td>DPT - DYNAMIC PENETRATION TEST</td> <td>e - VOID RATIO</td> <td>F - FINE</td> <td>FOSS. - FOSSILIFEROUS</td> <td>FRAC. - FRACTURED, FRACTURES</td> <td>FRAGS. - FRAGMENTS</td> <td>HI. - HIGHLY</td> <td>MED. - MEDIUM</td> <td>MICA. - MICACEOUS</td> <td>MOD. - MODERATELY</td> <td>NP - NON PLASTIC</td> <td>ORG. - ORGANIC</td> <td>PMT - PRESSUREMETER TEST</td> <td>SAP. - SAPROLITIC</td> <td>SD. - SAND, SANDY</td> <td>SL. - SILT, SILTY</td> <td>SLI. - SLIGHTLY</td> <td>TCR - TRICONE REFUSAL</td> <td>w - MOISTURE CONTENT</td> <td>V - VERY</td> <td>VST - VANE SHEAR TEST</td> <td>WEA. - WEATHERED</td> <td>UNIT WEIGHT</td> <td>DRY UNIT WEIGHT</td> </tr> <tr> <td colspan="10">SAMPLE ABBREVIATIONS</td> <td colspan="10"></td> </tr> <tr> <td>S - BULK</td> <td>SS - SPLIT SPOON</td> <td>ST - SHELBY TUBE</td> <td>RS - ROCK</td> <td>RT - RECOMPACTED TRIAXIAL</td> <td>CBR - CALIFORNIA BEARING RATIO</td> <td colspan="10"></td> </tr> </table>										AR - AUGER REFUSAL	CL - CLAY	CPT - COARSE PENETRATION TEST	CSE - COARSE	DMT - DILATOMETER TEST	DPT - DYNAMIC PENETRATION TEST	e - VOID RATIO	F - FINE	FOSS. - FOSSILIFEROUS	FRAC. - FRACTURED, FRACTURES	FRAGS. - FRAGMENTS	HI. - HIGHLY	MED. - MEDIUM	MICA. - MICACEOUS	MOD. - MODERATELY	NP - NON PLASTIC	ORG. - ORGANIC	PMT - PRESSUREMETER TEST	SAP. - SAPROLITIC	SD. - SAND, SANDY	SL. - SILT, SILTY	SLI. - SLIGHTLY	TCR - TRICONE REFUSAL	w - MOISTURE CONTENT	V - VERY	VST - VANE SHEAR TEST	WEA. - WEATHERED	UNIT WEIGHT	DRY UNIT WEIGHT	SAMPLE ABBREVIATIONS																				S - BULK	SS - SPLIT SPOON	ST - SHELBY TUBE	RS - ROCK	RT - RECOMPACTED TRIAXIAL	CBR - CALIFORNIA BEARING RATIO											<p><b>SOIL MOISTURE - CORRELATION OF TERMS</b></p> <table border="1"> <tr> <th>SOIL MOISTURE SCALE (ATTERBERG LIMITS)</th> <th>FIELD MOISTURE DESCRIPTION</th> <th>GUIDE FOR FIELD MOISTURE DESCRIPTION</th> </tr> <tr> <td>LL - LIQUID LIMIT</td> <td>- SATURATED - (SAT.)</td> <td>USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE</td> </tr> <tr> <td>PL - PLASTIC LIMIT</td> <td>- WET - (W)</td> <td>SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td>OM - OPTIMUM MOISTURE SHRINKAGE LIMIT</td> <td>- MOIST - (M)</td> <td>SOLID; AT OR NEAR OPTIMUM MOISTURE</td> </tr> <tr> <td>SL - SHRINKAGE LIMIT</td> <td>- DRY - (D)</td> <td>REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td> </tr> </table>										SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION	LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE	PL - PLASTIC LIMIT	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE	OM - OPTIMUM MOISTURE SHRINKAGE LIMIT	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE	SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE	<p><b>EQUIPMENT USED ON SUBJECT PROJECT</b></p> <table border="1"> <tr> <td><input type="checkbox"/> CME-45C</td> <td><input type="checkbox"/> CLAY BITS</td> <td><input type="checkbox"/> AUTOMATIC</td> <td><input type="checkbox"/> MANUAL</td> </tr> <tr> <td><input type="checkbox"/> CME-55</td> <td><input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER</td> <td colspan="2">CORE SIZE:</td> </tr> <tr> <td><input type="checkbox"/> CME-550</td> <td><input type="checkbox"/> 8" HOLLOW AUGERS</td> <td><input type="checkbox"/> -B</td> <td><input type="checkbox"/> -H</td> </tr> <tr> <td><input type="checkbox"/> VANE SHEAR TEST</td> <td><input type="checkbox"/> HARD FACED FINGER BITS</td> <td><input type="checkbox"/> -N</td> <td></td> </tr> <tr> <td><input type="checkbox"/> PORTABLE HOIST</td> <td><input type="checkbox"/> TUNG-CARBIDE INSERTS</td> <td colspan="2">HAND TOOLS:</td> </tr> <tr> <td><input type="checkbox"/></td> <td><input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER</td> <td><input type="checkbox"/> POST HOLE DIGGER</td> <td></td> </tr> <tr> <td><input type="checkbox"/></td> <td><input type="checkbox"/> TRICONE <input type="checkbox"/> STEEL TEETH</td> <td><input checked="" type="checkbox"/> HAND AUGER</td> <td></td> </tr> <tr> <td><input type="checkbox"/></td> <td><input type="checkbox"/> TRICONE <input type="checkbox"/> TUNG-CARB.</td> <td><input type="checkbox"/> SOUNDING ROD</td> <td></td> </tr> <tr> <td><input type="checkbox"/></td> <td><input type="checkbox"/> CORE BIT</td> <td><input type="checkbox"/> VANE SHEAR TEST</td> <td></td> </tr> </table>										<input type="checkbox"/> CME-45C	<input type="checkbox"/> CLAY BITS	<input type="checkbox"/> AUTOMATIC	<input type="checkbox"/> MANUAL	<input type="checkbox"/> CME-55	<input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER	CORE SIZE:		<input type="checkbox"/> CME-550	<input type="checkbox"/> 8" HOLLOW AUGERS	<input type="checkbox"/> -B	<input type="checkbox"/> -H	<input type="checkbox"/> VANE SHEAR TEST	<input type="checkbox"/> HARD FACED FINGER BITS	<input type="checkbox"/> -N		<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> TUNG-CARBIDE INSERTS	HAND TOOLS:		<input type="checkbox"/>	<input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER	<input type="checkbox"/> POST HOLE DIGGER		<input type="checkbox"/>	<input type="checkbox"/> TRICONE <input type="checkbox"/> STEEL TEETH	<input checked="" type="checkbox"/> HAND AUGER		<input type="checkbox"/>	<input type="checkbox"/> TRICONE <input type="checkbox"/> TUNG-CARB.	<input type="checkbox"/> SOUNDING ROD		<input type="checkbox"/>	<input type="checkbox"/> CORE BIT	<input type="checkbox"/> VANE SHEAR TEST		<p><b>FRACATURE SPACING</b></p> <table border="1"> <tr> <th>TERM</th> <th>SPACING</th> </tr> <tr> <td>VERY WIDE</td> <td>MORE THAN 10 FEET</td> </tr> <tr> <td>WIDE</td> <td>3 TO 10 FEET</td> </tr> <tr> <td>MODERATELY CLOSE</td> <td>1 TO 3 FEET</td> </tr> <tr> <td>CLOSE</td> <td>0.16 TO 1 FOOT</td> </tr> <tr> <td>VERY CLOSE</td> <td>LESS THAN 0.16 FEET</td> </tr> </table>										TERM	SPACING	VERY WIDE	MORE THAN 10 FEET	WIDE	3 TO 10 FEET	MODERATELY CLOSE	1 TO 3 FEET	CLOSE	0.16 TO 1 FOOT	VERY CLOSE	LESS THAN 0.16 FEET	<p><b>BEDDING</b></p> <table border="1"> <tr> <th>TERM</th> <th>THICKNESS</th> </tr> <tr> <td>VERY THICKLY BEDDED</td> <td>4 FEET</td> </tr> <tr> <td>THICKLY BEDDED</td> <td>1.5 - 4 FEET</td> </tr> <tr> <td>THINLY BEDDED</td> <td>0.16 - 1.5 FEET</td> </tr> <tr> <td>VERY THINLY BEDDED</td> <td>0.03 - 0.16 FEET</td> </tr> <tr> <td>THICKLY LAMINATED</td> <td>0.008 - 0.03 FEET</td> </tr> <tr> <td>THINLY LAMINATED</td> <td>&lt; 0.008 FEET</td> </tr> </table>										TERM	THICKNESS	VERY THICKLY BEDDED	4 FEET	THICKLY BEDDED	1.5 - 4 FEET	THINLY BEDDED	0.16 - 1.5 FEET	VERY THINLY BEDDED	0.03 - 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET	THINLY LAMINATED	< 0.008 FEET	<p><b>INDURATION</b></p> <table border="1"> <tr> <th>FRIBLE</th> <td>RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</td> </tr> <tr> <th>MODERATELY INDURATED</th> <td>GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</td> </tr> <tr> <th>INDURATED</th> <td>GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</td> </tr> <tr> <th>EXTREMELY INDURATED</th> <td>SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</td> </tr> </table>										FRIBLE	RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.	MODERATELY INDURATED	GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.	INDURATED	GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.	EXTREMELY INDURATED	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.	<p><b>BENCH MARK:</b></p> <p align="right">ELEVATION: FEET</p>										<p><b>NOTES:</b></p> <p>BORINGS LOCATED USING GPK FILED DATED 5/25/17 AND ELEVATIONS FROM TIN FILE DATED 5/30/17.</p>																																																																																																																																																																																																																																																								
PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT <sup>2</sup> )																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																							
GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	< 4 4 TO 10 10 TO 30 30 TO 50 > 50	N/A																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																							
GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30	< 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																							
	ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION		DIP & DIP DIRECTION OF ROCK STRUCTURES		SOIL SYMBOL		ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT		INFERRED SOIL BOUNDARY		INFERRED ROCK LINE		ALLUVIAL SOIL BOUNDARY		TEST BORING		AUGER BORING		CORE BORING		MONITORING WELL		PIEZOMETER INSTALLATION		SPT N-VALUE																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																	
VERY HARD	CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																									
HARD	CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																									
MODERATELY HARD	CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																									
MEDIUM HARD	CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																									
SOFT	CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																									
VERY SOFT	CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																									
U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																				
	4.76	2.00	0.42	0.25	0.075	0.053																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																				
BOULDER (BLD.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CS. SD.)	FINE SAND (F SD.)	SILT (SL.)	CLAY (CL.)																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																				
GRAIN SIZE	MM 305	75	2.0	0.25	0.05	0.005																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																				
	IN. 12	3																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																								
	UNDERCUT		UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE		UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK		UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE USED IN THE TOP 3 FEET OF EMBANKMENT OR BACKFILL																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																			
AR - AUGER REFUSAL	CL - CLAY	CPT - COARSE PENETRATION TEST	CSE - COARSE	DMT - DILATOMETER TEST	DPT - DYNAMIC PENETRATION TEST	e - VOID RATIO	F - FINE	FOSS. - FOSSILIFEROUS	FRAC. - FRACTURED, FRACTURES	FRAGS. - FRAGMENTS	HI. - HIGHLY	MED. - MEDIUM	MICA. - MICACEOUS	MOD. - MODERATELY	NP - NON PLASTIC	ORG. - ORGANIC	PMT - PRESSUREMETER TEST	SAP. - SAPROLITIC	SD. - SAND, SANDY	SL. - SILT, SILTY	SLI. - SLIGHTLY	TCR - TRICONE REFUSAL	w - MOISTURE CONTENT	V - VERY	VST - VANE SHEAR TEST	WEA. - WEATHERED	UNIT WEIGHT	DRY UNIT WEIGHT																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
SAMPLE ABBREVIATIONS																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
S - BULK	SS - SPLIT SPOON	ST - SHELBY TUBE	RS - ROCK	RT - RECOMPACTED TRIAXIAL	CBR - CALIFORNIA BEARING RATIO																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																					
SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																								
LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																								
PL - PLASTIC LIMIT	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																								
OM - OPTIMUM MOISTURE SHRINKAGE LIMIT	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																								
SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																								
<input type="checkbox"/> CME-45C	<input type="checkbox"/> CLAY BITS	<input type="checkbox"/> AUTOMATIC	<input type="checkbox"/> MANUAL																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																							
<input type="checkbox"/> CME-55	<input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER	CORE SIZE:																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																								
<input type="checkbox"/> CME-550	<input type="checkbox"/> 8" HOLLOW AUGERS	<input type="checkbox"/> -B	<input type="checkbox"/> -H																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																							
<input type="checkbox"/> VANE SHEAR TEST	<input type="checkbox"/> HARD FACED FINGER BITS	<input type="checkbox"/> -N																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																								
<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> TUNG-CARBIDE INSERTS	HAND TOOLS:																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																								
<input type="checkbox"/>	<input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER	<input type="checkbox"/> POST HOLE DIGGER																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																								
<input type="checkbox"/>	<input type="checkbox"/> TRICONE <input type="checkbox"/> STEEL TEETH	<input checked="" type="checkbox"/> HAND AUGER																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																								
<input type="checkbox"/>	<input type="checkbox"/> TRICONE <input type="checkbox"/> TUNG-CARB.	<input type="checkbox"/> SOUNDING ROD																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																								
<input type="checkbox"/>	<input type="checkbox"/> CORE BIT	<input type="checkbox"/> VANE SHEAR TEST																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																								
TERM	SPACING																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																									
VERY WIDE	MORE THAN 10 FEET																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																									
WIDE	3 TO 10 FEET																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																									
MODERATELY CLOSE	1 TO 3 FEET																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																									
CLOSE	0.16 TO 1 FOOT																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																									
VERY CLOSE	LESS THAN 0.16 FEET																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																									
TERM	THICKNESS																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																									
VERY THICKLY BEDDED	4 FEET																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																									
THICKLY BEDDED	1.5 - 4 FEET																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																									
THINLY BEDDED	0.16 - 1.5 FEET																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																									
VERY THINLY BEDDED	0.03 - 0.16 FEET																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																									
THICKLY LAMINATED	0.008 - 0.03 FEET																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																									
THINLY LAMINATED	< 0.008 FEET																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																									
FRIBLE	RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																									
MODERATELY INDURATED	GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																									
INDURATED	GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																									
EXTREMELY INDURATED	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																									
<p><b>PLASTICITY</b></p> <table border="1"> <tr> <th>NON PLASTIC</th> <th>SLIGHTLY PLASTIC</th> <th>MODERATELY PLASTIC</th> <th>HIGHLY PLASTIC</th> </tr> <tr> <td>0-5</td> <td>6-15</td> <td>16-25</td> <td>26 OR MORE</td> </tr> <tr> <th>VERY LOW</th> <th>SLIGHT</th> <th>MEDIUM</th> <th>HIGH</th> </tr> <tr> <td>0-5</td> <td>6-15</td> <td>16-25</td> <td>26 OR MORE</td> </tr> </table>										NON PLASTIC	SLIGHTLY PLASTIC	MODERATELY PLASTIC	HIGHLY PLASTIC	0-5	6-15	16-25	26 OR MORE	VERY LOW	SLIGHT	MEDIUM	HIGH	0-5	6-15	16-25	26 OR MORE	<p><b>COLOR</b></p> <p>DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-BROWN). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.</p>										<p><b>INDURATION</b></p> <p>FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.</p>										<p>DATE: 8-15-14</p>																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																												
NON PLASTIC	SLIGHTLY PLASTIC	MODERATELY PLASTIC	HIGHLY PLASTIC																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																							
0-5	6-15	16-25	26 OR MORE																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																							
VERY LOW	SLIGHT	MEDIUM	HIGH																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																							
0-5	6-15	16-25	26 OR MORE																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																							





STATE OF NORTH CAROLINA  
DEPARTMENT OF TRANSPORTATION

ROY COOPER  
GOVERNOR

JAMES H. TROGDON, III  
SECRETARY

February 8, 2018

STATE PROJECT: 41499.1.3 (R-5020B)  
 FEDERAL PROJECT: NHP-701(33)  
 COUNTY: COLUMBUS  
 DESCRIPTION: US 701 Bypass (Madison Street - JK Powell Boulevard) from SR 1437 (Virgil Avenue) to US 74/76  
 SUBJECT: Geotechnical Report – Inventory

The Geotechnical Engineering Unit has completed a subsurface investigation for this project and presents the following inventory.

**Project Description**

This project consists of widening existing US 701 Bypass (-L-) from approximately 200 feet south of West Virgil Street (-Y17-) to approximately 1000 feet north of Government Complex Road/Campground Road (-Y33-).

A geotechnical investigation was conducted during May of 2017. Hand augers were performed by the Geotechnical Engineering Unit. Representative soil samples were collected for visual classification in the field and selected samples were submitted for laboratory analysis by the Materials and Tests Unit.

The following alignments, totaling 2.98 miles, were investigated. Subsurface plans and cross sections of these alignments are included in this report.

<u>Line</u>	<u>Stations</u>
-L-	174+79 to 289+75
-RPA-	13+47 to 20+80
-RPB-	11+30 to 14+75
-RPC-	15+00 to 24+23
-RPD-	12+20 to 15+76
-Y31-	12+25 to 17+73

**Physiography and Geology**

The project is located within the city limits of the town of Whiteville, and within the Coastal Plain Province. Clays and sands of the Tertiary Yorktown Formation overlay clays and sands of the Cretaceous Peedee Formation. The terrain is relatively flat with some low-lying wetland areas towards the north of the project. The widening project is a mixture of small businesses, school facilities, single-family homes, woods, and wetlands.

**Soils Properties**

Soils encountered during this investigation are roadway embankment, alluvial, and Undivided Coastal Plain.

Roadway Embankment soils are present along all existing roads within the project limits such as US 701 Bypass (-L-), New Smyrna Road (-Y31-), and along exit ramps (-RPA-, -RPB-, -RPC-, -RPD-). These soils primarily consist of orange, tan, and brown, moist, loose to medium dense, silty sand (A-2-4).

Alluvial soils are present along the northern portion of US 701 (-L-) where low-lying wetlands are located on both sides of the road. These soils primarily consist of light to dark gray, moist to wet, very soft to soft, silty sand (A-2-4) and soft to medium stiff, sandy silt with trace organics and wood fragments (A-4).

Undivided Coastal Plain soils are also present along the entire project corridor. These soils are characterized by gray, orange, red, moist, medium stiff to stiff, mottled, sandy silt (A-4), sandy clay (A-6), and highly plastic, silty clay (A-7-6). Plastic indices for these soils range from 31 to 64.

**Groundwater**

Groundwater measurements were taken in May 2017 during average rainfall conditions. Groundwater was absent in most borings; however, groundwater was present in 9 borings and ranged from 3.0 to 4.5 feet from the ground surface.

**Areas of Special Geotechnical Interest**

- 1) Highly Plastic Clays: Highly plastic clays (PI > 25) were encountered on the project at the following locations:



<u>Line</u>	<u>Stations</u>	<u>Offsets</u>
-L-	181+50 to 198+50	LT to RT
-L-	201+00 to 207+50	LT to RT
-L-	211+00 to 213+50	LT to RT
-L-	225+00 to 232+00	LT to RT
-L-	234+50 to 239+50	LT to RT
-L-	262+50 to 278+50	LT to RT
-L-	286+00 to 290+50	LT to RT
-RPB-	10+00 to 14+50	LT to RT
-Y31-	10+00 to 17+00	LT to RT

2) High Groundwater: The following areas exhibit groundwater within 6.0 feet of proposed grade:

<u>Line</u>	<u>Stations</u>	<u>Offsets</u>
-L-	179+00	20' RT
-L-	220+00	25' LT
-L-	229+50	60' RT
-L-	243+00	40' RT
-L-	245+00	40' RT


3) Water Wells: Water wells were noted within or in close proximity to the construction limits at the following locations:

<u>Line</u>	<u>Stations</u>	<u>Offsets</u>
-L-	220+00	100' RT
-L-	289+33	85' LT

PROJECT REFERENCE NO. <b>R-5020B</b>	SHEET NO. <b>4</b>
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
<b>INCOMPLETE PLANS</b> DO NOT USE FOR R/W ACQUISITION	
<b>DOCUMENT NOT CONSIDERED FINAL</b> UNLESS ALL SIGNATURES COMPLETED	
 <b>KCI</b> <small>Engineers • Planners • Scientists • Construction Managers</small> <small>4505 Falls of Neuse Road, Suite 400</small> <small>Raleigh, NC 27609-6270</small> <small>Phone (919) 783-9214 • Fax (919) 783-9266</small>	
 <b>SUNGATE DESIGN GROUP, P.A.</b> <small>805 JONES FRANKLIN ROAD</small> <small>RALEIGH, NORTH CAROLINA 27608</small> <small>TEL (919) 859-2243 FAX (919) 859-4258</small> <small>ENG. FIRM LICENSE NO. C-995</small>	

8/17/99  
 01-FEB-2018 07:58  
 L:\Projects\Investigation\TIP\RS020B\_GEO\_RDWY\CADD\_GEO\TECH\Plan\Prof\RS-5020B-geo.psh\_4.dgn  
 \$\$\$\$LSRNAME\$\$\$\$

REVISIONS



-TIE- POT Sta. 10+00.00 10

**BEGIN TIP PROJECT R-5020B**  
 -Y17- SB POT Sta. 10+00.00  
 BEARING AH = S 89° 53' 05.9" E  
 -TIE- PT Sta. 17+79.88 =  
 -L- POT Sta. 174+78.94

BEGIN CONSTRUCTION  
 -Y17- SB POT Sta. 11+85.00

BEGIN CONSTRUCTION  
 -TIE- POT Sta. 12+25.00

-TIE- PC Sta. 12+96.18

-TIE- PC Sta. 15+34.39

-Y17- Sta. 13+64.13 =  
 -L- Sta. 176+27.56, OS=37.5' LT

-TIE- PT Sta. 17+79.88 =  
 -L- POT Sta. 174+78.94

-L- POT Sta. 176+27.67 =  
 -Y17- POT Sta. 14+01.63



-Y17- Sta. 14+01.63 =  
 -L- Sta. 176+27.67, OS=37.5' RT



END CONSTRUCTION  
 -Y17- POT Sta. 16+15.00



-Y17- POT Sta. 17+43.78

★ SIGNAL MODIFICATION


MATCHLINE -L- STA. 180+00 SEE SHEET 5

PROJECT REFERENCE NO.	SHEET NO.
R-5020B	5
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
<b>INCOMPLETE PLANS</b> DO NOT USE FOR R/W ACQUISITION	
<b>DOCUMENT NOT CONSIDERED FINAL</b> UNLESS ALL SIGNATURES COMPLETED	
 <b>KCI</b> <small>Engineers • Planners • Scientists • Construction Managers</small> <small>4505 Falls of Neuse Road, Suite 400</small> <small>Raleigh, NC 27609-2270</small> <small>Phone (919) 783-9214 • Fax (919) 783-9266</small>	
 <b>SUNGATE DESIGN GROUP, P.A.</b> <small>905 JONES FRANKLIN ROAD</small> <small>RALEIGH, NORTH CAROLINA 27608</small> <small>TEL (919) 859-2243 FAX (919) 859-4258</small> <small>ENG FROM LICENSE NO. C-995</small>	



PROJECT REFERENCE NO. <b>R-5020B</b>	SHEET NO. <b>6</b>
R/W SHEET NO. ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
<b>INCOMPLETE PLANS</b> DO NOT USE FOR R/W ACQUISITION	
<b>DOCUMENT NOT CONSIDERED FINAL</b> UNLESS ALL SIGNATURES COMPLETED	
 <b>KCI</b> <small>Engineers • Planners • Scientists • Construction Managers</small> <small>4505 Falls of Neuse Road, Suite 400</small> <small>Raleigh, NC 27609-6270</small> <small>Phone (919) 783-9214 • Fax (919) 783-9266</small>	
 <b>SUNGATE DESIGN GROUP, P.A.</b> <small>300 JONES FRANKLIN ROAD</small> <small>RALEIGH, NORTH CAROLINA 27606</small> <small>TEL (919) 859-2243 FAX (919) 859-6258</small> <small>ENG. FIRM LICENSE NO. C-997</small>	

01-FEB-2018 07:58  
 L:\Projects\Investigation\TIP\RS020B\_GEO\_RDWY\CADD\_GEO\TECH\Plan\Prof\R-5020B-geo\_psh\_6.dgn  
 \$\$\$\$LSERNAME\$\$\$\$  
 8/17/99





REVISIONS

MATCHLINE -L- STA. 193 + 75 SEE SHEET 5


MATCHLINE -L- STA. 207 + 65 SEE SHEET 7

★ SIGNAL MODIFICATION



PROJECT REFERENCE NO. <b>R-5020B</b>	SHEET NO. <b>7</b>
R/W SHEET NO.	HYDRAULICS ENGINEER
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
<b>INCOMPLETE PLANS</b> DO NOT USE FOR R/W ACQUISITION	
<b>DOCUMENT NOT CONSIDERED FINAL</b> UNLESS ALL SIGNATURES COMPLETED	
 <small>Engineers • Planners • Scientists • Construction Managers 4505 Falls of Neuse Road, Suite 400 Raleigh, NC 27609-6270 Phone (919) 783-9214 • Fax (919) 783-9266</small>	
 <small>905 JONES FRANKLIN ROAD RALEIGH, NORTH CAROLINA 27608 TEL (919) 859-2243 FAX (919) 859-4258 ENG FROM LICENSE NO. C-995</small>	

NAD 83/NA 2011



MATCHLINE -L- STA. 207 + 65 SEE SHEET 6

MATCHLINE -L- STA. 221 + 55 SEE SHEET 8

REVISIONS

01-FEB-2018 07:58  
 L:\Projects\Investigation\TIP\RS020B\_GEO\_RDWY\CADD\_GEO\TECH\Plan\Prof\R-5020B-geo.psh\_7.dgn  
 8/17/99


NOTE: DO NOT DISTURB FENCE  
ALONG WHITEVILLE  
HIGH SCHOOL PROPERTY





PROJECT REFERENCE NO. <b>R-5020B</b>		SHEET NO. <b>10</b>	
RW SHEET NO.		HYDRAULICS ENGINEER	
ROADWAY DESIGN ENGINEER		HYDRAULICS ENGINEER	
<b>INCOMPLETE PLANS</b> DO NOT USE FOR R/W ACQUISITION			
<b>DOCUMENT NOT CONSIDERED FINAL</b> UNLESS ALL SIGNATURES COMPLETED			
<b>KCI</b> Engineers • Planners • Scientists • Construction Managers 4505 Falls of Neuse Road, Suite 400 Raleigh, NC 27609-6270 Phone (919) 783-9214 • Fax (919) 783-9266			
<b>SUNGATE DESIGN GROUP, P.A.</b> 200 JONES FRANKLIN ROAD RALEIGH, NORTH CAROLINA 27606 TEL (919) 859-2243 FAX (919) 859-4256 ENG. FROM LICENSE NO. C-499			

NAD 83/NA 2011



MATCHLINE -L- STA. 249 + 00 SEE SHEET 9

MATCHLINE -L- STA. 262 + 00 SEE SHEET 11

UNDIVIDED COASTAL PLAIN

UNDIVIDED COASTAL PLAIN

UNDIVIDED COASTAL PLAIN

UNDIVIDED COASTAL PLAIN

END CONSTRUCTION  
-Y32- PT Sta. 11+22.00  
ISBK BUS

BOJANGLES

-L- POT Sta. 254+49.38 =  
-Y32- POT Sta. 10+00.00

-L- PC Sta. 254+83.83

-Y32- Sta. 10+37.50 =  
-L- POC Sta. 254+49.38, 0S=37.5'RT

-Y32- PC Sta. 10+47.24  
BEARING BK = N 82° 35' 04.3" E



-Y32- POT Sta. 14+43.50


REVISIONS

01-FEB-2018 07:58  
 L:\Projects\Investigation\TIP\RS020B\_GEO\_RDWY\CADD\_GEO\TECH\Plan\Prof\R-5020B-geo.psh\_10.dgn  
 \$\$\$\$LSER\$\$\$\$

8/17/99

MATCHLINE -RPC- STA. 19+50 SEE SHEET 14

PROJECT REFERENCE NO. <b>R-5020B</b>	SHEET NO. <b>11</b>
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
<b>INCOMPLETE PLANS</b> DO NOT USE FOR R/W ACQUISITION	
<b>DOCUMENT NOT CONSIDERED FINAL</b> UNLESS ALL SIGNATURES COMPLETED	
 <b>KCI</b> <small>Engineers • Planners • Scientists • Construction Managers</small> <small>4505 Falls of Neuse Road, Suite 400</small> <small>Raleigh, NC 27609-6270</small> <small>Phone (919) 783-9214 • Fax (919) 783-9266</small>	
 <b>SUNGATE DESIGN GROUP, P.A.</b> <small>805 JONES FRANKLIN ROAD</small> <small>RALEIGH, NORTH CAROLINA 27608</small> <small>TEL (919) 858-2243 FAX (919) 858-4258</small> <small>ENCL FROM LICENSE NO. C-995</small>	



REVISIONS

01-FEB-2018 07:58  
 L:\Projects\Investigation\TIP\RS020B\_GEO\_RDWY\CADD\_GEO\TECH\Plan\Prof of R-5020B-geo.psh-11.dgn  
 \$\$\$\$ \$\$\$\$\$\$

FOR -L- PROFILE, SEE SHEET 19  
 FOR -ROUND1-, -ROUND2- PROFILES, SEE SHEET 23  
 FOR -RPA-, -RPB-, -RPC-, -RPD- PROFILES, SEE SHEET 24








8/17/99

01-FEB-2018 07:59  
L:\Projects\Investigation\TIP\RS0208\_GEO\_RDWY\CADD\_GEO\TECH\Plan\Prof.R-50208-geo.psh\_14.dgn  
\$\$\$\$\$

REVISIONS

NAD 83/NA 2011



PROJECT REFERENCE NO. <b>R-5020B</b>	SHEET NO. <b>14</b>
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
<b>INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION</b>	
<b>DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED</b>	
 Engineers • Planners • Scientists • Construction Managers 4505 Falls of Neuse Road, Suite 400 Raleigh, NC 27609-6270 Phone (919) 783-9214 • Fax (919) 783-9266	
 <b>SUNGATE DESIGN GROUP, P.A.</b> 805 JONES FRANKLIN ROAD RALEIGH, NORTH CAROLINA 27608 TEL (919) 858-2243 FAX (919) 858-4258 ENG. FIRM LICENSE NO. C-490	

MATCHLINE -RPC- STA. 19+50 SEE SHEET 11

-RPC- CS Sta. 18+87.25

BEGIN CONSTRUCTION  
-RPC- POC Sta. 15+00.00

N 73° 41' 39.7" E


-RPC- TS Sta. 10+82.96

-RPC- SC Sta. 12+32.96


-RPC- POT Sta. 10+00.00



6/23/16  
 I:\FEB-2016\15-45\1\PROJECT\TIP\RD020B.GEO\_RDWY\CADD\GEO\TECH\SEC\RD020B.GEO.L.XSI.dgn  
 \$\$\$\$SERIAL\$\$\$\$



6/23/16  
I:\FEB-2016\15-45\1\PROJECT\TIP\RE020B.GEO\_RDWY\CADD\_GEO\TECH\ssc\RE020B.GEO.LL.XSI.dgn



ROADWAY EMBANKMENT, ORANGE TO BROWN, LOOSE TO MEDIUM DENSE, MOIST, SILTY SAND

UNDIVIDED COASTAL PLAIN, TAN AND DARK GRAY, VERY SOFT TO SOFT, WET, SANDY SILT

ROADWAY EMBANKMENT, ORANGE TO BROWN, LOOSE TO MEDIUM DENSE, MOIST, SILTY SAND

UNDIVIDED COASTAL PLAIN, TAN AND GRAY, VERY SOFT TO SOFT, WET, SANDY SILT

ROADWAY EMBANKMENT, ORANGE-BROWN, LOOSE TO MEDIUM DENSE, MOIST, SILTY SAND

UNDIVIDED COASTAL PLAIN, TAN TO GRAY, VERY SOFT TO SOFT, WET, SANDY SILT

ROADWAY EMBANKMENT, ORANGE-BROWN, LOOSE TO MEDIUM DENSE, MOIST, SILTY SAND

UNDIVIDED COASTAL PLAIN, TAN TO GRAY, VERY SOFT TO SOFT, WET, SANDY SILT

176+90


FIAD  
05/17

SEE -Y17-  
X-SECTIONS

SEE -Y17-  
X-SECTIONS

-L-






SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C.SAND	F.SAND	SILT	CLAY	10	40	200		
S-48	50' LT	181+00	2.5-3.0	A-4(0)	20	5	2.4	57.6	19.8	20.2	100	99	50	-	-

S-48


FIAD  
05/17



6/23/16  
3-FEB-2016 15:46  
L:\Projects\Geotechnical\TIP\RE020B.GEO\RDWY\CADD.GEOTECH\ysec\RE020B.GEO.L.XSI.dgn  
\$\$\$\$\$SERIAL\$\$\$\$\$





6/23/16  
I:\FEB-2016 15-46  
L:\PROJECTS\TIP\RE020B.GEO\_RDWY\CADD.GEOTECH\ssc\RE020B.GEO.L.XSI.dgn














6/23/16  
 I:\FEB-2016\15-46\1\PROJECT\TIP\RE020B.GEO\_ROWY\CADD.GEOTECH\SEC\RE020B.GEO.L.XSI.dgn  
 \$\$\$\$SERIAL\$\$\$\$





SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C.SAND	F.SAND	SILT	CLAY	10	40	200		
S-36	20' LT	194+00	3.0-3.5	A-2-6(1)	33	13	1.2	68.9	1.6	28.3	100	100	34		1.6

S-36

FIAD  
05/17

FIAD  
05/17



I:\FEB-2016\15-46\1\PROJECT\location\TIP\RE020B.GEO\_RDWY\CADD.GEOTECH\ssc\RE020B.GEO.L.XSI.dgn  
 \$\$\$\$SERIAL\$\$\$\$













6/23/16  
I:\FEB-2016\15-46\1\PROJECT\TIP\RE020B.GEO\_ROW\Y\CADD.GEOTECH\YSC\RE020B.GEO.L.XSI.dgn



6/23/16  
I:\FEB-2016\15-46\1\PROJECT\TIP\RE020B.GEO\_ROWY\CADD.GEOTECH\ysec\RE020B.GEO.L.XSI.dgn



SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
S-33	20' LT	206+50	1.5-2.0	A-6(2)	33	14	2.2	61.0	4.4	32.3	100	99	42	-	-
S-34	20' LT	206+50	4.0-4.5	A-2-6(0)	32	12	1.8	66.5	3.4	28.3	100	100	35	-	-

S-33  
S-34


FIAD  
05/17

206+50.00


—L—



6/23/16  
3-FEB-2016 15:47  
L:\Projects\Investigation\TIP\RE020B.GEO\_ROWY\CADD.GEOTECH\ssc\RE020B.GEO.LL.XSI.dgn  
\$\$\$\$SERIAL\$\$\$\$



6/23/16  
3-FEB-2016 15:47  
L:\Projects\Investigation\TIP\RE020B.GEO\_ROW\ACADD.GEOTECH\asc\RE020B.GEO.L.XSI.dgn  
\$\$\$\$\$SERIAL\$\$\$\$\$













6/23/16  
I:\FEB-2016\15-47\1\PROJECT\TIP\RD020B.GEO\_ROWY\CADD.GEOTECH\SEC\RD020B.GEO.LL.XSI.dgn

SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C.SAND	F.SAND	SILT	CLAY	10	40	200		
S-29	25' LT	220+00	2.5-3.0	A-6(7)	29	15	7.1	44.6	23.0	28.3	100	96	65	22.7	-




-L-

6/23/16  
I:\FEB-2016\15-47  
L:\Projects\Investigation\TIP\RE020B.GEO\_RDWY\CADD.GEOTECH\ssc\RE020B.GEO.L.XSI.dgn  
\$\$\$\$\$SERIAL\$\$\$\$\$



6/23/16  
 I:\FEB-2016\15-47\Investigation\TIP\RE020B.GEO\_ROWY\CADD.GEOTECH\asc\RE020B.GEO.LL.XSI.dgn  
 \$\$\$\$SERIAL\$\$\$\$




**SOIL TEST RESULTS**

SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
S-41	50' RT	224+00	2.5-3.0	A-4(0)	26	8	2.0	62.8	6.9	28.3	100	99	40	-	-
S-42	50' RT	224+00	3.5-4.0	A-6(8)	36	22	2.4	52.9	12.3	32.3	100	99	54	19.4	-


S-41  
S-42

FIAD  
05/17

6/23/16  
3-FEB-2016 15:47  
L:\Projects\Investigation\TIP\RE020B.GEO\_RDWY\CADD.GEOTECH\ssc\RE020B.GEO.LL.XSI.dgn  
\$\$\$\$\$SERIAL\$\$\$\$\$



6/23/16  
 I:\FEB-2016\5-47  
 L:\PROJECTS\TIP\RE020B.GEO\_RDWY\CADD.GEOTECH\ysec\RE020B.GEO.L.XSI.dgn  
 \$\$\$\$SERIAL\$\$\$\$



**SOIL TEST RESULTS**



SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
S-28	42' LT	227+35	3.0-3.5	A-2-4(0)	0	NP	5.5	75.6	10.9	8.1	100	98	28	-	2.6

S-28


FIAD  
05/17

FIAD  
05/17

-L-




6/23/16  
I:\FEB-2016\15-47\1\PROJECT\TIP\RE020B.GEO\_ROWY\CADD.GEOTECH\asc\RE020B.GEO.LL.XSI.dgn






6/23/16  
I:\FEB-2016\5-47\1\PROJECT\TIP\RE020B.GEO\_RDWY\CADD.GEOTECH\ssc\RE020B.GEO.L.XSI.dgn







6/23/16  
 I:\FEB-2016\15-48\1\PROJECT\TIP\RD020B.GEO\RD020B.GEOTECH\YSC\RD020B.GEO.L.XSL.dgn  
 \$\$\$\$SERIAL\$\$\$\$



**SOIL TEST RESULTS**


SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C-SAND	F-SAND	SILT	CLAY	#10	#40	#200		
S-24	30' LT	235+00	0.5- 1.0	A-4(0)	22	3	3.4	54.9	27.5	14.1	100	99	50	-	4.3
S-25	30' LT	235+00	1.5- 2.0	A-4(0)	17	2	2.2	55.4	22.2	20.2	100	99	52	-	-
S-26	30' LT	235+00	3.0- 3.5	A-6(3)	25	11	1.8	50.5	23.4	24.2	100	99	57	22.0	-

S-24  
 S-25  
 S-26




6/23/16  
 I:\FEB-2016\15-48\1\PROJECT\TIP\RE020B.GEO\_RDWY\CADD.GEOTECH\ssc\RE020B.GEO.L.XSI.dgn  
 \$\$\$\$SERIAL\$\$\$\$

SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	#10	#40	#200		
S-44	25' RT	237+00	2.0-2.5	A-7-6(36)	52	34	0.2	12.9	32.3	54.5	100	100	97	-	-




-L-

6/23/16  
I:\FEB-2016\15-48  
L:\PROJECTS\Investigation\TIP\RE020B.GEO\_RDWY\CADD.GEOTECH\ysec\RE020B.GEO.L.XSI.dgn  
\$\$\$\$SERIAL\$\$\$\$



6/23/16  
 I:\FEB-2016\15-48\1\PROJECT\TIP\RE020B.GEO\_ROWY\CADD.GEOTECH\SEC\RE020B.GEO.L.XSI.dgn



SEE -Y30-X-SECTIONS

SEE -Y30-X-SECTIONS

ROADWAY EMBANKMENT, ORANGE-BROWN AND LIGHT GRAY, LOOSE TO MEDIUM DENSE, MOIST, SILTY SAND  
 UNDIVIDED COASTAL PLAIN, TAN, ORANGE, BROWN, LIGHT AND DARK GRAY, SOFT TO STIFF, MOIST, SANDY CLAY AND SILT

240 + 00.00

ROADWAY EMBANKMENT, ORANGE-BROWN AND LIGHT GRAY, LOOSE TO MEDIUM DENSE, MOIST, SILTY SAND

UNDIVIDED COASTAL PLAIN, TAN, ORANGE, BROWN, LIGHT AND DARK GRAY, SOFT TO STIFF, MOIST, SANDY CLAY AND SILT AND HIGHLY PLASTIC, SILTY CLAY

239 + 50.00

SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS	L.L.	P.L.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
S-21	45' LT	239+00	1.5-2.0	A-6(4)	32	16	2.8	57.0	9.9	30.3	100	99	47	-	-
S-22	45' LT	239+00	2.0-2.5	A-4(0)	0	NP	3.4	55.8	14.5	26.3	100	99	49	-	4.9
S-23	45' LT	239+00	3.0-3.5	A-7-5(75)	96	64	0.4	2.2	12.5	84.8	100	100	98	-	-

S-21  
S-22  
S-23

ROADWAY EMBANKMENT, ORANGE-BROWN AND LIGHT GRAY, LOOSE TO MEDIUM DENSE, MOIST, SILTY SAND

UNDIVIDED COASTAL PLAIN, TAN, ORANGE, BROWN, LIGHT AND DARK GRAY, SOFT TO STIFF, MOIST, SANDY CLAY AND SILT AND HIGHLY PLASTIC, SILTY CLAY


FIAD  
05/17


FIAD  
05/17

239 + 00.00

-L-

6/23/16  
I:\FEB-2016\15-48\1\PROJECT\TIP\RE020B.GEO\_RDWY\CADD.GEOTECH\ssc\RE020B.GEO.LL.XSI.dgn






SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
S-20	55' LT	243+00	4.0-4.5	A-4(0)	20	6	1.2	50.7	27.9	20.2	100	100	56	21.3	-
S-45	40' RT	243+00	2.0-2.5	A-4(0)	19	2	2.6	59.2	18.0	20.2	100	99	46	-	-


I:\FEB-2016 15-48  
 L:\PROJECTS\2016\02\02020B\GEO\RDWY\CADD\GEO\TECH\SEC\RE020B.GEO.L.XSI.dgn  
 \$\$\$\$SERIAL\$\$\$\$







6/23/16  
 I:\FEB-2016\15-48\1\PROJECT\TIP\RE020B.GEO\_RDWY\CADD.GEOTECH\ysec\RE020B.GEO.L.XSI.dgn  
 \$\$\$\$SERIAL\$\$\$\$




**SOIL TEST RESULTS**


SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C.SAND	F.SAND	SILT	CLAY	10	40	200		
S-17	60' LT	248+00	3.0-3.5	A-4(0)	0	NP	2.6	64.0	17.2	16.2	100	99	43	22.3	-



6/23/16  
I:\FEB-2016\15-48\1\PROJECT\TIP\RE020B.GEO\RDWY\CADD.GEOTECH\ysec\RE020B.GEO.L.XSI.dgn




6/23/16  
I:\FEB-2016\15-48\1\PROJECT\TIP\RE020B.GEO\RDWY\CADD.GEOTECH\ysec\RE020B.GEO.L.XSI.dgn




6/23/16  
 I:\FEB-2016\15-49  
 L:\Projects\Investigation\TIP\RE020B.GEO\_RDWY\CADD.GEOTECH\ssc\RE020B.GEO.L.XSI.dgn  
 \$\$\$SERIALNAME\$\$\$

SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C.SAND	F.SAND	SILT	CLAY	10	40	200		
S-15	50' LT	255+00	1.5-2.0	A-2-4(0)	0	NP	2.0	76.4	9.5	12.1	100	99	29	-	-
S-16	50' LT	255+00	2.5-3.0	A-2-4(0)	0	NP	1.0	86.5	6.5	6.1	100	100	19	-	-
S-47	30' RT	255+00	4.5-5.0	A-2-5(0)	0	NP	1.6	78.6	11.7	8.1	100	100	26	-	-




6/23/16  
I:\FEB-2016\15-49\1\PROJECT\location\TIP\RE020B.GEO\_RDWY\CADD.GEOTECH\ssc\RE020B.GEO.L.XSI.dgn  
\$\$\$\$SERIAL\$\$\$\$





6/23/16  
3-FEB-2016 15:49  
L:\Projects\Investigation\TIP\RE020B.GEO\RDWY\CADD.GEOTECH\asc\RE020B.GEO.L.XSI.dgn  
\$\$\$\$SERIAL\$\$\$\$



259+00.00

258+50.00

258+00.00

257+50.00

4:1

4:1

4:1

4:1

4:1

4:1

4:1

4:1

FIAD  
05/17

ROADWAY EMBANKMENT, LIGHT GRAY, VERY LOOSE TO LOOSE, MOIST, SILTY SAND

UNDIVIDED COASTAL PLAIN, GRAY-BROWN, LOOSE TO MEDIUM DENSE, MOIST, SILTY SAND

ROADWAY EMBANKMENT, LIGHT GRAY, V. LOOSE TO LOOSE, MOIST, SILTY SAND


UNDIVIDED COASTAL PLAIN, GRAY-BROWN, LOOSE TO MEDIUM DENSE, MOIST, SILTY SAND

ROADWAY EMBANKMENT, LIGHT GRAY, VERY LOOSE TO LOOSE, MOIST, SILTY SAND


UNDIVIDED COASTAL PLAIN, GRAY-BROWN, LOOSE TO MEDIUM DENSE, MOIST, SILTY SAND

ROADWAY EMBANKMENT, LIGHT GRAY, VERY LOOSE TO LOOSE, MOIST, SILTY SAND

UNDIVIDED COASTAL PLAIN, GRAY-BROWN, LOOSE TO MEDIUM DENSE, MOIST, SILTY SAND











SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C.SAND	F.SAND	SILT	CLAY	10	40	200		
S-14	40' LT	261+50	2.0-2.5	A-2-4(0)	0	NP	2.4	77.4	12.1	8.1	100	99	27	-	2.0


S-14




6/23/16  
I:\FEB-2016\15-49  
L:\Projects\Investigation\TIP\RE020B.GEO\_RDWY\CADD.GEOTECH\ssc\RE020B.GEO.L.XSI\_2ND.dgn  
\$\$\$\$\$SERIAL\$\$\$\$\$




6/23/16  
I:\FEB-2016\15-49  
L:\PROJECTS\TIP\RE020B.GEO\_RDWY\CADD.GEOTECH\ssc\RE020B.GEO.L.XSL\_2ND.dgn  
\$\$\$\$\$SERIAL\$\$\$\$\$



6/23/16  
I:\FEB-2016 15-49  
L:\PROJECTS\TIP\RE020B.GEO\_RDWY\CADD.GEOTECH\ssc\RE020B.GEO.L.XSL\_2ND.dgn  
\$\$\$\$\$SERIAL\$\$\$\$\$




6/23/16  
I:\FEB-2016 15:49  
L:\PROJECTS\TIP\RE020B.GEO\RDWY\CADD.GEOTECH\asc\RE020B.GEO.L.XSL\_2ND.dgn  
\$\$\$\$\$SERIAL\$\$\$\$\$









6/23/16  
I:\FEB-2016\15-49  
L:\PROJECTS\TIP\RE020B.GEO\_RDWY\CADD.GEOTECH\asc\RE020B.GEO.L.XSI\_2ND.dgn  
\$\$\$\$\$SERIAL\$\$\$\$\$




PROJ. REFERENCE NO.	SHEET NO.
R-5020B	71




6/23/16  
3-FEB-2016 15:49  
L:\PROJECTS\2016\20160208\20160208\TIP\RE020B.GEO\_RDWY\CADD.GEOTECH\ssc\RE020B.GEO.L.XSL\_2ND.dgn  
\$\$\$\$\$SERIAL\$\$\$\$\$






I:\FEB-2016 15:49 L:\Projects\Investigation\TIP\RE020B.GEO\RDWY\CADD.GEOTECH\ssc\RE020B.GEO.L.XSL\_2ND.dgn

6/23/16  
 I:\FEB-2016\15-49\1\PROJECT\TIP\RD020B.GEO\_ROWY\CADD.GEOTECH\YSC\RD020B.GEO.L.XSL\_2ND.dgn  
 \$\$\$\$SERIAL\$\$\$\$




SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C.SAND	F.SAND	SILT	CLAY	10	40	200		
S-5	45' RT	277+00	3.0-4.0	A-7-6(63)	79	57	0.0	6.2	25.2	68.5	100	100	97		

6/23/16  
3-FEB-2016 15:49  
L:\Projects\Investigation\TIP\RE020B.GEO\_ROW\Y\CADD.GEOTECH\asc\RE020B.GEO.L.XSL\_2ND.dgn  
\$\$\$\$\$SERIAL\$\$\$\$\$




6/23/16  
3-FEB-2016 15:49  
L:\PROJECTS\2016\20160208\20160208\TIP\RE020B.GEO\_ROW\Y\CADD.GEOTECH\YSC\RE020B.GEO.L.XSL\_2ND.DGN  
\$\$\$\$SERIAL\$\$\$\$




6/23/16  
 I:\FEB-2016\15-49\1\PROJECT\OPTION\TIP\RE020B.GEO\_ROW\Y\CADD.GEOTECH\YSC\RE020B.GEO.L.XSL\_2ND.DGN  
 \$\$\$\$SERIAL\$\$\$\$

SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C.SAND	F.SAND	SILT	CLAY	10	40	200		
S-6	55' LT	282+50	3.0-4.0	A-4(0)	21	6	0.8	60.3	16.7	22.2	100	100	44	-	3.0
S-7	55' LT	282+50	4.0-5.0	A-4(0)	19	6	2.0	59.5	14.3	24.2	100	99	43	-	-



6/23/16  
I:\FEB-2016\15-49\1\PROJECT\TIP\RD020B.GEO\RDWY\CADD.GEOTECH\ssc\RD020B.GEO.L.XSL\_2ND.dgn



284+50.00

284+00.00

283+50.00

283+00.00

4:1

4:1

FIAD  
05/17

4:1

4:1


4:1

4:1

4:1


4:1

FIAD  
05/17





6/23/16  
I:\FEB-2016\15-49\1\PROJECT\TIP\RE020B.GEO\RDWY\CADD\GEO\TECH\SEC\RE020B.GEO.L.XSL\_2ND.dgn




SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
S-4	30' RT	285+00	4.0-5.0	A-4(0)	21	5	4.8	61.9	13.1	20.2	100	98	39	-	-
S-1	75' RT	285+00	3.0-5.0	A-2-4(0)	0	NP	6.2	79.4	4.2	10.1	100	99	19	-	1.9

Ⓐ ALLUVIAL, GRAY TO DARK GRAY, LOOSE TO MED. DENSE, SILTY SAND WITH TRACE WOOD FRAGMENTS

S-4

S-1

FIAD 05/17




**SOIL TEST RESULTS**

SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	-10-	-40-	-200-		
S-3	30' RT	287+00	1.0-2.0	A-2-4(0)	0	NP	43.1	42.1	0.6	14.1	100	81	17	-	-


I:\FEB-2016 IS-49  
 L:\Projects\Investigation\TIP\RE020B.GEO\RDWY\CADD.GEOTECH\asc\RE020B.GEO.L.XSI.L2ND.dgn  
 \$\$\$\$SERIAL\$\$\$\$

6/23/16  
I:\FEB-2016\15-49\1\PROJECT\TIP\RE020B.GEO\_ROW\CAD\GEO\TECH\SEC\RE020B.GEO.L.XSL\_2ND.dgn


SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
S-2	30' RT	289+00	3.0-4.0	A-7-6(14)	53	35	1.2	52.8	7.7	38.3	100	99	52	-	-



6/23/16  
I:\FEB-2016\15-49  
L:\Projects\Investigation\TIP\RE020B.GEO\_RDWY\CADD.GEOTECH\asc\RE020B.GEO.L.XSI\_2ND.dgn  
\$\$\$\$SERIAL\$\$\$\$




6/23/16




I:\FEB-2016 15:49 L:\Projects\Investigation\TIP\RE020B.GEO\RDWY\CADD.GEOTECH\ssc\IR-5020B\_GEO\_RPA.XSI.dgn

6/23/16  
3-FEB-2016 15:49  
L:\Projects\Investigation\TIP\RD020B.GEO\RDWY\CADD.GEOTECH\ysec\IR-5020B\_GEO\_RPA.XSI.dgn  
\$\$\$\$SERIAL\$\$\$\$



6/23/16  
 I:\FEB-2016\15-49  
 L:\PROJECTS\TIP\RD020B.GEO\_RPWY\CADD.GEOTECH\ssc\IR-5020B\_GEO\_RPA.XSI.dgn  
 \$\$\$SERIALNAME\$\$\$

<b>SOIL TEST RESULTS</b>															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C.SAND	F.SAND	SILT	CLAY	10	40	200		
S-31	35' LT	17+00	4.0-4.5	A-6(1)	29	13	1.6	64.0	8.1	26.3	100	100	39	-	-




-RPA-







6/23/16  
3-FEB-2016 15:50  
L:\Projects\Investigation\TIP\RD020B.GEO\RDWY\CADD.GEOTECH\ssc\R-5020B.GEO.RPB.XSI.dgn  
\$\$\$\$\$SERIAL\$\$\$\$\$



-RPB-











6/23/16  
3-FEB-2016 15:50  
L:\PROJECTS\2016\20160208\20160208\TIP\RE020B.GEO\_ROW\Y\CADD.GEOTECH\ysec\IR-5020B.GEO\_RPC.XSI.dgn  
\$\$\$\$\$SERIAL\$\$\$\$\$



6/23/16




I:\FEB-2016 15:50  
 L:\Projects\Investigation\TIP\RP020B.GEO\RDWY\CADD.GEOTECH\ysec\IR-5020B\_GEO\_RPC.XSI.dgn  
 \$\$\$\$SERIAL\$\$\$\$



6/23/16  
I:\FEB-2016\15450\1\PROJECT\LOCATION\TIP\RE020B\_GEO\_ROW\Y\CADD\_GEO\TECH\SEC-R-5020B\_GEO\_RPC\_XSI.dgn

SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C.SAND	F.SAND	SILT	CLAY	10	40	200		
S-11	25' LT	23+00	4.0-4.5	A-4(0)	26	6	1.4	60.8	15.6	22.2	100	100	38	-	-
S-12	55' RT	23+00	0.8-1.3	A-6(3)	30	15	8.5	49.3	11.9	30.3	100	95	47	-	-
S-13	55' RT	23+00	2.0-2.5	A-4(0)	20	2	1.4	66.9	15.6	16.2	100	100	38	-	-



S-11

S-12  
S-13

FIAD  
05/17

FIAD  
05/17


23 + 00.00

22 + 50.00

-RPC-




6/23/16  
I:\FEB-2016 15:50  
L:\PROJECTS\Investigation\TIP\RD020B.GEO\_RDWY\CADD.GEOTECH\asc\R-5020B\_GEO\_RPD.XSI.dgn  
\$\$\$\$\$SERIAL\$\$\$\$\$






6/23/16  
I:\FEB-2016 15:50  
L:\Projects\Investigation\TIP\RD020B.GEO\RDWY\CADD.GEOTECH\yssc\R-5020B\_GEO\_Y31.XSI.dgn  
\$\$\$\$\$SERIAL\$\$\$\$\$



6/23/16  
I:\FEB-2016 15:50  
L:\PROJECTS\Investigation\TIP\RD020B.GEO\RDWY\CADD.GEOTECH\ssc\R-5020B.GEO.Y31.XSL.dgn  
\$\$\$\$\$SERIAL\$\$\$\$\$



SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
S-19	25' LT	13+50	2.0-2.5	A-7-6(49)	73	47	1.8	8.3	15.2	74.7	100	99	91	37.1	-



6/23/16  
3-FEB-2016 15:50  
I:\PROJECTS\ESTIMATION\TIP\RE020B\_GEO\_RDWY\CADD\_GEO\TECH\ssc\R-5020B\_GEO\_Y31.XSI.dgn  
\$\$\$\$\$SERIAL\$\$\$\$\$

