

COMPUTED BY: JCK Jan-21
 CHECKED BY: SCC Jan-21

(5-15-18)

PROJECT NO. 15614.1075010
 SHEET NO. 3G-1

**STATE OF NORTH CAROLINA
 DIVISION OF HIGHWAYS**

SUMMARY OF SUBSURFACE DRAINAGE

LINE	Station	Station	Location LT/RT/CL	Drain Type* UD/BD/SD	LF
L	453+00	461+00	RT	SD	800
L	452+00	460+75	LT	SD	875
L	463+00	468+00	LT	SD	500
L	463+00	475+00	RT	SD	1200
L	470+00	472+75	LT	SD	275
L	477+00	481+50	RT	SD	450
L	483+00	497+00	CL	SD	1400
CONTINGENCY					200
TOTAL LF:					5700

*UD = Underdrain
 *BD = Blind Drain
 *SD = Subsurface Drain

SUMMARY OF AGGREGATE SUBGRADE/STABILIZATION

LINE	Station	Station	Aggregate Type* ASU(1/2)/ AST	Aggregate Thickness INCHES [8" for ASU(2)]	Shallow Undercut CY	Class IV Subgrade Stabilization TONS	Geotextile for Soil Stabilization SY	Stabilizer Aggregate TONS	Class IV Aggregate Stabilization TONS
CONTINGENCY			1	12	100	200	500		
TOTAL CY/TONS/SY:					100	200**	500**	0	0

*ASU(1/2) = Aggregate Subgrade (Type 1 or 2)
 *AST = Aggregate Stabilization
 **Total tons of "Class IV Subgrade Stabilization" and total square yards of "Geotextile for Soil Stabilization" are only the estimated quantities for ASU(1/2)/AST and may only represent a portion of the subgrade stabilization and geotextile quantities shown in the Item Sheets of the Proposal.