


CURVE DATA FOR -Y2-

PI Sta 27+77.03 Δ = 3° 49' 11.0" (LT) D = 1° 54' 35.5" L = 200.00' T = 100.00' R = 3,000.00' Se = EXIST.	PI Sta 29+80.99 Δ = 6° 42' 23.1" (LT) D = 3° 13' 40.6" L = 207.76' T = 104.00' R = 1,775.00' Se = EXIST.	PI Sta 31+83.69 Δ = 32° 20' 34.3" (LT) D = 16° 47' 33.9" L = 192.60' T = 98.94' R = 341.19' Se = EXIST.
--	--	---

CURVE DATA FOR -L-

PI Sta 70+27.77 Δ = 15° 12' 24.7" (RT) D = 1° 03' 25.6" L = 1,438.52' T = 723.51' R = 5,420.00' Se = 0.03 Runoff = 150'	PIs Sta 77+82.77 Θs = 0° 38' 03.4" Ls = 120.00' LT = 80.00' ST = 40.00'
--	---



MATCH TO SHEET 7 - L- STA. 75 + 00.00

**CLEARING AND GRUBBING
 EROSION CONTROL FOR
 CONSTRUCTION SHEET 8**

NOTE:
 PLACE TEMPORARY ROCK SEDIMENT DAMS TYPE - B
 AND TEMPORARY ROCK SILT CHECKS TYPE - A AT
 DRAINAGE OUTLETS.