

GEOTECHNICAL ENGINEER


SEAL
029869
ENGINEER
SHANE C. CLARK

ENGINEER

DocuSigned by:
Shane C. Clark 6/2/2021


DATE: 6/2/2021

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**



RETAINING WALL QUANTITIES		
RETAINING WALL NO. 1	-WL1-	1955 SQUARE FEET
ARCHITECTURAL SURFACE TREATMENT	-WL1-	1955 SQUARE FEET

NOTE: 2 FEET EMBEEMENT IS INCLUDED IN THE QUANTITIES



PROJECT NO.: 37512.1.4 (R-2566BA)
 WATAUGA COUNTY
 STATION: 19+35.15 -Y5- TO 21+39.07 -Y5-
 SHEET 1 OF 2


**NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS**

**GEOTECHNICAL
ENGINEERING UNIT**

REVISIONS						SHEET NO. W1
NO.	BY	DATE	NO.	BY	DATE	
1			3			
2			4			

PREPARED BY: SY	DATE: 9/19/2019
REVIEWED BY: SCC	DATE: 5/20/2021

GEOTECHNICAL ENGINEER




ENGINEER

DocuSigned by:
Shane C. Clark 6/2/2021

DATE SIGNATURE DATE

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**



**SOLDIER PILE WALL WITH
CAST-IN-PLACE FACE - TYPICAL SECTION**

*SEE CONCRETE DITCH BEHIND WALL DETAILS.
**SEE PLANS FOR FINISHED GRADE OR END BENT SLOPE DETAILS.

NOTES:

FOR SOLDIER PILE RETAINING WALLS, SEE SOLDIER PILE RETAINING WALLS PROVISION.
FOR SINGLE FACED PRECAST CONCRETE BARRIER, SEE ROADWAY PLANS AND SECTION 857 OF THE STANDARD SPECIFICATIONS.

DRILLED-IN H-PILES ARE REQUIRED FOR RETAINING WALL NO. 1.
USE A SOLDIER PILE RETAINING WALL WITH A CAST-IN-PLACE REINFORCED CONCRETE FACE FOR RETAINING WALL NO. 1.

AN ASHLAR ARCHITECTURAL FINISH IS REQUIRED FOR THE CAST-IN-PLACE REINFORCED CONCRETE FACE FOR RETAINING WALL NO. 1. INCLUDE UP TO 2" OF NON STRUCTURAL CONCRETE TO ALLOW FOR SURFACE TREATMENTS.

BEFORE BEGINNING SOLDIER PILE WALL DESIGN FOR RETAINING WALL NO. 1, SURVEY WALL LOCATION AND SUBMIT A REVISED WALL PROFILE VIEW (WALL ENVELOPE) FOR REVIEW. DO NOT START WALL DESIGN OR CONSTRUCTION UNTIL THE REVISED WALL ENVELOPE IS ACCEPTED.

THE WALL HAS A PROPOSED ENDING HEIGHT OF 8' +/- . BASED ON FIELD OBSERVATIONS THIS OCCURS AT A ROCK OUTCROP. TURN THE WALL BACK INTO THE SLOPE AS DIRECTED BY THE ENGINEER.

DESIGN RETAINING WALL NO. 1 FOR THE FOLLOWING:

- 1) H = DESIGN HEIGHT + WALL EMBEDMENT
- 2) DESIGN LIFE = 75 YEARS
- 3) MINIMUM WALL EMBEDMENT ELEVATION = 2 FT
- 4) MINIMUM PILE PENETRATION INTO ROCK = 10 FT
- 5) IN-SITU ASSUMED MATERIAL PARAMETERS ABOVE ELEVATION 2760 FT:
UNIT WEIGHT, $\gamma = 120$ LB/CF
FRICTION ANGLE, $\phi = 30$ DEGREES
COHESION, $c = 0$ LB/SF
- 6) IN-SITU ASSUMED MATERIAL PARAMETERS BELOW ELEVATION 2760 FT:
UNIT WEIGHT, $\gamma = 140$ LB/CF
FRICTION ANGLE, $\phi = 36$ DEGREES
COHESION, $c = 4,000$ LB/SF
- 7) IN-SITU ASSUMED MATERIAL PARAMETERS BELOW ELEVATION 2760 FT:
ROCK MASS SHEAR STRENGTH, $S_m = 8,000$ LB/SF

PREPARED BY: SY	DATE: 9/19/2019
REVIEWED BY: SCC	DATE: 5/20/2021



**NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS**

**GEOTECHNICAL
ENGINEERING UNIT**

PROJECT NO.: 37512.1.4 (R-2566BA)
WATAUGA
STATION: 19+35.15 -Y5- TO 21+39.07 -Y5-
SHEET 2 OF 2

REVISIONS						SHEET NO. W2
NO.	BY	DATE	NO.	BY	DATE	
1			3			
2			4			

**RETAINING WALL NO. 1
SOLDIER PILE WALL**