



| | |
|--|---|
| PROJECT REFERENCE NO. R-5751 | SHEET NO. 2A-1 |
| ROADWAY DESIGN ENGINEER  | PAVEMENT DESIGN ENGINEER  |

FINAL PAVEMENT SCHEDULE

| | | | |
|--|--|----|---|
| A1 | 12" JOINTED CONCRETE TRUCK APRON | J2 | PROP. 8" AGGREGATE BASE COURSE |
| C1 | PROP. APPROX. 1.5" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 165 LBS. PER SQ. YD. | P | PRIME COAT AT AN AVERAGE RATE OF 0.35 GAL. PER SQ. YARD |
| C2 | PROP. APPROX. 2.0" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 110 LBS. PER SQ. YD. IN EACH OF TWO LAYERS. | R1 | 1'-6" CURB AND GUTTER |
| C3 | PROP. APPROX. 3.0" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 165 LBS. PER SQ. YD. IN EACH OF TWO LAYERS. | R2 | 2'-9" CURB AND GUTTER |
| C4 | PROP. VAR. ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 110 LBS. PER SQ. YD. PER 1.0" DEPTH. TO BE PLACED IN LAYERS NOT LESS THAN 1.0" IN DEPTH OR GREATER THAN 1.5" IN DEPTH. | R3 | 9" X 18" CURB |
| C5 | PROP. APPROX. 1.5" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5C, AT AN AVERAGE RATE OF 168 LBS. PER SQ. YD. | R4 | 3" CONCRETE COVER |
| C6 | PROP. APPROX. 3.0" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5C, AT AN AVERAGE RATE OF 168 LBS. PER SQ. YD. IN EACH OF TWO LAYERS. | R5 | PRECAST CONCRETE BARRIER, SINGLE FACED |
| C7 | PROP. VAR. ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5C, AT AN AVERAGE RATE OF 112 LBS. PER SQ. YD. PER 1.0" DEPTH. TO BE PLACED IN LAYERS NOT LESS THAN 1.5" IN DEPTH OR GREATER THAN 2.0" IN DEPTH. | R6 | SHOULDER BERM GUTTER |
| D1 | PROP. APPROX. 2.5" ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0C, AT AN AVERAGE RATE OF 285 LBS. PER SQ. YD. | R7 | 4" CONCRETE COVER |
| D2 | PROP. APPROX. 4.0" ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0C, AT AN AVERAGE RATE OF 456 LBS. PER SQ. YD. | T1 | EARTH MATERIAL |
| D3 | PROP. VAR. ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0C, AT AN AVERAGE RATE OF 114 LBS. PER SQ. YD. PER 1" DEPTH. TO BE PLACED IN LAYERS NOT LESS THAN 2.5" IN DEPTH OR GREATER THAN 4" IN DEPTH. | T2 | SHOULDER RECONSTRUCTION W/ AGGREGATE SHOULDER BORROW |
| E1 | PROP. APPROX. 3.0" ASPHALT CONCRETE BASE COURSE, TYPE B25.0C, AT AN AVERAGE RATE OF 342 LBS. PER SQ. YD. | U | EXISTING PAVEMENT |
| E2 | PROP. APPROX. 4.0" ASPHALT CONCRETE BASE COURSE, TYPE B25.0C, AT AN AVERAGE RATE OF 456 LBS. PER SQ. YD. | V1 | INCIDENTAL MILLING (0 TO 3.0") |
| E3 | PROP. APPROX. 7.0" ASPHALT CONCRETE BASE COURSE, TYPE B25.0C, AT AN AVERAGE RATE OF 399 LBS. PER SQ. YD. IN EACH OF TWO LAYERS. | V2 | MILLING EXISTING PAVEMENT (1.5") |
| E4 | PROP. VAR. ASPHALT CONCRETE BASE COURSE, TYPE B25.0C, AT AN AVERAGE RATE OF 114 LBS. PER SQ. YD. PER 1.0" DEPTH. TO BE PLACED IN LAYERS NOT LESS THAN 3.0" IN DEPTH OR GREATER THAN 5.5" IN DEPTH. | W1 | VARIABLE DEPTH ASPHALT PAVEMENT (SEE WEDGING DETAIL 1) |
| J1 | PROP. 6" AGGREGATE BASE COURSE | W2 | VARIABLE DEPTH ASPHALT PAVEMENT (SEE WEDGING DETAIL 2) |
| NOTE: PAVEMENT EDGES ARE 1:1 UNLESS SHOWN OTHERWISE. | | Y | RUMBLE STRIPS |

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

