



CLEARING AND GRUBBING
EROSION CONTROL FOR
CONSTRUCTION SHEET 11

NOTE: PLACE TEMPORARY ROCK SEDIMENT DAMS TYPE - B AND TEMPORARY ROCK SILT CHECKS TYPE - A AT DRAINAGE OUTLETS.

-YIC- CURVE DATA	-SRB- CURVE DATA	-DRI- CURVE DATA
PI Sta 49+05.07	PI Sta 11+17.83	PI Sta 10+47.96
$\Delta = 37^{\circ} 35' 51.9''$ (LT)	$\Delta = 50^{\circ} 28' 17.2''$ (RT)	$\Delta = 7^{\circ} 19' 02.3''$ (LT)
D = 2' 28' 10.7"	D = 22' 55' 05.9"	D = 7' 38' 22.0"
L = 1,522.39'	L = 220.22'	L = 95.78'
T = 789.74'	T = 117.83'	T = 47.96'
R = 2,320.00'	R = 250.00'	R = 750.00'
SE = 06	SE = 02	SE = NC
RO = SEE PLANS	RO = SEE PLANS	
DS = 60 MPH		

NOTES: ANY DEVIATION FROM OPTIONS GIVEN WILL REQUIRE PRIOR APPROVAL BY ENGINEER.

ADDITIONAL EROSION CONTROL DEVICES MAY NEED TO BE INSTALLED AS DIRECTED BY THE ENGINEER.

CONSTRUCT PROPOSED SPECIAL LATERAL 'V' DITCH TO BE USED AS TEMPORARY SILT DITCH DURING C&G PHASE.

MATCHLINE SHEET 6 -YIC- STA. 46+00.00

MATCHLINE SHEET 12 -YIC- STA. 57+00.00

REVISIONS
 06-SEP-2022 09:47
 C:\Users\james\Documents\Transportation\1030036026.R-5751.US.74.NC.130.Final.Design\Design\Environmental\Design\PSH\R5751_EC_PSH_EC-11.dgn
 \$\$\$USERNAME\$\$\$