

AS-BUILT REPAIR QUANTITY TABLE DECK UNDERSIDE REPAIRS SPAN D QUANTITIES **ESTIMATE** ACTUAL VOLUME AREA VOLUME AREA SHOTCRETE REPAIRS SF UNDERSIDE OF DECK 0 CONCRETE DIAPHRAGM 0.5 0.3 OVERHANG 0 CONCRETE GIRDER VOLUME VOLUME AREA CONCRETE REPAIRS CF UNDERSIDE OF DECK 0 CONCRETE DIAPHRAGM CONCRETE GIRDER 0 LINEAR LINEAR EPOXY RESIN INJECTION FT

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 2" CLEAR TO SAWCUT. SEE REPAIR

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN BASED ON THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ENTER THE ACTUAL QUANTITIES INTO THE REPAIR QUANTITY TABLE.

SHOTCRETE REPAIRS MAY BE REPLACED WITH CONCRETE REPAIRS WITH THE APPROVAL OF THE ENGINEER.

FOR SHOTCRETE REPAIRS, SEE SPECIAL PROVISIONS.

CONTRACTOR SHALL SAWCUT TO A NOMINAL DEPTH OF 1/2" BUT REINFORCING STEEL SHALL NOT BE DAMAGED.

CONTRACTOR SHALL REMOVE SURFACE CONCRETE TO VERIFY THAT SAWCUT DEPTH WILL NOT DAMAGE EXISTING REINFORCING STEEL

FOR UNDERSIDE OF DECK AND OVERHANG REPAIRS, SEE "OVERHANG, DIAPHRAGM AND BRIDGE RAIL REPAIR DETAILS" SHEET.

PRIOR TO CLEANING AND PAINTING, REPLACE AND/ OR TIGHTEN MISSING NUTS AND

PAYMENT FOR REPLACING AND/OR TIGHTENING WASHERS AND NUTS SHALL BE CONSIDERED INCIDENTAL TO VARIOUS PAY ITEMS.

SHOTCRETE REPAIR AREA

EPOXY RESIN INJECTION

TIGHTEN NUT

PROJECT NO. 15BPR.61 CHEROKEE \_ COUNTY

190010 BRIDGE NO. \_\_\_

SHEET 4 OF 5

REPLACE WASHER

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

DECK UNDERSIDE REPAIRS SPAN D

SHEET NO. REVISIONS S2-16 DATE: DATE: NO. BY: DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

A. SORSENGINH \_ DATE : 6/2022 DESIGN ENGINEER OF RECORD: . DATE : \_

12/8/2022 R:\15BPR61\Structures\FinalPlans\402\_031\_15BPR61\_SMU\_DUR\_S16\_190010.dgn