




+

GIRDER REPAIR



SHOTCRETE REPAIR AREA



EPOXY RESIN INJECTION

| DRAWN BY : | S. AGUILAR HERNANDEZ | DATE : 6/2022 | 2 |
|--------------|----------------------|---------------|---|
| CHECKED BY : | A. SORSENGINH | DATE : 6/2022 | 2 |
| DESIGN ENGIN | EER OF RECORD: | DATE : | _ |
| | | 10 (0 (0000 | |

12/8/2022 R:\15BPR61\Structures\FinalPlans\402_033_15BPR61_SMU_DUR_S17_190010.dgn ksedai

GIRDER SECTION

GIRDER DAMAGE LOCATIONS

| AS-BUILT REP | AIR QU | ANTITY | TABLE | | |
|------------------------|------------|--------------|------------|--------------|--|
| DECK UNDERSIDE REPAIRS | QUANTITIES | | | | |
| SPAN E | ESTIMATE | | ACTUAL | | |
| SHOTCRETE REPAIRS | AREA SF | VOLUME CF | AREA SF | VOLUME CF | |
| UNDERSIDE OF DECK | 0 | 0 | | | |
| CONCRETE DIAPHRAGM | 0 | 0 | | | |
| OVERHANG | 0 | 0 | | | |
| | | | | | |
| CONCRETE REPAIRS | AREA SF | VOLUME CF | AREA SF | VOLUME CF | |
| UNDERSIDE OF DECK | 0 | 0 | | | |
| CONCRETE DIAPHRAGM | 0 | 0 | | | |
| OVERHANG | 0 | 0 | | | |
| | | | | | |
| GIRDER REPAIRS | AREA SF | VOLUME CF | AREA SF | VOLUME CF | |
| GIRDER | 0.8 | 0.3 | | | |
| | | | | | |
| EPOXY COATING | AREA SF | | AREA SF | | |
| GIRDER END | 185.3 | | | | |

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 2" CLEAR TO SAWCUT. SEE REPAIR DETAILS.

NOTES

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN BASED ON THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ENTER THE ACTUAL QUANTITIES INTO THE REPAIR QUANTITY TABLE.

SHOTCRETE REPAIRS MAY BE REPLACED WITH CONCRETE REPAIRS WITH THE APPROVAL OF THE ENGINEER.

FOR SHOTCRETE REPAIRS, SEE SPECIAL PROVISIONS.

FOR EPOXY COATING CONCRETE GIRDER ENDS, SEE SPECIAL PROVISIONS.

FOR PRESTRESSED CONCRETE GIRDER REPAIR DETAILS AND LIMITS OF EPOXY COATING CONCRETE GIRDER ENDS, SEE PRESTRESSED CONCRETE GIRDER REPAIRS DETAIL SHEET.

FOR UNDERSIDE OF DECK AND OVERHANG REPAIRS, SEE "OVERHANG AND DIAPHRAGM REPAIR DETAILS" SHEET.

FOR CONCRETE REPAIRS, SEE SPECIAL PROVISIONS.

CONTRACTOR SHALL SAWCUT TO A NOMINAL DEPTH OF 1/2" BUT REINFORCING STEEL SHALL NOT BE DAMAGED.

CONTRACTOR SHALL REMOVE SURFACE CONCRETE TO VERIFY THAT SAWCUT DEPTH WILL NOT DAMAGE EXISTING REINFORCING STEEL.

| | PROJECT | Γ NO | 15 | BPR.6 | 51 |
|--|--|-------------|-----------|-------|-----------------------|
| | | HEROKI | | | UNTY |
| | BRIDGE | NO | 1 | 90010 | 9 |
| | SHEET 5 OF | 5 | | | |
| I2/12/2022 IN OR FESSION SEAL O3I583 RDER Doctorer Krishna P. Sedai EA6F794150BF4B7 | STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH DECK UNDERSIDE REPAIRS SPAN E | | | | |
| | NO. BY: | | NS BY: | DATE: | SHEET NO. S2-17 |
| DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED | 1 2 | DATE: NO. 3 | DT: | | TOTAL SHEETS 28 |