



8/17/99

PROJECT REFERENCE NO. <i>BR-0160</i>		SHEET NO. <i>2A-1</i>	
RW SHEET NO.			
ROADWAY DESIGN ENGINEER		PAVEMENT DESIGN ENGINEER	
 SEAL 040418 3/14/2023		 SEAL 022622 3/14/2023	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED			

RS&H 8521 SIX FORKS ROAD, SUITE 400
 RALEIGH, NC 27615
 NC FIRM LICENSE No: F-0493

FINAL PAVEMENT DESIGN			
A	CONCRETE WEARING SURFACE (STRUCTURE PAY ITEM)	R1	2'-6" CONCRETE CURB AND GUTTER
C1	PROP. APPROX. 1.5" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 165 LBS. PER SQ YD.	R2	4" CONCRETE ISLAND COVER
C2	PROP. APPROX. 3.0" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5C, AT AN AVERAGE RATE OF 168 LBS. PER SQ. YD. IN EACH OF TWO LAYERS.	R3	SHOULDER BERM GUTTER
D1	PROP. APPROX. 4.0" ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0C, AT AN AVERAGE RATE OF 456 LBS. PER SQ. YD.	R4	42" SLOTTED VERTICAL CONCRETE BARRIER W/ MOMENT SLAB
E1	PROP. APPROX. 4.0" ASPHALT CONCRETE BASE COURSE, TYPE B25.0C, AT AN AVERAGE RATE OF 456 LBS. PER SQ. YD.	T	EARTH MATERIAL
J1	6" AGGREGATE BASE COURSE		

NOTE: PAVEMENT EDGES ARE 1:1 UNLESS SHOWN OTHERWISE.