



**NOTE:** UTILIZE FLOATING TURBIDITY CURTAIN WHERE APPLICABLE.

**NOTE:** UTILIZE TEMPORARY SEDIMENT BASIN OR SPECIAL STILLING BASIN(S) AS STILLING BASIN WHERE APPLICABLE.

**NOTES:** ANY DEVIATION FROM OPTIONS GIVEN WILL REQUIRE PRIOR APPROVAL BY ENGINEER.

ADDITIONAL EROSION CONTROL DEVICES MAY NEED TO BE INSTALLED AS DIRECTED BY THE ENGINEER.

PLACE MATTING FOR EROSION CONTROL ON SLOPE AS WORK ALLOWS.  
-L- STA. 18+22 TO STA. 18+90 LT  
-L- STA. 18+56 TO STA. 18+90 RT

**NOTE:** UTILIZE FABRIC INSERT INLET PROTECTION DEVICES IN LIEU OF ROCK INLET SEDIMENT TRAPS, TYPE-C AS DIRECTED TO AVOID IMPOUNDMENT OF RUNOFF IN ROADWAY OPEN TO TRAFFIC.

**-L- CURVE DATA**  
PI Sta 17+29.63  
Δ = 15° 31' 34.9" (RT)  
D = 6' 52" 41.7"  
L = 225.73'  
T = 113.56'  
R = 833.00'  
SE = 06  
RO = 144'

22-FEB-2023 14:25 P:\Projects\2023\BR0160\Plan\_Sheets\BR0160\_psh\_EC-6.dgn