JECT REFERENCE NO.	SHE	ET NO.
R-5799	Sig	15.2

OVERLAP PROGRAMMING

Front Panel

Main Menu >Controller >Overlap >Overlap Parameters/Overlap Timings

Web Interface

Home >Controller >Overlap Configuration >Overlaps

Overlap Plan 1

Overlap	1	3
Туре	FYA 4 - Section	FYA 4 - Section
Included Phases	2	6
Modifier Phases	1	· —
Modifier Overlaps	÷	-
Trail Green	0	0
Trail Yellow	0.0	0.0
Trail Red	0.0	0.0

ACCESSIBLE PEDESTRIAN SIGNAL (APS) INSTALLATION NOTES

- Install push buttons and APS equipment per manufacturer's instructions.
- 2. Provide a dedicated cable to each push button per manufacturer's instructions.
- 3. If APS equipment is mounted in cabinet, use filtered power (i.e., Controller Receptacle) to power APS equipment. Do not use Equipment Receptacle, which is a GFCI outlet.
- 4. Never attempt to operate a standard contact closure push button with the APS system unless cabinet is re-wired for standard button operation or unless explicitly allowed by the manufacturer.
- 5. Place manufacturer's instructions in cabinet with cabinet prints, signal plans, and electrical details.

THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 14-1288 DESIGNED: April 2023 SEALED: April 28, 2023 REVISED: _

Electrical Detail - Sheet 2 of 2

Prepared for the Offices of:

Electrical and Programming Details For: US 64 (Hendersonville Highway) Ecusta Bypass / Store Entrance

Transylvania County April 2023 REVIEWED BY: V. Kaiser PREPARED BY: S.G. Haynie REVIEWED BY:

REVISIONS

029531 Steven G. Haynie 4/28/2023 SIG. INVENTORY NO.

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

1520 SOUTH BOULEVARD, SUITE 200 CHARLOTTE, NC 28203 (704) 752-0610