

August 25, 2021

Mindy B. Isenhour, PE

Stantec

801 Jones Franklin Road, Suite 300

Raleigh, NC 27606

Project: 34554.1.3 (R-3383C)

County: Iredell

Description: Culvert on -L- (Brawley School Road) Station 36+00.33 Over Unnamed Tributary to Reeds Creek

Subject: Culvert Foundation Recommendations

Dear Ms. Isenhour,

As authorized, Falcon Engineering Inc. (Falcon) has completed the Culvert Foundation Recommendations for the above referenced project based on current NCDOT LRFD design policy and procedures.

Foundation recommendations and notes on plans are presented in the attachments. These recommendations are based on subsurface data obtained by Falcon as presented in the Subsurface Investigation Report submitted under separate cover. Culvert geometry used in our analysis were obtained from the approved Culvert Survey and Hydraulic Design Report (CSR).

Falcon appreciates the opportunity to have provided Stantec with geotechnical engineering services. If you have any questions concerning the contents of this report or need additional information, please do not hesitate to contact our office.

Respectfully submitted:

FALCON ENGINEERING, INC.

Stephen C. Crockett, PE

Geotechnical Engineer

Jeremy R. Hamm, PE

Geotechnical Engineering Manager

Attachments: Foundation Recommendations and Notes on Plans

FOUNDATION RECOMMENDATIONS

WBS # 34554.1.3 DESCRIPTION Culvert on -L- (Brawley School Road)

T.I.P. NO. R-3383C Station 36+00.33 over Unnamed Tributary to Reeds Creek

COUNTY Iredell

DESIGN SCC 04/30/21
CHECK JRH 08/25/21
APPROVAL

STATION

36+00.33 -L-



CULVERT SIZE	STATION	FOUNDATION TYPE	EXCAVATION DEPTH	MISCELLANEOUS DETAILS
2 @ 12' x 9' Reinforced Concrete Box Culvert with Beveled Inlet, 1.0' Sill in Left (East) Barrel, 2.0' Sill in Right (West) Barrel	-L- 36+00.33	Full Concrete Invert on 3.0' Class VI Foundation Conditioning Material w/ Geotextile	3.0' below bottom of culvert	Approximate Culvert Length = 164 ft Culvert Skew = 65 degrees Culvert Invert Elevation at CL = 767.4 ft Slope = 0.854%

FOUNDATION RECOMMENDATION SPECIAL NOTES ON PLANS

- 1. EXCAVATE FOUNDATION A MINIMUM OF 3.0 FEET BELOW CULVERT BEARING ELEVATION. PLACE 3.0 FEET OF CLASS VI FOUNDATION CONDITIONING MATERIAL IN ACCORDANCE WITH SECTION 414 OF THE STANDARD SPECIFICATIONS. ENCAPSULATE FOUNDATION CONDITIONING MATERIAL WITH TYPE 2 GEOTEXTILE.
- 2. CONSTRUCT THE REINFORCED CONCRETE BOX CULVERT AT -L- STATION 36+00.33 WITH 4" OF CAMBER TO ACCOUNT FOR ANTICIPATED SETTLEMENT.

FOUNDATION RECOMMENDATION COMMENTS

- 1. Unfactored bearing pressure of culvert foundation is 2.260 ksf.
- 2. Total culvert settlement of 8 inches is anticipated.