#### PROJECT REFERENCE NO. Sig. 5.2 U-5824

# MAXTIME OVERLAP PROGRAMMING DETAIL FOR DEFAULT PHASING

Front Panel

Main Menu >Controller >Overlap >Overlap Parameters/Overlap Timings

Web Interface

Home >Controller >Overlap Configuration >Overlaps

Overlap Plan 1

Overlap	1	3
Type	FYA 4 - Section	FYA 4 - Section
Included Phases	2	6
Modifier Phases	1	5
Modifier Overlaps	ı	-
Trail Green	0	0
Trail Yellow	0.0	0.0
Trail Red	0.0	0.0

#### MAXTIME OVERLAP PROGRAMMING DETAIL FOR ALTERNATE PHASING

Front Panel

Main Menu >Controller >Overlap >Overlap Parameters/Overlap Timings

Web Interface

Home >Controller >Overlap Configuration >Overlaps

In the table view of the web interface, right click on "Overlap" in the top left corner of the table. Copy the entire contents of Overlap Plan 1. Paste Overlap Plan 1 into Overlap Plan 2. Modify Overlap Plan 2 as shown below and save changes.

Overlap Plan 2

Overlap	1	3	
Type	FYA 4 - Section	FYA 4 - Section	
Included Phases	-	-	NOTICE INCLUDED PHASE
Modifier Phases	1	5	
Modifier Overlaps	•	1	
Trail Green	0	0	
Trail Yellow	0.0	0.0	
Trail Red	0.0	0.0	

### MAXTIME DETECTOR PROGRAMMING DETAIL FOR ALTERNATE PHASING LOOPS 1A & 5A

Front Panel

Main Menu >Controller >Detector >Veh Det Plans

Web Interface

Home >Controller >Detector Configuration >Vehicle Detectors

In the table view of web interface right click on "Detector" in the top left corner of the table. Copy the entire contents of Detector Plan 1. Paste Detector Plan 1 into Detector Plan 2. Modify Detector Plan 2 as shown below and save changes.

Plan 2

	Detector	Call Phase	Delay
4	1	1	3.0
	29	0	3.0

Detector	Call Phase	Delay
15	5	3.0
31	0	3.0

# MAXTIME ALTERNATE PHASING ACTIVATION DETAIL

To run alternate phasing, select a Pattern that is programmed to run Overlap Plan 2 and Detector Plan 2. A Pattern can be selected through the scheduler or manually by changing the Operational Mode.

PHASING	OVERLAP PLAN	VEH DET PLAN
ACTIVE PLAN REQUIRED TO RUN DEFAULT PHASING	1	1
ACTIVE PLAN REQUIRED TO RUN ALTERNATE PHASING	2	2
ACTIVE PLAN REQUIRED TO RUN ALTERNATE PHASING	2	2

ALTERNATE PHASING CHANGE SUMMARY

THE FOLLOWING IS A SUMMARY OF WHAT TAKES PLACE WHEN OVERLAP PLAN 2 AND VEHICLE DETECTOR PLAN 2 ACTIVATE TO CALL THE "ALTERNATE PHASING":

OVERLAP PLAN 2: Modifies overlap included phases for heads 11 and 51 to run protected

turns only.

VEH DET PLAN 2: Disables phase 6 call on loop 1A and reduces delay time for phase 1 call on loop 1A to 3.0 seconds.

> Disables phase 2 call on loop 5A and reduces delay time for phase 5 call on loop 5A to 3.0 seconds.

## MAXTIME ALTERNATE PHASING PATTERN PROGRAMMING DETAIL

Front Panel

Main Menu >Controller >Coordination >Patterns

Web Interface

Home >Controller >Coordination >Patterns

Pattern Parameters

Pattern	Veh Det Plan	Overlap Plar
*	2	2

\*The Pattern number(s) are to be determined by the Division Traffic Engineer.

> THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 09-0345 DESIGNED: August 2023 SEALED: 9/7/2023 REVISED: N/A

Electrical Detail - Final Design - Sheet 2 of 2

ELECTRICAL AND PROGRAMMIN

US 311 (New Walkertown Road)

NC 66 (Old Hollow Road)

Forsyth County REVIEWED BY: E. Sirgany PLAN DATE: August 2023 PREPARED BY: J. Smith REVIEWED BY: REVISIONS INIT. DATE

SIGNATURES COMPLETED 018174 Edward W Sirgany 9/7/2023

**DOCUMENT NOT CONSIDERED** 

FINAL UNLESS ALL

Prepared in the Office of:



NC FIRM LICENSE No: P-0339 320 Executive Court Hillsborough, NC 27278 (919) 732–3883 (919) 732–6676 (FAX)

750 N.Greenfield Pkwy.Garner.NC 27529

SIG. INVENTORY NO. 09-0345