



**PAVEMENT MARKING SCHEDULE**

<b>THERMOPLASTIC (4", 90 MIL)</b>		<b>THERMOPLASTIC SYMBOLS</b>	
T1	WHITE EDGE LINE	↙	T70 LEFT TURN ARROW
T2	WHITE SOLID LANE LINE	↘	T71 RIGHT TURN ARROW
T5	2 FT. - 6 FT./SP WHITE MINI-SKIP	↑	T72 STRAIGHT ARROW
T13	YELLOW DOUBLE CENTER	↙↘	T73 LEFT/STRAIGHT ARROW
<b>THERMOPLASTIC (6", 90 MIL)</b>		↘↙	T74 RIGHT/STRAIGHT ARROW
T20	WHITE EDGE LINE	↘↘	T79 MERGE ARROW
T21	WHITE SOLID LANE LINE	▼▼▼	T103 YIELD LINE TRIANGLE
T22	10 FT. WHITE SKIP	<b>SNOWPLOWABLE PAVEMENT MARKERS</b>	
T23	3 FT. - 9 FT./SP WHITE MINI-SKIP	ME	YELLOW/YELLOW
T24	2 FT. - 6 FT./SP WHITE MINI-SKIP	MF	CRYSTAL RED
T30	YELLOW EDGE LINE		
T33	YELLOW DOUBLE CENTER		
<b>THERMOPLASTIC (12", 90 MIL)</b>			
T50	WHITE GORE LINE		
T52	YELLOW DIAGONAL		
<b>THERMOPLASTIC (24", 90 MIL)</b>			
T61	WHITE STOP BAR		
T62	WHITE CROSSWALK LINE		

ENGINEER TO APPROVE LOCATION OF ALL UNSIGNALIZED STOP BARS.

ALL LANE WIDTHS 12' UNLESS OTHERWISE NOTED.  
TRANSITION FROM 6" MARKINGS TO 4" MARKINGS AT THE MIDPOINT OF THE RADIUS OR STOP BAR AS APPLICABLE AT INTERSECTIONS.

PAVEMENT MARKING DETAIL