

ESTIN	MATED	SOIL	NAIL	WALL	QUANT	ITIES
RETAINING WALL NO.	SOIL NAI (SQI	L RETAINI JARE FEET)	NG WALLS	SOIL VERIFICAT	NAIL ION TESTS	SOIL NAIL PROOF TESTS
2	5,155			2		18

## NOTES:

FOR SOIL NAIL RETAINING WALLS, SEE SOIL NAIL RETAINING WALLS PROVISION.

BEFORE BEGINNING SOIL NAIL WALL DESIGN FOR RETAINING WALL NO.2,SURVEY WALL LOCATION AND SUBMIT A REVISED WALL PROFILE VIEW (WALL ENVELOPE)FOR REVIEW. DO NOT START WALL DESIGN OR CONSTRUCTION UNTIL THE REVISED WALL ENVELOPE IS ACCEPTED.

DESIGN RETAINING WALL NO.2 FOR THE FOLLOWING: 1) H = WALL HEIGHT + WALL EMBEDMENT 2) DESIGN LIFE = 100 YEARS 3) IN-SITU ASSUMED MATERIAL PARAMETERS, ELEVATION ABOVE 2638 FT:

UNIT WEIGHT,  $\gamma$  = 110 PCF FRICTION ANGLE,  $\phi$  = 25 DEGREES COHESION, c = 0 PSF

4) IN-SITU ASSUMED MATERIAL PARAMETERS, ELEVATION FROM 2623 FT TO 2638 FT: UNIT WEIGHT,  $\gamma$  = 115 PCF FRICTION ANGLE,  $\phi$  = 30 DEGREES

COHESION, c = 0 PSF5) IN-SITU ASSUMED MATERIAL PARAMETERS BELOW ELEVATION 2623 FT: UNIT WEIGHT,  $\gamma$ = 115 PCF FRICTION ANGLE,  $\phi$ = 30 DEGREES COHESION, c = 0 PSF

EXISTING OR FUTURE OBSTRUCTIONS SUCH AS FOUNDATIONS, GUARDRAIL, FENCE OR HANDRAIL POSTS, PAVEMENTS, PIPES, INLETS OR UTILITIES MAY INTERFERE WITH SOIL NAILS FOR RETAINING WALL NO.2.

PROJECT REFERENCE NO. B-5898/B-3186	SHEET NO. W-2A				
GEOTECHNICAL ENGINEER OF ESS / OF SEAL 045161					
DocuSigned by: Kyan Patrick Doyle 41B30319749E410 STGNATURE	/9/2023				
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED					
AECOM					