	(FINAL PAVEMENT DESIGN- JUNE 5,2020)
C1	PROP. APPROX. 3" ASPHALT CONCRETE SURFACE COURSE TYPE S9.5E AN AVERAGE RATE OF 165 LBS. PER SQ. YD. IN EACH OF TWO LAYE
C2	PROP. VAR. DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5 AT AN AVERAGE RATE OF 110 LBS. PER SQ. YD. PER 1" DEPTH TO PLACED IN LAYERS NOT LESS THAN 1.0" IN DEPTH OR GREATER THA 1.5" IN DEPTH.
СЗ	PROP. APPROX. 1.5" ASPHALT CONCRETE SURFACE COURSE TYPE S9. AT AN AVERAGE RATE OF 165 LBS. PER SQ. YD.
D1	PROP. APPROX. 4" ASPHALT CONCRETE INTERMEDIATE COURSE TYPE I19.0C, AT AN AVERAGE RATE OF 456 LBS. PER SQ. YD.
D2	PROP. VAR. DEPTH ASPHALT CONCRETE INTERMEDIATE COURSE, TYPI I19.OC, AT AN AVERAGE RATE OF 114 LBS. PER SQ. YD. PER 1" DEPTH TO BE PLACED IN LAYERS NOT LESS THAN 2.5" IN DEPTH OR GREATER THAN 4" IN DEPTH.
E1	PROP. APPROX. 4" ASPHALT CONCRETE BASE COURSE, TYPE B25.0C AT AN AVERAGE RATE OF 456 LBS. PER SQ. YD.
E2	PROP. VAR. DEPTH ASPHALT CONCRETE BASE COURSE, TYPE B25.OC AT AN AVERAGE RATE OF 114 LBS. PER SQ. YD. PER 1" DEPTH TO PLACED IN LAYERS NOT LESS THAN 3" IN DEPTH OR GREATER THAN 5.5" IN DEPTH.
К	12" CLASS IV SUBGRADE STABILIZATION
Ν	GEOTEXTILE FOR SUBGRADE STABILIZATION
R	GRANITE CURB
R1	2'-6" CONCRETE CURB & GUTTER
R2	1'-6" CONCRETE CURB & GUTTER
R3	5" MONOLITHIC CONCRETE ISLAND (KEYED IN)
S	4" CONCRETE SIDEWALK
Т	EARTH MATERIAL
U	EXISTING PAVEMENT
V1	MILLING ASPHALT PAVEMENT, 1.5" DEPTH
V2	INCIDENTAL MILLING
W1	VARIABLE DEPTH ASPHALT PAVEMENT (SEE WEDGING DETAIL 1)
W2	VARIABLE DEPTH ASPHALT PAVEMENT (SEE WEDGING DETAIL 2)

1/10/2023 adway/Proj/U5839\_RDY\_PSH\_TYP.dc s Anderson







