PROJECT REFERENCE NO. U-5839 Sig 3 4

OVERLAP PROGRAMMING

Front Panel

Main Menu >Controller >Overlap >Overlap Parameters/Overlap Timings

Web Interface

Home >Controller >Overlap Configuration >Overlaps

Overlap Plan 1

Overlap	1	2
Туре	FYA - 4 Section	Normal
Included Phases	2	1,8
Modifier Phases	1	4
Trail Green	0	0
Trail Yellow	0.0	0:0
Trail Red	0.0	0:0


ACCESSIBLE PEDESTRIAN SIGNAL (APS) INSTALLATION NOTES

- 1. Install push buttons and APS equipment per manufacturer's instructions.
- 2. Provide a dedicated cable to each push button per manufacturer's instructions.
- 3. If APS equipment is mounted in cabinet, use filtered power (i.e., Controller Receptacle) to power APS equipment. Do not use Equipment Receptacle, which is a GFCI outlet.
- 4. Never attempt to operate a standard contact closure push button with the APS system unless cabinet is re-wired for standard button operation or unless explicitly allowed by the manufacturer.
- 5. Place manufacturer's instructions in cabinet with cabinet prints, signal plans, and electrical details.

THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 14-0417T2 DESIGNED: Apr 2023 SEALED: 04/11/2023


REVISED: N/A

Electrical Detail - Sheet 2 of 2 Temporary Design 2 - (TMP Phase III)



US 276 (Russ Avenue) Walnut Street

Division 14 Haywood County Waynesville April 2023 REVIEWED BY: WJ Hamilton PLAN DATE: PREPARED BY: TS Popelka RKA PROJ. NO: 16085 (040) REVISIONS



SIG. INVENTORY NO. |4-04|7]

750 N.Greenfield Pkwy, Garner, NC 27529

