

SHORING NOTES

TEMPORARY SHORING NO. 1

FOR TEMPORARY SHORING AND POSITIVE PROTECTION FOR TEMPORARY SHORING, SEE PLANS AND TEMPORARY SHORING PROVISION.

DESIGN TEMPORARY SHORING FROM STATION 18+84 +/- -L-, 30 FT. LT. TO STATION 19+12 +/- -L-, 30 LT., FOR THE FOLLOWING ASSUMED SOIL PARAMETERS AND GROUNDWATER ELEVATION:

- UNIT WEIGHT OF SOIL ABOVE WATER TABLE, γ . = 120 PCF
- UNIT WEIGHT OF SOIL BELOW WATER TABLE, γ' = 60 PCF
- FRICTION ANGLE, ϕ f= 30
- COHESION, c = 0 PSF
- GROUNDWATER ELEVATION = 425 FT

BEFORE BEGINNING TEMPORARY SHORING DESIGN OR CONSTRUCTION, SURVEY EXISTING GROUND ELEVATIONS IN THE VICINITY OF SHORING LOCATIONS TO DETERMINE ACTUAL SHORING HEIGHTS.

LIMITED SUBSURFACE INFORMATION IS AVAILABLE IN THE VICINITY OF TEMPORARY SHORING FROM STATION 18+84 +/- -L-, 30 FT. LT. TO STATION 19+12 +/- -L-, 30 LT. THE INFORMATION PROVIDED FOR TEMPORARY SHORING DESIGN WAS ASSUMED AND MAY NOT BE APPLICABLE TO THE ACTUAL SITE CONDITIONS ENCOUNTERED DURING CONSTRUCTION.

AT THE CONTRACTOR'S OPTION, USE STANDARD TEMPORARY SHORING FOR TEMPORARY SHORING FROM STATION. SEE GEOTECHNICAL STANDARD DETAIL 1801.01 FOR STANDARD TEMPORARY SHORING.

DRIVEN PILING FOR TEMPORARY SHORING FROM STATION 18+84 +/- -L-, 30 FT. LT. TO STATION 19+12 +/- -L-, 30 LT. MAY NOT PENETRATE BELOW ELEVATION 418 FT. DUE TO OBSTRUCTIONS, VERY DENSE OR HARD SOIL, BOULDERS OR WEATHERED OR HARD ROCK.

TEMPORARY SHORING NO. 2

FOR TEMPORARY SHORING AND POSITIVE PROTECTION FOR TEMPORARY SHORING, SEE PLANS AND TEMPORARY SHORING PROVISION.

DESIGN TEMPORARY SHORING FROM STATION 21+43 +/- -L-, 30 FT. LT. TO STATION 21+70 +/- -L-, 30 LT., FOR THE FOLLOWING ASSUMED SOIL PARAMETERS AND GROUNDWATER ELEVATION:

- UNIT WEIGHT OF SOIL ABOVE WATER TABLE, γ . = 120 PCF
- UNIT WEIGHT OF SOIL BELOW WATER TABLE, γ' = 60 PCF
- FRICTION ANGLE, ϕ f= 30
- COHESION, c = 0 PSF
- GROUNDWATER ELEVATION = 408 FT


BEFORE BEGINNING TEMPORARY SHORING DESIGN OR CONSTRUCTION, SURVEY EXISTING GROUND ELEVATIONS IN THE VICINITY OF SHORING LOCATIONS TO DETERMINE ACTUAL SHORING HEIGHTS.

LIMITED SUBSURFACE INFORMATION IS AVAILABLE IN THE VICINITY OF TEMPORARY SHORING FROM STATION 21+43 +/- -L-, 30 FT. LT. TO STATION 21+70 +/- -L-, 30 LT. THE INFORMATION PROVIDED FOR TEMPORARY SHORING DESIGN WAS ASSUMED AND MAY NOT BE APPLICABLE TO THE ACTUAL SITE CONDITIONS ENCOUNTERED DURING CONSTRUCTION.

AT THE CONTRACTOR'S OPTION, USE STANDARD TEMPORARY SHORING FOR TEMPORARY SHORING FROM STATION. SEE GEOTECHNICAL STANDARD DETAIL 1801.01 FOR STANDARD TEMPORARY SHORING.

DRIVEN PILING FOR TEMPORARY SHORING FROM STATION 21+43 +/- -L-, 30 FT. LT. TO STATION 21+70 +/- -L-, 30 LT. MAY NOT PENETRATE BELOW ELEVATION 383 FT. DUE TO OBSTRUCTIONS, VERY DENSE OR HARD SOIL, BOULDERS OR WEATHERED OR HARD ROCK.

9/27/2023 05:14:00 109\BR-0069\TrafficControl\TCP\BR0069_tc_tmp_02.dgn gmedlin




APPROVED: *Trent Hoffman*
DocuSigned by: Trent Hoffman
008251654523404

DATE: 2/5/2024

SEAL

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED



TEMPORARY SHORING NOTES