

PROJECT REFERENCE NO. R-2577A	SHEET NO. EC-18/CONST.18
RW SHEET NO.	HYDRAULICS ENGINEER
ROADWAY DESIGN ENGINEER	

**NOTE:**  
PLACE TEMPORARY ROCK SEDIMENT DAMS TYPE - B AND TEMPORARY ROCK SILT CHECKS TYPE - A AT DRAINAGE OUTLETS.

**NOTE:**  
UTILIZE FABRIC INSERT INLET PROTECTION IN LIEU OF TYPE C INLET PROTECTION WHERE WATER MIGHT POND ON ROADWAY USED BY PUBLIC TRAFFIC.

CLEARING AND GRUBBING EROSION CONTROL FOR CONSTRUCTION SHEET 18

SHADED BACK DRAINAGE IS THE U-2579B PROJECT DRAINAGE

98 x 38 x 3  
2.0 inch Skimmer  
with 1.625 inch  
Orifice Diameter  
14 ft. weir  
ID 18.1

28 x 17 x 3  
1.5 inch Skimmer  
with 0.625 inch  
Orifice Diameter  
4 ft. weir  
(See Tiered Skimmer  
Basin Detail)  
ID 18.1

Modified Silt Basin  
Type 'B'  
28 x 17 x 3  
4 ft. weir  
(See Tiered Skimmer  
Basin Detail)  
ID 18.1

BM # 10  
N 875520 E 1660195  
-L- STA. 182 + 91.04 OFF 321.72' RT  
ELEV = 923.01'

NOTE: ALL DRIVEWAYS ARE 18' UNLESS OTHERWISE NOTED

**RK&K**  
P: (919) 378-9950  
8601 Six Forks Road, Forum 1, Suite 700  
Raleigh, North Carolina 27615-3960  
NC License No. F-0112

Engineers | Construction Managers | Planners | Scientists  
www.rk.com  
Responsive People | Creative Solutions

8/17/199  
C:\Users\jshelton\OneDrive\Documents\Projects\2577A\EC-18.dgn  
12/14/2023 10:14:11 AM

MATCHLINE -L- STA. 177 + 00 SEE SHEET 17

MATCHLINE -L- STA. 190 + 00 SEE SHEET 19

