

1) FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE GREENSBORO SIGNAL OPTIMIZATION ENGINEER AT (336) 373–2437 TO ARRANGE FOR THE CITY TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SIGNAL SYSTEM SUPERVISOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND OPERATIONAL 2) ALL NCDOT ATTACHMENT POINTS ARE 12" BELOW PHONE, UNLESS OTHERWISE NOTED, FRONT SIDE OF POLE. 3) REPLACE ENTIRE SLAB OF SIDEWALK. UTILIZE A CONCRETE MIX THAT MATCHES ADJACENT SIDEWALK.