

REFERENCE: B-5777

PROJECT: 45733

SEE SHEET 3 FOR PLAN SHEET LAYOUT
AT TIME OF INVESTIGATION

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	B-5777	1	

CONTENTS

<u>SHEET NO.</u>	<u>DESCRIPTION</u>
2	LEGEND (SOIL & ROCK)
2A	SUPPLEMENTAL LEGEND, GSITABLES
4-5	SITE PLAN

CROSS SECTIONS

<u>LINE</u>	<u>STATION</u>	<u>SHEETS</u>
-L-	15+00-30+85	6-10
-RAB1-	11+00-13+00	11
-RAB2-	11+00-12+75	12
-RPA-	14+00	13
-RPB-	14+50	14
-RPC-	12+00-14+00	15
-RPD-	15+00	16

APPENDICES

<u>APPENDIX</u>	<u>TITLE</u>	<u>SHEETS</u>
A	LABORATORY TEST RESULTS	18

ROADWAY
SUBSURFACE INVESTIGATION

COUNTY DAVIDSON
PROJECT DESCRIPTION REPLACE BRIDGE NO. 58
ON NC 109 OVER US 64

INVENTORY

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT (919) 707-6850. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO PERFORM INDEPENDENT SUBSURFACE INVESTIGATIONS AND MAKE INTERPRETATIONS AS NECESSARY TO CONFIRM CONDITIONS ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

- NOTES:
- THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.
 - BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

PERSONNEL

A. SUTTLE, P.G.

C. OSBORNE

INVESTIGATED BY ECS SOUTHEAST, LLP

DRAWN BY A. SUTTLE, P.G.

CHECKED BY M. MULLA, P.E.

SUBMITTED BY ECS SOUTHEAST, LLP

DATE JUNE 2024

Prepared in the Office of:



ECS SOUTHEAST, LLP
1812 CENTER PARK DRIVE, SUITE D
CHARLOTTE, NC 28217
(704) 525-5152 [PHONE]
(704) 357-0023 [FAX]
NC REGISTERED
ENGINEERING
FIRM # F-1078



DocuSigned by:
Amanda R. Suttle 06/12/2024
399DBE4297A499
SIGNATURE DATE

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT
SUBSURFACE INVESTIGATION
SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS

SOIL DESCRIPTION

SOIL IS CONSIDERED UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER AND YIELD LESS THAN 100 BLOWS PER FOOT ACCORDING TO THE STANDARD PENETRATION TEST (AASHTO T 208, ASTM D1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY INCLUDE THE FOLLOWING: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. FOR EXAMPLE, *VERY STIFF, GRAY, SILTY CLAY, MOIST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC, A-7-6*

SOIL LEGEND AND AASHTO CLASSIFICATION

GENERAL CLASS.	GRANULAR MATERIALS (≤ 35% PASSING #200)							SILT-CLAY MATERIALS (> 35% PASSING #200)							ORGANIC MATERIALS				
	A-1	A-1-b	A-2	A-2-4	A-2-5	A-2-6	A-2-7	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7				
GROUP CLASS.	A-1-a	A-1-b	A-2	A-2-4	A-2-5	A-2-6	A-2-7	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7				
SYMBOL																			
% PASSING #10 #40 #200	50 MX 30 MX 15 MX	50 MX 25 MX	51 MN 35 MX	40 MX 35 MX	41 MN 35 MX	42 MN 35 MX	43 MN 35 MX	36 MN	37 MN	38 MN	39 MN	40 MN	41 MN	42 MN	43 MN				
MATERIAL PASSING #40 LL PI	-	-	40 MX 10 MN	41 MN 10 MN	42 MN 11 MN	43 MN 11 MN	44 MN 11 MN	40 MX 10 MN	41 MN 11 MN	42 MN 11 MN	43 MN 11 MN								
GROUP INDEX	0	0	0	4 MX	8 MX	12 MX	16 MX	NO MX											
USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS. GRAVEL, AND SAND	FINE SAND	SILTY OR CLAYEY GRAVEL AND SAND	SILTY SOILS	CLAYEY SOILS														
GEN. RATING AS SUBGRADE	EXCELLENT TO GOOD							FAIR TO POOR				FAIR TO POOR	POOR	UNSATURABLE					

PI OF A-7-5 SUBGROUP IS ≤ LL - 30; PI OF A-7-6 SUBGROUP IS > LL - 30

CONSISTENCY OR DENSENESS

PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT ²)
GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	< 4 4 TO 10 10 TO 30 30 TO 50 > 50	N/A
GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30	< 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4

TEXTURE OR GRAIN SIZE

U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270
	4.76	2.00	0.42	0.25	0.075	0.053
BOULDER (BLDR.)						
COBBLE (COB.)						
GRAVEL (GR.)						
COARSE SAND (CS, SD.)						
FINE SAND (F SD.)						
SILT (SL.)						
CLAY (CL.)						
GRAIN SIZE	305	75	2.0	0.25	0.05	0.005
MM						
IN.	12	3				

SOIL MOISTURE - CORRELATION OF TERMS

SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION
LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE
PLASTIC RANGE (PI)	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE
OM - OPTIMUM MOISTURE SHRINKAGE LIMIT	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE
SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE

PLASTICITY

	PLASTICITY INDEX (PI)	DRY STRENGTH
NON PLASTIC	0-5	VERY LOW
SLIGHTLY PLASTIC	6-15	SLIGHT
MODERATELY PLASTIC	16-25	MEDIUM
HIGHLY PLASTIC	26 OR MORE	HIGH

COLOR

DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-GRAY). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.

GRADATION

WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE.
UNIFORMLY GRADED - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE.
GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES.

ANGULARITY OF GRAINS

THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS IS DESIGNATED BY THE TERMS: ANGULAR, SUBANGULAR, SUBROUNDED, OR ROUNDED.

MINERALOGICAL COMPOSITION

MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHEN THEY ARE CONSIDERED OF SIGNIFICANCE.

COMPRESSIBILITY

SLIGHTLY COMPRESSIBLE LL < 31
MODERATELY COMPRESSIBLE LL = 31 - 50
HIGHLY COMPRESSIBLE LL > 50

PERCENTAGE OF MATERIAL

	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL
TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE 1 - 10%
LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE 10 - 20%
MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME 20 - 35%
HIGHLY ORGANIC	> 10%	> 20%	HIGHLY 35% AND ABOVE

GROUND WATER

- WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING
- STATIC WATER LEVEL AFTER 24 HOURS
- PERCHED WATER, SATURATED ZONE, OR WATER BEARING STRATA
- SPRING OR SEEP

MISCELLANEOUS SYMBOLS

- ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION
- SOIL SYMBOL
- ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT
- INFERRED SOIL BOUNDARY
- INFERRED ROCK LINE
- ALLUVIAL SOIL BOUNDARY
- DIP & DIP DIRECTION OF ROCK STRUCTURES
- SPT TEST BORING
- AUGER BORING
- CORE BORING
- MONITORING WELL
- PIEZOMETER INSTALLATION
- SLOPE INDICATOR INSTALLATION
- CONE PENETROMETER TEST
- SOUNDING ROD
- TEST BORING WITH CORE
- SPT N-VALUE

RECOMMENDATION SYMBOLS

- UNDERCUT
- SHALLOW UNDERCUT
- UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE
- UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK
- UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE USED IN THE TOP 3 FEET OF EMBANKMENT OR BACKFILL

ABBREVIATIONS

- AR - AUGER REFUSAL
- BT - BORING TERMINATED
- CL - CLAY
- CPT - COARSE PENETRATION TEST
- CSE - COARSE
- DMT - DILATOMETER TEST
- DPT - DYNAMIC PENETRATION TEST
- e - VOID RATIO
- F - FINE
- FOSS. - FOSSILIFEROUS
- FRAC. - FRACTURED, FRACTURES
- FRAGS. - FRAGMENTS
- HI. - HIGHLY
- MED. - MEDIUM
- MICA - MICACEOUS
- MOD. - MODERATELY
- NP - NON PLASTIC
- ORG. - ORGANIC
- PMT - PRESSUREMETER TEST
- SAP. - SAPROLITIC
- SD. - SAND, SANDY
- SL. - SILTY, SILTY
- SLI. - SLIGHTLY
- TCR - TRICONE REFUSAL
- w - MOISTURE CONTENT
- V - VERY
- VST - VANE SHEAR TEST
- WEA. - WEATHERED
- W - UNIT WEIGHT
- W_d - DRY UNIT WEIGHT
- S - BULK
- SS - SPLIT SPOON
- ST - SHELBY TUBE
- RS - ROCK
- RT - RECOMPACTED TRIAXIAL
- CBR - CALIFORNIA BEARING RATIO

EQUIPMENT USED ON SUBJECT PROJECT

- DRILL UNITS:
 - CME-45C
 - CME-55
 - CME-750X
 - VANE SHEAR TEST
 - PORTABLE HOIST
 - DIEDRICH D-70
- ADVANCING TOOLS:
 - CLAY BITS
 - 6" CONTINUOUS FLIGHT AUGER
 - 8" HOLLOW AUGERS
 - HARD FACED FINGER BITS
 - TUNG-CARBIDE INSERTS
 - CASING
 - W/ ADVANCER
 - TRICONE * STEEL TEETH
 - TRICONE * TUNG-CARB.
 - CORE BIT
- HAMMER TYPE:
 - AUTOMATIC
 - MANUAL
- CORE SIZE:
 - B
 - H
 - N 02
- HAND TOOLS:
 - POST HOLE DIGGER
 - HAND AUGER
 - SOUNDING ROD
 - VANE SHEAR TEST

ROCK DESCRIPTION

HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED, AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS IN NON-COASTAL PLAIN MATERIAL. THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:

- WEATHERED ROCK (WR) - NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT N VALUES > 100 BLOWS PER FOOT IF TESTED.
- CRYSTALLINE ROCK (CR) - FINE TO COARSE GRAIN IGNEOUS AND METAMORPHIC ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES GRANITE, GNEISS, GABBRO, SCHIST, ETC.
- NON-CRYSTALLINE ROCK (NCR) - FINE TO COARSE GRAIN METAMORPHIC AND NON-COASTAL PLAIN SEDIMENTARY ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES PHYLLITE, SLATE, SANDSTONE, ETC.
- COASTAL PLAIN SEDIMENTARY ROCK (CP) - COASTAL PLAIN SEDIMENTS CEMENTED INTO ROCK, BUT MAY NOT YIELD SPT REFUSAL. ROCK TYPE INCLUDES LIMESTONE, SANDSTONE, CEMENTED SHELL BEDS, ETC.

WEATHERING

- FRESH** - ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING. ROCK RINGS UNDER HAMMER IF CRYSTALLINE.
- VERY SLIGHT (V SL.)** - ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN. CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF OF A CRYSTALLINE NATURE.
- SLIGHT (SL.)** - ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO 1 INCH. OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR CRYSTALS ARE DULL AND DISCOLORED. CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS.
- MODERATE (MOD.)** - SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY. ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED WITH FRESH ROCK.
- MODERATELY SEVERE (MOD. SEV.)** - ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK. ROCK GIVES "CLUNK" SOUND WHEN STRUCK. *IF TESTED, WOULD YIELD SPT REFUSAL*
- SEVERE (SEV.)** - ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC CLEAR AND EVIDENT BUT REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN. *IF TESTED, WOULD YIELD SPT N VALUES > 100 BPF*
- VERY SEVERE (V SEV.)** - ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC ELEMENTS ARE DISCERNIBLE BUT MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK REMAINING. SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE THAT ONLY MINOR VESTIGES OF ORIGINAL ROCK FABRIC REMAIN. *IF TESTED, WOULD YIELD SPT N VALUES < 100 BPF*
- COMPLETE** - ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. FABRIC MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.

ROCK HARDNESS

- VERY HARD** - CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.
- HARD** - CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.
- MODERATELY HARD** - CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.
- MEDIUM HARD** - CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.
- SOFT** - CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.
- VERY SOFT** - CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.

FRACTURE SPACING

TERM	SPACING	TERM	THICKNESS
VERY WIDE	MORE THAN 10 FEET	VERY THICKLY BEDDED	4 FEET
WIDE	3 TO 10 FEET	THICKLY BEDDED	1.5 - 4 FEET
MODERATELY CLOSE	1 TO 3 FEET	THINLY BEDDED	0.16 - 1.5 FEET
CLOSE	0.16 TO 1 FOOT	VERY THINLY BEDDED	0.03 - 0.16 FEET
VERY CLOSE	LESS THAN 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET
		THINLY LAMINATED	< 0.008 FEET

INDURATION

- FRIABLE** - RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.
- MODERATELY INDURATED** - GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.
- INDURATED** - GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.
- EXTREMELY INDURATED** - SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.

TERMS AND DEFINITIONS

- ALLUVIUM (ALLUV.)** - SOILS THAT HAVE BEEN TRANSPORTED BY WATER.
- AQUIFER** - A WATER BEARING FORMATION OR STRATA.
- ARENACEOUS** - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND.
- ARGILLACEOUS** - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC.
- ARTESIAN** - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE.
- CALCAREOUS (CALC.)** - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE.
- COLLUVIUM** - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE.
- CORE RECOVERY (REC.)** - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.
- DIKE** - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK.
- DIP** - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL.
- DIP DIRECTION (DIP AZIMUTH)** - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH.
- FAULT** - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE.
- FISSILE** - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES.
- FLOAT** - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLODGED FROM PARENT MATERIAL.
- FLOOD PLAIN (FP)** - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM.
- FORMATION (FM.)** - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD.
- JOINT** - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED.
- LEDGE** - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT.
- LENS** - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS.
- MOTTLED (MOT.)** - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS. MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE.
- PERCHED WATER** - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM.
- RESIDUAL (RES.) SOIL** - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK.
- ROCK QUALITY DESIGNATION (RQD)** - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.
- SAPROLITE (SAP.)** - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK.
- SILL** - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS.
- SLICKENSIDE** - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE.
- STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT)** - NUMBER OF BLOWS (N OR BPF) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS.
- STRATA CORE RECOVERY (SREC.)** - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE.
- STRATA ROCK QUALITY DESIGNATION (SROD)** - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE.
- TOPSOIL (TS.)** - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.

BENCH MARK:

BM-1 (N737693 E1673323)
STA. 23+07, I21' RT ELEVATION: 779.6 FEET

NOTES:

- ROADWAY DESIGN FILES, .DTM FILE PROVIDED BY NCDOT.
- NORTHING AND EASTINGS OBTAINED USING A TRIMBLE GEO7X.
- ELEVATIONS FOR BRIDGE BORINGS OBTAINED USING BENCHMARK BM-1 (N737693 E1673323)
- FIAD = FILLED IMMEDIATELY AFTER DRILLING

**NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT**

SUBSURFACE INVESTIGATION

**SUPPLEMENTAL LEGEND, GEOLOGICAL STRENGTH INDEX (GSI) TABLES
FROM AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS**

AASHTO LRFD Figure 10.4.6.4-1 — Determination of GSI for Jointed Rock Mass (Marinos and Hoek, 2000)

AASHTO LRFD Figure 10.4.6.4-2 — Determination of GSI for Tectonically Deformed Heterogeneous Rock Masses (Marinos and Hoek, 2000)


<p>GEOLOGICAL STRENGTH INDEX (GSI) FOR JOINTED ROCKS (Hoek and Marinos, 2000)</p> <p>From the lithology, structure and surface conditions of the discontinuities, estimate the average value of GSI. Do not try to be too precise. Quoting a range from 33 to 37 is more realistic than stating that GSI = 35. Note that the table does not apply to structurally controlled failures. Where weak planar structural planes are present in an unfavorable orientation with respect to the excavation face, these will dominate the rock mass behaviour. The shear strength of surfaces in rocks that are prone to deterioration as a result of changes in moisture content will be reduced if water is present. When working with rocks in the fair to very poor categories, a shift to the right may be made for wet conditions. Water pressure is dealt with by effective stress analysis.</p> <p>STRUCTURE</p>	<p>SURFACE CONDITIONS</p>	<p>VERY GOOD Very rough, fresh unweathered surfaces</p>	<p>GOOD Rough, slightly weathered, iron stained surfaces</p>	<p>FAIR Smooth, moderately weathered and altered surfaces</p>	<p>POOR Slickensided, highly weathered surfaces with compact coatings or fillings or angular fragments</p>	<p>VERY POOR Slickensided, highly weathered surfaces with soft clay coatings or fillings</p>													
<p>INTACT OR MASSIVE - intact rock specimens or massive in situ rock with few widely spaced discontinuities</p> <p>BLOCKY - well interlocked undisturbed rock mass consisting of cubical blocks formed by three intersecting discontinuity sets</p> <p>VERY BLOCKY - interlocked, partially disturbed mass with multi-faceted angular blocks formed by 4 or more joint sets</p> <p>BLOCKY/DISTURBED/SEAMY - folded with angular blocks formed by many intersecting discontinuity sets. Persistence of bedding planes or schistosity</p> <p>DISINTEGRATED - poorly interlocked, heavily broken rock mass with mixture of angular and rounded rock pieces</p> <p>LAMINATED/SHEARED - Lack of blockiness due to close spacing of weak schistosity or shear planes</p>	<p>DECREASING INTERLOCKING OF ROCK PIECES</p>	<p>DECREASING SURFACE QUALITY</p>																	
<p>COMPOSITION AND STRUCTURE</p> <p>A. Thick bedded, very blocky sandstone The effect of pelitic coatings on the bedding planes is minimized by the confinement of the rock mass. In shallow tunnels or slopes these bedding planes may cause structurally controlled instability.</p> <p>B. Sandstone with thin inter-layers of siltstone</p> <p>C. Sandstone and siltstone in similar amounts</p> <p>D. Siltstone or silty shale with sandstone layers</p> <p>E. Weak siltstone or clayey shale with sandstone layers</p> <p>F. Tectonically deformed, intensively folded/faulted, sheared clayey shale or siltstone with broken and deformed sandstone layers forming an almost chaotic structure</p> <p>G. Undisturbed silty or clayey shale with or without a few very thin sandstone layers</p> <p>H. Tectonically deformed silty or clayey shale forming a chaotic structure with pockets of clay. Thin layers of sandstone are transformed into small rock pieces.</p> <p>→ Means deformation after tectonic disturbance</p>	<p>SURFACE CONDITIONS OF DISCONTINUITIES (Predominantly bedding planes)</p>	<p>VERY GOOD - Very Rough, fresh unweathered surfaces</p>	<p>GOOD - Rough, slightly weathered surfaces</p>	<p>FAIR - Smooth, moderately weathered and altered surfaces</p>	<p>POOR - Very smooth, occasionally slickensided surfaces with compact coatings or fillings with angular fragments</p>	<p>VERY POOR - Very smooth, slickensided or highly weathered surfaces with soft clay coatings or fillings</p>													
		<p>90</p>	<p>80</p>	<p>70</p>	<p>60</p>	<p>50</p>	<p>40</p>	<p>30</p>	<p>20</p>	<p>10</p>	<p>N/A</p>	<p>N/A</p>	<p>70</p>	<p>60</p>	<p>50</p>	<p>40</p>	<p>30</p>	<p>20</p>	<p>10</p>

09/08/09

TIP PROJECT: B-5777

CONTRACT:

See Sheet 1A For Index of Sheets



30% PLANS


STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

DAVIDSON COUNTY

LOCATION: BRIDGE NO. 58 OVER US 64 ON NC 109

TYPE OF WORK: GRADING, PAVING, DRAINAGE, AND STRUCTURE (BRIDGE)

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	B-5777	3	
STATE PROJ. NO.	F. A. PROJ. NO.	DESCRIPTION	
45733.1.1		PE	



THIS IS A PARTIAL CONTROLLED ACCESS PROJECT WITH ACCESS BEING LIMITED TO POINTS SHOWN ON THE PLANS. CLEARING ON THIS PROJECT SHALL BE PERFORMED TO THE LIMITS ESTABLISHED BY METHOD III.

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION
DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

<p>GRAPHIC SCALES</p> <p>50 25 0 50 100 PLANS</p> <p>50 25 0 50 100 PROFILE (HORIZONTAL)</p> <p>50 25 0 50 100 PROFILE (VERTICAL)</p>	<p>DESIGN DATA</p> <p>ADT 2025 = 11,800 ADT 2045 = 13,000 K = 9 % D = 60 % T = 3 % V = 60 MPH</p> <p>FUNC CLASS = PRINCIPAL ARTERIAL</p>	<p>PROJECT LENGTH</p> <p>LENGTH ROADWAY TIP PROJECT B-5777 0.377 MILES LENGTH STRUCTURE TIP PROJECT B-5777 0.29 MILES TOTAL LENGTH TIP PROJECT B-5777 0.406 MILES</p>	<p>PREPARED IN THE OFFICE OF: RS&H 8521 SIX FORKS ROAD, SUITE 400 RALEIGH, NC 27615 NC FIRM LICENSE No: F-0493 FOR THE NORTH CAROLINA DEPARTMENT OF TRANSPORTATION 2024 STANDARD SPECIFICATIONS</p> <p>RIGHT OF WAY DATE: JANUARY 31, 2024</p> <p>LETTING DATE: JUNE 17, 2025</p> <p>STEVEN SHUMAN, PE PROJECT ENGINEER</p> <p>DANA PACZEK, PE PROJECT DESIGN ENGINEER</p> <p>RYAN NEWCOMB, PE NC DOT CONTACT</p>	<p>HYDRAULICS ENGINEER</p> <p>_____ SIGNATURE: P.E.</p> <p>ROADWAY DESIGN ENGINEER</p> <p>_____ SIGNATURE: P.E.</p>	
--	---	--	---	---	---



ECS Southeast, LLC

1812 Center Park Drive, Suite D
 Charlotte, NC 28217
 T 704.525.5152 | F 704.357.0023
 www.ecslimited.com

May 14, 2024

WBS NO: 45733.1.1
 TIP NO: B-5777
 PROJECT ID: 43907
 COUNTY: Davidson
 DESCRIPTION: Replace Bridge No. 58 on NC 109 over US 64
SUBJECT: Geotechnical Report – Inventory

Project Description

The project consists of the replacement of Bridge No. 58 on NC 109 over US 64 in Thomasville, Davidson County, North Carolina. As a part of the replacement, a portion of NC 109 (-L- alignment), from Station 10+00 to Station 31+45 for an overall length of 2,145 feet (0.406 miles) will be realigned to the northwest to incorporate the new bridge structure. Roadway improvements will be made to Ramp A (-RPA- alignment), Ramp B (-RPB- alignment), Ramp C (-RPC- alignment), and Ramp D (-RPD- alignment) as well as the addition of two (2) new roundabouts (-RAB1-, -RAB2-) where they intersect with NC 109.

A new 150-foot long, 2-span bridge will be constructed on NC 109 (-L- alignment) over US64. The bridge will be located on new alignment and will begin at Station 19+89 and end at Station 21+39. The new bridge will likely be founded on a deep foundation system consisting of driven steel piles at the end bents and spread footings at the interior bent. Mechanically Stabilized Earth (MSE) walls will be constructed at the bridge abutments.

The provided roadway plans generally indicate new maximum embankment fill heights of approximately 15 feet along the -L- and -RAB2- alignments, and maximum cut depths of approximately 3 feet along the -L- and -RPD- alignments. Slopes are planned to be oriented at a 2:1 (horizontal:vertical) geometry.

A geotechnical field investigation was performed by ECS between April 2024 and May 2024. During this time period, a total of twenty-three (23) standard penetration test (SPT) roadway/structure borings were advanced using a Diedrich D-70 drill rig equipped with an automatic hammer. Representative soil samples were collected for visual classification in the field and selected for laboratory analysis by ECS's NCDOT approved testing laboratory.

The following alignments are included as a part of this investigation:

<u>Line</u>	<u>Station (±)</u>
-L- (NC 109)	10+00 to 31+45
-RPA-	10+26 to 15+46
-RPB-	10+00 to 16+40
-RPC-	10+00 to 15+50
-RPD-	10+00 to 16+42
-RAB1- (NC 109)	10+00 to 14+08
-RAB2- (NC 109)	10+00 to 14+08

Physiography and Geology

The site is located in the Carolina Slate Belt within the Piedmont Physiographic Province of North Carolina. In accordance with the Geologic Map of North Carolina, 1985, the predominant rock types under this site are mapped meta-argillite, interbedded with metasandstone, metaconglomerate and metavolcanic rock. Weathered rock and non-crystalline rock encountered during this investigation consists of Meta-Argillite. The virgin soils are the residual product of in-place chemical weathering of rock that was similar to the rock presently underlying the site.

Soil Properties

Soils within the area of this project have been divided into five categories: surficial materials (topsoil), roadway embankment, and residual soils.

Surficial Materials: The surficial organic soils (topsoil/rootmat) that were encountered ranged in thickness from approximately 0.1 to 0.6 feet.

Roadway Embankment: Roadway Embankment (R.E.) soils from the previous bridge construction are present throughout the project and generally consist of very dense, fine to coarse sandy gravel (A-1-b), medium dense, fine to coarse silty sand (A-2-4); medium stiff to hard, fine to coarse sandy/clayey silt (A-4, A-5); and stiff, slightly to highly plastic, sandy/silty clay (A-6, A-7-5/6). Varying amounts of gravel and asphalt were encountered throughout the roadway embankment soils. The roadway embankment extends to depths up to approximately 18.5 feet below existing grades. Laboratory testing of the Roadway Embankment soils indicated PI's ranging from 5 to 9 for the silty (A-4) soils, and PI's ranging from 12 to 30 for the clayey (A-7-5/6) soils.

Residual Soils: Residual soils were encountered throughout the project corridor are derived from the weathering of the underlying parent bedrock. The residual soils encountered generally consist of stiff to hard, fine to coarse sandy/clayey silt (A-4, A-5); and medium stiff to very stiff, slightly to moderately plastic,

sandy/silty clay (A-6, A-7-5). Varying amounts of rock fragments were encountered throughout the residual soils. Laboratory testing of the residual soils indicated a PI of 9 for the silty (A-4, A-5) soils, and PI's ranging from 15 to 23 for the clayey (A-6, A-7-5) soils.

Rock Properties

Weathered Rock: The top of the weathered rock varied significantly along the corridor and was encountered at depths ranging from approximately 0.0 to 18.5 feet below the existing ground surface; corresponding to elevations ranging from approximately 780.5 feet to 755.8 feet. The weathered rock encountered generally consists of Meta-Argillite.

Non-Crystalline Rock: The top of the crystalline rock varied significantly along the corridor and was encountered at depths ranging from approximately 2.4 to 38.6 feet below the existing ground surface; corresponding to elevations ranging from approximately 778.7 feet to 743.2 feet. The non-crystalline rock encountered generally consists of Meta-Argillite.

Groundwater Properties

At the time of drilling, Groundwater was encountered in one (1) boring at depth of approximately 36.3 feet below the existing ground surface; corresponding to an approximate elevation 745.6 feet. After a stabilization period of at least 24 hours, groundwater was encountered in three (3) borings at depths ranging from approximately 8.5 to 15.4 feet below the existing ground surface; corresponding to elevations ranging from approximately 768.7 to 762.1 feet. The recovered soil samples were generally described as moist above the groundwater level and moist below the groundwater level.

Areas of Special Geotechnical Interest

1) **High Plasticity Soils:** The following areas contain high plasticity soils with plasticity indices (PI's) in excess of 25. High plasticity soils have the potential to cause subgrade instability during construction, embankment stability or long term settlement problems.

<u>Line</u>	<u>Station (±)</u>	<u>Offsets</u>
-L-	26+50 to 28+00	LT

2) **Shallow Rock:** The following areas were found to contain rock above or within 6 feet of proposed subgrade:

<u>Line</u>	<u>Station (±)</u>	<u>Offsets</u>
-RPC-	11+50 to 12+50	RT
-RPD-	14+25 to 15+50	RT


Respectfully Submitted,

DocuSigned by:

399DBE42974A494
 Amanda R. Suttle, P.G.
 Project Geologist

DocuSigned by:

4EFC66AFC504B8
 Mohammed A. Mulla, P.E.
 Principal Engineer



MATCH LINE - L- STA 24+00.00 SEE SHEET 005



Prepared For:




B-5777

Replace Bridge No. 58 on NC 109 over US 64

GOTECHNICAL
UNIT




PREPARED BY









MATCH LINE -L- STA 24+00.00 SEE SHEET 004




B-5777
 Replace Bridge No. 58 on NC 109 over US 64
















11 -RAB-






12 -RAB2-








13 -RPA-




14 -RPB-




15 -RPC-





16 -R00-



NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT
SUBSURFACE INVESTIGATION
APPENDIX A
LABORATORY TEST RESULTS
SOIL TESTS FOR QUALITY

REFERENCE: B-5777

PROJECT: 45733

Prepared in the Office of:



ECS SOUTHEAST, LLP
1812 CENTER PARK DRIVE, SUITE D
CHARLOTTE, NC 28217
(704) 525-5152 [PHONE]
(704) 357-0023 [FAX]
NC REGISTERED
ENGINEERING
FIRM # F-1078

SOIL TEST RESULTS

BORING NO.	SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
								C. SAND	F. SAND	SILT	CLAY	10	40	200		
L_1100R	SS-60	60' RT	11+00 -L-	1.0-2.5	A-7-6(16)	51	23	28.3	2.2	25.2	44.3	80.3	72.8	70.0	11.3	-
L_1300L	SS-56	40' LT	13+00 -L-	1.0-2.5	A-4(9)	35	9	10.7	1.5	53.5	34.3	97.0	90.1	88.1	14.8	-
L_1500L	SS-53	20' LT	15+00 -L-	3.5-5.0	A-4(10)	37	9	3.6	0.9	72.0	23.5	99.8	96.9	95.5	12.1	-
L_1900L	SS-38	35' LT	19+00 -L-	1.0-2.5	A-4(2)	26	5	13.8	12.1	57.1	17.0	96.7	88.8	77.9	9.9	-
L_2250L	SS-07	27' LT	22+53 -L-	3.5-5.0	A-7-5(18)	46	15	3.1	1.1	48.8	47.0	99.3	97.4	96.1	25.1	-
L_2700L	SS-22	6' LT	27+00 -L-	1.0-2.5	A-7-5(36)	61	30	0.9	1.5	40.4	57.2	100.0	99.3	97.6	33.9	-
L_2900R	SS-26	25' RT	29+00 -L-	1.0-2.5	A-7-5(15)	42	12	1.4	0.9	62.5	35.2	99.5	98.9	97.9	18.2	-
RAB1_1100	SS-42	CL	11+00 -RAB1-	1.0-2.5	A-7-6(8)	41	17	36.6	6.7	29.8	26.9	97.6	67.3	57.9	14.7	-
RAB2_1100	SS-11	CL	11+00 -RAB2-	1.0-2.5	A-4(1)	32	9	48.1	6.6	23.1	22.2	86.6	56.2	46.2	10.4	-
RAB2_1275R	SS-01	25' RT	12+75 -RAB2-	1.0-2.5	A-7-6(10)	41	12	18.0	4.5	38.0	39.5	100.0	84.6	78.1	22.0	-
RPA_1400L	SS-34	20' LT	13+00 -RPA-	1.0-2.5	A-7-6(17)	43	16	6.2	1.6	53.3	38.9	98.5	94.5	92.6	17.6	-
RPC_1400R	SS-47	20' RT	14+00 -RPC-	1.0-2.5	A-7-5(19)	46	16	2.2	1.1	37.6	59.1	99.7	98.1	97.1	42.1	-
RPD_1500R	SS-64	30' RT	15+00 -RPD-	1.0-2.5	A-6(11)	36	15	13.5	14.0	47.6	24.9	97.1	89.2	78.1	15.5	-

LAB TECHNICIAN: AMANDA SUTTLE, P.G. NCDOT CERTIFICATION NO. 112-09-1003