

REFERENCE: U-6018

PROJECT: 47163

SEE SHEET 3 FOR PLAN SHEET LAYOUT
AT TIME OF INVESTIGATION

CONTENTS

LINE	STATION	PLAN
-L-	26+70 - 77+86	4-8
-Y3-	15+43 - 35+36	5,9
-Y5-	16+11 - 17+41	11
-Y6-	10+00 - 23+39	11
-Y8-	11+00 - 17+60	8
-Y9-	10+00 - 26+43	8,11
-RPA-	11+00 - 21+81	7,10
-RPD-	11+00 - 17+73	10
-RAB2-	10+00 - 12+20	11

CROSS SECTIONS

LINE	STATION	SHEET
-L-	28+00	12
-L-	30+00	13
-L-	32+00	14
-L-	34+00	15
-L-	35+00-38+00	16-19
-L-	40+00	20
-L-	42+00	21
-L-	44+00-47+50	22-29
-L-	51+00	30
-L-	62+00	31
-L-	64+00	32
-L-	65+00	33
-L-	66+00	34
-L-	68+00	35
-L-	72+00	36
-L-	75+00	37
-L-	77+00	38
-Y3-	17+50-20+00	39-41
-Y3-	21+00	42
-Y3-	22+00-27+00	43-50
-Y3-	28+00	51
-Y3-	30+00	52
-Y3-	32+00	53
-Y3-	34+00	54
-Y5-	17+00	55
-Y6-	18+50	56
-Y6-	21+50-23+50	57-59
-Y8-	14+00	60
-Y8-	16+00	61
-Y9-	11+00	62
-Y9-	13+00	63
-Y9-	15+00	64
-Y9-	17+00	65
-Y9-	19+00	66
-Y9-	21+00	67
-Y9-	23+00	68
-Y9-	25+00	69
-RPA-	12+00	70
-RPA-	14+00	71
-RPA-	16+00	72
-RPA-	18+00	73
-RPA-	19+50	74
-RPA-	21+50	75
-RPD-	12+00, 15+00	76
-RAB2-	11+00	77

APPENDICES

APPENDIX	TITLE	SHEET
A	SOIL TEST RESULTS	78,79

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT

ROADWAY
SUBSURFACE INVESTIGATION

COUNTY GUILFORD

PROJECT DESCRIPTION WIDENING OF NC62 (LIBERTY RD)
FROM EAST OF NC 610 (E. FAIRFIELD RD) TO EAST
OF SR 4066 (MODLIN GROVE RD) AND THE REALIGNMENT
OF SR 1154 (KERSEY VALLEY RD)

INVENTORY

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	U-6018	1	81

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT (919) 707-6850. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

- NOTES:
- THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.
 - BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

PERSONNEL

S. WOODS, GIT

TRIGON EXPLORATION LLC

R. TOOTHMAN

W. ALLEN


INVESTIGATED BY S. WOODS, GIT

DRAWN BY E. FERREIRA, EI

CHECKED BY D. BROWN, PE

SUBMITTED BY D. BROWN, PE

DATE AUGUST 2020



DocuSigned by

Donald W. Brown Jr.

C06817F5F770411...

9/21/2020

SIGNATURE

DATE

DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

DIVISION OF HIGHWAYS

GEOTECHNICAL ENGINEERING UNIT

SUBSURFACE INVESTIGATION

SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS

SOIL DESCRIPTION

SOIL IS CONSIDERED UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER AND YIELD LESS THAN 100 BLOWS PER FOOT ACCORDING TO THE STANDARD PENETRATION TEST (AASHTO T 206, ASTM D1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY INCLUDE THE FOLLOWING: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. FOR EXAMPLE, *VERY STIFF, GRAY, SILTY CLAY, MOIST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC, A-7-6*

SOIL LEGEND AND AASHTO CLASSIFICATION

GENERAL CLASS.	GRANULAR MATERIALS (≤ 35% PASSING #200)										SILT-CLAY MATERIALS (> 35% PASSING #200)						ORGANIC MATERIALS													
GROUP CLASS.	A-1		A-3		A-2		A-2-4		A-2-5		A-2-6		A-2-7		A-4		A-5		A-6		A-7		A-1, A-2		A-3		A-4, A-5		A-6, A-7	
SYMBOL																														
% PASSING	50 MX		30 MX		50 MX		51 MN		35 MX		35 MX		35 MX		36 MN		36 MN		36 MN		36 MN		GRANULAR SOILS		SILT-CLAY SOILS		MUCK, PEAT			
MATERIAL PASSING #40	LL		PI		—		NP		40 MX		41 MN		40 MX		41 MN		40 MX		41 MN		40 MX		41 MN		41 MN		41 MN		41 MN	
GROUP INDEX	0		0		0		0		4 MX		8 MX		12 MX		16 MX		NO MX		NO MX		NO MX		SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER		HIGHLY ORGANIC SOILS					
USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS. GRAVEL, AND SAND		FINE SAND		SILTY OR CLAYEY GRAVEL AND SAND						SILTY SOILS		CLAYEY SOILS																	
GEN. RATING AS SUBGRADE	EXCELLENT TO GOOD										FAIR TO POOR										FAIR TO POOR		POOR		UNSATURABLE					
PI OF A-7-5 SUBGROUP IS ≤ LL - 30; PI OF A-7-6 SUBGROUP IS > LL - 30																														

CONSISTENCY OR DENSENESS

PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT ²)
GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	< 4 4 TO 10 10 TO 30 30 TO 50 > 50	N/A
GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30	< 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4

TEXTURE OR GRAIN SIZE

U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270
	4.75	2.00	0.42	0.25	0.075	0.053
BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE. SD.)	FINE SAND (F SD.)	SILT (SL.)	CLAY (CL.)

GRAIN SIZE	MM IN.	305 12	75 3	2.0	0.25	0.05	0.005
------------	--------	--------	------	-----	------	------	-------

SOIL MOISTURE - CORRELATION OF TERMS

SOIL MOISTURE SCALE (ATTERBERG LIMITS)		FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION
LL PLASTIC RANGE (PI) PL	LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE
	PLASTIC LIMIT	- WET - (W)	SEMI-SOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE
		- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE
OM SL	OPTIMUM MOISTURE SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE

PLASTICITY

	PLASTICITY INDEX (PI)	DRY STRENGTH
NON PLASTIC	0-5	VERY LOW
SLIGHTLY PLASTIC	6-15	SLIGHT
MODERATELY PLASTIC	16-25	MEDIUM
HIGHLY PLASTIC	26 OR MORE	HIGH

COLOR

DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-GRAY). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.

GRADATION

WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE.
UNIFORMLY GRADED - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE.
GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES.

ANGULARITY OF GRAINS

THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS IS DESIGNATED BY THE TERMS:
ANGULAR, SUBANGULAR, SUBROUNDED, OR ROUNDED.

MINERALOGICAL COMPOSITION

MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHEN THEY ARE CONSIDERED OF SIGNIFICANCE.

COMPRESSIBILITY

SLIGHTLY COMPRESSIBLE	MODERATELY COMPRESSIBLE	HIGHLY COMPRESSIBLE
LL < 31	LL = 31 - 50	LL > 50

PERCENTAGE OF MATERIAL

ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL
TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE
LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE
MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME
HIGHLY ORGANIC	> 10%	> 20%	HIGHLY

GROUND WATER

WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING
STATIC WATER LEVEL AFTER 24 HOURS
PERCHED WATER, SATURATED ZONE, OR WATER BEARING STRATA
SPRING OR SEEP

MISCELLANEOUS SYMBOLS

ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION
SOIL SYMBOL
ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT
INFERRED SOIL BOUNDARY
INFERRED ROCK LINE
ALLUVIAL SOIL BOUNDARY
DIP & DIP DIRECTION OF ROCK STRUCTURES
TEST BORING
AUGER BORING
CORE BORING
MONITORING WELL
PIEZOMETER INSTALLATION
SLOPE INDICATOR INSTALLATION
CONE PENETROMETER TEST
SOUNDING ROD
TEST BORING WITH CORE
SPT N-VALUE

RECOMMENDATION SYMBOLS

UNDERCUT
SHALLOW UNDERCUT
UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE USED IN THE TOP 3 FEET OF EMBANKMENT OR BACKFILL
UNCLASSIFIED EXCAVATION - ACCEPTABLE WASTE
UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK

ABBREVIATIONS

AR - AUGER REFUSAL
BT - BORING TERMINATED
CL - CLAY
CPT - CONE PENETRATION TEST
CSE - COARSE
DMT - DILATOMETER TEST
DPT - DYNAMIC PENETRATION TEST
e - VOID RATIO
F - FINE
FOSS - FOSSILIFEROUS
FRAC. - FRACTURED, FRACTURES
FRAGS. - FRAGMENTS
HL - HIGHLY
MED. - MEDIUM
MICA - MICACEOUS
MOD. - MODERATELY
NP - NON PLASTIC
ORG. - ORGANIC
PMT - PRESSUREMETER TEST
SAP. - SAPROLITIC
SD. - SAND, SANDY
SL. - SILT, SILTY
SLI. - SLIGHTLY
TCR - TRICONE REFUSAL
w - MOISTURE CONTENT
V - VERY
VST - VANE SHEAR TEST
WEA. - WEATHERED
UNIT WEIGHT
DRY UNIT WEIGHT
SAMPLE ABBREVIATIONS
S - BULK
SS - SPLIT SPOON
ST - SHELBY TUBE
RS - ROCK
RT - RECOMPACTED TRIAXIAL
CBR - CALIFORNIA BEARING RATIO

EQUIPMENT USED ON SUBJECT PROJECT

DRILL UNITS:
☐ CME-45C
☒ CME-55
☐ CME-550
☐ VANE SHEAR TEST
☐ PORTABLE HOIST
☐
☐

ADVANCING TOOLS:
☐ CLAY BITS
☐ 6" CONTINUOUS FLIGHT AUGER
☒ 8" HOLLOW AUGERS
☐ HARD FACED FINGER BITS
☐ TUNG-CARBIDE INSERTS
☐ CASING ☐ W/ ADVANCER
☐ TRICONE ☐ STEEL TEETH
☐ TRICONE ☐ TUNG-CARB.
☐ CORE BIT
☐

HAMMER TYPE:
☒ AUTOMATIC ☐ MANUAL
CORE SIZE:
☐ -B ☐ -H ☐ -N
HAND TOOLS:
☐ POST HOLE DIGGER
☒ HAND AUGER
☐ SOUNDING ROD
☐ VANE SHEAR TEST
☐

ROCK DESCRIPTION

HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED. AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS IN NON-COASTAL PLAIN MATERIAL. THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:

WEATHERED ROCK (WR)
 CRYSTALLINE ROCK (CR)
 NON-CRYSTALLINE ROCK (NCR)
 COASTAL PLAIN SEDIMENTARY ROCK (CP)

NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT N VALUES > 100 BLOWS PER FOOT IF TESTED.
FINE TO COARSE GRAIN IGNEOUS AND METAMORPHIC ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES GRANITE, GNEISS, GABBRO, SCHIST, ETC.
FINE TO COARSE GRAIN METAMORPHIC AND NON-COASTAL PLAIN SEDIMENTARY ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES PHYLLITE, SLATE, SANDSTONE, ETC.
COASTAL PLAIN SEDIMENTS CEMENTED INTO ROCK, BUT MAY NOT YIELD SPT REFUSAL. ROCK TYPE INCLUDES LIMESTONE, SANDSTONE, CEMENTED SHELL BEDS, ETC.

WEATHERING

FRESH
VERY SLIGHT (V SL.)
SLIGHT (SL.)
MODERATE (MOD.)
MODERATELY SEVERE (MOD. SEV.)
SEVERE (SEV.)
VERY SEVERE (V SEV.)
COMPLETE

ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING. ROCK RINGS UNDER HAMMER IF CRYSTALLINE.
ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN. CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF OF A CRYSTALLINE NATURE.
ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO 1 INCH. OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR CRYSTALS ARE DULL AND DISCOLORED. CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS.
SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY. ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED WITH FRESH ROCK.
ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK. ROCK GIVES "CLUNK" SOUND WHEN STRUCK. *IF TESTED, WOULD YIELD SPT REFUSAL*
ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC CLEAR AND EVIDENT BUT REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN. *IF TESTED, WOULD YIELD SPT N VALUES > 100 BPF*
ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC ELEMENTS ARE DISCERNIBLE BUT MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK REMAINING. SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE THAT ONLY MINOR VESTIGES OF ORIGINAL ROCK FABRIC REMAIN. *IF TESTED, WOULD YIELD SPT N VALUES < 100 BPF*
ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.

ROCK HARDNESS

VERY HARD
HARD
MODERATELY HARD
MEDIUM HARD
SOFT
VERY SOFT

CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.
CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.
CAN BE SCRATCHED BY KNIFE OR PICK, GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.
CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.
CAN BE GROVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.
CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGERNAIL.

FRACTURE SPACING

TERM	SPACING
VERY WIDE	MORE THAN 10 FEET
WIDE	3 TO 10 FEET
MODERATELY CLOSE	1 TO 3 FEET
CLOSE	0.16 TO 1 FOOT
VERY CLOSE	LESS THAN 0.16 FEET

BEDDING

TERM	THICKNESS
VERY THICKLY BEDDED	4 FEET
THICKLY BEDDED	1.5 - 4 FEET
THINLY BEDDED	0.16 - 1.5 FEET
VERY THINLY BEDDED	0.03 - 0.16 FEET
THICKLY LAMINATED	0.008 - 0.03 FEET
THINLY LAMINATED	< 0.008 FEET

INDURATION

FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.

FRIABLE
MODERATELY INDURATED
INDURATED
EXTREMELY INDURATED

RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.
GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.
GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.
SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.

TERMS AND DEFINITIONS

ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER.
AQUIFER - A WATER BEARING FORMATION OR STRATA.
ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND.
ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC.
ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE.
CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE.
COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE.
CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.
DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK.
DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL.
DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH.
FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE.
FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES.
FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLOGGED FROM PARENT MATERIAL.
FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM.
FORMATION (FM.) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD.
JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED.
LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT.
LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS.
MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS. MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE.
PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM.
RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK.
ROCK QUALITY DESIGNATION (RQD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.
SAPROLITE (SAP.) - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK.
SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS.
SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE.
STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N OR BPF) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS.
STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE.
STRATA ROCK QUALITY DESIGNATION (SROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE.
TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.

BENCH MARK:

ELEVATION: FEET


NOTES:

BORING ELEVATIONS GENERATED FROM FILE U6018-IS.TIN..TIN, DATED 6/4/2019.
HA = HAND AUGER BORING
FIAD = FILLED IMMEDIATELY AFTER DRILLING

DATE: 8-15-14

09/08/2022

See Sheet 1A For Index of Sheets
See Sheet 1B For Conventional Symbols



STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

GUILFORD COUNTY

LOCATION: WIDENING OF NC 62 (LIBERTY RD) FROM EAST OF NC 610 (E. FAIRFIELD RD) TO EAST OF SR 4066 (MODLIN GROVE RD) AND THE REALIGNMENT OF SR 1154 (KERSEY VALLEY RD) AND SR 1162 (WEANT RD)


TYPE OF WORK: GRADING, PAVING, DRAINAGE, & SIGNALS

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	U-6018	3	81
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
47163.1.1			




TIP PROJECT: U-6018

CONTRACT:



THIS PROJECT IS WITHIN THE MUNICIPAL BOUNDARIES OF ARCHDALE, JAMESTOWN, AND HIGH POINT
CLEARING ON THIS PROJECT SHALL BE PERFORMED TO THE LIMITS ESTABLISHED BY METHOD II



DESIGN DATA

ADT 2018 = 11,300
ADT 2040 = 12,600
K = 11
D = 55%
T = 6%*
V = 50 MPH
*(TTST 2% + DUALS 4%)

FUNCTION CLASS:
MINOR ARTERIAL
REGIONAL TIER

PROJECT LENGTH

LENGTH ROADWAY TIP PROJECT U-6018 = 0.894 MILES
LENGTH EXIST. STRUCTURE TIP PROJECT U-6018 = 0.075 MILES
TOTAL LENGTH ROADWAY TIP PROJECT U-6018 = 0.969 MILES

NCDOT CONTACT: CHRIS SMITHERMAN, PE
DIV 7 - PROJECT DELIVERY TEAM LEAD
336-487-0075

Prepared In the Office of:

RKA
RAMEY KEMP ASSOCIATES
5808 Farlington Place Raleigh, North Carolina 27609
Phone: 919-872-5115 | www.rameykemp.com | NC License No. C-0910

2018 STANDARD SPECIFICATIONS

JUNE 2020
RIGHT OF WAY DATE:
JUNE 14, 2022
LETTING DATE:

CLAUDETTE M.K. ROQUE, PE
PROJECT ENGINEER


KAYLA M. POULOS, EI
PROJECT DESIGNER

HYDRAULICS ENGINEER

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION

SIGNATURE:
ROADWAY DESIGN ENGINEER

SIGNATURE:





August 25, 2020

STATE PROJECT: 47163.1.1 (U-6018)
COUNTY: Guilford
DESCRIPTION: Widening of NC 62 (Liberty Road) from east of NC 610 (E. Fairfield Road) to east of SR 4066 (Modlin Grove Road) and the realignment of SR 1154 (Kersey Valley Road) and SR 1162 (Weant Road).

SUBJECT: Roadway Subsurface Inventory

Project Description

The proposed project consists of the improvement of NC 62, located within the municipal boundaries of Archdale, Jamestown, and High Point in North Carolina. The total length of the project is approximately 0.97 miles, with 14 alignments as shown in the table below. The project corridor contains a roughly even mixture of developed and undeveloped land, extending through residential areas and woodlands.

Alignment	Description	Stations
-L-	NC 62	26+70± to 77+86.12±
-Y3-	Kersey Valley Road	15+43.44 to 35+36.09±
-Y5-	Old Weant Road	16+11.24 to 17+41.21±
-Y6-	Weant Road	10+00 to 23+39.20±
-Y7-	Bluewood Court	10+00 to 11+71.36±
-Y8-	Modlin Grove Road	11+00 to 17+60.19±
-Y9-	Weant Road	10+00 to 26+42.94±
-RPA-	I-85 SB Off Ramp	11+00 to 21+81.34±
-RPB-	I-85 SB On Ramp	10+00 to 11+32.54±
-RPC-	I-85 NB Off Ramp	10+00 to 11+50±
-RPD-	I-85 NB On Ramp	11+00± to 17+73.21±
-RAB2-	Roundabout	10+00 to 12+19.91±
-DR1-	Driveway	10+00 to 11+30±
-SR1-	Driveway	10+00 to 11+79.03±

Plans call for the improvement of NC 62 (-L-), from approximately 415± feet west of its intersection with E. Fairfield Road to 706± feet east of its intersection with Modlin Grove Road (-Y8-). The improvements include widening the existing roadways, adding curb and gutter on -L- on other Y-lines, and installation of sidewalks. Kersey Valley Road (-Y3-) will be moved to new alignment to intersect NC 62 approximately 760 feet west of its current intersection. The old Kersey Valley Road will be removed. Weant Road (-Y6-) will also be moved to new alignment to shift its intersection with NC 62 approximately 720 feet east of its current intersection. The existing Weant Road (-Y6-) will be left in place, but a roundabout (-RAB2-) will be constructed to connect it to the new Weant Road (-Y9-) and Old Weant Road (-Y5-). The I-85 SBL off-ramp (-RPA-) and the I-85 NBL on-ramp (-RPD-) will also be widened.

PROJECT REFERENCE NO.	SHEET NO.
U-6018	3A

A geotechnical field investigation was conducted for this project in March of 2020. Drilling was performed by Trigon Exploration LLC of Greensboro, NC using an ATV-mounted CME-55 drill rig. The drill rig was equipped with an automatic hammer with an efficiency of 87%. All drilling activities were supervised by Stewart personnel.

A total of 36 Standard Penetration Test (SPT) borings and 14 Hand Auger borings were performed for the project. Representative soil samples from select borings were collected in the field for laboratory analysis.

Physiography & Geology

The project site is located in Guilford County, North Carolina, which lies within the Piedmont Geologic Province of North Carolina. The site is part of the Carolina Slate Belt region, which is generally characterized by low grade metamorphosed volcanic rock. Review of the *Geologic Map of Region G, North Carolina* (P. Albert Carpenter, 1982) shows that the site is underlain by the Felsic intrusive complex (icf) of the Precambrian era that is primarily comprised of metamorphosed, felsic igneous rocks, such as granite and diorite.

Soil Properties

Soils encountered at the site include artificial fill, roadway embankment, alluvial, and residual soils.

Artificial fill was encountered on -Y9- consisting of loose Clayey SAND (A-2-6), with a Plasticity Index (PI) of 38 and was wet to moist.

Roadway embankment was encountered in borings along -L-, -RAB2-, -RPA-, -RPD-, -Y5-, AND -Y6-. The material was loose to medium dense Silty SAND (A-2-4) and Clayey SAND (A-2-6) and medium stiff Sandy Lean CLAY (A-2-6) and Fat CLAY (A-7). The samples were moist to wet. Laboratory test samples had PIs of 33 and 40.

Alluvial soil associated with the wetland areas was encountered along -L- and -Y3- with material classified as very loose to medium stiff Silty SAND (A-2-4) and Clayey SAND (A-2-6) and soft Sandy Lean CLAY (A-6). The samples were moist to saturated.

The native residual soils, which are the weathered remains of the parent rock, were encountered in all borings except for borings L_4000 HA, L_4200 HA, L_4400 HA, L_4600 HA, L_5120, L_7210 HA, L_7485 HA, RPA_2130, and RPD_1200. The soils types primarily consist of very loose to very dense, Clayey SAND (A-2-6) and Silty SAND (A-2-4), with lesser amounts of very soft to hard Sandy SILT (A-4), Silty CLAY (A-7), Clayey SILT (A-5), Sandy CLAY (A-6). The samples were moist to saturated. Laboratory test samples had PIs ranging from 6 to 40.

Rock Properties

Weathered rock (granite) was encountered in six borings (L_6800, RPA_2130, RPD_1200, Y9_1300, Y9_2300, and Y9_2500) at depths ranging from approximately 2 to 14.4 feet below the current ground surface. The weathered rock ranged in elevation from 801.1 feet and 821.8 feet.

Refusal on hard rock was encountered at one boring location, RPD_1200, at an elevation of 812.6 feet.

Groundwater

Of the 50 borings, groundwater was encountered in 17 during the drilling process, at depths ranging from 0.8 to 7.3 feet below the ground surface (el. 809.1± to 831.6± feet). Twenty-nine of the 50 borings were left open for a 24+ hour stabilization period, after which groundwater was measured in 13 borings at depths ranging from approximately 0.8 to 6.9 feet below the current ground surface (el. 809.1± to 831.6± feet).

Areas of Special Geotechnical Interest

Alluvial Soils

Alluvial soil was encountered along the two alignments as shown below.

Alignment	Station	Offset (ft)
-L-	44+20± to 49+00±	100± RT
-L-	71+40± to 72+40±*	10± RT
-Y3-	22+00± to 26+50±	CL

**Encountered below roadway embankment*

Groundwater

Groundwater was encountered within 6 feet of finished grade in the following locations:

Alignment	Station
-L-	46+00±
-Y3-	23+00± to 26+00±

Artificial Fill

Artificial fill was encountered at the following locations:

Alignment	Station	Offset (ft)
-Y9-	10+50± to 11+45±	CL

Water Wells

Water wells were noted on the plans near the right-of-way at the following location(s):

Alignment	Station	Offset (ft)
-L-	28+75±	192± LT
-L-	37+76±	82± LT
-L-	48+27±	81± LT
-L-	63+82±	132± LT
-L-	64+52±	71± RT
-L-	65+24±	99± LT
-L-	66+06±	83± RT
-L-	73+49±	120± LT
-L-	76+45±	149± RT
-L-	78+35±	103± RT
-L-	79+64± to 79+77±	125± RT
-L-	82+52±	61± RT
-Y3-	13+07±	39± RT

-Y3-	18+24±	95± RT
-Y3-	19+04±	67± RT
-RAB2-	11+12±	66± RT

Items of Interest

USTs, ASTs and gas pumps, or indictors thereof, were noted on the plans near the right-of-way at the following location(s):

Type	Alignment	Station	Offset (ft)
UST	-L-	39+10± to 39+42±	230± RT to 235± RT
UST	-Y3-	16+42±	96± RT
UST	-Y3-	19+41	16± RT
UST	-Y6-	13+30± to 13+95±	115± LT to 220± RT

Ponds and Wetland Locations


Type	Alignment	Station	Offset (ft)
Stream	-L-	31+23±	22± RT
Pond	-L-	45+25± to 46+48±	201± to 322± RT
Wetland	-Y3-	23+65± to 26+60±	20± to 95± RT
Spring/Stream	-Y3-	27+35±	9± RT
Stream	-Y3-	31+00±	138± RT
Wetland	-Y8-	14+42± to 15+96±	20± to 30± RT
Pond	-Y9-	11+00± to 13+75±	65± to 70± LT
Stream	-Y9-	24+05±	CL
Wetland	-Y9-	24+00± to 24+80±	90± to 120± RT

Soil with High Plasticity Indices

Based on laboratory testing, soil at the following locations Were determined to be highly plastic (PI=35 or greater).


Alignment	Station	Offset (ft)
-L-	36+00±	33± LT
-Y3-	19+00±	CL
-Y6-	22+00±	30± RT
-Y9-	19+00±	CL

8/17/99
\$\$\$\$\$SYTIME\$\$\$\$\$
\$\$\$\$\$USERNAME\$\$\$\$\$




PROJECT REFERENCE NO.		SHEET NO.	
U-6018		4	
RW SHEET NO.			
ROADWAY DESIGN ENGINEER		HYDRAULICS ENGINEER	
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION			
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED			
 STEWART			
Firm License No. C-1051 223 S. West St. Suite 1100 Raleigh, NC 27603 T 919.380.8750 www.stewartinc.com			


MATCHLINE -L- STA. 32+00.00
SEE SHEET 5



PROJECT REFERENCE NO.		SHEET NO.	
U-6018		5	
RW SHEET NO.			
ROADWAY DESIGN ENGINEER		HYDRAULICS ENGINEER	
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION			
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED			
		Firm License No. C-1051 223 S. West St. Suite 1100 Raleigh, NC 27603 T 919.380.8750 www.stewartinc.com	
STEWART			



MATCHLINE -L- STA. 58 + 00.00
SEE SHEET 6




MATCHLINE -L- STA. 70 + 00.00
SEE SHEET 8

PROJECT REFERENCE NO. U-6018		SHEET NO. 7	
RW SHEET NO.		HYDRAULICS ENGINEER	
ROADWAY DESIGN ENGINEER		HYDRAULICS ENGINEER	
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION			
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED			
		Firm License No. C-1051 223 S. West St. Suite 1100 Raleigh, NC 27603 T 919.380.8750 www.stewartinc.com	
		STEWART	

8/17/99


REVISIONS

\$\$\$\$\$SYTIME\$\$\$\$\$
\$\$\$\$\$USERNAME\$\$\$\$\$



PROJECT REFERENCE NO. U-6018		SHEET NO. 9	
RW SHEET NO.		HYDRAULICS SHEET NO.	
ROADWAY DESIGN ENGINEER		HYDRAULICS ENGINEER	
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION			
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED			
 STEWART Firm License No. C-1051 223 S. West St. Suite 1100 Raleigh, NC 27603 T 919.380.8750 www.stewartinc.com			

-RPA-





6/23/16



PROJ. REFERENCE NO.
U-6018

SHEET NO.
13

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

CL

L 3000

30+00

30 FT LT

(A)

RESIDUAL BROWN, LOOSE, MOIST, CLAYEY SAND
WITH TRACE ROOTS (A-2-6)

(A)

(5)

(11)

(8)

03/20

RESIDUAL ORANGE-WHITE, STIFF, MOIST, SANDY CLAYEY SILT (A-5)

RESIDUAL TAN-WHITE, MEDIUM STIFF, MOIST, SANDY SILT (A-4)

GROUND SURFACE

30 + 00.00

NOTE: EXISTING GROUND SURFACE SHOWN WAS
TAKEN FROM ELECTRONIC TIN FILE (DATED
JUNE 2019). INFERRED STRATIGRAPHY IS
DRAWN THROUGH THE BORINGS WITH BOTH
PROJECTED ONTO THE CROSS SECTION.

-L-

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

EXISTING GROUND SURFACE
BORING DATA
DATE: 6/23/16
DRAWN BY: [illegible]
CHECKED BY: [illegible]
APPROVED BY: [illegible]

6/23/16



PROJ. REFERENCE NO.
U-6018

SHEET NO.
14

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75


℄

L 3200
32+00
28 FT LT

(A) ROADWAY EMBANKMENT BROWN, WET, VERY LOOSE, SILTY SAND
WITH TRACE ROOTS (A-2-4)

(A)
RESIDUAL TAN AND ORANGE, MEDIUM DENSE, MOIST TO WET,
SILTY SAND WITH TRACE MICA (A-2-4)

GROUND SURFACE




32 + 00.00


NOTE: EXISTING GROUND SURFACE SHOWN WAS
TAKEN FROM ELECTRONIC TIN FILE DATED
JUNE 2019. INFERRED STRATIGRAPHY IS
DRAWN THROUGH THE BORINGS WITH BOTH
PROJECTED ONTO THE CROSS SECTION.


-L-


75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75


SYNTHETIC
SAND
FILL











6/23/16





PROJ. REFERENCE NO.
U-6018


SHEET NO.
20

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75


CL







6/23/16
CUSTIMER
SHEET NO. 23
PROJECT NO. U-6018



6/23/16



PROJ. REFERENCE NO.
U-6018

SHEET NO.
24

℄

(A) ROADWAY EMBANKMENT BROWN, MOIST, SILTY SAND WITH TRACE CLAY AND GRAVEL (A-2-4)

(B) ROADWAY EMBANKMENT ORANGE-BROWN, MOIST, SANDY CLAY (A-6)

(C) ALLUVIAL TAN, MOIST, SILTY SAND WITH TRACE ROOTS (A-2-4)

(D) ALLUVIAL BLUE-GRAY, WET, CLAYEY SAND WITH TRACE ROOTS AND ORGANICS (A-2-6)

(E) ALLUVIAL BLUE-GRAY, WET, SANDY CLAY WITH TRACE ROOTS AND ORAGNICS (A-6)

NOTE: EXISTING GROUND SURFACE SHOWN WAS
TAKEN FROM ELECTRONIC TIN FILE (DATED
JUNE 2019). INFERRED STRATIGRAPHY IS
DRAWN THROUGH THE BORINGS WITH BOTH
PROJECTED ONTO THE CROSS SECTION.

45 + 00.00

-L-

SYNTHETIC
CROSS
SECTION
DRAWN
THROUGH
BORINGS
WITH
BOTH
PROJECTED
ONTO
THE
CROSS
SECTION

6/23/16




PROJ. REFERENCE NO.
U-6018

SHEET NO.
25

30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75 80 85 90 95 100 105 110 115 120

CL



6/23/16




PROJ. REFERENCE NO.
U-6018


SHEET NO.
26

30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75 80 85 90 95 100 105 110 115 120

CL



6/23/16




6/23/16



PROJ. REFERENCE NO.
U-6018


SHEET NO.
28

20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75 80 85 90 95 100 105 110 115 120 125 130



- (A) ROADWAY EMBANKMENT BROWN, MOIST, SILTY SAND WITH TRACE CLAY AND GRAVEL (A-2-4)
(B) ROADWAY EMBANKMENT ORANGE-BROWN, MOIST, SANDY CLAY (A-6)

- (C) ALLUVIAL TAN, MOIST, SILTY SAND WITH TRACE ROOTS (A-2-4)
(D) ALLUVIAL BLUE-GRAY, WET, CLAYEY SAND WITH TRACE ROOTS AND ORGANICS (A-2-6)
(E) ALLUVIAL BLUE-GRAY, WET, SANDY CLAY WITH TRACE ROOTS AND ORAGNICS (A-6)



47 + 00.00

-L-

6/23/16
CUSTOMER: \$
DRAWN BY: \$
CHECKED BY: \$
APPROVED BY: \$
DATE: \$

6/23/16




PROJ. REFERENCE NO.
U-6018

SHEET NO.
29

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

CL



-L-

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

6/23/16
CUSTOMER: \$
DRAWN BY: \$
CHECKED BY: \$
DATE: \$
PROJECT: \$
SHEET: \$
29

6/23/16




PROJ. REFERENCE NO.
U-6018

SHEET NO.
30

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

℄



NOTE: EXISTING GROUND SURFACE SHOWN WAS
TAKEN FROM ELECTRONIC TIN FILE (DATED
JUNE 2019). INFERRED STRATIGRAPHY IS
DRAWN THROUGH THE BORINGS WITH BOTH
PROJECTED ONTO THE CROSS SECTION.

-L-

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

SYNTHETIC
SECTION
DRAWN
BY
JUN
2019
DATE
6/23/16
PROJECT
U-6018
SHEET
30

6/23/16




PROJ. REFERENCE NO.
U-6018

SHEET NO.
31

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

CL



6/23/16



PROJ. REFERENCE NO.
U-6018

SHEET NO.
32

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

CL

L_6397
63+97
30 FT LT

Ⓐ ROADWAY EMBANKMENT TAN, LOOSE, MOIST, SILTY SAND WITH TRACE ROOTS (A-2-4)

RESIDUAL TAN-WHITE, MEDIUM STIFF, MOIST, SANDY SILT (A-4)

TAN-ORANGE, MEDIUM DENSE, MOIST, SILTY SAND
WITH TRACE MICA (A-2-4)

DRY
B.T.

GROUND SURFACE

NOTE: EXISTING GROUND SURFACE SHOWN WAS
TAKEN FROM ELECTRONIC TIN FILE (DATED
JUNE 2019). INFERRED STRATIGRAPHY IS
DRAWN THROUGH THE BORINGS WITH BOTH
PROJECTED ONTO THE CROSS SECTION.

64+00.00

-L-

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

SYNTHETIC
SAND
FILL

6/23/16




PROJ. REFERENCE NO.
U-6018

SHEET NO.
33


75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

CL



6/23/16
C:\P\6485_HA
64+85
22 FT RT
DRY B.T.
GRAY-TAN AND ORANGE, MEDIUM DENSE, MOIST, SILTY SAND WITH TRACE ROOTS (A-4)


6/23/16




6/23/16

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

NOTE: EXISTING GROUND SURFACE SHOWN WAS
TAKEN FROM ELECTRONIC TIN FILE (DATED
JUNE 2019). INFERRED STRATIGRAPHY IS
DRAWN THROUGH THE BORINGS WITH BOTH
PROJECTED ONTO THE CROSS SECTION.





6/23/16




PROJ. REFERENCE NO.
U-6018

SHEET NO.
38

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

NOTE: EXISTING GROUND SURFACE SHOWN WAS
TAKEN FROM ELECTRONIC TIN FILE (DATED
JUNE 2019). INFERRED STRATIGRAPHY IS
DRAWN THROUGH THE BORINGS WITH BOTH
PROJECTED ONTO THE CROSS SECTION.



\$\$\$\$\$SYTIME\$\$\$\$\$
\$\$\$\$\$EDGN\$\$\$\$\$
\$\$\$\$\$CROSSSECTION\$\$\$\$\$

6/23/16



PROJ. REFERENCE NO.
U-6018

SHEET NO.
39

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

℄

GROUND SURFACE

RESIDUAL TAN-BROWN TO WHITE RED, MEDIUM STIFF TO STIFF, MOIST,
SILTY CLAY WITH TRACE ROOTS (A-7)

18 + 00.00

GROUND SURFACE

RESIDUAL TAN-BROWN TO WHITE RED, MEDIUM STIFF TO STIFF, MOIST,
SILTY CLAY WITH TRACE ROOTS (A-7)

17 + 50.00

-Y3-

NOTE: EXISTING GROUND SURFACE SHOWN WAS
TAKEN FROM ELECTRONIC TIN FILE (DATED
JUNE 2019). INFERRED STRATIGRAPHY IS
DRAWN THROUGH THE BORINGS WITH BOTH
PROJECTED ONTO THE CROSS SECTION.

EXISTING GROUND SURFACE
BORING DATA
DATE: 6/23/16
DRAWN BY: [illegible]
CHECKED BY: [illegible]
APPROVED BY: [illegible]

6/23/16



PROJ. REFERENCE NO.
U-6018

SHEET NO.
40

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

CL

855 855

850 850

845 845

GROUND SURFACE

840 840

Y3_1900
19+00
CL

SS-62

5

9

5

DRY
B.T.

RESIDUAL TAN-BROWN TO WHITE RED, MEDIUM STIFF TO STIFF, MOIST,
SILTY CLAY WITH TRACE ROOTS (A-7)

835 835

830 830

19 + 00.00

850 850

845 845

GROUND SURFACE

840 840

835 835

RESIDUAL TAN-BROWN TO WHITE RED, MEDIUM STIFF TO STIFF, MOIST,
SILTY CLAY WITH TRACE ROOTS (A-7)

830 830

18 + 50.00

NOTE: EXISTING GROUND SURFACE SHOWN WAS
TAKEN FROM ELECTRONIC TIN FILE (DATED
JUNE 2019). INFERRED STRATIGRAPHY IS
DRAWN THROUGH THE BORINGS WITH BOTH
PROJECTED ONTO THE CROSS SECTION.

-Y3-

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

EXISTING GROUND SURFACE SHOWN WAS
TAKEN FROM ELECTRONIC TIN FILE (DATED
JUNE 2019). INFERRED STRATIGRAPHY IS
DRAWN THROUGH THE BORINGS WITH BOTH
PROJECTED ONTO THE CROSS SECTION.

6/23/16





PROJ. REFERENCE NO.
U-6018

SHEET NO.
41

70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

CL



NOTE: EXISTING GROUND SURFACE SHOWN WAS TAKEN FROM ELECTRONIC TIN FILE (DATED JUNE 2019). INFERRED STRATIGRAPHY IS DRAWN THROUGH THE BORINGS WITH BOTH PROJECTED ONTO THE CROSS SECTION.

-Y3-

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

6/23/16
U-6018
41
CL
GROUND SURFACE
WHITE-ORANGE, MEDIUM STIFF TO STIFF, MOIST, SILTY CLAY (A-7)
RESIDUAL TAN-BROWN, SOFT, MOIST, SANDY CLAY WITH TRACE ROOTS (A-6)
20 + 00.00
19 + 50.00
-Y3-
NOTE: EXISTING GROUND SURFACE SHOWN WAS TAKEN FROM ELECTRONIC TIN FILE (DATED JUNE 2019). INFERRED STRATIGRAPHY IS DRAWN THROUGH THE BORINGS WITH BOTH PROJECTED ONTO THE CROSS SECTION.

6/23/16



PROJ. REFERENCE NO.
U-6018

SHEET NO.
42

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

CL

Y3-2100
21+00
CL
SS-65

GROUND SURFACE

4

10

6

DRY
B.T.

WHITE-ORANGE, MEDIUM STIFF TO STIFF, MOIST, SILTY CLAY (A-7)

A

A RESIDUAL TAN-BROWN, SOFT, MOIST,
SANDY CLAY WITH TRACE ROOTS (A-6)


21 + 00.00

NOTE: EXISTING GROUND SURFACE SHOWN WAS
TAKEN FROM ELECTRONIC TIN FILE (DATED
JUNE 2019). INFERRED STRATIGRAPHY IS
DRAWN THROUGH THE BORINGS WITH BOTH
PROJECTED ONTO THE CROSS SECTION.


-Y3-


70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75


SYNTHETIC
SAND
FILL




6/23/16









6/23/16



PROJ. REFERENCE NO.
U-6018

SHEET NO.
48

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75



CL

A

ALLUVIAL

DARK GRAY, VERY LOOSE, WET, SILTY SAND
WITH TRACE ROOTS AND ORGANICS (A-2-4)

A

ALLUVIAL

GRAY, MEDIUM DENSE, WET, CLAYEY SAND
WITH TRACE ROOTS (A-2-6)

RESIDUAL

TAN, VERY DENSE, MOIST, SILTY SAND (A-2-4)

GROUND SURFACE

25 + 00.00

-Y3-

NOTE: EXISTING GROUND SURFACE SHOWN WAS
TAKEN FROM ELECTRONIC TIN FILE (DATED
JUNE 2019). INFERRED STRATIGRAPHY IS
DRAWN THROUGH THE BORINGS WITH BOTH
PROJECTED ONTO THE CROSS SECTION.

840

835

830

825

820

815

810

805

800

840

835

830

825

820

815

810

805

800



6/23/16
CUSTIN
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2234
2235
2236
2237
2238
2239
2240
2241
2242
2243
2244
2245
2246
2247
2248
2249
2250
2251
2252
2253
2254
2255
2256
2257
2258
2259
2260
2261
2262
2263
2264
2265
2266
2267
2268
2269
2270
2271
2272
2273
2274
2275
2276
2277
2278
2279
2280
2281
2282
2283
2284
2285
2286
2287
2288
2289
2290
2291
2292
2293
2294
2295
2296
2297
2298
2299
2300
2301
2302
2303
2304
2305
2306
2307
2308
2309
2310
2311
2312
2313
2314
2315
2316
2317
2318
2319
2320
2321
2322
2323
2324
2325
2326
2327
2328
2329
2330
2331
2332
2333
2334
2335
2336
2337
2338
2339
2340
2341
2342
2343
2344
2345
2346
2347
2348
2349
2350
2351
2352
2353
2354
2355
2356
2357
2358
2359
2360
2361
2362
2363
2364
2365
2366
2367
2368
2369
2370
2371
2372
2373
2374
2375
2376
2377
2378
2379
2380
2381
2382
2383
2384
2385
2386
2387
2388
2389
2390
2391
2392
2393
2394
2395
2396
2397
2398
2399
2400
2401
2402
2403
2404
2405
2406
2407
2408
2409
2410
2411
2412
2413
2414
2415
2416
2417
2418
2419
2420
2421
2422
2423
2424
2425
2426
2427
2428
2429
2430
2431
2432
2433
2434
2435
2436
2437
2438
2439
2440
2441
2442
2443
2444
2445
2446
2447
2448
2449
2450
2451
2452
2453
2454
2455
2456
2457
2458
2459
2460
2461
2462
2463
2464
2465
2466
2467
2468
2469
2470
2471
2472
2473
2474
2475
2476
2477
2478
2479
2480
2481
2482
2483
2484
2485
2486
2487
2488
2489
2490
2491
2492
2493
2494
2495
2496
2497
2498
2499
2500
2501
2502
2503
2504
2505
2506
2507
2508
2509
2510
2511
2512
2513
2514
2515
2516
2517
2518
2519
2520
2521
2522
2523
2524
2525
2526
2527
2528
2529
2530
2531
2532
2533
2534
2535
2536
2537
2538
2539
2540
2541
2542
2543
2544
2545
2546
2547
2548
2549
2550
2551
2552
2553
2554
2555
2556
2557
2558
2559
2560
2561
2562
2563
2564
2565
2566
2567
2568
2569
2570
2571
2572
2573
2574
2575
2576
2577
2578
2579
2580
2581
2582
2583
2584
2585
2586
2587
2588
2589
2590
2591
2592
2593
2594
2595
2596
2597
2598
2599
2600
2601
2602
2603
2604
2605
2606
2607
2608
2609
2610
2611
2612
2613
2614
2615
2616
2617
2618
2619
2620
2621
2622
2623
2624
2625
2626
2627
2628
2629
2630
2631
2632
2633
2634
2635
2636
2637
2638
2639
2640
2641
2642
2643
2644
2645
2646
2647
2648
2649
2650
2651
2652
2653
2654
2655
2656
2657
2658
2659
2660
2661
2662
2663
2664
2665
2666
2667
2668
2669
2670
2671
2672
2673
2674
2675
2676
2677
2678
2679
2680
2681
2682
2683
2684
2685
2686
2687
2688
2689
2690
2691
2692
2693
2694
2695
2696
2697
2698
2699
2700
2701
2702
2703
2704
2705
2706
2707
2708
2709
2710
2711
2712
2713
2714
2715
2716
2717
2718
2719
2720
2721
2722
2723
2724
2725
2726
2727
2728
2729
2730
2731
2732
2733
2734
2735
2736
2737
2738
2739
2740
2741
2742
2743
2744
2745
2746
2747
2748
2749
2750
2751
2752
2753
2754
2755
2756
2757
2758
2759
2760
2761
2762
2763
2764
2765
2766
2767
2768
2769
2770
2771
2772
2773
2774
2775
2776
2777
2778
2779
2780
2781
2782
2783
2784
2785
2786
2787
2788
2789
2790
2791
2792
2793
2794
2795
2796
2797
2798
2799
2800
2801
2802
2803
2804
2805
2806
2807
2808
2809
2810
2811
2812
2813
2814
2815
2816
2817
2818
2819
2820
2821
2822
2823
2824
2825
2826
2827
2828
2829
2830
2831
2832
2833
2834
2835
2836
2837
2838
2839
2840
2841
2842
2843
2844
2845
2846
2847
2848
2849
2850
2851
2852
2853
2854
2855
2856
2857
2858
2859
2860
2861
2862
2863
2864
2865
2866
2867
2868
2869
2870
2871
2872
2873
2874
2875
2876
2877
2878
2879
2880
2881
2882
2883
2884
2885
2886
2887
2888
2889
2890
2891
2892
2893
2894
2895
2896
2897
2898
2899
2900
2901
2902
2903
2904
2905
2906
2907
2908
2909
2910
2911
2912
2913
2914
2915
2916
2917
2918
2919
2920
2921
2922
2923
2924
2925
2926
2927
2928
2929
2930
2931
2932
2933
2934
2935
2936
2937
2938
2939
2940
2941
2942
2943
2944
2945
2946
2947
2948
2949
2950
2951
2952
2953
2954
2955
2956
2957
2958
2959
2960
2961
2962
2963
2964
2965
2966
2967
2968
2969
2970
2971
2972
2973
2974
2975
2976
2977
2978
2979
2980
2981
2982
2983
2984
2985
2986
2987
2988
2989
2990
2991
2992
2993
2994
2995
2996
2997
2998
2999
3000
3001
3002
3003
3004
3005
3006
3007
3008
3009
3010
3011
3012
3013
3014
3015
3016
3017
3018
3019
3020
3021
3022
3023
3024
3025
3026
3027
3028
3029
3030
3031
3032
3033
3034
3035
3036
3037
3038
3039
3040
3041
3042
3043
3044
3045
3046
3047
3048
3049
3050
3051
3052
3053
3054
3055
3056
3057
3058
3059
3060
3061
3062
3063
3064
3065
3066
3067
3068
3069
3070
3071
3072
3073
3074
3075
3076
3077
3078
3079
3080
3081
3082
3083
3084
3085
3086
3087
3088
3089
3090
3091
3092
3093
3094
3095
3096
3097
3098
3099
3100
3101
3102
3103
3104
3105
3106
3107
3108
3109
3110
3111
3112
3113
3114
3115
3116
3117
3118
3119
3120
3121
3122
3123
3124
3125
3126
3127
3128
3129
3130
3131
3132
3133
3134
3135
3136
3137
3138
3139
3140
3141
3142
3143
3144
3145
3146
3147
3148
3149
3150
3151
3152
3153
3154
3155
3156
3157
3158
3159
3160
3161
3162
3163
3164
3165
3166
3167
3168
3169
3170
3171
3172
3173
3174
3175
3176
3177
3178
3179
3180
3181
3182
3183
3184
3185
3186
3187
3188
3189
3190
3191
3192
3193
3194
3195
3196
3197
3198
3199
3200
3201
3202
3203
3204
3205
3206
3207
3208
3209
3210
3211
3212
3213
3214
3215
3216
3217
3218
3219
3220
3221
3222
3223
3224
3225
3226
3227
3228
3229
3230
3231
3232
3233
3234
3235
3236
3237
3238
3239
3240
3241
3242
3243
3244
3245
3246
3247
3248
3249
3250
3251
3252
3253
3254
3255
3256
3257
3258
3259
3260
3261
3262
3263
3264
3265
3266
3267
3268
3269
3270
3271
3272
3273
3274
3275
3276
3277
3278
3279
3280
3281
3282
3283
3284
3285
3286
3287
3288
3289
3290
3291
3292
3293
3294
3295
3296
3297
3298
3299
3300
3301
3302
3303
3304
3305
3306
3307
3308
3309
3310
3311
3312
3313
3314
3315
3316
3317
3318
3319
3320
3321
3322
3323
3324
3325
3326
3327
3328
3329
3330
3331
3332
3333
3334
3335
3336
3337
3338
3339
3340
3341
3342
3343
3344
3345
3346
3347
3348
3349
3350
3351
3352
3353
3354
3355
3356
3357
3358
3359
3360
3361
3362
3363
3364
3365
3366
3367
3368
3369
3370
3371
3372
3373
3374
3375
3376
3377
3378
3379
3380
3381
3382
3383
3384
3385
3386
3387
3388
3389
3390
3391
3392
3393
3394
3395
3396
3397
3398
3399
3400
3401
3402
3403
3404
3405
3406
3407
3408
3409
3410
3411
3412
3413
3414
3415
3416
3417
3418
3419
3420
3421
3422
3423
3424
3425
3426
3427
3428
3429
3430
3431
3432
3433
3434
3435
3436
3437
3438
3439
3440
3441
3442
3443
3444
3445
3446
3447
3448
3449
3450
3451
3452
3453
3454
3455
3456
3457
3458
3459
3460
3461
3462
3463
3464
3465
3466
3467
3468
3469
3470
3471
3472
3473
3474
3475
3476
3477
3478
3479
3480
3481
3482
3483
3484
3485
3486
3487
3488
3489
3490
3491
3492
3493
3494
3495
3496
3497
3498
3499
3500
3501
3502
3503
3504
3505
3506
3507
3508
3509
3510
3511
3512
3513
3514
3515
3516
3517
3518
3519
3520
3521
3522
3523
3524
3525
3526
3527
3528
3529
3530
3531
3532
3533
3534
3535
3536
3537
3538
3539
3540
3541
3542
3543
3544
3545
3546
3547
3548
3549
3550
3551
3552
3553
3554
3555
3556
3557
3558
3559
3560
3561
3562
3563
3564
3565
3566
3567
3568
3569
3570
3571
3572
3573
3574
3575
3576
3577
3578
3579
3580
3581
3582
3583
3584
3585
3586
3587
3588
3589
3590
3591
3592
3593
3594
3595
3596
3597
3598
3599
3600
3601
3602
3603
3604
3605
3606
3607
3608
3609
3610
3611
3612
3613
3614
3615
3616
3617
3618
3619
3620
3621
3622
3623
3624
3625
3626
3627
3628
3629
3630
3631
3632
3633
3634
3635
3636
3637
3638
3639
3640
3641
3642
3643
3644
3645
3646
3647
3648
3649
3650
3651
3652
3653
3654
3655
3656
3657
3658
3659
3660
3661
3662
3663
3664
3665
3666
3667
3668
3669
3670
3671
3672
3673
3674
3675
3676
3677
3678
3679
3680
3681
3682
3683
3684
3685
3686
3687
3688
3689
3690
3691
3692
3693
3694
3695
3696
3697
3698
3699
3700
3701
3702
3703
3704
3705
3706
3707
3708
3709
3710
3711
3712
3713
3714
3715
3716
3717
3718
3719
3720
3721
3722
3723
3724
3725
3726
3727
3728
3729
3730
3731
3732
3733
3734
3735
3736
3737
3738
3739
3740
3741
3742
3743
3744
3745
3746
3747
3748
3749
3750
3751
3752
3753
3754
3755
3756
3757
3758
3759
3760
3761
3762
3763
3764
3765
3766
3767
3768
3769
3770
3771
3772
3773
3774
3775
3776
3777
3778
3779
3780
3781
3782
3783
3784
3785
3786
3787
3788
3789
3790
3791
3792
3793
3794
3795
3796
3797
3798
3799
3800
3801
3802
3803
3804
3805
3806
3807
3808
3809
3810
3811
3812
3813
3814
3815
3

6/23/16



PROJ. REFERENCE NO.
U-6018

SHEET NO.
49





NOTE: EXISTING GROUND SURFACE SHOWN WAS
TAKEN FROM ELECTRONIC TIN FILE (DATED
JUNE 2019). INFERRED STRATIGRAPHY IS
DRAWN THROUGH THE BORINGS WITH BOTH
PROJECTED ONTO THE CROSS SECTION.

6/23/16



PROJ. REFERENCE NO.
U-6018


SHEET NO.
50



NOTE: EXISTING GROUND SURFACE SHOWN WAS
TAKEN FROM ELECTRONIC TIN FILE (DATED
JUNE 2019). INFERRED STRATIGRAPHY IS
DRAWN THROUGH THE BORINGS WITH BOTH
PROJECTED ONTO THE CROSS SECTION.

-Y3-

6/23/16




6/23/16



PROJ. REFERENCE NO.
U-6018

SHEET NO.
52

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75




30+00.00

NOTE: EXISTING GROUND SURFACE SHOWN WAS
TAKEN FROM ELECTRONIC TIN FILE (DATED
JUNE 2019). INFERRED STRATIGRAPHY IS
DRAWN THROUGH THE BORINGS WITH BOTH
PROJECTED ONTO THE CROSS SECTION.

-Y3-

SYNTHETIC
SEAL



6/23/16



PROJ. REFERENCE NO.
U-6018

SHEET NO.
54

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

CL

Y3_3400

34+00

CL

SS-59

840

840

835

835

830

830

825

825

820

820

RESIDUAL TAN, MEDIUM STIFF, MOIST

7

SILTY CLAY WITH TRACE ROOTS (A-2-6)

39

TAN-ORANGE, MEDIUM DENSE TO DENSE, MOIST,
SILTY SAND WITH TRACE MICA (A-2-4)

17

DRY
B.T.


34 + 00.00

NOTE: EXISTING GROUND SURFACE SHOWN WAS
TAKEN FROM ELECTRONIC TIN FILE (DATED
JUNE 2019). INFERRED STRATIGRAPHY IS
DRAWN THROUGH THE BORINGS WITH BOTH
PROJECTED ONTO THE CROSS SECTION.

-Y3-

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

SYNTHETIC
CROSS
SECTION
DRAWN
THROUGH
BORINGS
WITH
BOTH
PROJECTED
ONTO
THE
CROSS
SECTION




6/23/16



PROJ. REFERENCE NO.
U-6018

SHEET NO.
56




6/23/16




PROJ. REFERENCE NO.
U-6018

SHEET NO.
57

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75



22 + 00.00






21 + 50.00

-Y6-

NOTE: EXISTING GROUND SURFACE SHOWN WAS
TAKEN FROM ELECTRONIC TIN FILE (DATED
JUNE 2019). INFERRED STRATIGRAPHY IS
DRAWN THROUGH THE BORINGS WITH BOTH
PROJECTED ONTO THE CROSS SECTION.

EXISTING GROUND SURFACE SHOWN WAS
TAKEN FROM ELECTRONIC TIN FILE (DATED
JUNE 2019). INFERRED STRATIGRAPHY IS
DRAWN THROUGH THE BORINGS WITH BOTH
PROJECTED ONTO THE CROSS SECTION.







NOTE: EXISTING GROUND SURFACE SHOWN WAS
TAKEN FROM ELECTRONIC TIN FILE (DATED
JUNE 2019). INFERRED STRATIGRAPHY IS
DRAWN THROUGH THE BORINGS WITH BOTH
PROJECTED ONTO THE CROSS SECTION.

6/23/16

CL






6/23/16



PROJ. REFERENCE NO.
U-6018

SHEET NO.
62



6/23/16




PROJ. REFERENCE NO.
U-6018

SHEET NO.
63

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

CL



6/23/16





PROJ. REFERENCE NO.
U-6018


SHEET NO.
64


75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

CL









6/23/16




PROJ. REFERENCE NO.
U-6018

SHEET NO.
68


75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

CL



NOTE: EXISTING GROUND SURFACE SHOWN WAS TAKEN FROM ELECTRONIC TIN FILE (DATED JUNE 2019). INFERRED STRATIGRAPHY IS DRAWN THROUGH THE BORINGS WITH BOTH PROJECTED ONTO THE CROSS SECTION.

-Y9-



6/23/16




PROJ. REFERENCE NO.
U-6018

SHEET NO.
70

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

℄

NOTE: EXISTING GROUND SURFACE SHOWN WAS
TAKEN FROM ELECTRONIC TIN FILE (DATED
JUNE 2019). INFERRED STRATIGRAPHY IS
DRAWN THROUGH THE BORINGS WITH BOTH
PROJECTED ONTO THE CROSS SECTION.




-RPA-


6/23/16
CUSTOMER: \$
PROJECT: \$
SHEET: \$
DATE: \$
BY: \$
CHECKED: \$
APPROVED: \$



$$\mathcal{C}$$

NOTE: EXISTING GROUND SURFACE SHOWN WAS
TAKEN FROM ELECTRONIC TIN FILE (DATED :
JUNE 2019). INFERRED STRATIGRAPHY IS :
DRAWN THROUGH THE BORINGS WITH BOTH :
PROJECTED ONTO THE CROSS SECTION. :





6/23/16



PROJ. REFERENCE NO.
U-6018

SHEET NO.
74

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

℄

NOTE: EXISTING GROUND SURFACE SHOWN WAS
TAKEN FROM ELECTRONIC TIN FILE (DATED
JUNE 2019). INFERRED STRATIGRAPHY IS
DRAWN THROUGH THE BORINGS WITH BOTH
PROJECTED ONTO THE CROSS SECTION.

860

860

855

855

850

850

845

845

840

840

835

835

830

830


GROUND SURFACE

ROADWAY EMBANKMENT BROWN, MEDIUM DENSE, MOIST, SILTY SAND
WITH TRACE ROOTS (A-2-4)

RESIDUAL ORANGE-TAN, STIFF, MOIST, SILTY CLAY (A-7)

ORANGE-TAN, MEDIUM DENSE, MOIST, SILTY SAND
WITH TRACE MICA (A-2-4)

RPA 1960
19+60
40 FT RT



DRY
B.T.

(1)

(10)

(4)

19 + 50.00


-RPA-

6/23/16
CUSTOMER: \$
DRAWN BY: \$
CHECKED BY: \$
APPROVED BY: \$
DATE: \$


6/23/16

2015105105110115120125130

0
E



6/23/16




15+00

12+00
-RPD-

NOTE: EXISTING GROUND SURFACE SHOWN WAS
TAKEN FROM ELECTRONIC TIN FILE (DATED
JUNE 2019). INFERRED STRATIGRAPHY IS
DRAWN THROUGH THE BORINGS WITH BOTH
PROJECTED ONTO THE CROSS SECTION.

6/23/16



11+00
-RAB2-

NOTE: EXISTING GROUND SURFACE SHOWN WAS
TAKEN FROM ELECTRONIC TIN FILE (DATED
JUNE 2019). INFERRED STRATIGRAPHY IS
DRAWN THROUGH THE BORINGS WITH BOTH
PROJECTED ONTO THE CROSS SECTION.

PROJECT REFERENCE NO.	SHEET NO.
U-6018	78

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT

ROADWAY
SUBSURFACE INVESTIGATION

APPENDIX A
SOIL TEST RESULTS

SOIL TEST RESULTS																
SAMPLE NO.	STATION		DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC	% CBR
							C. Sand	F. Sand	Silt	Clay	10	40	200			
SS-38	36+00	-L-	0.2-1.5	A-7-5	75	42	19.7	11.42	9.81	59.06	97.52	85.74	68.91	27.3	-	-
SS-47	38+00	-L-	0.1-1.5	A-6	32	16	23.66	20.97	25.15	30.22	99.53	86.35	60.29	16.1	-	-
SS-50	30+00	-Y3-	0.1-1.5	A-6	27	13	33.35	26.01	9.74	30.9	99.11	80.86	43.8	12.8	-	-
SS-59	34+00	-Y3-	0.2-1.5	A-7-6	42	21	28.31	16.92	10.05	44.72	97.06	80.92	55.27	12.5	-	-
SS-62	19+00	-Y3-	0.2-1.5	A-7-5	68	38	12.62	8.17	14.32	64.89	99.05	92.08	79.65	29.8	-	-
SS-65	21+00	-Y3-	0.2-1.5	A-6	36	19	30.59	16.09	10.89	42.42	99.1	82.19	54.7	12.7	-	-
SS-69	23+00	-Y3-	3.5-5.0	A-6	31	17	26.28	21.97	15.68	36.07	99.65	86.68	55.17	16.2	-	-
SS-89	22+00	-Y6-	0.0-1.5	A-7-6	67	40	19.67	9.92	11.8	58.61	94.37	81.71	68.13	29.6	-	-
SS-92	17+00	-Y5-	0.0-1.5	A-7-6	48	33	13.73	13.36	25.56	47.35	94.79	87.07	71.96	17.3	-	-
SS-102	23+00	-Y9-	3.5-5.0	A-7-6	47	30	24.96	18.08	12.51	44.44	99.78	87.92	59.46	24	-	-
SS-105	21+00	-Y9-	0.2-1.5	A-6	38	14	35.85	22.01	12.04	30.1	92.81	72.87	41.92	16.0	-	-
SS-108	19+00	-Y9-	0.2-0.8	A-4	20	6	36.99	27.94	12.33	22.74	96	74.55	37.86	10.7	-	-
SS-109	19+00	-Y9-	0.8-1.5	A-7-6	56	35	19.17	17.93	9.39	53.5	99.28	88.8	65.44	18.2	-	-
S-2	73+20	-L-	0.7-5.0	A-6	38	19	30.8	21.6	17.1	30.4	95.4	76.8	49.3	7.4	-	-
S-5	34+50	-L-	0.8-5.0	A-2-6	24	12	41.2	26.9	9.4	22.5	97.26	76.1	34.1	23.9	-	-
CBR #1	14+00	-RPA-	1.0-10.0	A-2-4	34	8	42.1	29.8	10.0	18.1	100.0	77.7	32.5	16.6	-	4.5
CBR #2	63+97	-L-	2.0-7.0	A-4	33	7	37.4	29.5	15.2	18.0	98.0	76.5	37.5	19.9	-	2.8
CBR #3	19+00	-Y9-	2.0-10.0	A-4	27	9	33.9	33.4	21.1	11.7	99.0	75.2	36.5	11.2	-	4.7
CBR #4	17+00	-Y5-	2.0-10.0	A-6	38	14	72.4	14.1	1.7	11.8	99.8	95.8	84.5	19.0	-	1.4