


PROJECT: 15BPR.108.3

CONTRACT: C205014

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS


JOHNSTON COUNTY



STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	15BPR.108.3	1	
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
15BPR.108.1	-	P.E.	
15BPR.108.3	-	CONST.	

LOCATION: BRIDGE #500042 ON US 70 OVER I-95
BRIDGE #500608 ON SR 1923 OVER NEUSE RIVER

TYPE OF WORK: BRIDGE PRESERVATION - POLYMER CONCRETE BRIDGE DECK OVERLAY, SILANE DECK TREATMENT, JOINT REHABILITATION, CONCRETE MEDIAN REPLACEMENT, STRUCTURAL STEEL REPAIRS, CLEANING AND PAINTING EXISTING WEATHERING STEEL AND SUBSTRUCTURE REPAIRS.



VICINITY MAP - JOHNSTON CO.



DESIGN DATA

JOHNSTON COUNTY

#500042 ADT 2018 = 26,000
#500608 ADT 2018 = 8,900

PROJECT LENGTH

JOHNSTON COUNTY

#500042 = 0.053 MILE
#500608 = 0.566 MILE

Prepared In the Office of:



MI ENGINEERING
1011 SCHAUB DRIVE, SUITE 100
RALEIGH, NC 27606
(919) 851-6606
FIRM PE NUMBER : P-0671

for the North Carolina Department of Transportation

2024 STANDARD SPECIFICATIONS

MI ENGINEERING CONTACT

LETTING DATE:
JUNE 17, 2025

MORRIS ISRAELNAIM, P.E.
PROJECT ENGINEER

NCDOT CONTACT

TIMOTHY M. SHERRILL, P.E.
PROJECT ENGINEER




3/19/2025

BYRON E. ATKINSON, P.E.
PROJECT DESIGN ENGINEER

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

JOHNSTON COUNTY



STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	15BPR.108.3	1A	
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
15BPR.108.1	-	P.E.	
15BPR.108.3	-	CONST.	

LOCATION: BRIDGE #500042 ON US 70 OVER I-95
BRIDGE #500608 ON SR 1923 OVER NEUSE RIVER

TYPE OF WORK: BRIDGE PRESERVATION - POLYMER CONCRETE BRIDGE DECK OVERLAY, SILANE DECK TREATMENT, JOINT REHABILITATION, CONCRETE MEDIAN REPLACEMENT, STRUCTURAL STEEL REPAIRS, CLEANING AND PAINTING EXISTING WEATHERING STEEL AND SUBSTRUCTURE REPAIRS.

INDEX OF SHEETS

<i>1</i>	<i>TITLE SHEET</i>
<i>1A</i>	<i>INDEX OF SHEETS</i>
<i>S-1</i>	<i>TOTAL BILL OF MATERIAL</i>
<i>S1-1 THRU S1-20</i>	<i>STRUCTURAL PLANS - BRIDGE NO. 500042</i>
<i>S2-1 THRU S2-13</i>	<i>STRUCTURAL PLANS - BRIDGE NO. 500608</i>
<i>SD-1 THRU SD-2</i>	<i>STRUCTURAL PLANS - BRIDGE DETAILS</i>
<i>SN</i>	<i>STANDARD NOTES</i>

PROJECT: 15BPR.108.3

CONTRACT: C205014



3/19/2025
10:02:39 AM
\$USERNAME\$

Filename: N:\NC BrIdges\M24001\37_15BPR.108_Johnston Co. Br. Rehab (2)\Structures\400_005_15BPR\08_SMU_TBOM1.dgn

— TOTAL BILL OF MATERIAL —											
BRIDGE NO.	GROOVING BRIDGE FLOORS	CONCRETE WORK FOR MEDIAN REPLACEMENT	SHOTCRETE REPAIRS	EPOXY RESIN INJECTION	FOAM JOINT SEALS FOR PRESERVATION	EXPANSION JOINT SEALS FOR PRESERVATION	POLYESTER POLYMER CONCRETE MATERIALS	EPOXY POLYMER CONCRETE MATERIALS (ALTERNATE)	SCARIFYING BRIDGE DECK	SHOTBLASTING BRIDGE DECK	PLACING & FINISHING POLYMER CONCRETE OVERLAY
	SQ. FT.	SQ. FT.	CU. FT.	LIN. FT.	LIN. FT.	LIN. FT.	CU. YDS.	CU. YDS.	SQ. YDS.	SQ. YDS.	SQ. YDS.
500042	23,573	74	38.6	15.0	226.2	335.1	99.0	99.0	2844	2844	2844
500608	---	---	---	---	435.5	---	---	---	---	10,770	---
TOTAL	23,573	74	38.6	15.0	661.7	335.1	99.0	99.0	2844	13,614	2844

— TOTAL BILL OF MATERIAL —							
BRIDGE NO.	EPOXY COATING	BEAM REPAIR PLATING	SILANE DECK TREATMENT	CLEANING AND PAINTING EXISTING WEATHERING STEEL FOR BRIDGE # ___	PAINTING CONTAINMENT FOR BRIDGE # ___	MISC. HARDWARE REPLACEMENT	POLLUTION CONTROL
	SQ. FT.	LBS.	SQ. YDS.	LUMP SUM	LUMP SUM	EACH	LUMP SUM
500042	1580	1325	---	LUMP SUM	LUMP SUM	---	LUMP SUM
500608	---	---	10,770	---	---	7	---
TOTAL	1580	1325	10,770	LUMP SUM	LUMP SUM	7	LUMP SUM

NOTE:

AT THE TIME OF THE PREPARATION OF THESE PLANS, IT WAS NOT ANTICIPATED THAT THE FOLLOWING ITEM(S) LISTED WOULD BE REQUIRED. HOWEVER, IT MAY BE DETERMINED IN THE FIELD THAT THE FOLLOWING ITEM(S) LISTED, OR OTHER WORK WILL BE NECESSARY TO PROPERLY COMPLETE THE INTENDED BRIDGE PRESERVATION/REHABILITATION WORK. THE CONTRACTOR SHALL BE PREPARED TO PERFORM SUCH WORK IN A TIMELY MANNER, AS DETERMINED IN THE FIELD. SUCH WORK SHALL BE CONSIDERED EXTRA WORK AND SHALL BE ADDRESSED AS PER ARTICLE 104-7 OF THE STANDARD SPECIFICATIONS. PROJECT SPECIAL PROVISIONS THAT OUTLINE REQUIREMENTS FOR THESE POTENTIAL ADDITIONAL WORK ITEMS HAVE BEEN PROVIDED IN THE PROJECT DOCUMENTS, BUT NO QUANTITIES HAVE BEEN LISTED. ACTUAL PAY ITEMS, QUANTITIES, AND COSTS WILL BE ESTABLISHED, AS REQUIRED, IF EXTRA WORK IS ENCOUNTERED. UNANTICIPATED ITEMS:

ITEM	DESCRIPTION	UNIT
1	CLASS II SURFACE PREPARATION	SY
2	CLASS III SURFACE PREPARATION	SY
3	CONCRETE DECK REPAIR FOR POLYMER CONCRETE OVERLAY	SY
4	CONCRETE DECK REPAIR FOR SILANE DECK TREATMENT	SF
5	VOLUMETRIC MIXER	LS
6	CONCRETE REPAIRS	CF

PROJECT NO. 15BPR.108.3
JOHNSTON COUNTY
 BRIDGE NO. 500042, 500608



STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

TOTAL BILL OF MATERIAL

**DOCUMENT NOT CONSIDERED FINAL
 UNLESS ALL SIGNATURES COMPLETED**



MI ENGINEERING
 1011 SCHAUB DRIVE, SUITE 100
 RALEIGH, NC 27606
 (919) 851-6606
 FIRM PE NUMBER : P-0671

REVISIONS					
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		

SHEET NO.
S-1
 TOTAL SHEETS
36

DRAWN BY : <u>B.E. LANNING</u>	DATE : <u>10/2024</u>
CHECKED BY : <u>B.E. ATKINSON</u>	DATE : <u>01/2025</u>
DESIGN ENGINEER OF RECORD : <u>B.E. ATKINSON</u>	DATE : <u>01/2025</u>



LOCATION SKETCH

INFORMATION INDICATED ON THE LOCATION SKETCH SHALL BE CONSIDERED GENERAL INFORMATION ONLY. CONTRACTOR SHALL CONFIRM, THROUGH OTHER SOURCES, SPECIFIC INFORMATION REGARDING THE BRIDGES, ROADWAYS, UTILITIES, THE SURROUNDING AREA, AND ANY OTHER ASPECTS THAT MAY BE NECESSARY TO PERFORM AND COMPLETE THE PROJECT.

BRIDGE COORDINATES	
LATITUDE	LONGITUDE
35°-31'-9.84"	78°-17'-22.45"

NOTES:

- SEE CONTRACT DOCUMENTS FOR LANE WIDTHS, SEQUENCING AND OTHER TRAFFIC CONTROL MEASURES FOR STAGING OF OVERLAY SURFACE PREPARATION AND POLYMER CONCRETE (PC) PLACEMENT.
- THE CONTRACTOR'S ATTENTION IS CALLED TO THE FACT THAT DUE TO THE NATURE OF PRESERVATION PROJECTS, THE EXTENT OF WORK CANNOT ALWAYS BE ACCURATELY DETERMINED PRIOR TO COMMENCEMENT OF WORK. REPAIR LOCATIONS AND ESTIMATES OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIR.
- EXISTING DIMENSIONS AND BRIDGE CONDITION ARE FROM THE BEST INFORMATION AVAILABLE. THE CONTRACTOR SHALL FIELD VERIFY THE INFORMATION SHOWN ON THE PLANS AND NOTIFY THE ENGINEER IF ACTUAL DIMENSIONS AND CONDITIONS DIFFER.
- THE CONTRACTOR SHALL HAVE NO CLAIM WHATSOEVER AGAINST THE DEPARTMENT OF TRANSPORTATION FOR ANY DELAYS OR ADDITIONAL COST INCURRED BASED ON DIFFERENCES BETWEEN THAT SHOWN ON THE PLANS AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.
- IT IS THE CONTRACTOR'S RESPONSIBILITY TO FOLLOW ALL STATE AND FEDERAL SAFETY REQUIREMENTS.
- WORK ON THE BRIDGE SHALL BE PERFORMED SO AS NOT TO ALLOW DEBRIS TO FALL BELOW, EXCEPT WHERE THE CONTRACTOR'S PLAN USES PLATFORMS, NETS, SCREEN OR OTHER PROTECTIVE DEVICES TO CATCH THE MATERIAL. THE CONTRACTOR SHALL SUBMIT PLANS FOR CONSTRUCTION IN ACCORDANCE WITH ARTICLE 402-2 OF THE STANDARD SPECIFICATIONS AND THE PROJECT SPECIAL PROVISIONS.
- ANY DAMAGE TO EXISTING REINFORCING STEEL DURING CONTRACTOR'S OPERATION SHALL BE REPAIRED AS DIRECTED BY THE ENGINEER AND PERFORMED AT NO ADDITIONAL COST TO THE DEPARTMENT.
- FOR CONTROL OF TRAFFIC AND LIMITS ON PHASING OF CONSTRUCTION, SEE CONTRACT DOCUMENTS.
- PRIOR TO BEGINNING WORK, THE CONTRACTOR SHALL SUBMIT FOR REVIEW AND APPROVAL A COMPLETE SEQUENCE OF TASKS FOR EACH OPERATION AFFECTING THE BRIDGE SURFACE AND/OR TRAFFIC.
- FOR OTHER DESIGN DATA AND GENERAL NOTES, SEE SHEET SN.
- FOR FALSEWORK AND FORMWORK, SEE SPECIAL PROVISIONS.
- FOR SUBMITTAL OF WORKING DRAWINGS, SEE SPECIAL PROVISIONS.
- FOR CRANE SAFETY, SEE SPECIAL PROVISIONS.
- FOR GROUT FOR STRUCTURES, SEE SPECIAL PROVISIONS.
- FOR MAINTENANCE AND PROTECTION OF TRAFFIC BENEATH BRIDGE, SEE SPECIAL PROVISIONS.
- ALL PAVEMENT MARKING WILL BE IN ACCORDANCE WITH THE CONTRACT DOCUMENTS.
- EXISTING JOINTS AND DECK DRAINS SHALL BE SEALED PRIOR TO BEGINNING SURFACE PREPARATIONS OF THE BRIDGE DECK. THE CONTRACTOR SHALL TAKE CARE THAT ANY CONSTRUCTION DEBRIS THAT COLLECTS IN THE DRAINS IS CONTAINED. DRAINS IN SHOULDERS OF ADJACENT TRAVEL LANES SHALL BE KEPT FREE AND CLEAR OF DEBRIS.
- LONGITUDINAL CONSTRUCTION JOINTS OF OVERLAYS SHALL BE LOCATED ALONG THE CENTERLINE OR EDGE OF TRAVEL LANES.
- FOR SCARIFYING BRIDGE DECK, SHOTBLASTING BRIDGE DECK AND CLASS II SURFACE PREPARATION, SEE OVERLAY SURFACE PREPARATION FOR POLYMER CONCRETE SPECIAL PROVISION.
- FOR CONCRETE DECK REPAIR FOR PC OVERLAY, PC MATERIALS, AND PLACING AND FINISHING PC OVERLAY, SEE POLYMER CONCRETE BRIDGE DECK OVERLAY SPECIAL PROVISION.
- FOR PAINTING, POLLUTION CONTROL AND PAINTING CONTAINMENT, SEE PAINTING EXISTING WEATHERING STEEL STRUCTURE SPECIAL PROVISIONS.
- FOR EXPANSION JOINT SEAL FOR PRESERVATION, SEE SPECIAL PROVISIONS.
- FOR FOAM JOINT SEALS FOR PRESERVATION, SEE SPECIAL PROVISIONS.
- FOR CONCRETE REPAIRS, SEE SPECIAL PROVISIONS.
- FOR SHOTCRETE REPAIRS, SEE SPECIAL PROVISIONS.
- FOR EPOXY RESIN INJECTION, SEE SPECIAL PROVISIONS.
- FOR EPOXY COATING AND DEBRIS REMOVAL, SEE SPECIAL PROVISIONS.
- FOR BEAM REPAIR PLATING, SEE SPECIAL PROVISIONS.

PROJECT NO. 15BPR.108.3
JOHNSTON COUNTY
 BRIDGE NO. 500042

SHEET 2 OF 2



STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

GENERAL DRAWING

FOR BRIDGE ON US 70
 OVER I-95 BETWEEN
 SR 2398 AND SR 2375

**DOCUMENT NOT CONSIDERED FINAL
 UNLESS ALL SIGNATURES COMPLETED**

MI ENGINEERING
 1011 SCHAUB DRIVE, SUITE 100
 RALEIGH, NC 27606
 (919) 851-6606
 FIRM PE NUMBER : P-0671


REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			S1-2 TOTAL SHEETS: 36
2			4			

DRAWN BY :	B. E. LANNING	DATE :	10/2024
CHECKED BY :	B. E. ATKINSON	DATE :	01/2025
DESIGN ENGINEER OF RECORD :	B. E. ATKINSON	DATE :	01/2025


3/19/2025 10:03:21 AM \$USERNAME\$ File: \\nc-brldges\w24001\37-15BPR.108..Johnston Co. Br. Rehab (2)\Structures\401_003_15BPR108_SML_CD2_500042.dgn

3/19/2025
10:05:30 AM
\$USERNAME\$


File Name: N:\NC Bridges\W24001.37_15BPR.108_15BPR108_SMU_JT3_500042.dgn




SECTION THRU RAIL NORMAL TO JOINT




**TYPE II - ELEVATION VIEW
COVER PLATE DETAILS**



SECTION A-A




BLOCK OUT DETAIL
SEE "SECTION A-A" FOR OTHER DETAILS



**PLAN ELEVATION
CONCRETE INSERT**

* * EACH WELDED ATTACHMENT OF WIRE TO FERRULE SHALL DEVELOP THE TENSILE STRENGTH OF THE WIRE.



PLAN OF EXPANSION JOINT SEAL

TABLE A			
LOCATION	①	②	③
BENT 1	2 3/16"	2"	1 3/4"
BENT 2	2 1/16"	1 7/8"	1 3/4"
BENT 3	1 13/16"	1 3/4"	1 11/16"

DATA FROM EXISTING PLANS.



**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**



MI ENGINEERING
1011 SCHAUB DRIVE, SUITE 100
RALEIGH, NC 27606
(919) 851-6606
FIRM PE NUMBER : P-0671

PROJECT NO. 15BPR.108.3
JOHNSTON COUNTY
BRIDGE NO. 500042
SHEET 2 OF 2

DEPARTMENT OF TRANSPORTATION RALEIGH					
EXPANSION JOINT SEAL REPAIR DETAILS AT BENT 1, 2, AND 3					
REVISIONS					
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		

SHEET NO.	S1-9
TOTAL SHEETS	36

3/19/2025
10:06:54 AM
\$USERNAME\$
Filename: N:\NC Bridges\W2400137_15BPR.108_Johnston Co. Br. Rehab (2)\Structures\401_027_15BPR108_SMU.BTIB.500042.dgn



NOTES:
FOR NOTES AND QUANTITIES, SEE SHEET 1 OF 2.

KEY

	SHOTCRETE REPAIR
	ERI EPOXY RESIN INJECTION
	CONCRETE REPAIR

PROJECT NO. 15BPR.108.3
JOHNSTON COUNTY
BRIDGE NO. 500042
SHEET 2 OF 2



**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**


MI ENGINEERING
1011 SCHAUB DRIVE, SUITE 100
RALEIGH, NC 27606
(919) 851-6606
FIRM PE NUMBER : P-0671

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH
**SUBSTRUCTURE REPAIRS
BENT 1**


DRAWN BY : <u>B.E. LANNING</u>	DATE : <u>12/2024</u>
CHECKED BY : <u>B.E. ATKINSON</u>	DATE : <u>01/2025</u>
DESIGN ENGINEER OF RECORD : <u>B.E. ATKINSON</u>	DATE : <u>01/2025</u>

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			S1-14
2			4			TOTAL SHEETS 36

NOTES:
FOR NOTES AND QUANTITIES, SEE SHEET 1 OF 2.



PLAN
END BENT 2



ELEVATION
END BENT 2

- KEY**
-  SHOTCRETE REPAIR
 -  ERI EPOXY RESIN INJECTION
 -  CONCRETE REPAIR



**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

MI ENGINEERING
1011 SCHAUH DRIVE, SUITE 100
RALEIGH, NC 27606
(919) 851-6606
FIRM PE NUMBER: P-0671

PROJECT NO. 15BPR.108.3
JOHNSTON COUNTY
BRIDGE NO. 500042

SHEET 2 OF 2


STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

**SUBSTRUCTURE REPAIRS
END BENT 2**

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S1-20
1			3			TOTAL SHEETS 36
2			4			

3/19/2025 10:07:49 AM \$USER\$
Filename: N:\NC Bridges\W2400137_15BPR.108_Johnston Co. Br. Rehab (2)\Structures\401_039_15BPR108_SMU.EB2B.500042.dgn

DRAWN BY: B.E. LANNING DATE: 12/2024
CHECKED BY: B.E. ATKINSON DATE: 01/2025
DESIGN ENGINEER OF RECORD: B.E. ATKINSON DATE: 01/2025




SECTION ALONG ORIGINAL GRADE LINE

NOTES:
 PROFILE INFORMATION IS TAKEN FROM THE ORIGINAL PLANS AND THE ROUTINE INSPECTION REPORT DATED 12/07/2023.
 BRIDGE ORIENTATION CONFORMS TO EXISTING PLAN AND ROUTINE INSPECTION REPORT.

- SCOPE OF WORK:**
- SHOTBLAST EXISTING CONCRETE DECK.
 - APPLY SILANE DECK TREATMENT.
 - REMOVE EXISTING JOINT MATERIAL AND INSTALL FOAM JOINTS.
 - MISC. HARWARE REPLACEMENT.

I HEREBY CERTIFY THAT THIS STRUCTURE HAS REHABILITATED ACCORDING TO THESE PLANS OR AS NOTED HEREIN.
 RESIDENT ENGINEER _____ DATE _____



PLAN

PROJECT NO. 15BPR.108.3
JOHNSTON COUNTY
 BRIDGE NO. 500608

SHEET 1 OF 4
 STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
GENERAL DRAWING
 FOR BRIDGE ON SR 1923
 OVER NEUSE RIVER BETWEEN
 SR 1913 AND SR 1003





DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED
 MI ENGINEERING
 1011 SCHAUB DRIVE, SUITE 100
 RALEIGH, NC 27606
 (919) 851-6606
 FIRM PE NUMBER: P-0671

REVISIONS						SHEET NO.	
NO.	BY:	DATE:	NO.	BY:	DATE:	S2-1	
1			3			TOTAL SHEETS 36	
2			4				

DRAWN BY: B.E. LANNING DATE: 12/2024
 CHECKED BY: B.E. ATKINSON DATE: 01/2025
 DESIGN ENGINEER OF RECORD: B.E. ATKINSON DATE: 01/2025

3/19/2025 10:08:18 AM \$USER\$
 File Name: N:\NC BrIdges\W2400137_15BPR.108_108\Johnston Co. Br. Rehab (2)\Structures\402.001.15BPR108.SMU.GD1.500608.dgn



PROJECT NO. 15BPR.108.3
JOHNSTON COUNTY
 BRIDGE NO. 500608
 SHEET 2 OF 4



STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
GENERAL DRAWING
 FOR BRIDGE ON SR 1923
 OVER NEUSE RIVER BETWEEN
 SR 1913 AND SR 1003

**DOCUMENT NOT CONSIDERED FINAL
 UNLESS ALL SIGNATURES COMPLETED**

MI ENGINEERING
 1011 SCHAUB DRIVE, SUITE 100
 RALEIGH, NC 27606
 (919) 851-6606
 FIRM PE NUMBER: P-0671

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S2-2
1			3			TOTAL SHEETS
2			4			36

DRAWN BY: <u>B.E. LANNING</u>	DATE: <u>12/2024</u>
CHECKED BY: <u>B.E. ATKINSON</u>	DATE: <u>01/2025</u>
DESIGN ENGINEER OF RECORD: <u>B.E. ATKINSON</u>	DATE: <u>01/2025</u>

3/19/2025 10:08:28 AM \$USER\$
 File name: N:\NC Bridges\W2400137_15BPR.108_108\Johnston Co. Br. Rehab (2)\Structures\402.003.15BPR108_SMU_G02_500608.dgn

AS-BUILT REPAIR QUANTITY TABLE		
TOP OF DECK REPAIRS SPANS S, T, U		
	ESTIMATE	ACTUAL
CONCRETE DECK REPAIR FOR SILANE DECK TREATMENT	0.0 SF	
SHOTBLASTING BRIDGE DECK	1359 SY	
SILANE DECK TREATMENT	1359 SY	


NOTES:

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE BASED ON THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER WILL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATIONS AND DESCRIPTION OF THE REPAIRS AND ENTER THE ACTUAL QUANTITIES INTO THE AS-BUILT REPAIR QUANTITY TABLE.



FOR SECTION B-B, SEE "JOINT DETAILS" SHEET.

FOR CONCRETE DECK REPAIR FOR SILANE DECK TREATMENT, SEE SPECIAL PROVISIONS.

FOR SHOTBLASTING BRIDGE DECK AND SILANE DECK TREATMENT, SEE SPECIAL PROVISIONS.



PLAN OF SPANS S, T, U



DETAIL "A"

PROJECT NO. 15BPR.108.3
JOHNSTON COUNTY
 BRIDGE NO. 500608
 SHEET 6 OF 7



STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
**SILANE DECK TREATMENT
 SPANS S THRU U**

**DOCUMENT NOT CONSIDERED FINAL
 UNLESS ALL SIGNATURES COMPLETED**

MI ENGINEERING
 1011 SCHAUB DRIVE, SUITE 100
 RALEIGH, NC 27606
 (919) 851-6606
 FIRM PE NUMBER : P-0671

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			S2-11
2			4			TOTAL SHEETS 36

DRAWN BY : <u>B.E. LANNING</u>	DATE : <u>01/2025</u>
CHECKED BY : <u>B.E. ATKINSON</u>	DATE : <u>01/2025</u>
DESIGN ENGINEER OF RECORD : <u>B.E. ATKINSON</u>	DATE : <u>01/2025</u>

3/19/2025 10:10:58 AM \$USERNAME\$ File Name: N:\NC Bridges\W2400137_15BPR.108_108\Johnston Co. Br. Rehab (2)\Structures\402.021.15BPR108.SMU.DWG_500608.dgn

STANDARD NOTES

DESIGN DATA:

SPECIFICATIONS	AASHTO (CURRENT)
LIVE LOAD	SEE PLANS
IMPACT ALLOWANCE	SEE AASHTO
STRESS IN EXTREME FIBER OF STRUCTURAL STEEL - AASHTO M270 GRADE 36 ----	20,000 LBS. PER SQ. IN.
- AASHTO M270 GRADE 50W ---	27,000 LBS. PER SQ. IN.
- AASHTO M270 GRADE 50 ----	27,000 LBS. PER SQ. IN.
REINFORCING STEEL IN TENSION - GRADE 60	24,000 LBS. PER SQ. IN.
CONCRETE IN COMPRESSION	1,200 LBS. PER SQ. IN.
CONCRETE IN SHEAR	SEE AASHTO
STRUCTURAL TIMBER - TREATED OR UNTREATED EXTREME FIBER STRESS ----	1,800 LBS. PER SQ. IN.
COMPRESSION PERPENDICULAR TO GRAIN OF TIMBER	375 LBS. PER SQ. IN.
EQUIVALENT FLUID PRESSURE OF EARTH	30 LBS. PER CU. FT. (MINIMUM)

MATERIAL AND WORKMANSHIP:

EXCEPT AS MAY OTHERWISE BE SPECIFIED ON PLANS OR IN THE SPECIAL PROVISIONS, ALL MATERIAL AND WORKMANSHIP SHALL BE IN ACCORDANCE WITH THE 2024 "STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES" OF THE N. C. DEPARTMENT OF TRANSPORTATION.

STEEL SHEET PILING FOR PERMANENT OR TEMPORARY APPLICATIONS SHALL BE HOT ROLLED.

CONCRETE:

UNLESS OTHERWISE REQUIRED ON PLANS, CLASS A CONCRETE SHALL BE USED FOR ALL PORTIONS OF ALL STRUCTURES WITH THE EXCEPTION THAT: CLASS AA CONCRETE SHALL BE USED IN BRIDGE SUPERSTRUCTURES, ABUTMENT BACKWALLS, AND APPROACH SLABS; AND CLASS B CONCRETE SHALL BE USED FOR SLOPE PROTECTION AND RIP RAP.

CONCRETE CHAMFERS:

UNLESS OTHERWISE NOTED ON THE PLANS, ALL EXPOSED CORNERS ON STRUCTURES SHALL BE CHAMFERED $\frac{3}{4}$ " WITH THE FOLLOWING EXCEPTIONS: TOP CORNERS OF CURBS MAY BE ROUNDED TO 1 $\frac{1}{2}$ " RADIUS WHICH IS BUILT INTO CURB FORMS; CORNERS OF TRANSVERSE FLOOR EXPANSION JOINTS SHALL BE ROUNDED WITH A $\frac{1}{4}$ " FINISHING TOOL UNLESS OTHERWISE REQUIRED ON PLANS; AND CORNERS OF EXPANSION JOINTS IN THE ROADWAY FACES AND TOPS OF CURBS AND SIDEWALKS SHALL BE ROUNDED TO A $\frac{1}{4}$ " RADIUS WITH A FINISHING STONE OR TOOL UNLESS OTHERWISE REQUIRED ON PLANS.

DOWELS:

DOWELS WHEN INDICATED ON PLANS AS FOR CULVERT EXTENSIONS, SHALL BE EMBEDDED AT LEAST 12" INTO THE OLD CONCRETE AND GROUTED INTO PLACE WITH 1:2 CEMENT MORTAR.

ALLOWANCE FOR DEAD LOAD DEFLECTION, SETTLEMENT, ETC. IN CASTING SUPERSTRUCTURES:

BRIDGES SHALL BE BUILT ON THE GRADE OR VERTICAL CURVE SHOWN ON PLANS. SLABS, CURBS AND PARAPETS SHALL CONFORM TO THE GRADE OR CURVE.

ALL DIMENSIONS WHICH ARE GIVEN IN SECTION AND ARE AFFECTED BY DEAD LOAD DEFLECTIONS ARE DIMENSIONS AT CENTER LINE OF BEARING UNLESS OTHERWISE NOTED ON PLANS. IN SETTING FORMS FOR STEEL BEAM BRIDGES AND PRESTRESSED CONCRETE GIRDER BRIDGES, ADJUSTMENTS SHALL BE MADE DUE TO THE DEAD LOAD DEFLECTIONS FOR THE ELEVATIONS SHOWN. WHERE BLOCKS ARE SHOWN OVER BEAMS FOR BUILDING UP TO THE SLAB, THE VERTICAL DIMENSIONS OF THE BLOCKS SHALL BE ADJUSTED BETWEEN BEARINGS TO COMPENSATE FOR DEAD LOAD DEFLECTIONS, VERTICAL CURVE ORDINATE, AND ACTUAL BEAM CAMBER. WHERE BOTTOM OF SLAB IS IN LINE WITH BOTTOM OF TOP FLANGES, DEPTH OF SLAB BETWEEN BEARINGS SHALL BE ADJUSTED TO COMPENSATE FOR DEAD LOAD DEFLECTION, VERTICAL CURVE ORDINATE, AND ACTUAL BEAM CAMBER.

IN SETTING FALSEWORK AND FORMS FOR REINFORCED CONCRETE SPANS, AN ALLOWANCE SHALL BE MADE FOR DEAD LOAD DEFLECTIONS, SETTLEMENT OF FALSEWORK, AND PERMANENT CAMBER WHICH SHALL BE PROVIDED FOR IN ADDITION TO THE ELEVATIONS SHOWN. AFTER REMOVAL OF THE FALSEWORK, THE FINISHED STRUCTURES SHALL CONFORM TO THE PROFILE AND ELEVATIONS SHOWN ON THE PLANS AND CONSTRUCTION ELEVATIONS FURNISHED BY THE ENGINEER.

DETAILED DRAWINGS FOR FALSEWORK OR FORMS FOR BRIDGE SUPERSTRUCTURE AND ANY STRUCTURE OR PARTS OF A STRUCTURE AS NOTED ON THE PLANS SHALL BE SUBMITTED TO THE ENGINEER FOR APPROVAL BEFORE CONSTRUCTION OF THE FALSEWORK OR FORMS IS STARTED.

REINFORCING STEEL:

ALL REINFORCING STEEL SHALL BE DEFORMED. DIMENSIONS RELATIVE TO PLACEMENT OF REINFORCING ARE TO CENTERS OF BARS UNLESS OTHERWISE INDICATED IN THE PLANS. DIMENSIONS ON BAR DETAILS ARE TO CENTERS OF BARS OR ARE OUT TO OUT AS INDICATED ON PLANS.

WIRE BAR SUPPORTS SHALL BE PROVIDED FOR REINFORCING STEEL WHERE INDICATED ON THE PLANS. WHEN BAR SUPPORT PIECES ARE PLACED IN CONTINUOUS LINES, THEY SHALL BE SO PLACED THAT THE ENDS OF THE SUPPORTING WIRES SHALL BE LAPPED TO LOCK LEGS ON ADJOINING PIECES.

STRUCTURAL STEEL:

AT THE CONTRACTOR'S OPTION, HE MAY SUBSTITUTE $\frac{7}{8}$ " \emptyset SHEAR STUDS FOR THE $\frac{3}{4}$ " \emptyset STUDS SPECIFIED ON THE PLANS. THIS SUBSTITUTION SHALL BE MADE AT THE RATE OF 3 - $\frac{7}{8}$ " \emptyset STUDS FOR 4 - $\frac{3}{4}$ " \emptyset STUDS, AND STUD SPACING CHANGES SHALL BE MADE AS NECESSARY TO PROVIDE THE SAME EQUIVALENT NUMBER OF $\frac{7}{8}$ " \emptyset STUDS ALONG THE BEAM AS SHOWN FOR $\frac{3}{4}$ " \emptyset STUDS BASED ON THE RATIO OF 3 - $\frac{7}{8}$ " \emptyset STUDS FOR 4 - $\frac{3}{4}$ " \emptyset STUDS. STUDS OF THE LENGTH SPECIFIED ON THE PLANS MUST BE PROVIDED. THE MAXIMUM SPACING SHALL BE 2'-0".

EXCEPT AT THE INTERIOR SUPPORTS OF CONTINUOUS BEAMS WHERE THE COVER PLATE IS IN CONTACT WITH BEARING PLATE, THE CONTRACTOR MAY, AT HIS OPTION, SUBSTITUTE FOR THE COVER PLATES DESIGNATED ON THE PLANS COVER PLATES OF THE EQUIVALENT AREA PROVIDED THESE PLATES ARE AT LEAST $\frac{5}{16}$ " IN THICKNESS AND DO NOT EXCEED A WIDTH EQUAL TO THE FLANGE WIDTH LESS 2" OR A THICKNESS EQUAL TO 2 TIMES THE FLANGE THICKNESS. THE SIZE OF FILLET WELDS SHALL CONFORM TO THE REQUIREMENTS OF THE CURRENT ANSI/AASHTO/AWS "BRIDGE WELDING CODE". ELECTROSLAG WELDING WILL NOT BE PERMITTED.

WITH THE SOLE EXCEPTION OF EDGES AT SURFACES WHICH BEAR ON OTHER SURFACES, ALL SHARP EDGES AND ENDS OF SHAPES AND PLATES SHALL BE SLIGHTLY ROUNDED BY SUITABLE MEANS TO A RADIUS OF APPROXIMATELY $\frac{1}{16}$ " OR EQUIVALENT FLAT SURFACE AT A SUITABLE ANGLE PRIOR TO PAINTING, GALVANIZING, OR METALLIZING.

HANDRAILS AND POSTS:

METAL STANDARDS AND FACES OF THE CONCRETE END POSTS FOR THE METAL RAIL SHALL BE SET NORMAL TO THE GRADE OF THE CURB, UNLESS OTHERWISE SHOWN ON PLANS. THE METAL RAIL AND TOPS OF CONCRETE POSTS USED WITH THE ALUMINUM RAIL SHALL BE BUILT PARALLEL TO THE GRADE OF THE CURB.

METAL HANDRAILS SHALL BE IN ACCORDANCE WITH THE PLANS. RAILS SHALL BE AS MANUFACTURED FOR BRIDGE RAILING. CASTINGS SHALL BE OF A UNIFORM APPEARANCE. FINIS AND OTHER DEFORMATIONS RESULTING FROM CASTING OR OTHERWISE SHALL BE REMOVED IN A MANNER SO THAT A UNIFORM COLORING OF THE COMPLETED CASTING SHALL BE OBTAINED. CASTINGS WITH DISCOLORATIONS OR OF NON-UNIFORM COLORING WILL NOT BE ACCEPTED. CERTIFIED MILL REPORTS ARE REQUIRED FOR METAL RAILS AND POSTS.

SPECIAL NOTES:

GENERALLY, IN CASE OF DISCREPANCY, THIS STANDARD SHEET OF NOTES SHALL GOVERN OVER THE SPECIFICATIONS, BUT THE REMAINDER OF THE PLANS SHALL GOVERN OVER NOTES HEREON, AND SPECIAL PROVISIONS SHALL GOVERN OVER ALL. SEE SPECIFICATIONS ARTICLE 105-4.