

REFERENCE: U-6005

PROJECT: 47140

SEE SHEET 3 FOR PLAN SHEET LAYOUT
AT TIME OF INVESTIGATION

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	U-6005	1	29

CONTENTS

<u>LINE</u>	<u>STATION</u>	<u>PLAN</u>	<u>CROSS SECTION</u>
-L-	12+00 to 61+25	4-7	8-26
-RAB-	10+00 to 13+58	5	
-Y1-	10+00 to 11+00	4	
-Y2-	11+40 to 12+56	4	
-Y3-	10+00 to 11+00	4	
-Y4-	12+40 to 13+46	4	
-Y5-	10+00 to 11+30	4	
-Y6-	10+30 to 12+60	5	27
-Y7-	10+00 to 12+00	5	27
-Y8-	10+00 to 11+00	5	
-Y9-	10+00 to 12+15	6	
-Y10-	10+00 to 11+00	7	
-Y11-	10+00 to 12+46	7	

APPENDICES

<u>APPENDIX</u>	<u>TITLE</u>	<u>SHEET</u>
A	LABORATORY TESTING SUMMARY	29

ROADWAY SUBSURFACE INVESTIGATION

COUNTY FORSYTH
PROJECT DESCRIPTION NC 65 (BETHANIA-RURAL
HALL RD.) WIDENING FROM US 52 TO SR 3983
(NORTHRIDGE PARK DR.) IN RURAL HALL

INVENTORY

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT (919) 707-6850. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

- NOTES:
- THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.
 - BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

PERSONNEL

M. STANBURY
D. JOYNES
N. MOHS, LG

INVESTIGATED BY N. MOHS, LG
DRAWN BY M. STANBURY
CHECKED BY S. JOHNSON, PE, PG
SUBMITTED BY N. MOHS, LG
DATE JULY 2022



DocuSigned by:
Nathan D. Mohs 07/20/2022
35A8C1164EE6A00 SIGNATURE DATE

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**


**NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT
SUBSURFACE INVESTIGATION
SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS**

SOIL DESCRIPTION										GRADATION										ROCK DESCRIPTION										TERMS AND DEFINITIONS																																																																										
<p>SOIL IS CONSIDERED UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER AND YIELD LESS THAN 100 BLOWS PER FOOT ACCORDING TO THE STANDARD PENETRATION TEST (AASHTO T 208, ASTM D1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY INCLUDE THE FOLLOWING: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. FOR EXAMPLE, <i>VERY STIFF, GRAY, SILTY CLAY, MOIST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC, A-7-6</i></p>										<p>WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. UNIFORMLY GRADED - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES.</p>										<p>HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED, AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS IN NON-COASTAL PLAIN MATERIAL. THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:</p>										<p>ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER. AQUIFER - A WATER BEARING FORMATION OR STRATA. ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND. ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC. ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE. CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE. COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE. CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK. DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL. DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH. FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE. FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES. FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLODGED FROM PARENT MATERIAL. FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM. FORMATION (FM) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD. JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED. LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT. LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS. MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS, MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM. RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK. ROCK QUALITY DESIGNATION (RQD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. SAPROLITE (SAP.) - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK. SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS. SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE. STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N OR BPF) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE. STRATA ROCK QUALITY DESIGNATION (SROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.</p>																																																																										
SOIL LEGEND AND AASHTO CLASSIFICATION										ANGULARITY OF GRAINS										WEATHERED ROCK (WR)										NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT N VALUES > 100 BLOWS PER FOOT IF TESTED.																																																																										
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>GENERAL CLASS.</th> <th colspan="5">GRANULAR MATERIALS (<= 35% PASSING #200)</th> <th colspan="5">SILT-CLAY MATERIALS (> 35% PASSING #200)</th> <th colspan="5">ORGANIC MATERIALS</th> </tr> <tr> <th>GROUP CLASS.</th> <th>A-1</th> <th>A-3</th> <th>A-2</th> <th>A-4</th> <th>A-5</th> <th>A-6</th> <th>A-7</th> <th>A-1, A-2</th> <th>A-3</th> <th>A-4, A-5</th> <th>A-6, A-7</th> <th colspan="5"></th> </tr> <tr> <th>SYMBOL</th> <td colspan="5">[Pattern]</td> <td colspan="5">[Pattern]</td> <td colspan="5">[Pattern]</td> </tr> <tr> <th>% PASSING</th> <td colspan="5">50 MX, 30 MX, 15 MX, 10 MX, 5 MN</td> <td colspan="5">35 MX, 35 MX, 35 MX, 35 MX, 36 MN, 36 MN, 36 MN, 36 MN</td> <td colspan="5">GRANULAR SOILS, SILT-CLAY SOILS, MUCK, PEAT</td> </tr> </table>										GENERAL CLASS.	GRANULAR MATERIALS (<= 35% PASSING #200)					SILT-CLAY MATERIALS (> 35% PASSING #200)					ORGANIC MATERIALS					GROUP CLASS.	A-1	A-3	A-2	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7						SYMBOL	[Pattern]					[Pattern]					[Pattern]					% PASSING	50 MX, 30 MX, 15 MX, 10 MX, 5 MN					35 MX, 35 MX, 35 MX, 35 MX, 36 MN, 36 MN, 36 MN, 36 MN					GRANULAR SOILS, SILT-CLAY SOILS, MUCK, PEAT					<p>THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS IS DESIGNATED BY THE TERMS: ANGULAR, SUBANGULAR, SUBROUNDED, OR ROUNDED.</p>										<p>CRISTALLINE ROCK (CR)</p> <p>NON-CRYSTALLINE ROCK (NCR)</p> <p>COASTAL PLAIN SEDIMENTARY ROCK (CP)</p>										<p>CRYSTALLINE ROCK (CR) - FINE TO COARSE GRAIN IGNEOUS AND METAMORPHIC ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES GRANITE, GNEISS, GABBRO, SCHIST, ETC.</p> <p>NON-CRYSTALLINE ROCK (NCR) - FINE TO COARSE GRAIN METAMORPHIC AND NON-COASTAL PLAIN SEDIMENTARY ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES PHYLLITE, SLATE, SANDSTONE, ETC.</p> <p>COASTAL PLAIN SEDIMENTARY ROCK (CP) - COASTAL PLAIN SEDIMENTS CEMENTED INTO ROCK, BUT MAY NOT YIELD SPT REFUSAL. ROCK TYPE INCLUDES LIMESTONE, SANDSTONE, CEMENTED SHELL BEDS, ETC.</p>									
GENERAL CLASS.	GRANULAR MATERIALS (<= 35% PASSING #200)					SILT-CLAY MATERIALS (> 35% PASSING #200)					ORGANIC MATERIALS																																																																																													
GROUP CLASS.	A-1	A-3	A-2	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7																																																																																													
SYMBOL	[Pattern]					[Pattern]					[Pattern]																																																																																													
% PASSING	50 MX, 30 MX, 15 MX, 10 MX, 5 MN					35 MX, 35 MX, 35 MX, 35 MX, 36 MN, 36 MN, 36 MN, 36 MN					GRANULAR SOILS, SILT-CLAY SOILS, MUCK, PEAT																																																																																													
MINERALOGICAL COMPOSITION										COMPRESSION										WEATHERING										CRISTALLINE ROCK (CR)																																																																										
<p>MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHEN THEY ARE CONSIDERED OF SIGNIFICANCE.</p>										<p>SLIGHTLY COMPRESSIBLE LL < 31 MODERATELY COMPRESSIBLE LL = 31 - 50 HIGHLY COMPRESSIBLE LL > 50</p>										<p>FRESH - ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING. ROCK RINGS UNDER HAMMER IF CRYSTALLINE.</p> <p>VERY SLIGHT (V SLI.) - ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN, CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF OF A CRYSTALLINE NATURE.</p> <p>SLIGHT (SLI.) - ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO 1 INCH. OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR CRYSTALS ARE DULL AND DISCOLORED. CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS.</p> <p>MODERATE (MOD.) - SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY. ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED WITH FRESH ROCK.</p> <p>MODERATELY SEVERE (MOD. SEV.) - ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK. ROCK GIVES "CLUNK" SOUND WHEN STRUCK. <i>IF TESTED, WOULD YIELD SPT REFUSAL</i></p> <p>SEVERE (SEV.) - ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC CLEAR AND EVIDENT BUT REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN. <i>IF TESTED, WOULD YIELD SPT N VALUES > 100 BPF</i></p> <p>VERY SEVERE (V SEV.) - ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC ELEMENTS ARE DISCERNIBLE BUT MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK REMAINING. SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE THAT ONLY MINOR VESTIGES OF ORIGINAL ROCK FABRIC REMAIN. <i>IF TESTED, WOULD YIELD SPT N VALUES < 100 BPF</i></p> <p>COMPLETE - ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.</p>										<p>CRISTALLINE ROCK (CR) - FINE TO COARSE GRAIN IGNEOUS AND METAMORPHIC ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES GRANITE, GNEISS, GABBRO, SCHIST, ETC.</p>																																																																										
PERCENTAGE OF MATERIAL										GROUND WATER										MISCELLANEOUS SYMBOLS										ROCK HARDNESS																																																																										
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>ORGANIC MATERIAL</th> <th>GRANULAR SOILS</th> <th>SILT - CLAY SOILS</th> <th>OTHER MATERIAL</th> </tr> <tr> <td>TRACE OF ORGANIC MATTER</td> <td>2 - 3%</td> <td>3 - 5%</td> <td>TRACE</td> </tr> <tr> <td>LITTLE ORGANIC MATTER</td> <td>3 - 5%</td> <td>5 - 12%</td> <td>LITTLE</td> </tr> <tr> <td>MODERATELY ORGANIC</td> <td>5 - 10%</td> <td>12 - 20%</td> <td>SOME</td> </tr> <tr> <td>HIGHLY ORGANIC</td> <td>> 10%</td> <td>> 20%</td> <td>HIGHLY</td> </tr> </table>										ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL	TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE	LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE	MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME	HIGHLY ORGANIC	> 10%	> 20%	HIGHLY	<p>WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING</p> <p>STATIC WATER LEVEL AFTER 24 HOURS</p> <p>PERCHED WATER, SATURATED ZONE, OR WATER BEARING STRATA</p> <p>SPRING OR SEEP</p>										<p>ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT</p> <p>INFERRED SOIL BOUNDARY</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>25/025 DIP & DIP DIRECTION OF ROCK STRUCTURES</p> <p>SPT DMT TEST</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>CONE PENETROMETER TEST</p> <p>SOUNDING ROD</p> <p>TEST BORING WITH CORE</p> <p>SPT N-VALUE</p>										<p>VERY HARD - CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.</p> <p>HARD - CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.</p> <p>MODERATELY HARD - CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.</p> <p>MEDIUM HARD - CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.</p> <p>SOFT - CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.</p> <p>VERY SOFT - CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.</p>																																																						
ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL																																																																																																					
TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE																																																																																																					
LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE																																																																																																					
MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME																																																																																																					
HIGHLY ORGANIC	> 10%	> 20%	HIGHLY																																																																																																					
TEXTURE OR GRAIN SIZE										RECOMMENDATION SYMBOLS										ABBREVIATIONS										FRACTURE SPACING																																																																										
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>U.S. STD. SIEVE SIZE OPENING (MM)</th> <th>4</th> <th>10</th> <th>40</th> <th>60</th> <th>200</th> <th>270</th> </tr> <tr> <td></td> <td>4.75</td> <td>2.00</td> <td>0.42</td> <td>0.25</td> <td>0.075</td> <td>0.053</td> </tr> </table>										U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270		4.75	2.00	0.42	0.25	0.075	0.053	<p>UNDERCUT [Symbol]</p> <p>SHALLOW UNDERCUT [Symbol]</p> <p>UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE [Symbol]</p> <p>UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK [Symbol]</p>										<p>AR - AUGER REFUSAL BT - BORING TERMINATED CL - CLAY CPT - COARSE PENETRATION TEST CSE - COARSE DMT - DILATOMETER TEST DPT - DYNAMIC PENETRATION TEST e - VOID RATIO F - FINE FOSS. - FOSSILIFEROUS FRAC. - FRACTURED, FRACTURES FRAGS. - FRAGMENTS HI. - HIGHLY</p> <p>MED. - MEDIUM MICA - MICACEOUS MOD. - MODERATELY NP - NON PLASTIC ORG. - ORGANIC PMT - PRESSUREMETER TEST SAP. - SAPROLITIC SD. - SAND, SANDY SL. - SILT, SILTY SLI. - SLIGHTLY TCR - TRICONE REFUSAL w - MOISTURE CONTENT V - VERY</p> <p>VST - VANE SHEAR TEST WEA. - WEATHERED γ_s - UNIT WEIGHT γ_d - DRY UNIT WEIGHT</p> <p>SAMPLE ABBREVIATIONS</p> <p>S - BULK SS - SPLIT SPOON ST - SHELBY TUBE RS - ROCK RT - RECOMPACTED TRIAXIAL CBR - CALIFORNIA BEARING RATIO</p>										<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>TERM</th> <th>SPACING</th> <th>TERM</th> <th>THICKNESS</th> </tr> <tr> <td>VERY WIDE</td> <td>MORE THAN 10 FEET</td> <td>VERY THICKLY BEDDED</td> <td>4 FEET</td> </tr> <tr> <td>WIDE</td> <td>3 TO 10 FEET</td> <td>THICKLY BEDDED</td> <td>1.5 - 4 FEET</td> </tr> <tr> <td>MODERATELY CLOSE</td> <td>1 TO 3 FEET</td> <td>THINLY BEDDED</td> <td>0.16 - 1.5 FEET</td> </tr> <tr> <td>CLOSE</td> <td>0.16 TO 1 FOOT</td> <td>VERY THINLY BEDDED</td> <td>0.03 - 0.16 FEET</td> </tr> <tr> <td>VERY CLOSE</td> <td>LESS THAN 0.16 FEET</td> <td>THICKLY LAMINATED</td> <td>0.008 - 0.03 FEET</td> </tr> <tr> <td></td> <td></td> <td>THINLY LAMINATED</td> <td>< 0.008 FEET</td> </tr> </table>										TERM	SPACING	TERM	THICKNESS	VERY WIDE	MORE THAN 10 FEET	VERY THICKLY BEDDED	4 FEET	WIDE	3 TO 10 FEET	THICKLY BEDDED	1.5 - 4 FEET	MODERATELY CLOSE	1 TO 3 FEET	THINLY BEDDED	0.16 - 1.5 FEET	CLOSE	0.16 TO 1 FOOT	VERY THINLY BEDDED	0.03 - 0.16 FEET	VERY CLOSE	LESS THAN 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET			THINLY LAMINATED	< 0.008 FEET																							
U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270																																																																																																		
	4.75	2.00	0.42	0.25	0.075	0.053																																																																																																		
TERM	SPACING	TERM	THICKNESS																																																																																																					
VERY WIDE	MORE THAN 10 FEET	VERY THICKLY BEDDED	4 FEET																																																																																																					
WIDE	3 TO 10 FEET	THICKLY BEDDED	1.5 - 4 FEET																																																																																																					
MODERATELY CLOSE	1 TO 3 FEET	THINLY BEDDED	0.16 - 1.5 FEET																																																																																																					
CLOSE	0.16 TO 1 FOOT	VERY THINLY BEDDED	0.03 - 0.16 FEET																																																																																																					
VERY CLOSE	LESS THAN 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET																																																																																																					
		THINLY LAMINATED	< 0.008 FEET																																																																																																					
SOIL MOISTURE - CORRELATION OF TERMS										EQUIPMENT USED ON SUBJECT PROJECT										INDURATION										NOTES:																																																																										
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>SOIL MOISTURE SCALE (ATTERBERG LIMITS)</th> <th>FIELD MOISTURE DESCRIPTION</th> <th>GUIDE FOR FIELD MOISTURE DESCRIPTION</th> </tr> <tr> <td>LL - LIQUID LIMIT</td> <td>- SATURATED - (SAT.)</td> <td>USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE</td> </tr> <tr> <td>PLASTIC RANGE (PI)</td> <td>- WET - (W)</td> <td>SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td>OM - OPTIMUM MOISTURE</td> <td>- MOIST - (M)</td> <td>SOLID; AT OR NEAR OPTIMUM MOISTURE</td> </tr> <tr> <td>SL - SHRINKAGE LIMIT</td> <td>- DRY - (D)</td> <td>REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td> </tr> </table>										SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION	LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE	PLASTIC RANGE (PI)	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE	OM - OPTIMUM MOISTURE	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE	SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE	<p>DRILL UNITS:</p> <p><input type="checkbox"/> CME-45C</p> <p><input type="checkbox"/> CME-55</p> <p><input type="checkbox"/> CME-550</p> <p><input type="checkbox"/> VANE SHEAR TEST</p> <p><input type="checkbox"/> PORTABLE HOIST</p> <p><input checked="" type="checkbox"/> D-50 TRACK</p> <p>ADVANCING TOOLS:</p> <p><input type="checkbox"/> CLAY BITS</p> <p><input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER</p> <p><input checked="" type="checkbox"/> 8" HOLLOW AUGERS</p> <p><input type="checkbox"/> HARD FACED FINGER BITS</p> <p><input checked="" type="checkbox"/> TUNG-CARBIDE INSERTS</p> <p><input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER</p> <p><input type="checkbox"/> TRICONE _____ * STEEL TEETH</p> <p><input type="checkbox"/> TRICONE _____ * TUNG-CARB.</p> <p><input type="checkbox"/> CORE BIT</p> <p>HAMMER TYPE:</p> <p><input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL</p> <p>CORE SIZE:</p> <p><input type="checkbox"/> -B _____ <input type="checkbox"/> -H _____</p> <p><input type="checkbox"/> -N _____</p> <p>HAND TOOLS:</p> <p><input type="checkbox"/> POST HOLE DIGGER</p> <p><input checked="" type="checkbox"/> HAND AUGER</p> <p><input type="checkbox"/> SOUNDING ROD</p> <p><input type="checkbox"/> VANE SHEAR TEST</p>										<p>FRAGILE - RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</p> <p>MODERATELY INDURATED - GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</p> <p>INDURATED - GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</p> <p>EXTREMELY INDURATED - SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</p>										<p>BENCH MARK: ELEVATIONS DETERMINED FROM FILE U6005_LS_TIN.TIN DATED 11-19-2018</p> <p style="text-align: right;">ELEVATION: _____ FEET</p>																																																											
SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION																																																																																																						
LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE																																																																																																						
PLASTIC RANGE (PI)	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE																																																																																																						
OM - OPTIMUM MOISTURE	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE																																																																																																						
SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE																																																																																																						
PLASTICITY										INDURATION										INDURATION										INDURATION																																																																										
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>NON PLASTIC</th> <th>SLIGHTLY PLASTIC</th> <th>MODERATELY PLASTIC</th> <th>HIGHLY PLASTIC</th> </tr> <tr> <td>0-5</td> <td>6-15</td> <td>16-25</td> <td>26 OR MORE</td> </tr> </table>										NON PLASTIC	SLIGHTLY PLASTIC	MODERATELY PLASTIC	HIGHLY PLASTIC	0-5	6-15	16-25	26 OR MORE	<p>FRAGILE - RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</p> <p>MODERATELY INDURATED - GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</p> <p>INDURATED - GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</p> <p>EXTREMELY INDURATED - SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</p>										<p>FRAGILE - RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</p> <p>MODERATELY INDURATED - GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</p> <p>INDURATED - GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</p> <p>EXTREMELY INDURATED - SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</p>										<p>FRAGILE - RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</p> <p>MODERATELY INDURATED - GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</p> <p>INDURATED - GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</p> <p>EXTREMELY INDURATED - SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</p>																																																																		
NON PLASTIC	SLIGHTLY PLASTIC	MODERATELY PLASTIC	HIGHLY PLASTIC																																																																																																					
0-5	6-15	16-25	26 OR MORE																																																																																																					
COLOR										INDURATION										INDURATION										INDURATION																																																																										
<p>DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-GRAY). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.</p>										<p>FRAGILE - RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</p> <p>MODERATELY INDURATED - GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</p> <p>INDURATED - GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</p> <p>EXTREMELY INDURATED - SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</p>										<p>FRAGILE - RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</p> <p>MODERATELY INDURATED - GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</p> <p>INDURATED - GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</p> <p>EXTREMELY INDURATED - SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</p>										<p>FRAGILE - RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</p> <p>MODERATELY INDURATED - GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</p> <p>INDURATED - GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</p> <p>EXTREMELY INDURATED - SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</p>																																																																										

09/08/20

TIP PROJECT: U-6005

See Sheet 1A For Index of Sheets



25% PRELIMINARY PLANS




STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

FORSYTH COUNTY

LOCATION: NC 65 (BETHANIA RURAL HALL RD.) FROM
ANGUS STREET TO SR 3983 (NORTHRIDGE PARK DRIVE)

TYPE OF WORK: GRADING, DRAINAGE, PAVING, AND SIGNALS

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	U-6005	3	29
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
47140.1.1	N/A	P.E.	




V&M
Vaughn & Melton
Consulting Engineers

Asheville, North Carolina
828-252-2798

909-877-9455 Raleigh, NC
704-251-0488 Charlotte, NC
770-627-3590 Atlanta, GA


Boone, NC 828-252-9933
Tri-Cities, TN 423-467-8401
Knoxville, TN 865-546-5800
Spartanburg, SC 864-574-4775
Charleston, SC 843-974-5650
Middleboro, KY 606-248-1600

Copyright © 2006 Vaughn & Melton, Inc. All Rights Reserved



★ PROPOSED SIGNAL
PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION
INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION
DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

GRAPHIC SCALES



DESIGN DATA

ADT 2021 = 12,800
ADT 2040 = 15,600
K = 10 %
D = 60 %
T = 6 % *
V = 50 MPH
* TTST = 3% DUAL 3%
FUNC CLASS = MINOR ARTERIAL

PROJECT LENGTH

LENGTH ROADWAY TIP PROJECT U-6005 = 0.933 MILES
TOTAL LENGTH OF TIP PROJECT U-6005 = 0.933 MILES

Prepared In the Office of:
V&M Vaughn & Melton
Consulting Engineers
1318-F Patton Ave. Asheville, NC 28806

2018 STANDARD SPECIFICATIONS

RIGHT OF WAY DATE:
JUNE 30, 2021

LETTING DATE:
JUNE 20, 2023

JOEL SETZER, PE
PROJECT ENGINEER


DANIEL ALMUETI, EIT
PROJECT DESIGN ENGINEER

HYDRAULICS ENGINEER

SIGNATURE: _____ P.E.

ROADWAY DESIGN ENGINEER

SIGNATURE: _____ P.E.



I:\21453 AM R\Projects\20-70-09 U-6005 RDWY\CADD\GEOTECH\PlanProf\U6005.GEO_RDWY_TSH.dgn
nathan.mohs

July 12, 2022

STATE PROJECT: 47140.1.1 (U-6005)
 PROJECT ID: 39378
 COUNTY: Forsyth
 DESCRIPTION: NC 65 (Bethania-Rural Hall Rd.) Widening from US 52 to SR 3983 (Northridge Park Dr.) in Rural Hall
 SUBJECT: Geotechnical Report – Inventory

Project Description

This project consists of widening NC 65 (-L-). The project begins just north of Tobacoville Road and runs 0.933 miles south to Angus Street. A traffic circle will be added to the intersection of Falconbridge Road (-Y7-) and Spruce Garden Drive (-Y6-).

The geotechnical field investigation was conducted from May to June 2022. Standard Penetration Tests were performed with a track mounted D-50 with an automatic hammer along the project mainline. Borings performed in the existing roadway were filled and patched immediately after drilling (FIAD). Several hand augers were also performed along -L-, -Y6-, and -Y7- in areas of shallow cut/fill. Representative soil samples were collected for visual classification in the field and submitted for laboratory analysis by ICE, PLLC in Columbia, SC.

The following alignments, totaling 0.933 miles, were investigated. Subsurface cross-sections of these alignments are included in this report:

<u>Line</u>	<u>Stations</u>	
-L-	10+00	to 63+46
-Y6-	10+00	to 11+00
-Y7-	10+00	to 13+06

Physiography and Geology

The project is in the gently rolling terrain of central North Carolina. The project runs through the town of Rural Hall, North of US 52.

Geologically, the project lies within the Milton terrane. The Milton terrane consists of gneiss, schist, and metamorphose intrusive rocks. The rocks were formed 460 to 470 Mya. Generally, the rocks of the terrane are interpreted as part of a chain of volcanic islands.

The geology of the project area consists of residual soils which are the weathered remains of parent material, crystalline meta-volcanic rock.

Soil Properties

Soils encountered at the project site include roadway embankment, artificial fill and residual soils.

Roadway embankment mostly underlies the existing lanes of NC-65 and the surrounding surface roads. Due to the area topography portions of the roadway were graded and paved. Where encountered roadway embankment soils range from 3 to 7 feet thick. These soils mainly consist of dry to moist, medium to very stiff, sandy silt and silty clay (AASHTO classifications of A-4 and A-7-5/A-7-6). Some of the A-7 soils exhibit a PI of 26 or more and are considered to be highly plastic.

Artificial fill is found in landscaping features along NC-65 from approximate stations -L- 51+00 to 55+00 and 57+00 to 59+50. The artificial fill soils range from 1.5 to 3.5 feet thick. The artificial fills soils consist of moist, loose, silty sand and medium stiff, silty clay (AASHTO classifications of A-2-4 and A-7-5). Both soil types were placed during the during the construction of NC 65 from nearby borrow sources.

Residual soils are found at the ground surface and immediately below the embankment soils. These soils mainly consist of dry to moist, soft to very stiff, sandy silt, clayey silt, sandy clay, and silty clay (AASHTO classifications of A-4, A-5, A-6, and A-7-5/A-7-6). Some of the A-7 soils exhibit a PI of 26 or more and are considered to be highly plastic.

Groundwater


No groundwater was encountered in any borings across this project. The investigation was conducted during a period of relatively low rainfall. Seasonal fluctuations in groundwater elevations can be expected.

Areas of Special Geotechnical Interest

1. Highly Plastic Clays: Highly plastic clay (PI>25) was encountered on the project at the following locations:

<u>Line</u>	<u>Stations</u>	<u>Offset</u>
-L-	32+00	RT
-L-	48+00	LT
-L-	57+07	LT
-L-	59+38	RT



Prepared by,

DocuSigned by:

 Nathan Mohs, LG



Engineering Geologist Manager

5/14/2017

PROJECT REFERENCE NO. U-6005	SHEET NO. 4
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
PRELIMINARY PLANS DO NOT USE FOR CONSTRUCTION	
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	





MATCHLINE -L- STA. 24+00.00 (SEE SHEET 5)



J:\6005\RDWY\CADD_GEO\TECH\Plan\Prof\U6005_GEO_RDWY_INV04.dgn


- (25) BITTING HALL HOMEOWNERS ASSOC. INC.
DB 2866 PG 4490
- (26) U.S.F.E. ASSET COMPANY 5, LLC.
DB 3362 PG 829
- (A) HOME S.F.R. BORROWER IV, LLC.
DB 3381 PG 1942
- (B) DESHAUNDA HAMPTON
DB 2873 PG 191
- (C) WESLEY A. BLEVINS
DB 3035 PG 1709
- (D) TAMEKA MEBANE
DB 3243 PG 3161
- (E) HEATHER OVERBY
DB 3057 PG 2986
- (F) DAKOTA DONTNAN
DB 3299 PG 3366
- (G) FREDIA DAVIS
DB 2817 PG 851
- (H) ANGELA AUSTIN
DB 2985 PG 626
- (I) HOME S.F.R. BORROWER II, LLC
DB 3344 PG 4256
- (J)
- (K)
- (L)
- (M)
- (N)
- (O)
- (P)
- (AA)
- (BB)
- (CC)
- (DD)



PROJECT REFERENCE NO. U-6005	SHEET NO. 5
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
PRELIMINARY PLANS DO NOT USE FOR CONSTRUCTION INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

MATCHLINE -L- STA 24+00.00 (SEE SHEET 4)

MATCHLINE -L- STA 38+00.00 (SEE SHEET 6)




-L- CURVE DATA		-Y6- CURVE DATA		-Y7- CURVE DATA		-RAB- CURVE DATA	
PI Sta 29+93.36	PI Sta 39+08.03	PI Sta 11+52.64	PI Sta 12+56.98	PI Sta 10+00.07			
$\Delta = 3^\circ 23' 44.0"$ (LT)	$\Delta = 28^\circ 27' 55.3"$ (LT)	$\Delta = 45^\circ 26' 33.8"$ (LT)	$\Delta = 41^\circ 24' 08.7"$ (RT)	$\Delta = 359^\circ 51' 27.7"$ (LT)			
D = 1' 54' 35.5"	D = 2' 51' 53.2"	D = 19' 59' 01.8"	D = 40' 00' 00.0"	D = 100' 31' 08.1"			
L = 177.79'	L = 993.63'	L = 227.40'	L = 103.51'	L = 358.00'			
T = 88.92'	T = 507.29'	T = 120.06'	T = 54.13'	T = 0.07'			
R = 3,000.00'	R = 2,000.00'	R = 286.71'	R = 143.24'	R = 57.00'			
DS = 50 MPH	DS = 50 MPH	DS = SC	DS = SC	DS = 25 MPH			
e = NC	e = 3%	e = NC	e = NC	e = 2%			

PROJECT REFERENCE NO. U-6005	SHEET NO. 6
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
PRELIMINARY PLANS DO NOT USE FOR CONSTRUCTION	
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	



MATCHLINE -L- STA. 38+00.00 (SEE SHEET 5)


MATCHLINE -L- STA. 50+00.00 (SEE SHEET 7)



-L- CURVE DATA


PI Sta 39+08.03	PI Sta 48+36.05
$\Delta = 28^\circ 27' 55.3" (LT)$	$\Delta = 4^\circ 30' 34.5" (LT)$
$D = 2^\circ 51' 53.2"$	$D = 1^\circ 54' 35.5"$
$L = 993.63'$	$L = 236.12'$
$T = 507.29'$	$T = 118.12'$
$R = 2,000.00'$	$R = 3,000.00'$
$DS = 50 MPH$	$DS = 50 MPH$
$e = 3\%$	$e = RC$

8/17/99
 10:22:10 AM
 R:\Projects\20-70-09 U-6005 RDWY\CADD_GEDTECH\Plan\Prof\U6005_GEO_RDWY_INV07.dgn
 Connor-Starkman





MATCHLINE -L- STA. 50+00.00 (SEE SHEET 6)

-L- CURVE DATA		
PI Sta 52+71.08 Δ = 5° 35' 51.2" (RT) D = 1' 54' 35.5" L = 293.09' T = 146.66' R = 3,000.00' DS = 50 MPH e = RC	PI Sta 59+65.63 Δ = 13° 20' 57.8" (RT) D = 4' 58' 56.1" L = 267.94' T = 134.58' R = 1,150.00' DS = 50 MPH e = NC	PI Sta 62+07.21 Δ = 5° 55' 00.0" (RT) D = 5' 00' 00.0" L = 118.33' T = 59.22' R = 1,145.92' DS = 50 MPH e = 4%
-Y10- CURVE DATA		-Y11- CURVE DATA
PI Sta 12+35.38 Δ = 41° 42' 00.0" (LT) D = 76' 23' 39.7" L = 54.59' T = 28.56' R = 75.00' DS = 25 MPH e = NC	PI Sta 13+09.56 Δ = 40° 56' 08.6" (RT) D = 54' 34' 02.7" L = 75.02' T = 39.19' R = 105.00' DS = 25 MPH e = NC	PI Sta 11+03.12 Δ = 22° 32' 00.0" (LT) D = 16' 45' 00.0" L = 134.53' T = 68.14' R = 342.06' DS = 25 MPH e = NC




REVISIONS








6/23/16





8:31:38 AM
 R:\Projects\20-70\09 U-6005 RDWY\CADD\GEO\TECH\sec\U6005_GEO_RDWY_XSI.dgn
 connor.stephens

















(A) ROADWAY EMBANKMENT, BROWN AND ORANGE, DRY, STIFF, SANDY SILT WITH TRACE ASPHALT GRAVEL

RESIDUAL, BROWN AND RED, MOIST, MEDIUM STIFF TO STIFF, SANDY SILT WITH TRACE GRAVEL

DRY
(05/22)


42 + 00.00


RESIDUAL, RED, ORANGE AND BROWN, MOIST, MEDIUM STIFF TO STIFF, SANDY SILT AND SILTY CLAY WITH TRACE GRAVEL


DRY
(05/22)



40 + 00.00


—L—






















8:31:06 AM
 R:\Projects\20-70\09 U-6005 RDWY\CADD\GEO\TECH\use\U6005_GEO_RDWY_XS1.dgn
 connor.stephens





RESIDUAL, BROWN AND RED, MOIST, STIFF, SANDY CLAY WITH TRACE GRAVEL

11 + 50.00
-Y7-

DRY
(05/22)

S-32

10 + 50
4:1

DRY
(05/22)

RESIDUAL, ORANGE, MOIST, VERY STIFF, SILTY CLAY WITH SOME GRAVEL

10 + 50.00
-Y6-

*NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT*

SUBSURFACE INVESTIGATION

APPENDIX A
LABORATORY TESTING SUMMARY

REFERENCE: U-6005

PROJECT: 47140

Laboratory Testing Summary

Project Number: 47140.1.1
TIP Number: U-6005
City/County/State: Rural Hall, Forsyth, NC
Description: NC 65 (Bethania-Rural Hall Rd.) Widening from US 52 to SR 3983 (Northridge Park Dr.) in Rural Hall

Sample No.	Alignment	Station	Offset (feet)	Depth Interval (feet)	ICE	AASHTO Class.	L.L.	P.I.	% by Weight				% Retained #4 Sieve	% Passing (sieves)			% Moisture	% Organic
					Lab No.				Coarse Sand	Fine Sand	Silt	Clay		#10	#40	#200		
SS-7	-L-	23+00	1 RT	0.8-2.3	22-0835	A-4 (0)	23	6	22.4	38.5	15.1	24	0	94.6	85.7	40.7	10.6%	-
S-34	-L-	29+00	38 LT	2.5-3.0	22-0775	A-7-5 (25)	70	20	5.7	12.3	20.5	61.5	0.3	98.9	95.9	84	33.3%	-
SS-12	-L-	30+00	CL	0.8-2.3	22-0836	A-7-6 (9)	44	18	21	22.2	20.6	36.2	0	89.7	79.3	53.3	12.9%	-
S-31	-L-	32+00	45 RT	1.5-2.0	22-0776	A-7-5 (30)	71	30	7.7	13	14.1	65.2	1.5	97.4	94.2	79	26.3%	-
S-23	-L-	36+00	25 RT	0.5-1.0	22-0777	A-6 (4)	31	12	19.7	31.3	14.6	34.4	4.5	93.2	84.8	48.8	9.4%	-
SS-16	-L-	38+00	8 LT	0.8-2.3	22-0837	A-6 (7)	37	16	17.8	27.5	16.4	38.3	0	97.8	90.2	56.1	16.3%	-
S-16	-L-	42+00	28 RT	0.5-1.0	22-0778	A-4 (0)	32	2	18.4	42.8	28.2	10.6	2	96.5	88.2	46.5	11.9%	-
SS-21	-L-	45+00	16 LT	3.5-5.0	22-0839	A-7-5 (10)	58	11	8.8	29.4	19.1	42.7	0	99.8	97.1	67.7	26.4%	-
S-12	-L-	48+00	38 LT	0.5-1.0	22-0779	A-7-5 (24)	66	28	9.9	17.5	13.2	59.4	0.3	99.1	94.9	74.3	27.1%	-
S-10	-L-	50+00	40 RT	0.5-1.0	22-0780	A-7-6 (13)	46	20	14.5	19.9	14.6	51	0	99.1	92.8	67.1	18.2%	-
S-54	-L-	52+00	30 LT	0.5-1.0	22-0810	A-7-5 (21)	58	23	8.5	16.7	22	52.8	0	98.1	94.3	76.2	17.6%	-
S-51	-L-	53+93	30 LT	2.5-3.0	22-0809	A-7-5 (17)	58	16	7.1	18.4	20.1	54.4	0	98.3	95.3	77.3	40.3%	-
S-1	-L-	56+00	47 RT	0.5-1.0	22-0781	A-4 (0)	NP	NP	14.8	43.6	28.7	12.9	0	98.6	93.6	48.8	18.2%	-
S-5	-L-	57+07	46 LT	1.5-2.0	22-0782	A-7-5 (22)	61	27	13	15.9	16.2	54.9	0	98.9	91.6	72.7	23.8%	-
S-6	-L-	57+07	46 LT	3.5-4.0	22-0783	A-7-5 (13)	64	20	25.1	17.5	16.9	40.5	17.2	73.1	59.6	44.6	18.9%	-
SS-25	-L-	59+38	13 RT	0.8-2.3	22-0838	A-7-5 (25)	61	27	8.9	13.5	18.4	59.2	0	96.3	91.6	76.7	26.9%	-
S-8	-L-	60+00	30 LT	0.5-1.0	22-0784	A-7-6 (18)	51	22	8.1	18.7	21.2	52	0	95	92.1	72.1	18.1%	-
S-32	-Y6-	10+50	27 LT	0.5-1.0	22-0785	A-7-5 (18)	60	18	8.3	17.4	29.2	45.1	0	99	94.9	77.7	26.8%	-
S-27	-Y7-	11+50	31 RT	0.5-1.0	22-0786	A-6 (4)	32	11	22.1	26.8	22.4	28.7	0	98.2	87.4	53	10.5%	-