

COMPUTED BY: E. Beverly      DATE: 1-20-21  
UPDATED BY: S. Yang      DATE: 6-4-25

(12-17-19)

STATE OF NORTH CAROLINA  
DIVISION OF HIGHWAYS

PROJECT NO.  
SF-590165

SHEET NO.  
3G-1

SUMMARY OF SUBSURFACE DRAINAGE

LINE	Station	Station	Location LT/RT/CL	Drain Type* UD/BD/SD	LF
			CONTINGENCY	SD	250
				TOTAL LF:	250

\*UD = Underdrain

\*BD = Blind Drain

\*SD = Subsurface Drain

SUMMARY OF AGGREGATE SUBGRADE/STABILIZATION

LINE	Station	Station	Aggregate Type* ASU(1/2)/ AST	Aggregate Thickness INCHES [8" for ASU(2)]	Shallow Undercut CY	Class IV Subgrade Stabilization TONS	Geotextile for Subgrade Stabilization SY	Stabilizer Aggregate TONS	Class IV Aggregate Stabilization TONS
	-L-	22+80	23+30				6312		
			CONTINGENCY		100	200	300		
				TOTAL CY/TONS/SY:	100	6512**	300**	0	0

\*ASU(1/2) = Aggregate Subgrade (Type 1 or 2)

\*AST = Aggregate Stabilization

\*\*Total tons of "Class IV Subgrade Stabilization" and total square yards of "Geotextile for Subgrade Stabilization" are only the estimated quantities for ASU(1/2)/AST and may only represent a portion of the subgrade stabilization and geotextile quantities shown in the Item Sheets of the Proposal.