ECONOLITE ASC/3-2070 LOGIC PROCESSOR PROGRAMMING DETAIL FOR LEADING PED INTERVAL (DELAYED GREEN)

(program controller as shown)

The following logic processor configuration holds the FYA on signal head 11 red for the duration of the delayed green time (leading ped interval) when serving a ped call on the opposing through phase.

- 1. From Main Menu select | 1. CONFIGURATION
- 2. From CONFIGURATION Submenu select 8. LOGIC PROCESSOR
- 3. From the LOGIC PROCESSOR Submenu select 2. LOGIC STATEMENTS

ENTER A "1" IN THE LP# FIELD, PRESS 'ENTER', AND PROGRAM AS SHOWN.

LP#:	1	COPY FROM: 1	ACTIVE:	М	(T/F)	
I F AND		ON PH WALK GREEN ON PH	2 2	IS IS	ON OF F	
THEN	SIG	SET OLP RED SET OLP YELLOW SET OVLP GREEN	1 1 1		ON OF F OF F	
ELSE						

HOLD SIGNAL HEAD 11 FYA RED DURING THE PHASE 2 DELAYED GREEN TIME (LEADING PED INTERVAL)

- 1. From Main Menu select | 1. CONFIGURATION
- 2. From CONFIGURATION Submenu select 8. LOGIC PROCESSOR
- 3. From the LOGIC PROCESSOR Submenu select 1, LOGIC STATEMENT CONTROL

ENABLE LOGIC PROCESSOR STATEMENT 1 BY POSITIONING THE CURSOR OVER THE FIELDS SHOWN BELOW AND USING THE TOGGLE KEY TO ENABLE THEM .

LOGIC STA	CONTROL															
	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6
LP 1-15	Ε	•	•			•	•		•	•		•		•	•	•
LP 16-30	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
LP 31-45	•	•	•		•	•	•	•	•	•		•	•	•	•	•
LP 46-60	•	•	•		•	•	•		•	•		•	•	•	•	•
LP 61-75	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
LP 76-90	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•

END PROGRAMMING

FLASHER CIRCUIT MODIFICATION DETAIL

PROJECT REFERENCE NO. SHEET NO.

| Sig. 3.4

U-4758

IN ORDER TO INSURE THAT SIGNALS FLASH CONCURRENTLY ON THE SAME APPROACH, MAKE THE FOLLOWING FLASHER CIRCUIT CHANGES:

- 1. ON REAR OF PDA REMOVE WIRE FROM TERM. T2-4 AND TERMINATE ON T2-2.
- 2. ON REAR OF PDA REMOVE WIRE FROM TERM. T2-5 AND TERMINATE ON T2-3.
- 3. REMOVE FLASHER UNIT 2.

THE CHANGES LISTED ABOVE TIES ALL PHASES AND OVERLAPS TO FLASHER UNIT 1.

COUNTDOWN PEDESTRIAN SIGNAL OPERATION

Countdown Ped Signals are required to display timing only during Ped Clearance Interval. Consult Ped Signal Module user's manual for instructions on selecting this feature.

ECONOLITE ASC/3-2070 STARTUP AND SOFTWARE FLASH PROGRAMMING DETAIL

(program controller as shown)

1. From Main Menu select | 2. CONTROLLER |

2. From CONTROLLER Submenu select 5. START/FLASH

START/FLASH DATA ----START UP-----1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 PHASE G A B C D E F G H I J K L M N O P FLASH>MON, NO FL TIME.. O ALL RED... 6 PWR START SEQ.. 1 MUTCD→ YES Y- G: NO

Scroll down on this screen and set "Exit FI" to Green "G"

ASC/3 FLASH SENSE INPUT CONTROL FOR RED-RED FLASH

*The NCDOT default database is programmed to addresss Yellow-Red flash. Logic Statement 100 must be modified as shown when running Red-Red flash.

- 1. From Main Menu select 1. CONFIGURATION
- 2. From CONFIGURATION Submenu select 8. LOGIC PROCESSOR
- 3. From LOGIC PROCESSOR Submenu select 2. LOGIC STATEMENTS

Change the "LP" to 100 and move the cursor down. Delete the two "CTR-SET" statements by moving the cursor over them and hitting the "C" key. then hit "ENTER", select "LP SET CIB ON", hit "ENT", and then set the number to 427.

LP#:100 COPY FROM:100 ACTIVE: M FALSE IF LP CIB CODE ON 331 F THEN LP DELAY FOR 1.0 SECONDS LP SET CIB ON 427 ELSE

TO CONTROL THE FLASH SENSE INPUT WHEN RUNNING RED-RED FLASH OPERATION.

THIS STATEMENT IS USED

Hit "ESC", then 1 for "LOGIC STATEMENT CONTROL", next verify that LP#100 is ENABLED.

END PROGRAMMING

Q AtkinsRéalis 1616 EAST MILLBROOK ROAD, SUITE 160 RALEIGH, NORTH CAROLINA 27609 (919) 876-6888 NCBEES #F-0326

THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 07-0935T2 DESIGNED: August 2025 SEALED: Ø8-14-2025 REVISED: N/A

Electrical Detail - Sheet 4 of 4 Temporary Design 2

ELECTRICAL AND PROGRAMMING Prepared for the Offices of:

SR 1820 (Skeet Club Road) SR 1818 (Johnson Street)

Division 7 Guilford County PLAN DATE: August 2025 REVIEWED BY: AM Encarnacion PREPARED BY: JT Stiff REVIEWED BY: PL Alexander REVISIONS

DOCUMENT NOT CONSIDERED

FINAL UNLESS ALL SIGNATURES COMPLETED

SIG. INVENTORY NO. 07-0935T2

INIT. DATE