

[illegible]

SIGN NUMBER: 10B	BACK COLOR: Green	DESIGN BY: SDW	CHECKED BY: WJH	May 13, 2023
TYPE: A (OH)	COPY COLOR: White	PROJECT ID: I-600I	LOCATION:	DIV: 5

QUANTITY: 1		
SIGN WIDTH: 14'-0"		
HEIGHT: 15'-0"		
TOTAL AREA: 210 Sq.Ft.		
BORDER TYPE: FLUSH		
RECESS: 0"		
WIDTH: 2"		
RADII: 12"		
NO. Z BARS: 6		
LENGTH: 160.0		

MAT'L: 0.125" (3.2 mm) ALUMINUM

USE NOTES: 1,2,3

- 1.Legend and border(except those that are colored black) shall be direct applied Grade C sheeting.
- 2.Background shall be Grade C reflective sheeting.
- 3.Shields: A, B, and C type arrows shall be on 0.032" (0.8mm) aluminum with Grade C reflective sheeting and demountable.

Spacing Factor is 1 unless specified otherwise

[illegible]

SIGN NUMBER: TYPE: A (OH) QUANTITY: 1 SIGN WIDTH: 15'-0" HEIGHT: 17'-0" TOTAL AREA: 255.01 Sq.Ft. BORDER TYPE: FLUSH RECESS: 0" WIDTH: 2" RADII: 12" NO. Z BARS: 6 LENGTH: 172.0	BACK COLOR: Green COPY COLOR: White <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <tr> <th>SYMBOL</th> <th>X</th> <th>Y</th> <th>WID</th> <th>HT</th> </tr> <tr> <td>M1_4</td> <td>55.92</td> <td>132.35</td> <td>36</td> <td>36</td> </tr> <tr> <td>M1-5-2-36-15C</td> <td>113.21</td> <td>132.35</td> <td>36</td> <td>36</td> </tr> <tr> <td>ARDOWN</td> <td>68.6</td> <td>8.82</td> <td>32.01</td> <td>21.97</td> </tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> </table> MAT'L: 0.125" (3.2 mm) ALUMINUM	SYMBOL	X	Y	WID	HT	M1_4	55.92	132.35	36	36	M1-5-2-36-15C	113.21	132.35	36	36	ARDOWN	68.6	8.82	32.01	21.97																					DESIGN BY: SDW PROJECT ID: I-6001 CHECKED BY: WJH LOCATION: Feb 19, 2025 DIV: 5
SYMBOL	X	Y	WID	HT																																						
M1_4	55.92	132.35	36	36																																						
M1-5-2-36-15C	113.21	132.35	36	36																																						
ARDOWN	68.6	8.82	32.01	21.97																																						

USE NOTES: 1,2,3,4

- Legend and border(except those that are colored black) shall be direct applied Grade A sheeting.
- Background shall be Grade C reflective sheeting.
- Shields: A, B, and C type arrows shall be on 0.032" (0.8mm) aluminum with Grade A reflective sheeting and demountable.
- Bottom panel shall be yellow Grade C sheeting. Legend shall be direct applied black non-reflective sheeting. Arrow shall be on 0.032" aluminum, black non-reflective sheeting and demountable. Yellow panel is:

Spacing Factor is 1 unless specified otherwise

Letter locations are panel edge to lower left corner																Series/Size Text Length
B	U	S	I	N	E	S	S									E 2000 86.28
Z	e	b	u	l	o	n										EM 2000 98.4
O	x	f	o	r	d											EM 2000 80
1/2	M	I	L	E												E 2000 65.08
E	X	I	T													EM 2000 36.96
O	N	L	Y													EM 2000 47.76

FILENAME: I-6001_SIGN_DSGN NORTH CAROLINA D.O.T. SIGN DETAIL

