



CLEARING AND GRUBBING EROSION CONTROL FOR CONSTRUCTION SHEET 4

NOTE: PLACE TEMPORARY ROCK SEDIMENT DAMS TYPE - B AND TEMPORARY ROCK SILT CHECKS TYPE - A AT DRAINAGE OUTLETS.

UTILIZE FABRIC INSERT INLET PROTECTION IN LIEU OF ROCK INLET SEDIMENT TRAPS, TYPE-C AS DIRECTED BY THE ENGINEER TO AVOID IMPOUNDMENT OF RUNOFF IN ROADWAY OPEN TO TRAFFIC

60 x 25 x 3
1.5 inch Skimmer
with 1.125 inch
Orifice Diameter
6 ft. weir
ID 6.1 C&G

96 x 30 x 3
1.5 inch Skimmer
with 1.500 inch
Orifice Diameter
12 ft. weir
ID 6.2 C&G

37 x 10 x 3
ID 6.3 C&G

FOR -L- PROFILE SEE SHEETS 8 & 9
FOR -Y5- PROFILE SEE SHEET 11
FOR -Y6- PROFILE SEE SHEET 11
FOR -Y7- PROFILE SEE SHEET 12
FOR -Y8- PROFILE SEE SHEET 12
FOR -TRAIL- PROFILE SEE SHEET 12
FOR ISLAND DETAIL SEE SHEET 2B-1
FOR CULVERT DESIGN SEE SHEET C-1

Prepared in the Office of: **M** MOTT MACDONALD
930 Main Campus Drive, Suite 200
Raleigh, NC 27606
www.mottmac.com

HR HDR Engineering, Inc. of the Carolinas
555 Fayetteville St., Suite 900, Raleigh, NC 27601
N.C.B.E.L.S. License Number: F-0116

PAVEMENT REMOVAL

★ NEW SIGNAL

3/31/2026 10:41:41 U-5743_EC_PSH.dgn 5743-6-6

