

REFERENCE: U-5743

PROJECT: 50165

SEE SHEET 3 FOR PLAN SHEET LAYOUT
AT TIME OF INVESTIGATION

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	U-5743	1	24

CONTENTS

LINE	STATION	PLAN	PROFILE
-L-	15+00.00 - 55+00.00	4,7	8,9
-Y1-	10+00.00 - 16+50.00	4,5	10
-Y2-	10+00.00 - 17+85.67	5	10
-Y5-	10+00.00 - 13+00.00	6	11
-Y6-	11+50.00 - 14+66.38	6	11

CROSS SECTIONS

LINE	STATION	SHEETS
-L-	22+50.00 - 25+50.00	12,13
-L-	44+50.00 - 47+50.00	14,15
-L-	50+50.00 - 53+50.00	16,17
-Y5-	11+00.00 - 13+00.00	18,19

APPENDICES

APPENDIX	TITLE	SHEETS
A	LABORATORY RESULTS	20,21

ROADWAY SUBSURFACE INVESTIGATION

COUNTY RANDOLPH
PROJECT DESCRIPTION NC 42 FROM SR 2237
(EAST SALISBURY STREET) TO NORTH OF
US 64 /NC 49 (DIXIE DRIVE) IN ASHEBORO

INVENTORY

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT (919) 707-6850. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

- NOTES:
1. THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.
 2. BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

PERSONNEL

TRIGON

WEIS, J.M.

INVESTIGATED BY FALCON ENG.

DRAWN BY HILL, M.J.

CHECKED BY HUNSBERGER, W.S.

SUBMITTED BY FALCON ENG.

DATE APRIL 2019



DocuSigned by:
W. Scott Hunsberger 4/17/2019

5A469AC80FCD49E...
SIGNATURE DATE

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT
SUBSURFACE INVESTIGATION
SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS

SOIL DESCRIPTION										GRADATION										ROCK DESCRIPTION										TERMS AND DEFINITIONS																																																																								
<p>SOIL IS CONSIDERED UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER AND YIELD LESS THAN 100 BLOWS PER FOOT ACCORDING TO THE STANDARD PENETRATION TEST (AASHTO T 206, ASTM D1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY INCLUDE THE FOLLOWING: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. FOR EXAMPLE, VERY STIFF, GRAY, SILTY CLAY, MOIST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC, A-7-6</p>										<p>WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. UNIFORMLY GRADED - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES.</p>										<p>HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED, AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS IN NON-COASTAL PLAIN MATERIAL. THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:</p>										<p>ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER. AQUIFER - A WATER BEARING FORMATION OR STRATA. ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND. ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC. ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE. CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE. COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE. CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK. DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL. DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH. FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE. FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES. FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLOADED FROM PARENT MATERIAL. FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM. FORMATION (FM) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD. JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED. LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT. LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS. MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS. MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM. RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK. ROCK QUALITY DESIGNATION (ROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. SAPROLITE (SAP.) - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK. SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS. SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE. STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N OR BPF) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE. STRATA ROCK QUALITY DESIGNATION (SROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.</p>																																																																								
SOIL LEGEND AND AASHTO CLASSIFICATION										ANGULARITY OF GRAINS										WEATHERED ROCK (WR)										NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT N VALUES > 100 BLOWS PER FOOT IF TESTED.																																																																								
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>GENERAL CLASS.</th> <th colspan="5">GRANULAR MATERIALS (<= 35% PASSING #200)</th> <th colspan="5">SILT-CLAY MATERIALS (> 35% PASSING #200)</th> <th colspan="5">ORGANIC MATERIALS</th> </tr> <tr> <th>GROUP CLASS.</th> <th>A-1</th> <th>A-3</th> <th>A-2</th> <th>A-2-4</th> <th>A-2-5</th> <th>A-2-6</th> <th>A-2-7</th> <th>A-4</th> <th>A-5</th> <th>A-6</th> <th>A-7</th> <th>A-1, A-2</th> <th>A-3</th> <th>A-4, A-5</th> <th>A-6, A-7</th> </tr> <tr> <th>SYMBOL</th> <td colspan="5">[Pattern]</td> <td colspan="5">[Pattern]</td> <td colspan="5">[Pattern]</td> </tr> <tr> <th>% PASSING #10 #40 #200</th> <td>50 MX 30 MX 15 MX</td> <td>50 MX 25 MX</td> <td>51 MN 10 MX</td> <td>35 MX 35 MX</td> <td>35 MX 35 MX</td> <td>35 MX 35 MX</td> <td>35 MX 35 MX</td> <td>36 MN 36 MN</td> <td>36 MN 36 MN</td> <td>36 MN 36 MN</td> <td>36 MN 36 MN</td> <td>GRANULAR SOILS</td> <td>SILT-CLAY SOILS</td> <td>MUCK, PEAT</td> </tr> </table>										GENERAL CLASS.	GRANULAR MATERIALS (<= 35% PASSING #200)					SILT-CLAY MATERIALS (> 35% PASSING #200)					ORGANIC MATERIALS					GROUP CLASS.	A-1	A-3	A-2	A-2-4	A-2-5	A-2-6	A-2-7	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7	SYMBOL	[Pattern]					[Pattern]					[Pattern]					% PASSING #10 #40 #200	50 MX 30 MX 15 MX	50 MX 25 MX	51 MN 10 MX	35 MX 35 MX	35 MX 35 MX	35 MX 35 MX	35 MX 35 MX	36 MN 36 MN	36 MN 36 MN	36 MN 36 MN	36 MN 36 MN	GRANULAR SOILS	SILT-CLAY SOILS	MUCK, PEAT	<p>THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS IS DESIGNATED BY THE TERMS: ANGULAR, SUBANGULAR, SUBROUNDED, OR ROUNDED.</p>										<p>CRISTALLINE ROCK (CR) FINE TO COARSE GRAIN IGNEOUS AND METAMORPHIC ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES GRANITE, GNEISS, GABBRO, SCHIST, ETC.</p>										<p>NON-CRYSTALLINE ROCK (NCR) FINE TO COARSE GRAIN METAMORPHIC AND NON-COASTAL PLAIN SEDIMENTARY ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES PHYLLITE, SLATE, SANDSTONE, ETC.</p>									
GENERAL CLASS.	GRANULAR MATERIALS (<= 35% PASSING #200)					SILT-CLAY MATERIALS (> 35% PASSING #200)					ORGANIC MATERIALS																																																																																											
GROUP CLASS.	A-1	A-3	A-2	A-2-4	A-2-5	A-2-6	A-2-7	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7																																																																																							
SYMBOL	[Pattern]					[Pattern]					[Pattern]																																																																																											
% PASSING #10 #40 #200	50 MX 30 MX 15 MX	50 MX 25 MX	51 MN 10 MX	35 MX 35 MX	35 MX 35 MX	35 MX 35 MX	35 MX 35 MX	36 MN 36 MN	36 MN 36 MN	36 MN 36 MN	36 MN 36 MN	GRANULAR SOILS	SILT-CLAY SOILS	MUCK, PEAT																																																																																								
MINERALOGICAL COMPOSITION										COMPRESSION										WEATHERING										FRESH																																																																								
<p>MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHEN THEY ARE CONSIDERED OF SIGNIFICANCE.</p>										<p>SLIGHTLY COMPRESSIBLE LL < 31 MODERATELY COMPRESSIBLE LL = 31 - 50 HIGHLY COMPRESSIBLE LL > 50</p>										<p>ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING. ROCK RINGS UNDER HAMMER IF CRYSTALLINE.</p>										<p>ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN. CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF OF A CRYSTALLINE NATURE.</p>																																																																								
PERCENTAGE OF MATERIAL										GROUND WATER										MODERATE (MOD.)										SEVERE (SEV.)																																																																								
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>ORGANIC MATERIAL</th> <th>GRANULAR SOILS</th> <th>SILT - CLAY SOILS</th> <th>OTHER MATERIAL</th> </tr> <tr> <td>TRACE OF ORGANIC MATTER</td> <td>2 - 3%</td> <td>3 - 5%</td> <td>TRACE 1 - 10%</td> </tr> <tr> <td>LITTLE ORGANIC MATTER</td> <td>3 - 5%</td> <td>5 - 12%</td> <td>LITTLE 10 - 20%</td> </tr> <tr> <td>MODERATELY ORGANIC</td> <td>5 - 10%</td> <td>12 - 20%</td> <td>SOME 20 - 35%</td> </tr> <tr> <td>HIGHLY ORGANIC</td> <td>> 10%</td> <td>> 20%</td> <td>HIGHLY 35% AND ABOVE</td> </tr> </table>										ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL	TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE 1 - 10%	LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE 10 - 20%	MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME 20 - 35%	HIGHLY ORGANIC	> 10%	> 20%	HIGHLY 35% AND ABOVE	<p>WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING</p> <p>STATIC WATER LEVEL AFTER 24 HOURS</p> <p>PERCHED WATER, SATURATED ZONE, OR WATER BEARING STRATA</p> <p>SPRING OR SEEP</p>										<p>ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK. ROCK GIVES "CLUNK" SOUND WHEN STRUCK. IF TESTED, WOULD YIELD SPT REFUSAL</p>										<p>ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC CLEAR AND EVIDENT BUT REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN. IF TESTED, WOULD YIELD SPT N VALUES > 100 BPF</p>																																																				
ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL																																																																																																			
TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE 1 - 10%																																																																																																			
LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE 10 - 20%																																																																																																			
MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME 20 - 35%																																																																																																			
HIGHLY ORGANIC	> 10%	> 20%	HIGHLY 35% AND ABOVE																																																																																																			
CONSISTENCY OR DENSENESS										MISCELLANEOUS SYMBOLS										SEVERE (SEV.)										VERY SEVERE (IV SEV.)																																																																								
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>PRIMARY SOIL TYPE</th> <th>COMPACTNESS OR CONSISTENCY</th> <th>RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)</th> <th>RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT²)</th> </tr> <tr> <td>GENERALLY GRANULAR MATERIAL (NON-COHESIVE)</td> <td>VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE</td> <td>< 4 4 TO 10 10 TO 30 30 TO 50 > 50</td> <td>N/A</td> </tr> <tr> <td>GENERALLY SILT-CLAY MATERIAL (COHESIVE)</td> <td>VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD</td> <td>< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30</td> <td>< 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4</td> </tr> </table>										PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT ²)	GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	< 4 4 TO 10 10 TO 30 30 TO 50 > 50	N/A	GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30	< 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4	<p>ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT</p> <p>INFERRED SOIL BOUNDARY</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP & DIP DIRECTION OF ROCK STRUCTURES</p> <p>SPT TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>CONE PENETROMETER TEST</p> <p>SOUNDING ROD</p> <p>TEST BORING WITH CORE</p> <p>SPT N-VALUE</p>										<p>ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC ELEMENTS ARE DISCERNIBLE BUT MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK REMAINING. SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE THAT ONLY MINOR VESTIGES OF ORIGINAL ROCK FABRIC REMAIN. IF TESTED, WOULD YIELD SPT N VALUES < 100 BPF</p>										<p>ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.</p>																																																												
PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT ²)																																																																																																			
GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	< 4 4 TO 10 10 TO 30 30 TO 50 > 50	N/A																																																																																																			
GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30	< 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4																																																																																																			
TEXTURE OR GRAIN SIZE										RECOMMENDATION SYMBOLS										MODERATELY HARD										MEDIUM HARD																																																																								
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>U.S. STD. SIEVE SIZE OPENING (MM)</th> <th>4</th> <th>10</th> <th>40</th> <th>60</th> <th>200</th> <th>270</th> </tr> <tr> <td></td> <td>4.75</td> <td>2.00</td> <td>0.42</td> <td>0.25</td> <td>0.075</td> <td>0.053</td> </tr> </table>										U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270		4.75	2.00	0.42	0.25	0.075	0.053	<p>UNDERCUT</p> <p>SHALLOW UNDERCUT</p> <p>UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE</p> <p>UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK</p>										<p>CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.</p>										<p>CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.</p>																																																										
U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270																																																																																																
	4.75	2.00	0.42	0.25	0.075	0.053																																																																																																
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>BOULDER (BLDR.)</th> <th>COBBLE (COB.)</th> <th>GRAVEL (GR.)</th> <th>COARSE SAND (CSE. SD.)</th> <th>FINE SAND (F SD.)</th> <th>SILT (SL.)</th> <th>CLAY (CL.)</th> </tr> <tr> <td>GRAIN SIZE</td> <td>MM 305 IN. 12</td> <td>75</td> <td>2.0</td> <td>0.25</td> <td>0.05</td> <td>0.005</td> </tr> </table>										BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE. SD.)	FINE SAND (F SD.)	SILT (SL.)	CLAY (CL.)	GRAIN SIZE	MM 305 IN. 12	75	2.0	0.25	0.05	0.005	ABBREVIATIONS										SOFT										VERY SOFT																																																										
BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE. SD.)	FINE SAND (F SD.)	SILT (SL.)	CLAY (CL.)																																																																																																
GRAIN SIZE	MM 305 IN. 12	75	2.0	0.25	0.05	0.005																																																																																																
<p>AR - AUGER REFUSAL BT - BORING TERMINATED CL - CLAY CPT - CONE PENETRATION TEST CSE - COARSE DMT - DILATOMETER TEST DPT - DYNAMIC PENETRATION TEST e - VOID RATIO F - FINE FOSS. - FOSSILIFEROUS FRAC. - FRACTURED, FRACTURES FRAGS. - FRAGMENTS HI. - HIGHLY</p>										<p>MED. - MEDIUM MICA - MICACEOUS MOD. - MODERATELY NP - NON PLASTIC ORG. - ORGANIC PMT - PRESSUREMETER TEST SAP. - SAPROLITIC SD. - SAND, SANDY SL. - SILT, SILTY SLI. - SLIGHTLY TCR - TRICONE REFUSAL w - MOISTURE CONTENT V - VERY</p>										<p>VST - VANE SHEAR TEST WEA. - WEATHERED W - UNIT WEIGHT W_d - DRY UNIT WEIGHT</p>										<p>SAMPLE ABBREVIATIONS S - BULK SS - SPLIT SPOON ST - SHELBY TUBE RS - ROCK RT - RECOMPACTED TRIAXIAL CBR - CALIFORNIA BEARING RATIO</p>																																																																								
SOIL MOISTURE - CORRELATION OF TERMS										EQUIPMENT USED ON SUBJECT PROJECT										MODERATELY HARD										MEDIUM HARD																																																																								
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>SOIL MOISTURE SCALE (ATTERBERG LIMITS)</th> <th>FIELD MOISTURE DESCRIPTION</th> <th>GUIDE FOR FIELD MOISTURE DESCRIPTION</th> </tr> <tr> <td>LL - LIQUID LIMIT PL - PLASTIC LIMIT</td> <td>- SATURATED - (SAT.) - WET - (W)</td> <td>USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td>OM - OPTIMUM MOISTURE SL - SHRINKAGE LIMIT</td> <td>- MOIST - (M) - DRY - (D)</td> <td>SOLID; AT OR NEAR OPTIMUM MOISTURE REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td> </tr> </table>										SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION	LL - LIQUID LIMIT PL - PLASTIC LIMIT	- SATURATED - (SAT.) - WET - (W)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE	OM - OPTIMUM MOISTURE SL - SHRINKAGE LIMIT	- MOIST - (M) - DRY - (D)	SOLID; AT OR NEAR OPTIMUM MOISTURE REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE	<p>DRILL UNITS: <input type="checkbox"/> CME-45C <input checked="" type="checkbox"/> CME-55 <input type="checkbox"/> CME-550 <input type="checkbox"/> VANE SHEAR TEST <input type="checkbox"/> PORTABLE HOIST</p>										<p>ADVANCING TOOLS: <input type="checkbox"/> CLAY BITS <input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER <input checked="" type="checkbox"/> 8" HOLLOW AUGERS <input type="checkbox"/> HARD FACED FINGER BITS <input type="checkbox"/> TUNG-CARBIDE INSERTS <input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER <input type="checkbox"/> TRICONE * STEEL TEETH <input type="checkbox"/> TRICONE * TUNG-CARB. <input type="checkbox"/> CORE BIT</p>										<p>HAMMER TYPE: <input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL</p> <p>CORE SIZE: <input type="checkbox"/> -B <input type="checkbox"/> -H <input type="checkbox"/> -N</p> <p>HAND TOOLS: <input type="checkbox"/> POST HOLE DIGGER <input checked="" type="checkbox"/> HAND AUGER <input type="checkbox"/> SOUNDING ROD <input type="checkbox"/> VANE SHEAR TEST</p>										<p>CAN BE GROUDED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.</p>										<p>CAN BE GROUDED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.</p>																																											
SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION																																																																																																				
LL - LIQUID LIMIT PL - PLASTIC LIMIT	- SATURATED - (SAT.) - WET - (W)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE																																																																																																				
OM - OPTIMUM MOISTURE SL - SHRINKAGE LIMIT	- MOIST - (M) - DRY - (D)	SOLID; AT OR NEAR OPTIMUM MOISTURE REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE																																																																																																				
PLASTICITY										FRACTURE SPACING										SOFT										VERY SOFT																																																																								
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>NON PLASTIC</th> <th colspan="2">PLASTICITY INDEX (PI)</th> <th>DRY STRENGTH</th> </tr> <tr> <td></td> <td>0-5</td> <td>6-15</td> <td>VERY LOW</td> </tr> <tr> <td>SLIGHTLY PLASTIC</td> <td>16-25</td> <td>26 OR MORE</td> <td>SLIGHT</td> </tr> <tr> <td>MODERATELY PLASTIC</td> <td></td> <td></td> <td>MEDIUM</td> </tr> <tr> <td>HIGHLY PLASTIC</td> <td></td> <td></td> <td>HIGH</td> </tr> </table>										NON PLASTIC	PLASTICITY INDEX (PI)		DRY STRENGTH		0-5	6-15	VERY LOW	SLIGHTLY PLASTIC	16-25	26 OR MORE	SLIGHT	MODERATELY PLASTIC			MEDIUM	HIGHLY PLASTIC			HIGH	<p>TERM SPACING</p> <p>VERY WIDE MORE THAN 10 FEET WIDE 3 TO 10 FEET MODERATELY CLOSE 1 TO 3 FEET CLOSE 0.16 TO 1 FOOT VERY CLOSE LESS THAN 0.16 FEET</p>										<p>TERM THICKNESS</p> <p>VERY THICKLY BEDDED 4 FEET THICKLY BEDDED 1.5 - 4 FEET THINLY BEDDED 0.16 - 1.5 FEET VERY THINLY BEDDED 0.03 - 0.16 FEET THICKLY LAMINATED 0.008 - 0.03 FEET THINLY LAMINATED < 0.008 FEET</p>										<p>CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.</p>																																																				
NON PLASTIC	PLASTICITY INDEX (PI)		DRY STRENGTH																																																																																																			
	0-5	6-15	VERY LOW																																																																																																			
SLIGHTLY PLASTIC	16-25	26 OR MORE	SLIGHT																																																																																																			
MODERATELY PLASTIC			MEDIUM																																																																																																			
HIGHLY PLASTIC			HIGH																																																																																																			
COLOR										INDURATION										MODERATELY HARD										MEDIUM HARD																																																																								
<p>DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-BROWN). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.</p>										<p>FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.</p>										<p>FRIABLE RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</p>										<p>MODERATELY INDURATED GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</p>																																																																								
BENCH MARK:										INDURATED										VERY HARD										HARD																																																																								
<p>BORING ELEVATIONS TAKEN FROM u5743.ls.tin.tin</p> <p>DATED 12/17/2018 ELEVATION: FEET</p>										<p>GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</p>										<p>SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</p>										<p>NOTES: FIAD - FILLED IMMEDIATELY AFTER DRILLING</p>																																																																								

I:\Projects\2019\G18083.01U-5743 NC 42 Widening in Randolph County\U-5743_NCDOT_Electronic_File_Tree\Geotech\InvestigationDesign\U-5743_GEO_RDWY\CADD_GEO\TECH\Plan\Prof\U-5743_GEO_rfs_09_08_19.cadmachine AT CADD

CONTRACT:

TIP PROJECT: U-5743


STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

RANDOLPH COUNTY


LOCATION: NC 42 FROM SR 2237 (EAST SALISBURY STREET) TO NORTH OF US 64 / NC 49 (DIXIE DRIVE) IN ASHEBORO

TYPE OF WORK: GRADING, PAVING, DRAINAGE, SIGNALS AND CULVERTS

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	U-5743	3	24
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
50165.1.1		P.E.	




25% PLANS



INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION
DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

★ SIGNALIZED INTERSECTION



DESIGN DATA

ADT 2020 =	15,960
ADT 2040 =	18,600
K =	9 %
D =	60 %
T =	3 % *
V =	40 / 50 MPH
* TTST =	1% DUAL = 2%
FUNC CLASS =	URBAN PRINCIPAL ARTERIAL REGIONAL TIER

PROJECT LENGTH

LENGTH ROADWAY TIP PROJECT U-5743	=	0.777 MI
TOTAL LENGTH TIP PROJECT U-5743	=	0.777 MI

PLANS PREPARED FOR THE NCDOT BY:

M MOTT MACDONALD 2018 STANDARD SPECIFICATIONS	PO Box 700 Fuquay-Varina, NC 27526 (919) 552-2253 (919) 552-2254 (Fax) www.mottmac.com/america LICENSE NO. F-0669	HR HDR Engineering, Inc. of the Carolinas 555 Fayetteville St. Suite 900 Raleigh, N.C. 27601 N.C.B.E.L.S. License Number: F-0116
---	--	--

RIGHT OF WAY DATE: JUNE 21, 2019

LETTING DATE: FEBRUARY 18, 2020

TIM JORDAN, PE
PROJECT ENGINEER

JAMES RICE, PE
HYDRAULICS PROJECT ENGINEER


JEFFREY L. TEAGUE, PE
NCDOT CONTACT

ROADWAY DESIGN ENGINEER

SIGNATURE: _____ P.E.

HYDRAULICS ENGINEER

SIGNATURE: _____ P.E.





WBS: 50165.1.1
TIP: U-5743
COUNTY: Randolph
DESCRIPTION: NC 42 From SR 2237 (East Salisbury Street) to North of US 64 / NC 49 (Dixie Drive) in Asheboro
SUBJECT: Roadway Subsurface Investigation – Inventory

Roadway Subsurface Investigation Report - Inventory

**NC 42 From SR 2237 (East Salisbury Street) to
North of US 64 / NC 49 (Dixie Drive) in Asheboro
Randolph County, North Carolina
WBS: 50165.1.1 TIP: U-5743
Falcon Project No.: G18083.00**

Prepared for:
NCDOT Geotechnical Engineering Unit
1020 Birch Ridge Drive
Raleigh, NC 27610

Submitted by:
Falcon Engineering, Inc.
1210 Trinity Road, Suite 110
Cary, North Carolina 27513
(919) 871-0800
www.falconengineers.com

April 16, 2019

PROJECT DESCRIPTION

This project consists of widening existing NC 42 from SR 2237 (East Salisbury Street) to north of US 64 / NC 69 (Dixie Drive) in Randolph County. The overall corridor is approximately 0.75 miles long and consists of existing two lane highway. The widened corridor will consist of a three lane highway with a center turn lane. Some reconfiguration/improvement of intersections and adjustments to varying lengths of numerous Y-lines is also planned. Two reinforced concrete box culverts are included in this project.

The investigation was conducted between February 4th and 19th, 2019 in general accordance with our Proposal to Provide Geotechnical Roadway Investigation and Design Services, dated December 21st, 2018.

A total of twenty-five (25) Standard Penetration Test (SPT) borings and twelve (12) hand auger borings were performed for the proposed roadway alignments. All mechanical borings were drilled using a CME 55 ATV mounted drill rig equipped with 2 ¼-inch inside diameter hollow-stem augers, and SPT testing was performed with a recently calibrated and NCDOT approved automatic hammer. Representative soil samples, collected with a split-barrel sampler or hand auger, were selected for laboratory testing to verify visual field classifications. In addition, one (1) bulk sample was collected for standard Proctor compaction and California Bearing Ratio (CBR) testing.



Portions of the following alignments, totaling approximately 1.15 miles were investigated. Other minor driveways are included on the project but proposed improvements are not significant enough to warrant investigation.

<u>Alignment</u>	<u>Station (ft)</u>
-L- (NC 42)	15+00 to 55+00
-Y1- (E. Salisbury Street)	10+00 to 16+50
-Y2- (Dublin Square Road)	10+00 to 17+85.67
-Y5- (Thomas Street)	10+00 to 13+00
-Y6- (Leslieshire Drive)	11+50 to 14+66.38

AREAS OF SPECIAL GEOTECHNICAL INTEREST

A. The following locations contain highly plastic soils with plasticity indices (PI) greater than 25 within 3 feet of proposed subgrade elevations:

<u>Alignment</u>	<u>Station (ft)</u>
-L-	24+00
-L-	46+00
-L-	52+00
-Y5-	12+49

B. The following location contains very soft to soft/very loose soils with an N-value less than 4 near the ground surface:

<u>Alignment</u>	<u>Station (ft)</u>
-Y2-	13+00

C. Alluvial soils were encountered at the following location:

<u>Alignment</u>	<u>Station (ft)</u>
-L-	44+38

Isolated alluvial soils may exist elsewhere on the site between borings in proximity to natural waterways and/or constructed drainage features.

D. Shallow groundwater was encountered in the following areas:

<u>Alignment</u>	<u>Station (ft)</u>
-L-	16+00
-L-	18+00
-L-	44+50

PHYSIOGRAPHY AND GEOLOGY

According to the *Geologic Map of North Carolina* (1985), the site is in the Carolina Slate Belt Physiographic Province of North Carolina. Specifically, rocks at the site are noted as Metamudstone and Meta-Argillite (**CZmd**) bedding plane and axial-planar cleavage common; interbedded with metamudstone, meta-conglomerate, and metavolcanic rock.

Existing site topography is typical of North Carolina's Piedmont Region. Existing roadway embankments on the site vary generally from 3 to 5 feet. Low areas and drainage ditches are present adjacent to the existing roadway that will require fill for the proposed widening. The site lies in east Asheboro and is currently a two lane highway. The existing corridor is populated with residential and commercial properties on either side of the corridor. A small stream flows southward across the mainline near station 43+75.

SOIL PROPERTIES

A variety of soils were encountered along the project, including artificial fill, roadway embankments, alluvial soils, residual soils, weathered rock, and crystalline rock.

Topsoil and rootmat were encountered in grassy, brushy, and wooded areas ranging in thickness from 0.2 to 0.5 feet, typically on the order of 0.3 feet, and consisting of sandy clay.

Artificial Fill soils were encountered at the ground surface beneath thin layers of topsoil associated with prior grading of private properties adjacent to the roadway. These consist of up to 9.5 feet of moist to wet, soft to very stiff, silty clay (A-7).

Roadway Embankment soils were encountered at the ground surface adjacent to existing roadways. These consist of up to 2 feet of moist, clayey silt (A-5).





Alluvial soils were encountered at the ground surface near the historic floodplains of natural waterways. These soils extended to depths of up to approximately 4.0 feet and consist of moist to saturated, silty clays (A-7).

Residual soils were encountered at the ground surface, or beneath artificial fill, roadway embankments or alluvial deposits. These soils consist of dry to moist, clean sands (A-1-b) and soft to very stiff, sandy clay and silt, clayey silt, and silty clays (A-4, A-5, A-6, A-7) and extend to depths of 3.0 feet to greater than 13.0 feet where borings were terminated in residual soils.

Weathered Rock (WR) is a very hard material with properties intermediate of soil and rock. WR is classified as having an N-value of greater than 100 blows per one foot. WR was encountered at depths of 3.0 feet to 19.8 feet and generally consists of tan and white metamudstone.

Crystalline Rock, in the form of metamudstone, was encountered beneath weathered rock or residual soils at various locations throughout the site at depths of 2.7 to 11.9. Crystalline Rock is classified as material that yields auger refusal or SPT refusal (blow count of 60/0.0 or 60/0.1 feet.)

GROUNDWATER PROPERTIES

Groundwater levels were measured at the time of boring completion, and in many cases after a waiting period of at least 24 hours. Borings drilled within and in close proximity to existing roadways were backfilled immediately after completion due to safety considerations. Where encountered, groundwater was measured in borings at depths of 0.5 feet to 5.6 feet, corresponding to elevations ranging from 836.2 ft to 753.3 ft.

Detailed groundwater measurements are included in the attached subsurface profiles and cross sections.

ADDITIONAL LABORATORY TESTING

The following bulk sample was obtained:

Sample	Location	Location	Test
BS-1	33+81, 21' LT, -L-	1.0 – 6.0	California Bearing Ratio, Standard Proctor

Classification test results for these samples are included in the subsurface profiles. Standard Proctor and California Bearing Ratio (CBR) data is attached in Appendix A.

CLOSING

Falcon appreciates the opportunity to have provided our geotechnical engineering services for the above referenced project. If you have any questions concerning the contents of this report or need additional information, please do not hesitate to contact our office.

FALCON ENGINEERING, INC.

DOCUMENT NOT CONSIDERED FINAL UNTIL ALL SIGNATURES COMPLETED

Report Prepared By:

Report Reviewed By:

DocuSigned by:
W. Scott Hunsberger
5A469AC80FCD49E...


DocuSigned by:
Jeremy R Hamm
ED7938089E22487...

W. Scott Hunsberger, PE
Geotechnical Engineer

Jeremy R. Hamm, PE
Geotechnical Engineering Manager



5/14/2019
 01:41:19
 C:\Users\jgibson\OneDrive\Documents\Projects\5743\5743_GEO\RDWY\CADD_GEO\TECH\Plan\Prof\U-5743_GEO_psh04.dgn
 5743_NICD\Structure\5743\5743_GEO\RDWY\CADD_GEO\TECH\Plan\Prof\U-5743_GEO_psh04.dgn
 5/14/2019 14:21
 C:\Users\jgibson\OneDrive\Documents\Projects\5743\5743_GEO\RDWY\CADD_GEO\TECH\Plan\Prof\U-5743_GEO_psh04.dgn




PROJECT REFERENCE NO.	SHEET NO.
U-5743	4
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
Prepared in the Office of:	
M PO Box 700 Fuquay-Varina, NC 27526 MOTT MAEDONAD www.mottmac.com/mma/mkts	
HR HDR Engineering, Inc. of the Carolinas 555 Fayetteville St., Suite 550, Raleigh, NC 27601 N.C.S.E.L.S. License Number: F-0116	
FOR -L- PROFILE SEE SHEET 8	
FOR -Y1- PROFILE SEE SHEET 10	



SIGNALIZED INTERSECTION

5/14/19
 C:\MIS-2019\4222\1\Tree\Geotech\Investigation\Design\U-5743_GEO_RDW\CADD_GEO\TECH\Plan\Prof\U-5743_GEO_psh05.dgn
 5743_NICD01.ctb
 5/14/19 14:22:11
 5743_NICD01.ctb




PROJECT REFERENCE NO.	SHEET NO.
U-5743	5
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
Prepared in the Office of:	M MOTT MADONALD
	PO Box 700 Fuquay-Varano, NC 27526 www.mottmac.com/mackos
	HDR HDR Engineering, Inc. of the Carolinas 555 Fayetteville St., Suite 550 Raleigh, NC 27601 N.C.S.E.L.S. License Number: F-0116
FOR -L- PROFILE SEE SHEETS 8 & 9 FOR -Y2- PROFILE SEE SHEET 10	

-Y2-
 PI Sta 11+16.93
 $\Delta = 63^\circ 42' 22.4''$ (LT)
 $D = 37' 12'' 18.2''$
 $L = 171.23'$
 $T = 95.68'$
 $R = 154.00'$
 $SE = 04'$
 $RO = 84.00'$

MATCHLINE SEE SHEET 4
 -L- STA 24+00.00

MATCHLINE SEE SHEET 6
 -L- STA 33+50.00


PROJECT REFERENCE NO.	SHEET NO.
U-5743	6
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
Prepared in the Office of:	M MOTT MAGDONALD
	PO Box 700 Fuquay-Varina, NC 27526 www.mottmac.com/mmarks
	DR HDR Engineering, Inc. of the Carolinas 335 Fayetteville St., Suite 200, Raleigh, NC 27601 N.C.S.E.L.S. License Number: F-0116
FOR -L- PROFILE SEE SHEETS 8 & 9 FOR -Y2- PROFILE SEE SHEET 10	



5/14/2019
 C:\MIS-2019\4422\1_electrical\5743\Investigation\Design\U-5743_GEO\RDW\X\CADD_GEO\TECH\Plan\Prof\U-5743_GEO_psh06.dgn
 5743_NIC001.dwg
 5/14/2019 14:22:11

SIGNALIZED INTERSECTION

5/14/99
C:\MIS-2019\4227\1-Tree\Geotech\InvestigationDesign\U-5743_GEO_RDW\CADD_GEO\TECH\Plan\Prof\U-5743_GEO_psh07.dgn
5743_NICD\U-5743\1-Tree\Geotech\InvestigationDesign\U-5743_GEO_RDW\CADD_GEO\TECH\Plan\Prof\U-5743_GEO_psh07.dgn





PROJECT REFERENCE NO.	SHEET NO.
U-5743	7
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
Prepared in the Office of:	M MOTT MCDONALD
	PO Box 700 Fuquay-Varano, NC 27526 www.mottmac.com/mattm
HR HDR Engineering, Inc. of the Carolinas 35 Fayetteville St., Suite 200 Raleigh, NC 27601 N.C.S.E.L.S. License Number: F-0116	
FOR -L- PROFILE SEE SHEETS 8 & 9	

5/28/99
 07-APR-2009 08:40
 I:\Projects\2008\0818\GIS\083.01 U-5743 NC 42 Widening in Randolph County\U-5743_GEO\RDWY\CADD_GEO\TECH\Plan\Prof\U-5743_GEO.psh_08-12.dgn
 0818\GIS\083.01 U-5743 NC 42 Widening in Randolph County\U-5743_GEO\RDWY\CADD_GEO\TECH\Plan\Prof\U-5743_GEO.psh_08-12.dgn
 0818\GIS\083.01 U-5743 NC 42 Widening in Randolph County\U-5743_GEO\RDWY\CADD_GEO\TECH\Plan\Prof\U-5743_GEO.psh_08-12.dgn

**DESIGN EXCEPTION REQUIRED:
SAG VERTICAL CURVE K
VERTICAL SSD**



-L-

PROJECT REFERENCE NO. U-5743	SHEET NO. 9
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR A/W ACQUISITION	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
Prepared in the Office of:	M M PO Box 700 MOTT MACDONALD Fuquay-Varina, NC 27526 www.mottmac.com/america
HDR HDR Engineering, Inc. of the Carolinas 555 Fayetteville St. Suite 900 Raleigh, NC 27601 N.C.E.E.L.S. License Number: F-0116	



5/28/99
 C:\p1p\2008_0818\18\18\083.01 U-5743 NC 42 Widening in Randolph County\U-5743_GEO_RDWY\CADD_GEO\TECH\PlanProf\U-5743_GEO_psh_08-12.dgn
 C:\p1p\2008_0818\18\18\083.01 U-5743 NC 42 Widening in Randolph County\U-5743_NCDOT_Electronic\File_Tree\Geotech\Investigation\Design\U-5743_GEO.psh_08-12.dgn
 C:\p1p\2008_0818\18\18\083.01 U-5743 NC 42 Widening in Randolph County\U-5743_NCDOT_Electronic\File_Tree\Geotech\Investigation\Design\U-5743_GEO.psh_08-12.dgn

PROJECT REFERENCE NO. U-5743	SHEET NO. 10
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR A/W ACQUISITION	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
Prepared in the Office of:	M MOTT MACDONALD
	PO Box 700 Furqay-Vasno, NC 27526 www.mottmac.com/merkos
HDR HDR Engineering, Inc. of the Carolinas 555 Fayetteville St. Suite 900 Raleigh, NC 27601 N.C.E.E.L.S. License Number: F-0116	




PROJECT REFERENCE NO. U-5743	SHEET NO. 11
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR A/W ACQUISITION	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
Prepared in the Office of:	M PO Box 700 Furqay-Yarino, NC 27526 MOTT MACDONALD www.mottmac.com/americas
HDR HDR Engineering, Inc. of the Carolinas 555 Fayetteville St., Suite 900, Raleigh, NC, 27601 N.C.B.E.L.S. License Number: P-0116	

-Y3-

NO BORINGS ON THIS ALIGNMENT


FOR PLAN VIEW SEE SHEET 5

-Y5-



FOR PLAN VIEW SEE SHEET 6



-Y6-




FOR PLAN VIEW SEE SHEET 6

I:\Projects\2018\18083.01 U-5743 NC 42 Widening in Randolph County\U-5743_GEO\RDWY\CADD_GEO\TECH\PlanPr\U-5743_GEO_PlanPr\U-5743_GEO_PlanPr.dwg
 15-APR-2019 13:17
 MOTT MACDONALD

03-APR-2019 08:56
 I:\Projects\2018\08083.01 U-5743 NC 42 Widening in Randolph County\U-5743.NC001.Electronic\File Tree\Geotech\InvestigationDesign\U-5743.GEO.RDWAY.CADD.GEOTECH\XSE\U-5743.GEO.XPL.L.DGN
 cadmanline AT CAD01




SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-3	30 FT LT	24+00	1.0'-2.5'	A-7-6	59	38	19	12	25	44	73	60	54	23	-






PROJ. REFERENCE NO.	SHEET NO.
U-5743	13



25 + 50.00


25 + 00.00



RESIDUAL TAN, DRY, HARD SILT
WEATHERED ROCK TAN, METAMUDSTONE

RESIDUAL BROWN, MOIST, MED. STIFF, HIGHLY PLASTIC SILTY CLAY
RESIDUAL TAN, DRY, HARD SILT
WEATHERED ROCK TAN, METAMUDSTONE

03-APR-2019 09:00
 I:\Projects\2018\08083.01 U-5743 NC 42 Widening in Randolph County\U-5743.NCDDT.Electronic.File.Tree\Geotech\InvestigationDesign\U-5743.GEO.RDWY\CADD.GEOTECH\XSE\U-5743.GEO.XPL.L.DGN
 cadman



SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-9	25 FT RT	46+00	6.0'-7.5'	A-7-6	51	33	4	8	39	49	90	87	82	22	-

46 + 00.00

45 + 50.00

45 + 00.00

44 + 50.00

—L—

RESIDUAL TAN AND RED, MOIST, MED. STIFF, HIGHLY PLASTIC SILTY CLAY WITH TRACE ROCK FRAGMENTS

RESIDUAL TAN, MOIST, V. STIFF, SILT

RESIDUAL TAN AND RED, MOIST, MED. STIFF, HIGHLY PLASTIC SILTY CLAY WITH TRACE ROCK FRAGMENTS


RESIDUAL TAN, MOIST, V. STIFF, SILT

RESIDUAL TAN AND RED, MOIST, MED. STIFF, HIGHLY PLASTIC SILTY CLAY WITH TRACE ROCK FRAGMENTS


RESIDUAL TAN, MOIST, V. STIFF, SILT

RESIDUAL TAN AND RED, MOIST, SOFT TO STIFF, SILTY CLAY WITH TRACE ROCK FRAGMENTS


ALLOWING BROWN, MOIST TO WET, SILTY CLAY




6/23/16
03-APR-2019 09:00
I:\Projects\2018\08083.01 U-5743 NC 42 Widening in Randolph County\U-5743.NCDDT.Electronic.File.Tree\Geotech\InvestigationDesign\U-5743.GEO.RDYY\CADD.GEOTECH\U-5743.GEO.xpl.L.dgn
cadd\cadd



PROJ. REFERENCE NO.	SHEET NO.
U-5743	15




SOIL TEST RESULTS																
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC	
							C. SAND	F. SAND	SILT	CLAY	10	40	200			
SS-12	39 FT RT	52+00	1.0'-2.5'	A-7-5	71	40	3	10	27	60	97	95	88	39	-	



03-APR-2019 09:01
I:\Projects\2018\08083.01 U-5743 NC 42 Widening in Randolph County\U-5743.NCDDT.Electronic.File.Tree\Geotech\InvestigationDesign\U-5743.GEO.RDWAY.CADD.GEOTECH\XSEC\U-5743.GEO.XPL.L.dgn
Geotechnical

6/23/16
03-APR-2019 09:01
I:\Projects\2018\08083.01 U-5743 NC 42 Widening in Randolph County\U-5743.NCDDT.Electronic.File.Tree\Geotech\InvestigationDesign\U-5743.GEO.RDYY\CADD.GEOTECH\XSE\U-5743.GEO.XPL.L.DGN
C:\CAD


0 5 10	PROJ. REFERENCE NO.	SHEET NO.
	U-5743	17






150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150


SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-14	25 FT RT	12+49	1.0'-2.5'	A-7-6	68	42	0	8	31	61	100	100	96	30	-



03-APR-2019 09:03
I:\Projects\2018\080803.01 U-5743 NC 42 Widening in Randolph County\U-5743.NC001.Electronic.File.Tree\Geotech\InvestigationDesign\U-5743.GEO.RDXY\CADD.GEOTECH\XSE\U-5743.GEO.XPL.Y5.dgn
6/23/16
cadd\line



PROJ. REFERENCE NO.	SHEET NO.
U-5743	19



13 + 00.00


-Y5-

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
 DIVISION OF HIGHWAYS
 GEOTECHNICAL ENGINEERING UNIT
SUBSURFACE INVESTIGATION
 APPENDIX A
 LABORATORY RESULTS

REFERENCE: U-5743

PROJECT: 50165

DS WSH	4/17/2019
INITIALS	DATE



Project No: G18083.01
 Project Name: U-5743 | NC 42 from SR 2237 to North of US 64 / NC 49
 Sample No: BS-01
 Source of Material: L_3400
 Color: Tan
 Visual/Manual Description: Silty Clay
 USCS Classification: LEAN CLAY(CL)
 AASHTO Classification: A-7-6
 Test Method: AASHTO T-99 Method A

TEST RESULTS
 Maximum Dry Unit Weight: 103.8 PCF
 Optimum Water Content: 17.7 %
 Natural Water Content: 22.0 %
 Percent Passing #200: 93.6 %

ATTERBERG LIMITS

LL	PL	PI
49	25	24

Curves of 100% Saturation for Specific Gravity Equal to:
 — 2.6
 - - - 2.5
 2.4

FALCON ENGINEERING

1210 TRINITY RD., SUITE 110, Cary, NC 27513

CBR (CALIFORNIA BEARING RATIO) OF LABORATORY COMPACTED SOIL

AASHTO T-193 \ ASTM D-1883

PROJECT #: G18083.01 DATE: 2/25/2019
 PROJECT NAME: U-5743 | NC42 from SR 2237 to North of US 64 / NC 49
 BORING: L_3400 SAMPLE: BS-01 DEPTH: 1.0-6.0'

SOIL DESCRIPTION: Tan Silty Clay (A-7-6)

COMPACTION METHOD	AASHTO T99 A	SOAK	96 HRS.
MAXIMUM DRY DENSITY	103.8 PCF	STRAIN RATE	.05 IN / MIN.
OPTIMUM MOISTURE CONTENT	17.7%	LOAD CELL	6000
TEST DATA		SURCHARGE WEIGHT	
DRY DENSITY	102.4 PCF	SURCHARGE PER SQUARE FOOT	51 lbs/sq.ft.
MOISTURE CONTENT	17.6%	FINAL MOISTURE CONTENT	N/A
PERCENT COMPACTION	98.6%	SWELL	5.56%

