

APPROVED: *Jason T. Gaddy*
DATE: 6/8/2026



DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

AMT A. MORTON THOMAS AND ASSOCIATES, INC.
500 RIDGEFIELD DRIVE, SUITE 333 • FARMERSVILLE, NC 27834
(919) 855-9989 • NC LICENSE NO. F-1049
WWW.AMTEngineering.com

<p>SIGN NUMBER: 301 TYPE: D QUANTITY: 1</p> <p>BACKG COLOR: Green COPY COLOR: White</p> <p>SIGN WIDTH: 8'-4" HEIGHT: 1'-6" TOTAL AREA: 12.5 Sq.Ft.</p> <p>ROUTE MARKERS:</p> <p>BORDER TYPE: FLUSH RECESS: 0" WIDTH: 0.75" RADII: 2.25"</p> <p>ARROW TYPES: 6.0"x9.0"(AR_Type D)</p> <p>NO. Z BARS: LENGTH:</p> <p>MAT: 1.6 mm ALUMINUM</p>	<p>DESIGN BY: ABC PROJECT ID: I-5716</p> <p>CHECKED BY: JTG DIV: 12</p> <p>STD #: STD DATE: Apr 10, 2026</p>
<p>LETTER POSITIONS</p> <p>L e n o i r - R h y n e U n i v .</p> <p>3.72 3.54 3.54 3.66 0.96 2.28 2.1 4.08 3.54 4.5 3.54 3.54 4.08 3.54 0.96 4.26 1.08 72.24</p>	<p>BORDER R=2.25" TH=0.75"</p> <p>Panel Style: guide_con_destination_1-line_2012.ssi M.U.T.C.D.: 2009 Edition</p>
<p>Letter positions are to the lower left corners</p> <p>USE NOTES: 1,3,4,6</p> <ol style="list-style-type: none"> Legend and border shall be direct applied encapsulated lens reflective sheeting. Legend and border shall be direct applied enclosed lens reflective sheeting. Shields shall be encapsulated lens reflective sheeting on 0.8mm aluminum and demountable. Background shall be encapsulated lens reflective sheeting. Background shall be enclosed lens reflective sheeting. Center arrows vertically on sign. 	<p>NORTH CAROLINA D.O.T. SIGN DETAIL</p>

<p>SIGN NUMBER: 303 TYPE: D QUANTITY: 1</p> <p>BACKG COLOR: Green COPY COLOR: White</p> <p>SIGN WIDTH: 5'-9" HEIGHT: 2'-6" TOTAL AREA: 14.38 Sq.Ft.</p> <p>ROUTE MARKERS:</p> <p>BORDER TYPE: FLUSH RECESS: 0" WIDTH: 0.75" RADII: 2.25"</p> <p>ARROW TYPES: 6.0"x9.0"(AR_Type D)</p> <p>NO. Z BARS: LENGTH:</p> <p>MAT: 1.6 mm ALUMINUM</p>	<p>DESIGN BY: ABC PROJECT ID: I-5716</p> <p>CHECKED BY: JTG DIV: 12</p> <p>STD #: STD DATE: Apr 10, 2026</p>
<p>LETTER POSITIONS</p> <p>H i c k o r y</p> <p>4.08 0.96 3.54 3.84 3.66 2.28 4.5 27.6</p> <p>F u r n i t u r e M a r t</p> <p>3.72 3.54 2.28 3.54 0.96 2.4 3.54 2.28 3.54 4.68 3.42 2.28 2.4 54.6</p>	<p>BORDER R=2.25" TH=0.75"</p> <p>Panel Style: guide_con_destination_1-line_2012.ssi M.U.T.C.D.: 2009 Edition</p>
<p>Letter positions are to the lower left corners</p> <p>USE NOTES: 1,3,4,6</p> <ol style="list-style-type: none"> Legend and border shall be direct applied encapsulated lens reflective sheeting. Legend and border shall be direct applied enclosed lens reflective sheeting. Shields shall be encapsulated lens reflective sheeting on 0.8mm aluminum and demountable. Background shall be encapsulated lens reflective sheeting. Background shall be enclosed lens reflective sheeting. Center arrows vertically on sign. 	<p>NORTH CAROLINA D.O.T. SIGN DETAIL</p>

<p>SIGN NUMBER: 302 TYPE: D QUANTITY: 1</p> <p>BACKG COLOR: Green COPY COLOR: White</p> <p>SIGN WIDTH: 5'-10" HEIGHT: 2'-6" TOTAL AREA: 14.58 Sq.Ft.</p> <p>ROUTE MARKERS:</p> <p>BORDER TYPE: FLUSH RECESS: 0" WIDTH: 0.75" RADII: 2.25"</p> <p>ARROW TYPES: 6.0"x9.0"(AR_Type D)</p> <p>NO. Z BARS: LENGTH:</p> <p>MAT: 1.6 mm ALUMINUM</p>	<p>DESIGN BY: ABC PROJECT ID: I-5716</p> <p>CHECKED BY: JTG DIV: 12</p> <p>STD #: STD DATE: Apr 10, 2026</p>
<p>LETTER POSITIONS</p> <p>D r i v e r s L i c e n s e</p> <p>4.08 2.28 0.96 4.26 3.54 2.28 2.82 3.72 0.96 3.54 3.54 3.54 2.82 3.54 57.54</p> <p>O f f i c e</p> <p>4.26 2.16 2.16 0.96 3.54 3.54 20.04</p>	<p>BORDER R=2.25" TH=0.75"</p> <p>Panel Style: guide_con_destination_1-line_2012.ssi M.U.T.C.D.: 2009 Edition</p>
<p>Letter positions are to the lower left corners</p> <p>USE NOTES: 1,3,4,6</p> <ol style="list-style-type: none"> Legend and border shall be direct applied encapsulated lens reflective sheeting. Legend and border shall be direct applied enclosed lens reflective sheeting. Shields shall be encapsulated lens reflective sheeting on 0.8mm aluminum and demountable. Background shall be encapsulated lens reflective sheeting. Background shall be enclosed lens reflective sheeting. Center arrows vertically on sign. 	<p>NORTH CAROLINA D.O.T. SIGN DETAIL</p>

<p>SIGN NUMBER: 304 TYPE: D QUANTITY: 1</p> <p>BACKG COLOR: Green COPY COLOR: White</p> <p>SIGN WIDTH: 5'-6" HEIGHT: 1'-6" TOTAL AREA: 8.25 Sq.Ft.</p> <p>ROUTE MARKERS:</p> <p>BORDER TYPE: FLUSH RECESS: 0" WIDTH: 0.75" RADII: 2.25"</p> <p>ARROW TYPES: 6.0"x9.0"(AR_Type D)</p> <p>NO. Z BARS: LENGTH:</p> <p>MAT: 1.6 mm ALUMINUM</p>	<p>DESIGN BY: ABC PROJECT ID: I-5716</p> <p>CHECKED BY: JTG DIV: 12</p> <p>STD #: STD DATE: Apr 10, 2026</p>
<p>LETTER POSITIONS</p> <p>D o w n t o w n</p> <p>4.08 3.66 6.78 3.54 2.4 3.66 6.78 3.54 38.82</p>	<p>BORDER R=2.25" TH=0.75"</p> <p>Panel Style: guide_con_destination_1-line_2012.ssi M.U.T.C.D.: 2009 Edition</p>
<p>Letter positions are to the lower left corners</p> <p>USE NOTES: 1,3,4,6</p> <ol style="list-style-type: none"> Legend and border shall be direct applied encapsulated lens reflective sheeting. Legend and border shall be direct applied enclosed lens reflective sheeting. Shields shall be encapsulated lens reflective sheeting on 0.8mm aluminum and demountable. Background shall be encapsulated lens reflective sheeting. Background shall be enclosed lens reflective sheeting. Center arrows vertically on sign. 	<p>NORTH CAROLINA D.O.T. SIGN DETAIL</p>

4/14/2026 X:\Raleigh\114-568 - NCDOT - I-5716 1-40 Lenoir-Rhyne Interchange\05-CAD\I-5716\Signing and Delimitation\05-CAD\I-5716-SD-Series.dgn