

10'-30'/SP SKIP LINE

15' 15' 80' REFER TO SPACING CHART FOR SPACING REDUCTIONS 10' WHITE SKIP

3'-9'/SP MINI-SKIP LINE

24' MARKER CENTERED BETWEEN MINI-SKIP LINES

LEGEND

CRYSTAL/RED PAVEMENT MARKER

YELLOW/YELLOW PAVEMENT MARKER

DIRECTION OF TRAFFIC FLOW

GORE LINES

20' MARKERS OFFSET 2" FROM GORE LINES

YELLOW CENTER LINES

80' 80' 15' 15' 15' 15' REFER TO SPACING CHART FOR SPACING REDUCTIONS

CENTER LINES FOR -
TWO-LANE, TWO-WAY ROADWAYS
UNDIVIDED ROADWAYS
TWO-WAY LEFT TURN LANES

MARKERS CENTERED BETWEEN DOUBLE CENTER LINES

DETAIL OF PAVEMENT MARKER PLACEMENT

RAISED REFLECTIVE PAVEMENT MARKERS

6" MARKERS CENTERED BETWEEN DOUBLE CENTER LINES MARKERS CENTERED BETWEEN SKIP LINES

STATE OF NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.

ROADWAY DETAIL DRAWING FOR
RAISED PAVEMENT MARKERS
INSTALLATION SPACING

SHEET 2 OF 3
1250D01

CONTRACTS STANDARDS
AND DEVELOPMENT UNIT
Office 919-707-8950 FAX 919-250-4119

SEE TITLE BLOCK

ORIGINAL BY: M.V. SPRINGER DATE: 2-15-24
MODIFIED BY: DATE:
CHECKED BY: DATE:
FILE SPEC.: