
Docusign Envelope ID: CAF5B4CB-9967-81FC-836A-0ADB0024037B

PROJECT REFERENCE NO.	SHEET NO.
U-3422B	PMP-1B


CONTINUOUS LINES

EDGE LINE



YELLOW OR WHITE

LANE LINE




WHITE

CENTER LINE




YELLOW

GORE LINE



WHITE

DIAGONAL LINE




YELLOW OR WHITE

CROSSWALK LINE




WHITE

RxR LINE



WHITE


STOP OR TRANSVERSE BAR



WHITE

10′-30′/SP SKIP LINE


UNLESS OTHERWISED SHOWN, USE 10′-30′/SP SKIPS FOR SKIP LANE LINES AND SKIP CENTER LINES.



YELLOW OR WHITE

2′-6′/SP MINI-SKIP LINE


UNLESS OTHERWISED SHOWN, USE 2′-6′/SP MINI-SKIPS FOR LANE LINE EXTENSIONS THROUGH INTERSECTIONS, EDGE LINE EXTENSIONS THROUGH INTERSECTIONS AND BICYCLE LANE EXTENSIONS.



YELLOW OR WHITE

3′-3′/SP MINI-SKIP LINE


UNLESS OTHERWISED SHOWN, USE 3′-3′/SP MINI-SKIPS FOR THE WHITE EDGE LINE ENTENSIONS AT ROUNDABOUTS.



WHITE

3′-9′/SP MINI-SKIP LINE

UNLESS OTHERWISED SHOWN, USE 3′-9′/SP MINI-SKIPS FOR MINI-SKIP LANE LINES, LINE EXTENSIONS THROUGH TAPERS, AND MINI-SKIPS USED FOR BICYCLE LANE LINES.



WHITE

GENERAL NOTES:

1- USE 6″ LANE, EDGE, AND CENTER LINES ON ALL FULL CONTROL OF ACCESS FACILITIES AND OTHER ROUTES AS DIRECTED BY THE ENGINEER.

2- LANE LINES INDICATED AS "WIDE" ON THE ROADWAY STANDARD DRAWINGS SHALL BE AT LEAST TWICE THE WIDTH OF THE NORMAL LINE.

3- GORE LINES SHALL BE TWICE THE WIDTH OF THE NORMAL LINE.

STATE OF
NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.

ROADWAY DETAIL DRAWING FOR

PAVEMENT MARKINGS

LINE TYPES AND OFFSETS

SHEET 1 OF 2

1205D01

NORTH CAROLINA PROFESSIONAL SEAL 042546 ENGINEER MATTHEW V. SPRINGER

11/3/2026

CONTRACTS STANDARDS AND DEVELOPMENT UNIT
Office 919-707-8950 FAX 919-250-4119

SEE TITLE BLOCK

ORIGINAL BY: M.V. SPRINGER DATE: 2-15-24
MODIFIED BY: _____ DATE: _____
CHECKED BY: _____ DATE: _____
FILE SPEC.: _____