

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	42608.1JA12 (M-0423)	1	10

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT

STRUCTURE
SUBSURFACE INVESTIGATION

PROJ. REFERENCE NO. 42608.1JA12 (M-0423) F.A. PROJ. _____

COUNTY ALEXANDER

PROJECT DESCRIPTION ARRA BRIDGES - DIVISION 12

SITE DESCRIPTION BRIDGE NO. 87 ON SR 1337 (SILAS DEAL RD.)
OVER KIRBY CREEK

CONTENTS

<u>SHEET</u>	<u>DESCRIPTION</u>
1	TITLE SHEET
2, 2A	LEGEND
3	BORING LOCATION MAP
4-9	BORE LOG & CORE REPORTS WITH CORE PHOTOGRAPHS

PERSONNEL

M. GRAGG

J. CONCI

B. SMITH

F. WOODARD

INVESTIGATED BY F&H

CHECKED BY S. PROVANCE

SUBMITTED BY F&H

DATE 4/5/2010

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF PREPARING THE SCOPE OF WORK TO BE INCLUDED IN THE REQUEST FOR PROPOSAL. THE VARIOUS FIELD BORING LOGS, ROCK CORES, AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N.C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT (919) 250-4088. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES, AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.


SOIL AND ROCK BOUNDARIES WITHIN A BOREHOLE ARE BASED ON GEOTECHNICAL INTERPRETATION UNLESS ENCOUNTERED IN A SAMPLE. INTERPRETED BOUNDARIES MAY NOT NECESSARILY REFLECT ACTUAL SUBSURFACE CONDITIONS BETWEEN SAMPLED STRATA, AND BOREHOLE INFORMATION MAY NOT NECESSARILY REFLECT ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION, AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

NOTE - THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N.C. DEPARTMENT OF TRANSPORTATION AS BEING ACCURATE NOR IT IS CONSIDERED TO BE PART OF THE PLANS, SPECIFICATIONS, OR CONTRACT FOR THE PROJECT.

NOTE - BY HAVING REQUESTED THIS INFORMATION THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

DRAWN BY: T. RIDEOUT



NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT
SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS

SOIL DESCRIPTION										GRADATION																																																																																																									
SOIL IS CONSIDERED TO BE THE UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER, AND YIELD LESS THAN 100 BLOWS PER FOOT ACCORDING TO STANDARD PENETRATION TEST (AASHTO T206, ASTM D-1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY SHALL INCLUDE: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. EXAMPLE: <i>VERY STIFF, GRAY, SILTY CLAY, MOST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC, A-7-6</i>										WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. UNIFORM - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. (ALSO POORLY GRADED) GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLES OF TWO OR MORE SIZES.																																																																																																									
										ANGULARITY OF GRAINS																																																																																																									
THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS IS DESIGNATED BY THE TERMS <u>ANGULAR</u>, <u>SUBANGULAR</u>, <u>SUBROUNDED</u>, OR <u>ROUNDED</u>.										MINERALOGICAL COMPOSITION																																																																																																									
										MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHENEVER THEY ARE CONSIDERED OF SIGNIFICANCE.																																																																																																									
SOIL LEGEND AND AASHTO CLASSIFICATION										COMPRESSION																																																																																																									
GENERAL CLASS. <table border="1" style="width: 100%; text-align: center;"><thead><tr><th colspan="4">GRANULAR MATERIALS (≤ 35% PASSING #200)</th><th colspan="4">SILT-CLAY MATERIALS (> 35% PASSING #200)</th><th colspan="4">ORGANIC MATERIALS</th></tr><tr><th>A-1</th><th>A-3</th><th colspan="2">A-2</th><th>A-4</th><th>A-5</th><th>A-6</th><th>A-7</th><th>A-1, A-2</th><th>A-4, A-5</th><th>A-6, A-7</th><th></th></tr><tr><th>GROUP CLASS.</th><th>A-1-a</th><th>A-1-b</th><th>A-2-4</th><th>A-2-5</th><th>A-2-6</th><th>A-2-7</th><th></th><th>A-7-5</th><th>A-7-6</th><th></th><th></th></tr></thead><tbody><tr><td>SYMBOL</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>% PASSING</td><td>50 MX</td><td>38 MX</td><td>50 MX</td><td>51 MN</td><td>35 MX</td><td>35 MX</td><td>35 MX</td><td>35 MX</td><td>36 MN</td><td>36 MN</td><td>36 MN</td></tr><tr><td>• 10</td><td>15 MX</td><td>25 MX</td><td>10 MX</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>• 40</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>• 200</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></tbody></table>										GRANULAR MATERIALS (≤ 35% PASSING #200)				SILT-CLAY MATERIALS (> 35% PASSING #200)				ORGANIC MATERIALS				A-1	A-3	A-2		A-4	A-5	A-6	A-7	A-1, A-2	A-4, A-5	A-6, A-7		GROUP CLASS.	A-1-a	A-1-b	A-2-4	A-2-5	A-2-6	A-2-7		A-7-5	A-7-6			SYMBOL												% PASSING	50 MX	38 MX	50 MX	51 MN	35 MX	35 MX	35 MX	35 MX	36 MN	36 MN	36 MN	• 10	15 MX	25 MX	10 MX									• 40												• 200												SLIGHTLY COMPRESSIBLE MODERATELY COMPRESSIBLE HIGHLY COMPRESSIBLE LIQUID LIMIT LESS THAN 31 LIQUID LIMIT EQUAL TO 31-50 LIQUID LIMIT GREATER THAN 50									
										GRANULAR MATERIALS (≤ 35% PASSING #200)				SILT-CLAY MATERIALS (> 35% PASSING #200)				ORGANIC MATERIALS																																																																																																	
A-1	A-3	A-2		A-4	A-5	A-6	A-7	A-1, A-2	A-4, A-5	A-6, A-7																																																																																																									
GROUP CLASS.	A-1-a	A-1-b	A-2-4	A-2-5	A-2-6	A-2-7		A-7-5	A-7-6																																																																																																										
SYMBOL																																																																																																																			
% PASSING	50 MX	38 MX	50 MX	51 MN	35 MX	35 MX	35 MX	35 MX	36 MN	36 MN	36 MN																																																																																																								
• 10	15 MX	25 MX	10 MX																																																																																																																
• 40																																																																																																																			
• 200																																																																																																																			
LIQUID LIMIT PLASTIC INDEX <table border="1" style="width: 100%; text-align: center;"><thead><tr><th>GROUP INDEX</th><th>0</th><th>0</th><th>0</th><th>4 MX</th><th>8 MX</th><th>12 MX</th><th>16 MX</th><th>No MX</th></tr></thead><tbody><tr><td>USUAL TYPES OF MAJOR MATERIALS</td><td>STONE FRAGS, GRAVEL, AND SAND</td><td>FINE SAND</td><td>SILTY OR CLAYEY GRAVEL AND SAND</td><td>SILTY SOILS</td><td>CLAYEY SOILS</td><td colspan="3">SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER</td><td colspan="3">HIGHLY ORGANIC SOILS</td></tr></tbody></table>										GROUP INDEX	0	0	0	4 MX	8 MX	12 MX	16 MX	No MX	USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS, GRAVEL, AND SAND	FINE SAND	SILTY OR CLAYEY GRAVEL AND SAND	SILTY SOILS	CLAYEY SOILS	SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER			HIGHLY ORGANIC SOILS			PERCENTAGE OF MATERIAL <table border="1" style="width: 100%; text-align: center;"><thead><tr><th>ORGANIC MATERIAL</th><th>GRANULAR SOILS</th><th>SILT - CLAY SOILS</th><th>OTHER MATERIAL</th></tr></thead><tbody><tr><td>TRACE OF ORGANIC MATTER</td><td>2 - 3%</td><td>3 - 5%</td><td>TRACE</td></tr><tr><td>LITTLE ORGANIC MATTER</td><td>3 - 5%</td><td>5 - 12%</td><td>LITTLE</td></tr><tr><td>MODERATELY ORGANIC</td><td>5 - 10%</td><td>12 - 20%</td><td>SOME</td></tr><tr><td>HIGHLY ORGANIC</td><td>>10%</td><td>>20%</td><td>HIGHLY</td></tr></tbody></table>										ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL	TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE	LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE	MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME	HIGHLY ORGANIC	>10%	>20%	HIGHLY																																																							
										GROUP INDEX	0	0	0	4 MX	8 MX	12 MX	16 MX	No MX																																																																																																	
USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS, GRAVEL, AND SAND	FINE SAND	SILTY OR CLAYEY GRAVEL AND SAND	SILTY SOILS	CLAYEY SOILS	SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER			HIGHLY ORGANIC SOILS																																																																																																										
ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL																																																																																																																
TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE																																																																																																																
LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE																																																																																																																
MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME																																																																																																																
HIGHLY ORGANIC	>10%	>20%	HIGHLY																																																																																																																
GEN. RATING AS A SUBGRADE <table border="1" style="width: 100%; text-align: center;"><thead><tr><th>EXCELLENT TO GOOD</th><th>FAIR TO POOR</th><th>FAIR TO POOR</th><th>POOR</th><th>UNSATURABLE</th></tr></thead><tbody><tr><td colspan="5">PI OF A-7-5 SUBGROUP IS ≤ LL - 30 ; PI OF A-7-6 SUBGROUP IS > LL - 30</td></tr></tbody></table>										EXCELLENT TO GOOD	FAIR TO POOR	FAIR TO POOR	POOR	UNSATURABLE	PI OF A-7-5 SUBGROUP IS ≤ LL - 30 ; PI OF A-7-6 SUBGROUP IS > LL - 30					GROUND WATER																																																																																															
										EXCELLENT TO GOOD	FAIR TO POOR	FAIR TO POOR	POOR	UNSATURABLE																																																																																																					
PI OF A-7-5 SUBGROUP IS ≤ LL - 30 ; PI OF A-7-6 SUBGROUP IS > LL - 30																																																																																																																			
PI OF A-7-5 SUBGROUP IS ≤ LL - 30 ; PI OF A-7-6 SUBGROUP IS > LL - 30										WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING STATIC WATER LEVEL AFTER 24 HOURS PERCHED WATER, SATURATED ZONE, OR WATER BEARING STRATA SPRING OR SEEP																																																																																																									
										CONSISTENCY OR DENSENESS										MISCELLANEOUS SYMBOLS																																																																																															
PRIMARY SOIL TYPE <table border="1" style="width: 100%; text-align: center;"><thead><tr><th>COMPACTNESS OR CONSISTENCY</th><th>RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)</th><th>RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT²)</th></tr></thead><tbody><tr><td>VERY LOOSE</td><td><4</td><td><0.25</td></tr><tr><td>LOOSE</td><td>4 TO 10</td><td>0.25 TO 0.50</td></tr><tr><td>MEDIUM DENSE</td><td>10 TO 30</td><td>0.5 TO 1.0</td></tr><tr><td>DENSE</td><td>30 TO 50</td><td>1 TO 2</td></tr><tr><td>VERY DENSE</td><td>>50</td><td>>2</td></tr></tbody></table>										COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT ²)	VERY LOOSE	<4	<0.25	LOOSE	4 TO 10	0.25 TO 0.50	MEDIUM DENSE	10 TO 30	0.5 TO 1.0	DENSE	30 TO 50	1 TO 2	VERY DENSE	>50	>2	ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION SOIL SYMBOL ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT INFERRED SOIL BOUNDARY INFERRED ROCK LINE ALLUVIAL SOIL BOUNDARY DIP & DIP DIRECTION OF ROCK STRUCTURES																																																																																							
										COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT ²)																																																																																																							
VERY LOOSE	<4	<0.25																																																																																																																	
LOOSE	4 TO 10	0.25 TO 0.50																																																																																																																	
MEDIUM DENSE	10 TO 30	0.5 TO 1.0																																																																																																																	
DENSE	30 TO 50	1 TO 2																																																																																																																	
VERY DENSE	>50	>2																																																																																																																	
TEXTURE OR GRAIN SIZE <table border="1" style="width: 100%; text-align: center;"><thead><tr><th>U.S. STD. SIEVE SIZE OPENING (MM)</th><th>4</th><th>10</th><th>40</th><th>60</th><th>200</th><th>270</th></tr></thead><tbody><tr><td></td><td>4.76</td><td>2.00</td><td>0.42</td><td>0.25</td><td>0.075</td><td>0.053</td></tr></tbody></table>										U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270		4.76	2.00	0.42	0.25	0.075	0.053	SPT TEST BORE AUGER BORE CORE BORE MONITORING WELL PIEZOMETER INSTALLATION SLOPE INDICATOR INSTALLATION CONE PENETROMETER TEST SOUNDING ROD																																																																																											
										U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270																																																																																																			
	4.76	2.00	0.42	0.25	0.075	0.053																																																																																																													
BOULDER (BLDR.) COBBLE (COB.) GRAVEL (GR.) COARSE SAND (CSE, SD.) FINE SAND (F SD.) SILT (SL.) CLAY (CL.)										ABBREVIATIONS																																																																																																									
										AR - AUGER REFUSAL BT - BORING TERMINATED CL - CLAY CPT - CONE PENETRATION TEST CSE - COARSE DMT - DILATOMETER TEST DPT - DYNAMIC PENETRATION TEST • - VOID RATIO F - FINE FOSS - FOSSILIFEROUS FRAC - FRACTURED, FRACTURES FRAGS - FRAGMENTS HI - HIGHLY MED. - MEDIUM MICA - MICACEOUS MOD. - MODERATELY NP - NON PLASTIC ORG. - ORGANIC PMT - PRESSUREMETER TEST SAP. - SAPROLITIC SD. - SAND, SANDY SL. - SILT, SILTY SLI. - SLIGHTLY TCR - TRICONE REFUSAL w - MOISTURE CONTENT V - VERY YST - VANE SHEAR TEST WEA. - WEATHERED γ - UNIT WEIGHT γ_d - DRY UNIT WEIGHT																																																																																																									
SOIL MOISTURE - CORRELATION OF TERMS										EQUIPMENT USED ON SUBJECT PROJECT																																																																																																									
SOIL MOISTURE SCALE (ATTERBERG LIMITS) <table border="1" style="width: 100%; text-align: center;"><thead><tr><th>FIELD MOISTURE DESCRIPTION</th><th>GUIDE FOR FIELD MOISTURE DESCRIPTION</th></tr></thead><tbody><tr><td>- SATURATED - (SAT.)</td><td>USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE</td></tr><tr><td>- WET - (W)</td><td>SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td></tr><tr><td>- MOIST - (M)</td><td>SOLID; AT OR NEAR OPTIMUM MOISTURE</td></tr><tr><td>- DRY - (D)</td><td>REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td></tr></tbody></table>										FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE	DRILL UNITS: MOBILE B- _____ BK-51 CME-45C CME-550 PORTABLE HOIST																																																																																															
										FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION																																																																																																								
- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE																																																																																																																		
- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE																																																																																																																		
- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE																																																																																																																		
- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE																																																																																																																		
PLASTICITY <table border="1" style="width: 100%; text-align: center;"><thead><tr><th>PLASTICITY INDEX (PI)</th><th>DRY STRENGTH</th></tr></thead><tbody><tr><td>0-5</td><td>VERY LOW</td></tr><tr><td>6-15</td><td>SLIGHT</td></tr><tr><td>16-25</td><td>MEDIUM</td></tr><tr><td>26 OR MORE</td><td>HIGH</td></tr></tbody></table>										PLASTICITY INDEX (PI)	DRY STRENGTH	0-5	VERY LOW	6-15	SLIGHT	16-25	MEDIUM	26 OR MORE	HIGH	ADVANCING TOOLS: CLAY BITS 6" CONTINUOUS FLIGHT AUGER 8" HOLLOW AUGERS HARD FACED FINGER BITS TUNG.-CARBIDE INSERTS CASING _____ W/ ADVANCER TRICONE _____ STEEL TEETH TRICONE _____ TUNG.-CARB. CORE BIT																																																																																															
										PLASTICITY INDEX (PI)	DRY STRENGTH																																																																																																								
0-5	VERY LOW																																																																																																																		
6-15	SLIGHT																																																																																																																		
16-25	MEDIUM																																																																																																																		
26 OR MORE	HIGH																																																																																																																		
COLOR DESCRIPTORS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-GRAY). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.										HAMMER TYPE: ☒ AUTOMATIC ☐ MANUAL CORE SIZE: -B _____ -N <u>02</u> -H _____ HAND TOOLS: POST HOLE DIGGER HAND AUGER SOUNDING ROD VANE SHEAR TEST																																																																																																									

		PROJECT REFERENCE NO. 42608.1JA12 (M-0423)	SHEET NO. 2A
NORTH CAROLINA DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS GEOTECHNICAL ENGINEERING UNIT SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS			
ROCK DESCRIPTION		TERMS AND DEFINITIONS	
HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT IF TESTED, WOULD YIELD SPT REFUSAL. AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. IN NON-COASTAL PLAIN MATERIAL, THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:		ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER. AQUIFER - A WATER BEARING FORMATION OR STRATA. ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND. ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, AS SHALE, SLATE, ETC. ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE. CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE. COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE. CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK. DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL. DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH. FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE. FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES. FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLODGED FROM PARENT MATERIAL. FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM. FORMATION (FM.) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD. JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED. LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT. LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS. MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS. MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM. RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK. ROCK QUALITY DESIGNATION (RQD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. SAPROLITE (SAP.) - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK. SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS. SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE. STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N OR BPF) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. STRATA CORE RECOVERY (SRC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE. STRATA ROCK QUALITY DESIGNATION (SRQD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.	
	NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT N VALUES > 100 BLOWS PER FOOT IF TESTED.		
	FINE TO COARSE GRAIN IGNEOUS AND METAMORPHIC ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES GRANITE, GNEISS, GABBRO, SCHIST, ETC.		
	FINE TO COARSE GRAIN METAMORPHIC AND NON-COASTAL PLAIN SEDIMENTARY ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES PHYLLITE, SLATE, SANDSTONE, ETC.		
	COASTAL PLAIN SEDIMENTS CEMENTED INTO ROCK, BUT MAY NOT YIELD SPT REFUSAL. ROCK TYPE INCLUDES LIMESTONE, SANDSTONE, CEMENTED SHELL BEDS, ETC.		
WEATHERING			
FRESH	ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING. ROCK RINGS UNDER HAMMER IF CRYSTALLINE.		
VERY SLIGHT (V SLI.)	ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN. CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF OF A CRYSTALLINE NATURE.		
SLIGHT (SLI.)	ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO 1 INCH. OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR CRYSTALS ARE DULL AND DISCOLORED. CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS.		
MODERATE (MOD.)	SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY. ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED WITH FRESH ROCK.		
MODERATELY SEVERE (MOD. SEV.)	ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK. ROCK GIVES "CLUNK" SOUND WHEN STRUCK. <i>IF TESTED, WOULD YIELD SPT REFUSAL</i>		
SEVERE (SEV.)	ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC CLEAR AND EVIDENT BUT REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN. <i>IF TESTED, YIELDS SPT N VALUES > 100 BPF</i>		
VERY SEVERE (V SEV.)	ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC ELEMENTS ARE DISCERNIBLE BUT THE MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK REMAINING. SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE SUCH THAT ONLY MINOR VESTIGES OF THE ORIGINAL ROCK FABRIC REMAIN. <i>IF TESTED, YIELDS SPT N VALUES < 100 BPF</i>		
COMPLETE	ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.		
ROCK HARDNESS			
VERY HARD	CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.		
HARD	CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.		
MODERATELY HARD	CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.		
MEDIUM HARD	CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.		
SOFT	CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.		
VERY SOFT	CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGERNAIL.		
FRACTURE SPACING		BEDDING	
TERM	SPACING	TERM	THICKNESS
VERY WIDE	MORE THAN 10 FEET	VERY THICKLY BEDDED	> 4 FEET
WIDE	3 TO 10 FEET	THICKLY BEDDED	1.5 - 4 FEET
MODERATELY CLOSE	1 TO 3 FEET	THINLY BEDDED	0.16 - 1.5 FEET
CLOSE	0.16 TO 1 FEET	VERY THINLY BEDDED	0.03 - 0.16 FEET
VERY CLOSE	LESS THAN 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET
		THINLY LAMINATED	< 0.008 FEET
INDURATION			
FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF THE MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.			
FRIABLE	RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.		
MODERATELY INDURATED	GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.		
INDURATED	GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.		
EXTREMELY INDURATED	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.		
		BENCH MARK: ORANGE PAINT CIRCLE LABELED G NW CORNER OF BRIDGE DECK (NEAREST EB1-A) ELEVATION: 100 FT.	
		NOTES:	

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	42608.1.JA12 (M-0423)	3	10



BORING LOCATION MAP
BRIDGE NO. 87
ON SR 1337 (SILAS DEAL RD.)
OVER KIRBY CREEK
TIP No. M-0423

DRAWN BY: _____ T. RIDEOUT

ALEXANDER COUNTY, NORTH CAROLINA



NCDOT GEOTECHNICAL ENGINEERING UNIT

BORELOG REPORT

SHEET 4

PROJECT NO. 42608.1.JA12		ID. M-0423		COUNTY Alexander		GEOLOGIST J. Conci	
SITE DESCRIPTION Bridge No. 87 on SR 1337 (Silas Deal Rd.) over Kirby Creek							GROUND WTR (ft)
BORING NO. EB1-A		STATION N/A		OFFSET N/A		ALIGNMENT N/A	
COLLAR ELEV. 100.2 ft		TOTAL DEPTH 13.0 ft		NORTHING 826,427		EASTING 1,352,100	
DRILL MACHINE CME-45C		DRILL METHOD H.S. Augers/SPT/Core					HAMMER TYPE Automatic
DRILLER Contract Driller		START DATE 03/20/10		COMP. DATE 03/20/10		SURFACE WATER DEPTH N/A	

ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	MOI	LOG	SOIL AND ROCK DESCRIPTION		
			0.5ft	0.5ft	0.5ft	0	25	50	75	100				ELEV. (ft)	DEPTH (ft)	
105																
100															100.2	GROUND SURFACE
	98.2	2.0														
	96.2	4.0	2	4	12											
95			3	4	7											
	92.2	8.0														
90			60/0.0												92.2	8.0
85																
80																
75																
70																
65																
60																
55																
50																
45																
40																
35																
30																
25																

ROADWAY EMBANKMENT
 Red, brown, stiff to v. stiff, silty clay (A-6).
 Auger refusal @ 8.0'.

CRYSTALLINE ROCK
 Gneiss

Boring Terminated at Elevation 87.2 ft in Crystalline Rock (Gneiss).
 Core loss interval 11.5'-13.0'



NCDOT GEOTECHNICAL ENGINEERING UNIT CORE BORING REPORT

SHEET 5

PROJECT NO. 42608.1.JA12		ID. M-0423		COUNTY Alexander		GEOLOGIST J. Conci						
SITE DESCRIPTION Bridge No. 87 on SR 1337 (Silas Deal Rd.) over Kirby Creek						GROUND WTR (ft)						
BORING NO. EB1-A		STATION N/A		OFFSET N/A		0 HR. Core						
COLLAR ELEV. 100.2 ft		TOTAL DEPTH 13.0 ft		NORTHING 826,427		24 HR. N.M						
DRILL MACHINE CME-45C		DRILL METHOD H.S. Augers/SPT/Core				HAMMER TYPE Automatic						
DRILLER Contract Driller		START DATE 03/20/10		COMP. DATE 03/20/10		SURFACE WATER DEPTH N/A						
CORE SIZE NQ2		TOTAL RUN 5.0 ft										
ELEV (ft)	RUN ELEV (ft)	DEPTH (ft)	RUN (ft)	DRILL RATE (Min/ft)	RUN REC. (ft) %	RQD (ft) %	SAMP. NO.	STRATA REC. (ft) %	RQD (ft) %	L O G	DESCRIPTION AND REMARKS	DEPTH (ft)
92.2											Begin Coring @ 8.0 ft	
90	92.2	8.0	5.0	1.46 N=60/0.0	(3.5) 70%	(2.4) 48%		(3.5) 70%	(2.4) 48%		92.2 CRYSTALLINE ROCK	8.0
				1.30							Gray, white, black w/brown-orange-red stain, tan, sli. weathered, v. close to close frac. spacing, med. crystalline quartz biotite gneiss w/core loss	
	87.2	13.0		1.00							11.5'-13.0'	
				1.58							3 60° frags. w/iron stain & clay; 11 0°-20° frags. w/clay & iron stain	13.0
85				2.00							Boring Terminated at Elevation 87.2 ft in Crystalline Rock (Gneiss).	
											Core loss interval 11.5'-13.0'	
80												
75												
70												
65												
60												
55												
50												
45												
40												
35												
30												
25												
20												
15												

NCDOT CORE SINGLE 001_GEO_BRDG_0087.GPJ NC_DOT.GDT 4/7/10

CORE PHOTOGRAPHIC RECORD

Bridge Site No. 87 – SR 1337 (Silas Deal Road) Over Kirby Creek



Boring EB1-A – Box 1 of 1



NCDOT GEOTECHNICAL ENGINEERING UNIT BORELOG REPORT

SHEET 7

PROJECT NO. 42608.1.JA12		ID. M-0423		COUNTY Alexander		GEOLOGIST J. Conci						
SITE DESCRIPTION Bridge No. 87 on SR 1337 (Silas Deal Rd.) over Kirby Creek						GROUND WTR (ft)						
BORING NO. EB1-B		STATION N/A		OFFSET N/A		ALIGNMENT N/A						
COLLAR ELEV. 99.4 ft		TOTAL DEPTH 12.4 ft		NORTHING 826,406		EASTING 1,352,114						
DRILL MACHINE CME-45C		DRILL METHOD H.S. Augers/SPT				HAMMER TYPE Automatic						
DRILLER Contract Driller		START DATE 03/20/10		COMP. DATE 03/20/10		SURFACE WATER DEPTH N/A						
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT		SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION		
			0.5ft	0.5ft	0.5ft	0	25	50	75	100	ELEV. (ft)	DEPTH (ft)
100											99.4	0.0
	97.4	2.0	2	3	4						GROUND SURFACE	
95	95.4	4.0	3	3	1						ROADWAY EMBANKMENT Red, brown, soft to med. stiff, silty clay w/rock frags. (A-6).	
											92.1	7.3
90	90.4	9.0	8	8	5						RESIDUAL Red, brown, soft to stiff, sandy clay w/rock frags. (A-6).	
	87.1	12.3	60/0.1								87.1	12.3
85											87.0	12.4
											HARD ROCK Auger refusal @ 12.3' in gray & white rock frags., interpreted as HR. Boring Terminated with Standard Penetration Test Refusal at Elevation 87.0 ft on Hard Rock.	
80												
75												
70												
65												
60												
55												
50												
45												
40												
35												
30												
25												
20												

NCDOT BORE SINGLE 001_GEO_BRDG_0087.GPJ NC_DOT.GDT 4/7/10



NCDOT GEOTECHNICAL ENGINEERING UNIT

BORELOG REPORT

SHEET 8

PROJECT NO. 42608.1.JA12		ID. M-0423		COUNTY Alexander		GEOLOGIST J. Conci	
SITE DESCRIPTION Bridge No. 87 on SR 1337 (Silas Deal Rd.) over Kirby Creek							GROUND WTR (ft)
BORING NO. EB2-A		STATION N/A		OFFSET N/A		ALIGNMENT N/A	
COLLAR ELEV. 100.0 ft		TOTAL DEPTH 17.3 ft		NORTHING 826,472		EASTING 1,352,172	
DRILL MACHINE CME-45C		DRILL METHOD H.S. Augers/SPT					HAMMER TYPE Automatic
DRILLER Contract Driller		START DATE 03/20/10		COMP. DATE 03/20/10		SURFACE WATER DEPTH N/A	

ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	MOI	LOG	SOIL AND ROCK DESCRIPTION		
			0.5ft	0.5ft	0.5ft	0	25	50	75	100				ELEV. (ft)	DEPTH (ft)	
100															100.0	GROUND SURFACE
	98.0	2.0														
	95.9	4.1	3	4	5											
95			2	3	5											
	90.9	9.1	5	5	6											
90																
	85.9	14.1	2	2	2											
85																
	82.8	17.2														
80																
75																
70																
65																
60																
55																
50																
45																
40																
35																
30																
25																
20																

ROADWAY EMBANKMENT
Red, brown, med. stiff to stiff, silty clay w/rock frags. (A-6).

RESIDUAL
Red, brown, tan & white, soft to stiff, sandy clay w/rock frags. (A-6).

HARD ROCK
Auger refusal @ 17.2' in dark gray, white, rock frags., interpreted as HR.
Boring Terminated with Standard Penetration Test Refusal at Elevation 82.7 ft on Hard Rock.

NCDOT BORE SINGLE 001_GEO_BRDG_0087.GPJ NC_DOT.GDT 4/7/10



NCDOT GEOTECHNICAL ENGINEERING UNIT

BORELOG REPORT

SHEET 9

PROJECT NO. 42608.1.JA12		ID. M-0423		COUNTY Alexander		GEOLOGIST J. Conci	
SITE DESCRIPTION Bridge No. 87 on SR 1337 (Silas Deal Rd.) over Kirby Creek							GROUND WTR (ft)
BORING NO. EB2-B		STATION N/A		OFFSET N/A		ALIGNMENT N/A	
COLLAR ELEV. 99.5 ft		TOTAL DEPTH 21.9 ft		NORTHING 826,451		EASTING 1,352,185	
DRILL MACHINE CME-45C		DRILL METHOD H.S. Augers/SPT					HAMMER TYPE Automatic
DRILLER Contract Driller		START DATE 03/20/10		COMP. DATE 03/20/10		SURFACE WATER DEPTH N/A	

ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	MOI	LOG	SOIL AND ROCK DESCRIPTION		
			0.5ft	0.5ft	0.5ft	0	25	50	75	100				ELEV. (ft)	DEPTH (ft)	
100																
	97.5	2.0	3	5	5											GROUND SURFACE
95	95.5	4.0	2	4	6											ROADWAY EMBANKMENT
																Red, stiff, silty clay w/rock frags. (A-6).
90	90.5	9.0	5	7	9											RESIDUAL
																Red, v. stiff, sandy clay w/rock frags. (A-6).
85	85.5	14.0	1	2	3											RESIDUAL
																Red, brown, med. stiff, silty clay (A-6).
80	80.5	19.0	1	3	13											RESIDUAL
																Red, brown, dk. gray & white, v. stiff, sandy clay w/rock frags. (A-6).
	77.6	21.9														Auger refusal @ 21.9'.
75																Boring Terminated with Standard Penetration Test Refusal at Elevation 77.6 ft on Hard Rock.
70																
65																
60																
55																
50																
45																
40																
35																
30																
25																
20																