




PROJECT REFERENCE NO. 1-2102	SHEET NO. 2A
ROADWAY DESIGN ENGINEER	PAVEMENT DESIGN ENGINEER




TYPICAL SECTION 9
RAMP C DETOUR STA 0+00.00 TO 3+40.88




TYPICAL SECTION 13
RAMP C STA 15+66.18 TO STA 16+50.79




TYPICAL SECTION 10
RAMP A STA 0+00.00 TO 3+20.71
(MILL EXISTING RAMP AT PAVEMENT TIE-IN)




TYPICAL SECTION 14
RAMP C STA 0+00.00 TO 7+50.00




TYPICAL SECTION 15
RAMP B STA 0+00.00 TO 3+79.75




TYPICAL SECTION 11
RAMP A STA 3+20.71 TO 4+34.51
* RAMP D STA 2+00.00 TO 2+83.87 (RT) CURB BEGINS
** RAMP D STA 2+83.87 TO STA 3+40.87 (LT) CURB BEGINS



TYPICAL SECTION 16
RAMP C STA 7+50.00 TO 15+66.18
RAMP B STA 3+79.75 TO 12+71.37



TYPICAL SECTION 12
RAMP D STA 0+00.00 TO 2+00.00
(MILL EXISTING RAMP AT PAVEMENT TIE-IN)



TYPICAL SECTION 17
RAMP B STA 12+71.37 TO STA 13+25.32

PAVEMENT SCHEDULE	
B	PROP. APPROX. 5/8" OPEN-GRADED ASPHALT FRICTION COURSE, TYPE FC2-MODIFIED, AT AN AVERAGE RATE OF 70 LBS. PER SQ. YD.
C	PROP. APPROX. 1 1/4" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 140 LBS. PER SQ. YD.
C1	PROP. APPROX. 1 1/2" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 168 LBS. PER SQ. YD.
C2	PROP. APPROX. 2" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 224 LBS. PER SQ. YD.
C3	PROP. APPROX. 2 1/2" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 140 LBS. PER SQ. YD. IN EACH OF TWO LAYERS.
C4	PROP. VAR. DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 112 LBS. PER SQ. YD. PER 1" DEPTH. TO BE PLACED IN LAYERS NOT TO EXCEED 1 1/2" IN DEPTH.
D	PROP. APPROX. 3" ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0B, AT AN AVERAGE RATE OF 342 LBS. PER SQ. YD.
D1	PROP. APPROX. 4 1/2" ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0B, AT AN AVERAGE RATE OF 513 LBS. PER SQ. YD.
D2	PROP. VAR. DEPTH ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0B, AT AN AVERAGE RATE OF 114 LBS. PER SQ. YD. PER 1" DEPTH. TO BE PLACED IN LAYERS NOT LESS THAN 2 1/4" IN DEPTH OR GREATER THAN 4" IN DEPTH.
E	PROP. APPROX. 4" ASPHALT CONCRETE BASE COURSE, TYPE B25.0B, AT AN AVERAGE RATE OF 456 LBS. PER SQ. YD.
E1	PROP. APPROX. 5" ASPHALT CONCRETE BASE COURSE, TYPE B25.0B, AT AN AVERAGE RATE OF 570 LBS. PER SQ. YD.
E2	PROP. APPROX. 8 1/2" ASPHALT CONCRETE BASE COURSE, TYPE B25.0B AT AN AVERAGE RATE OF 485 LBS. PER SQ. YD. IN EACH OF TWO LAYERS.
E3	PROP. APPROX. 6" ASPHALT CONCRETE BASE COURSE, TYPE B25.0B, AT AN AVERAGE RATE OF 342 LBS. PER SQ. YD. IN EACH OF TWO LAYERS.
E4	PROP. VAR. DEPTH ASPHALT CONCRETE BASE COURSE, TYPE B25.0B, AT AN AVERAGE RATE OF 114 LBS. PER SQ. YD. PER 1" DEPTH. TO BE PLACED IN LAYERS NOT LESS THAN 3" IN DEPTH OR GREATER THAN 5 1/2" IN DEPTH.
J	8" ABC STONE
R	2'-6" CONCRETE CURB AND GUTTER.
R1	CONCRETE EXPRESSWAY GUTTER.
R2	5" MONOLITHIC CONCRETE ISLAND (KEYED IN).
U	EXISTING PAVEMENT.
T	EARTH MATERIAL.
W	WEDGING