REVISIONS

PROJECT REFERENCE NO.	SHEET NO.
	22
R /W SHEET NO.	

METRIC 5 0 10

CONST.REV.

R /W REV.

ROADWAY DESIGN ENGINEER — NORTH CAROLINA PROFESSIONAL SEAL 12300 ENGINEER CHARLES LEE FLOWE — 7/16/04

HYDRAULICS ENGINEER — NORTH CAROLINA PROFESSIONAL SEAL 20754 ENGINEER T. STEPHENS, JR. — 7/16/04

TGS ENGINEERS
975 WALNUT STREET, SUITE 141
CARY, NC 27511
PH (919) 319-8850

-Y9-

PIs Sta 15+81.476	PI Sta 17+74.523	PIs Sta 19+66.409
Θs = 0° 44' 10.3"	Δ = 11° 20' 22.7" (RT)	Θs = 0° 44' 10.3"
Ls = 46.000	L = 354.266	Ls = 46.000
LT = 30.667	T = 177.714	LT = 30.667
ST = 15.334	R = 1,790.000	ST = 15.334
	SE = 2%	

-Y9-

PIs Sta 21+41.706	PI Sta 22+13.264	PIs Sta 22+83.863
Θs = 5° 43' 46.5"	Δ = 19° 30' 38.7" (LT)	Θs = 5° 43' 46.5"
Ls = 60.000	L = 102.158	Ls = 60.000
LT = 40.021	T = 51.578	LT = 40.021
ST = 20.019	R = 300.000	ST = 20.019
	SE = 8%	

-Y9- CS 19+51.075

-Y9- ST 19+97.075

-Y9- TS 21+01.685

-Y9- SC 21+61.685

45
BEN E. PITTMAN, JR.
DB 20D PG 108

NAD 83

S 69° 18' 27.3" E

PROP. 5m DR.

EXISTING R/W

R/W MON

300 PVC

375 RCP

450 RCP

375 mm CONC

FES REMOVE FES

2GI

FALSE SUMP SEE DETAIL 1 SHT.2-J

FALSE SUMP SEE DETAIL 2 SHT.2-J

FALSE SUMP SEE DETAIL 3 SHT.2-J

PROP. CABLE GUIDERAIL

+50 BEG. CABLE GUIDERAIL

+65 END CABLE GUIDERAIL

VG-55 -L-311+75.808 0.822 (LT)

VG-56 -L-312+51.324 1.635 (LT)

VG-57 -L-313+28.095 0.450 (LT)

VG-58 -L-314+03.860 1.073 (LT)

VG-59 -L-314+81.649 0.866 (LT)

BY8B-10 -Y8-45+75.603 1.612 (LT)

-L- CS 314+66.745

-Y8- CS 45+40.672

-Y8- SC 46+00.672

US HWY 74 W 7.2 BST

US HWY 74 E 7.2 BST

12 BST

22.8 SOIL

3.5 SOIL

4.5 SOIL

25FD

S

LT

MATCHLINE STA. 22+20.000 TO SHT. NO. 23

MATCHLINE STA. 311+60.000 MATCH TO SHT. NO. 21

MATCHLINE STA. 315+20.000 MATCH TO SHT. NO. 23

-Y8-		
PIs Sta 40+86.528	PI Sta 43+31.133	
Θs = 1° 39' 47.7"	Δ = 14° 11' 50.8" (RT)	
Ls = 98.700	L = 421.247	
LT = 65.803	T = 211.708	
ST = 32.903	R = 1,700.001	
	SE = 2%	

-Y8-		
PIs Sta 45+77.705	PI Sta 46+84.050	PIs Sta 47+83.343
Θs = 6° 44' 26.4"	Δ = 31° 03' 50.8" (RT)	Θs = 5° 43' 46.5"
Ls = 60.000	L = 162.651	Ls = 60.000
R1 = 1700.000	T = 83.378	LT = 40.021
R2 = 300.000	R = 300.000	ST = 20.019
LT = 37.033	SE = 8%	
ST = 23.030		

-L-		
PIs Sta 308+86.745	PI Sta 311+95.668	PIs Sta 315+00.081
Θs = 1° 38' 30.2"	Δ = 17° 56' 58.2" (RT)	Θs = 1° 38' 30.2"
Ls = 100.000	L = 546.670	Ls = 100.000
LT = 66.670	T = 275.593	LT = 66.670
ST = 33.336	R = 1,745.000	ST = 33.336
	SE = 4%	

SEE SHEET NO. 62 FOR -L- RT LN & -L- LT LN GRADES AND PROFILES.
SEE SHEETS NO. 126 AND NO. 127 FOR LINE -Y8- GRADE AND PROFILE.
SEE SHEET NO. 133 AND 134 FOR LINE -Y9- GRADE AND PROFILE.

6/10/2004

\\SYSTEMS\PROJECTS\PROJECTS\DESIGN***************