

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL UNIT

ID	STATE PROJECT NO.	SHEET NO.	TOTAL SHEETS
R-0513BB	6.469002T	2	9

SUBSURFACE INVESTIGATION

SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS

SOIL DESCRIPTION		GRADATION		TERMS AND DEFINITIONS		ABBREVIATIONS																																																																																																																														
<p>SOIL IS CONSIDERED TO BE THE UNCONSOLIDATED, SEMI-CONSOLIDATED OR WEATHERED EARTH MATERIALS WHICH CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER, AND WHICH YIELDS LESS THAN 100 BLOWS ACCORDING TO STANDARD PENETRATION TEST (ASTM D-1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM AND BASIC DESCRIPTIONS GENERALLY SHALL INCLUDE CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION AND OTHER PERTINENT FACTORS, SUCH AS, MINERALOGICAL COMPOSITION, ANGULARITY STRUCTURE, PLASTICITY, ETC. EXAMPLE: VERY STIFF, GRAY SILTY CLAY, MOST WITH INTERBEDDED FINE SAND LAYERS, HIGH PLASTIC, A-7-6.</p>		<p>WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. UNIFORM - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. (ALSO POORLY GRADED) GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLES OF TWO OR MORE SIZES.</p> <p>ANGULARITY OF GRAINS THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS ARE DESIGNATED BY THE TERMS: ANGULAR, SUBANGULAR, SUBROUNDED, OR ROUNDED.</p>		<p>ALLUVIUM (ALLUV.) - SOILS WHICH HAVE BEEN TRANSPORTED BY WATER. APPARENT DIP - THE DIP OF ROCK STRATA NOT PERPENDICULAR TO STRIKE. AQUIFER - A WATER BEARING FORMATION OR STRATA. AUGER REFUSAL (A.R.) - POINT AT WHICH POWER AUGERS WILL NOT PENETRATE. BEDDED - SOIL OR ROCK LYING IN A POSITION ESSENTIALLY PARALLEL. BEDROCK - ROCK OF RELATIVELY GREAT THICKNESS AND EXTENT IN ITS ORIGINAL LOCATION. CALCAREOUS (CALC.) - SOILS WHICH CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE. COHESIVE SOIL - A SOIL THAT WHEN UNCONFINED HAS CONSIDERABLE DRY STRENGTH AND SIGNIFICANT COHESION WHEN SUBMERGED. COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE. CORE RECOVERY (% REC.) - TOTAL LENGTH OF ALL ROCK DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. COQUINA - A ROCK TYPE COMPOSED ESSENTIALLY OF MARINE SHELLS CEMENTED BY CALCIUM CARBONATE. DIKE - IGNEOUS ROCK INTRUSION WHICH IS NARROW COMPARED WITH ITS OTHER DIMENSIONS. DIP - THE ANGLE BETWEEN A BEDDING PLANE, JOINT PLANE OR FAULT PLANE AND THE HORIZONTAL, MEASURED PERPENDICULAR TO THE STRIKE. DUMPS - UNCOVERED DEPOSITS OF WASTE MATERIAL SUCH AS WOOD, MASONRY DEBRIS OR GARBAGE. FAULT - A BREAK IN THE CONTINUITY OF A BODY OF ROCK, ATTENDED BY A MOVEMENT ON EITHER OR BOTH SIDES OF THE BREAK. FINES - PORTIONS OF A SOIL FINER THAN NO. 200 U.S. STANDARD SIEVE. FISSILITY OR FISSILE - A PROPERTY OF SPLITTING EASILY ALONG CLOSELY SPACED PARALLEL PLANES. FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLOGGED FROM PARENT MATERIAL. FLOODPLAIN - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM. FORMATION - A MAPPABLE UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD. FRACTURE - A CRACK LARGE ENOUGH TO BE VISIBLE TO THE UNAIDED EYE. FRIABLE - EASY TO BREAK OR CRUMBLE. GRANULAR MATERIAL - SOIL THAT WHEN UNCONFINED HAS LITTLE OR NO DRY STRENGTH AND HAS LITTLE OR NO COHESION WHEN SUBMERGED. GROUNDWATER (G.W.) - WATER THAT IS FREE TO MOVE THROUGH SOIL MASS UNDER THE INFLUENCE OF GRAVITY. GROUNDWATER LEVEL - LEVEL OF WATER WITH RESPECT TO EXISTING GROUND SURFACE. HARDPAN - A GENERAL TERM USED TO DESCRIBE A HARD CEMENTED SOIL LAYER WHICH DOES NOT SOFTEN WHEN WET. INDURATED - EARTH MATERIAL HARDENED BY HEAT, PRESSURE OR CEMENTATION. INTERBEDDED - ALTERNATING LENSES OR LAYERS OF SOIL AND/OR ROCK MATERIALS. JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED. LAMINATED - VERY THIN ALTERNATING LAYERS LESS THAN 1cm. LAYER - SUBJECT MATERIAL GREATER THAN 1cm IN THICKNESS. LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT. LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS. MARL - A NON-INDURATED, CALCAREOUS DEPOSIT OF CLAYS, SILTS AND SANDS, OFTEN CONTAINING SHELLS. MICACEOUS SOIL (MIC.) - A SOIL OR ROCK TYPE CONTAINING AN APPRECIABLE AMOUNT OF MICA. MUCK (MK.) - A HIGHLY ORGANIC SOIL OF VERY SOFT CONSISTENCY, GENERALLY FOUND ON TIDAL FLATS, LAKE OR STREAM FLOODPLAINS. PEAT (PT) - A FIBROUS MASS OF ORGANIC MATTER IN VARIOUS STAGES OF DECOMPOSITION. PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM. RESIDUAL SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK. ROCK - SEE LEGEND ROCK QUALITY DESIGNATION (R.O.D.) - A MEASURE OF ROCK QUALITY DESCRIBED BY: TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 0.1 METER DIVIDED BY THE TOTAL LENGTH OF CORE RUN EXPRESSED AS A PERCENTAGE. SANITARY LANDFILLS - COMPACTED AND/OR COVERED LAYERS OF SOIL AND WASTE PRODUCTS. SAPROLITE (SAP.) - RESIDUAL SOIL WHICH RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK. SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLAIN. SILL - AN IGNEOUS SHEET OF INTRUSIVE ROCK WHOSE THICKNESS IS SLIGHT COMPARED TO ITS LATERAL EXTENT. SOME - PRESENCE OF 5% TO 30% OF SUBJECT MATERIAL. STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N) OF A 63.5 kg HAMMER FALLING 0.76 METERS REQUIRED TO PRODUCE A PENETRATION OF 30 cm INTO SOIL WITH A 5 cm OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION RESISTANCE OF LESS THAN 2.5 cm WITH 50 BLOWS. STRIKE - THE DIRECTION OR BEARING OF A HORIZONTAL LINE IN THE PLANE OF AN INCLINED STRATUM, JOINT, FAULT OR OTHER STRUCTURAL PLANE. SUBGRADE - THE SOIL PREPARED TO SUPPORT A STRUCTURE OR A PAVEMENT SYSTEM. TOPSOIL (T.S.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER. TRACE - PRESENCE OF LESS THAN 5% OF SUBJECT MATERIAL.</p>		<p>BLDR. - BOULDER CL. - CLAY COB. - COBBLE CSE. - COARSE EST. - ESTIMATED F. - FINE FOSS. - FOSSILIFEROUS FRAC. - FRACTURED GR. - GRAVEL LL - LIQUID LIMIT MED. - MEDIUM W - MOISTURE CONTENT MOT. - MOTTLED OM - OPTIMUM MOISTURE ORG. - ORGANIC</p> <p>PL - PLASTIC LIMIT PI - PLASTICITY INDEX n - POROSITY SD. - SAND SAT. - SATURATED SL. - SILT, SILTY SLI. - SLIGHTLY G_s - SPECIFIC GRAVITY qu - UNCONFINED COMPRESSIVE STRENGTH γ - UNIT WEIGHT (WET UNIT WEIGHT) γ_d - DRY UNIT WEIGHT γ_{SAT} - SATURATED UNIT WEIGHT e - VOID RATIO V. - VERY</p>																																																																																																																														
<p>MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHENEVER THEY ARE CONSIDERED OF SIGNIFICANCE.</p>		<p>MINERALOGICAL COMPOSITION</p>		<p>LIQUID LIMIT LESS THAN 30 LIQUID LIMIT 31-50 LIQUID LIMIT GREATER THAN 50</p>		<p>FIELD BORING LOGS ROCK CORES SOIL & ROCK TEST DATA SUBSURFACE REPORT</p>																																																																																																																														
<p>MINERALOGICAL COMPOSITION</p>		<p>COMPRESSIBILITY</p>		<p>ROCK DESCRIPTION</p>		<p>THIS INFORMATION MAY BE VIEWED BY APPOINTMENT BY CONTACTING THE N.C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL UNIT @ (919) 250-4088, NEITHER THE SUBSURFACE PLANS AND REPORTS, NOR THE FIELD BORING LOGS, ROCK CORES, OR SOIL TEST DATA IS PART OF THE CONTRACT.</p>																																																																																																																														
<p>SOIL LEGEND AND AASHTO CLASSIFICATION</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>GENERAL CLASS.</th> <th colspan="4">GRANULAR MATERIALS (≤ 35% PASSING #200)</th> <th colspan="4">SILT-CLAY MATERIALS (> 35% PASSING #200)</th> <th colspan="4">ORGANIC MATERIALS</th> </tr> <tr> <td>GROUP CLASS.</td> <td>A-1</td><td>A-3</td><td>A-2</td><td>A-4</td> <td>A-5</td><td>A-6</td><td>A-7</td> <td>A-1, A-2</td><td>A-3</td><td>A-4, A-5</td><td>A-6, A-7</td> <td></td><td></td><td></td><td></td> </tr> <tr> <td>SYMBOL</td> <td></td><td></td><td></td><td></td> <td></td><td></td><td></td> <td></td><td></td><td></td><td></td> <td></td><td></td><td></td><td></td> </tr> <tr> <td>% PASSING</td> <td>50 MX</td><td>30 MX</td><td>10 MX</td><td>5 MX</td> <td>5 MX</td><td>5 MX</td><td>5 MX</td> <td>5 MX</td><td>5 MX</td><td>5 MX</td><td>5 MX</td> <td></td><td></td><td></td><td></td> </tr> <tr> <td>LIQUID LIMIT PLASTIC INDEX</td> <td>6 MX</td><td>N.P.</td><td>40 MX</td><td>40 MX</td> <td>40 MX</td><td>40 MX</td><td>40 MX</td> <td>40 MX</td><td>40 MX</td><td>40 MX</td><td>40 MX</td> <td></td><td></td><td></td><td></td> </tr> <tr> <td>GROUP INDEX</td> <td>0</td><td>0</td><td>0</td><td>4 MX</td> <td>8 MX</td><td>12 MX</td><td>16 MX</td> <td>20 MX</td><td>20 MX</td><td>20 MX</td><td>20 MX</td> <td></td><td></td><td></td><td></td> </tr> <tr> <td>USUAL TYPES OF MAJOR MATERIALS</td> <td>STONE FRAGS GRAVEL AND SAND</td><td>FINE SAND</td><td>SILTY OR CLAYEY GRAVEL AND SAND</td><td>SILTY SOILS</td> <td>CLAYEY SOILS</td><td></td><td></td> <td>SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER</td><td></td><td></td><td></td> <td></td><td></td><td></td><td></td> </tr> <tr> <td>GEN. RATING AS A SUBGRADE</td> <td colspan="4">EXCELLENT TO GOOD</td><td colspan="4">FAIR TO POOR</td><td>FAIR TO POOR</td><td>POOR</td><td>UNSATISFACTORY</td><td></td><td></td><td></td><td></td> </tr> </table>		GENERAL CLASS.	GRANULAR MATERIALS (≤ 35% PASSING #200)				SILT-CLAY MATERIALS (> 35% PASSING #200)				ORGANIC MATERIALS				GROUP CLASS.	A-1	A-3	A-2	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7					SYMBOL																% PASSING	50 MX	30 MX	10 MX	5 MX	5 MX	5 MX	5 MX	5 MX	5 MX	5 MX	5 MX					LIQUID LIMIT PLASTIC INDEX	6 MX	N.P.	40 MX	40 MX	40 MX	40 MX	40 MX	40 MX	40 MX	40 MX	40 MX					GROUP INDEX	0	0	0	4 MX	8 MX	12 MX	16 MX	20 MX	20 MX	20 MX	20 MX					USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS GRAVEL AND SAND	FINE SAND	SILTY OR CLAYEY GRAVEL AND SAND	SILTY SOILS	CLAYEY SOILS			SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER								GEN. RATING AS A SUBGRADE	EXCELLENT TO GOOD				FAIR TO POOR				FAIR TO POOR	POOR	UNSATISFACTORY					<p>COMPRESSIBILITY</p>		<p>ROCK DESCRIPTION</p>		<p>GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.</p>	
GENERAL CLASS.	GRANULAR MATERIALS (≤ 35% PASSING #200)				SILT-CLAY MATERIALS (> 35% PASSING #200)				ORGANIC MATERIALS																																																																																																																											
GROUP CLASS.	A-1	A-3	A-2	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7																																																																																																																									
SYMBOL																																																																																																																																				
% PASSING	50 MX	30 MX	10 MX	5 MX	5 MX	5 MX	5 MX	5 MX	5 MX	5 MX	5 MX																																																																																																																									
LIQUID LIMIT PLASTIC INDEX	6 MX	N.P.	40 MX	40 MX	40 MX	40 MX	40 MX	40 MX	40 MX	40 MX	40 MX																																																																																																																									
GROUP INDEX	0	0	0	4 MX	8 MX	12 MX	16 MX	20 MX	20 MX	20 MX	20 MX																																																																																																																									
USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS GRAVEL AND SAND	FINE SAND	SILTY OR CLAYEY GRAVEL AND SAND	SILTY SOILS	CLAYEY SOILS			SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER																																																																																																																												
GEN. RATING AS A SUBGRADE	EXCELLENT TO GOOD				FAIR TO POOR				FAIR TO POOR	POOR	UNSATISFACTORY																																																																																																																									
<p>CONSISTENCY OR DENSENESS</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>PRIMARY SOIL TYPE</th> <th>COMPACTNESS OR CONSISTENCY</th> <th>RANGE OF STANDARD PENETRATION RESISTANCE (BLOWS)</th> <th>RANGE OF UNCONFINED COMPRESSIVE STRENGTH (kN/m²)</th> </tr> <tr> <td>GENERALLY GRANULAR MATERIAL</td> <td>VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE</td> <td><4 4 TO 10 10 TO 30 30 TO 50 >50</td> <td>N/A</td> </tr> <tr> <td>GENERALLY SILT-CLAY MATERIAL</td> <td>VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD</td> <td><2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 >30</td> <td><25 25 TO 50 50 TO 100 100 TO 200 200 TO 400 >400</td> </tr> </table>		PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (BLOWS)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (kN/m ²)	GENERALLY GRANULAR MATERIAL	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	<4 4 TO 10 10 TO 30 30 TO 50 >50	N/A	GENERALLY SILT-CLAY MATERIAL	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	<2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 >30	<25 25 TO 50 50 TO 100 100 TO 200 200 TO 400 >400	<p>GROUND WATER</p> <p>WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING. STATIC WATER LEVEL AFTER 24 HOURS. PERCHED WATER, SATURATED ZONE OR WATER BEARING STRATA SPRING OR SEEPAGE</p>		<p>ADDITIONAL INFORMATION MAY BE AVAILABLE, INCLUDING, BUT NOT LIMITED TO THE FOLLOWING:</p>																																																																																																																				
PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (BLOWS)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (kN/m ²)																																																																																																																																	
GENERALLY GRANULAR MATERIAL	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	<4 4 TO 10 10 TO 30 30 TO 50 >50	N/A																																																																																																																																	
GENERALLY SILT-CLAY MATERIAL	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	<2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 >30	<25 25 TO 50 50 TO 100 100 TO 200 200 TO 400 >400																																																																																																																																	
<p>TEXTURE OR GRAIN SIZE</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>U.S. STD. SIEVE SIZE OPENING (MM)</th> <th>4</th><th>10</th><th>40</th><th>60</th><th>200</th><th>270</th> </tr> <tr> <td></td> <td>4.76</td><td>2.0</td><td>0.42</td><td>0.25</td><td>0.075</td><td>0.053</td> </tr> </table>		U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270		4.76	2.0	0.42	0.25	0.075	0.053	<p>MISCELLANEOUS SYMBOLS AND ABBREVIATIONS</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td></td> <td>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</td> <td></td> <td>SPT TEST BORING</td> <td></td> <td>SAMPLE DESIGNATIONS</td> </tr> <tr> <td></td> <td>SOIL SYMBOL</td> <td></td> <td>AUGER BORING</td> <td></td> <td>S- BULK SAMPLE</td> </tr> <tr> <td></td> <td>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</td> <td></td> <td>CORE BORING</td> <td></td> <td>SS- SPLIT SPOON SAMPLE</td> </tr> <tr> <td></td> <td>INFERRED SOIL BOUNDARIES</td> <td></td> <td>MONITORING WELL</td> <td></td> <td>ST- SHELBY TUBE SAMPLE</td> </tr> <tr> <td></td> <td>ALLUVIAL/RESIDUAL BOUNDARIES</td> <td></td> <td>PIEZOMETER INSTALLATION</td> <td></td> <td>RS- ROCK SAMPLE</td> </tr> <tr> <td></td> <td>DIP DIRECTION AND DIP OF STRUCTURES</td> <td></td> <td>SLOPE INDICATOR INSTALLATION</td> <td></td> <td>● - SOUNDING ROD</td> </tr> <tr> <td></td> <td>APPARENT DIP (NORMAL TO)</td> <td></td> <td></td> <td></td> <td>○ - SPT N-COUNT</td> </tr> </table>			ROADWAY EMBANKMENT WITH SOIL DESCRIPTION		SPT TEST BORING		SAMPLE DESIGNATIONS		SOIL SYMBOL		AUGER BORING		S- BULK SAMPLE		ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS		CORE BORING		SS- SPLIT SPOON SAMPLE		INFERRED SOIL BOUNDARIES		MONITORING WELL		ST- SHELBY TUBE SAMPLE		ALLUVIAL/RESIDUAL BOUNDARIES		PIEZOMETER INSTALLATION		RS- ROCK SAMPLE		DIP DIRECTION AND DIP OF STRUCTURES		SLOPE INDICATOR INSTALLATION		● - SOUNDING ROD		APPARENT DIP (NORMAL TO)				○ - SPT N-COUNT	<p>GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.</p>																																																																								
U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270																																																																																																																														
	4.76	2.0	0.42	0.25	0.075	0.053																																																																																																																														
	ROADWAY EMBANKMENT WITH SOIL DESCRIPTION		SPT TEST BORING		SAMPLE DESIGNATIONS																																																																																																																															
	SOIL SYMBOL		AUGER BORING		S- BULK SAMPLE																																																																																																																															
	ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS		CORE BORING		SS- SPLIT SPOON SAMPLE																																																																																																																															
	INFERRED SOIL BOUNDARIES		MONITORING WELL		ST- SHELBY TUBE SAMPLE																																																																																																																															
	ALLUVIAL/RESIDUAL BOUNDARIES		PIEZOMETER INSTALLATION		RS- ROCK SAMPLE																																																																																																																															
	DIP DIRECTION AND DIP OF STRUCTURES		SLOPE INDICATOR INSTALLATION		● - SOUNDING ROD																																																																																																																															
	APPARENT DIP (NORMAL TO)				○ - SPT N-COUNT																																																																																																																															
<p>SOIL MOISTURE - CORRELATION OF TERMS</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>SOIL MOISTURE SCALE (ATTERBERG LIMITS)</th> <th>FIELD MOISTURE DESCRIPTION</th> <th>GUIDE FOR FIELD MOISTURE DESCRIPTION</th> </tr> <tr> <td>LL - LIQUID LIMIT</td> <td>- SATURATED - (SAT.)</td> <td>USUALLY LIQUID; VERY WET. USUALLY FROM BELOW THE GROUND WATER TABLE</td> </tr> <tr> <td>PL - PLASTIC LIMIT</td> <td>- WET - (W)</td> <td>SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td>OM - OPTIMUM MOISTURE</td> <td>- MOIST - (M)</td> <td>SOLID; AT OR NEAR OPTIMUM MOISTURE</td> </tr> <tr> <td>SL - SHRINKAGE LIMIT</td> <td>- DRY - (D)</td> <td>REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td> </tr> </table>		SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION	LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET. USUALLY FROM BELOW THE GROUND WATER TABLE	PL - PLASTIC LIMIT	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE	OM - OPTIMUM MOISTURE	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE	SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE	<p>EQUIPMENT USED ON SUBJECT PROJECT</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>DRILL UNITS:</td> <td>AUGER TOOLS:</td> <td>HAMMER TYPE:</td> </tr> <tr> <td><input type="checkbox"/> MOBILE B</td> <td><input type="checkbox"/> 6" (152mm) CONTINUOUS FLIGHT</td> <td><input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL</td> </tr> <tr> <td><input type="checkbox"/> BK-51</td> <td><input type="checkbox"/> 8" (203mm) HOLLOW AUGERS</td> <td>CORE BORING TOOLS:</td> </tr> <tr> <td><input type="checkbox"/> CME-45</td> <td><input type="checkbox"/> HARD FACED FINGER BITS</td> <td><input type="checkbox"/> -AX <input type="checkbox"/> -BX <input type="checkbox"/> -NX</td> </tr> <tr> <td><input checked="" type="checkbox"/> CME-550</td> <td><input type="checkbox"/> TUNG. - CARBIDE INSERTS</td> <td>HAND TOOLS:</td> </tr> <tr> <td><input type="checkbox"/> PORTABLE HOIST</td> <td><input type="checkbox"/> CLAY BITS</td> <td><input type="checkbox"/> POST HOLE DIGGER</td> </tr> <tr> <td><input type="checkbox"/> OTHER _____</td> <td>OTHER: DRAG BIT, AW RODS</td> <td><input type="checkbox"/> HAND AUGER</td> </tr> <tr> <td><input type="checkbox"/> OTHER _____</td> <td></td> <td><input type="checkbox"/> SOUNDING ROD</td> </tr> <tr> <td></td> <td></td> <td><input type="checkbox"/> VANE SHEAR TEST</td> </tr> </table>		DRILL UNITS:	AUGER TOOLS:	HAMMER TYPE:	<input type="checkbox"/> MOBILE B	<input type="checkbox"/> 6" (152mm) CONTINUOUS FLIGHT	<input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL	<input type="checkbox"/> BK-51	<input type="checkbox"/> 8" (203mm) HOLLOW AUGERS	CORE BORING TOOLS:	<input type="checkbox"/> CME-45	<input type="checkbox"/> HARD FACED FINGER BITS	<input type="checkbox"/> -AX <input type="checkbox"/> -BX <input type="checkbox"/> -NX	<input checked="" type="checkbox"/> CME-550	<input type="checkbox"/> TUNG. - CARBIDE INSERTS	HAND TOOLS:	<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> CLAY BITS	<input type="checkbox"/> POST HOLE DIGGER	<input type="checkbox"/> OTHER _____	OTHER: DRAG BIT, AW RODS	<input type="checkbox"/> HAND AUGER	<input type="checkbox"/> OTHER _____		<input type="checkbox"/> SOUNDING ROD			<input type="checkbox"/> VANE SHEAR TEST	<p>GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.</p>																																																																																						
SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION																																																																																																																																		
LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET. USUALLY FROM BELOW THE GROUND WATER TABLE																																																																																																																																		
PL - PLASTIC LIMIT	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE																																																																																																																																		
OM - OPTIMUM MOISTURE	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE																																																																																																																																		
SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE																																																																																																																																		
DRILL UNITS:	AUGER TOOLS:	HAMMER TYPE:																																																																																																																																		
<input type="checkbox"/> MOBILE B	<input type="checkbox"/> 6" (152mm) CONTINUOUS FLIGHT	<input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL																																																																																																																																		
<input type="checkbox"/> BK-51	<input type="checkbox"/> 8" (203mm) HOLLOW AUGERS	CORE BORING TOOLS:																																																																																																																																		
<input type="checkbox"/> CME-45	<input type="checkbox"/> HARD FACED FINGER BITS	<input type="checkbox"/> -AX <input type="checkbox"/> -BX <input type="checkbox"/> -NX																																																																																																																																		
<input checked="" type="checkbox"/> CME-550	<input type="checkbox"/> TUNG. - CARBIDE INSERTS	HAND TOOLS:																																																																																																																																		
<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> CLAY BITS	<input type="checkbox"/> POST HOLE DIGGER																																																																																																																																		
<input type="checkbox"/> OTHER _____	OTHER: DRAG BIT, AW RODS	<input type="checkbox"/> HAND AUGER																																																																																																																																		
<input type="checkbox"/> OTHER _____		<input type="checkbox"/> SOUNDING ROD																																																																																																																																		
		<input type="checkbox"/> VANE SHEAR TEST																																																																																																																																		
<p>PLASTICITY</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>NONPLASTIC</th> <th>PLASTICITY INDEX</th> <th>DRY STRENGTH</th> </tr> <tr> <td>LOW PLASTICITY</td> <td>0-5</td> <td>VERY LOW</td> </tr> <tr> <td>MED. PLASTICITY</td> <td>6-15</td> <td>SLIGHT</td> </tr> <tr> <td>HIGH PLASTICITY</td> <td>16-25</td> <td>MEDIUM</td> </tr> <tr> <td></td> <td>26 OR MORE</td> <td>HIGH</td> </tr> </table>		NONPLASTIC	PLASTICITY INDEX	DRY STRENGTH	LOW PLASTICITY	0-5	VERY LOW	MED. PLASTICITY	6-15	SLIGHT	HIGH PLASTICITY	16-25	MEDIUM		26 OR MORE	HIGH	<p>NOTES: BL-98 (POT STA. 216+94.093--BY5- POT STA. 10+22.376 ELEVATION = 45.53 METERS</p>																																																																																																																			
NONPLASTIC	PLASTICITY INDEX	DRY STRENGTH																																																																																																																																		
LOW PLASTICITY	0-5	VERY LOW																																																																																																																																		
MED. PLASTICITY	6-15	SLIGHT																																																																																																																																		
HIGH PLASTICITY	16-25	MEDIUM																																																																																																																																		
	26 OR MORE	HIGH																																																																																																																																		
<p>COLOR</p> <p>DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YEL-BRN, BLUE-GRAY) MODIFIERS SUCH AS LIGHT, DARK, MOTTLED, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.</p>		<p>REVISOR: _____</p> <p>DATE: _____</p> <p>REVISED NOVEMBER 11, 1998</p>																																																																																																																																		